CLAIMS

1. An attachment for a hand held appliance comprising a body having a first wall; a second wall; and a slot formed along at least part of the length of the attachment, wherein the slot is defined on a first side by a surface of the first wall and on a second side by a surface of the second wall wherein the second wall is moveable relative to the first wall..

2. An attachment according to claim 1, wherein the second wall is rotatable with respect to the first wall.

3. An attachment according to claim 1 or claim 2, wherein the second wall extends out from the first wall.

4. An attachment according to any preceding claim, wherein two slots are provided and the second wall separates the two slots.

5. An attachment according to claim 4, wherein the second wall divides the slot into two.

6. An attachment according to any of claims 1 to 5, wherein the slot is formed on one side of the second wall or the other side of the second wall.

7. An attachment according to claim 6, wherein a slot is provided either side of the second wall.

8. An attachment according to any preceding clam, wherein the second wall has a first indexed position defining a first slot position.

9. An attachment according to any preceding claim, wherein the second wall has a second indexed position defining a second slot position.

10. An attachment according to claim 8 or 9, wherein a first or second indexed position is defined by a detent mechanism.

11. An attachment according to claim 10, wherein the detent mechanism includes an actuator biased into a recess.

12. An attachment according to claim 11, wherein the actuator is a ball bearing.

13. An attachment according to claim 10 or claim 11, wherein the actuator is biased by a spring.

14. An attachment according to any preceding claim, wherein an external surface of the attachment includes at least one row of bristles.

15. An attachment according to claim 14, wherein the external surface is an external surface of the first wall.

16. A hand held appliance comprising a handle having a fluid flow path from a fluid inlet to a fluid outlet and a fan unit for drawing fluid into the fluid inlet and an attachment for attaching to the handle, the attachment comprising a body having a first wall; a second wall; and a slot formed along at least part of the length of the attachment, wherein the slot is defined on a first side by a surface of the first wall and on a second side by a surface of the second wall wherein the second wall is moveable relative to the first wall..

17. An appliance according to claim 16, wherein the second wall is rotatable with respect to the first wall.

18. An appliance according to claim 16 or 17, wherein the second wall extends out from the first wall.

19. An appliance according to any of claims 16 to 18, wherein two slots are provided and the second wall separates the two slots.

20. An appliance according to claim 19, wherein the second wall divides the slot into two.

21. An appliance according to any of claims 16 to 19, wherein the slot is formed on one side of the second wall or the other side of the second wall.

22. An appliance according to claim 19, wherein a slot is provided either side of the second wall.

23. An appliance according to any of clam 16 to 22, wherein the second wall has a first indexed position defining a first slot position.

24. An appliance according to any of claims 16 to 23, wherein the second wall has a second indexed position defining a second slot position.

25. An appliance according to claim 23 or 24, wherein an indexed position is defined by a detent mechanism.

26. An appliance according to claim 25, wherein the detent mechanism includes an actuator biased into a recess.

27. An appliance according to claim 26, wherein the actuator is a ball bearing.

28. An appliance t according to claim 25 or claim 26, wherein the actuator is biased by a spring.

29. An appliance according to any of claims 16 to 28, wherein an external surface of the attachment includes at least one row of bristles.

30. An appliance according to claim 29, wherein the external surface is an external surface of the first wall.

31. An appliance according to any of claims 16 to 30, wherein the appliance is a hair care appliance.

32. An appliance according to any of claims 16 to 30, wherein the appliance is a hot styling appliance.

33. An attachment as substantially herein described with reference to the drawings.

CLAIMS

1. An attachment for a hand held appliance comprising a body having:

a first wall, the first wall having a first edge and a second edge;

a second wall, the second wall being moveable relative to the first wall and extending between the first edge and the second edge of the first wall;

a slot formed along at least part of the length of the attachment, wherein a first side of the slot is the first edge of the first wall and a second side of the slot is a surface of the second wall.

2. An attachment according to claim 1, wherein the first wall is generally tubular.

3. An attachment according to claim 1 or claim 2, wherein the surface of the second wall is substantially linear.

4. An attachment according to any preceding claim, wherein the second wall has two further sections which extend away from the first wall and meet, such that the second wall has a generally triangular cross-section.

5. An attachment according to any preceding claim, wherein the second wall is rotatable with respect to the first wall.

6. An attachment according to any preceding claim, wherein two slots are provided and the second wall separates the two slots.

7. An attachment according to claim 1, wherein the second wall divides the slot into two.

8. An attachment according to any of claims 1 to 5, wherein the slot is formed on one side of the second wall or the other side of the second wall.

9. An attachment according to claim 6, wherein a slot is provided either side of the second wall.

10. An attachment according to any of claim 6 to 9, wherein the second wall has a first indexed position defining a first slot position.

11. An attachment according to any of claims 6 to 10, wherein the second wall has a second indexed position defining a second slot position.

12. An attachment according to claim 10 or 11, wherein an indexed position is defined by a detent mechanism.

13. An attachment according to claim 12, wherein the detent mechanism includes an actuator biased into a recess.

14. An attachment according to claim 13, wherein the actuator is a ball bearing.

15. An attachment according to claim 12 or claim 13, wherein the actuator is biased by a spring.

16. An attachment according to any preceding claim, wherein an external surface of the attachment includes at least one row of bristles.

17. An attachment according to claim 16, wherein the external surface is an external surface of the first wall.

18. An attachment according to claim 17, wherein the external surface comprises a first set of bristles comprising at least one row of bristles and a second set of bristles comprising at least one row of bristles.

19. An attachment according to claim 18, wherein the first set of bristles and the second set of bristles are spaced apart on the external surface.

20. An attachment according to claim 19, wherein the external surface is forms at least part of the circumference of a circle and the first set of bristles is radially spaced from the second set of bristles.

21. A hand held appliance comprising a handle having a fluid flow path from a fluid inlet to a fluid outlet and a fan unit for drawing fluid into the fluid inlet and an attachment for attaching to the handle, the attachment comprising a body having:
a first wall, the first wall having a first edge and a second edge
a second wall, the second wall being moveable relative to the first wall; and extending between the first edge and the second edge of the first wall;
a slot formed along at least part of the length of the attachment, wherein a first side of the slot is the first edge of the first wall and a second side of the slot is a surface of the second wall.

22. An appliance according to claim 21, wherein the first wall is generally tubular.

23. An appliance according to claim 21 or claim 22, wherein the surface of the second wall is substantially linear.

24. An appliance according to any of claims 21 to 23, wherein the second wall has two further sections which extend away from the first wall and meet, such that the second wall has a generally triangular cross-section.

25. An appliance according to any of claims 21 to 24, wherein the second wall is rotatable with respect to the first wall.

26. An appliance according to any of claims 21 to 25, wherein two slots are provided and the second wall separates the two slots.

27. An appliance according to claim 26, wherein the second wall divides the slot into two.

28. An appliance according to any of claims 21 to 25, wherein the slot is formed on one side of the second wall or the other side of the second wall.

29. An appliance according to claim 26, wherein a slot is provided either side of the second wall.

30. An appliance according to any of claims 21 to 29, wherein the second wall has a first indexed position defining a first slot position.

31. An appliance according to any of claims 21 to 30, wherein the second wall has a second indexed position defining a second slot position.

32. An appliance according to claim 30 or 31, wherein an indexed position is defined by a detent mechanism.

33. An appliance according to claim 32, wherein the detent mechanism includes an actuator biased into a recess.

34. An appliance according to claim 33, wherein the actuator is a ball bearing.

35. An appliance t according to claim 32 or claim 33, wherein the actuator is biased by a spring.

36. An appliance according to any of claims 21 to 35, wherein an external surface of the attachment includes at least one row of bristles.

37. An appliance according to claim 36, wherein the external surface is an external surface of the first wall.

38. An appliance according to claim 37, wherein the external surface comprises a first set of bristles comprising at least one row of bristles and a second set of bristles comprising at least one row of bristles.

39. An appliance according to claim 38, wherein the first set of bristles and the second set of bristles are spaced apart on the external surface.

40. An appliance according to claim 39, wherein the external surface is forms at least part of the circumference of a circle and the first set of bristles is radially spaced from the second set of bristles.

41. An appliance according to any of claims 21 to 40, wherein the appliance is a hair care appliance.

42. An appliance according to any of claims 21 to 40, wherein the appliance is a hot styling brush.