

"FEED MECHANISM FOR ELONGATE FLEXIBLE ARTICLE"

The present invention relates to a feed mechanism for use in transporting an elongate flexible article such as a slide fastener product from one station to another in an apparatus for manufacturing such products.

- 5 In the manufacture of slide fasteners, a pair of interengaged slide fastener stringers of a continuous length is fed into a finishing station where the individual slide fastener is finished by mounting a slider onto the continuous slide fastener stringers, applying end stops to the same, and severing a slide fastener
- 10 length from the continuous slide fastener stringers. The finished slide fastener product is then fed to a packing station by means of a conveyor. To this end, it has been a common practice to draw the slide fastener product by means of reciprocable grippers out of the finishing station to a predetermined position where
- 15 the product is released from the grippers onto the conveyor. In order to maximize the rate of production, the grippers are returned to the finishing station as soon as the preceding product has been fed and released; that is to say, the grippers start to return with the product incompletely released therefrom.
- 20 Consequently, with the prior art it is difficult to place the products in proper position and posture on the conveyor.

According to a first aspect of the invention there is provided

a feed mechanism for use in transporting an elongate flexible article, comprising:

(a) a pair of parallel grippers for gripping the article on a pair of laterally spaced leading end
5 portions thereof, said grippers being reciprocable between a first position and a second position disposed away from said first position for advancing the article along a longitudinal path;

(b) means operative on said grippers for
10 closing said grippers at said first position and for opening said grippers at said second position;

(c) a removal lever disposed adjacent to said second position and having a first and a second leg, said removal lever being pivotable, in response to the arrival
15 of said grippers at said second position, to cause said first leg to project through a space between said pair of grippers for kicking down the article from said grippers while the latter are opened, said removal lever having a first roller mounted on said second leg;

20 (d) means for supporting said grippers, said supporting means including a first rail extending parallel to said longitudinal path, and a slide slidably mounted on said first rail for movement therealong, said grippers being mounted on said slide;

25 (e) a first cam plate carried by said grippers,

said first cam plate being engageable with said first roller, when said grippers approach said second position, to cause said removal lever to pivot in response to movement of said grippers in the direction of said longitudinal path;

(f) each of said grippers including a pair of coacting upper and lower grip members, such two upper grip members projecting from a common first base fixed to said slide, such two lower grip members being pivotally mounted on said first base; and

(g) said closing and opening means including
(1) an actuator lever carried by said grippers and operatively connected to said lower grip members, said actuator lever being pivotable between a closing position in which said grippers are closed and an opening position in which said grippers are opened, said actuator lever carrying a second and a third roller,

(2) a second cam plate disposed adjacent to said first position and engageable with said second roller, when the grippers are disposed at said first position, to cause said actuator lever to pivot to said closing position, and

(3) a third cam plate disposed adjacent to said second position and engageable with said third roller, in response to the arrival of said grippers at said second position, to cause said actuator lever to pivot to said opening position.

(18)

Conveniently, the feed mechanism comprise means for reciprocably driving said slide along said first rail said driving means including a reciprocably drivable endless belt extending parallel to said first rail, said slide being fixed to said endless belt.

Preferably, the closing and opening means further including a crank connecting said actuator lever to said lower grip members, said crank including a crank disc mounted on a shaft of said actuator lever, and a connecting rod connected at one end to said crank disc at a position eccentric to said shaft and at the other end to said lower grip members.

More preferably, the feed mechanism comprises means for supporting said removal lever, the last-named supporting means including a second rail parallel to said first rail, and a second base mounted on said second rail, said removal lever being pivotally mounted on said second base.

More preferably, the feed mechanism includes an over centre spring acting between said slide and said actuator lever and biasing said actuator lever to remain in said closing and opening positions thereof.

(19)

- 3 -

The invention will be described by way of example
with reference to the accompanying drawings in which
a preferred embodiment of the present invention
is shown by way of illustrative example. In the
5 drawings:-

Fig. 1 is a front elevational view of a feed mechanism
embodying the present invention;

Fig. 2 is an enlarged view showing a portion of
Fig.1, with parts broken away;

10 Fig. 3 is a plan view corresponding to Fig. 2;

Fig. 4 is a cross-sectional view taken along line IV - IV of Fig. 2;

Fig. 5 is a cross-sectional view taken along line V - V of Fig. 4, showing a crank in its position as grippers are closed;

- 5 Fig. 6 is a view similar to Fig. 5, showing the crank in its position as grippers are opened;

Fig. 7 is a fragmentary perspective view showing the grippers in their position as they have gripped leading end portions of a finished slide fastener drawn from a finishing station;

- 10 Figs. 8, 9 and 10 are detail front elevational views showing the manner in which the slide fastener is kicked down from the grippers by means of a removal lever;

Fig. 11 is an enlarged perspective view corresponding to Fig. 9;

- 15 Fig. 12 is a cross-sectional view taken along line XII - XII of Fig. 1, showing the manner in which the successive slide fasteners released from the grippers are transferred onto a conveyor by means of pallets; and

Figs. 13 and 14 are views showing prior problems.

(21)

- 5 -

The invention is particularly useful when embodied in a feed mechanism such as shown in Fig. 1, generally indicated by the numeral 20. The feed mechanism 20 is adapted to feed an elongate flexible article, such as a finished slide fastener (hereinafter called as slide fastener product) 21, from a finishing station 22 to a predetermined position (described below) from where the slide fastener product 21 is conveyed to a packing station (not shown) by means of a conveyor 23. The slide fastener product 21 has a slider 70 (Figs. 7 - 12) threaded onto a pair of slide fastener stringers.

The feed mechanism 20 comprises a pair of horizontally spaced parallel grippers 24, 24 for gripping the slide fastener product 21 on a pair of laterally spaced leading end portions 21a, 21a (Figs. 3 and 7 - 11). The grippers 24, 24 are reciprocable between a first position adjacent to the finishing station 22 and a second position away from the first position, there being means (described below) operative on the grippers 24, 24 for closing the grippers 24, 24 at the first position and for opening the grippers 24, 24 at the second position.

As best shown in Figs. 2 and 3, the grippers 24, 24 are supported by a slide 25 slidably mounted on a first guide rail 26 projecting horizontally from a frame 27. A pair of rolls 25a, 25a is mounted on the bottom of the slide 25 and rolls one on each side of an auxiliary guide rail 26a extending parallel to the first guide rail 26, thus preventing the grippers 24, 24 from being angularly

displaced about the first guide rail 26 during linear movement therealong. Each of the grippers 24, 24 includes a pair of coaxing upper and lower grip members 24a, 24b. The two upper grip members 24a, 24a project from a common first base 28 fixed to the slide 5 25, and the two lower grip members 24b, 24b are pivotally mounted on the first base 28 by means of a pin 28a. The slide 25 is fixed to a reciprocally driven endless belt 29 extending alongside the first guide rail 26. Thus, the grippers 24, 24 are reciprocally movable along the first guide rail 26 for advancing the slide 10 fastener product 21 along a longitudinal path.

The feed mechanism 20 further comprises a removal lever 30 pivotally mounted on a second base 31 adjustably mounted on a second rail 32 extending parallel to the first guide rail 26, the second base 31 and thus the removal lever 30 being disposed adjacent 15 to the second position. The removal lever 30 has a first leg 30a and a second leg 30b. An extension spring 33 is mounted between a free end of the first leg 30a and the second base 31 to normally urge the removal lever 30 to pivot clockwise about a pin 31a; that is, the first leg 30a is normally urged upwardly. 20 Such pivotal movement of the removal lever 30 is restricted by a stop 34 adjustably mounted on the second base 31.

A first cam plate 35 is carried by the first base 28 remotely from the grippers 24, 24 and has a cam surface 35a slanting down to the right (Figs. 1, 2 and 3). When the grippers 24, 24 approach 25 to the second position, a first roll 36 mounted on a free end

52

- 7 -

of the second leg 30b of the removal lever 30 rolls on and along the cam surface 35a, causing the removal lever 30 to pivot counter-clockwise against the bias of the spring 33 until the first leg 30a projects through a space between the pair of grippers 24, 24 to kick down the slide fastener product 21 from the grippers 24, 24 while the latter are opened, as illustrated in Figs. 8 - 11.

The closing and opening of the grippers 24, 24 is controlled as follows. An actuator lever 37 of triangular shape is pivotably mounted on the first base 28 and is operatively connected to the lower grip members 24b, 24b by a crank. The crank includes a double crank disc 38 mounted on a shaft 39 of the actuator lever 37, and a connecting rod 40 connected at one end to the crank disc 38 at a position eccentric to the shaft 39 and at the other end to a sliding bar 41, the shaft 39 being journaled by a pair of bearings 42, 42 each supported by a support block 43. As best shown in Fig. 11, the sliding bar 41 is slidably mounted on a pair of guide pins 44, 44 pivotally connected at one end to the respective lower grip members 24b, 24b. The sliding bar 41 is normally urged to move away from the lower grip members 24b, 24b by means of a pair of compression springs 45, 45. Such movement of the sliding bar 41 along the guide pins 44, 44 is restricted by a pair of nuts 46, 46 each adjustably mounted on the other end of the respective guide pin 44.

As shown in Figs. 4, 5 and 6, the crank disc 38 has a first and

a second flat peripheral portion 38a, 38b selectively engageable with a locking member 47 in response to pivotal movement of the actuator lever 37. The actuator lever 37 is pivotable between a "closing" position in which the grippers 24, 24 are closed and in which the first flat peripheral disc portion 38a is in engagement with the locking member 47 (Fig. 5), and an "opening" position in which the grippers 24, 24 are opened and in which the second flat peripheral disc portion 38b is in engagement with the locking member 47. The first and second flat peripheral disc portions 38a, 38b with the locking member 47 serve not only to restrict the extent to which the actuator lever 37 is angularly moved, but also to hold the grippers 24, 24 in closed position as they trip from the first position to the second position and then in opened position as they come back from the second position to the first position.

The triangular actuator lever 37 has a second roll 48 and a third roll 49 one on each free apex thereof. A second cam plate 50 is slidably mounted on a horizontal guide bar 51 extending as a cantilever from the frame 27 adjacent to the finishing station 22. The second cam plate 50 has a cam surface 50a slanting up to the right (Fig. 1) and is movable between a projected position in which the cam surface 50a is engageable with the second roll 48 when the grippers 24, 24 are disposed at the first position, and a retracted position. The second cam plate 50, normally urged to the retracted position by means of a compression spring 51a, is operably connected to an actuator lever 52 with a bell

crank 53. The actuator lever 52 is upwardly movable, in timed relation with the discharge of a freshly finished slide fastener product 21 from the finishing station 22, to cause the second cam plate 50 to move to the projected position against the bias of the spring 51a. When the second cam plate 50 is moved to the projected position as the grippers 24, 24 are at the first station, the second cam plate 50 pushes the second roll 48 carried by the actuator lever 37, thus causing the actuator lever 37 to pivot from the "opening" position to the "closing" position.

10 A third cam plate 54 is supported by the second base 31 and has a cam surface 54a slanting down to the right (Figs. 1 and 2). When the grippers 24, 24 approach to the second position, the third roll 49 carried by the actuator lever 37 rolls on and along the cam surface 54a, causing the actuator lever 37 to pivot from the "closing" position to the "opening" position.

The extent to which the grippers 24, 24 are reciprocally movable along the first guide rail 26 is restricted by a pair of limit switches 55, 56 supported by the second rail 32 at positions adjacent to the first and second positions, respectively.

20 In order to receive and then transport the released slide fastener product 21 onto the conveyor 23, a pair of first and second trays or pallets 57, 58 is mounted on their respective support rails 59, 60 extending parallel to the first guide rail 26. The slide fastener product 21 having released from the grippers 24, 24

falls on the first pallet 57. The first pallet 57 is then inclined (phantom lines in Fig. 12) to slide the slide fastener product 21 down to the second pallet 58, at which time the second pallet 58 is also inclined (solid lines in Fig. 12). Thence, the slide fastener product 21 is transferred to the conveyor 23 by turning the second pallet 58 over (phantom lines in Fig. 12). Thus the slide fastener product 21 is placed upside down on the conveyor 23. If it is unnecessary to turn the slide fastener product 21 over, the second pallet 58 may be omitted. The conveyor 23 extends perpendicularly to the direction of the longitudinal path.

In operation, a freshly finished slide fastener product 21 is drawn to an unnumbered outlet of the finishing station 22 by means of grippers 61, 61 (Fig. 7) in the finishing station 22. At that time the grippers 24, 24 is disposed at the first position. The actuator lever 52 (Fig. 1) is raised, and the second cam plate 50 is thereby moved forward to push the second roll 48 carried by the actuator lever 37, thus causing the actuator lever 37 to pivot from the "opening" position to the "closing" position as the crank disc 38 is angularly moved from the position of Fig. 6 to the position of Fig. 5. As a result, the grippers 24, 24 are closed to grip the slide fastener product 21 on a pair of spaced leading end portions 21a, 21a, as shown in Fig. 7.

With the actuator lever 37 held in the "closing" position, the

(27)

- 11 -

grippers 24, 24 are then moved downstream along the first guide rail 26 until they reach the second position, bringing the leading end portion 21a of the slide fastener product 21 to that position. As the grippers 24, 24 approach to the second position, the third
5 roll 49 carried by the actuator lever 37 rolls on and along the cam surface 54a of the third cam plate 54, causing the actuator lever 37 to pivot from the "closing" position to the "opening" position; that is, the crank disc 38 is angularly moved from the position of Fig. 5 to the position of Fig. 6. Thus the grippers
10 24, 24 are opened to release the slide fastener product 21. At the same time the first roll 36 carried by the second leg 30b of the removal lever 30 rolls on and along the cam surface 35a of the first cam plate 35, causing the removal lever 30 to pivot so that the first leg 30a projects through a space between
15 the pair of grippers 24, 24 to kick down the slide fastener product 21 from the grippers 24, 24 while the latter are opened, as illustrated in Figs. 9 - 11. The released slide fastener product 21 falls onto the first pallet 57 and is thence transferred to the conveyor 23 via the second pallet 58. The conveyor 23 conveys the slide
20 fastener product 21 to the packing station (not shown).

After the slide fastener product 21 has been completely released exactly at the second position, the grippers 24, 24 are returned to the first position to grip the succeeding slide fastener product 21.

25 With the feed mechanism 20, an elongate flexible article such

as a finished slide fastener 21 drawn from a finishing station can be released exactly at a predetermined position and hence can be placed in proper position and posture on a conveyor that conveys the product to a packing station. Accordingly, streamlining transportation of the successive products from the finishing station to the packing station can be secured. Whereas, with the prior art the grippers start to return with the product incompletely released therefrom (Fig. 13) and, for this reason, it is difficult to place the products in proper position and posture on the conveyor (Fig. 14).

Various modifications may be made within the scope of the present invention.

(29)



- 13 -

CLAIMS:

1. A feed mechanism for use in transporting an elongate flexible article, comprising:

(a) a pair of parallel grippers for gripping the article on a pair of laterally spaced leading end
5 portions thereof, said grippers being reciprocable between a first position and a second position disposed away from said first position for advancing the article along a longitudinal path;

(b) means operative on said grippers for
10 closing said grippers at said first position and for opening said grippers at said second position;

(c) a removal lever disposed adjacent to said second position and having a first and a second leg, said removal lever being pivotable, in response to the arrival
15 of said grippers at said second position, to cause said first leg to project through a space between said pair of grippers for kicking down the article from said grippers while the latter are opened, said removal lever having a first roller mounted on said second leg;

(d) means for supporting said grippers, said
20 supporting means including a first rail extending parallel to said longitudinal path, and a slide slidably mounted on said first rail for movement therealong, said grippers being mounted on said slide;

25 (e) a first cam plate carried by said grippers,



30

- 14 -

said first cam plate being engageable with said first roller, when said grippers approach said second position, to cause said removal lever to pivot in response to movement of said grippers in the direction of said longitudinal path;

(f) each of said grippers including a pair of coacting upper and lower grip members, such two upper grip members projecting from a common first base fixed to said slide, such two lower grip members being pivotally mounted on said first base; and

(g) said closing and opening means including

(1) an actuator lever carried by said grippers and operatively connected to said lower grip members, said actuator lever being pivotable between a closing position in which said grippers are closed and an opening position in which said grippers are opened, said actuator lever carrying a second and a third roller,

(2) a second cam plate disposed adjacent to said first position and engageable with said second roller, when the grippers are disposed at said first position, to cause said actuator lever to pivot to said closing position, and

(3) a third cam plate disposed adjacent to said second position and engageable with said third roller, in response to the arrival of said grippers at said second position, to cause said actuator lever to pivot to said opening position.

(31)



- 15 -

2. A feed mechanism according to claim 1,
comprising means for reciprocally driving said slide along
said first rail said driving means including a
reciprocably drivable endless belt extending parallel to
5 said first rail, said slide being fixed to said endless
belt.

3. A feed mechanism according to claim 1, said
closing and opening means further including a crank
connecting said actuator lever to said lower grip members,
10 said crank including a crank disc mounted on a shaft of
said actuator lever, and a connecting rod connected at one
end to said crank disc at a position eccentric to said
shaft and at the other end to said lower grip members.

4. A feed mechanism according to claim 1,
15 comprising means for supporting said removal lever, the
last-named supporting means including a second rail
parallel to said first rail, and a second base mounted on
said second rail, said removal lever being pivotally
mounted on said second base.

20 5. A feed mechanism according to claim 1, including
an over-center spring acting between said slide and said
actuator lever and biasing said actuator lever to remain in
said closing and opening positions thereof.



32

- 15a -

6. A feed mechanism for use in transporting an elongate flexible article, substantially as hereinbefore described with reference to and as illustrated in the accompanying figures.
