

Description

This invention relates to the handling of a ribbon or tape. More specifically, it relates to the transport of ribbon or tape from the ribbon box to the print point in a typewriter, dot matrix printer, or serial impact printer.

A typewriter as well as other forms of printers typically includes provision for relative motion between the impact means and the print receiving means so that the characters may be printed along a line. Commonly, in older style typewriters, the print receiving medium is moved with respect to the character elements which remain stationary. The paper and platen move with respect to the frame of the machine while the character elements are substantially fixed. In modern typewriters and printers the print elements are typically moved with respect to the platen. Since the mechanical operations are the limiting factor in the speed of such machines, a reduction in the inertia of moving parts allows an increase in speed. Thus, it is desirable to move the print element rather than the platen since the former is generally lighter in weight.

It is also desirable that the printing ribbon which passes between the print receiving means and the character elements be stored in a stationary position with respect to the frame of the machine again allowing a reduction in the inertia of moving parts. This has led to the use of flexible leaders which guide the printing ribbon between a stationary ribbon cartridge and movable print point. In order for these leaders to function properly it is necessary that they bend in one direction only so that the ink side of the ribbon will not contact the leader where the leader forms an enclosed channel. It is also important to reduce frictional load between the ribbon and the leader. Furthermore, the leader must be flexible enough in the vertical direction to allow for movement in that direction when multi-colored ribbons are used. Also, the leader must provide good ribbon tracking. EP-A-23 806 describes a flexible leader which comprises a C-shaped channel. This leader does not protect the ribbon from operator contact.

It is an object of this invention to provide an improved leader of the type which may be used to guide ribbon between the stationary ribbon cartridge and a location movable with respect to the ribbon cartridge.

It is another object of this invention to improve the leader by reducing the frictional load between the ribbon and the leader while maintaining adequate leader flexibility in the vertical direction.

It is a further object of this invention to provide good ribbon tracking.

It is another object of this invention to improve the leader so that the ribbon is protected from operator contact.

It is a still further object of this invention to provide a leader which is easy to install.

Summary of the Invention

The flexible leader for guiding a ribbon in a ribbon supply apparatus is of the type comprising a channel with a continuous side and discontinuous sides, so that bending of the channel occurs in one direction only. It is characterized in that the channel is a U-shaped channel having two vertical sides and a bottom wherein a first one of the side is the continuous side and a second one of the sides and the bottom are the discontinuous sides. The flexible leader comprises a plurality of top latches connecting the two sides of the channel, whereby the flexible leader achieves good ribbon tracing and protects the ribbon from contact with anything other than the leader.

Brief Description of the Drawing

Fig. 1 is an exploded view of the ribbon supply apparatus for a one color ribbon.

Fig. 2 is an exploded view of the ribbon supply apparatus for a multi-color ribbon.

Fig. 3 is a top view of the flexible leader.

Fig. 4 is a sectional view taken along line C—C of Fig. 3.

Fig. 5 is a sectional view taken along line A—A of Fig. 3.

Fig. 6 is a sectional view taken along line B—B of Fig. 3.

Fig. 7 is a sectional view taken along line D—D of Fig. 3.

Fig. 8 is a side view of the flexible leader.

Fig. 9a and 9b are cross-sectional views of the leader with the top latch in open and closed positions, respectively.

Description of the Preferred Embodiments

Referring now to Fig. 1, one embodiment of the ribbon supply apparatus in a printer according to the present invention is shown. Ribbon box 11 holding a supply of ribbon is mounted on the main frame of the printer and remains stationary during operation. Nosepiece 12 is mounted on the movable printhead and positions ribbon 14 between the print element or printhead and the recording medium (not shown). The ribbon path length is maintained constant by a first flexible leader 16 which extends from ribbon box 11 to nosepiece 12 and a second flexible leader 17 which extends from nosepiece 12 to ribbon box 11. The nosepiece ends of the flexible leaders move back and forth with the nosepiece during printing operations. The flexible nature of leaders 16 and 17 permits this.

Referring now to Figs. 5—7, it will be seen that flexible leaders 16 and 17 are of generally U-shaped construction and ribbon 14 rides inside the leaders in the manner indicated. In order to increase the flexibility of flexible leaders 16 and 17, vertical slits 18 are cut through outer wall 19 and bottom wall 21 of the U-shaped channel. Inner wall 20 is continuous. These slits create leader hinge points 22 so that flexible leaders 16 and 17 are discontinuous and comprise a series of short, relatively rigid sections 23.

Referring now to Fig. 3, the insides of one or

both of the vertical walls of the flexible leaders have vertical ridges. Inner wall ridges 24 reduce frictional drag between ribbon 14 and inner wall 20 as the ribbon moves along the center passageway of the flexible leader. Because of the outward flexure of flexible leaders 16 and 17, ribbon 14 will tend to rub against outer wall 19 in the areas opposite leader hinge points 22. Outer wall ridges 26 minimize contact between outer wall 19 and the inked side of the ribbon so that the ink does not tend to rub off on leaders 16 and 17. When multi-colored ribbon 15 is used (as shown in Fig. 2) the ends of flexible leaders 16 and 17 attached to nosepiece 13 must move up and down with nosepiece 13 as it selects the proper color track. Therefore, the ridges are vertical to allow good flexibility in the vertical direction of the leader when it is used with a multi-colored ribbon.

Small top latches 27 are provided on every third segment of flexible leaders 16 and 17. These latches keep the ribbon from coming out of the U-shaped track. This is especially important when a multi-colored ribbon is used which is raised and lowered during printing depending on the color track selected. In addition, they keep the ribbon away from the operator. These latches can be opened and closed. (See Figs. 9A and 9B). Flexible leaders 16 and 17 are single molded pieces of plastic material. Thus, the top latches are an integral part of the molded pieces. The molded material is thinner at latch hinge points 25. This allows upper portion 27a of latch 27 to pivot about latch hinge point 25 between open and closed positions. Foot 30 on upper portion 27a snaps into opening 35 on lower portion 27b of latch 27 to close the latch. Top latch 27 can be opened by applying pressure on lip 44 to flex lower portion 27b of latch 27 away from outer wall 19. This releases foot 30 from opening 35 in lower portion 27b of latch 27.

Flexible leaders 16 and 17 are designed for easy installation. As shown in Figs. 1 and 2, attachment of the flexible leaders to nosepiece 12 (in Fig. 1) or 13 (in Fig. 2) and to ribbon box 11 can be by a variety of means.

In Fig. 1, hollow cylindrical endposts 28 formed at the ends of flexible leaders 16 and 17 are inserted into corresponding cylindrical passageways 31 in nosepiece 12. The combination is then slid down onto vertical mounting posts on the print head carrier (not shown). Attachment to ribbon box 11 can be by means of mounting post 33 on leader 17 which engages apertures 34 and 36 on top 37 and bottom 38 of ribbon box 11, respectively. Alternatively, attachment to ribbon box 11 can be by means of a second hollow cylindrical endpost 39 which fits on mounting post 41 on ribbon box 11.

In Fig. 2, attachment of flexible leaders 16 and 17 to ribbon box 11 is the same as in Fig. 1. However, the attachment of the leaders to nosepiece 13 is different. In this embodiment, flexible leaders 16 and 17 are provided with slotted sleeves 42 which snap onto mounting bars 43 on nosepiece 13.

The entire ribbon supply apparatus is easy and inexpensive to produce. As such it can be used as a throwaway item. The ribbon supply apparatus can be provided with the ribbon already inserted in the flexible leaders. The installation of a new ribbon is then a simple matter of snapping ribbon box 11 onto the printer frame and attaching endposts 28 or slotted sleeves 42 of flexible leaders 16 and 17 to nosepiece 12 or 13. As already explained, the attachment of flexible leaders 16 or 17 to the nosepiece is a simple matter of sliding or snapping corresponding mating parts together. Since the improved design of the flexible leader almost totally encases ribbon 14 or 15, the operator does not come in contact with the ribbon and "clean hands" installation is achieved.

Claims

1. A flexible leader for guiding a ribbon in a ribbon supply apparatus of the type comprising a channel with a continuous side and discontinuous sides, so that bending of the channel occurs in one direction only, and being characterized in that,

said channel is a U-shaped channel (17, 18) having two sides and a bottom wherein a first one of the sides (20) is the continuous side and a second one of the sides (19) and the bottom (21) are the discontinuous sides and in that it comprises a plurality of top latches (27) connecting the two sides of the channel, whereby the flexible leader achieves good ribbon tracing and protects the ribbon from contact with anything other than the leader.

2. A flexible leader according to claim 1 characterized in that it comprises:

a plurality of substantially vertical raised ridges (24) on the inside of at least one of the sides of the channel whereby frictional contact between the ribbon and the leader is reduced without a reduction in the flexibility of the leader.

3. A flexible leader according to claim 1 or 2 to be used in a printing apparatus of the type having a laterally movable print location, a ribbon (14, 15), a ribbon supply means (11, 41), and support means (12, 13) for positioning the ribbon adjacent to the print location, characterized in that it comprises:

attachment means (28, 42; 33, 39) for attaching the flexible leader to the ribbon supply means and the support means.

4. A flexible leader according to claim 3 characterized in that the attachment means (23) for attaching the flexible leader to the support means is a hollow cylindrical endpost which is inserted into a corresponding cylindrical passageway (31) in the support means (12).

5. A flexible leader according to claim 3 characterized in that the attachment means (42) for attaching the flexible leader to the support means is a slotted sleeve (42) which snaps onto a mounting bar (43) on the support means (13).

6. A flexible leader according to claim 3, 4 or 5

both of the vertical walls of the flexible leaders have vertical ridges. Inner wall ridges 24 reduce frictional drag between ribbon 14 and inner wall 20 as the ribbon moves along the center passageway of the flexible leader. Because of the outward flexure of flexible leaders 16 and 17, ribbon 14 will tend to rub against outer wall 19 in the areas opposite leader hinge points 22. Outer wall ridges 26 minimize contact between outer wall 19 and the inked side of the ribbon so that the ink does not tend to rub off on leaders 16 and 17. When multi-colored ribbon 15 is used (as shown in Fig. 2) the ends of flexible leaders 16 and 17 attached to nosepiece 13 must move up and down with nosepiece 13 as it selects the proper color track. Therefore, the ridges are vertical to allow good flexibility in the vertical direction of the leader when it is used with a multi-colored ribbon.

Small top latches 27 are provided on every third segment of flexible leaders 16 and 17. These latches keep the ribbon from coming out of the U-shaped track. This is especially important when a multi-colored ribbon is used which is raised and lowered during printing depending on the color track selected. In addition, they keep the ribbon away from the operator. These latches can be opened and closed. (See Figs. 9A and 9B). Flexible leaders 16 and 17 are single molded pieces of plastic material. Thus, the top latches are an integral part of the molded pieces. The molded material is thinner at latch hinge points 25. This allows upper portion 27a of latch 27 to pivot about latch hinge point 25 between open and closed positions. Foot 30 on upper portion 27a snaps into opening 35 on lower portion 27b of latch 27 to close the latch. Top latch 27 can be opened by applying pressure on lip 44 to flex lower portion 27b of latch 27 away from outer wall 19. This releases foot 30 from opening 35 in lower portion 27b of latch 27.

Flexible leaders 16 and 17 are designed for easy installation. As shown in Figs. 1 and 2, attachment of the flexible leaders to nosepiece 12 (in Fig. 1) or 13 (in Fig. 2) and to ribbon box 11 can be by a variety of means.

In Fig. 1, hollow cylindrical endposts 28 formed at the ends of flexible leaders 16 and 17 are inserted into corresponding cylindrical passageways 31 in nosepiece 12. The combination is then slid down onto vertical mounting posts on the print head carrier (not shown). Attachment to ribbon box 11 can be by means of mounting post 33 on leader 17 which engages apertures 34 and 36 on top 37 and bottom 38 of ribbon box 11, respectively. Alternatively, attachment to ribbon box 11 can be by means of a second hollow cylindrical endpost 39 which fits on mounting post 41 on ribbon box 11.

In Fig. 2, attachment of flexible leaders 16 and 17 to ribbon box 11 is the same as in Fig. 1. However, the attachment of the leaders to nosepiece 13 is different. In this embodiment, flexible leaders 16 and 17 are provided with slotted sleeves 42 which snap onto mounting bars 43 on nosepiece 13.

The entire ribbon supply apparatus is easy and inexpensive to produce. As such it can be used as a throwaway item. The ribbon supply apparatus can be provided with the ribbon already inserted in the flexible leaders. The installation of a new ribbon is then a simple matter of snapping ribbon box 11 onto the printer frame and attaching endposts 28 or slotted sleeves 42 of flexible leaders 16 and 17 to nosepiece 12 or 13. As already explained, the attachment of flexible leaders 16 or 17 to the nosepiece is a simple matter of sliding or snapping corresponding mating parts together. Since the improved design of the flexible leader almost totally encases ribbon 14 or 15, the operator does not come in contact with the ribbon and "clean hands" installation is achieved.

Claims

1. A flexible leader for guiding a ribbon in a ribbon supply apparatus of the type comprising a channel with a continuous side and discontinuous sides, so that bending of the channel occurs in one direction only, and being characterized in that,

said channel is a U-shaped channel (17, 18) having two sides and a bottom wherein a first one of the sides (20) is the continuous side and a second one of the sides (19) and the bottom (21) are the discontinuous sides and in that it comprises a plurality of top latches (27) connecting the two sides of the channel, whereby the flexible leader achieves good ribbon tracing and protects the ribbon from contact with anything other than the leader.

2. A flexible leader according to claim 1 characterized in that it comprises:

a plurality of substantially vertical raised ridges (24) on the inside of at least one of the sides of the channel whereby frictional contact between the ribbon and the leader is reduced without a reduction in the flexibility of the leader.

3. A flexible leader according to claim 1 or 2 to be used in a printing apparatus of the type having a laterally movable print location, a ribbon (14, 15), a ribbon supply means (11, 41), and support means (12, 13) for positioning the ribbon adjacent to the print location, characterized in that it comprises:

attachment means (28, 42; 33, 39) for attaching the flexible leader to the ribbon supply means and the support means.

4. A flexible leader according to claim 3 characterized in that the attachment means (23) for attaching the flexible leader to the support means is a hollow cylindrical endpost which is inserted into a corresponding cylindrical passageway (31) in the support means (12).

5. A flexible leader according to claim 3 characterized in that the attachment means (42) for attaching the flexible leader to the support means is a slotted sleeve (42) which snaps onto a mounting bar (43) on the support means (13).

6. A flexible leader according to claim 3, 4 or 5



characterized in that the attachment means (33) for attaching the flexible leader to the ribbon supply means is a mounting post (33) which engages apertures (34, 36) in the top (37) and bottom (38) of the ribbon supply means (11).

7. A flexible leader according to claim 3, 4 or 5 characterized in that the attachment means for attaching the flexible leader to the ribbon supply means is a hollow cylindrical endpost (39) which fits onto a mounting post (41) on the ribbon supply means.

Patentansprüche

1. Flexible Führung, um ein Band in einer Bandausgabevorrichtung zu lenken, deren Typ eine Führung mit einer Seite ohne Durchbrüche und durchbrochene Seiten aufweist, wodurch ein Biegen der Führung nur in einer Richtung möglich ist, und die weiter durch folgende Merkmale gekennzeichnet ist:

die genannte Führung ist ein U-Profil (17, 18) mit zwei Seiten und einem Boden, bei dem eine erste Seite (20) keine Durchbrüche aufweist während die andere Seite (19) und der Boden (21) durch Unterbrechungen gekennzeichnet sind und die Führung weiter eine Vielzahl von Querriegeln (27) aufweist, die beide Seiten miteinander verbinden und dadurch der flexiblen Führung eine gute Bandlenkung erlauben sowie auch das Band gegen Kontakt mit anderen Elementen mit Ausnahme der Führung selber schützen.

2. Flexible Führung nach Anspruch 1, dadurch gekennzeichnet, daß sie umfasst:

eine Vielzahl von im wesentlichen vertikal angeordneten Stegen (24) auf mindestens einer Innenseite der Führung, wodurch der Reibungskontakt zwischen Band und Führung vermindert wird ohne daß die Flexibilität der letzteren dadurch reduziert wird.

3. Flexible Führung nach Anspruch 1 oder 2, angeordnet auf einem Druckgerät vom Typ mit einer quer verschiebbaren Druckstelle, einem Farbband (14, 15), einem Bandausgabemittel (11, 41) und Haltermitteln (12, 13), um das Farbband neben die Druckstelle zu bringen, dadurch gekennzeichnet, daß sie weiter aufweist:

Befestigungsmittel (28, 42; 33, 39), um die flexible Führung mechanisch mit dem Bandausgabemittel und den Haltermitteln zu verbinden.

4. Flexible Führung nach Anspruch 3, dadurch gekennzeichnet, daß das Befestigungsmittel (23) zum Befestigen der flexiblen Führung an den Haltermitteln eine hohle zylinderförmige Stirnsäule ist, die in einen entsprechenden zylinderförmigen Durchgang (31) in Haltermittel (12) gesetzt wird.

5. Flexible Führung nach Anspruch 3, dadurch gekennzeichnet, daß das Befestigungsmittel (42) zum Befestigen der flexiblen Führung an den Haltermitteln eine geschlitzte Muffe (42) ist, die in die Montagestange (43) auf dem Haltermittel (13) einschnappt.

6. Flexible Führung nach Anspruch 3, 4 oder 5, dadurch gekennzeichnet, daß das Befestigungs-

mittel (33) zum Befestigen der flexiblen Führung am Bandausgabemittel eine Montagessäule (33) ist, die in Öffnungen (34, 36) auf der Oberseite (37) und Unterseite (38) des Bandausgabemittels (11) sitzt.

7. Flexible Führung nach Anspruch 3, 4 oder 5, dadurch gekennzeichnet, daß das Befestigungsmittel zum Befestigen der flexiblen Führung am Bandausgabemittel eine hohle zylinderförmige Stirnsäule (39) ist, die in eine Montagessäule (41) auf dem Bandausgabemittel geführt wird.

Revendications

1. Un guide flexible pour guider un ruban dans un dispositif d'alimentation de ruban du type comprenant un canal présentant un côté continu et des côtés discontinus de façon qui le canal ne soit recourbé que dans une seule direction, et étant caractérisé en ce que:

ledit canal est un canal en forme de U (17, 18) comprenant deux côtés et un fond, le premier côté (20) étant le côté continu et le second côté (19) et le fond (21) étant les côtés discontinus, et en ce qu'il comprend une pluralité de pinces supérieures (27) raccordant les deux côtés du canal, ce qui permet au guide de ruban d'assurer un bon cheminement du ruban et de le maintenir hors du contact de tout élément autre que le guide de ruban lui-même.

2. Un guide flexible selon la revendication 1 caractérisé en ce qu'il comprend:

une pluralité de nervures pratiquement verticales (24) sur la face interne d'au moins l'un des côtés du canal afin de réduire ainsi le contact par frottement du ruban et du guide sans réduire la flexibilité du guide.

3. Un guide flexible selon la revendication 1 ou 2 à utiliser dans un dispositif d'impression du type à point d'impression latéralement mobile, comprenant un ruban (14, 15), un moyen d'alimentation de ruban (11, 41) et des moyens de support (12, 13) assurant le positionnement du ruban adjacent au point d'impression, caractérisé en ce qu'il comprend:

des attaches (28, 42, 33, 39) pour fixer le guide flexible au moyen d'alimentation de ruban et aux moyens de support.

4. Un guide flexible selon la revendication 3 caractérisé en ce que les attaches (28) pour la fixation du guide flexible aux moyens de support sont constituées par une colonnette cylindrique creuse qui est insérée dans des passages cylindriques correspondants (31) prévus dans le moyen de support (12).

5. Un guide flexible selon la revendication 3 caractérisé en ce que les attaches (42) fixant le guide flexible au moyen de support est un manchon (42) à découpes qui se fixe automatiquement sur un axe de montage (43) du moyen de support (13).

6. Un guide flexible selon la revendication 3, 4 ou 5 caractérisé en ce que les attaches (33) fixant le guide flexible au moyen d'alimentation de ruban sont des colonnettes de montage (33) qui



sont engagées dans des trous (34, 36) ménagés dans les languettes supérieure (34) et inférieure (36) des côtés supérieur (37) et inférieur (38) du moyen d'alimentation de ruban (11).

7. Un guide flexible selon la revendication 3, 4 ou 5 caractérisé en ce que les attaches pour fixer

le guide flexible au moyen d'alimentation de ruban consistent en colonnettes cylindriques creuses (39) qui sont engagées sur une colonnette de montage (41) du moyen d'alimentation de ruban.



10

15

20

25

30

35

40

45

50

55

60

