# HYDROCARBON GAS PROCESSING

of which the following is a

## SPECIFICATION

## BACKGROUND OF THE INVENTION

**[0001]** This invention relates to a process for the separation of a gas containing hydrocarbons. The applicants claim the benefits under Title 35, United States Code, Section

119(e) of prior U.S. Provisional Application Number 60/692,126 which was filed on June 20, 2005.

[0002] Ethylene, ethane, propylene, propane, and/or heavier hydrocarbons can be recovered from a variety of gases, such as natural gas, refinery gas, and synthetic gas streams obtained from other hydrocarbon materials such as coal, crude oil, naphtha, oil shale, tar sands, and lignite. Natural gas usually has a major proportion of methane and ethane, i.e., methane and ethane together comprise at least 50 mole percent of the gas. The gas also contains relatively lesser amounts of heavier hydrocarbons such as propane, butanes, pentanes, and the like, as well as hydrogen, nitrogen, carbon dioxide, and other gases.

[0003] The present invention is generally concerned with the recovery of ethylene, ethane, propylene, propane, and heavier hydrocarbons from such gas streams. A typical analysis of a gas stream to be processed in accordance with this invention would be, in approximate mole percent, 91.6% methane, 4.2% ethane and other $C_2$ components, 1.3% propane and other $C_3$ components, 0.4% iso-butane, 0.3% normal butane, 0.5% pentanes plus, 1.4% carbon dioxide, with the balance made up of nitrogen. Sulfur containing gases are also sometimes present.

[0004] The historically cyclic fluctuations in the prices of both natural gas and its natural gas liquid (NGL) constituents have at times reduced the incremental value of ethane, ethylene, propane, propylene, and heavier components as liquid products. This has resulted in a demand for processes that can provide more efficient recoveries of these products, for processes that can provide efficient recoveries with lower capital investment and lower operating costs, and for processes that can be easily adapted or adjusted to vary the recovery of a specific component over a broad range. Available processes for separating these materials include those based upon

cooling and refrigeration of gas, oil absorption, and refrigerated oil absorption. Additionally, cryogenic processes have become popular because of the availability of economical equipment that produces power while simultaneously expanding and extracting heat from the gas being processed. Depending upon the pressure of the gas source, the richness (ethane, ethylene, and heavier hydrocarbons content) of the gas, and the desired end products, each of these processes or a combination thereof may be employed.

[0005] The cryogenic expansion process is now generally preferred for natural gas liquids recovery because it provides maximum simplicity with ease of startup, operating flexibility, good efficiency, safety, and good reliability. U.S. Patent Nos. 3,292,380; 4,061,481; 4,140,504; 4,157,904; 4,171,964; 4,185,978; 4,251,249; 4,278,457; 4,519,824; 4,617,039; 4,687,499; 4,689,063; 4,690,702; 4,854,955; 4,869,740; 4,889,545; 5,275,005; 5,555,748; 5,568,737; 5,771,712; 5,799,507; 5,881,569; 5,890,378; 5,983,664; 6,182,469; 6,712,880; 6,915,662; reissue U.S. Patent No. 33,408; U.S. Application Publ. No. 2002/0166336 A1; and co-pending application no. 11/201,358 describe relevant processes (although the description of the present invention in some cases is based on different processing conditions than those described in the cited patents and applications).

[0006] In a typical cryogenic expansion recovery process, a feed gas stream under pressure is cooled by heat exchange with other streams of the process and/or external sources of refrigeration such as a propane compression-refrigeration system. As the gas is cooled, liquids may be condensed and collected in one or more separators as high-pressure liquids containing some of the desired $C_2$+ or $C_3$+ components. Depending on the richness of the gas and the amount of liquids formed, the high-pressure liquids may be expanded to a lower pressure and

fractionated. The vaporization occurring during expansion of the liquids results in further cooling of the stream. Under some conditions, pre-cooling the high pressure liquids prior to the expansion may be desirable in order to further lower the temperature resulting from the expansion. The expanded stream, comprising a mixture of liquid and vapor, is fractionated in a distillation (demethanizer or deethanizer) column. In the column, the expansion cooled stream(s) is (are) distilled to separate residual methane, nitrogen, and other volatile gases as overhead vapor from the desired $C_2$ components, $C_3$ components, and heavier hydrocarbon components as bottom liquid product, or to separate residual methane, $C_2$ components, nitrogen, and other volatile gases as overhead vapor from the desired $C_3$ components and heavier hydrocarbon components as bottom liquid product.

[0007] If the feed gas is not totally condensed (typically it is not), the vapor remaining from the partial condensation can be passed through a work expansion machine or engine, or an expansion valve, to a lower pressure at which additional liquids are condensed as a result of further cooling of the stream. The pressure after expansion is essentially the same as the pressure at which the distillation column is operated. The expanded stream is then supplied as top feed to the demethanizer. Typically, the vapor portion of the expanded stream and the demethanizer overhead vapor combine in an upper separator section in the fractionation tower as residual methane product gas. Alternatively, the cooled and expanded stream may be supplied to a separator to provide vapor and liquid streams. The vapor is combined with the tower overhead and the liquid is supplied to the column as a top column feed.

[0008] In the ideal operation of such a separation process, the residue gas leaving the process will contain substantially all of the methane in the feed gas with essentially none of the

heavier hydrocarbon components and the bottoms fraction leaving the demethanizer will contain substantially all of the heavier hydrocarbon components with essentially no methane or more volatile components. In practice, however, this ideal situation is not obtained for two main reasons. The first reason is that the conventional demethanizer is operated largely as a stripping column. The methane product of the process, therefore, typically comprises vapors leaving the top fractionation stage of the column, together with vapors not subjected to any rectification step. Considerable losses of $C_2$, $C_3$, and $C_4$+ components occur because the top liquid feed contains substantial quantities of these components, resulting in corresponding equilibrium quantities of $C_2$ components, $C_3$ components, $C_4$ components, and heavier hydrocarbon components in the vapors leaving the top fractionation stage of the demethanizer. The loss of these desirable components could be significantly reduced if the rising vapors could be brought into contact with a significant quantity of liquid (reflux) capable of absorbing the $C_2$ components, $C_3$ components, $C_4$ components, and heavier hydrocarbon components from the vapors.

[0009] The second reason that this ideal situation cannot be obtained is that carbon dioxide contained in the feed gas fractionates in the demethanizer and can build up to concentrations of as much as 5% to 10% or more in the tower even when the feed gas contains less than 1% carbon dioxide. At such high concentrations, formation of solid carbon dioxide can occur depending on temperatures, pressures, and the liquid solubility. It is well known that natural gas streams usually contain carbon dioxide, sometimes in substantial amounts. If the carbon dioxide concentration in the feed gas is high enough, it becomes impossible to process the feed gas as desired due to blockage of the process equipment with solid carbon dioxide (unless carbon dioxide removal equipment is added, which would increase capital cost substantially).

The present invention provides a means for generating a supplemental liquid reflux stream that will improve the recovery efficiency for the desired products while simultaneously substantially mitigating the problem of carbon dioxide icing.

[0010] In recent years, the preferred processes for hydrocarbon separation use an upper absorber section to provide additional rectification of the rising vapors. The source of the reflux stream for the upper rectification section is typically a recycled stream of residue gas supplied under pressure. The recycled residue gas stream is usually cooled to substantial condensation by heat exchange with other process streams, e.g., the cold fractionation tower overhead. The resulting substantially condensed stream is then expanded through an appropriate expansion device, such as an expansion valve, to the pressure at which the demethanizer is operated. During expansion, a portion of the liquid will usually vaporize, resulting in cooling of the total stream. The flash expanded stream is then supplied as top feed to the demethanizer. Typically, the vapor portion of the expanded stream and the demethanizer overhead vapor combine in an upper separator section in the fractionation tower as residual methane product gas. Alternatively, the cooled and expanded stream may be supplied to a separator to provide vapor and liquid streams, so that thereafter the vapor is combined with the tower overhead and the liquid is supplied to the column as a top column feed. Typical process schemes of this type are disclosed in U.S. Patent Nos. 4,889,545; 5,568,737; 5,881,569; 6,712,880; and in Mowrey, E. Ross, "Efficient, High Recovery of Liquids from Natural Gas Utilizing a High Pressure Absorber", Proceedings of the Eighty-First Annual Convention of the Gas Processors Association, Dallas, Texas, March 11-13, 2002.

[0011] The present invention also employs an upper rectification section (or a separate rectification column in some embodiments). However, two reflux streams are provided for this rectification section. The upper reflux stream is a recycled stream of residue gas as described above. In addition, however, a supplemental reflux stream is provided at a lower feed point by using a side draw of the vapors rising in a lower portion of the tower (which may be combined with some of the separator liquids). Because of the relatively high concentration of $C_2$ components and heavier components in the vapors lower in the tower, a significant quantity of liquid can be condensed in this side draw stream without elevating its pressure, often using only the refrigeration available in the cold vapor leaving the upper rectification section. This condensed liquid, which is predominantly liquid methane and ethane, can then be used to absorb $C_3$ components, $C_4$ components, and heavier hydrocarbon components from the vapors rising through the lower portion of the upper rectification section and thereby capture these valuable components in the bottom liquid product from the demethanizer. Since the lower reflux stream captures essentially all of the $C_3$+ components, only a relatively small flow rate of liquid in the upper reflux stream is needed to absorb the $C_2$ components remaining in the rising vapors and likewise capture these $C_2$ components in the bottom liquid product from the demethanizer.

[0012] Heretofore, such a vapor side draw feature has been employed in $C_3$+ recovery systems, as illustrated in the assignee's U.S. Patent No. 5,799,507. The process and apparatus of U.S. Patent No. 5,799,507, however, are unsuitable for high ethane recovery. Surprisingly, applicants have found that $C_2$ recoveries may be improved without sacrificing $C_3$+ component recovery levels or system efficiency by combining the side draw feature of the assignee's U.S.

Patent No. 5,799,507 invention with the residue reflux feature of the assignee's U.S. Patent No. 5,568,737.

[0013] In accordance with the present invention, it has been found that $C_2$ component recoveries in excess of 97 percent can be obtained with no loss in $C_3$+ component recovery. The present invention provides the further advantage of being easily adapted to using much of the equipment required to implement assignee's U.S. Patent No. 5,799,507, resulting in lower capital investment costs compared to other prior art processes. In addition, the present invention makes possible essentially 100 percent separation of methane and lighter components from the $C_2$ components and heavier components while maintaining the same recovery levels as the prior art and improving the safety factor with respect to the danger of carbon dioxide icing. The present invention, although applicable at lower pressures and warmer temperatures, is particularly advantageous when processing feed gases in the range of 400 to 1500 psia [2,758 to 10,342 kPa(a)] or higher under conditions requiring NGL recovery column overhead temperatures of -50°F [-46°C] or colder.

[0014] For a better understanding of the present invention, reference is made to the following examples and drawings. Referring to the drawings:

[0015] FIG. 1 is a flow diagram of a prior art natural gas processing plant in accordance with United States Patent No. 5,799,507;

[0016] FIG. 2 is a flow diagram of a base case natural gas processing plant modifying a design in accordance with United States Patent No. 5,568,737;

[0017] FIG. 3 is a flow diagram of a natural gas processing plant in accordance with the present invention;

[0018] FIG. 4 is a concentration-temperature diagram for carbon dioxide showing the effect of the present invention;

[0019] FIG. 5 is a flow diagram illustrating an alternative means of application of the present invention to a natural gas stream;

[0020] FIG. 6 is a concentration-temperature diagram for carbon dioxide showing the effect of the present invention with respect to the process of FIG. 5; and

[0021] FIGS. 7 through 10 are flow diagrams illustrating alternative means of application of the present invention to a natural gas stream.

[0022] In the following explanation of the above figures, tables are provided summarizing flow rates calculated for representative process conditions. In the tables appearing herein, the values for flow rates (in moles per hour) have been rounded to the nearest whole number for convenience. The total stream rates shown in the tables include all non-hydrocarbon components and hence are generally larger than the sum of the stream flow rates for the hydrocarbon components. Temperatures indicated are approximate values rounded to the nearest degree. It should also be noted that the process design calculations performed for the purpose of comparing the processes depicted in the figures are based on the assumption of no heat leak from (or to) the surroundings to (or from) the process. The quality of commercially available insulating materials makes this a very reasonable assumption and one that is typically made by those skilled in the art.

[0023] For convenience, process parameters are reported in both the traditional British units and in the units of the Système International d'Unités (SI). The molar flow rates given in the tables may be interpreted as either pound moles per hour or kilogram moles per hour. The

energy consumptions reported as horsepower (HP) and/or thousand British Thermal Units per hour (MBTU/Hr) correspond to the stated molar flow rates in pound moles per hour. The energy consumptions reported as kilowatts (kW) correspond to the stated molar flow rates in kilogram moles per hour.

**[0024]** FIG. 1 is a process flow diagram showing the design of a processing plant to recover $C_3$+ components from natural gas using prior art according to assignee's U.S. Pat. No. 5,799,507. In this simulation of the process, inlet gas enters the plant at 120°F [49°C] and 1040 psia [7,171 kPa(a)] as stream **31**. If the inlet gas contains a concentration of sulfur compounds which would prevent the product streams from meeting specifications, the sulfur compounds are removed by appropriate pretreatment of the feed gas (not illustrated). In addition, the feed stream is usually dehydrated to prevent hydrate (ice) formation under cryogenic conditions. Solid desiccant has typically been used for this purpose.

**[0025]** The feed stream **31** is cooled in heat exchanger **10** by heat exchange with cool residue gas at -88°F [-67°C] (stream **52**) and flash expanded separator liquids (stream **33a**). The cooled stream **31a** enters separator **11** at -34°F [–37°C] and 1025 psia [7,067 kPa(a)] where the vapor (stream **32**) is separated from the condensed liquid (stream **33**). The separator liquid (stream **33**) is expanded to slightly above the operating pressure of fractionation tower **19** by expansion valve **12**, cooling stream **33a** to -67°F [-55°C]. Stream **33a** enters heat exchanger **10** to supply cooling to the feed gas as described previously, heating stream **33b** to 116°F [47°C] before it is supplied to fractionation tower **19** at a lower mid-column feed point.

[0026] The separator vapor (stream **32**) enters a work expansion machine **17** in which mechanical energy is extracted from this portion of the high pressure feed. The machine **17** expands the vapor substantially isentropically to the tower operating pressure of approximately 420 psia [2,894 kPa(a)], with the work expansion cooling the expanded stream **32a** to a temperature of approximately -108°F [-78°C]. The typical commercially available expanders are capable of recovering on the order of 80-88% of the work theoretically available in an ideal isentropic expansion. The work recovered is often used to drive a centrifugal compressor (such as item **18**) that can be used to re-compress the residue gas (stream **52a**), for example. The partially condensed expanded stream **32a** is thereafter supplied as feed to fractionation tower **19** at an upper mid-column feed point.

[0027] The deethanizer in tower **19** is a conventional distillation column containing a plurality of vertically spaced trays, one or more packed beds, or some combination of trays and packing. The deethanizer tower consists of two sections: an upper absorbing (rectification) section **19a** that contains the trays and/or packing to provide the necessary contact between the vapor portion of the expanded stream **32a** rising upward and cold liquid falling downward to condense and absorb the $C_3$ components and heavier components; and a lower, stripping section **19b** that contains the trays and/or packing to provide the necessary contact between the liquids falling downward and the vapors rising upward. The deethanizing section **19b** also includes at least one reboiler (such as reboiler **20**) which heats and vaporizes a portion of the liquids flowing down the column to provide the stripping vapors which flow up the column to strip the liquid product, stream **41**, of methane, $C_2$ components, and lighter components. Stream **32a** enters deethanizer **19** at an upper mid-column feed position located in the lower region of absorbing

section **19a** of deethanizer **19**. The liquid portion of expanded stream **32a** commingles with liquids falling downward from the absorbing section **19a** and the combined liquid continues downward into the stripping section **19b** of deethanizer **19**. The vapor portion of expanded stream **32a** rises upward through absorbing section **19a** and is contacted with cold liquid falling downward to condense and absorb the $C_3$ components and heavier components.

**[0028]** A portion of the distillation vapor (stream **42**) is withdrawn from the upper region of stripping section **19b**. This stream is then cooled and partially condensed (stream **42a**) in exchanger **22** by heat exchange with cold deethanizer overhead stream **38** which exits the top of deethanizer **19** at -114°F [-81°C] and with a portion of the cold distillation liquid (stream **47**) withdrawn from the lower region of absorbing section **19a** at -112°F [-80°C]. The cold deethanizer overhead stream is warmed to approximately -87°F [-66°C] (stream **38a**) and the distillation liquid is heated to -43°F [-42°C] (stream **47a**) as they cool stream **42** from -39°F [-40°C] to about -109°F [-78°C] (stream **42a**). The heated and partially vaporized distillation liquid (stream **47a**) is then returned to deethanizer **19** at a mid-point of stripping section **19b**.

**[0029]** The operating pressure in reflux separator **23** is maintained slightly below the operating pressure of deethanizer **19**. This pressure difference provides the driving force that allows distillation vapor stream **42** to flow through heat exchanger **22** and thence into the reflux separator **23** wherein the condensed liquid (stream **44**) is separated from the uncondensed vapor (stream **43**). The uncondensed vapor stream **43** combines with the warmed deethanizer overhead stream **38a** from exchanger **22** to form cool residue gas stream **52** at -88°F [-67°C].

**[0030]** The liquid stream **44** from reflux separator **23** is pumped by pump **24** to a pressure slightly above the operating pressure of deethanizer **19**. The resulting stream **44a** is

then divided into two portions. The first portion (stream **45**) is supplied as cold top column feed (reflux) to the upper region of absorbing section **19a** of deethanizer **19**. This cold liquid causes an absorption cooling effect to occur inside the absorbing (rectification) section **19a** of deethanizer **19**, wherein the saturation of the vapors rising upward through the tower by vaporization of liquid methane and ethane contained in stream **45** provides refrigeration to the section. Note that, as a result, both the vapor leaving the upper region (overhead stream **38**) and the liquids leaving the lower region (liquid distillation stream **47**) of absorbing section **19a** are colder than the either of the feed streams (streams **45** and stream **32a**) to absorbing section **19a**. This absorption cooling effect allows the tower overhead (stream **38**) to provide the cooling needed in heat exchanger **22** to partially condense the vapor distillation stream (stream **42**) without operating stripping section **19b** at a pressure significantly higher than that of absorbing section **19a**. This absorption cooling effect also facilitates reflux stream **45** condensing and absorbing the $C_3$ components and heavier components in the distillation vapor flowing upward through absorbing section **19a**. The second portion (stream **46**) of pumped stream **44a** is supplied to the upper region of stripping section **19b** of deethanizer **19** where the cold liquid acts as reflux to absorb and condense the $C_3$ components and heavier components flowing upward from below so that vapor distillation stream **42** contains minimal quantities of these components.

**[0031]** In stripping section **19b** of deethanizer **19**, the feed streams are stripped of their methane and $C_2$ components. The resulting liquid product stream **41** exits the bottom of deethanizer **19** at 225°F [107°C] (based on a typical specification of a ethane to propane ratio of 0.025:1 on a molar basis in the bottom product) before flowing to storage.

[0032] The cool residue gas (stream **52**) passes countercurrently to the incoming feed gas in heat exchanger **10** where it is heated to 115°F [46°C] (stream **52a**). The residue gas is then re-compressed in two stages. The first stage is compressor **18** driven by expansion machine **17**. The second stage is compressor **25** driven by a supplemental power source which compresses the residue gas (stream **52c**) to sales line pressure. After cooling to 120°F [49°C] in discharge cooler **26**, the residue gas product (stream **52d**) flows to the sales gas pipeline at 1040 psia [7,171 kPa(a)], sufficient to meet line requirements (usually on the order of the inlet pressure).

[0033] A summary of stream flow rates and energy consumption for the process illustrated in FIG. 1 is set forth in the following table:

Table I

(FIG. 1)

Stream Flow Summary - Lb. Moles/Hr [kg moles/Hr]

| Stream | Methane | Ethane | Propane | Butanes+ | C. Dioxide | Total |
|---|---|---|---|---|---|---|
| 31 | 25,384 | 1,161 | 362 | 332 | 400 | 27,714 |
| 32 | 25,085 | 1,104 | 315 | 186 | 389 | 27,153 |
| 33 | 299 | 57 | 47 | 146 | 11 | 561 |
| 47 | 2,837 | 1,073 | 327 | 186 | 169 | 4,595 |
| 42 | 4,347 | 1,797 | 26 | 1 | 279 | 6,452 |
| 43 | 1,253 | 69 | 0 | 0 | 25 | 1,349 |
| 44 | 3,094 | 1,728 | 26 | 1 | 254 | 5,103 |
| 45 | 1,887 | 1,054 | 16 | 1 | 155 | 3,113 |
| 46 | 1,207 | 674 | 10 | 0 | 99 | 1,990 |
| 38 | 24,131 | 1,083 | 3 | 0 | 375 | 25,665 |
| 52 | 25,384 | 1,152 | 3 | 0 | 400 | 27,014 |
| 41 | 0 | 9 | 359 | 332 | | 700 |

Recoveries*

| | |
|---|---|
| Propane | 99.08% |
| Butanes+ | 99.99% |

Power

| | | | |
|---|---|---|---|
| Residue Gas Compression | 12,774 | HP | [ 21,000 kW] |

* (Based on un-rounded flow rates)

[0034] The FIG. 1 process is often the optimum choice for gas processing plants when recovery of $C_2$ components is not desired, because it provides very efficient recovery of the $C_3$+ components using equipment that requires less capital investment than other processes. However, the FIG. 1 process is not well suited to recovering $C_2$ components, as $C_2$ component recovery levels on the order of 40% are generally the highest that can be achieved without inordinate increases in the power requirements for the process. If higher $C_2$ component recovery levels than this are desired, a different process is usually required, such as assignee's U.S. Pat. No. 5,568,737.

[0035] FIG. 2 is a process flow diagram showing one manner in which the design of the processing plant in FIG. 1 can be adapted to operate at a higher $C_2$ component recovery level using a base case design according to assignee's U.S. Pat. No. 5,568,737. The process of FIG. 2 has been applied to the same feed gas composition and conditions as described previously for FIG. 1. However, in the simulation of the process of FIG. 2, certain equipment and piping have been added (shown by bold lines) while other equipment and piping have been removed from service (shown by light dashed lines) so that the process operating conditions can be adjusted to increase the recovery of $C_2$ components to about 97%.

[0036] The feed stream **31** is cooled in heat exchanger **10** by heat exchange with a portion of the cool distillation column overhead stream (stream **48**) at -15°F [-26°C], demethanizer liquids (stream **39**) at -33°F [-36°C], demethanizer liquids (stream **40**) at 37°F [3°C], and the pumped demethanizer bottoms liquid (stream **41a**) at 60°F [16°C]. The cooled

stream **31a** enters separator **11** at 4°F [–16°C] and 1025 psia [7,067 kPa(a)] where the vapor (stream **32**) is separated from the condensed liquid (stream **33**).

**[0037]** The separator vapor (stream **32**) is divided into two streams, **34** and **36**. Stream **34**, containing about 30% of the total vapor, is combined with the separator liquid (stream **33**). The combined stream **35** passes through heat exchanger **22** in heat exchange relation with the cold distillation column overhead stream **38** where it is cooled to substantial condensation. The resulting substantially condensed stream **35a** at -138°F [-95°C] is then flash expanded through expansion valve **16** to the operating pressure of fractionation tower **19**, 412 psia [2,839 kPa(a)]. During expansion a portion of the stream is vaporized, resulting in cooling of the total stream. In the process illustrated in FIG. 2, the expanded stream **35b** leaving expansion valve **16** reaches a temperature of -141°F [-96°C] and is supplied to fractionation tower **19** at an upper mid-column feed point.

**[0038]** The remaining 70% of the vapor from separator **11** (stream **36**) enters a work expansion machine **17** in which mechanical energy is extracted from this portion of the high pressure feed. The machine **17** expands the vapor substantially isentropically to the tower operating pressure, with the work expansion cooling the expanded stream **36a** to a temperature of approximately -80°F [-62°C]. The partially condensed expanded stream **36a** is thereafter supplied as feed to fractionation tower **19** at a lower mid-column feed point.

**[0039]** The recompressed and cooled distillation stream **38e** is divided into two streams. One portion, stream **52**, is the residue gas product. The other portion, recycle stream **51**, flows to heat exchanger **27** where it is cooled to -1°F [-18°C] (stream **51a**) by heat exchange with a portion (stream **49**) of cool distillation column overhead stream **38a** at -15°F [-26°C]. The

cooled recycle stream then flows to exchanger **22** where it is cooled to -138°F [-95°C] and substantially condensed by heat exchange with cold distillation stream **38**. The substantially condensed stream **51b** is then expanded through an appropriate expansion device, such as expansion valve **15**, to the demethanizer operating pressure, resulting in cooling of the total stream. In the process illustrated in FIG. 2, the expanded stream **51c** leaving expansion valve **15** reaches a temperature of -145°F [-98°C] and is supplied to the fractionation tower as the top column feed. The vapor portion (if any) of stream **51c** combines with the vapors rising from the top fractionation stage of the column to form distillation stream **38**, which is withdrawn from an upper region of the tower.

**[0040]** The demethanizer in tower **19** is a conventional distillation column containing a plurality of vertically spaced trays, one or more packed beds, or some combination of trays and packing. As is often the case in natural gas processing plants, the fractionation tower may consist of two sections. The upper section **19a** is a separator wherein the top feed is divided into its respective vapor and liquid portions, and wherein the vapor rising from the lower distillation or demethanizing section **19b** is combined with the vapor portion (if any) of the top feed to form the cold demethanizer overhead vapor (stream **38**) which exits the top of the tower at -142°F [-97°C]. The lower, demethanizing section **19b** contains the trays and/or packing and provides the necessary contact between the liquids falling downward and the vapors rising upward. The demethanizing section **19b** also includes reboilers (such as trim reboiler **20** and the reboiler and side reboiler described previously) which heat and vaporize a portion of the liquids flowing down the column to provide the stripping vapors which flow up the column to strip the liquid product, stream **41**, of methane and lighter components.

[0041] The liquid product stream **41** exits the bottom of the tower at 55°F [13°C], based on a typical specification of a methane to ethane ratio of 0.025:1 on a molar basis in the bottom product. Pump **21** delivers stream **41a** to heat exchanger **10** as described previously where it is heated to 116°F [47°C] before flowing to storage. The demethanizer overhead vapor stream **38** passes countercurrently to the incoming feed gas and recycle stream in heat exchanger **22** where it is heated to -15°F [-26°C]. The heated stream **38a** is divided into two portions (streams **49** and **48**), which are heated to 116°F [47°C] and 78°F [25°C], respectively, in heat exchanger **27** and heat exchanger **10**. The heated streams recombine to form stream **38b** at 84°F [29°C] which is then re-compressed in two stages, compressor **18** driven by expansion machine **17** and compressor **25** driven by a supplemental power source. After stream **38d** is cooled to 120°F [49°C] in discharge cooler **26** to form stream **38e**, recycle stream **51** is withdrawn as described earlier to form residue gas stream **52** which flows to the sales gas pipeline at 1040 psia [7,171 kPa(a)].

[0042] A summary of stream flow rates and energy consumption for the process illustrated in FIG. 2 is set forth in the following table:

Table II

(FIG. 2)

Stream Flow Summary - Lb. Moles/Hr [kg moles/Hr]

| Stream | Methane | Ethane | Propane | Butanes+ | C. Dioxide | Total |
|---|---|---|---|---|---|---|
| 31 | 25,384 | 1,161 | 362 | 332 | 400 | 27,714 |
| 32 | 25,307 | 1,145 | 348 | 252 | 397 | 27,524 |
| 33 | 77 | 16 | 14 | 80 | 3 | 190 |
| 34 | 7,719 | 349 | 106 | 77 | 121 | 8,395 |
| 36 | 17,588 | 796 | 242 | 175 | 276 | 19,129 |
| 35 | 7,796 | 365 | 120 | 157 | 124 | 8,585 |
| 38 | 29,587 | 40 | 0 | 0 | 146 | 29,859 |
| 51 | 4,231 | 6 | 0 | 0 | 21 | 4,270 |
| 52 | 25,356 | 34 | 0 | 0 | 125 | 25,589 |
| 41 | 28 | 1,127 | 362 | 332 | 275 | 2,125 |

Recoveries*

| | |
|---|---|
| Ethane | 97.04% |
| Propane | 100.00% |
| Butanes+ | 100.00% |

Power

| | | | |
|---|---|---|---|
| Residue Gas Compression | 14,219 | HP | [ 23,376 kW] |

* (Based on un-rounded flow rates)

[0043] By modifying the FIG. 1 equipment and piping as shown in FIG. 2, the natural gas processing plant can now achieve 97% recovery of the $C_2$ components in the feed gas. This means that the plant has the flexibility to operate as shown in FIG. 2 and recover essentially all of the $C_2$ components when the value of liquid $C_2$ components is attractive, or to operate as shown in FIG. 1 and reject the $C_2$ components to the plant residue gas when the $C_2$ components are more valuable as gaseous fuel. However, the required modifications require much additional equipment and piping (as shown by the bold lines) and do not make use of much of the equipment present in the FIG. 1 plant (shown by the light dashed lines), so the capital cost of a plant designed to operate using both the FIG. 1 process and the FIG. 2 process will be higher than is desirable. (Note that although the FIG. 2 process can be adapted to reject the $C_2$ components like the FIG. 1 process, the power consumption when operating in this manner is essentially the same as that shown in Table II. Since this is about 11% higher than that of the FIG. 1 process as shown in Table I, the operating cost of a plant using the FIG. 1 process is considerably lower than that of one using the FIG. 2 process in this manner.)

## DESCRIPTION OF THE INVENTION

### Example 1

**[0044]** FIG. 3 is a process flow diagram illustrating how the design of the processing plant in FIG. 1 can be adapted to operate at a higher $C_2$ component recovery level in accordance with the present invention. The process of FIG. 3 has been applied to the same feed gas composition and conditions as described previously for FIG. 1. However, in the simulation of the process of the present invention as shown in FIG. 3, certain equipment and piping have been added (shown by bold lines) while other equipment and piping have been removed from service (shown by light dashed lines) as noted by the legend on FIG. 3 so that the process operating conditions can be adjusted to increase the recovery of $C_2$ components to about 97%. Since the feed gas composition and conditions considered in the process presented in FIG. 3 are the same as those in FIG. 2, the FIG. 3 process can be compared with that of the FIG. 2 process to illustrate the advantages of the present invention.

**[0045]** In the simulation of the FIG. 3 process, inlet gas enters the plant as stream **31** and is cooled in heat exchanger **10** by heat exchange with a portion (stream **48**) of cool distillation stream **50** at -90°F [-68°C], demethanizer liquids (stream **39**) at -59°F [-50°C], demethanizer liquids (stream **40**) at 44°F [7°C], and the pumped demethanizer bottoms liquid (stream **41a**) at 69°F [21°C]. The cooled stream **31a** enters separator **11** at -49°F [-45°C] and 1025 psia [7,067 kPa(a)] where the vapor (stream **32**) is separated from the condensed liquid (stream **33**)

**[0046]** The separator vapor (stream **32**) enters a work expansion machine **17** in which mechanical energy is extracted from this portion of the high pressure feed. The machine **17**

expands the vapor substantially isentropically to the tower operating pressure of 440 psia [3,032 kPa(a)], with the work expansion cooling the expanded stream **32a** to a temperature of approximately -115°F [-82°C]. The partially condensed expanded stream **32a** is thereafter supplied as feed to fractionation tower **19** at a lower mid-column feed point.

**[0047]** The recompressed and cooled distillation stream **50d** is divided into two streams. One portion, stream **52**, is the residue gas product. The other portion, recycle stream **51**, flows to heat exchanger **27** where it is cooled to -49°F [-45°C] (stream **51a**) by heat exchange with a portion (stream **49**) of cool distillation stream **50** at -90°F [-68°C]. The cooled recycle stream then flows to exchanger **22** where it is cooled to -134°F [-92°C] and substantially condensed by heat exchange with cold distillation column overhead stream **38**. The substantially condensed stream **51b** is then expanded through an appropriate expansion device, such as expansion valve **15**, to the demethanizer operating pressure, resulting in cooling of the total stream. In the process illustrated in FIG. 3, the expanded stream **51c** leaving expansion valve **15** reaches a temperature of -141°F [-96°C] and is supplied to the fractionation tower as the top column feed. The vapor portion (if any) of stream **51c** combines with the vapors rising from the top fractionation stage of the column to form distillation stream **38**, which is withdrawn from an upper region of the tower.

**[0048]** The demethanizer in tower **19** is a conventional distillation column containing a plurality of vertically spaced trays, one or more packed beds, or some combination of trays and packing. The demethanizer tower consists of three sections: an upper separator section **19a** wherein the top feed is divided into its respective vapor and liquid portions, and wherein the vapor rising from the intermediate absorbing section **19b** is combined with the vapor portion (if

any) of the top feed to form the cold demethanizer overhead vapor (stream **38**); an intermediate absorbing (rectification) section **19b** that contains the trays and/or packing to provide the necessary contact between the vapor portion of the expanded stream **32a** rising upward and cold liquid falling downward to condense and absorb the $C_2$ components, $C_3$ components, and heavier components; and a lower, stripping section **19c** that contains the trays and/or packing to provide the necessary contact between the liquids falling downward and the vapors rising upward. The demethanizing section **19c** also includes reboilers (such as trim reboiler **20** and the reboiler and side reboiler described previously) which heat and vaporize a portion of the liquids flowing down the column to provide the stripping vapors which flow up the column to strip the liquid product, stream **41**, of methane and lighter components.

**[0049]** Stream **32a** enters demethanizer **19** at an intermediate feed position located in the lower region of absorbing section **19b** of demethanizer **19**. The liquid portion of expanded stream **32a** commingles with liquids falling downward from the absorbing section **19b** and the combined liquid continues downward into the stripping section **19c** of demethanizer **19**. The vapor portion of expanded stream **32a** rises upward through absorbing section **19b** and is contacted with cold liquid falling downward to condense and absorb the $C_2$ components, $C_3$ components, and heavier components.

**[0050]** The separator liquid (stream **33**) may be divided into two portions (stream **34** and stream **35**). The first portion (stream **34**), which may be from 0% to 100%, is expanded to the operating pressure of fractionation tower **19** by expansion valve **14** and the expanded stream **34a** is supplied to fractionation tower **19** at a second lower mid-column feed point. Any remaining portion (stream **35**), which may be from 100% to 0%, is expanded to the operating pressure of

fractionation tower **19** by expansion valve **12**, cooling it to -88°F [-67°C] (stream **35a**). A portion of the distillation vapor (stream **42**) is withdrawn from the upper region of stripping section **19c** at -118°F [-83°C] and combined with stream **35a**. The combined stream **37** is then cooled from -101°F [-74°C] to -135°F [-93°C] and condensed (stream **37a**) in heat exchanger **22** by heat exchange with the cold demethanizer overhead stream **38** exiting the top of demethanizer **19** at -138°F [-95°C]. The cold demethanizer overhead stream is heated to -90°F [-68°C] (stream **38a**) as it cools and condenses streams **37** and **51a**. Note that in all cases exchangers **10**, **22**, and **27** are representative of either a multitude of individual heat exchangers or a single multi-pass heat exchanger, or any combination thereof. (The decision as to whether to use more than one heat exchanger for the indicated heating services will depend on a number of factors including, but not limited to, inlet gas flow rate, heat exchanger size, stream temperatures, etc.)

**[0051]** The operating pressure in reflux separator **23** (436 psia [3,005 kPa(a)]) is maintained slightly below the operating pressure of demethanizer **19**. This provides the driving force which allows distillation vapor stream **42** to combine with stream **35a** and the combined stream **37** to flow through heat exchanger **22** and thence into the reflux separator **23**. Any uncondensed vapor (stream **43**) is separated from the condensed liquid (stream **44**) in reflux separator **23** and then combined with the heated demethanizer overhead stream **38a** from heat exchanger **22** to form cool distillation vapor stream **50** at -90°F [-68°C].

**[0052]** The liquid stream **44** from reflux separator **23** is pumped by pump **24** to a pressure slightly above the operating pressure of demethanizer **19**, and the resulting stream **44a** is then supplied as cold liquid reflux to an intermediate region in absorbing section **19b** of demethanizer **19**. This supplemental reflux absorbs and condenses most of the $C_3$ components

and heavier components (as well as some of the $C_2$ components) from the vapors rising in the lower rectification region of absorbing section **19b** so that only a small amount of recycle (stream **51**) must be cooled, condensed, subcooled, and flash expanded to produce the top reflux stream **51c** that provides the final rectification in the upper region of absorbing section **19b**. As the cold reflux stream **51c** contacts the rising vapors in the upper region of absorbing section **19b**, it condenses and absorbs the $C_2$ components and any remaining $C_3$ components and heavier components from the vapors so that they can be captured in the bottom product (stream **41**) from demethanizer **19**.

**[0053]** In stripping section **19c** of demethanizer **19**, the feed streams are stripped of their methane and lighter components. The resulting liquid product (stream **41**) exits the bottom of tower **19** at 65°F [19°C], based on a typical specification of a methane to ethane ratio of 0.025:1 on a molar basis in the bottom product. Pump **21** delivers stream **41a** to heat exchanger **10** as described previously where it is heated to 114°F [45°C] before flowing to storage.

**[0054]** The distillation vapor stream forming the tower overhead (stream **38**) is warmed in heat exchanger **22** as it provides cooling to combined stream **37** and recycle stream **51a** as described previously, then combines with any uncondensed vapor in stream **43** to form cool distillation stream **50**. Distillation stream **50** is divided into two portions (streams **49** and **48**), which are heated to 116°F [47°C] and 80°F [27°C], respectively, in heat exchanger **27** and heat exchanger **10**. The heated streams recombine to form stream **50a** at 87°F [31°C] which is then re-compressed in two stages, compressor **18** driven by expansion machine **17** and compressor **25** driven by a supplemental power source. After stream **50c** is cooled to 120°F [49°C] in discharge

cooler **26** to form stream **50d**, recycle stream **51** is withdrawn as described earlier to form residue gas stream **52** which flows to the sales gas pipeline at 1040 psia [7,171 kPa(a)].

**[0055]** A summary of stream flow rates and energy consumption for the process illustrated in FIG. 3 is set forth in the following table:

Table III

(FIG. 3)

Stream Flow Summary - Lb. Moles/Hr [kg moles/Hr]

| Stream | Methane | Ethane | Propane | Butanes+ | C. Dioxide | Total |
|---|---|---|---|---|---|---|
| 31 | 25,384 | 1,161 | 362 | 332 | 400 | 27,714 |
| 32 | 24,823 | 1,066 | 293 | 163 | 380 | 26,800 |
| 33 | 561 | 95 | 69 | 169 | 20 | 914 |
| 34 | 0 | 0 | 0 | 0 | 0 | 0 |
| 35 | 561 | 95 | 69 | 169 | 20 | 914 |
| 42 | 2,025 | 44 | 3 | 0 | 26 | 2,100 |
| 37 | 2,586 | 139 | 72 | 169 | 46 | 3,014 |
| 43 | 0 | 0 | 0 | 0 | 0 | 0 |
| 44 | 2,586 | 139 | 72 | 169 | 46 | 3,014 |
| 38 | 31,498 | 42 | 0 | 0 | 216 | 31,850 |
| 50 | 31,498 | 42 | 0 | 0 | 216 | 31,850 |
| 51 | 6,142 | 8 | 0 | 0 | 42 | 6,211 |
| 52 | 25,356 | 34 | 0 | 0 | 174 | 25,639 |
| 41 | 28 | 1,127 | 362 | 332 | 226 | 2,075 |

| | | |
|---|---|---|
| Recoveries* | | |
| Ethane | 97.05% | |
| Propane | 100.00% | |
| Butanes+ | 100.00% | |
| Power | | |
| Residue Gas Compression | 14,303 HP | [ 23,514 kW] |

* (Based on un-rounded flow rates)

[0056] A comparison of Tables II and III shows that, compared to the base case, the present invention maintains essentially the same ethane recovery (97.05% versus 97.04%), propane recovery (100.00% versus 100.00%), and butanes+ recovery (100.00% versus 100.00%). Comparison of Tables II and III further shows that these yields were achieved using essentially the same horsepower requirements.

[0057] However, a comparison of FIG. 2 and FIG. 3 shows that the present invention as depicted in FIG. 3 makes much more effective use of the equipment and piping for the FIG. 1 process than the process depicted in FIG. 2 does. The following Tables IV and V compare the changes needed to convert the natural gas processing plant depicted in FIG. 1 to use either the process depicted in FIG. 2 or the process of the present invention as depicted in FIG. 3. Table IV shows the equipment and piping that must be added to or modified in the FIG. 1 process to convert it, and Table V shows the equipment and piping in the FIG. 1 process that become surplus when it is converted.

Table IV

Comparison of FIG. 2 and FIG. 3

| Additional / Modified Equipment and Piping | FIG. 2 | FIG. 3 |
|---|---|---|
| Additional passes in heat exchanger 10 | yes | yes |
| Flash expansion valve 14 | no | maybe |
| Flash expansion valve 15 | yes | yes |
| Flash expansion valve 16 | yes | no |
| Additional feed point and rectification section for column 19 | yes | yes |
| Demethanizer bottoms pump 21 | yes | yes |
| First cooling pass in heat exchanger 22 designed for high pressure | yes | no |
| Second cooling pass in heat exchanger 22 | yes | yes |
| Heat exchanger 27 | yes | yes |
| Column liquid draw piping for stream 39 | yes | yes |
| Column liquid draw and return piping for streams 40 and 40a | yes | yes |
| Liquid piping for streams 41a and 41b | yes | yes |
| Gas piping for streams 49 and 49a | yes | yes |
| Liquid piping for stream 51c | yes | yes |
| Gas/liquid piping for streams 34 and 35 (as depicted in FIG. 2) | yes | no |
| Liquid piping for streams 34 and 34a (as depicted in FIG. 3) | no | maybe |
| Liquid piping for stream 35a (as depicted in FIG. 3) | no | maybe |

Table V

Comparison of FIG. 2 and FIG. 3

| Surplus Equipment and Piping | FIG. 2 | FIG. 3 |
|---|---|---|
| Flash expansion valve 12 | yes | no |
| Reflux drum 23 | yes | no |
| Reflux pump 24 | yes | no |
| Liquid piping for upper reflux from stream 44a | yes | no |
| Liquid piping for lower reflux from stream 44a | yes | yes |
| Vapor piping for vapor distillation stream 42 | yes | no |
| Liquid piping for liquid distillation streams 47 and 47a | yes | yes |

**[0058]** As Table IV shows, the present invention as depicted in FIG. 3 requires fewer changes to the equipment and piping of the FIG. 1 process to adapt it for high $C_2$ component recovery levels compared to the process of FIG. 2. Further, as Table V shows, nearly all of the equipment and piping of the FIG. 1 process can remain in service when the present invention is applied as shown in FIG. 3, making more effective use of the capital investment already required for the FIG. 1 gas processing plant. Thus, the present invention provides a very economical means for constructing a gas processing plant that can adjust its recovery level to adapt to changes in the plant economics. When the value of $C_2$ components as a liquid is high, the present invention can be operated as depicted in FIG. 3 to efficiently recover essentially all of the $C_2$ components (plus the $C_3$ components and heavier components) present in the feed gas. When the $C_2$ components have greater value as gaseous fuel, the same plant can be operated using the prior art process depicted in FIG. 1 to efficiently reject all of the $C_2$ components to the residue

gas while recovering essentially all of the $C_3$ components and heavier components in the column bottom product. Although the process depicted in FIG. 2 can accomplish this same flexibility, the capital cost of a gas processing plant capable of operating as shown in both FIGS. 1 and 2 is higher than a plant that can operate as shown in both FIGS. 1 and 3.

**[0059]** The key feature of the present invention is the supplemental rectification provided by reflux stream **44a**, which reduces the amount of $C_3$ components and $C_4$+ components contained in the vapors rising in the upper region of absorbing section **19b**. Although the flow rate of reflux stream **44a** in FIG. 3 is less than half of the flow rate of stream **35b** in FIG. 2, its mass is sufficient to provide bulk recovery of the $C_3$ components and heavier hydrocarbon components contained in expanded feed **32a** and the vapors rising from stripping section **19c**. Consequently, the quantity of liquid methane reflux (stream **51c**) that must be supplied to the upper rectification section in absorbing section **19b** to capture nearly all of the $C_2$ components is only about 45% higher than the flow rate of stream **51c** in FIG. 2, and is still small enough that the cold demethanizer overhead vapor (stream **38**) can provide the refrigeration needed to generate both this reflux and the reflux in stream **44a**. As a result, nearly 100% of the $C_2$ components and substantially all of the heavier hydrocarbon components are recovered in liquid product **41** leaving the bottom of demethanizer **19** without requiring the additional equipment and piping needed to produce stream **35b** in FIG. 2 to accomplish the same result.

**[0060]** A further advantage of the present invention is a reduced likelihood of carbon dioxide icing. FIG. 4 is a graph of the relation between carbon dioxide concentration and temperature. Line **71** represents the equilibrium conditions for solid and liquid carbon dioxide in methane. (The liquid-solid equilibrium line in this graph is based on the data given in

FIG. 16-33 on page 16-24 of the Engineering Data Book, Twelfth Edition, published in 2004 by the Gas Processors Suppliers Association.) A liquid temperature on or to the right of line 71, or a carbon dioxide concentration on or above this line, signifies an icing condition. Because of the variations which normally occur in gas processing facilities (e.g., feed gas composition, conditions, and flow rate), it is usually desired to design a demethanizer with a considerable safety factor between the expected operating conditions and the icing conditions. (Experience has shown that the conditions of the liquids on the fractionation stages of a demethanizer, rather than the conditions of the vapors, govern the allowable operating conditions in most demethanizers. For this reason, the corresponding vapor-solid equilibrium line is not shown in FIG. 4.)

[0061] Also plotted in FIG. 4 is a line representing the conditions for the liquids on the fractionation stages of demethanizer 19 in the FIG. 2 process (line 72). As can be seen, a portion of this operating line lies above the liquid-solid equilibrium line, indicating that the FIG. 2 process cannot be operated at these conditions without encountering carbon dioxide icing problems. As a result, it is not possible to use the FIG. 2 process under these conditions, so the FIG. 2 process cannot actually achieve the recovery efficiencies stated in Table II in practice without removal of at least some of the carbon dioxide from the feed gas. This would, of course, substantially increase capital cost.

[0062] Line 73 in FIG. 4 represents the conditions for the liquids on the fractionation stages of demethanizer 19 in the present invention as depicted in FIG. 3. In contrast to the FIG. 2 process, there is a minimum safety factor of 1.52 between the anticipated operating conditions and the icing conditions for the FIG. 3 process. That is, it would require a 51 percent

increase in the carbon dioxide content of the liquids to cause icing. Thus, the present invention could tolerate a 51% higher concentration of carbon dioxide in its feed gas than the FIG. 2 process could tolerate without risk of icing. Further, whereas the FIG. 2 process cannot be operated to achieve the recovery levels given in Table II because of icing, the present invention could in fact be operated at even higher recovery levels than those given in Table III without risk of icing.

[0063] The shift in the operating conditions of the FIG. 3 demethanizer as indicated by line 73 in FIG. 4 can be understood by comparing the distinguishing features of the present invention to the process of FIG. 2. While the shape of the operating line for the FIG. 2 process (line 72) is similar to the shape of the operating line for the present invention (line 73), there are two key differences. One difference is that the operating temperatures of the critical upper fractionation stages in the demethanizer in the FIG. 3 process are warmer than those of the corresponding fractionation stages in the demethanizer in the FIG. 2 process, effectively shifting the operating line of the FIG. 3 process away from the liquid-solid equilibrium line. The warmer temperatures of the fractionation stages in the FIG. 3 demethanizer are partly the result of operating the tower at higher pressure than the FIG. 2 process. However, the higher tower pressure does not cause a loss in $C_2$+ component recovery levels because the recycle stream 51 in the FIG. 3 process is in essence an open direct-contact compression-refrigeration cycle for the demethanizer using a portion of the volatile residue gas as the working fluid, supplying needed refrigeration to the process to overcome the loss in recovery that normally accompanies an increase in demethanizer operating pressure.

[0064] The more significant difference between the two operating lines in FIG. 4, however, is the much lower concentrations of carbon dioxide in the liquids on the fractionation stages of demethanizer **19** in the FIG. 3 process compared to those of demethanizer **19** in the FIG. 2 process. One of the inherent features in the operation of a demethanizer column to recover $C_2$ components is that the column must fractionate between the methane that is to leave the tower in its overhead product (vapor stream **38**) and the $C_2$ components that are to leave the tower in its bottom product (liquid stream **41**). However, the relative volatility of carbon dioxide lies between that of methane and $C_2$ components, causing the carbon dioxide to appear in both terminal streams. Further, carbon dioxide and ethane form an azeotrope, resulting in a tendency for carbon dioxide to accumulate in the intermediate fractionation stages of the column and thereby cause large concentrations of carbon dioxide to develop in the tower liquids.

[0065] It is well known that adding a third component is often an effective means for "breaking" an azeotrope. As noted in U.S. Patent No. 4,318,723, $C_3$-$C_6$ alkane hydrocarbons, particularly n-butane, are effective in modifying the behavior of carbon dioxide in hydrocarbon mixtures. Experience has shown that the composition of the upper mid-column feed (i.e., stream **35b** in FIG. 2 or stream **44a** in FIG. 3) to demethanizers of this type has significant impact on the composition of the liquids on the crucial fractionation stages in the upper section of the demethanizer. Comparing these two streams in Table II and Table III, note that the $C_3$+ and $C_4$+ component concentrations for the FIG. 2 process are 3.2% and 1.8%, respectively, versus 8.0% and 5.6%, respectively, for the FIG. 3 process. Thus, the concentrations of $C_3$+ components and $C_4$+ components for the upper mid-column feed of the present invention shown in FIG. 3 are 2-3 times higher than those of the process in FIG. 2. The net impact of this is to "break" the

azeotrope and reduce the carbon dioxide concentrations in the column liquids accordingly. A further impact of the higher concentrations of $C_4$+ components in the liquids on the fractionation stages of demethanizer **19** in the FIG. 3 process is to raise the bubble point temperatures of the tray liquids, adding to the favorable shift of operating line **73** for the FIG. 3 process away from the liquid-solid equilibrium line in FIG. 4.

Example 2

**[0066]** FIG. 3 represents the preferred embodiment of the present invention for the temperature and pressure conditions shown because it typically requires the least equipment and the lowest capital investment. An alternative method of producing the supplemental reflux stream for the column is shown in another embodiment of the present invention as illustrated in FIG. 5. The feed gas composition and conditions considered in the process presented in FIG. 5 are the same as those in FIGS. 1 through 3. Accordingly, FIG. 5 can be compared with the FIG. 2 process to illustrate the advantages of the present invention, and can likewise be compared to the embodiment displayed in FIG. 3.

**[0067]** In the simulation of the FIG. 5 process, inlet gas enters the plant as stream **31** and is cooled in heat exchanger **10** by heat exchange with a portion (stream **48**) of cool distillation stream **38a** at -79°F [-62°C], demethanizer liquids (stream **39**) at -47°F [-44°C], demethanizer liquids (stream **40**) at 44°F [7°C], and the pumped demethanizer bottoms liquid (stream **41a**) at 68°F [20°C]. The cooled stream **31a** enters separator **11** at -47°F [–44°C] and 1025 psia [7,067 kPa(a)] where the vapor (stream **32**) is separated from the condensed liquid (stream **33**).

[0068] The separator vapor (stream **32**) enters a work expansion machine **17** in which mechanical energy is extracted from this portion of the high pressure feed. The machine **17** expands the vapor substantially isentropically to the tower operating pressure of 449 psia [3,094 kPa(a)], with the work expansion cooling the expanded stream **32a** to a temperature of approximately -113°F [-80°C]. The partially condensed expanded stream **32a** is thereafter supplied as feed to fractionation tower **19** at a lower mid-column feed point. The separator liquid (stream **33**) may be divided into two portions (stream **34** and stream **35**). The first portion (stream **34**), which may be from 0% to 100%, is expanded to the operating pressure of fractionation tower **19** by expansion valve **14** and the expanded stream **34a** is supplied to fractionation tower **19** at a second lower mid-column feed point.

[0069] The recompressed and cooled distillation stream **38e** is divided into two streams. One portion, stream **52**, is the residue gas product. The other portion, recycle stream **51**, flows to heat exchanger **27** where it is cooled to -70°F [-57°C] (stream **51a**) by heat exchange with a portion (stream **49**) of cool distillation stream **38a** at -79°F [-62°C]. The cooled recycle stream then flows to exchanger **22** where it is cooled to -134°F [-92°C] and substantially condensed by heat exchange with cold distillation column overhead stream **38**. The substantially condensed stream **51b** is then expanded through an appropriate expansion device, such as expansion valve **15**, to the demethanizer operating pressure, resulting in cooling of the total stream. In the process illustrated in FIG. 5, the expanded stream **51c** leaving expansion valve **15** reaches a temperature of -141°F [-96°C] and is supplied to the fractionation tower as the top column feed. The vapor portion (if any) of stream **51c** combines with the vapors rising from the top

fractionation stage of the column to form distillation stream **38**, which is withdrawn from an upper region of the tower.

**[0070]** A portion of the distillation vapor (stream **42**) is withdrawn from the upper region of the stripping section of demethanizer **19** at -119°F [-84°C] and compressed by compressor **30** (stream **42a**) to 668 psia [4,604 kPa(a)]. The remaining portion of separator liquid stream **33** (stream **35**), which may be from 100% to 0%, is expanded to this pressure by expansion valve **12**, cooling it to -67°F [-55°C] before stream **35a** is combined with stream **42a**. The combined stream **37** is then cooled from -74°F [-59°C] to -134°F [-92°C] and condensed (stream **37a**) in heat exchanger **22** by heat exchange with the cold demethanizer overhead stream **38** exiting the top of demethanizer **19** at -138°F [-94°C]. The condensed stream **37a** is then expanded by expansion valve **16** to the operating pressure of demethanizer **19**, and the resulting stream **37b** at -135°F [-93°C] is then supplied as cold liquid reflux to an intermediate region in the absorbing section of demethanizer **19**. This supplemental reflux absorbs and condenses most of the $C_3$ components and heavier components (as well as some of the $C_2$ components) from the vapors rising in the lower rectification region of the absorbing section so that only a small amount of recycle (stream **51**) must be cooled, condensed, subcooled, and flash expanded to produce the top reflux stream **51c** that provides the final rectification in the upper region of the absorbing section.

**[0071]** In the stripping section of demethanizer **19**, the feed streams are stripped of their methane and lighter components. The resulting liquid product (stream **41**) exits the bottom of tower **19** at 64°F [18°C]. Pump **21** delivers stream **41a** to heat exchanger **10** as described previously where it is heated to 116°F [47°C] before flowing to storage.

[0072] The distillation vapor stream forming the tower overhead (stream **38**) is warmed in heat exchanger **22** as it provides cooling to combined stream **37** and recycle stream **51a** as described previously. Stream **38a** is then divided into two portions (streams **49** and **48**), which are heated to 116°F [47°C] and 80°F [31°C], respectively, in heat exchanger **27** and heat exchanger **10**. The heated streams recombine to form stream **38b** at 94°F [34°C] which is then re-compressed in two stages, compressor **18** driven by expansion machine **17** and compressor **25** driven by a supplemental power source. After stream **38d** is cooled to 120°F [49°C] in discharge cooler **26** to form stream **38e**, recycle stream **51** is withdrawn as described earlier to form residue gas stream **52** which flows to the sales gas pipeline at 1040 psia [7,171 kPa(a)].

[0073] A summary of stream flow rates and energy consumption for the process illustrated in FIG. 5 is set forth in the following table:

Table VI

(FIG. 5)

Stream Flow Summary - Lb. Moles/Hr [kg moles/Hr]

| Stream | Methane | Ethane | Propane | Butanes+ | C. Dioxide | Total |
|---|---|---|---|---|---|---|
| 31 | 25,384 | 1,161 | 362 | 332 | 400 | 27,714 |
| 32 | 24,870 | 1,072 | 296 | 166 | 382 | 26,860 |
| 33 | 514 | 89 | 66 | 166 | 18 | 854 |
| 34 | 0 | 0 | 0 | 0 | 0 | 0 |
| 35 | 514 | 89 | 66 | 166 | 18 | 854 |
| 42 | 5,118 | 101 | 5 | 1 | 70 | 5,300 |
| 37 | 5,632 | 190 | 71 | 167 | 88 | 6,154 |
| 38 | 29,831 | 41 | 0 | 0 | 149 | 31,107 |
| 51 | 4,475 | 6 | 0 | 0 | 22 | 4,516 |
| 52 | 25,356 | 35 | 0 | 0 | 127 | 25,591 |
| 41 | 28 | 1,126 | 362 | 332 | 273 | 2,123 |

| | | | | | |
|---|---|---|---|---|---|
| Recoveries* | | | | | |
| Ethane | 97.01% | | | | |
| Propane | 99.99% | | | | |
| Butanes+ | 100.00% | | | | |
| Power | | | | | |
| Residue Gas Compression | 13,161 | HP | [ | 21,637 | kW] |
| Reflux Compression | 522 | HP | [ | 858 | kW] |
| Total Compression | 13,683 | HP | [ | 22,495 | kW] |

* (Based on un-rounded flow rates)

[0074] A comparison of Tables III and VI shows that, compared to the FIG. 3 embodiment of the present invention, the FIG. 5 embodiment maintains essentially the same ethane recovery (97.01% versus 97.05%), propane recovery (99.99% versus 100.00%), and butanes+ recovery (100.00% versus 100.00%). However, comparison of Tables III and VI further shows that these yields were achieved using about 4% less horsepower than that required by the FIG. 3 embodiment. The drop in the power requirements for the FIG. 5 embodiment is mainly due to the lower flow rate of recycle stream **51** compared to that needed with the FIG. 3 embodiment to maintain the same recovery levels. Using compressor **30** in the FIG. 5 embodiment makes it easier to condense combined stream **37** (due to the elevation in pressure), so that a higher flow rate of supplemental reflux stream **37b** can be used and the flow rate of recycle stream **51** reduced accordingly.

[0075] When the present invention is employed as in Example 2 using a compressor to allow increasing the flow rate of the supplemental reflux stream, the advantage with regard to

avoiding carbon dioxide icing conditions is further enhanced compared to the FIG. 3 embodiment. FIG. 6 is another graph of the relation between carbon dioxide concentration and temperature, with line **71** as before representing the equilibrium conditions for solid and liquid carbon dioxide in methane. Line **74** in FIG. 6 represents the conditions for the liquids on the fractionation stages of demethanizer **19** in the present invention as depicted in FIG. 5, and shows a safety factor of 1.64 between the anticipated operating conditions and the icing conditions for the FIG. 5 process. Thus, this embodiment of the present invention could tolerate an increase of 64 percent in the concentration of carbon dioxide without risk of icing. In practice, this improvement in the icing safety factor could be used to advantage by operating the demethanizer at lower pressure (i.e., with colder temperatures on the fractionation stages) to raise the $C_2$+ component recovery levels without encountering icing problems. The shape of line **74** in FIG. 6 is very similar to that of line **73** in FIG. 4 (which is shown for reference in FIG. 6). The primary difference is the significantly lower carbon dioxide concentrations of the liquids on the fractionation stages in the critical upper section of the FIG. 5 demethanizer due to the higher flow rate of upper mid-column feed to the column that is possible with this embodiment.

## Other Embodiments

**[0076]** In accordance with this invention, it is generally advantageous to design the absorbing (rectification) section of the demethanizer to contain multiple theoretical separation stages. However, the benefits of the present invention can be achieved with as few as one theoretical stage, and it is believed that even the equivalent of a fractional theoretical stage may allow achieving these benefits. For instance, all or a part of the expanded substantially

condensed recycle stream **51c** from expansion valve **15**, all or a part of the supplemental reflux (stream **44a** in FIG. 3 or stream **37b** in FIG. 5), and all or a part of the expanded stream **32a** from work expansion machine **17** can be combined (such as in the piping joining the expansion valve to the demethanizer) and if thoroughly intermingled, the vapors and liquids will mix together and separate in accordance with the relative volatilities of the various components of the total combined streams. Such commingling of the three streams shall be considered for the purposes of this invention as constituting an absorbing section.

**[0077]** Some circumstances may favor mixing any remaining vapor portion of combined stream **37a** with the fractionation column overhead (stream **38**), then supplying the mixed stream to heat exchanger **22** to provide cooling of combined stream **37** and recycle stream **51a**. This is shown in FIG. 7, where the mixed stream **50** resulting from combining the reflux separator vapor (stream **43**) with the column overhead (stream **38**) is routed to heat exchanger **22**.

**[0078]** FIG. 8 depicts a fractionation tower constructed in two vessels, a contacting and separating device (or absorber column or rectifier column) **28** and distillation (or stripper) column **19**. In such cases, the overhead vapor (stream **53**) from stripper column **19** is split into two portions. One portion (stream **42**) is combined with stream **35a** and routed to heat exchanger **22** to generate supplemental reflux for absorber column **28**. The remaining portion (stream **54**) flows to the lower section of absorber column **28** to be contacted by expanded substantially condensed recycle stream **51c** and supplemental reflux liquid (stream **44a**). Pump **29** is used to route the liquids (stream **55**) from the bottom of absorber column **28** to the top of stripper column **19** so that the two towers effectively function as one distillation system. The decision whether to construct the fractionation tower as a single vessel (such as demethanizer **19**

in FIGS. 3, 5, and 7) or multiple vessels will depend on a number of factors such as plant size, the distance to fabrication facilities, etc.

[0079] In those circumstances when the fractionation column is constructed as two vessels, it may be desirable to operate absorber column **28** at higher pressure than stripper column **19**, such as the alternative embodiments of the present invention shown in FIGS. 9 and 10. In the FIG. 9 embodiment, compressor **30** provides the motive force to direct the remaining portion (stream **54**) of overhead stream **53** to absorber column **28**. In the FIG. 10 embodiment, compressor **30** is used to elevate the pressure of overhead stream **53** so that reflux separator **23** and pump **24** in the FIG. 9 embodiment are not required. For both embodiments, the liquids from the bottom of absorber column **28** (stream **55**) will be at elevated pressure relative to stripper column **19**, so that a pump is not required to direct these liquids to stripper column **19**. Instead, a suitable expansion device, such as expansion valve **29** in FIGS. 9 and 10, can be used to expand the liquids to the operating pressure of stripper column **19** and the expanded stream **55a** thereafter supplied to the top of stripper column **19**.

[0080] As described in the earlier examples, the combined stream **37** is totally condensed and the resulting condensate used to absorb valuable $C_2$ components, $C_3$ components, and heavier components from the vapors rising through the lower region of absorbing section **19b** of demethanizer **19**. However, the present invention is not limited to this embodiment. It may be advantageous, for instance, to treat only a portion of these vapors in this manner, or to use only a portion of the condensate as an absorbent, in cases where other design considerations indicate portions of the vapors or the condensate should bypass absorbing section **19b** of demethanizer **19**. Some circumstances may favor partial condensation, rather than total condensation, of

combined stream **37** in heat exchanger **22**. Other circumstances may favor that distillation stream **42** be a total vapor side draw from fractionation column **19** rather than a partial vapor side draw. It should also be noted that, depending on the composition of the feed gas stream, it may be advantageous to use external refrigeration to provide some portion of the cooling of combined stream **37** in heat exchanger **22**.

**[0081]** It is generally advantageous to totally condense combined stream **37** in order to minimize the loss of the desired $C_2$+ components in distillation stream **50**. As such, some circumstances may favor the elimination of reflux separator **23** and uncondensed vapor line **43** as shown by the dashed lines in FIGS. 3, 8, and 9.

**[0082]** Feed gas conditions, plant size, available equipment, or other factors may indicate that elimination of work expansion machine **17**, or replacement with an alternate expansion device (such as an expansion valve), is feasible. Although individual stream expansion is depicted in particular expansion devices, alternative expansion means may be employed where appropriate. For example, conditions may warrant work expansion of the substantially condensed recycle stream (stream **51b**).

**[0083]** When the inlet gas is leaner, separator **11** in FIGS. 3, 5, and 7 through 10 may not be needed. Depending on the quantity of heavier hydrocarbons in the feed gas and the feed gas pressure, the cooled feed stream **31a** leaving heat exchanger **10** in FIGS. 3, 5, and 7 through 10 may not contain any liquid (because it is above its dewpoint, or because it is above its cricondenbar), so that separator **11** shown in FIGS. 3, 5, and 7 through 10 is not required. Additionally, even in those cases where separator **11** is required, it may not be advantageous to combine any of the resulting liquid in stream **33** with distillation vapor stream **42**. In such cases,

all of the liquid would be directed to stream **34** and thence to expansion valve **14** and a lower mid-column feed point on demethanizer **19** (FIGS. 3, 5, and 7) or a mid-column feed point on stripping column **19** (FIGS. 8 through 10).

**[0084]** In accordance with this invention, the use of external refrigeration to supplement the cooling available to the inlet gas and/or the recycle gas from other process streams may be employed, particularly in the case of a rich inlet gas. The use and distribution of separator liquids and demethanizer side draw liquids for process heat exchange, and the particular arrangement of heat exchangers for inlet gas cooling must be evaluated for each particular application, as well as the choice of process streams for specific heat exchange services.

**[0085]** It will also be recognized that the relative amount of feed found in each branch of the split liquid feed will depend on several factors, including gas pressure, feed gas composition, the amount of heat which can economically be extracted from the feed, and the quantity of horsepower available. The relative locations of the mid-column feeds may vary depending on inlet composition or other factors such as desired recovery levels and amount of liquid formed during inlet gas cooling. Moreover, two or more of the feed streams, or portions thereof, may be combined depending on the relative temperatures and quantities of individual streams, and the combined stream then fed to a mid-column feed position.

**[0086]** While there have been described what are believed to be preferred embodiments of the invention, those skilled in the art will recognize that other and further modifications may be made thereto, e.g. to adapt the invention to various conditions, types of feed, or other

requirements without departing from the spirit of the present invention as defined by the following claims.

WE CLAIM:

1. In a process for the separation of a gas stream containing methane, $C_2$ components, $C_3$ components, and heavier hydrocarbon components into a volatile residue gas fraction and a relatively less volatile fraction containing a major portion of said $C_2$ components, $C_3$ components, and heavier hydrocarbon components or said $C_3$ components and heavier hydrocarbon components, in which process

(a) said gas stream is cooled under pressure to provide a cooled stream;

(b) said cooled stream is expanded to a lower pressure whereby it is further cooled; and

(c) said further cooled expanded stream is directed into a distillation column and fractionated at said lower pressure whereby the components of said relatively less volatile fraction are recovered;

the improvement wherein said further cooled expanded stream is directed to a first mid-column feed position on said distillation column; and

(1) a vapor distillation stream is withdrawn from a region of said distillation column below said first mid-column feed position and is cooled sufficiently to condense at least a part of it, thereby forming a condensed stream and a residual vapor stream containing any uncondensed vapor remaining after said vapor distillation stream is cooled;

(2) at least a portion of said condensed stream is supplied to said distillation column at a second mid-column feed position above said first mid-column feed position;

(3) an overhead vapor stream is withdrawn from an upper region of said distillation column and is directed into heat exchange relation with at least said vapor distillation stream and heated, thereby to supply at least a portion of the cooling of step (1);

(4) said heated overhead vapor stream is combined with any said residual vapor stream to form a heated combined vapor stream;

(5) said heated combined vapor stream is compressed to higher pressure and thereafter divided into said volatile residue gas fraction and a compressed recycle stream;

(6) said compressed recycle stream is cooled sufficiently to substantially condense it;

(7) said substantially condensed compressed recycle stream is expanded to said lower pressure and supplied to said distillation column at a top feed position; and

(8) the quantities and temperatures of said feed streams to said distillation column are effective to maintain the overhead temperature of said distillation column at a temperature whereby the major portions of the components in said relatively less volatile fraction are recovered.

2. The improvement according to claim 1 wherein said gas stream is cooled sufficiently to partially condense it; and

(1) said partially condensed gas stream is separated thereby to provide a vapor stream and at least one liquid stream;

(2) said vapor stream is expanded to said lower pressure whereby it is further cooled, and thereafter supplied to said distillation column at said first mid-column feed position; and

(3) from 0% to 100% of said at least one liquid stream is expanded to said lower pressure and supplied to said distillation column at a third mid-column feed position;

(4) from 100% to 0% of said at least one liquid stream is expanded to said lower pressure and combined with said vapor distillation stream to form a combined stream;

(5) said combined stream is cooled sufficiently to condense at least a part of it, thereby forming said condensed stream and said residual vapor stream containing any uncondensed vapor remaining after said combined stream is cooled; and

(6) said overhead vapor stream is directed into heat exchange relation with at least said combined stream and heated, thereby to supply at least a portion of the cooling of step (5).

3. In a process for the separation of a gas stream containing methane, $C_2$ components, $C_3$ components, and heavier hydrocarbon components into a volatile residue gas fraction and a relatively less volatile fraction containing a major portion of said $C_2$ components, $C_3$ components, and heavier hydrocarbon components or said $C_3$ components and heavier hydrocarbon components, in which process

(a) said gas stream is cooled under pressure to provide a cooled stream;

(b) said cooled stream is expanded to a lower pressure whereby it is further cooled; and

(c) said further cooled expanded stream is directed into a distillation column and fractionated at said lower pressure whereby the components of said relatively less volatile fraction are recovered;

the improvement wherein said further cooled expanded stream is directed to a first mid-column feed position on said distillation column; and

(1) a vapor distillation stream is withdrawn from a region of said distillation column below said first mid-column feed position and compressed to an intermediate pressure;

(2) said compressed vapor distillation stream is cooled sufficiently to condense at least a part of it, thereby forming a condensed stream;

(3) at least a portion of said condensed stream is supplied to said distillation column at a second mid-column feed position above said first mid-column feed position;

(4) an overhead vapor stream is withdrawn from an upper region of said distillation column and is directed into heat exchange relation with at least said compressed vapor distillation stream and heated, thereby to supply at least a portion of the cooling of step (2);

(5) said heated overhead vapor stream is compressed to higher pressure and thereafter divided into said volatile residue gas fraction and a compressed recycle stream;

(6) said compressed recycle stream is cooled sufficiently to substantially condense it;

(7) said substantially condensed compressed recycle stream is expanded to said lower pressure and supplied to said distillation column at a top feed position; and

(8) the quantities and temperatures of said feed streams to said distillation column are effective to maintain the overhead temperature of said distillation column at a temperature whereby the major portions of the components in said relatively less volatile fraction are recovered.

4. The improvement according to claim 3 wherein said gas stream is cooled sufficiently to partially condense it; and

(1) said partially condensed gas stream is separated thereby to provide a vapor stream and at least one liquid stream;

(2) said vapor stream is expanded to said lower pressure whereby it is further cooled, and thereafter supplied to said distillation column at said first mid-column feed position;

(3) from 0% to 100% of said at least one liquid stream is expanded to said lower pressure and supplied to said distillation column at a third mid-column feed position;

(4) from 100% to 0% of said at least one liquid stream is expanded to said intermediate pressure and combined with said compressed vapor distillation stream to form a combined stream;

(5) said combined stream is cooled sufficiently to condense at least a part of it, thereby forming said condensed stream; and

(6) said overhead vapor stream is directed into heat exchange relation with at least said combined stream and heated, thereby to supply at least a portion of the cooling of step (5).

5. In a process for the separation of a gas stream containing methane, $C_2$ components, $C_3$ components, and heavier hydrocarbon components into a volatile residue gas fraction and a relatively less volatile fraction containing a major portion of said $C_2$ components, $C_3$ components, and heavier hydrocarbon components or said $C_3$ components and heavier hydrocarbon components, in which process

(a) said gas stream is cooled under pressure to provide a cooled stream;

(b) said cooled stream is expanded to a lower pressure whereby it is further cooled; and

(c) said further cooled expanded stream is directed into a distillation column and fractionated at said lower pressure whereby the components of said relatively less volatile fraction are recovered;

the improvement wherein said further cooled expanded stream is directed to a first mid-column feed position on said distillation column; and

(1) a vapor distillation stream is withdrawn from a region of said distillation column below said first mid-column feed position and is cooled sufficiently to condense at least a part of it, thereby forming a condensed stream and a residual vapor stream containing any uncondensed vapor remaining after said vapor distillation stream is cooled;

(2) at least a portion of said condensed stream is supplied to said distillation column at a second mid-column feed position above said first mid-column feed position;

(3) an overhead vapor stream is withdrawn from an upper region of said distillation column and combined with any said residual vapor stream to form a combined vapor stream;

(4) said combined vapor stream is directed into heat exchange relation with at least said vapor distillation stream and heated, thereby to supply at least a portion of the cooling of step (1);

(5) said heated combined vapor stream is compressed to higher pressure and thereafter divided into said volatile residue gas fraction and a compressed recycle stream;

(6) said compressed recycle stream is cooled sufficiently to substantially condense it;

(7) said substantially condensed compressed recycle stream is expanded to said lower pressure and supplied to said distillation column at a top feed position; and

(8) the quantities and temperatures of said feed streams to said distillation column are effective to maintain the overhead temperature of said distillation column at a temperature whereby the major portions of the components in said relatively less volatile fraction are recovered.

6. The improvement according to claim 5 wherein said gas stream is cooled sufficiently to partially condense it; and

(1) said partially condensed gas stream is separated thereby to provide a vapor stream and at least one liquid stream;

(2) said vapor stream is expanded to said lower pressure whereby it is further cooled, and thereafter supplied to said distillation column at said first mid-column feed position;

(3) from 0% to 100% of said at least one liquid stream is expanded to said lower pressure and supplied to said distillation column at a third mid-column feed position;

(4) from 100% to 0% of said at least one liquid stream is expanded to said lower pressure and combined with said vapor distillation stream to form a combined stream;

(5) said combined stream is cooled sufficiently to condense at least a part of it, thereby forming said condensed stream and said residual vapor stream containing any uncondensed vapor remaining after said combined stream is cooled; and

(6) said combined vapor stream is directed into heat exchange relation with at least said combined stream and heated, thereby to supply at least a portion of the cooling of step (5).

7. In a process for the separation of a gas stream containing methane, $C_2$ components, $C_3$ components, and heavier hydrocarbon components into a volatile residue gas fraction and a relatively less volatile fraction containing a major portion of said $C_2$ components, $C_3$ components, and heavier hydrocarbon components or said $C_3$ components and heavier hydrocarbon components, in which process

(a) said gas stream is cooled under pressure to provide a cooled stream;

(b) said cooled stream is expanded to a lower pressure whereby it is further cooled; and

(c) said further cooled expanded stream is directed into a distillation column and fractionated at said lower pressure whereby the components of said relatively less volatile fraction are recovered;

the improvement wherein

(1) said further cooled expanded stream is supplied at a first lower feed position to a contacting and separating device that produces an overhead vapor stream and a bottom liquid stream, whereupon said bottom liquid stream is supplied to said distillation column;

(2) a vapor distillation stream is withdrawn from an upper region of said distillation column to form at least a first distillation stream;

(3) said first distillation stream is cooled sufficiently to condense at least a part of it, thereby forming a condensed stream and a residual vapor stream containing any uncondensed vapor remaining after said first distillation stream is cooled;

(4) at least a portion of said condensed stream is supplied to said contacting and separating device at a mid-column feed position;

(5) said overhead vapor stream is directed into heat exchange relation with at least said first distillation stream and heated, thereby to supply at least a portion of the cooling of step (3);

(6) said heated overhead vapor stream is combined with any said residual vapor stream to form a heated combined vapor stream;

(7) said heated combined vapor stream is compressed to higher pressure and thereafter divided into said volatile residue gas fraction and a compressed recycle stream;

(8) said compressed recycle stream is cooled sufficiently to substantially condense it;

(9) said substantially condensed compressed recycle stream is expanded to said lower pressure and supplied to said contacting and separating device at a top feed position;

(10) any remaining portion of said vapor distillation stream is directed to said contacting and separating device at a second lower feed position; and

(11) the quantities and temperatures of said feed streams to said contacting and separating device are effective to maintain the overhead temperature of said contacting and separating device at a temperature whereby the major portions of the components in said relatively less volatile fraction are recovered.

8. The improvement according to claim 7 wherein said gas stream is cooled sufficiently to partially condense it; and

(1) said partially condensed gas stream is separated thereby to provide a vapor stream and at least one liquid stream;

(2) said vapor stream is expanded to said lower pressure whereby it is further cooled, and thereafter supplied to said contacting and separating device at said first lower column feed position;

(3) from 0% to 100% of said at least one liquid stream is expanded to said lower pressure and supplied to said distillation column at a mid-column feed position;

(4) from 100% to 0% of said at least one liquid stream is expanded to said lower pressure and combined with said first distillation stream to form a combined stream;

(5) said combined stream is cooled sufficiently to condense at least a part of it, thereby forming said condensed stream and said residual vapor stream containing any uncondensed vapor remaining after said combined stream is cooled; and

(6) said overhead vapor stream is directed into heat exchange relation with at least said combined stream and heated, thereby to supply at least a portion of the cooling of step (5).

9. In a process for the separation of a gas stream containing methane, $C_2$ components, $C_3$ components, and heavier hydrocarbon components into a volatile residue gas fraction and a relatively less volatile fraction containing a major portion of said $C_2$ components, $C_3$ components, and heavier hydrocarbon components or said $C_3$ components and heavier hydrocarbon components, in which process

(a) said gas stream is cooled under pressure to provide a cooled stream;

(b) said cooled stream is expanded to a lower pressure whereby it is further cooled; and

(c) said further cooled expanded stream is directed into a distillation column and fractionated at said lower pressure whereby the components of said relatively less volatile fraction are recovered;

the improvement wherein said cooled stream is expanded to an intermediate pressure whereby it is further cooled; and

(1) said further cooled expanded stream is supplied at a first lower feed position to a contacting and separating device that produces an overhead vapor stream and a bottom liquid stream, whereupon said bottom liquid stream is expanded to said lower pressure and thereafter supplied to said distillation column;

(2) a vapor distillation stream is withdrawn from an upper region of said distillation column to form at least a first distillation stream;

(3) said first distillation stream is cooled sufficiently to condense at least a part of it, thereby forming a condensed stream and a residual vapor stream containing any uncondensed vapor remaining after said first distillation stream is cooled;

(4) at least a portion of said condensed stream is supplied to said contacting and separating device at a mid-column feed position;

(5) said overhead vapor stream is directed into heat exchange relation with at least said first distillation stream and heated, thereby to supply at least a portion of the cooling of step (3);

(6) said heated overhead vapor stream is combined with any said residual vapor stream to form a heated combined vapor stream;

(7) said heated combined vapor stream is compressed to higher pressure and thereafter divided into said volatile residue gas fraction and a compressed recycle stream;

(8) said compressed recycle stream is cooled sufficiently to substantially condense it;

(9) said substantially condensed compressed recycle stream is expanded to said intermediate pressure and supplied to said contacting and separating device at a top feed position;

(10) any remaining portion of said vapor distillation stream is compressed to said intermediate pressure and thereafter directed to said contacting and separating device at a second lower feed position; and

(11) the quantities and temperatures of said feed streams to said contacting and separating device are effective to maintain the overhead temperature of said contacting and separating device at a temperature whereby the major portions of the components in said relatively less volatile fraction are recovered.

10. The improvement according to claim 9 wherein said gas stream is cooled sufficiently to partially condense it; and

(1) said partially condensed gas stream is separated thereby to provide a vapor stream and at least one liquid stream;

(2) said vapor stream is expanded to said intermediate pressure whereby it is further cooled, and thereafter supplied to said contacting and separating device at said first lower column feed position;

(3) from 0% to 100% of said at least one liquid stream is expanded to said lower pressure and supplied to said distillation column at a mid-column feed position;

(4) from 100% to 0% of said at least one liquid stream is expanded to said lower pressure and combined with said first distillation stream to form a combined stream;

(5) said combined stream is cooled sufficiently to condense at least a part of it, thereby forming said condensed stream and said residual vapor stream containing any uncondensed vapor remaining after said combined stream is cooled; and

(6) said overhead vapor stream is directed into heat exchange relation with at least said combined stream and heated, thereby to supply at least a portion of the cooling of step (5).

11. In a process for the separation of a gas stream containing methane, $C_2$ components, $C_3$ components, and heavier hydrocarbon components into a volatile residue gas fraction and a relatively less volatile fraction containing a major portion of said $C_2$ components, $C_3$ components, and heavier hydrocarbon components or said $C_3$ components and heavier hydrocarbon components, in which process

(a) said gas stream is cooled under pressure to provide a cooled stream;

(b) said cooled stream is expanded to a lower pressure whereby it is further cooled; and

(c) said further cooled expanded stream is directed into a distillation column and fractionated at said lower pressure whereby the components of said relatively less volatile fraction are recovered;

the improvement wherein said cooled stream is expanded to an intermediate pressure whereby it is further cooled; and

(1) said further cooled expanded stream is supplied at a first lower feed position to a contacting and separating device that produces an overhead vapor stream and a

bottom liquid stream, whereupon said bottom liquid stream is expanded to said lower pressure and thereafter supplied to said distillation column;

(2) a vapor distillation stream is withdrawn from an upper region of said distillation column, compressed to said intermediate pressure, and divided to form a first compressed distillation stream and a second compressed distillation stream;

(3) said first compressed distillation stream is cooled sufficiently to condense at least a part of it, thereby forming a condensed stream;

(4) at least a portion of said condensed stream is supplied to said contacting and separating device at a mid-column feed position;

(5) said overhead vapor stream is directed into heat exchange relation with at least said first compressed distillation stream and heated, thereby to supply at least a portion of the cooling of step (3);

(6) said heated overhead vapor stream is compressed to higher pressure and thereafter divided into said volatile residue gas fraction and a compressed recycle stream;

(7) said compressed recycle stream is cooled sufficiently to substantially condense it;

(8) said substantially condensed compressed recycle stream is expanded to said intermediate pressure and supplied to said contacting and separating device at a top feed position;

(9) said second compressed vapor distillation stream is directed to said contacting and separating device at a second lower feed position; and

(10) the quantities and temperatures of said feed streams to said contacting and separating device are effective to maintain the overhead temperature of said contacting and separating device at a temperature whereby the major portions of the components in said relatively less volatile fraction are recovered.

12. The improvement according to claim 11 wherein said gas stream is cooled sufficiently to partially condense it; and

(1) said partially condensed gas stream is separated thereby to provide a vapor stream and at least one liquid stream;

(2) said vapor stream is expanded to said intermediate pressure whereby it is further cooled, and thereafter supplied to said contacting and separating device at said first lower column feed position;

(3) from 0% to 100% of said at least one liquid stream is expanded to said lower pressure and supplied to said distillation column at a mid-column feed position;

(4) from 100% to 0% of said at least one liquid stream is expanded to said intermediate pressure and combined with said first compressed distillation stream to form a combined stream;

(5) said combined stream is cooled sufficiently to condense at least a part of it, thereby forming said condensed stream; and

(6) said overhead vapor stream is directed into heat exchange relation with at least said combined stream and heated, thereby to supply at least a portion of the cooling of step (5).

13. In an apparatus for the separation of a gas stream containing methane, $C_2$ components, $C_3$ components, and heavier hydrocarbon components into a volatile residue gas fraction and a relatively less volatile fraction containing a major portion of said $C_2$ components, $C_3$ components, and heavier hydrocarbon components or said $C_3$ components and heavier hydrocarbon components, in said apparatus there being

(a) a first cooling means to cool said gas under pressure connected to provide a cooled stream under pressure;

(b) a first expansion means connected to receive at least a portion of said cooled stream under pressure and expand it to a lower pressure, whereby said stream is further cooled; and

(c) a distillation column connected to receive said further cooled expanded stream, said distillation column being adapted to separate said further cooled expanded stream into an overhead vapor stream and said relatively less volatile fraction;

the improvement wherein said apparatus includes

(1) said distillation column connected to said first expansion means to receive said further cooled expanded stream at a first mid-column feed position on said distillation column;

(2) vapor withdrawing means connected to said distillation column to receive a vapor distillation stream from a region of said distillation column below said first mid-column feed position;

(3) heat exchange means connected to said vapor withdrawing means to receive said vapor distillation stream and cool it sufficiently to condense at least a part of it;

(4) first separating means connected to said heat exchange means to receive said at least partially condensed distillation stream and separate it, thereby forming a condensed stream and a residual vapor stream containing any uncondensed vapor remaining after said vapor distillation stream is cooled, said first separating means being further connected to said distillation column to supply at least a portion of said condensed stream to said distillation column at a second mid-column feed position above said first mid-column feed position;

(5) said distillation column being further connected to said heat exchange means to direct at least a portion of said overhead vapor stream separated therein into heat exchange relation with at least said vapor distillation stream and heat said overhead vapor stream, thereby to supply at least a portion of the cooling of element (3);

(6) first combining means connected to combine said heated overhead vapor stream and any said residual vapor stream into a heated combined vapor stream;

(7) compressing means connected to said first combining means to receive said heated combined vapor stream and compress it to higher pressure;

(8) dividing means connected to said compressing means to receive said compressed heated combined vapor stream and divide it into said volatile residue gas fraction and a compressed recycle stream;

(9) second cooling means connected to said dividing means to receive said compressed recycle stream and cool it sufficiently to substantially condense it;

(10) second expansion means connected to said second cooling means to receive said substantially condensed compressed recycle stream and expand it to said lower pressure, said second expansion means being further connected to said distillation column to

supply said expanded condensed recycle stream to said distillation column at a top feed position; and

(11) control means adapted to regulate the quantities and temperatures of said feed streams to said distillation column to maintain the overhead temperature of said distillation column at a temperature whereby the major portions of the components in said relatively less volatile fraction are recovered.

14. The improvement according to claim 13 wherein said apparatus includes

(1) said first cooling means being adapted to cool said gas stream under pressure sufficiently to partially condense it;

(2) second separating means connected to said first cooling means to receive said partially condensed gas stream and separate it into a vapor stream and at least one liquid stream;

(3) said first expansion means connected to said second separating means to receive said vapor stream and expand it to said lower pressure, said first expansion means being further connected to said distillation column to supply said expanded vapor stream to said distillation column at said first mid-column feed position;

(4) third expansion means connected to said second separating means to receive from 0% to 100% of said at least one liquid stream and expand it to said lower pressure, said third expansion means being further connected to said distillation column to supply said expanded liquid stream to said distillation column at a third mid-column feed position;

(5) fourth expansion means connected to said second separating means to receive from 100% to 0% of said at least one liquid stream and expand it to said lower pressure;

(6) second combining means connected to said fourth expansion means to receive said expanded portion, said second combining means being further connected to said vapor withdrawing means to receive said vapor distillation stream and thereby combine said streams to form a combined stream;

(7) said heat exchange means connected to said second combining means to receive said combined stream and cool it sufficiently to condense at least a part of it, said heat exchange means being further connected to supply said at least partially condensed combined stream to said first separating means; and

(8) said heat exchange means being further connected to said distillation column to direct at least a portion of said overhead vapor stream separated therein into heat exchange relation with at least said combined stream and heat said overhead vapor stream, thereby to supply at least a portion of the cooling of element (7).

15. In an apparatus for the separation of a gas stream containing methane, $C_2$ components, $C_3$ components, and heavier hydrocarbon components into a volatile residue gas fraction and a relatively less volatile fraction containing a major portion of said $C_2$ components, $C_3$ components, and heavier hydrocarbon components or said $C_3$ components and heavier hydrocarbon components, in said apparatus there being

(a) a first cooling means to cool said gas under pressure connected to provide a cooled stream under pressure;

(b) a first expansion means connected to receive at least a portion of said cooled stream under pressure and expand it to a lower pressure, whereby said stream is further cooled; and

(c) a distillation column connected to receive said further cooled expanded stream, said distillation column being adapted to separate said further cooled expanded stream into an overhead vapor stream and said relatively less volatile fraction;

the improvement wherein said apparatus includes

(1) said distillation column connected to said first expansion means to receive said further cooled expanded stream at a first mid-column feed position on said distillation column;

(2) vapor withdrawing means connected to said distillation column to receive a vapor distillation stream from a region of said distillation column below said first mid-column feed position;

(3) first compressing means connected to said vapor withdrawing means to receive said vapor distillation stream and compress it to intermediate pressure;

(4) heat exchange means connected to said first compressing means to receive said compressed vapor distillation stream and cool it sufficiently to condense at least a part of it, thereby forming a condensed stream, said heat exchange means being further connected to said distillation column to supply at least a portion of said condensed stream to said distillation column at a second mid-column feed position above said first mid-column feed position;

(5) said distillation column being further connected to said heat exchange means to direct at least a portion of said overhead vapor stream separated therein into heat exchange relation with at least said compressed vapor distillation stream and heat said overhead vapor stream, thereby to supply at least a portion of the cooling of element (4);

(6) second compressing means connected to said heat exchange means to receive said heated overhead vapor stream and compress it to higher pressure;

(7) dividing means connected to said second compressing means to receive said compressed heated overhead vapor stream and divide it into said volatile residue gas fraction and a compressed recycle stream;

(8) second cooling means connected to said dividing means to receive said compressed recycle stream and cool it sufficiently to substantially condense it;

(9) second expansion means connected to said second cooling means to receive said substantially condensed compressed recycle stream and expand it to said lower pressure, said second expansion means being further connected to said distillation column to supply said expanded condensed recycle stream to said distillation column at a top feed position; and

(10) control means adapted to regulate the quantities and temperatures of said feed streams to said distillation column to maintain the overhead temperature of said distillation column at a temperature whereby the major portions of the components in said relatively less volatile fraction are recovered.

16. The improvement according to claim 15 wherein said apparatus includes

(1) said first cooling means being adapted to cool said gas stream under pressure sufficiently to partially condense it;

(2) separating means connected to said first cooling means to receive said partially condensed gas stream and separate it into a vapor stream and at least one liquid stream;

(3) said first expansion means connected to said separating means to receive said vapor stream and expand it to said lower pressure, said first expansion means being further connected to said distillation column to supply said expanded vapor stream to said distillation column at said first mid-column feed position;

(4) third expansion means connected to said separating means to receive from 0% to 100% of said at least one liquid stream and expand it to said lower pressure, said third expansion means being further connected to said distillation column to supply said expanded liquid stream to said distillation column at a third mid-column feed position;

(5) fourth expansion means connected to said separating means to receive from 100% to 0% of said at least one liquid stream and expand it to said intermediate pressure;

(6) combining means connected to said fourth expansion means to receive said expanded portion, said combining means being further connected to said first compressing means to receive said compressed vapor distillation stream and thereby combine said streams to form a combined stream;

(7) said heat exchange means connected to said combining means to receive said combined stream and cool it sufficiently to condense at least a part of it, thereby forming a condensed stream, said heat exchange means being further connected to said distillation column to supply at least a portion of said condensed stream to said distillation column at said second mid-column feed position above said first mid-column feed position; and

(8) said heat exchange means being further connected to said distillation column to direct at least a portion of said overhead vapor stream separated therein into heat

exchange relation with at least said combined stream and heat said overhead vapor stream, thereby to supply at least a portion of the cooling of element (7).

17. In an apparatus for the separation of a gas stream containing methane, $C_2$ components, $C_3$ components, and heavier hydrocarbon components into a volatile residue gas fraction and a relatively less volatile fraction containing a major portion of said $C_2$ components, $C_3$ components, and heavier hydrocarbon components or said $C_3$ components and heavier hydrocarbon components, in said apparatus there being

(a) a first cooling means to cool said gas under pressure connected to provide a cooled stream under pressure;

(b) a first expansion means connected to receive at least a portion of said cooled stream under pressure and expand it to a lower pressure, whereby said stream is further cooled; and

(c) a distillation column connected to receive said further cooled expanded stream, said distillation column being adapted to separate said further cooled expanded stream into an overhead vapor stream and said relatively less volatile fraction;

the improvement wherein said apparatus includes

(1) said distillation column connected to said first expansion means to receive said further cooled expanded stream at a first mid-column feed position on said distillation column;

(2) vapor withdrawing means connected to said distillation column to receive a vapor distillation stream from a region of said distillation column below said first mid-column feed position;

(3) heat exchange means connected to said vapor withdrawing means to receive said vapor distillation stream and cool it sufficiently to condense at least a part of it;

(4) first separating means connected to said heat exchange means to receive said at least partially condensed distillation stream and separate it, thereby forming a condensed stream and a residual vapor stream containing any uncondensed vapor remaining after said vapor distillation stream is cooled, said first separating means being further connected to said distillation column to supply at least a portion of said condensed stream to said distillation column at a second mid-column feed position above said first mid-column feed position;

(5) first combining means connected to combine said overhead vapor stream and any said residual vapor stream into a combined vapor stream;

(6) said first combining means being further connected to said heat exchange means to direct at least a portion of said combined vapor stream into heat exchange relation with at least said vapor distillation stream and heat said combined vapor stream, thereby to supply at least a portion of the cooling of element (3);

(7) compressing means connected to said heat exchange means to receive said heated combined vapor stream and compress it to higher pressure;

(8) dividing means connected to said compressing means to receive said compressed heated combined vapor stream and divide it into said volatile residue gas fraction and a compressed recycle stream;

(9) second cooling means connected to said dividing means to receive said compressed recycle stream and cool it sufficiently to substantially condense it;

(10) second expansion means connected to said second cooling means to receive said substantially condensed compressed recycle stream and expand it to said lower pressure, said second expansion means being further connected to said distillation column to supply said expanded condensed recycle stream to said distillation column at a top feed position; and

(11) control means adapted to regulate the quantities and temperatures of said feed streams to said distillation column to maintain the overhead temperature of said distillation column at a temperature whereby the major portions of the components in said relatively less volatile fraction are recovered.

18. The improvement according to claim 17 wherein said apparatus includes

(1) said first cooling means being adapted to cool said gas stream under pressure sufficiently to partially condense it;

(2) second separating means connected to said first cooling means to receive said partially condensed gas stream and separate it into a vapor stream and at least one liquid stream;

(3) said first expansion means connected to said second separating means to receive said vapor stream and expand it to said lower pressure, said first expansion means being further connected to said distillation column to supply said expanded vapor stream to said distillation column at said first mid-column feed position;

(4) third expansion means connected to said second separating means to receive from 0% to 100% of said at least one liquid stream and expand it to said lower pressure,

said third expansion means being further connected to said distillation column to supply said expanded liquid stream to said distillation column at a third mid-column feed position;

(5) fourth expansion means connected to said second separating means to receive from 100% to 0% of said at least one liquid stream and expand it to said lower pressure;

(6) second combining means connected to said fourth expansion means to receive said expanded portion, said second combining means being further connected to said vapor withdrawing means to receive said vapor distillation stream and thereby combine said streams to form a combined stream;

(7) said heat exchange means connected to said second combining means to receive said combined stream and cool it sufficiently to condense at least a part of it, said heat exchange means being further connected to supply said at least partially condensed combined stream to said first separating means; and

(8) said heat exchange means being further connected to said distillation column to direct at least a portion of said overhead vapor stream separated therein into heat exchange relation with at least said combined stream and heat said overhead vapor stream, thereby to supply at least a portion of the cooling of element (7).

19. In an apparatus for the separation of a gas stream containing methane, $C_2$ components, $C_3$ components, and heavier hydrocarbon components into a volatile residue gas fraction and a relatively less volatile fraction containing a major portion of said $C_2$ components, $C_3$ components, and heavier hydrocarbon components or said $C_3$ components and heavier hydrocarbon components, in said apparatus there being

(a) a first cooling means to cool said gas under pressure connected to provide a cooled stream under pressure;

(b) a first expansion means connected to receive at least a portion of said cooled stream under pressure and expand it to a lower pressure, whereby said stream is further cooled; and

(c) a distillation column connected to receive said further cooled expanded stream, said distillation column being adapted to separate said further cooled expanded stream into an overhead vapor stream and said relatively less volatile fraction;

the improvement wherein said apparatus includes

(1) contacting and separating means connected to said first expansion means to receive said further cooled expanded stream at a first lower column feed position on said contacting and separating means, said contacting and separating means being adapted to produce an overhead vapor stream and a bottom liquid stream;

(2) said contacting and separating means further connected to said distillation column to supply said bottom liquid stream to said distillation column;

(3) vapor withdrawing means connected to said distillation column to receive a vapor distillation stream from an upper region of said distillation column to form at least a first distillation stream;

(4) heat exchange means connected to said vapor withdrawing means to receive said first distillation stream and cool it sufficiently to condense at least a part of it;

(5) first separating means connected to said heat exchange means to receive said at least partially condensed first distillation stream and separate it, thereby forming a

condensed stream and a residual vapor stream containing any uncondensed vapor remaining after said vapor distillation stream is cooled, said first separating means being further connected to said contacting and separating means to supply at least a portion of said condensed stream to said contacting and separating means at a mid-column feed position;

(6) said contacting and separating means being further connected to said heat exchange means to direct at least a portion of said overhead vapor stream separated therein into heat exchange relation with at least said first distillation stream and heat said overhead vapor stream, thereby to supply at least a portion of the cooling of element (4);

(7) first combining means connected to combine said heated overhead vapor stream and any said residual vapor stream into a heated combined vapor stream;

(8) compressing means connected to said first combining means to receive said heated combined vapor stream and compress it to higher pressure;

(9) dividing means connected to said compressing means to receive said compressed heated combined vapor stream and divide it into said volatile residue gas fraction and a compressed recycle stream;

(10) second cooling means connected to said dividing means to receive said compressed recycle stream and cool it sufficiently to substantially condense it;

(11) second expansion means connected to said second cooling means to receive said substantially condensed compressed recycle stream and expand it to said lower pressure, said second expansion means being further connected to said contacting and separating means to supply said expanded condensed recycle stream to said contacting and separating means at a top feed position;

(12) said contacting and separating means being further connected to said vapor withdrawing means to receive any remaining portion of said vapor distillation stream at a second lower column feed position; and

(13) control means adapted to regulate the quantities and temperatures of said feed streams to said contacting and separating means to maintain the overhead temperature of said contacting and separating means at a temperature whereby the major portions of the components in said relatively less volatile fraction are recovered.

20. The improvement according to claim 19 wherein said apparatus includes

(1) said first cooling means being adapted to cool said gas stream under pressure sufficiently to partially condense it;

(2) second separating means connected to said first cooling means to receive said partially condensed gas stream and separate it into a vapor stream and at least one liquid stream;

(3) said first expansion means connected to said second separating means to receive said vapor stream and expand it to said lower pressure, said first expansion means being further connected to said contacting and separating means to supply said expanded vapor stream to said contacting and separating means at said first lower column feed position;

(4) third expansion means connected to said second separating means to receive from 0% to 100% of said at least one liquid stream and expand it to said lower pressure, said third expansion means being further connected to said distillation column to supply said expanded liquid stream to said distillation column at a mid-column feed position;

(5) fourth expansion means connected to said second separating means to receive from 100% to 0% of said at least one liquid stream and expand it to said lower pressure;

(6) second combining means connected to said fourth expansion means to receive said expanded portion, said second combining means being further connected to said vapor withdrawing means to receive said first distillation stream and thereby combine said streams to form a combined stream;

(7) said heat exchange means connected to said second combining means to receive said combined stream and cool it sufficiently to condense at least a part of it, said heat exchange means being further connected to supply said at least partially condensed combined stream to said first separating means; and

(8) said heat exchange means being further connected to said contacting and separating means to direct at least a portion of said overhead vapor stream separated therein into heat exchange relation with at least said combined stream and heat said overhead vapor stream, thereby to supply at least a portion of the cooling of element (7).

21. In an apparatus for the separation of a gas stream containing methane, $C_2$ components, $C_3$ components, and heavier hydrocarbon components into a volatile residue gas fraction and a relatively less volatile fraction containing a major portion of said $C_2$ components, $C_3$ components, and heavier hydrocarbon components or said $C_3$ components and heavier hydrocarbon components, in said apparatus there being

(a) a first cooling means to cool said gas under pressure connected to provide a cooled stream under pressure;

(b) a first expansion means connected to receive at least a portion of said cooled stream under pressure and expand it to a lower pressure, whereby said stream is further cooled; and

(c) a distillation column connected to receive said further cooled expanded stream, said distillation column being adapted to separate said further cooled expanded stream into an overhead vapor stream and said relatively less volatile fraction;

the improvement wherein said apparatus includes

(1) said first expansion means being adapted to expand said at least a portion of said cooled stream to an intermediate pressure whereby said stream is further cooled;

(2) contacting and separating means connected to said first expansion means to receive said further cooled expanded stream at a first lower column feed position on said contacting and separating means, said contacting and separating means being adapted to produce an overhead vapor stream and a bottom liquid stream;

(3) second expansion means connected to said contacting and separating means to receive said bottom liquid stream and expand it to said lower pressure;

(4) said second expansion means further connected to said distillation column to supply said expanded bottom liquid stream to said distillation column;

(5) vapor withdrawing means connected to said distillation column to receive a vapor distillation stream from an upper region of said distillation column to form at least a first distillation stream;

(6) heat exchange means connected to said vapor withdrawing means to receive said first distillation stream and cool it sufficiently to condense at least a part of it;

(7) first separating means connected to said heat exchange means to receive said at least partially condensed first distillation stream and separate it, thereby forming a condensed stream and a residual vapor stream containing any uncondensed vapor remaining after said first distillation stream is cooled, said first separating means being further connected to said contacting and separating means to supply at least a portion of said condensed stream to said contacting and separating means at a mid-column feed position;

(8) said contacting and separating means being further connected to said heat exchange means to direct at least a portion of said overhead vapor stream separated therein into heat exchange relation with at least said first distillation stream and heat said overhead vapor stream, thereby to supply at least a portion of the cooling of element (6);

(9) first combining means connected to combine said heated overhead vapor stream and any said residual vapor stream into a heated combined vapor stream;

(10) first compressing means connected to said first combining means to receive said heated combined vapor stream and compress it to higher pressure;

(11) dividing means connected to said first compressing means to receive said compressed heated combined vapor stream and divide it into said volatile residue gas fraction and a compressed recycle stream;

(12) second cooling means connected to said dividing means to receive said compressed recycle stream and cool it sufficiently to substantially condense it;

(13) third expansion means connected to said second cooling means to receive said substantially condensed compressed recycle stream and expand it to said intermediate pressure, said third expansion means being further connected to said contacting and

separating means to supply said expanded condensed recycle stream to said contacting and separating means at a top feed position;

(14) second compressing means connected to said vapor withdrawing means to receive any remaining portion of said vapor distillation stream and compress it to said intermediate pressure;

(15) said contacting and separating means being further connected to said second compressing means to receive said compressed any remaining portion of said vapor distillation stream at a second lower column feed position; and

(16) control means adapted to regulate the quantities and temperatures of said feed streams to said contacting and separating means to maintain the overhead temperature of said contacting and separating means at a temperature whereby the major portions of the components in said relatively less volatile fraction are recovered.

22. The improvement according to claim 21 wherein said apparatus includes

(1) said first cooling means being adapted to cool said gas stream under pressure sufficiently to partially condense it;

(2) second separating means connected to said first cooling means to receive said partially condensed gas stream and separate it into a vapor stream and at least one liquid stream;

(3) said first expansion means connected to said second separating means to receive said vapor stream and expand it to said intermediate pressure, said first expansion means being further connected to said contacting and separating means to supply said expanded vapor stream to said contacting and separating means at said first lower column feed position;

(4) fourth expansion means connected to said second separating means to receive from 0% to 100% of said at least one liquid stream and expand it to said lower pressure, said fourth expansion means being further connected to said distillation column to supply said expanded liquid stream to said distillation column at a mid-column feed position;

(5) fifth expansion means connected to said second separating means to receive from 100% to 0% of said at least one liquid stream and expand it to said lower pressure;

(6) second combining means connected to said fifth expansion means to receive said expanded portion, said second combining means being further connected to said vapor withdrawing means to receive said first distillation stream and thereby combine said streams to form a combined stream;

(7) said heat exchange means connected to said second combining means to receive said combined stream and cool it sufficiently to condense at least a part of it, said heat exchange means being further connected to supply said at least partially condensed combined stream to said first separating means; and

(8) said heat exchange means being further connected to said contacting and separating means to direct at least a portion of said overhead vapor stream separated therein into heat exchange relation with at least said combined stream and heat said overhead vapor stream, thereby to supply at least a portion of the cooling of element (7).

23. In an apparatus for the separation of a gas stream containing methane, $C_2$ components, $C_3$ components, and heavier hydrocarbon components into a volatile residue gas fraction and a relatively less volatile fraction containing a major portion of said $C_2$ components,

$C_3$ components, and heavier hydrocarbon components or said $C_3$ components and heavier hydrocarbon components, in said apparatus there being

(a) a first cooling means to cool said gas under pressure connected to provide a cooled stream under pressure;

(b) a first expansion means connected to receive at least a portion of said cooled stream under pressure and expand it to a lower pressure, whereby said stream is further cooled; and

(c) a distillation column connected to receive said further cooled expanded stream, said distillation column being adapted to separate said further cooled expanded stream into an overhead vapor stream and said relatively less volatile fraction;

the improvement wherein said apparatus includes

(1) said first expansion means being adapted to expand said at least a portion of said cooled stream to an intermediate pressure whereby said stream is further cooled;

(2) contacting and separating means connected to said first expansion means to receive said further cooled expanded stream at a first lower column feed position on said contacting and separating means, said contacting and separating means being adapted to produce an overhead vapor stream and a bottom liquid stream;

(3) second expansion means connected to said contacting and separating means to receive said bottom liquid stream and expand it to said lower pressure;

(4) said second expansion means further connected to said distillation column to supply said expanded bottom liquid stream to said distillation column;

(5) vapor withdrawing means connected to said distillation column to receive a vapor distillation stream from an upper region of said distillation column;

(6) first compressing means connected to said vapor withdrawing means to receive said vapor distillation stream and compress it to said intermediate pressure, thereby forming a compressed distillation stream;

(7) first dividing means connected to said first compressing means to receive said compressed distillation stream and divide it into a first compressed distillation stream and a second compressed distillation stream;

(8) heat exchange means connected to said first dividing means to receive said first compressed distillation stream and cool it sufficiently to condense at least a part of it, thereby forming a condensed stream, said heat exchange means being further connected to said contacting and separating means to supply at least a portion of said condensed stream to said contacting and separating means at a mid-column feed position;

(9) said contacting and separating means being further connected to said heat exchange means to direct at least a portion of said overhead vapor stream separated therein into heat exchange relation with at least said first compressed distillation stream and heat said overhead vapor stream, thereby to supply at least a portion of the cooling of element (8);

(10) second compressing means connected to said heat exchange means to receive said heated overhead vapor stream and compress it to higher pressure;

(11) second dividing means connected to said second compressing means to receive said compressed heated overhead vapor stream and divide it into said volatile residue gas fraction and a compressed recycle stream;

(12) second cooling means connected to said dividing means to receive said compressed recycle stream and cool it sufficiently to substantially condense it;

(13) third expansion means connected to said second cooling means to receive said substantially condensed compressed recycle stream and expand it to said intermediate pressure, said third expansion means being further connected to said contacting and separating means to supply said expanded condensed recycle stream to said contacting and separating means at a top feed position;

(14) said contacting and separating means being further connected to said first dividing means to receive said second compressed vapor distillation stream at a second lower column feed position; and

(15) control means adapted to regulate the quantities and temperatures of said feed streams to said contacting and separating means to maintain the overhead temperature of said contacting and separating means at a temperature whereby the major portions of the components in said relatively less volatile fraction are recovered.

24. The improvement according to claim 23 wherein said apparatus includes

(1) said first cooling means being adapted to cool said gas stream under pressure sufficiently to partially condense it;

(2) separating means connected to said first cooling means to receive said partially condensed gas stream and separate it into a vapor stream and at least one liquid stream;

(3) said first expansion means connected to said separating means to receive said vapor stream and expand it to said intermediate pressure, said first expansion means

being further connected to said contacting and separating means to supply said expanded vapor stream to said contacting and separating means at said first lower column feed position;

(4) fourth expansion means connected to said separating means to receive from 0% to 100% of said at least one liquid stream and expand it to said lower pressure, said fourth expansion means being further connected to said distillation column to supply said expanded liquid stream to said distillation column at a mid-column feed position;

(5) fifth expansion means connected to said separating means to receive from 100% to 0% of said at least one liquid stream and expand it to said intermediate pressure;

(6) combining means connected to said fifth expansion means to receive said expanded portion, said combining means being further connected to said first compressing means to receive said first compressed distillation stream and thereby combine said streams to form a combined stream;

(7) said heat exchange means connected to said combining means to receive said combined stream and cool it sufficiently to condense at least a part of it, thereby forming a condensed stream, said heat exchange means being further connected to said contacting and separating means to supply at least a portion of said condensed stream to said contacting and separating means at said mid-column feed position; and

(8) said heat exchange means being further connected to said contacting and separating means to direct at least a portion of said overhead vapor stream separated therein into heat exchange relation with at least said combined stream and heat said overhead vapor stream, thereby to supply at least a portion of the cooling of element (7).