

9904836-0

1P0S

This Sheet Has Been Replaced

Attorney Docket No. 36856.218

COMPOSITE INDUCTOR ELEMENT

BACKGROUND OF THE INVENTION1. Field of the Invention

The present invention relates to a composite inductor element. More particularly, ~~this the present~~ invention relates to a composite inductor element ~~to be used~~ constructed to function as an anti-noise ~~part component~~ in personal computers and ~~so on~~ other electronic apparatuses.

2. Description of the Related Art

In recent years, software in personal computers has become more and more complicated and advanced. In order to perform instructions contained in such software at high speed, the clock frequency of CPUs ~~mounted~~ in personal computers has greatly increased.

Personal computers have a plurality of types of power supply circuits such as power circuits to drive CPUs, power circuits to drive ~~other~~ circuits other than the CPUs, power circuits to drive hard disks, floppy disks and the like, and so on. Among these power circuits, although there are ~~some~~ supplying currents as large as tens of amperes, as in the power circuits for driving CPUs having high clock frequencies, there are also ~~some others~~ other supplying currents as small as hundreds of milliamperes. ~~And in~~ In each of these power circuits, an anti-noise ~~part component~~ having a current capacity corresponding to each ~~of the~~ supply current is separately

9904836-5

24 SEP 1999

THIS SHEET HAS BEEN
REPLACED

required. Up to now, ~~as an anti noise part of this kind~~ a single element having a current capacity corresponding to the current capacity of each of the power circuits has been used as an anti-noise component.

However, when the above single elements are used in the power circuits of personal computers to function as an anti-noise part, component, many different types of anti-noise parts of many types components are required. Accordingly, there is a problem that the cost of anti-noise ~~parts increases~~ components is greatly increased and the space occupied by the anti-noise ~~parts~~ components also increases.

This Sheet Has Been Replaced



SUMMARY OF THE INVENTION

~~Accordingly, it is an object To overcome the problems described above, preferred embodiments~~ of the present invention to provide a composite inductor element which ~~allows the cost of anti noise parts to be reduced and the space occupied to be decreased, has~~ a significantly reduced cost and greatly reduced space requirement as compared to conventional anti-noise components.

~~In order to attain the above object, in According to a preferred embodiment of the present invention,~~ a composite inductor element ~~according to the present invention includes~~ a plurality of coils are buried in a block ~~part~~ made up of at least either resin or rubber having magnetic material dispersed therein and the end portions of each of the coils are electrically connected to external electrodes provided on the block ~~part~~. The coils have different



electrical characteristics. ~~Here, the electrical characteristics~~
mean such as current capacity, inductance, and ~~se on other~~
characteristics.

Therefore, in the block part, coils constructed in accordance
with the noise and current capacity specifications of power circuits
in personal computers, and ~~se on other apparatuses~~, are buried.
In this way, a plurality of conventional anti-noise ~~parts can be~~
components are realized as single-type units.

Further, in a composite inductor element according to a
preferred embodiment of the present invention, a plurality of
electromagnetically close-coupled coils ~~of defined by~~ spirally
wound parallel lines, ~~where are provided and~~ a plurality of
conductors integrally coated with insulating coating resin are
arranged in parallel, ~~are constructed and the.~~ The plurality of
coils are buried in a block part made up of at least either resin
or rubber having a magnetic material dispersed therein.

~~Based on~~ With the above construction, a composite inductor
element acts as a common-mode choke coil, and when common mode noise
is applied to each of a plurality of electromagnetically
close-coupled coils, the noise is prevented from ~~passing through.~~
~~And through being transmitted.~~ Thus, an array type composite
inductor element having a plurality of common-mode choke coils
embedded in a block includes a plurality of spirally wound
parallel-wire lines constituting a plurality of
electromagnetically close-coupled coils buried, in a block while
being separated from each other, ~~in the block part, a composite~~

~~inductor element of an array type, where a plurality of common mode choke coils are embedded in a block part, is obtained.~~

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a plan view of a first preferred embodiment of a composite inductor element according to the present invention;

Fig. 2 is a front view of the composite inductor element shown in Fig. 1;

Fig. 3 is a sectional view showing a manufacturing method of the composite inductor element shown in Fig. 1;

Fig. 4 is a plan view showing the manufacturing process after ~~that of the step shown in~~ Fig. 3;

Fig. 5 is a partial longitudinal sectional view showing the manufacturing process after ~~that the step~~ of Fig. 4;

Fig. 6 is a plan view showing a second preferred embodiment of a composite inductor element according to the present invention;

Fig. 7 is a plan view showing a modification of the second preferred embodiment of the composite inductor element according to the present invention;

Fig. 8 is a schematic perspective view showing a third preferred embodiment of a composite inductor element according to the present invention;

Fig. 9 is a longitudinal sectional view of the composite inductor element shown in Fig. 8;

Fig. 10 is a right-side view of the composite inductor element shown in Fig. 8;

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

Fig. 11 is a sectional view showing a manufacturing method of the composite inductor element shown in Fig. 8;

Fig. 12 is a schematic perspective view showing a modification of the composite inductor element shown in Fig. 8;

Fig. 13 is a longitudinal sectional view of the composite inductor element shown in Fig. 12; and

Fig. 14 is a right-side view of the composite inductor element shown in Fig. 12.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT EMBODIMENTS

Hereinafter, ~~the preferred~~ embodiments of a composite inductor element according to the present invention are explained with reference to the attached drawings.

A plan view of ~~an a preferred~~ embodiment of a composite inductor element according to the present invention and a front view of the ~~this preferred~~ embodiment are shown in Figs. 1 and 2, respectively. The composite inductor element 1 ~~comprises~~ includes a plurality of spirally wound coils 11 through 14 (~~1, 12, 13, 14~~ (preferably, four coils in the first preferred embodiment) buried in a block ~~part 2 of a 2. The block 2 preferably has a substantially~~ rectangular parallelepiped shape ~~so and the coils 11-14 are preferably arranged such that the axes of the coils are arranged extend in the same direction. As a material of the block part 2,~~ The block 2 is preferably made of either resin or rubber having magnetic material of ferrite, ~~and so on, dispersed therein is used.~~





~~In opposing two side portions 2a and 2b of the block part 2, external or other magnetic material, dispersed therein.~~

External electrodes 21a through 24a and 21b through 24b are provided, respectively, on two opposite side portions 2a and 2b of the block 2. The end portions 11t and 11t of the coil 11 are electrically connected to the external electrodes 21a and 21b, respectively, the end portions 12t and 12t of the coil 12 are electrically connected to the external electrodes 22a and 22b, respectively, the end portions 13t and 13t of the coil 13 are electrically connected to the external electrodes 23a and 23b, respectively, and the end portions 14t and 14t of the coil 14 are electrically connected to the external electrodes 24a and 24b, respectively. The external electrodes 21a through 24a and 21b through 24b can be formed, for example, by applying and hardening conductive paste of Ag, Ag-Pd, Ni, and ~~so on~~, other suitable material, on the side portions 2a and 2b of the block part 2. Further, the external electrodes 21a through 24b may be constructed using metal caps ~~formed preferably having a~~ substantially in a U-shape which is made up of silver and ~~so on~~ or other suitable material. After the metal caps have been attached ~~by fitting them~~ to the side portions 2a and 2b of the block ~~part 2~~, the caps are electrically connected to the end portions 11t through 14t of the coils 11 through 14 by preferably via soldering or spot welding.

A composite inductor element 1 having such a construction is mounted, for example, as an anti-noise ~~part of the element~~ for power circuits in personal computers. The coils constructed in

accordance with the noise and current capacity specifications of the power circuits in the personal computers where the element 1 is to be mounted are buried inside of the block part 2. Because of this 2. As a result, a plurality of conventional anti-noise parts can be elements are realized as one type of unit, and accordingly in a single unit. Accordingly, the cost of providing anti-noise measures can be is greatly reduced and the space occupied can also be lessened by anti-noise elements is greatly reduced.

Next, one example of a manufacturing method of a composite inductor element 1 is explained with reference to Figs. 3 through 5. First of all, pellets of PPS resin (polyphenylene sulfide resin) mixed with 90 wt% of ferrite powder are prepared. Further, sets of spirally wound coils 11 through 14, which are needed for one molding shot, are prepared.

Next, as shown in Fig. 3, after the coils 11 through 14 have been put on pins 41 through 44 ~~given provided~~ on a lower mold 31 for injection molding, an upper mold 32 and the lower mold 31 are joined together. Next, the PPS pellets mixed with ferrite prepared in the above process are melted and injected between the lower mold 31 and upper mold 32 as shown by arrows A1, and thus, a first injection molding is performed. After that, the lower mold 31 is removed to pull out the pins 41 through 44 from the coils 11 through 14, and, a second injection molding is performed in order to fill the hollow portions which previously occupied by the pins 41 through 44 with, using the same melted PPS pellets mixed with ferrite as in the first injection molding. Thus, as shown in Fig. 4, a molded part 34, in



which coil sets 33 of the coils 11 through 14 of one molding shot (namely, four sets) are buried, is manufactured.

The molded part 34 is cut at the locations shown by one-dot chain lines L1 using a slicing machine, a dicing cutter, ~~and so on, or other suitable device,~~ to produce ~~block-parts~~ blocks 2. The ~~obtained block-parts~~ blocks 2 are further cut at the locations shown by one-dot chain lines L2 in Fig. 5 and the end portions 11t through 14t of the coils 11 through 14, respectively, buried inside of the ~~block-parts~~ blocks 2 become exposed on the surface of the ~~block-parts~~ blocks 2. Furthermore, ~~conductive~~ conductive paste is applied and hardened on the side portions 2a and 2b where the end portions 11t through 14t of the coils 11 through 14, respectively, are exposed. Thus, the external electrodes 21a through 24a and 21b through 24b electrically connected to the end portions 11t through 14t of the coils 11 through 14, respectively, are formed. In this way, ~~by~~ via a molding process and a cutting process using resin material suitable for mass production, a composite inductor element 1 can be efficiently manufactured.

Another preferred embodiment of a composite inductor element according to the present invention ~~is will now be~~ explained. In a composite inductor element 51, the plan view of which is shown in Fig. 6, four coils 61 through 64 having different numbers of windings (that is, different inductances), which are different from those of the composite inductor element 1 of the first preferred embodiment, are buried in a block ~~part~~ 2. The number of windings of the coils 61 through 64 is determined individually based on the



noise and current capacity specifications of the power circuits of the personal computers ~~and so on~~ or other electronic apparatuses, to which the composite inductor element 51 is connected. On two ~~opposing~~ opposite side portions 2a and 2b of the block 2, external electrodes 21a through 24a and 21b through 24b are provided, respectively. End portions 61t and 61t of the coil 61 are electrically connected to the external electrodes 21a and 21b, respectively, and portions 62t and 62t of the coil 62 are electrically connected to the external electrodes 22a and 22b, respectively, and portions 63t and 63t of the coil 63 are electrically connected to the external electrodes 23a and 23b, respectively, and end portions 64t and 64t of the coil 64 are electrically connected to the external electrodes 24a and 24b, respectively.

Further, in a composite inductor element 71, the plan view of which is shown in Fig. 7, four coils 61a through 64a having ~~not~~ only different numbers of windings, ~~but also~~ and different coil wire thicknesses and different coil diameters, which are different from the case of the composite inductor element 1 of the first preferred embodiment, are buried in a block part 2. The wire thicknesses, numbers of windings, and coil diameters of the coils 61a through 64a are determined individually based on the noise and current capacity specifications of the power circuits of the personal computers ~~and so on~~ or other electronic apparatuses to which the composite inductor element 71 is connected. On two ~~opposing~~ opposite side portions 2a and 2b of the block 2, external



electrodes 21a through 24a and 21b through 24b are provided, respectively. End portions 61t and 61t of the coil 61a are electrically connected to the external electrodes 21a and 21b, respectively, end portions 62t and 62t of the coil 62a are electrically connected to the external electrodes 22a and 22b, respectively, end portions 63t and 63t of the coil 63a are electrically connected to the external electrodes 23a and 23b, respectively, and end portions 64t and 64t of the coil 64a are electrically connected to the external electrodes 24a and 24b, respectively.

In the composite inductor elements 51 and 71 having such a construction, a combination of coils 61 through 64 and 61a through 64a can be changed, for example, in accordance with the current capacity and noise elimination characteristics corresponding to a plurality of power circuits of personal computers or other electronic apparatuses.

Another preferred embodiment of a composite inductor element according to the present invention ~~is~~ will now be explained. A perspective view, a longitudinal sectional view, and a right-side view of a composite inductor element 81 are shown in Figs. 8, 9, and 10 respectively. The composite inductor element 81 ~~contains~~ preferably includes two electromagnetically close-coupled coils 91 and 92. The two coils 91 and 92 are ~~composed~~ preferably made of a parallel-wire line 94 in which two conductors 91a and 92a integrally coated with insulating coating resin 93 are arranged in parallel. The parallel-wire line 94 is spirally wound around



one coil axis and buried in a block ~~part 2 of a 2~~ having a substantially rectangular parallelepiped. As a material of the block part 2, at least shape. The block 2 is preferably made of either resin or rubber having magnetic material of ferrite ~~and so on or other magnetic material dispersed therein is used.~~

On two ~~opposing~~ opposite side portions 2a and 2b of the block 2, external electrodes 21a and 21b, and 22a and 22b are provided. The end portions 91t and 91t of the coil 91 are electrically connected to the external electrodes 21a and 21b, respectively, and the end portions 92t and 92t (not illustrated) of the coil 92 are electrically connected to the external electrodes 22a and 22b, respectively.

In the composite inductor element 81 having such a construction, the two coils 91 and 92 are arranged to be ~~in~~ parallel in the insulating coating resin 93 and are electromagnetically close-coupled. Accordingly, the composite inductor array element 81 ~~becomes~~ is a common-mode choke coil of a bifilar type. When common mode noise is applied to each of the coils 91 and 92, the noise is prevented from ~~passing through~~ being transmitted therethrough. Further, ~~as because~~ the coils 91 and 92 are ~~comprised~~ made up of conductors 91a and 91b, the cross section of which can be made relatively large, the current capacity is greatly increased in comparison with a composite inductor element of a conventional laminated type where the conductors constituting coils are formed by printing conductive paste. Further, ~~as because~~ the two conductors 91a and 92a constituting the two coils 91 and 92 are covered by



insulating coating resin 93, the reliability of the insulation between the two coils 91 and 92 is also increased.

Next, one example of a manufacturing method of the composite inductor element 81 is explained ~~in~~ with reference to Fig. 11. First, pellets of PPS resin mixed with ferrite powder are prepared. Further, the coils 91 and 92 made up of the parallel-wire line 94 of the two conductors 91a and 92a contained within the insulating resin 93, which is spirally wound around one coil axis, are prepared.

Next, after the spirally wound parallel-wire line 94 has been put on a pin ~~given~~ provided on a lower mold 31a for injection molding, an upper mold 32a and the lower mold 31a are joined together. Next, the PPS pellets mixed with ferrite prepared in the above process are melted and injected between the lower mold 31a and upper mold 32a as shown by an arrow A1, and thus, a first injection molding is performed. After that, the lower mold 31a is removed to pull out the pin 41a from the spirally wound parallel-wire line 94, and a second injection molding is performed to fill the concave portion which was occupied by the pin 41a with the same melted PPS pellets mixed with ferrite as in the first injection molding. Thus, a molded part having the coils 91 and 92 buried therein is produced.

Next, both of the end portions of the molded part are cut off using a slicing machine, a dicing cutter, ~~and so on or other suitable~~ cutting apparatus, to produce the block part 2. ~~On~~ At the side portions 2a and 2b of the block ~~part 2-2~~, the end portions 91t and 92t of the coils 91 and 92 are exposed. Furthermore, by laser machining and so on, a guide groove 95 (see Fig. 10) is formed on



the side portions 2a and 2b of the block ~~part~~ 2. In accordance with this guide groove 95, the end portions 91t and 92t of the coils 91 and 92 are guided respectively, and the end portions 91t and 92t are set within the guide groove 95.

After that, on the side portions 2a and 2b where the end portions 91t and 92t of the coils 91 and 92 are exposed, conductive paste is coated and hardened. Thus, the external electrodes 21a and 21b, and 22a and 22b electrically connected to the end portions 91t and 92t of the coils 91 and 92, respectively, are formed.

Information on the breakdown voltage, the coupling coefficient, and the direct-current resistance of the composite inductor element 81 manufactured in this way are shown in Table 1. In Table 1, for comparison, the measurements of laminated-type composite inductor elements, in which a plurality of magnetic layers and two sets of conductors ~~for forming~~ defining coils are alternately laminated, are also shown (see Comparative Example 1 and Comparative Example 2). Example 1 was constructed by simply laminating each layer of conductors ~~for forming~~ defining the coils. Example 2 was constructed by arranging electrical insulation material having lower permeability than that of the magnetic layer between the conductor layers ~~for forming~~ defining the coils.

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

This Sheet Has Been Replaced



Table 1

	Breakdown voltage	Coupling coefficient	DC resistance
Preferred Embodiment	100 V	99 %	10 m
Comparative Example 1	50 V	80 %	1
Comparative Example 2	16 V	95 %	1

As clearly seen in Table 1, the composite inductor element 81 of this preferred embodiment ~~had~~ has superior reliability of the insulation and a high coupling coefficient. Because the insulating coating resin 93 of the parallel-wire line 94 has a high breakdown voltage, the high breakdown voltage of the preferred embodiment ~~resulted,~~ was achieved, and ~~by thus,~~ selection of the resin to be used the breakdown voltage can be further improved. Further, in the composite inductor element 81, the permeability of the block part 2 is about 13, but on the other hand, the permeability of the insulating coating resin 93 is about 1 and the magnetic reluctance is relatively high. Accordingly, the ratio of the magnetic flux leaking from the coils 91 and 92 (short path phenomenon) is relatively smaller than that of the laminated-type composite inductor elements, and the coupling coefficient is greatly improved. Furthermore, in the composite inductor element 81, ~~as~~ because the conductors of relatively large thickness and

made of base metal such as copper and so on can be used as the conductors 91a and 92a, the problem of wire breakage caused by heating due to a large current is solved.

Although the two coils 91 and 92 are formed using the parallel-wire line 94 in which the two conductors 91a and 92a are arranged in parallel in the insulating coating resin 93, in a composite inductor element 101, as shown in Figs. 12 through 14, three electromagnetically close-coupled coils 96, 97, and 98 spirally wound around one coil axis may be formed using a parallel-wire line 99 in which three (or more than three) conductors 96a, 97a, and 98a are arranged in parallel in an insulating coating resin 93, and buried in a block ~~part 2~~ with magnetic material dispersed therein. ~~And as~~ ~~As~~ shown in Fig. 14, through the groove guide 95a formed ~~on~~ in the block ~~part 2~~, the end portions 96t through 98t of the coils 96 through 98 are electrically connected to external electrodes 21a through 23a and 21b through 23b.

Further, the number of parallel-wire lines is not limited to one, and a plurality of spirally wound parallel-wire lines may be buried in a block ~~part 2 in a condition in which~~ such that the lines are separated from each other. Thus, because, in a composite an array-type inductor element, a plurality of common-mode choke coils are contained in the block ~~part 2~~, the occupied space can also be further reduced.

The present invention is not limited to the above preferred embodiments, but various modifications are possible within the spirit and scope of the invention. For example, in the first and



second preferred embodiments, the number of coils are not limited to four, and may be changed to any arbitrary number in accordance with the specification of equipment or product in which an anti-noise ~~part~~ component is mounted. Further, apart from a spirally wound form, the coils may be of a linear form or other suitable form.

As clearly understood from the above explanation, according to the present invention, by burying a plurality of coils in a block ~~part~~ made of at least either resin or rubber having a magnetic material dispersed therein, a plurality of ~~conventional~~ anti-noise ~~parts~~ components are able to be realized as single-type units. As a result, the cost of anti-noise measures can be greatly reduced.

Further, since a plurality of electromagnetically close-coupled coils are constructed by spirally winding a parallel-wire line in which a plurality of conductors are integrally coated with insulating coating resin and arranged in parallel and buried in a block ~~part~~, a composite inductor element functioning as a common-mode choke coil having a high breakdown voltage, a large coupling coefficient, and a large current capacity can be obtained.

While the invention has been shown and described with reference to the preferred embodiments, it will be understood by those skilled in the art that the foregoing and other changes in form and details can be made without departing from the spirit and scope of the invention.

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

This Sheet Has Been Replaced



WHAT IS CLAIMED IS:

1. A composite inductor element comprising:

a block part made of at least either resin or rubber having a magnetic material dispersed therein, external electrodes being provided on said block part; and

a plurality of coils buried in said block part, end portions of each of the plurality of coils being electrically connected to said external electrodes.

2. A composite inductor element according to claim 1, wherein each of the coils has different electrical characteristics.

3. A composite inductor element according to claim 1, wherein four of the coils are provided.

4. A composite inductor element according to claim 1, wherein the plurality of coils are spirally wound.

5. A composite inductor element according to claim 1, wherein the block has a substantially rectangular parallelepiped shape.

6. A composite inductor element according to claim 1, wherein the plurality of coils are arranged such that axes of the plurality of coils extend in the same direction.



* C L M S *

THIS SHEET HAS BEEN
REPLACED

7. A composite inductor element according to claim 1, wherein the external electrodes are made of one of Ag, Ag-Pd, and Ni.

8. A composite inductor element according to claim 1, wherein the external electrodes comprise substantially U-shaped caps made of silver.

9. A composite inductor element according to claim 1, wherein one of the plurality of coils has a different number of windings from that of others of the plurality of coils.

10. A composite inductor element according to claim 1, wherein one of the plurality of coils has a different thickness from that of others of the plurality of coils.

11. A composite inductor element according to claim 1, wherein one of the plurality of coils has a different diameter from that of others of the plurality of coils.

This Sheet Has Been Replaced



12. A composite inductor element comprising:

a block ~~part~~ made of at least either resin or rubber having a magnetic material dispersed therein; and

a plurality of electromagnetically close-coupled coils buried in said block ~~part~~, said coils being arranged in parallel and being constructed ~~by of spirally winding a wound parallel-wire line and~~



THIS SHEET HAS BEEN
REPLACED

~~by integrally coating lines made of a plurality of insulation-coated conductors with an insulating coating resin.~~

4 13. A composite inductor element according to claim 3 12, wherein the plurality of spirally wound parallel-wire lines constituting the plurality of electromagnetically close-coupled coils are buried in the block ~~part in a condition in which such that~~ the lines are separated from each other.

14. A composite inductor element according to claim 12, wherein one of the plurality of coils has a different number of windings from that of others of the plurality of coils.

15. A composite inductor element according to claim 12, wherein one of the plurality of coils has a different thickness from that of others of the plurality of coils.

16. A composite inductor element according to claim 12, wherein one of the plurality of coils has a different diameter from that of others of the plurality of coils.

17. A composite inductor element according to claim 12, wherein the plurality of coils are arranged such that axes of the plurality of coils extend in the same direction.

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

18. A composite inductor element according to claim 12, wherein each of the coils has different electrical characteristics.

19. A composite inductor element according to claim 12, wherein four of the coils are provided.

20. A composite inductor element according to claim 12, wherein the block has a substantially rectangular parallelepiped shape.

This Sheet Has Been Replaced



* C L M S *

THIS SHEET HAS BEEN
REPLACED