

A METHOD AND APPARATUS FOR SPLITTING FLUID FLOW
IN A MEMBRANELESS PARTICLE SEPARATION SYSTEM

[0001] Several different types of membraneless particle separation devices having a generally spiral or curved configuration have been described in co-pending patent applications.

[0002] In general, such devices are useful in connection with particles having density differences compared with water, thus creating centrifugal or buoyancy forces necessary for transverse migration through the channel for purposes of separation. Some of these devices are also useful, depending on their configuration, to separate neutrally buoyant particles. With reference to Figure 1, one example form of a separation device 20 is shown. This form shows an exemplary spiral channel 22 with increasing radius of curvature. This geometry takes advantage of the rate of pressure change. Any suitable form will suffice. However, for example, in another form, the device may have a contracting spiral channel with a decreasing radius of curvature for the sidewalls. The channel may also maintain a substantially constant radius of curvature and a constant channel size. In any of these cases, or others, the channel 22 evolves into two separate channels 24 and 26 (e.g. also referred to as channel #1 and channel #2 in Figure 1 to allow for multiple outlet paths).

[0003] These types of separation devices provide for particle separation in a variety of manners. For example, depending on the flow rate, the particle separation may be driven by the centrifugal force or the pressure that is created by flow fluid through the channel. In any of these cases, the objective is for particle separation to occur. Typically the fluid flow will then have a first portion with particles of one type of

particle or band and a second portion having fluid without the particles of the first portion therein.

[0004] In these types of systems, it would be desirable to provide for enhanced separation at the outlet of the devices.

[0005] In one aspect of the presently described embodiments, a particle separation device comprises an inlet operative to receive fluid having particles dispersed therein, at least one curved channel operative to generate a flow field comprising a first portion and a second portion, and, an outlet including a mechanism to split the flow such that the first portion flows on a first path and the second portion flows on a second path.

[0006] In another aspect of the presently described embodiments, the outlet includes a knife edge.

[0007] In another aspect of the presently described embodiments, the knife edge is operative to pivot.

[0008] In another aspect of the presently described embodiments, the knife edge is operative to slide.

[0009] In another aspect of the presently described embodiments, the outlet comprises a system to generate a pressure differential between the first path and the second path.

[0010] In another aspect of the presently described embodiments, the system comprises a first valve positioned in the first path and a second valve positioned in the second path.

[0011] In another aspect of the presently described embodiments, the device further comprises a feedback system.

[0012] In another aspect of the presently described embodiments, the feedback system is operative to control the device based on at least one of pressure, bandwidth and flow rate.

[0013] In another aspect of the presently described embodiments, the feedback system is operative to control the device based on at least one of viscosity and temperature.

[0014] In another aspect of the presently described embodiments, the system comprises at least two channels having an actuator disposed between the channels, wherein the actuator selectively deforms walls of the channel to generate a pressure differential.

[0015] In another aspect of the presently described embodiments, the system comprises at least two channels having two actuators disposed between the channels, wherein each actuator selectively deforms a wall of one of the channels to generate a pressure differential.

[0016] In another aspect of the presently described embodiments, the system comprises compression rings positioned and operative to selectively apply pressure to channels corresponding to the first and second paths.

[0017] In another aspect of the presently described embodiments, the method comprises initiating fluid flow in the separation device, and, adjusting a mechanism in the outlet to vary the fluid flow between the first and second outlet paths.

[0018] In another aspect of the presently described embodiments, the adjusting comprises moving a knife edge within the outlet.

[0019] In another aspect of the presently described embodiments, the adjusting comprises a changing pressure with the device.

[0020] In another aspect of the presently described embodiments, changing the pressure is based on operation of at least one actuator.

[0021] In another aspect of the presently described embodiments, changing the pressure is based on manipulation of at least one of compression rings and expansion rings.

[0022] In another aspect of the presently described embodiments, changing the pressure is based on initiation of at least one valve.

[0023] In another aspect of the presently described embodiments, the adjusting is based on feedback data items.

[0024] In another aspect of the presently described embodiments, the data items are based on at least one of pressure, bandwidth, flow rate, viscosity and temperature.

[0025] FIGURE 1 is a representation of an example spiral particle separation device;

[0026] FIGURE 2 illustrates a form of the presently described embodiments;

[0027] FIGURE 3 illustrates a form of the presently described embodiments;

[0028] FIGURE 4 illustrates a form of the presently described embodiments;

[0029] FIGURE 5 illustrates a form of the presently described embodiments;

[0030] FIGURE 6 illustrates a form of the presently described embodiments;

[0031] FIGURE 7 illustrates a form of the presently described embodiments;

[0032] FIGURE 8 illustrates a form of the presently described embodiments;

[0033] FIGURE 9 illustrates a form of the presently described embodiments;

[0034] FIGURES 10(a)-10(b) illustrate one form of the presently described embodiments;

[0035] FIGURE 11 illustrates a form of the presently described embodiments

[0036] FIGURE 12 illustrates a form of the presently described embodiments; and

[0037] FIGURE 13 illustrates a form of the presently described embodiments.

[0038] The presently described embodiments provide for a mechanism at the outlet of a spiral separation device for splitting, or bifurcating, the fluid flow. This is particularly advantageous in spiral or curved devices because the outlet of the separation device typically will have different size particles on one side of the channel relative to the other side of the channel. In some forms, one side of the channel may have a band of particles flowing therein while the opposite side of the channel has very few resident particles. This is particularly true where neutrally buoyant particles are flowing and separated in a fluid. In at least one form, the portion of the fluid flow containing particles (or relatively more particles) is referred to as the particulate stream, while the remaining portion of the fluid is referred to as the effluent stream.

[0039] The presently described embodiments provide a splitting system to the outlet of the various separation devices that is transparent to the fluid flow. That is, implementation of the presently described embodiments does not typically cause dispersion or otherwise compromise the integrity of a focused particle band or group of particles, does not create undue turbulence, and does not cause excessive pressure fluctuations that would impair the desired fluid flow. The presently described embodiments allow for adaptability of the split of fluid flow, e.g. in a range from a 20:80 split to an 80:20 split. Suitable flow sensing and computer feedback control may also be applied to the system.

[0040] The presently described embodiments may take a variety of forms, as those of skill in the art will appreciate. As described herein, the presently described embodiments may include static or passive mechanisms or subsystems. These mechanisms could also be modular and interchangeable to provide for preset fluid split divisions of 20:80, 30:70, 40:60, 50:50, ... etc. In other forms of the presently described embodiments, the system is adjustable and variable. In still another form of the presently described embodiments, the system allows for differential pressure control at the outlets to facilitate the flow of varying size particles or particle bands in the respective channels or paths.

[0041] With reference to Figures 2-12, it should be appreciated that the mechanisms illustrated may also be implemented in a variety of different environments and configurations. For ease of illustration and explanation, such mechanisms are shown herein as applied to a single channel, in simple form and/or in representative environments. For example, it will be understood by those of skill in the art that these techniques and structures may be implemented in multiple and repetitive fashion where, for example, a plurality of channels are configured within a device or system.

[0042] With reference now to Figure 2, a spiral separation device A having an inlet B, curved channel portion C, and outlet 10 is illustrated. It will be appreciated that the separation device A is shown merely in representative form for ease of explanation. Figures 3-12 do not specifically show a full separation device, but it will be understood that any of the outlets of these drawings could be applied to the contemplated separation devices, such as that shown in Figure 2.

[0043] As shown, the end 12 of the spiral channel C is split into a first channel or path 14 and a second channel or path 16. This channel configuration is shown to be resident in a substrate 18. However, it will

be appreciated that other forms of or environment for the outlet may exist. Notably, the split of the channels 14 and 16 from the end 12 of the spiral device C is facilitated and enhanced by a knife mechanism 11 formed of a generally static wall 15 having a knife edge 17 protruding into the end 12. In this regard, the flow of fluid and separation thereof is enhanced.

[0044] It should be appreciated the shape of the knife edge may well depend on the channel cross section. For example, rectangular shaped channels may have rectangular shaped knife edges while elliptical shaped channels (e.g. formed by vertically deforming a tube) may have a parabolic shaped knife edge. Of course, other shapes for the knife edges and corresponding walls are contemplated by the presently described embodiments.

[0045] With reference now to Figure 3, another form of the presently described embodiments is shown. A parabolic fluid flow 30 is illustrated as flowing through the end 12 of the spiral device (not shown) and being divided in the outlet 10 to flow in a first channel 14 or the second channel 16. In these embodiments, however, the knife edge mechanism 32 is pivoted at a point 34 near the separation of the channels. Although only representatively shown, the knife edge mechanism 32 includes a wall 36 and a knife edge portion 38. As can be seen, the knife edge device 32 can pivot through a range of positions, as exemplary shown by the arrow and dotted lines. As noted above, in at least one form, this range will provide relative fluid flow in the two channels in a range from 20:80 to 80:20. It will be appreciated by those of skill in the art that the pivoting of the knife edge device 32 may be accomplished in a variety of different manners using a variety of different techniques. The dimensions of the channel may dictate the technology to actuate the pivot in the knife edge device 32. For example, in one form, pivoting may be accomplished

utilizing piezoelectric devices or hydraulic devices. It should also be appreciated that the pivot may be accomplished manually.

[0046] With reference now to Figure 4, a parabolic fluid flow 30 is illustrated as flowing in the end 12 of the channel of the spiral device (not shown) and being split or bifurcated in the outlet 10 into fluid flow down the first channel 14 and the second channel 16. However, in this embodiment, the knife edge mechanism 40 is adapted to slide on, for example, a rail of an external actuator 42. As with the other embodiments, it will be appreciated that the knife edge device 40 includes a wall 46, as well as a suitable knife edge portion 48. It will further be appreciated that the external actuator may take a variety of forms. Again, depending on the relative dimensions of the separation device and other environmental factors, the external actuator may be a piezoelectric actuator, hydraulic actuator or a manual actuator.

[0047] With reference now to Figure 5, the outlet 10 of the separation device (not shown) has a parabolic fluid flow 30 flowing through the end 12 of the channel which is split into the first channel 14 and the second channel 16. Also shown are the knife edge mechanism 40 and the external actuator 42. However, in this embodiment, a sliding pin 50 is provided to channel wall portions 52 and 54 of the first and second channels 14 and 16, respectively. It will be appreciated that the wall portions 52 and 54 are formed of a flexible membrane. The flexible membrane may be formed of a variety of suitable materials. This allows the pin 50 to slide in the external actuator 42, thus changing the position of the knife edge device 40. The flexibility of the wall portions 52 and 54 allow the channel integrity to be maintained.

[0048] The embodiments illustrated in Figures 2-5 illustrate configurations wherein the knife edge extends into the end of the channel at the end of the separation device. However, the presently

described embodiments also contemplate configurations wherein the knife edge does not extend into the channel -- but, for example, merely abuts the end of the channel or the appropriate channel stack. For example, with reference now to Figure 6, an outlet 100 of a separation device is illustrated. As shown, a channel 102 of the separation device is split into a first channel 104 and a second channel 106 by a knife mechanism 108. As with the other embodiments, the knife mechanism 108 includes a wall portion 110 as well as a knife edge 112. In this configuration, outer walls 114 and 116 are also illustrated. In operation, in this embodiment, the knife edge mechanism 108 slides along a rail or by way of other types of actuators, to split the fluid flow in a variable and adaptable way. As shown, a band or group or concentration of particles could flow into the first channel 104 while the remaining fluid -- not including the band (or group or concentration) of particles -- could flow through the second channel 106.

[0049] With reference now to Figure 7, a further embodiment wherein the knife edge does not extend into the end of the channel is illustrated. As shown, the outlet 120 for the end 122 of a separation device includes a first channel 124 and a second channel 126. A splitting or bifurcation of the fluid flow is accomplished using a mechanism 128 comprising a rotating cylinder 130 and a knife edge 132. The channel 124 is defined by an outer wall 134 and an inner wall 135. Likewise, channel 126 is defined by an outer wall 136 and an inner wall 137. It should be appreciated that the knife edge 132 is rotated to change the split ratio at the end of the channel 122. The inner walls 135 and 137 are configured to accommodate such rotation. For example, the inner walls 135 and 137 could be flexible in nature -- which would allow for them to be attached to the rotating cylinder. In other forms, the inner walls 135 and 137 may simply static in nature, with suitable sealing techniques to

ensure no leakage between the inner walls 135 and 137 and the rotating cylinder 130.

[0050] With reference now to Figure 8, an outlet 120 of a separation device (not shown) includes the end of the channel 122 being divided into the first channel 124 and the second channel 126. In this configuration, a mechanism 140 is provided to the system to split the fluid flow. The mechanism 140 includes a sliding cylinder 142, as well as a knife edge 144. As with the previous embodiment, the channel 124 is defined by an outer wall 134 and an inner wall 135. Likewise, the channel 126 is defined by an outer wall 136 and an inner wall 137. In this embodiment, the inner walls 135 and 137, in at least one form, are formed of a flexible membrane to allow for the sliding of the cylinder 142, yet still maintaining the fluid within the channels 124 and 126.

[0051] With reference now to Figures 9 through 11, varying the split or bifurcation of the fluid flow in the spiral separation devices contemplated herein may also be accomplished using differential pressure or flow control at the respective outlets. In the presently described embodiments, this differential pressure and/or flow control can be accomplished using independently controlled actuators or a simultaneous two-way actuation for adjacent channels. Flexible membrane walls for the outlet channels are typically used to allow for deformation. The deformation of the wall will modify the flow cross section and, thus, the pressure on the upstream fluid. Flow control valves can be implemented independently on the outlet channels. The channels in this case need not be flexible.

[0052] With reference now to Figure 9, an outlet 200 showing the end 202 of a channel of a spiral separation device (not shown) is shown. The channel 202 is split between a first channel 204 and a second channel 206. The channel 204 is defined by a rigid outer wall 208, as well as a

flexible inner wall 210. The channel 206 is defined by a rigid outer wall 212 and a flexible inner wall 214. In this embodiment, an actuator 216 having a plunger 218 (e.g. a solenoid) is actuated to deform the wall 210 in a variety of different manners to create differential pressure upstream in the channel. Likewise, an actuator 220 having a plunger 222 is utilized to deform wall 214 to achieve desired differential pressure or flow control. It will be appreciated that the actuators can be controlled in a variety of different manners to accomplish the objectives of the presently described embodiments. For example, one of the actuators could be actuated to create differential pressure and flow control. Or, both of the actuators can be actuated in tandem or in a complementary manner, at the same or varying rates, to generate differential pressure and flow control.

[0053] With reference to Figures 10(a) and (b), the system 200 includes only a single actuator 250. The single actuator 250 includes a plunger 252 that is sized to manipulate both flexible walls 210 and 214. As shown in Figure 10(a), the plunger 252 is shown in an extreme position to the left. Figure 10(b) shows an opposite extreme position to the right.

[0054] In either of the embodiments of Figures 9 and 10, it will be appreciated that implementation of the actuators will create a differential pressure and flow control in the channel that will allow for varying degrees of particle flow in each of the channels 204 and 206.

[0055] Another manner of achieving such a result is to provide adjustable valves in each or at least one of the outlet paths or channels. As shown in Figure 11, a system 200 includes a first channel 230 and a second channel 232. The first channel 230 has positioned therein a valve 234. The second channel 232 has positioned therein a valve 236. Thus, two separate valves are able to control the flow in the channels. In

this case, the walls of the channels 230, 232 need not be flexible. In addition, the valves may take a variety of known forms; however, in at least one form, the valves are in-line valves. Selective operation of the valves will create a desired differential pressure and flow control in the system. It should be appreciated that one valve is sufficient to divide the flow between the two outlets without impacting the inlet pressure.

[0056] With reference now to Figure 12, another embodiment relying on differential pressure and/or flow control within a system to split the fluid flow is shown. In this embodiment, radial compression of bifurcated outlets is used to do so. An end view of an outlet 300 is shown. The outlet includes a compliant outer ring 302, a rigid ring 304 and a compliant inner ring 306. A first set of channels 310 is disposed between the outer ring 302 and the rigid ring 304. A second set of channels 312 is disposed between the rigid ring 304 and the compliant inner ring 306. It will be appreciated that the set of channels 310 corresponds to a first set of outlet channels that have been split, such as channel 204 of Figure 10(a). The second set of channels 312 relates to a second set of channels that have been split from an outlet, such as channel 206 of Figure 10(a). Those of skill in the art will appreciate that this configuration results from the implementation of a plurality of separation devices and the suitable gathering of the flow paths or channels, as shown.

[0057] The pressure in the channels can be adjusted by manipulating channel diameters and relative flow rates of inner and outer streams of fluid by reciprocal radial compression/expansion of inner and outer rings 302 and 306. The rings 302 and 306 can be compressed and/or expanded simultaneously, or individually, to create a differential pressure and/or flow control in the system. It will be understood by those of skill in the art that ring compression could provide for more uniform and

smoother transitions. However, ring expansion will also achieve the objectives of the presently described embodiments. It should also be understood that all inner and outer channels may ultimately be combined, in one form, downstream, depending on the configuration of the overall system.

[0058] It should be understood that the embodiments illustrated herein serve as mere examples. Variations are contemplated. For example, each outlet shown and described herein is split or bifurcated into two channels. The split of the outlet (and this application of the presently described embodiments) may be extended to three or more channels.

[0059] Also, it will be understood that the materials used to construct the various configurations contemplated herein will vary as a function of the dimensions, application and environment of the system. Likewise, the dimensions of the contemplated systems may vary.

[0060] As noted, the presently described embodiments may include various sensing and feedback control to allow for the enhanced splitting of the fluid flow. For example, optical sensors may be placed in the system prior to the point of splitting or bifurcation and, at a midway point, may be used to detect bandwidth and location. A feedback signal may be sent to the splitting mechanisms to maximize band capture and fluid recovery in the channels. A flow sensor may also be provided along the channeling to detect velocity variations. This data may then be used to feedback to necessary pumps to maintain constant flow rate, and hence, velocity. A pressure sensor could also be provided to adjust flow rate in each channel to minimize band dispersion and to maximize flow recovery. Temperature sensors may be used to correct fluidic operation and viscosity sensors may be used to correct for adjustment in operation parameters.

[0061] It should be appreciated that these types of sensing and feedback control devices may be implemented in a variety of different manners within the system to achieve the sensing and feedback objectives noted herein and others. In this regard, these types of devices may be implemented using different hardware configurations and/or software techniques that are suited to the environment and system configuration.

[0062] With reference to Figure 13, an example feedback and/or control system 400 is illustrated. The system 400 includes a separator such as a spiral separator 402 that receives input fluid 404. In operation, the separator 402 separates the input fluid 404 into an effluent stream 406 and a particulate stream 408. As shown, the process is enhanced through the use of any of a variety of flow splitters 400 contemplated herein. It will be understood that the flow splitter may be controlled based on various data items that are collected. These data items include, for example, pressure, bandwidth and flow rate. As noted above, temperature and viscosity sensors may also be used to collect desired data. Such data items are fed to a controller 420. The controller 420 controls actuators 430, which are used to split the fluid, as will be understood from the above embodiments. It will be understood that the actuators 430 and the flow splitter may be integrated in the same device.

Claims:

1. A particle separation device comprising:
 - an inlet operative to receive fluid having particles dispersed therein;
 - at least one curved channel operative to generate a flow field comprising a first portion and a second portion; and,
 - an outlet including a mechanism to split the fluid such that the first portion flows on a first path and the second portion flows on a second path.
2. The device as set forth in claim 1 further comprising a feedback system.
3. A method for splitting fluid flow at an outlet of a spiral separation device having a first and second outlet paths, the method comprising:
 - initiating fluid flow in the separation device; and,
 - adjusting a mechanism in the outlet to vary the fluid flow between the first and second outlet paths.
4. The method as set forth in claim 3 wherein the adjusting is based on feedback data items.