

Description

The present invention relates to an electron gun assembly for a cathode-ray tube (CRT) and, more particularly, to a structure for strengthening the sidewall of a cup-shaped member of an inline assembly for a plural beam CRT.

The electrode members of an inline electron gun assembly are serially arranged to accelerate and focus a plurality of electron beams along spaced, coplanar electron beam paths. The electrode members of the gun assembly are mechanically secured by means of attachment tabs and studs to at least a pair of insulative support rods which extend along the beam paths. Each of the electrode members commonly has several spatially-related apertures formed therein to accommodate the respective electron beams generated within the electron gun assembly. It is important that these several apertures be accurately located and aligned relative to the related apertures in adjacent electrode members, and to the respective electron generating surfaces. During the fabrication of the electron gun assembly, the attachment tabs and studs of the various electrode members are embedded into the temporarily heat-softened insulative support rods, at which time the support rods on opposed sides of the gun assembly are pressured inwardly toward the electrode members to force the attachment tabs and studs into the support rods. The compressive pressure tends to exert a distorting force upon the several deep-drawn, cup-shaped electrode members which comprise the main focus lens of the electron gun assembly.

Most experience to date with conventional deep-drawn, cup-shaped electrodes, having sidewalls up to about 12.7 mm long, shows that these electrodes tend to develop a negative or concave "oil-canning" tendency; i.e., the sidewall of the electrode tends to bow inwardly toward the electron beam axes. When studs are welded to opposite sides of the sidewall of such electrodes, exact positioning and welding are difficult because of the variable slope and degree of negative "oil-canning" that occurs.

An even greater problem has been encountered in electron guns in which ultra-deep drawn, cup-shaped electrodes have sidewalls more than 12.7 mm long. In such ultra-deep drawn electrodes, a critical thinning of the sidewall occurs. The apex of the "oil-canning" in these electrodes occurs about 10.16 mm from the support flange located at the open end of the electrode. In the vicinity of the apex, the sidewall thins from the desired thickness of about 0.25 mm to about 0.19 mm. If the "oil-canning" is negative or concave on both sides of the sidewall, the problem of stud positioning is similar to that of the shorter deep-drawn electrodes described above; however, if the "oil-canning" of one side of the sidewall is positive or convex and the other side is negative or concave, or if both

sides exhibit positive or convex "oil-canning," a new phenomenon occurs. During the beading operation, in which the insulative support rods are heated to a molten state and formed into contact with the attachment tabs and studs of the electron gun, the positive or convex "oil-canning" sidewall is forced inward by the stud attached to the sidewall of the previously convex surface.

The inward displacement of the previously convex sidewall acts like a loaded spring. As soon as the arms of the beading apparatus retract at the end of the beading cycle, the compressed sidewall of the electrode tends to return to its previous convex position forcing the insulative support rods, which are still in a plastic state, to bulge outwardly. Shear forces are thereby introduced into the insulative support rods during the cooling-deflection cycle, causing the support rods to crack in the vicinity of the attachment tabs or studs.

Even in electron guns in which the stress forces are not sufficiently great to crack the support rods, the varying degree of "oil-canning" of the sidewalls can cause a side-to-side displacement or offset of the ultra-deep drawn electrode relative to the other electrode members of the main focus lens. This results in a change of aperture locations relative to those in the adjacent electrode members, thereby producing deleterious inter-electrode spacing relationships and distortion in the electron beam trajectories.

U.S. Pat. No. 4,484,102, issued to J. R. Hale on Nov. 20, 1984, discloses a structure for strengthening the sidewall of a conventional deep-drawn electrode. The structure described therein comprises a wedge-shaped shoulder that is formed in opposite parallel sides of the sidewall of a deep-drawn substantially rectangular cup-shaped member. The wedge-shaped shoulder projects outwardly at an acute angle of about 45 degrees from the sidewall and extends into the supporting flange of the electrode adjacent to the attachment tabs. This structure is insufficient to prevent flexure of the sidewall of ultra-deep drawn electrodes.

U.S. Pat. No. 4,595,858, issued to J. R. Hale on Jun. 17, 1986, discloses a structure suitable for reinforcing either deep-drawn or ultra-deep drawn electrodes. A pair of reinforcing ribs are formed into each of the opposed parallel sides of the sidewall of the electrode to minimize flexure of the opposed sides in the vicinity of the studs, which are attached to the sidewall and embedded into the glass support rods, so as to minimize deleterious displacement, i.e., "oil-canning" of the electrode. However, the reinforcing ribs formed in the sidewall do nothing to provide a flat welding surface for the studs. Accordingly, a structure is desired which simultaneously strengthens the sidewall of the electrode while providing a flat surface for attachment of the studs.

In accordance with the invention, an electron gun

assembly for a cathode-ray tube includes a plurality of electrodes longitudinally spaced along and attached to a plurality of insulative support means. The electrodes include at least one substantially cup-shaped member having a base portion at one end, a supporting flange portion substantially parallel to said base portion at the oppositely disposed other end and a sidewall extending therebetween. Attachment means are secured to the sidewall to facilitate attaching the cup-shaped member to the insulative support means. The electron gun assembly is characterised in that the sidewall includes strengthening means comprising at least one coined area formed therein for providing a substantially flat welding surface having structural rigidity for securing the attachment means thereto.

In the drawings:

FIG. 1 is a partial broken-away side elevational view of an electron gun assembly incorporating a novel cup-shaped electrode having strengthening means.

FIG. 2 is a front elevational view of the novel electrode of FIG. 1.

FIG. 3 is a partially broken-away side elevational view of the novel electrode.

FIG. 1 shows structural details of an improved six-electrode inline electron gun assembly 10 centrally mounted in the neck 11 of a cathode-ray tube (CRT) 13. The CRT 13 includes an evacuated envelope (mainly not shown) closed at the neck end by a glass stem 15 having a plurality of leads or pins 17 extending therethrough. A faceplate (not shown), having a viewing screen, closes the other end of the envelope. A funnel (not shown) extends between the faceplate and the neck 11 of the envelope.

The inline electron gun assembly 10 is designed to generate and focus three electron beams along spaced, co-planar convergent beam paths having a common, generally longitudinal direction toward the viewing screen. The gun assembly 10 comprises two insulative support means 23 which are preferably glass support rods from which the various components are supported to form a coherent unit in a manner commonly used in the art. These components include three substantially equally transversely-spaced, co-planar cathodes 25 (one for producing each beam), a first electrode 27 (also referred to as G1), a second electrode 29 (also referred to as G2), a third electrode 31 (also referred to as G3), a fourth electrode 33 (also referred to as G4), a fifth electrode 35 (also referred to as G5), a sixth electrode 37 (also referred to as G6), and a shield cup 39, longitudinally-spaced, in that order, along the support rods 23. In FIG. 1, the common plane of the cathodes 25 is perpendicular to the plane of the drawing.

The electrodes 35 and 37 form the main focusing lens of the electron gun assembly 10. The various electrodes of the gun assembly 10 are electrically

connected to the pins 17 either directly or through metal ribbons 41. The gun assembly 10 is held in a predetermined position in the neck 11 on the pins 17, and with snubbers 43 on the shield cup 39 which press-on and make contact with an electrically conductive coating 45 on the inside surface of the neck 11. The conductive coating 45 extends over the inside surface of the funnel and is connected to an anode button (not shown). A conventional getter assembly (also not shown) is attached at one end to the cup 39 and extends in cantilever fashion in the funnel of the envelope.

The G5 electrode 35 comprises a focus electrode as does the G3 electrode 31 which is electrically connected to the G5 electrode. The electrode 35 comprises first and second substantially rectangular cup-shaped members 47 and 49, respectively. The cup-shaped members are joined together at their open ends. The first cup-shaped member 47 is shown in FIGS. 2 and 3. The cup-shaped member 47 is a deep-drawn part comprising a supporting flange portion 51, located at the open end, and a base portion 53 at the opposite end. The base portion 53 is substantially parallel to the supporting flange portion 51. Three inline apertures 55 are formed through the base portion 53, although only one aperture is shown in FIG 3. A sidewall 57, having substantially parallel opposed sides 59a and 59b and opposed end portions 61a and 61b, extends between the supporting flange portions 51 and the base portion 53 of the cup-shaped member 47. A plurality of attachment tabs 63 are formed in the supporting flange portion 51 adjacent to the opposite sides 59a and 59b of the sidewall 57 to facilitate attachment of the cup-shaped member 47 to the glass support rods 23. As shown in FIGS 1 and 3, a pair of studs 65 are attached to the sidewall 57 of the cup-shaped member 47, one stud to each of the opposed sides 59a and 59b. The studs 65 and the attachment tabs 63 are embedded into the support rods 23. As described above, deep-drawn electrodes, such as the cup-shaped member 47, have a tendency to "oil-can", i.e., bow either inwardly or outwardly, unless the sidewall is strengthened. One means of strengthening or reinforcing the sidewall is described in the abovementioned U.S. Pat No. 4,595,858. In that patent, as discussed above, a pair of reinforcing ribs are formed into each of the opposed sides of the sidewall. However, the reinforcing ribs do not provide a flat support surface for attaching the studs to the sidewall, with the result that some side-to-side displacement or offset of the deep-drawn electrode occurs relative to the other electrodes of the electron gun. This provides some distortion in electron beam trajectories.

The present invention addresses both the problem of strengthening the opposed sides 59a and 59b of the sidewall 57 of the deep-drawn cup-shaped member 47, as well as that of providing a flat, geomet-

rically consistent welding surface for the attachment of the studs 65. A coined welding area 67 is formed in each of the opposed sides 59a and 59b of the sidewall 47. The coined area 67 is centrally located in each of the opposed sides 59a and 59b, and is slightly larger in size than the studs 65 to permit the studs to be located within an innermost portion 69 of the coined area. "Coining", as is known in the art, is the process of forming metal by squeezing between two dies so as to impress a well-defined imprint on one or both surfaces. With the cup-shaped electrode member 47 positioned on the last extruding die (not shown), a pair of dies (also not shown) contact the opposed sides 59a and 59b to squeeze the portions 67 of the sidewall therebetween to imprint the substantially flat, geometrically consistent welding surface 69 therein. The "coining" work-hardens and strengthens the affected portions of the sidewall 57, while providing substantially flat welding surfaces for the attachment of the studs 65. The coined area 67 is shown in FIG 3 as formed only in the exterior surface of the side 59a. An inward projection of the coined area can be achieved by having a mating recess formed in an inner die; however, the present structure is cost effective and provides the necessary structural strength or rigidity and flatness.

Claims

1. An electron gun assembly for use in a cathode-ray tube, said gun assembly including a plurality of electrodes longitudinally spaced along and attached to a plurality of insulative support means, said electrodes including at least one substantially cup-shaped member having a base portion at one end, a supporting flange portion substantially parallel to said base portion at the oppositely disposed other end and a sidewall extending therebetween, and attachment means secured to said sidewall to facilitate attaching said cup-shaped member to said insulative support means; characterized in that said sidewall (57) includes strengthening means (67) comprising at least coined area formed therein for providing a substantially flat welding surface (69) having structural rigidity for securing said attachment means (65) thereto.
2. The electron gun assembly of claim 1, characterized in that said attachment means comprises at least one stud (65).
3. An inline electron gun assembly for use in a cathode-ray tube, said gun assembly including three co-planar cathodes, a G1 electrode, a G2 electrode and at least two focus electrodes longitudinally spaced along and attached to at least two

glass support rods, at least one of the focus electrodes comprising a first and a second substantially rectangular cup-shaped member joined together at their open ends, at least one of said cup-shaped members having a supporting flange portion located at the open end and a base portion located at the opposite end, said base portion being substantially parallel to said supporting flange portion and being connected thereto by a sidewall having opposed sides and opposed end portions, said base portion having three inline apertures therethrough, and at least two studs attached to said sidewall, one stud being attached to each of said opposed sides, and said studs being embedded into said glass support rods to secure said cup-shaped member thereto; characterized in that said sidewall (57) includes a pair of coined welding areas (67) formed in each of said opposed sides (59a, 59b) of said sidewall to strengthen said sidewalls and to provide a geometrically consistent, substantially flat welding surface (69) for attachment of said studs.

Patentansprüche

1. Elektronenkanonenanordnung für die Verwendung in einer Elektronenstrahlröhre mit einer Vielzahl von in Längsrichtung einen Abstand voneinander aufweisenden und an einer Vielzahl von isolierenden Trägermitteln angebrachten Elektroden, wobei die Elektroden wenigstens ein im wesentlichen schalenförmiges Element enthalten, das ein Basisteil an einem Ende, einen Lagerflanschteil im wesentlichen parallel zu dem Basisteil an dem gegenüberliegenden anderen Ende und eine sich dazwischen erstreckende Seitenwand aufweist, wobei Befestigungsmittel an der Seitenwand angebracht sind, um die Befestigung des schalenförmigen Elements an den isolierenden Trägermitteln zu erleichtern, dadurch gekennzeichnet, daß die Seitenwand (57) Verstärkungsmittel (67) einschließt, die wenigstens einen darin gebildeten geprägten Bereich umfassen, um eine im wesentlichen ebene Schweißfläche (69) zu bilden, die eine bauliche Steifigkeit zur Anbringung der Befestigungsmittel (65) an ihr hat.
2. Elektronenkanonenanordnung nach Anspruch 1, dadurch gekennzeichnet, daß die Befestigungsmittel wenigstens einen Ansatz (65) umfassen.
3. Inline-Elektronenkanonenanordnung für die Verwendung in einer Kathodenstrahlröhre, wobei die Elektronenkanonenanordnung drei koplanare Elektroden enthält, eine G1-Elektrode, eine G2-Elektrode und wenigstens zwei Fokussierungs-



rically consistent welding surface for the attachment of the studs 65. A coined welding area 67 is formed in each of the opposed sides 59a and 59b of the sidewall 47. The coined area 67 is centrally located in each of the opposed sides 59a and 59b, and is slightly larger in size than the studs 65 to permit the studs to be located within an innermost portion 69 of the coined area. "Coining", as is known in the art, is the process of forming metal by squeezing between two dies so as to impress a well-defined imprint on one or both surfaces. With the cup-shaped electrode member 47 positioned on the last extruding die (not shown), a pair of dies (also not shown) contact the opposed sides 59a and 59b to squeeze the portions 67 of the sidewall therebetween to imprint the substantially flat, geometrically consistent welding surface 69 therein. The "coining" work-hardens and strengthens the affected portions of the sidewall 57, while providing substantially flat welding surfaces for the attachment of the studs 65. The coined area 67 is shown in FIG 3 as formed only in the exterior surface of the side 59a. An inward projection of the coined area can be achieved by having a mating recess formed in an inner die; however, the present structure is cost effective and provides the necessary structural strength or rigidity and flatness.

Claims

1. An electron gun assembly for use in a cathode-ray tube, said gun assembly including a plurality of electrodes longitudinally spaced along and attached to a plurality of insulative support means, said electrodes including at least one substantially cup-shaped member having a base portion at one end, a supporting flange portion substantially parallel to said base portion at the oppositely disposed other end and a sidewall extending therebetween, and attachment means secured to said sidewall to facilitate attaching said cup-shaped member to said insulative support means; characterized in that said sidewall (57) includes strengthening means (67) comprising at least coined area formed therein for providing a substantially flat welding surface (69) having structural rigidity for securing said attachment means (65) thereto.
2. The electron gun assembly of claim 1, characterized in that said attachment means comprises at least one stud (65).
3. An inline electron gun assembly for use in a cathode-ray tube, said gun assembly including three co-planar cathodes, a G1 electrode, a G2 electrode and at least two focus electrodes longitudinally spaced along and attached to at least two

glass support rods, at least one of the focus electrodes comprising a first and a second substantially rectangular cup-shaped member joined together at their open ends, at least one of said cup-shaped members having a supporting flange portion located at the open end and a base portion located at the opposite end, said base portion being substantially parallel to said supporting flange portion and being connected thereto by a sidewall having opposed sides and opposed end portions, said base portion having three inline apertures therethrough, and at least two studs attached to said sidewall, one stud being attached to each of said opposed sides, and said studs being embedded into said glass support rods to secure said cup-shaped member thereto; characterized in that said sidewall (57) includes a pair of coined welding areas (67) formed in each of said opposed sides (59a, 59b) of said sidewall to strengthen said sidewalls and to provide a geometrically consistent, substantially flat welding surface (69) for attachment of said studs.

Patentansprüche

1. Elektronenkanonenanordnung für die Verwendung in einer Elektronenstrahlröhre mit einer Vielzahl von in Längsrichtung einen Abstand voneinander aufweisenden und an einer Vielzahl von isolierenden Trägermitteln angebrachten Elektroden, wobei die Elektroden wenigstens ein im wesentlichen schalenförmiges Element enthalten, das ein Basisteil an einem Ende, einen Lagerflanschteil im wesentlichen parallel zu dem Basisteil an dem gegenüberliegenden anderen Ende und eine sich dazwischen erstreckende Seitenwand aufweist, wobei Befestigungsmittel an der Seitenwand angebracht sind, um die Befestigung des schalenförmigen Elements an den isolierenden Trägermitteln zu erleichtern, dadurch gekennzeichnet, daß die Seitenwand (57) Verstärkungsmittel (67) einschließt, die wenigstens einen darin gebildeten geprägten Bereich umfassen, um eine im wesentlichen ebene Schweißfläche (69) zu bilden, die eine bauliche Steifigkeit zur Anbringung der Befestigungsmittel (65) an ihr hat.
2. Elektronenkanonenanordnung nach Anspruch 1, dadurch gekennzeichnet, daß die Befestigungsmittel wenigstens einen Ansatz (65) umfassen.
3. Inline-Elektronenkanonenanordnung für die Verwendung in einer Kathodenstrahlröhre, wobei die Elektronenkanonenanordnung drei koplanare Elektroden enthält, eine G1-Elektrode, eine G2-Elektrode und wenigstens zwei Fokussierungs-



elektroden, die an wenigstens zwei Glastragstangen mit einem Abstand voneinander in Längsrichtung angebracht sind, wobei wenigstens eine der Fokussierungselektroden ein erstes und ein zweites im wesentlichen rechteckiges, schalenförmiges Element enthält, und die Elemente an ihren offenen Enden miteinander verbunden sind, wobei wenigstens eines der schalenförmigen Elemente einen stützenden Flanschteil am offenen Ende und ein Basisteil am gegenüberliegenden Ende hat, wobei der Basisteil im wesentlichen parallel zu dem stützenden Flanschteil verläuft und mit diesem durch eine Seitenwand verbunden ist, die gegenüberliegende Seiten und gegenüberliegende Endteile hat, wobei der Basisteil drei in Reihe liegende Durchgangsöffnungen aufweist und wenigstens zwei Ansätze an der Seitenwand angebracht sind, und wobei jeweils ein Ansatz an den gegenüberliegenden Seiten angebracht ist und die Ansätze in die Glastragstangen eingebettet sind, um das schalenförmige Element darin zu befestigen, dadurch gekennzeichnet, daß die Seitenwand (57) zwei geprägte, in den gegenüberliegenden Seiten (59a, 59b) gebildete Schweißbereiche (67) enthält, um die Seitenwände zu versteifen und eine geometrisch konsistente, im wesentlichen ebene Schweißfläche (69) zur Anbringung der Ansätze vorzusehen.

Revendications

1. Système de canons électroniques devant être utilisé dans un tube à rayons cathodiques, ledit système de canons comprenant une pluralité d'électrodes espacées longitudinalement le long d'une pluralité de moyens de support isolants et fixés à ces moyens, lesdits électrodes comprenant au moins un élément sensiblement en forme de coupe ayant une portion de base à une extrémité, une portion de collerette de support sensiblement parallèle à ladite portion de base sur l'autre extrémité disposée à l'opposé et une paroi latérale s'étendant entre ces portions, et des moyens de fixation fixés à ladite paroi latérale afin de faciliter la fixation dudit élément en forme de coupe aux dits moyens de support isolants, caractérisé en ce que ladite paroi latérale (57) comprend des moyens de renforcement (67) comprenant au moins une zone estampée, qui y est formée afin de fournir une surface de soudure sensiblement plate (69) présentant une rigidité structurelle pour y fixer lesdits moyens de fixation (65).
2. Système de canons électroniques selon la revendication 1, caractérisé en ce que lesdits moyens

de fixation comprennent au moins une entretoise.

3. Système de canons électroniques en ligne devant être utilisé dans un tube à rayons cathodiques, ledit système de canons comprenant trois cathodes coplanaires, une électrode G1, une électrode G2 et au moins deux électrodes de focalisation espacées longitudinalement le long de deux tiges supports en verre auxquelles elles sont fixées, l'une au moins des électrodes de focalisation comprenant un premier et un second élément en forme de coupe, sensiblement rectangulaire, raccordés ensemble à leurs extrémités ouvertes, au moins l'un des éléments en forme de coupe ayant une portion de collerette de support située à l'extrémité ouverte et une portion de base située à l'extrémité opposée, ladite portion de base étant sensiblement parallèle à ladite portion de collerette de support et y étant connectée par une paroi latérale ayant des côtés opposés et des portions et extrémités opposées, ladite portion de base ayant trois ouvertures traversantes en ligne et au moins deux entretoises fixées à ladite paroi latérale, l'une des entretoises étant fixée à chacun desdits côtés opposés, et lesdites entretoises étant noyées dans lesdites tiges de support en verre pour y assurer la fixation dudit élément en forme de coupe, caractérisé en ce que ladite paroi latérale (57) comporte une paire de zones de soudure estampées (67) formées dans chacun desdits côtés opposés (59a, 59b) de ladite paroi latérale pour renforcer lesdites parois latérales et fournir une surface de soudure géométriquement consistante et sensiblement stable (69) pour la fixation desdites entretoises.