



(51) International Patent Classification:

E21B 43/10 (2006.01) *E21B 33/12* (2006.01)
E21B 43/08 (2006.01)

(21) International Application Number:

PCT/US2013/047731

(22) International Filing Date:

25 June 2013 (25.06.2013)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

13/552,647 19 July 2012 (19.07.2012) US

(71) Applicant: **HALLIBURTON ENERGY SERVICES, INC.** [US/US]; 10200 Bellaire Boulevard, Houston, Texas 77072 (US).(72) Inventors: **HOLDERMAN, Luke**; 3709 Campstone Dr., Plano, Texas 75023 (US). **LOPEZ, Jean-Marc**; 7308 Stoddard Lane, Plano, Texas 75025 (US).(74) Agents: **CONLEY ROSE, P.C.** et al.; 5601 Granite Parkway, Suite 500, Plano, Texas 75024 (US).(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM,

AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).


Declarations under Rule 4.17:

— as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))

Published:

— with international search report (Art. 21(3))

(54) Title: SACRIFICIAL PLUG FOR USE WITH A WELL SCREEN ASSEMBLY



(57) Abstract: A well screen assembly for use downhole comprises a fluid pathway configured to provide fluid communication between an exterior of a wellbore tubular and an interior of the wellbore tubular, a flow restrictor disposed in the fluid pathway, and a plug disposed in series with the flow restrictor in the fluid pathway. The plug substantially prevents a fluid flow through the fluid pathway. The plug is configured to be at least partially dissolvable when contacted by a fluid, and the fluid comprises a chemical configured to dissolve the plug.

