

Description

A tool is disclosed in U.S. 4 089 104 for mounting a card edge connector onto a printed circuit board; i.e. driving or inserting the two rows of aligned contact pins depending from the connector into plated-through holes in the board. The connector housing mounts on the tool and around the previously loaded contacts which are still attached to their selvage strip. The housing functions as a support and guide for the contacts as they are inserted into the holes. The tool, loaded with the housing and contacts, is then lowered, driving the contact pins into the holes in the board. As set forth in the specification the tool includes a rotating clamping bar with related mechanisms for clamping the connector contacts between a pair of connector support members. Further, the tool includes a detent subassembly and its related mechanism for engaging apertures in the selvage strips for locating and initially retaining the contacts. The tool further includes a latching subassembly and its related mechanism for retaining the housing after it is placed onto the tool over the already loaded contacts. The selvage strips are removed from the contacts after the connector has been mounted on the board.

The present invention is intended to provide an improvement to an insertion tool which is substantially simplified for inserting or driving the depending contact pins of a preassembled card edge connector into the holes in the board.

According to the present invention, in an improvement to a tool for mounting a connector having contacts with contact pins into a printed circuit board, said tool comprising a housing containing a plurality of depending push pins arranged in identical spacing as the contacts, said improvement is characterised in that a vertically sliding shaft in the housing with a guide block is attached to the free end of the shaft below the housing, said guide block having a plurality of holes extending vertically therethrough with the holes being arranged to conformably receive the push pins therethrough so that as the guide block is placed on top of the connector the push pins are guided by the holes in said guide block into the connector to engage shoulders on the contact pins against which an insertion force may be applied by the tool to drive the contact pins into holes in the circuit board.

For a better understanding of the invention, reference will now be made by way of example to the accompanying drawings, in which:

Figure 1 is a perspective and exploded view of an insertion tool module with the improvement therefor constructed in accordance with the present invention;

Figure 2 is a perspective view of the tool module and improvement assembled together;

Figure 3 is a perspective view showing several improved tool modules joined together and mounted on an arbor press for driving the contact pins of a card edge connector into a printed circuit board; and

Figures 4 through 7 are cross-sectional views showing the several steps in driving the contact pins into the board.

An insertion tool consists of one or more modules 10 (Figure 2) which includes the components exploded out in Figure 1. These components include housing 12, push pins 14, retaining bar 16, and roll pin 18. The push pins 14 are held in housing 12 by bar 16. Bar 16 in turn is held in the housing by roll pin 18. The bar is shown as having a length greater than the housing to indicate that a number of modules may be mounted on one bar to make an insertion tool of a desired length.

The improvement of the present invention, shown in exploded fashion in Figure 1, includes guide block 20, shaft 22, coil spring 24 and retaining ring 26.

Module 10 must be modified by adding a vertical hole 28 through housing 12 and hole 30 through bar 16.

Guide block 20 is preferably made from glass filled NYLON although other suitable materials can be used. Holes 32 extend vertically through the block on a spacing such as to receive push pins 14 therethrough as shown in Figures 2-7.

A depending, elongated guide member 34 is located on the underside of the block and centered between the sides thereof. The sides of the member are straight for a short distance and then converge in to form a tip 36. The ends of the member are preferably bevelled as indicated by reference numeral 38.

Block 20 further includes a means to centrally receive shaft 22 such as a threaded hole or the like.

The upper end of shaft 22 is circumferentially grooved, indicated by reference numeral 40, to receive retaining ring 26.

Figure 2 shows a one module insertion tool 10 with the improvement of the present invention assembled thereto. First shaft 22 is secured to block 20 by any conventional means. Coil spring 24 is placed on the shaft and the free end of the shaft pushed into housing 12 from below with push pins 14 being guided into holes 32. The shaft is pushed upwardly through hole 30 in bar 16 and hole 28 in housing 12. Upon groove 40 clearing the top of housing 12, retaining ring 26 is located therein to lock the improvement to the module.

Figure 3 shows a press 42 having a vertically moving plate 44 to which an insertion tool 10 composed of several modules will be secured with push pins 14 and guide blocks 20 depending therefrom. A printed circuit board 46 is positioned below with a card edge connector 48 thereon ready for the insertion of its pins.

Plate 44 can carry a plurality of insertion tools so that a plurality of connectors 48 can be mounted on board 46 simultaneously.

Figures 4 through 7 illustrate how the improved insertion tool works.

With reference to Figure 4, the pins 50 of contacts 52, depending from connector 48, have been pushed into plated-through holes 54 on

board 46 down to where the retaining sections 56 on the pins are just ready to enter the holes. As is well known, considerable force is required to drive the retaining sections 56 into holes 54. Mylar (Registered Trade Mark) strip 58 on the pins have held them in proper alignment relative to holes 54 during this step which was done manually.

In Figure 4, the insertion tool is shown being lowered with guide block 20 resting on top of connector 48. As the tool was brought down guide member 34 on block 20 entered card edge receiving slot 60 in connector 48 and, if the connector has been placed on the board crooked, the tip straightens it up as it entered the slot.

Figure 5 shows the tool being lowered further with push pins 14 entering connector 48 with holes 32 in guide block 20 aligning them with the upper portions 62 of contacts 50. Coil spring 24 is being compressed and shaft 22 is rising above housing 12.

In Figure 6, the guided push pins 14 have landed and bottomed out on shoulders 64 on contacts 50. Further, housing 12 has bottomed out on block 20. Accordingly, further downward travel of tool 10 drives retaining sections 56 into holes 54 in board 46. The predominant driving force is on shoulders 64 so that connector housing 66 will not be damaged.

Figure 7 shows tool 10 being withdrawn. As it does so, coil spring exerts a downward force on connector 48 through block 20. Thus, any frictional drag between push pins 14 and the connector will not dislodge the connector.

Claims

1. An improvement to a tool (10) for mounting a connector (48) having contacts (52) with contact pins (50) onto a printed circuit board (26), said tool (10) comprising a housing (12) containing a plurality of depending push pins (14) arranged in identical spacing as the contacts (52), said improvement characterised in providing a vertically sliding shaft (22) in the housing (12) with a guide block (20) attached to the free end of the shaft (22) below the housing (12), said guide block (20) having a plurality of holes (32) extending vertically therethrough with the holes (32) being arranged to conformably receive the push pins (14) therethrough so that as the guide block (20) is placed on top of the connector (48) the push pins (14) are guided by the holes (32) in said guide block (20) into the connector (48) to engage shoulders (64) on the contact pins (50) against which an insertion force may be applied by the tool (10) to drive the contact pins (50) into holes (54) in the circuit board (46).

2. The improvement of claim 1 further including a coil spring (24) mounted on the shaft (22) between the housing (12) and the guide block (20) and compressible therebetween as the push pins (14) are driven against the contact pin shoulders (64) so that the coil spring (24) biases the guide block (20) against the top of the connector (48) to

steady it as the push pins (14) are withdrawn therefrom.

3. The improvement of claims 1 or 2 further including an elongated member (34) on and depending from the underside of guide block (20), said member (34) having a tip (36) for entering the card edge receiving slot (60) in the connector (48) to align the connector (48) with the guide block (20).

Revendications

1. Perfectionnement à un outil (10) de montage d'un connecteur (48) comportant des contacts (52) munis de broches (50) de contact sur une plaque (46) à circuit imprimé, ledit outil (10) comprenant un boîtier (12) contenant plusieurs broches de poussée descendantes (14) disposées à un espacement identique à celui des contacts (52), ledit perfectionnement caractérisé par la présence d'une tige (22) coulissant verticalement dans le boîtier (12), un bloc (20) de guidage étant fixé à l'extrémité libre de la tige (22) au-dessous du boîtier (12), ledit bloc (20) de guidage étant traversé verticalement de plusieurs trous (32) qui sont disposés de façon à recevoir de manière complémentaire les broches (14) de poussée afin que, lorsque le bloc (20) de guidage est placé sur le dessus du connecteur (48), les broches (14) de poussée soient guidées par les trous (32) dudit bloc (20) de guidage vers l'intérieur du connecteur (48) pour porter sur des épaulements (64) situés sur les broches (50) de contact et contre lesquels une force d'insertion peut être appliquée par l'outil (10) pour introduire les broches (50) de contact dans des trous (54) de la plaquette (46) à circuit.

2. Perfectionnement selon la revendication 1, contenant en outre un ressort hélicoïdal (24) monté sur la tige (22) entre le boîtier (12) et le bloc (20) de guidage et pouvant être comprimé entre eux pendant que les broches (14) de poussée sont introduites en portant contre les épaulements (64) des broches de contact afin que le ressort hélicoïdal (24) rappelle le bloc (20) de guidage contre le dessus du connecteur (48) pour maintenir ce dernier de façon stable au moment les broches (14) de poussée en sont tirées.

3. Perfectionnement selon la revendication 1 ou 2, comprenant en outre un élément allongé (34) faisant saillie vers le bas de la face inférieure du bloc (20) de guidage, ledit élément (34) présentant une pointe (36) destinée à entrer dans la fente (60) de réception d'un bord de carte, ménagée dans le connecteur (48) afin d'aligner le connecteur (48) avec le bloc (20) de guidage.

Patentansprüche

1. Verbesserung an einem Werkzeug (10) zum Befestigen eines Kontakte (52) mit Kontaktstiften (50) aufweisenden Verbinders (48) auf einer gedruckten Schaltungsplatte (46), wobei das Werkzeug (10) ein Gehäuse (12) aufweist, das eine Mehrzahl sich nach unten erstreckender Drück-

board 46 down to where the retaining sections 56 on the pins are just ready to enter the holes. As is well known, considerable force is required to drive the retaining sections 56 into holes 54. Mylar (Registered Trade Mark) strip 58 on the pins have held them in proper alignment relative to holes 54 during this step which was done manually.

In Figure 4, the insertion tool is shown being lowered with guide block 20 resting on top of connector 48. As the tool was brought down guide member 34 on block 20 entered card edge receiving slot 60 in connector 48 and, if the connector has been placed on the board crooked, the tip straightens it up as it entered the slot.

Figure 5 shows the tool being lowered further with push pins 14 entering connector 48 with holes 32 in guide block 20 aligning them with the upper portions 62 of contacts 50. Coil spring 24 is being compressed and shaft 22 is rising above housing 12.

In Figure 6, the guided push pins 14 have landed and bottomed out on shoulders 64 on contacts 50. Further, housing 12 has bottomed out on block 20. Accordingly, further downward travel of tool 10 drives retaining sections 56 into holes 54 in board 46. The predominant driving force is on shoulders 64 so that connector housing 66 will not be damaged.

Figure 7 shows tool 10 being withdrawn. As it does so, coil spring exerts a downward force on connector 48 through block 20. Thus, any frictional drag between push pins 14 and the connector will not dislodge the connector.

Claims

1. An improvement to a tool (10) for mounting a connector (48) having contacts (52) with contact pins (50) onto a printed circuit board (26), said tool (10) comprising a housing (12) containing a plurality of depending push pins (14) arranged in identical spacing as the contacts (52), said improvement characterised in providing a vertically sliding shaft (22) in the housing (12) with a guide block (20) attached to the free end of the shaft (22) below the housing (12), said guide block (20) having a plurality of holes (32) extending vertically therethrough with the holes (32) being arranged to conformably receive the push pins (14) therethrough so that as the guide block (20) is placed on top of the connector (48) the push pins (14) are guided by the holes (32) in said guide block (20) into the connector (48) to engage shoulders (64) on the contact pins (50) against which an insertion force may be applied by the tool (10) to drive the contact pins (50) into holes (54) in the circuit board (46).

2. The improvement of claim 1 further including a coil spring (24) mounted on the shaft (22) between the housing (12) and the guide block (20) and compressible therebetween as the push pins (14) are driven against the contact pin shoulders (64) so that the coil spring (24) biases the guide block (20) against the top of the connector (48) to

steady it as the push pins (14) are withdrawn therefrom.

3. The improvement of claims 1 or 2 further including an elongated member (34) on and depending from the underside of guide block (20), said member (34) having a tip (36) for entering the card edge receiving slot (60) in the connector (48) to align the connector (48) with the guide block (20).

Revendications

1. Perfectionnement à un outil (10) de montage d'un connecteur (48) comportant des contacts (52) munis de broches (50) de contact sur une plaque (46) à circuit imprimé, ledit outil (10) comprenant un boîtier (12) contenant plusieurs broches de poussée descendantes (14) disposées à un espacement identique à celui des contacts (52), ledit perfectionnement caractérisé par la présence d'une tige (22) coulissant verticalement dans le boîtier (12), un bloc (20) de guidage étant fixé à l'extrémité libre de la tige (22) au-dessous du boîtier (12), ledit bloc (20) de guidage étant traversé verticalement de plusieurs trous (32) qui sont disposés de façon à recevoir de manière complémentaire les broches (14) de poussée afin que, lorsque le bloc (20) de guidage est placé sur le dessus du connecteur (48), les broches (14) de poussée soient guidées par les trous (32) dudit bloc (20) de guidage vers l'intérieur du connecteur (48) pour porter sur des épaulements (64) situés sur les broches (50) de contact et contre lesquels une force d'insertion peut être appliquée par l'outil (10) pour introduire les broches (50) de contact dans des trous (54) de la plaquette (46) à circuit.

2. Perfectionnement selon la revendication 1, contenant en outre un ressort hélicoïdal (24) monté sur la tige (22) entre le boîtier (12) et le bloc (20) de guidage et pouvant être comprimé entre eux pendant que les broches (14) de poussée sont introduites en portant contre les épaulements (64) des broches de contact afin que le ressort hélicoïdal (24) rappelle le bloc (20) de guidage contre le dessus du connecteur (48) pour maintenir ce dernier de façon stable au moment les broches (14) de poussée en sont tirées.

3. Perfectionnement selon la revendication 1 ou 2, comprenant en outre un élément allongé (34) faisant saillie vers le bas de la face inférieure du bloc (20) de guidage, ledit élément (34) présentant une pointe (36) destinée à entrer dans la fente (60) de réception d'un bord de carte, ménagée dans le connecteur (48) afin d'aligner le connecteur (48) avec le bloc (20) de guidage.

Patentansprüche

1. Verbesserung an einem Werkzeug (10) zum Befestigen eines Kontakte (52) mit Kontaktstiften (50) aufweisenden Verbinders (48) auf einer gedruckten Schaltungsplatte (46), wobei das Werkzeug (10) ein Gehäuse (12) aufweist, das eine Mehrzahl sich nach unten erstreckender Drück-



stifte (14) aufweist, die im gleichen Abstand wie die Kontakte (52) angeordnet sind, wobei die Verbesserung dadurch gekennzeichnet ist, daß eine senkrecht verschiebbare Stange (22) in dem Gehäuse (12) mit einem Führungsblock (20) versehen ist, der an dem freien Ende der Stange (22) unterhalb des Gehäuses (12) befestigt ist, wobei der Führungsblock (20) eine Mehrzahl von Öffnungen (32) aufweist, die sich senkrecht durch diesen hindurcherstrecken und derart angeordnet sind, daß die Drückstifte (14) in entsprechender Weise durch diese hindurchführbar sind, so daß dann, wenn der Führungsblock (20) auf der Oberseite des Verbinders (48) plaziert ist, die Drückstifte (14) durch die Öffnungen (32) in dem Führungsblock (20) in den Verbinder (48) eingeführt werden, um an Schultern (64) an den Kontaktstiften (50) anzugreifen, gegen die durch das Werkzeug (10) eine Einsetzkraft ausgeübt werden kann, um die Kontaktstifte (50) in Löcher (54) in der Schaltungsplatte (46) hineinzudrängen.

2. Verbesserung nach Anspruch 1 dadurch gekennzeichnet, daß eine Schraubenfeder (24) vorgesehen ist, die zwischen dem Gehäuse (12) und dem Führungsblock (20) auf der Stange (22) befestigt ist und dazwischen zusammendrückbar ist, wenn die Drückstifte (14) gegen die Kontaktstiftschultern (64) gedrängt werden, so daß die Schraubenfeder (24) den Führungsblock (20) gegen die Oberseite des Verbinders (48) vorspannt, um diesen zu stabilisieren, wenn die Drückstifte (14) von diesem entfernt werden.

3. Verbesserung nach Anspruch 1 oder 2, dadurch gekennzeichnet, daß an der Unterseite des Führungsblocks (20) ein sich von dieser nach unten erstreckendes längliches Glied (34) vorgesehen ist, wobei das Glied (34) eine Spitze (36) zum Eintreten in den Kartenrandaufnahmeschlitz (60) in dem Verbinder (48) aufweist, um den Verbinder (48) mit dem Führungsblock (20) auszurichten.

25

30

35

40

45

50

55

60

65

4



* C L M S *