



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : G01N 27/28, 27/403	A1	(11) International Publication Number: WO 98/43073 (43) International Publication Date: 1 October 1998 (01.10.98)
(21) International Application Number: PCT/AU98/00184 (22) International Filing Date: 20 March 1998 (20.03.98) (30) Priority Data: PO 5813 21 March 1997 (21.03.97) AU (71) Applicant (for all designated States except US): MEMTEC AMERICA CORPORATION [US/US]; Suite 700, 9690 Deereco Road, Timonium, MD 21093 (US). (72) Inventors; and (75) Inventors/Applicants (for US only): CHAMBERS, Garry [AU/AU]; Unit 4, 7 Paget Street, Richmond, NSW 2753 (AU). HODGES, Alastair, McIndoe [AU/AU]; 15 Jasmine Court, Blackburn South, VIC 3130 (AU). BECK, Thomas, William [AU/AU]; 31 Drummond Street, South Windsor, NSW 2756 (AU). MAXWELL, Ian, Andrew [AU/AU]; 3 Whiting Street, Leichhardt, NSW 2040 (AU). (74) Agent: SHELSTON WATERS; 60 Margaret Street, Sydney, NSW 2000 (AU).	(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, GW, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i>	
(54) Title: SENSOR CONNECTION MEANS (57) Abstract The invention relates to a sensor adapted for electrical connection to a power source having an electrical contact means (3). The sensor has a first insulating substrate (1) carrying a first electrode (2) and a second insulating substrate (7) carrying a second electrode (6). The electrodes are disposed to face each other in spaced apart relationship, sandwiching a spacer (4) therebetween. A first cut-out portion extends through the first insulating substrate (1) and a spacer (4) to expose a first contact area (23) on the second insulating substrate (7). This permits the electrical contact means (31) to effect electrical connection with the first contact (23) which in turn is in electrically conductive connection with the second electrode (6). A similar contact arrangement may be disposed on the opposite side of the sensor.		