

TITLE

Drum for a creasing device

DESCRIPTIONTechnical Field

This invention relates to the drum that mounts a resilient creasing ring in a device for creasing stock such as paper, card, film, foil or other sheet material to enable it to be easily folded. The device is especially well suited for fitting to the output of a printing machine or the input of a folding machine but it can also be used in a stand-alone creasing machine or in other contexts.

Background

A high percentage of printed stock such as book covers or greetings cards needs to be creased before the next operation of folding can be carried out.

A known device for creasing stock is described in international patent application WO 00/55080. The device consists of a first drum mounted on a first rotary shaft, the first drum having at least one groove for holding a resilient ring that protrudes from the groove. A second drum is mounted on a second, parallel rotary shaft and has at least one corresponding groove. When the resilient ring protruding from the first drum is aligned with the groove of the second drum, a sheet of the stock fed between the two rotating drums will be creased by the pressure of the resilient ring deforming the paper into the groove of the second drum.

The first and second parallel shafts may conveniently be the top and bottom shafts of a conventional folding machine. The first drum is clamped on the first shaft so that the drum and the resilient ring rotate with the shaft. The second drum may be clamped on the second shaft with the corresponding grooves in alignment. Alternatively, as described in international patent application WO 2004/073966, the second drum may be mounted on bearings so that it can rotate independently of the

second shaft and in a preferred arrangement can also slide axially along the second shaft.

A first problem with the aforementioned prior art is that the resilient ring must be stretched beyond its working diameter in order to pass over the outer surface of the drum and reach the groove. Despite the resilience of the ring, this stretching – particularly if done repeatedly during the lifetime of the ring – may cause the ring to lengthen so that it does not retract fully into the groove and does not have sufficient tension to grip the groove tightly. As a result, creasing may become less reliable and – because a loosely held ring is continuously deformed as the drum turns – the lifetime of the ring may be shortened.

A second problem with the aforementioned prior art is that a new ring can only be added to the creasing device by removing the shaft from the machine in which it is mounted. Although the device may provide space for storage of spare rings, their lifetime is limited and the rings will eventually need to be replaced. The difficulty of removing the shaft varies between machines but is always a time-consuming operation, during which the entire machine cannot be used for any of its functions.

Summary of the invention

The invention provides a drum for a creasing device, comprising a first drum part having a cylindrical outer surface and a bore for mounting the first drum part about a shaft; and a second drum part having a cylindrical outer surface and a bore for mounting the second drum part about the shaft; wherein the first and second drum parts are shaped such that the two drum parts may abut one another to define between them the base and two side walls of a channel for receiving a resilient creasing ring; and wherein at least one side wall of the channel is recessed so that a resilient creasing ring located in the channel and projecting laterally into the recess cannot be withdrawn radially from the channel.

Forming the drum in two parts, with the channel defined at the junction of the two parts, allows the drum to be assembled round the resilient creasing ring, rather than

stretching the ring to pass around the drum. In particular, the ring may be slid into place against the first drum part by a predominantly axial movement, so that the ring is not stretched beyond its working diameter, before the second drum part is brought into abutment to complete the channel. Preferably, the first drum part is shaped to define the base and one side wall of the channel; while the second drum part is shaped to define the other side wall of the channel. This allows the ring to be seated securely against the base of the channel before the second drum part is brought into abutment.

Once the two drum parts are locked in their abutting relationship to define the channel between them, the interlocking geometry of the recessed channel walls and the ring holds the ring in place in the channel. It is no longer required that the ring be under tension to hold it in place so a split ring can be used and can be added to the device without removing the shaft from the machine in which it is mounted.

To achieve the purpose of the recess – that a resilient creasing ring located in the channel and projecting laterally into the recess cannot be withdrawn radially from the channel – it is sufficient that, when the channel is viewed looking radially inwards, some part of the channel is hidden from view. This includes but is not limited to the case where the mouth of the channel is the narrowest part. “Recess” and cognate words are used in this specification in that sense.

Preferably the cross section of the channel has a generally flat base and two side walls converging from their junction with the base towards the mouth of the channel. Such a channel can accommodate a resilient ring of “dovetail” cross-section and it allows the flat base to be the widest part of the channel, whereby the ring is securely located and retained within the channel.

In a preferred embodiment of drum according to the invention, the first drum part has an outwardly facing guide surface of smaller radius than the outer cylindrical surface; and the second drum part has an inwardly facing surface that slides on the guide surface of the first drum part to bring the two drum parts into axial abutment. The guide surface of the first drum part may ramp up to the base of the channel to assist in

expanding a continuous resilient ring to its working diameter; or the guide surface may be a cylindrical surface that also forms the base of the channel to assist in locating a split ring.

The second drum part may be in the form of a collar that slides solely on the guide surface of the first drum part, the inwardly facing surface of the second drum part being constituted by the bore of the second drum part.

The invention also provides a resilient creasing ring for a creasing device, the ring comprising a radially projecting creasing rib and at least one lateral rib for location in a recessed side wall of a channel in a drum of the creasing device. As previously described, the ring may be split to form two abutting ends to make it possible to add the ring to the device without dismounting the shaft.

Finally, the invention provides a method of mounting a resilient creasing ring in the drum of a creasing device, comprising the steps of locating the resilient creasing ring against a base and one side wall of a channel defined by a first drum part; and axially sliding a second drum part into abutment with the first drum part, whereby the resilient creasing ring is also located against a second side wall of the channel defined by the second drum part.

The drawings

Figure 1 illustrates a first embodiment of drum according to the invention, the upper half being shown in longitudinal section.

Figure 2 illustrates a second embodiment of drum according to the invention, the upper half being shown in longitudinal section.

Figure 3 illustrates alternative channel cross sections for use in a creasing device according to the invention.

Figure 1 shows a drum 2 mounted on a rotary shaft 4 which forms part of a creasing device. The drum 2 defines a channel 6 in which is received a resilient creasing ring 8 such that a creasing rib 10 of the ring 8 projects above a cylindrical outer surface 12

of the drum 2. In use, the illustrated drum 2 is placed adjacent to another, female drum (not shown) mounted on a second, parallel shaft (not shown), as is well known from the prior art. The female drum may be fixedly mounted for rotation with the second shaft but preferably it is free to rotate independently of the second shaft and to slide axially along the second shaft. The female drum has at least one circumferential groove around its cylindrical outer surface, which receives the creasing rib 10. As the male drum 2 of this invention rotates and the female drum counter-rotates, a sheet of paper, card or other stock fed between the creasing rib 10 of the male drum and the circumferential groove of the female drum then is deformed and creased.

The drum 2 shown in Figure 1 itself has a circumferential groove 13 in the outer surface 12. This allows an identical drum 2 to be used, inverted, as the female drum on the second shaft to form a crease. Moreover, if the identical drum also carries a creasing ring 8, then the creasing rib 10 of each drum can engage the groove 13 of the other drum so as to form a closely spaced pair of creases (e.g. 6mm apart), one up and one down, which is useful for applications such as the covers of catalogues and directories.

The drum 2 comprises a first drum part 14 and a second drum part 15. Each drum part 14,15 is annular in shape with a central bore that fits closely around the shaft 4. Grub screws 16,17 can be tightened to clamp the respective drum parts 14,15 to the shaft 4 or loosened to allow the drum parts 14,15 to slide along the shaft 4.

The channel 6 for retaining the creasing ring 8 (shown also in Figure 3a) is located in the outer surface 12 of the drum 2 at the junction between the two drum parts 14,15. The first drum part 14 defines the base 18 and a first side wall 20 of the channel 6, while the second drum part defines a second side wall 21 of the channel 6. The base 18 of the channel is formed by part of an outwardly facing, cylindrical guide surface 22 of the first drum part 14, which has a smaller radius than the cylindrical outer surface 12. The second drum part 15 has a corresponding, inwardly facing, cylindrical guide surface 24, which slides along the guide surface 22 of the first part until facing end surfaces of the respective parts 14,15 come into abutment.

The channel 6 has a generally rectangular cross section but each side wall 20,21 has an undercut 26, whereby the channel 6 is wider at its base 18 than at its mouth. The resilient creasing ring 8 has a corresponding cross section, with a broad base tapering to a narrower body. Alternatively, this can be viewed as a body of generally rectangular cross section with lateral ribs 27 extending into the undercut recesses 26 of the side walls 20,21 of the channels 6. The creasing rib 10 projects radially outwardly from the creasing ring 8; and on each side of the creasing rib 10 is an outwardly facing resilient surface 28. The resilient surface stands very slightly proud of the cylindrical outer surface 12 of the drum 2 so that it can provide traction to stock that is fed through the creasing device and assist or replace dedicated traction bands known in the prior art.

Because the creasing ring 8 will be held in place by the interlocking geometry of the recessed side walls 20,21 of the channel 6 and the lateral ribs 27 of the ring 8, the creasing ring 8 does not need to be under tension around the drum 2. Therefore the creasing ring 8 may be split at a point 30 around its circumference. The split may be formed either by moulding the ring originally with the split in place or by moulding a continuous ring which is subsequently cut. Alternatively, if the thickness of the ring and the curvature of the channel are not too great, then the ring 8 may be moulded or extruded as a straight strip and subsequently wrapped around the drum 2 to form a ring *in situ*.

The drum 2 is assembled in the following manner. The two drum parts 14,15 are mounted on the shaft 4 and the grub screw 16 is tightened to lock the first drum part 14 in the correct axial position for a creasing ring 8 located in the channel 6 to form a crease at the desired point. Next a creasing ring 8 is located on the first drum part 14. The ends of the ring 8 may be separated at the split 30 and the resilient ring 8 deformed to pass the gap between the ends over the shaft. The base of the ring 8 is then wrapped around the guide surface 22 of the first part 14 and slid axially so that the ring 8 engages the side wall 20 of the channel 6 with a lateral rib 27 located in the undercut recess 26. The two ends of the split ring 8 should meet perfectly so that

there is no gap in the creasing rib 10. Next, the second drum part 15 is slid axially along the shaft 4 and along the guide surface 22 of the first drum part 14 until the facing end surfaces of the respective parts 14,15 abut one another, at which point the second lateral rib 27 of the creasing ring 8 is located in the undercut 26 of the second side wall 21 of the channel 6. The grub screw 17 is tightened to lock the second drum part 15 in position. The sequence may be reversed to remove or exchange a creasing ring 8.

Figure 2 illustrates an embodiment of the invention similar to that shown in Figure 1. Corresponding parts are given the same reference numerals and their description will not be repeated here. The main difference is that in this embodiment the first drum part 14 extends over the whole axial length of the drum 2; and the second drum part 15 does not contact the shaft but takes the form of a collar sliding solely on the guide surface 22 of the first drum part.

The cross section in Figure 2 is taken through the grub screws 16 and 17. Grub screw 16 is the same as in Figure 1 and turns in a threaded bore to bear against the shaft 4 and lock the first drum part 14 in position. Compared with Figure 1, grub screw 17 is shorter and does not bear against the shaft 4 but against the first drum part 14. It could bear simply on the guide surface 22 but, as shown, it is preferred that it runs in a keyway 32 cut into the guide surface 22. The keyway 32 could be of any circumferential extent but it is preferred that it should be essentially a linear channel, parallel to the axis, at one circumferential position around the guide surface 22. The keyway 32 stops short of the end of the drum 2 so that when grub screw 17 is loosened slightly, the second drum part 15 can be slid axially along the guide surface 22 of the first drum part 14 until the grub screw 17 reaches the end of the keyway 32. That opens the channel 6 enough for a resilient ring 8 to be inserted or removed but prevents the second drum part 15 from becoming detached from the first drum part 2 without unscrewing the grub screw 17 further.

Figure 3 shows various possible cross sections for the channel 6, though many others can readily be imagined. The junction between the first and second drum parts 14,15

is not shown in these drawings because it may intersect the base 18 of the channel 6 at various points and at various angles.

Figure 3a is an enlargement of the channel 6 of Figures 1 and 2. It has a broad, flat base 18 and the vertical side walls 20,21 are undercut at an angle to intersect the corners of the base 18 and form recesses 26.

Figure 3b shows a variant of the channel 6 in which the side walls 20,21 have no vertical part but are angled from the mouth of the channel to the corners of the base 18 to form recesses 26 over the whole depth of the channel.

Figure 3c shows that the narrowest part of the channel 6 need not be at the mouth.

Figure 3d shows that recesses 26 can be provided even in a channel 6 of constant width, although this asymmetrical shape is not preferred.

Figure 3e shows recesses 26 of semicircular cross section, which do not extend to the base 18 of the channel.

Figure 3f shows a channel 6 of circular cross-section, in which there is no clear boundary between the side walls 20,21 and the base 18. This cross-section still has recesses 26 as previously defined because parts of the channel adjacent to the side walls 20,21 are not visible when viewed from above.

It will be understood that the embodiments of the invention described here are illustrative only and not limiting. In particular, features shown here in separate embodiments may be used together in various combinations.

Although in the illustrated embodiments the second drum part 15 is shown to be sliding on the guide surface 22 of the first drum part 14 and locked in place by a grub screw 17, it could alternatively be mounted via a screw-threaded connection, provided that care is taken to secure the part 15 against unscrewing as the drum 2 rotates.

Means such as a storage channel may be provided in the second drum part or between the second drum part and a similar third drum part (not shown) to store spare resilient creasing rings.

CLAIMS

1. A drum for a creasing device, comprising:
 - a first drum part having a cylindrical outer surface and a bore for mounting the first drum part about a shaft; and
 - a second drum part having a cylindrical outer surface and a bore for mounting the second drum part about the shaft;
 - wherein the first and second drum parts are shaped such that the two drum parts may abut one another to define between them the base and two side walls of a channel for receiving a resilient creasing ring; and
 - wherein at least one side wall of the channel is recessed so that a resilient creasing ring located in the channel and projecting laterally into the recess cannot be withdrawn radially from the channel.
2. A drum according to claim 1, wherein the cross section of the channel has a generally flat base and two side walls converging from their junction with the base towards the mouth of the channel.
3. A drum according to claim 1 or claim 2, wherein the first drum part is shaped to define the base and one side wall of the channel; and the second drum part is shaped to define the other side wall of the channel.
4. A drum according to any preceding claim, wherein the first drum part has an outwardly facing guide surface of smaller radius than the outer cylindrical surface; and the second drum part has an inwardly facing surface that slides on the guide surface of the first drum part.
5. A drum according to claim 4, wherein the guide surface of the first drum part is a cylindrical surface that also forms the base of the channel.
6. A drum according to claim 4 or claim 5, wherein the second drum part is in the form of a collar that slides solely on the guide surface of the first drum part, the inwardly facing surface of the second drum part being constituted by the bore of the second drum part.

7. A resilient creasing ring for a creasing device, wherein the ring is split to form two abutting ends, the ring comprising a radially projecting creasing rib and at least one lateral rib for location in a recessed side wall of a channel in a drum of the creasing device.

8. A resilient creasing ring according to claim 7, further comprising a generally cylindrical traction surface adjacent to the creasing rib.

9. A method of mounting a resilient creasing ring in the drum of a creasing device, comprising the steps of:

locating the resilient creasing ring against a base and a first side wall of a channel defined by a first drum part; and

axially sliding a second drum part into abutment with the first drum part, whereby the resilient creasing ring is also located against a second side wall of the channel defined by the second drum part;

the creasing ring comprising at least one lateral rib, which is thereby located in a recess of at least one of the first and second side walls so that the ring cannot be withdrawn radially from the channel.

10. A method according to claim 9, wherein the resilient creasing ring is split to form two ends and wherein the step of locating the ring includes wrapping the ring around the first drum part to bring the two ends of the ring into mutual abutment in the channel.

11. A drum for a creasing device substantially as described herein, with reference to the drawings.

12. A resilient creasing ring substantially as described herein, with reference to the drawings.