

MANAGING MAKE-UP GAS COMPOSITION VARIATION FOR A HIGH PRESSURE EXPANDER PROCESS

CROSS-REFERENCE TO RELATED APPLICATIONS

5 **[0001]** This application claims the priority benefit of U.S. Provisional Application No. 62/721367, “Managing Make-Up Gas Composition Variation for a High Pressure Expander Process,” filed August 22, 2018; U.S. Provisional Application No. 62/565,725, “Natural Gas Liquefaction by a High Pressure Expansion Process”, filed September 29, 2017; U.S. Provisional Application No. 62/565,733, “Natural Gas Liquefaction by a High Pressure Expansion Process,” filed September 29, 2017; and U.S. Provisional Application No. 62/576,989, “Natural Gas Liquefaction by a High Pressure Expansion Process Using Multiple Turboexpander Compressors”, filed October 25, 2017, the disclosures of which are incorporated by reference herein in their entireties for all purposes.

[0002] This application is related to U.S. Provisional Application No. 62/721375, “Primary Loop Start-up Method for a High Pressure Expander Process”; and U.S. Provisional Application No. 62/721374, “Heat Exchanger Configuration for a High Pressure Expander Process and a Method of Natural Gas Liquefaction Using the Same,” having common ownership and filed on an even date, the disclosures of which are incorporated by reference herein in their entireties for all purposes.

20 BACKGROUND

Field of Disclosure

[0003] The disclosure relates generally to liquefied natural gas (LNG) production. More specifically, the disclosure relates to LNG production at high pressures.

Description of Related Art

25 **[0004]** This section is intended to introduce various aspects of the art, which may be associated with the present disclosure. This discussion is intended to provide a framework to facilitate a better understanding of particular aspects of the present disclosure. Accordingly, it should be understood that this section should be read in this light, and not necessarily as an admission of prior art.

30 **[0005]** Because of its clean burning qualities and convenience, natural gas has become widely used in recent years. Many sources of natural gas are located in remote areas, which are great distances from any commercial markets for the gas. Sometimes a pipeline is available for transporting produced natural gas to a commercial market. When pipeline transportation is not

feasible, produced natural gas is often processed into liquefied natural gas (LNG) for transport to market.

[0006] In the design of an LNG plant, one of the most important considerations is the process for converting the natural gas feed stream into LNG. Currently, the most common liquefaction processes use some form of refrigeration system. Although many refrigeration cycles have been used to liquefy natural gas, the three types most commonly used in LNG plants today are: (1) the "cascade cycle," which uses multiple single component refrigerants in heat exchangers arranged progressively to reduce the temperature of the gas to a liquefaction temperature; (2) the "multi-component refrigeration cycle," which uses a multi-component refrigerant in specially designed exchangers; and (3) the "expander cycle," which expands gas from feed gas pressure to a low pressure with a corresponding reduction in temperature. Most natural gas liquefaction cycles use variations or combinations of these three basic types.

[0007] The refrigerants used in liquefaction processes may comprise a mixture of components such as methane, ethane, propane, butane, and nitrogen in multi-component refrigeration cycles. The refrigerants may also be pure substances such as propane, ethylene, or nitrogen in "cascade cycles." Substantial volumes of these refrigerants with close control of composition are required. Further, such refrigerants may have to be imported and stored, which impose logistics requirements, especially for LNG production in remote locations. Alternatively, some of the components of the refrigerant may be prepared, typically by a distillation process integrated with the liquefaction process.

[0008] The use of gas expanders to provide the feed gas cooling, thereby eliminating or reducing the logistical problems of refrigerant handling, is seen in some instances as having advantages over refrigerant-based cooling. The expander system operates on the principle that the refrigerant gas can be allowed to expand through an expansion turbine, thereby performing work and reducing the temperature of the gas. The low temperature gas is then heat exchanged with the feed gas to provide the refrigeration needed. The power obtained from cooling expansions in gas expanders can be used to supply part of the main compression power used in the refrigeration cycle. The typical expander cycle for making LNG operates at the feed gas pressure, typically under about 6,895 kPa (1,000 psia). Supplemental cooling is typically needed to fully liquefy the feed gas and this may be provided by additional refrigerant systems, such as secondary cooling and/or sub-cooling loops. For example, U. S. Pat. No. 6,412,302 and U. S. Pat. No. 5,916,260 present expander cycles which describe the use of nitrogen as refrigerant in the sub-cooling loop.

[0009] Previously proposed expander cycles have all been less efficient

thermodynamically, however, than the current natural gas liquefaction cycles based on refrigerant systems. Expander cycles have therefore not offered any installed cost advantage to date, and liquefaction cycles involving refrigerants are still the preferred option for natural gas liquefaction.

5 **[0010]** Because expander cycles result in a high recycle gas stream flow rate and high inefficiency for the primary cooling (warm) stage, gas expanders have typically been used to further cool feed gas after it has been pre-cooled to temperatures well below -20 °C using an external refrigerant in a closed cycle, for example. Thus, a common factor in most proposed expander cycles is the requirement for a second, external refrigeration cycle to pre-cool the gas
10 before the gas enters the expander. Such a combined external refrigeration cycle and expander cycle is sometimes referred to as a "hybrid cycle." While such refrigerant-based pre-cooling eliminates a major source of inefficiency in the use of expanders, it significantly reduces the benefits of the expander cycle, namely the elimination of external refrigerants.

[0011] U. S. Patent Application US2009/0217701 introduced the concept of using high
15 pressure within the primary cooling loop to eliminate the need for external refrigerant and improve efficiency, at least comparable to that of refrigerant-based cycles currently in use. The high pressure expander process (HPXP), disclosed in U. S. Patent Application US2009/0217701, is an expander cycle which uses high pressure expanders in a manner distinguishing from other expander cycles. A portion of the feed gas stream may be extracted
20 and used as the refrigerant in either an open loop or closed loop refrigeration cycle to cool the feed gas stream below its critical temperature. Alternatively, a portion of LNG boil-off gas may be extracted and used as the refrigerant in a closed loop refrigeration cycle to cool the feed gas stream below its critical temperature. This refrigeration cycle is referred to as the primary cooling loop. The primary cooling loop is followed by a sub-cooling loop which acts to further
25 cool the feed gas. Within the primary cooling loop, the refrigerant is compressed to a pressure greater than 1,500 psia, or more preferably, to a pressure of approximately 3,000 psia. The refrigerant is then cooled against an ambient cooling medium (air or water) prior to being near isentropically expanded to provide the cold refrigerant needed to liquefy the feed gas.

[0012] Figure 1 depicts an example of a known HPXP liquefaction process **100**, and is
30 similar to one or more processes disclosed in U. S. Patent Application US2009/0217701. In Figure 1, an expander loop **102** (i.e., an expander cycle) and a sub-cooling loop **104** are used. Feed gas stream **106** enters the HPXP liquefaction process at a pressure less than about 1,200 psia, or less than about 1,100 psia, or less than about 1,000 psia, or less than about 900 psia, or less than about 800 psia, or less than about 700 psia, or less than about 600 psia. Typically, the

pressure of feed gas stream **106** will be about 800 psia. Feed gas stream **106** generally comprises natural gas that has been treated to remove contaminants using processes and equipment that are well known in the art.

[0013] In the expander loop **102**, a compression unit **108** compresses a refrigerant stream **109** (which may be a treated gas stream) to a pressure greater than or equal to about 1,500 psia, thus providing a compressed refrigerant stream **110**. Alternatively, the refrigerant stream **109** may be compressed to a pressure greater than or equal to about 1,600 psia, or greater than or equal to about 1,700 psia, or greater than or equal to about 1,800 psia, or greater than or equal to about 1,900 psia, or greater than or equal to about 2,000 psia, or greater than or equal to about 2,500 psia, or greater than or equal to about 3,000 psia, thus providing compressed refrigerant stream **110**. After exiting compression unit **108**, compressed refrigerant stream **110** is passed to a cooler **112** where it is cooled by indirect heat exchange with a suitable cooling fluid to provide a compressed, cooled refrigerant stream **114**. Cooler **112** may be of the type that provides water or air as the cooling fluid, although any type of cooler can be used. The temperature of the compressed, cooled refrigerant stream **114** depends on the ambient conditions and the cooling medium used, and is typically from about 35 °F. to about 105 °F. Compressed, cooled refrigerant stream **114** is then passed to an expander **116** where it is expanded and consequently cooled to form an expanded refrigerant stream **118**. Expander **116** is a work-expansion device, such as a gas expander, which produces work that may be extracted and used for compression. Expanded refrigerant stream **118** is passed to a first heat exchanger **120**, and provides at least part of the refrigeration duty for first heat exchanger **120**. Upon exiting first heat exchanger **120**, expanded refrigerant stream **118** is fed to a compression unit **122** for pressurization to form refrigerant stream **109**.

[0014] Feed gas stream **106** flows through first heat exchanger **120** where it is cooled, at least in part, by indirect heat exchange with expanded refrigerant stream **118**. After exiting first heat exchanger **120**, the feed gas stream **106** is passed to a second heat exchanger **124**. The principal function of second heat exchanger **124** is to sub-cool the feed gas stream. Thus, in second heat exchanger **124** the feed gas stream **106** is sub-cooled by sub-cooling loop **104** (described below) to produce sub-cooled stream **126**. Sub-cooled stream **126** is then expanded to a lower pressure in expander **128** to form a liquid fraction and a remaining vapor fraction. Expander **128** may be any pressure reducing device, including, but not limited to a valve, control valve, Joule Thompson valve, Venturi device, liquid expander, hydraulic turbine, and the like. The sub-cooled stream **126**, which is now at a lower pressure and partially liquefied, is passed to a surge tank **130** where the liquefied fraction **132** is withdrawn from the process as

an LNG stream **134**, which has a temperature corresponding to the bubble point pressure. The remaining vapor fraction (flash vapor) stream **136** may be used as fuel to power the compressor units.

[0015] In sub-cooling loop **104**, an expanded sub-cooling refrigerant stream **138** (preferably comprising nitrogen) is discharged from an expander **140** and drawn through second and first heat exchangers **124**, **120**. Expanded sub-cooling refrigerant stream **138** is then sent to a compression unit **142** where it is re-compressed to a higher pressure and warmed. After exiting compression unit **142**, the re-compressed sub-cooling refrigerant stream **144** is cooled in a cooler **146**, which can be of the same type as cooler **112**, although any type of cooler may be used. After cooling, the re-compressed sub-cooling refrigerant stream is passed to first heat exchanger **120** where it is further cooled by indirect heat exchange with expanded refrigerant stream **118** and expanded sub-cooling refrigerant stream **138**. After exiting first heat exchanger **120**, the re-compressed and cooled sub-cooling refrigerant stream is expanded through expander **140** to provide a cooled stream which is then passed through second heat exchanger **124** to sub-cool the portion of the feed gas stream to be finally expanded to produce LNG.

[0016] U. S. Patent Application US2010/0107684 disclosed an improvement to the performance of the HPXP through the discovery that adding external cooling to further cool the compressed refrigerant to temperatures below ambient conditions provides significant advantages which in certain situations justifies the added equipment associated with external cooling. The HPXP embodiments described in the aforementioned patent applications perform comparably to alternative mixed external refrigerant LNG production processes such as single mixed refrigerant processes. However, there remains a need to further improve the efficiency of the HPXP as well as overall train capacity. There remains a particular need to improve the efficiency of the HPXP in cases where the feed gas pressure is less than 1,200 psia.

[0017] U. S. Patent Application 2010/0186445 disclosed the incorporation of feed compression up to 4,500 psia to the HPXP. Compressing the feed gas prior to liquefying the gas in the HPXP's primary cooling loop has the advantage of increasing the overall process efficiency. For a given production rate, this also has the advantage of significantly reducing the required flow rate of the refrigerant within the primary cooling loop which enables the use of compact equipment, which is particularly attractive for floating LNG applications. Furthermore, feed compression provides a means of increasing the LNG production of an HPXP train by more than 30% for a fixed amount of power going to the primary cooling and sub-cooling loops. This flexibility in production rate is again particularly attractive for floating

LNG applications where there are more restrictions than land based applications in matching the choice of refrigerant loop drivers with desired production rates.

[0018] For LNG production via an HPXP process, the refrigerant used in primary cooling loop needs to be built up during start-up procedures, and must also be made up during normal operation. In known processes, the primary cooling loop refrigerant make-up source may be feed gas or boil-off gas (BOG) from an LNG storage tank. However, the compositions of feed gas and/or BOG gas compositions could change with reservoir conditions and/or gas plant operation conditions. The changes in gaseous refrigerant composition could affect liquefaction performance, causing the process to deviate from optimum operating conditions. If using feed gas for start-up or make-up processes, the primary cooling loop refrigerant should have sufficiently low C_{2+} content to stay at one phase before entering the suction sides of compressors and turboexpander compressors. Furthermore, liquid pooling in the primary loop passages of the main cryogenic heat exchanger could also cause gas mal-distribution, which is undesirable for efficient operation of the main cryogenic heat exchanger. Using BOG as for start-up and and make-up processes, on the other hand, could avoid the issues related to heavy components breakthrough. However, BOG is generally has much higher N_2 content than feed gas. Generally, too high of a nitrogen concentration negatively impacts the effectiveness of the primary loop refrigerant. In addition, the BOG composition is very sensitive to variations in composition of light ends such as nitrogen, hydrogen, helium in the feed gas. As shown in Table 1, an increase in the nitrogen concentration by 0.2% in the feed gas would result in an increase in BOG nitrogen concentration by 2%. For these reasons, there remains a need to manage variations in the feed gas composition during normal operation – both for the light contents (i.e., nitrogen, hydrogen, helium, etc.) and the heavy contents (i.e., C_{2+}). There is also a need to provide for efficient start-up operations of a high-pressure LNG liquefaction process.

25

Table 1. BOG Gas N_2 content sensitivity to the feed gas N_2 content variation

Case	$N_2/(N_2+C_1)$			
	Scrubber Feed	Scrubber OVHD	LNG	BOG
Base	0.56%	0.56%	0.23%	5.8%
1	0.61%	0.62%	0.25%	6.3%
2	0.67%	0.67%	0.27%	6.9%
3	0.72%	0.73%	0.29%	7.4%
4	0.78%	0.78%	0.31%	7.9%

SUMMARY

[0019] According to disclosed aspects, a method is provided for liquefying a feed gas stream rich in methane. According to the method, The feed gas stream is provided at a pressure less than 1,200 psia. A compressed refrigerant stream with a pressure greater than or equal to 1,500 psia is provided. The compressed refrigerant stream is cooled by indirect heat exchange with an ambient temperature air or water, to produce a compressed, cooled refrigerant stream. The compressed, cooled refrigerant stream is expanded in at least one work producing expander, thereby producing an expanded, cooled refrigerant stream. Part or all of the expanded, cooled refrigerant stream is mixed with a make-up refrigerant stream in a separator, thereby condensing heavy hydrocarbon components from the make-up refrigerant stream and forming a gaseous expanded, cooled refrigerant stream. The gaseous expanded, cooled refrigerant stream is passed through a heat exchanger zone to form a warm refrigerant stream. The feed gas stream is passed through the heat exchanger zone to cool at least part of the feed gas stream by indirect heat exchange with the expanded, cooled refrigerant stream, thereby forming a liquefied gas stream. The warm refrigerant stream is compressed to produce the compressed refrigerant stream.

[0020] According to another aspect of the disclosure, a method is provided for liquefying a feed gas stream rich in methane in a system having a first heat exchanger zone and a second heat exchanger zone. A compressed refrigerant stream with a pressure greater than or equal to 1,500 psia is provided. The compressed refrigerant stream is cooled by indirect heat exchange with an ambient temperature air or water to produce a compressed, cooled refrigerant stream. The compressed, cooled refrigerant stream is directed to the second heat exchanger zone to additionally cool the compressed, cooled refrigerant stream below ambient temperature to produce a compressed, additionally cooled refrigerant stream. The compressed, additionally cooled refrigerant stream is expanded in at least one work producing expander, thereby producing an expanded, cooled refrigerant stream. Part or all of the expanded, cooled refrigerant stream is routed to at least one separator, such as a separation vessel. The expanded, cooled refrigerant stream is mixed with a make-up refrigerant gas stream, to thereby condition the make-up refrigerant gas stream by condensing heavy hydrocarbon components therefrom and producing a gaseous overhead refrigerant stream. The gaseous overhead refrigerant stream is combined with the remaining expanded, cooled refrigerant stream to form a cold primary refrigerant mixture. The cold primary refrigerant mixture is passed through the first heat exchanger zone to form a warm refrigerant stream. The warm refrigerant stream may have a temperature that is cooler by at least 5 °F of the highest fluid temperature within the first heat exchanger zone. The heat exchanger type of the first heat exchanger zone is different from the

heat exchanger type of the second heat exchanger zone. The feed gas stream is passed through the first heat exchanger zone to cool at least part of the feed gas stream by indirect heat exchange with the cold primary refrigerant mixture, thereby forming a liquefied gas stream. The warm refrigerant stream is compressed to produce the compressed refrigerant stream.

5 [0021] According to still other aspects of the disclosure, a method is disclosed for liquefying a feed gas stream rich in methane. According to the method, the feed gas stream is provided at a pressure less than 1,200 psia. The feed gas stream is compressed to a pressure of at least 1,500 psia to form a compressed gas stream. The compressed gas stream is cooled by indirect heat exchange with an ambient temperature air or water to form a compressed, cooled
10 gas stream. The compressed, cooled gas stream is expanded in at least one work producing expander to a pressure that is less than 2,000 psia and no greater than the pressure to which the gas stream was compressed, to thereby form a chilled gas stream. A compressed refrigerant stream with a pressure greater than or equal to 1,500 psia is provided. The compressed refrigerant stream is cooled by indirect heat exchange with an ambient temperature air or water
15 to produce a compressed, cooled refrigerant stream. The compressed, cooled refrigerant stream is expanded in at least one work producing expander, thereby producing an expanded, cooled refrigerant stream. Part or all of the expanded, cooled refrigerant stream is routed to at least one separator, such as a separation vessel, and mixing said expanded, cooled refrigerant stream therein with a make-up refrigerant gas stream, to thereby condition the make-up refrigerant gas
20 stream by condensing heavy hydrocarbon components therefrom and producing a gaseous overhead refrigerant stream. The gaseous overhead refrigerant stream is combined with the remaining expanded, cooled refrigerant to form a cold primary refrigerant mixture. The cold primary refrigerant mixture is passed through a heat exchanger zone to form a warm refrigerant stream. The chilled gas stream is passed through the heat exchanger zone to cool at least part
25 of the chilled gas stream by indirect heat exchange with the cold primary refrigerant mixture, thereby forming a liquefied gas stream. The warm refrigerant stream is compressed to produce the compressed refrigerant stream.

[0022] The foregoing has broadly outlined the features of the present disclosure so that the detailed description that follows may be better understood. Additional features will also be
30 described herein.

BRIEF DESCRIPTION OF THE DRAWINGS

[0023] These and other features, aspects and advantages of the disclosure will become apparent from the following description, appending claims and the accompanying drawings, which are briefly described below.

- [0024] Figure 1 is a schematic diagram of a system for LNG production according to known principles.
- [0025] Figure 2 is a schematic diagram of a system for LNG production according to disclosed aspects.
- 5 [0026] Figure 3 is a schematic diagram of a system for LNG production according to disclosed aspects.
- [0027] Figure 4 is a schematic diagram of a system for LNG production according to disclosed aspects.
- [0028] Figure 5 is a schematic diagram of a system for LNG production according to disclosed aspects.
- 10 [0029] Figure 6 is a schematic diagram of a system for LNG production according to disclosed aspects.
- [0030] Figure 7 is a schematic diagram of a system for LNG production according to disclosed aspects.
- 15 [0031] Figure 8 is a schematic diagram of a system for LNG production according to disclosed aspects.
- [0032] Figure 9 is a schematic diagram of a system for LNG production according to disclosed aspects.
- [0033] Figure 10 is a flowchart of a method according to aspects of the disclosure.
- 20 [0034] Figure 11 is a flowchart of a method according to aspects of the disclosure.
- [0035] Figure 12 is a flowchart of a method according to aspects of the disclosure.
- [0036] It should be noted that the figures are merely examples and no limitations on the scope of the present disclosure are intended thereby. Further, the figures are generally not drawn to scale, but are drafted for purposes of convenience and clarity in illustrating various aspects of the disclosure.
- 25

DETAILED DESCRIPTION

- [0037] To promote an understanding of the principles of the disclosure, reference will now be made to the features illustrated in the drawings and specific language will be used to describe the same. It will nevertheless be understood that no limitation of the scope of the disclosure is thereby intended. Any alterations and further modifications, and any further applications of the principles of the disclosure as described herein are contemplated as would normally occur to one skilled in the art to which the disclosure relates. For the sake of clarity, some features not relevant to the present disclosure may not be shown in the drawings.
- 30
- [0038] At the outset, for ease of reference, certain terms used in this application and their

meanings as used in this context are set forth. To the extent a term used herein is not defined below, it should be given the broadest definition persons in the pertinent art have given that term as reflected in at least one printed publication or issued patent. Further, the present techniques are not limited by the usage of the terms shown below, as all equivalents, synonyms, 5 new developments, and terms or techniques that serve the same or a similar purpose are considered to be within the scope of the present claims.

[0039] As one of ordinary skill would appreciate, different persons may refer to the same feature or component by different names. This document does not intend to distinguish between components or features that differ in name only. The figures are not necessarily to scale. Certain 10 features and components herein may be shown exaggerated in scale or in schematic form and some details of conventional elements may not be shown in the interest of clarity and conciseness. When referring to the figures described herein, the same reference numerals may be referenced in multiple figures for the sake of simplicity. In the following description and in the claims, the terms "including" and "comprising" are used in an open-ended fashion, and 15 thus, should be interpreted to mean "including, but not limited to."

[0040] The articles "the," "a" and "an" are not necessarily limited to mean only one, but rather are inclusive and open ended so as to include, optionally, multiple such elements.

[0041] As used herein, the terms "approximately," "about," "substantially," and similar terms are intended to have a broad meaning in harmony with the common and accepted usage 20 by those of ordinary skill in the art to which the subject matter of this disclosure pertains. It should be understood by those of skill in the art who review this disclosure that these terms are intended to allow a description of certain features described and claimed without restricting the scope of these features to the precise numeral ranges provided. Accordingly, these terms should be interpreted as indicating that insubstantial or inconsequential modifications or alterations of 25 the subject matter described and are considered to be within the scope of the disclosure. The term "near" is intended to mean within 2%, or within 5%, or within 10%, of a number or amount.

[0042] As used herein, the term "ambient" refers to the atmospheric or aquatic environment where an apparatus is disposed. The term "at" or "near" "ambient temperature" as used herein 30 refers to the temperature of the environment in which any physical or chemical event occurs plus or minus ten degrees, alternatively, five degrees, alternatively, three degrees, alternatively two degrees, and alternatively, one degree, unless otherwise specified. A typical range of ambient temperatures is between about 0 °C. (32 °F.) and about 40 °C. (104 °F.), though ambient temperatures could include temperatures that are higher or lower than this range. While

it is possible in some specialized applications to prepare an environment with particular characteristics, such as within a building or other structure that has a controlled temperature and/or humidity, such an environment is considered to be “ambient” only where it is substantially larger than the volume of heat-sink material and substantially unaffected by operation of the apparatus. It is noted that this definition of an “ambient” environment does not require a static environment. Indeed, conditions of the environment may change as a result of numerous factors other than operation of the thermodynamic engine—the temperature, humidity, and other conditions may change as a result of regular diurnal cycles, as a result of changes in local weather patterns, and the like.

10 [0043] As used herein, the term “compression unit” means any one type or combination of similar or different types of compression equipment, and may include auxiliary equipment, known in the art for compressing a substance or mixture of substances. A “compression unit” may utilize one or more compression stages. Illustrative compressors may include, but are not limited to, positive displacement types, such as reciprocating and rotary compressors for example, and dynamic types, such as centrifugal and axial flow compressors, for example.

15 [0044] “Exemplary” is used exclusively herein to mean “serving as an example, instance, or illustration.” Any embodiment or aspect described herein as “exemplary” is not to be construed as preferred or advantageous over other embodiments.

[0045] The term “gas” is used interchangeably with “vapor,” and is defined as a substance or mixture of substances in the gaseous state as distinguished from the liquid or solid state. Likewise, the term “liquid” means a substance or mixture of substances in the liquid state as distinguished from the gas or solid state.

[0046] As used herein, “heat exchange area” means any one type or combination of similar or different types of equipment known in the art for facilitating heat transfer. Thus, a “heat exchange area” may be contained within a single piece of equipment, or it may comprise areas contained in a plurality of equipment pieces. Conversely, multiple heat exchange areas may be contained in a single piece of equipment.

[0047] A “hydrocarbon” is an organic compound that primarily includes the elements hydrogen and carbon, although nitrogen, sulfur, oxygen, metals, or any number of other elements can be present in small amounts. As used herein, hydrocarbons generally refer to components found in natural gas, oil, or chemical processing facilities.

[0048] As used herein, the terms “loop” and “cycle” are used interchangeably.

[0049] As used herein, “natural gas” means a gaseous feedstock suitable for manufacturing LNG, where the feedstock is a methane-rich gas. A “methane-rich gas” is a gas containing

methane (C₁) as a major component, i.e., having a composition of at least 50 % methane by weight. Natural gas may include gas obtained from a crude oil well (associated gas) or from a gas well (non-associated gas).

[0050] The disclosed aspects provide a method for liquefying a feed gas stream, particularly one rich in methane. The method comprises: (a) providing the gas stream at a pressure less than 1,200 psia; (b) providing a compressed refrigerant with a pressure greater than or equal to 1,500 psia; (c) cooling the compressed refrigerant by indirect heat exchange with an ambient temperature air or water to produce a compressed, cooled refrigerant; (d) expanding the compressed, cooled refrigerant in at least one work producing expander thereby producing an expanded, cooled refrigerant; (e) routing part or all of the expanded, cooled refrigerant to at least one separator, such as a separation vessel, and mixing said expanded, cooled refrigerant with a make-up refrigerant gas stream, to thereby condition the make-up refrigerant gas stream by condensing excessive heavy hydrocarbon components therefrom and producing a gaseous overhead refrigerant stream; (f) combining the gaseous overhead refrigerant stream with the remaining expanded, cooled refrigerant to form a cold primary refrigerant mixture; (g) passing the cold primary refrigerant mixture through a heat exchanger zone to form a warm refrigerant; (h) passing the gas stream through the heat exchanger zone to cool at least part of the gas stream by indirect heat exchange with the cold primary refrigerant mixture, thereby forming a liquefied gas stream; and (i) compressing the warm refrigerant to produce the compressed refrigerant.

[0051] In another aspect, a method is provided for liquefying a feed gas stream, comprising: (a) providing the feed gas stream at a pressure less than 1,200 psia; (b) compressing the feed gas stream to a pressure of at least 1,500 psia to form a compressed gas stream; (c) cooling the compressed gas stream by indirect heat exchange with an ambient temperature air or water to form a compressed, cooled gas stream; (d) expanding the compressed, cooled gas stream in at least one work producing expander to a pressure that is less than 2,000 psia and no greater than the pressure to which the gas stream was compressed, to thereby form a chilled gas stream; (e) providing a compressed refrigerant stream with a pressure greater than or equal to 1,500 psia; (f) cooling the compressed refrigerant stream by indirect heat exchange with an ambient temperature air or water to produce a compressed, cooled refrigerant stream; (g) expanding the compressed, cooled refrigerant stream in at least one work producing expander, thereby producing an expanded, cooled refrigerant stream; (h) routing part or all of the expanded, cooled refrigerant stream to at least one separator, such as a separation vessel, and mixing said expanded, cooled refrigerant stream with a make-up refrigerant gas stream, to

thereby condition the make-up refrigerant gas stream by condensing excessive heavy hydrocarbon components therefrom and producing a gaseous overhead refrigerant stream; (i) combining the gaseous overhead refrigerant stream with the remaining expanded, cooled refrigerant to form a cold primary refrigerant mixture; (j) passing the cold primary refrigerant mixture through a heat exchanger zone to form a warm refrigerant stream; (k) passing the chilled gas stream through the heat exchanger zone to cool at least part of the chilled gas stream by indirect heat exchange with the cold primary refrigerant mixture, thereby forming a liquefied gas stream; and (l) compressing the warm refrigerant stream to produce the compressed refrigerant stream.

10 [0052] In another aspect, a method is provided for liquefying a feed gas stream in a system having a first heat exchanger zone and a second heat exchanger zone, comprising: (a) providing the feed gas stream at a pressure less than 1,200 psia; (b) compressing the gas stream to a pressure of at least 1,500 psia to form a compressed gas stream; (c) cooling the compressed gas stream by indirect heat exchange with an ambient temperature air or water to form a compressed, cooled gas stream; (d) expanding the compressed, cooled gas stream in at least one work producing expander to a pressure that is less than 2,000 psia and no greater than the pressure to which the gas stream was compressed, to thereby form a chilled gas stream; (e) providing a compressed refrigerant stream with a pressure greater than or equal to 1,500 psia; (f) cooling the compressed refrigerant stream by indirect heat exchange with an ambient temperature air or water to produce a compressed, cooled refrigerant stream; (g) directing the compressed, cooled refrigerant stream to the second heat exchanger zone to additionally cool the compressed, cooled refrigerant stream below ambient temperature to produce a compressed, additionally cooled refrigerant stream; (h) expanding the compressed, additionally cooled refrigerant stream in at least one work producing expander, thereby producing an expanded, cooled refrigerant stream; (i) routing part or all of the expanded, cooled refrigerant stream to at least one separator, such as a separation vessel, and mixing said expanded, cooled refrigerant stream with a make-up refrigerant gas stream, to thereby condition the make-up refrigerant gas stream by condensing excessive heavy hydrocarbon components therefrom and producing a gaseous overhead refrigerant stream; (j) combining the gaseous overhead refrigerant stream with the remaining expanded, cooled refrigerant stream to form a cold primary refrigerant mixture; (k) passing the cold primary refrigerant mixture through the first heat exchanger zone to form a warm refrigerant stream, whereby the warm refrigerant stream has a temperature that is cooler by at least 5°F of the highest fluid temperature within the heat exchanger zone and whereby the heat exchanger type of the first heat exchanger zone is

different from the heat exchanger type of the second heat exchanger zone; (l) passing the chilled gas stream through the first heat exchanger zone to cool at least part of the chilled gas stream by indirect heat exchange with the cold primary refrigerant mixture, thereby forming a liquefied gas stream; and (m) compressing the warm refrigerant stream to produce the compressed refrigerant stream.

[0053] In still another aspect of the disclosure, a method of liquefying a feed gas stream is provided, comprising: (a) providing the feed gas stream at a pressure less than 1,200 psia; (b) providing a refrigerant stream at or near the same pressure of the feed gas stream; (c) mixing the feed gas stream with the refrigerant stream to form a second feed gas stream; (d) compressing the second feed gas stream to a pressure of at least 1,500 psia to form a compressed second feed gas stream; (e) cooling the compressed feed second gas stream by indirect heat exchange with an ambient temperature air or water to form a compressed, cooled second feed gas stream; (f) directing the compressed, cooled second feed gas stream to a second heat exchanger zone to additionally cool the compressed, cooled second gas stream below ambient temperature to produce a compressed, additionally cooled second feed gas stream; (g) expanding the compressed, additionally cooled second feed gas stream in at least one work producing expander to a pressure that is less than 2,000 psia and no greater than the pressure to which the second feed gas stream was compressed, to thereby form an expanded, cooled second feed gas stream; (h) separating the expanded, cooled second feed gas stream into a first expanded refrigerant stream and a chilled gas stream; (i) expanding the first expanded refrigerant stream in at least one work producing expander, thereby producing a second expanded refrigerant stream; (j) routing part or all of the second expanded refrigerant stream to at least one separator, such as a separation vessel, and mixing the second expanded refrigerant stream with a make-up refrigerant gas stream, to thereby condition the make-up refrigerant gas stream by condensing excessive heavy hydrocarbon components therefrom and producing a gaseous overhead refrigerant stream; (k) combining the gaseous overhead refrigerant stream with the remaining second expanded refrigerant stream to form a cold primary refrigerant mixture; (l) passing the cold primary refrigerant mixture through a first heat exchanger zone to form a first warm refrigerant stream, whereby the first warm refrigerant stream has a temperature that is cooler by at least 5°F than the highest fluid temperature within the first heat exchanger zone and whereby the heat exchanger type of the first heat exchanger zone is different from the heat exchanger type of the second heat exchanger zone; (m) passing the chilled gas stream through the first heat exchanger zone to cool at least part of the chilled gas stream by indirect heat exchange with the second expanded refrigerant, thereby forming a

liquefied gas stream; (n) directing the first warm refrigerant to the second heat exchanger zone to cool by indirect heat exchange the compressed, cooled second gas, thereby forming a second warm refrigerant; and (o) compressing the second warm refrigerant to produce the refrigerant stream.

5 **[0054]** Aspects of the disclosure may compress the gas stream to a pressure no greater than 1,600 psia and then cooling the compressed gas stream by indirect heat exchange with an ambient temperature air or water prior to directing the gas stream to the first heat exchanger zone. Aspects of the disclosure may cool the gas stream to a temperature below the ambient by indirect heat exchange within an external cooling unit prior to directing the gas stream to the
10 first heat exchanger zone. Aspects of the disclosure may cool the compressed, cooled refrigerant to a temperature below the ambient temperature by indirect heat exchange with an external cooling unit prior to directing the compressed, cooled refrigerant to the at least one work producing expander or the second heat exchanger zone. These described additional steps may be employed singularly or in combination with each other.

15 **[0055]** Figure 2 is a schematic diagram that illustrates a liquefaction system **200** according to an aspect of the disclosure. The liquefaction system **200** includes a primary cooling loop **202**, which may also be called an expander loop. The liquefaction system also includes a sub-cooling loop **204**, which is a closed refrigeration loop preferably charged with nitrogen as the sub-cooling refrigerant. Within the primary cooling loop **202**, a refrigerant stream **205** is
20 directed to a heat exchanger zone **201** where it exchanges heat with a feed gas stream **206** to form a first warm refrigerant stream **208**. The first warm refrigerant stream **208** is compressed in one or more compression units **218**, **220** to a pressure greater than 1,500 psia, or more preferably, to a pressure of approximately 3,000 psia, to form a compressed refrigerant stream **222**. The compressed refrigerant stream **222** is then cooled against an ambient cooling medium
25 (air or water) in a cooler **224** to produce a compressed, cooled refrigerant stream **226**. Cooler **224** may be similar to cooler **112** as previously described. The compressed, cooled refrigerant stream **226** is near isentropically expanded in an expander **228** to produce an expanded, cooled refrigerant stream **230**. Expander **228** may be a work-expansion device, such as a gas expander, which produces work that may be extracted and used for compression.

30 **[0056]** All or a portion of the expanded, cooled refrigerant stream **230** is directed to a separation vessel **232**. A make-up gas stream **234** is also directed to the separation vessel **232** and mixes therein with the expanded, cooled refrigerant stream **230**. The rate at which the make-up gas stream **234** is added to the separation vessel **232** will depend on the rate of loss of refrigerant due to such factors as leaks from equipment seals. The mixing conditions the make-

up gas stream **234** by condensing heavy hydrocarbon components (e.g., C_{2+} compounds) contained in the make-up gas stream **234**. The condensed components accumulate in the bottom of the separator and are periodically discharged as a separator bottom stream **236** to maintain a desired liquid level in the separation vessel **232**. The conditioned make-up gas stream, minus
5 the condensed heavy hydrocarbon components, exits the separation vessel as a gaseous overhead refrigerant stream **238**. The gaseous overhead refrigerant stream **238** optionally mixes with a bypass stream **230a** of the expanded, cooled refrigerant stream **230**, forming the refrigerant stream **205**.

[0057] The heat exchanger zone **201** may include a plurality of heat exchanger devices,
10 and in the aspects shown in Figure 2, the heat exchanger zone includes a main heat exchanger **240** and a sub-cooling heat exchanger **242**. The main heat exchanger **240** exchanges heat with the refrigerant stream **205**. These heat exchangers may be of a brazed aluminum heat exchanger type, a plate fin heat exchanger type, a spiral wound heat exchanger type, or a combination thereof. Within the sub-cooling loop **204**, an expanded sub-cooling refrigerant stream **244**
15 (preferably comprising nitrogen) is discharged from an expander **246** and drawn through the sub-cooling heat exchanger **242** and the main heat exchanger **240**. Expanded sub-cooling refrigerant stream **244** is then sent to a compression unit **248** where it is re-compressed to a higher pressure and warmed. After exiting compression unit **248**, the re-compressed sub-cooling refrigerant stream **250** is cooled in a cooler **252**, which can be of the same type as
20 cooler **224**, although any type of cooler may be used. After cooling, the re-compressed sub-cooling refrigerant stream is passed through the main heat exchanger **240** where it is further cooled by indirect heat exchange with the refrigerant stream **205** and expanded sub-cooling refrigerant stream **244**. After exiting the heat exchange area **201**, the re-compressed and cooled sub-cooling refrigerant stream is expanded through expander **246** to provide the expanded sub-cooling refrigerant stream **244** that is re-cycled through the heat exchanger zone as described
25 herein. In this manner, the feed gas stream **206** is cooled, liquefied and sub-cooled in the heat exchanger zone **201** to produce a sub-cooled gas stream **254**. Sub-cooled gas stream **254** is then expanded to a lower pressure in an expander **256** to form a liquid fraction and a remaining vapor fraction. Expander **256** may be any pressure reducing device, including but not limited to a valve, control valve, Joule Thompson valve, Venturi device, liquid expander, hydraulic turbine, and the like. The sub-cooled stream **254**, which is now at a lower pressure and partially
30 liquefied, is passed to a surge tank **258** where the liquefied fraction **260** is withdrawn from the process as an LNG stream **262**. The remaining vapor fraction, which is withdrawn from the surge tank as a flash vapor stream **264**, may be used as fuel to power the compressor units.

[0058] Figure 3 is a schematic diagram that illustrates a liquefaction system **300** according to another aspect of the disclosure. Liquefaction system **300** is similar to liquefaction system **200** and for the sake of brevity similarly depicted or numbered components may not be further described. Liquefaction system **300** includes a primary cooling loop **302** and a sub-cooling loop **304**. The sub-cooling loop **304** is a closed refrigeration loop preferably charged with nitrogen as the sub-cooling refrigerant. Liquefaction system **300** also includes a heat exchanger zone **301**. Within the primary cooling loop **302**, a refrigerant stream **305** is directed to the heat exchanger zone **301** where it exchanges heat with a feed gas stream **306** to form a first warm refrigerant stream **308**. The first warm refrigerant stream **308** is compressed in one or more compression units **318**, **320** to a pressure greater than 1,500 psia, or more preferably, to a pressure of approximately 3,000 psia, to form a compressed refrigerant stream **322**. The compressed refrigerant stream **322** is then cooled against an ambient cooling medium (air or water) in a cooler **324** to produce a compressed, cooled refrigerant stream **326**. Cooler **324** may be similar to cooler **112** as previously described. The compressed, cooled refrigerant stream **326** is near isentropically expanded in an expander **328** to produce an expanded, cooled refrigerant stream **330**. Expander **328** may be a work-expansion device, such as a gas expander, which produces work that may be extracted and used for compression.

[0059] In contrast with liquefaction system **200**, all of the expanded, cooled refrigerant stream **330** is directed to a separation vessel **332**. A make-up gas stream **334** is also directed to the separation vessel **332** and mixes therein with the expanded, cooled refrigerant stream **330**. The rate at which the make-up gas stream **334** is added to the separation vessel **332** will depend on the rate of loss of refrigerant due to such factors as leaks from equipment seals. The mixing conditions the make-up gas stream **334** by condensing heavy hydrocarbon components (e.g., C₂₊ compounds) contained in the make-up gas stream **334**. The condensed components accumulate in the bottom of the separator and are periodically discharged as a separator bottom stream **336** to maintain a desired liquid level in the separation vessel **332**. The conditioned make-up gas stream, minus the condensed heavy hydrocarbon components, exits the separation vessel as a gaseous overhead refrigerant stream **338**. The gaseous overhead refrigerant stream **338** forms the refrigerant stream **305**.

[0060] The heat exchanger zone **301** may include a plurality of heat exchanger devices, and in the aspects shown in Figure 3, the heat exchanger zone includes a main heat exchanger **340** and a sub-cooling heat exchanger **342**. The main heat exchanger **340** exchanges heat with the refrigerant stream **305**. These heat exchangers may be of a brazed aluminum heat exchanger type, a plate fin heat exchanger type, a spiral wound heat exchanger type, or a combination

thereof. Within the sub-cooling loop **304**, an expanded sub-cooling refrigerant stream **344** (preferably comprising nitrogen) is discharged from an expander **346** and drawn through the sub-cooling heat exchanger **342** and the main heat exchanger **340**. Expanded sub-cooling refrigerant stream **344** is then sent to a compression unit **348** where it is re-compressed to a higher pressure and warmed. After exiting compression unit **348**, the re-compressed sub-cooling refrigerant stream **350** is cooled in a cooler **352**, which can be of the same type as cooler **324**, although any type of cooler may be used. After cooling, the re-compressed sub-cooling refrigerant stream is passed through the main heat exchanger **340** where it is further cooled by indirect heat exchange with the refrigerant stream **305** and expanded sub-cooling refrigerant stream **344**. After exiting the heat exchange area **301**, the re-compressed and cooled sub-cooling refrigerant stream is expanded through expander **346** to provide the expanded sub-cooling refrigerant stream **344** that is re-cycled through the heat exchanger zone as described herein. In this manner, the feed gas stream **306** is cooled, liquefied and sub-cooled in the heat exchanger zone **301** to produce a sub-cooled gas stream **354**. Sub-cooled gas stream **354** is then expanded to a lower pressure in an expander **356** to form a liquid fraction and a remaining vapor fraction. Expander **356** may be any pressure reducing device, including but not limited to a valve, control valve, Joule Thompson valve, Venturi device, liquid expander, hydraulic turbine, and the like. The sub-cooled stream **354**, which is now at a lower pressure and partially liquefied, is passed to a surge tank **358** where the liquefied fraction **360** is withdrawn from the process as an LNG stream **362**. The remaining vapor fraction, which is withdrawn from the surge tank as a flash vapor stream **364**, may be used as fuel to power the compressor units.

[0061] Figure 4 is a schematic diagram that illustrates a liquefaction system **400** according to another aspect of the disclosure. Liquefaction system **400** is similar to liquefaction system **200**, and for the sake of brevity similarly depicted or numbered components may not be further described. Liquefaction system **400** includes a primary cooling loop **402** and a sub-cooling loop **404**. Liquefaction system **400** includes first and second heat exchanger zones **401**, **410**. Within the first heat exchanger zone **401**, the first warm refrigerant stream **405** is used to liquefy the feed gas stream **406**. One or more heat exchangers **410a** within the second heat exchanger zone **410** uses all or a portion of the first warm refrigerant stream **408** to cool a compressed, cooled refrigerant stream **426**, thereby forming a second warm refrigerant stream **409**. The first heat exchanger zone **401** may be physically separate from the second heat exchanger zone **410**. Additionally, the heat exchangers of the first heat exchanger zone may be of a different type(s) from the heat exchangers of the second heat exchanger zone. Both heat exchanger zones may comprise multiple heat exchangers.

[0062] The first warm refrigerant stream **405** has a temperature that is cooler by at least 5 °F, or more preferably, cooler by at least 10 °F, or more preferably, cooler by at least 15 °F, than the highest fluid temperature within the first heat exchanger zone **401**. The second warm refrigerant stream **409** may be compressed in one or more compressors **418**, **420** to a pressure greater than 1,500 psia, or more preferably, to a pressure of approximately 3,000 psia, to thereby form a compressed refrigerant stream **422**. The compressed refrigerant stream **422** is then cooled against an ambient cooling medium (air or water) in a cooler **424** to produce the compressed, cooled refrigerant stream **426** that is directed to the second heat exchanger zone **410** to form a compressed, additionally cooled refrigerant stream **429**. The compressed, additionally cooled refrigerant stream **429** is near isentropically expanded in an expander **428** to produce the expanded, cooled refrigerant stream **430**. All or a portion of the expanded, cooled refrigerant stream **430** is directed to a separation vessel **432** where it is mixed with a make-up gas stream **434** as previously described with respect to Figure 2. The rate at which the make-up gas stream **434** is added to the separation vessel **432** will depend on the rate of loss of refrigerant due to such factors as leaks from equipment seals. The conditioned make-up gas stream, minus the condensed heavy hydrocarbon components, exits the separation vessel as a gaseous overhead refrigerant stream **438**. The gaseous overhead refrigerant stream **438** optionally mixes with a bypass stream **430a** of the expanded, cooled refrigerant stream **430**, forming the warm refrigerant stream **405**.

[0063] Figure 5 is a schematic diagram that illustrates a liquefaction system **500** according to another aspect of the disclosure. Liquefaction system **500** is similar to liquefaction systems **200** and **300** and for the sake of brevity similarly depicted or numbered components may not be further described. Liquefaction system **500** includes a primary cooling loop **502** and a sub-cooling loop **504**. Liquefaction system **500** also includes a heat exchanger zone **501**. Liquefaction system **500** stream includes the additional steps of compressing the feed gas stream **506** in a compressor **566** and then, using a cooler **568**, cooling the compressed feed gas **567** with ambient air or water to produce a cooled, compressed feed gas stream **570**. Feed gas compression may be used to improve the overall efficiency of the liquefaction process and increase LNG production.

[0064] Figure 6 is a schematic diagram that illustrates a liquefaction system **600** according to still another aspect of the disclosure. Liquefaction system **600** is similar to liquefaction systems **200** and **300** and for the sake of brevity similarly depicted or numbered components may not be further described. Liquefaction system **600** includes a primary cooling loop **602** and a sub-cooling loop **604**. Liquefaction system **600** also includes a heat exchanger zone **601**.

Liquefaction system **600** includes the additional step of chilling, in an external cooling unit **665**, the feed gas stream **606** to a temperature below the ambient temperature to produce a chilled gas stream **667**. The chilled gas stream **667** is then directed to the first heat exchanger zone **601** as previously described. Chilling the feed gas as shown in Figure 6 may be used to improve the overall efficiency of the liquefaction process and increase LNG production.

[0065] Figure 7 is a schematic diagram that illustrates a liquefaction system **700** according to another aspect of the disclosure. Liquefaction system **700** is similar to liquefaction system **200** and for the sake of brevity similarly depicted or numbered components may not be further described. Liquefaction system **700** includes a primary cooling loop **702** and a sub-cooling loop **704**. Liquefaction system **700** also includes first and second heat exchanger zones **701**, **710**. Liquefaction system **700** includes an external cooling unit **774** that chills the compressed, cooled refrigerant **726** in the primary cooling loop **702** to a temperature below the ambient temperature, to thereby produce a compressed, chilled refrigerant **776**. The compressed, chilled refrigerant **776** is then directed to the second heat exchanger zone **710** as previously described. Using an external cooling unit to further cool the compressed, cool refrigerant may be used to improve the overall efficiency of the process and increase LNG production.

[0066] Figure 8 is a schematic diagram that illustrates a liquefaction system **800** according to another aspect of the disclosure. Liquefaction system **800** is similar to liquefaction system **400** and for the sake of brevity similarly depicted or numbered components may not be further described. Liquefaction system **800** includes a primary cooling loop **802** and a sub-cooling loop **804**. Liquefaction system **800** also includes first and second heat exchanger zones **801**, **810**. In liquefaction system **800**, the feed gas stream **806** is compressed in a compressor **880** to a pressure of at least 1,500 psia, thereby forming a compressed gas stream **881**. Using an external cooling unit **882**, the compressed gas stream **881** is cooled by indirect heat exchange with an ambient temperature air or water to form a compressed, cooled gas stream **883**. The compressed, cooled gas stream **883** is expanded in at least one work producing expander **884** to a pressure that is less than 2,000 psia but no greater than the pressure to which the gas stream was compressed, to thereby form a chilled gas stream **886**. The chilled gas stream **886** is then directed to the first heat exchanger zone **801** where a primary cooling refrigerant and a sub-cooling refrigerant are used to liquefy the chilled gas stream as previously described.

[0067] Figure 9 is a schematic diagram that illustrates a liquefaction system **900** according to yet another aspect of the disclosure. Liquefaction system **900** contains similar structure and components with previously disclosed liquefaction systems and for the sake of brevity similarly depicted or numbered components may not be further described. Liquefaction system **900**

includes a primary cooling loop **902** and a sub-cooling loop **904**. Liquefaction system **900** also includes first and second heat exchanger zones **901**, **910**. In liquefaction system **900**, the feed gas stream **906** is mixed with a refrigerant stream **907** to produce a second feed gas stream **906a**. Using a compressor **960**, the second feed gas stream **906a** is compressed to a pressure greater than 1,500 psia, or more preferably, to a pressure of approximately 3,000 psia, to form a compressed second gas stream **961**. Using an external cooling unit **962**, the compressed second gas stream **961** is then cooled against an ambient cooling medium (air or water) to produce a compressed, cooled second gas stream **963**. The compressed, cooled second gas stream **963** is directed to the second heat exchanger zone **910** where it exchanges heat with a first warm refrigerant stream **908**, to produce a compressed, additionally cooled second gas stream **913** and a second warm refrigerant stream **909**.

[0068] The compressed, additionally cooled second gas stream **913** is expanded in at least one work producing expander **926** to a pressure that is less than 2,000 psia, but no greater than the pressure to which the second gas stream **906a** was compressed, to thereby form an expanded, cooled second gas stream **980**. The expanded, cooled second gas stream **980** is separated into a first expanded refrigerant stream **905** and a chilled feed gas stream **906b**. The first expanded refrigerant stream **905** may be near isentropically expanded using an expander **982** to form a second expanded refrigerant stream **905a**, which is directed to a separation vessel **932**. A make-up gas stream **934** is also directed to the separation vessel **932** and mixes therein with the expanded, cooled refrigerant stream **930**. The rate at which the make-up gas stream **934** is added to the separation vessel **932** will depend on the rate of loss of refrigerant due to such factors as leaks from equipment seals. The mixing conditions the make-up gas stream **934** by condensing heavy hydrocarbon components (e.g., C_{2+} compounds) contained in the make-up gas stream **934**. The condensed components accumulate in the bottom of the separator and are periodically discharged as a separator bottom stream **936** to maintain a desired liquid level in the separation vessel **932**. The conditioned make-up gas stream, minus the condensed heavy hydrocarbon components, exits the separation vessel as a gaseous overhead refrigerant stream **938**, which is directed to the first heat exchanger zone **901**. The chilled feed gas stream **906b** is directed to the first heat exchanger zone **901** where a primary cooling refrigerant (i.e., the gaseous overhead refrigerant stream **938**) and a sub-cooling refrigerant (from the sub-cooling loop **904**) are used to liquefy and sub-cool the chilled feed gas stream **906b** to produce a sub-cooled gas stream **948**, which is processed as previously described to form LNG. The sub-cooling loop **904** may be a closed refrigeration loop, preferably charged with nitrogen as the sub-cooling refrigerant. After exchanging heat with the chilled feed gas stream **906b**, the

gaseous overhead refrigerant stream **938** forms the first warm refrigerant stream **908**. The first warm refrigerant stream **908** may have a temperature that is cooler by at least 5 °F, or more preferably, cooler by at least 10 °F, or more preferably, cooler by at least 15 °F, than the highest fluid temperature within the first heat exchanger zone **901**. The second warm refrigerant stream

5 **909** is compressed in one or more compressors **918** and then cooled with an ambient cooling medium in an external cooling device **924** to produce the refrigerant stream **907**.

[0069] Aspects of the disclosure illustrated in Figure 9 demonstrate that the primary refrigerant stream may comprise part of the feed gas stream, which in a preferred aspect may be primarily or nearly all methane. Indeed, it may be advantageous for the refrigerant in the

10 primary cooling loop of all the disclosed aspects (i.e., Figures 2 through 9) be comprised of at least 85% methane, or at least 90% methane, or at least 95% methane, or greater than 95% methane. This is because methane may be readily available in various parts of the disclosed processes, and the use of methane may eliminate the need to transport refrigerants to remote LNG processing locations. As a non-limiting example, the refrigerant in the primary cooling

15 loop **202** in Figure 2 may be taken through line **206a** of the feed gas stream **206** if the feed gas is high enough in methane to meet the compositions as described above. Make-up gas may be taken from the sub-cooled gas stream **254** during normal operations. Alternatively, part or all of a boil-off gas stream **259** from an LNG storage tank **257** may be used to supply refrigerant for the primary cooling loop **202**. Furthermore, if the feed gas stream is sufficiently low in

20 nitrogen, part or all of the end flash gas stream **264** (which would then be low in nitrogen) may be used to supply refrigerant for the primary cooling loop **202**. Lastly, any combination of line **206a**, boil-off gas stream **259**, and end flash gas stream **264** may be used to provide or even occasionally replenish the refrigerant in the primary cooling loop **202**.

[0070] Figure 10 is a flowchart of a method **1000** for liquefying a feed gas stream rich in methane, where the method comprises the following steps: **1002**, providing the feed gas stream

25 at a pressure less than 1,200 psia; **1004**, providing a compressed refrigerant stream with a pressure greater than or equal to 1,500 psia; **1006**, cooling the compressed refrigerant stream by indirect heat exchange with an ambient temperature air or water, to produce a compressed, cooled refrigerant stream; **1008**, expanding the compressed, cooled refrigerant stream in at least

30 one work producing expander, thereby producing an expanded, cooled refrigerant stream; **1010**, mixing part or all of the expanded, cooled refrigerant stream with a make-up refrigerant stream in a separator, thereby condensing heavy hydrocarbon components from the make-up refrigerant stream and forming a gaseous expanded, cooled refrigerant stream; **1012**, passing the gaseous expanded, cooled refrigerant stream through a heat exchanger zone to form a warm

refrigerant stream; **1014**, passing the feed gas stream through the heat exchanger zone to cool at least part of the feed gas stream by indirect heat exchange with the expanded, cooled refrigerant stream, thereby forming a liquefied gas stream; and **1016**, compressing the warm refrigerant stream to produce the compressed refrigerant stream.

5 **[0071]** Figure 11 is a flowchart of a method **1100** for liquefying a feed gas stream rich in methane in a system having a first heat exchanger zone and a second heat exchanger zone, where the method comprises the following steps: **1102**, providing a compressed refrigerant stream with a pressure greater than or equal to 1,500 psia; **1104**, cooling the compressed refrigerant stream by indirect heat exchange with an ambient temperature air or water to
10 produce a compressed, cooled refrigerant stream; **1106**, directing the compressed, cooled refrigerant stream to the second heat exchanger zone to additionally cool the compressed, cooled refrigerant stream below ambient temperature to produce a compressed, additionally cooled refrigerant stream; **1108**, expanding the compressed, additionally cooled refrigerant stream in at least one work producing expander, thereby producing an expanded, cooled
15 refrigerant stream; **1110**, routing part or all of the expanded, cooled refrigerant stream to at least one separator, such as a separation vessel, and mixing said expanded, cooled refrigerant stream with a make-up refrigerant gas stream, to thereby condition the make-up refrigerant gas stream by condensing heavy hydrocarbon components therefrom and producing a gaseous overhead refrigerant stream; **1112**, combining the gaseous overhead refrigerant stream with the
20 remaining expanded, cooled refrigerant stream to form a cold primary refrigerant mixture; **1114**, passing the cold primary refrigerant mixture through the first heat exchanger zone to form a warm refrigerant stream, whereby the warm refrigerant stream has a temperature that is cooler by at least 5 °F of the highest fluid temperature within the heat exchanger zone, and wherein a heat exchanger type of the first heat exchanger zone is different from a heat
25 exchanger type of the second heat exchanger zone; **1116**, passing the feed gas stream through the first heat exchanger zone to cool at least part of the feed gas stream by indirect heat exchange with the cold primary refrigerant mixture, thereby forming a liquefied gas stream; and **1118**, compressing the warm refrigerant stream to produce the compressed refrigerant stream.

30 **[0072]** Figure 12 is a method **1200** for liquefying a feed gas stream rich in methane, where the method comprises the following steps: **1202**, providing the feed gas stream at a pressure less than 1,200 psia; **1204**, compressing the feed gas stream to a pressure of at least 1,500 psia to form a compressed gas stream; **1206**, cooling the compressed gas stream by indirect heat exchange with an ambient temperature air or water to form a compressed, cooled gas stream;

1208, expanding the compressed, cooled gas stream in at least one work producing expander to a pressure that is less than 2,000 psia and no greater than the pressure to which the gas stream was compressed, to thereby form a chilled gas stream; 1210, providing a compressed refrigerant stream with a pressure greater than or equal to 1,500 psia; 1212, cooling the compressed refrigerant stream by indirect heat exchange with an ambient temperature air or water to produce a compressed, cooled refrigerant stream; 1214, expanding the compressed, cooled refrigerant stream in at least one work producing expander, thereby producing an expanded, cooled refrigerant stream; 1216, routing part or all of the expanded, cooled refrigerant stream to at least one separator, and mixing said expanded, cooled refrigerant stream therein with a make-up refrigerant gas stream, to thereby condition the make-up refrigerant gas stream by condensing heavy hydrocarbon components therefrom and producing a gaseous overhead refrigerant stream; 1218, combining the gaseous overhead refrigerant stream with the remaining expanded, cooled refrigerant to form a cold primary refrigerant mixture; 1220, passing the cold primary refrigerant mixture through a heat exchanger zone to form a warm refrigerant stream; 1222, passing the chilled gas stream through the heat exchanger zone to cool at least part of the chilled gas stream by indirect heat exchange with the cold primary refrigerant mixture, thereby forming a liquefied gas stream; and 1224, compressing the warm refrigerant stream to produce the compressed refrigerant stream.

[0073] The steps depicted in Figures 10-12 are provided for illustrative purposes only and a particular step may not be required to perform the disclosed methodology. Moreover, Figures 10-12 may not illustrate all the steps that may be performed. The claims, and only the claims, define the disclosed system and methodology.

[0074] Aspects of the disclosure have several advantages over the known liquefaction processes, in which feed gas must be consistently sufficiently lean to be used as make-up gas in the primary refrigerant loop. BOG, which is rich in lighter components such as nitrogen, is required as a reliable make-up gas source. But using BOG as make-up gas negatively impacts the effectiveness of the primary loop refrigerant, either by demanding higher power consumption or requiring a larger main cryogenic heat exchanger. In addition, BOG composition is very sensitive to variation in the composition of light ends (e.g., nitrogen, hydrogen, helium) in the feed gas, thereby potentially adversely impacting process stability. The disclosed aspects enable the primary refrigerant make-up gas to comprise feed gas having a wide range of compositions, from lean to rich. Taking liquefaction system 300 as an example, the size of the main cryogenic heat exchanger can be reduced 10-16% and thermal efficiency can be improved up to about 1%, when compared to a similar system using BOG as the primary

refrigerant make-up gas. Such size reductions of the main cryogenic heat exchanger, which typically is one of the largest and heaviest component or vessel in an LNG liquefaction system, may greatly reduce the size and cost of LNG liquefaction plants. Additionally, the disclosed aspects offer flexibility in tuning light (e.g., N₂) and heavy (e.g., C₂₊) contents for the primary
5 refrigerant loop that could potentially dynamically match incoming feed from gas wells, thereby optimizing energy use or production rate. For example, the make-up gas streams could be from feed gas, N₂, and LPG product streams. Their relative rates could be tuned for optimization purposes illustrated above.

[0075] It should be understood that the numerous changes, modifications, and alternatives
10 to the preceding disclosure can be made without departing from the scope of the disclosure. The preceding description, therefore, is not meant to limit the scope of the disclosure. Rather, the scope of the disclosure is to be determined only by the appended claims and their equivalents. It is also contemplated that structures and features in the present examples can be altered, rearranged, substituted, deleted, duplicated, combined, or added to each other.

15

CLAIMS

1. A method for liquefying a feed gas stream rich in methane, comprising:
 - (a) providing the feed gas stream at a pressure less than 1,200 psia (8.3×10^6 Pa);
 - 5 (b) providing a compressed refrigerant stream with a pressure greater than or equal to 1,500 psia (1.0×10^7 Pa);
 - (c) cooling the compressed refrigerant stream by indirect heat exchange with an ambient temperature air or water, to produce a compressed, cooled refrigerant stream;
 - (d) expanding the compressed, cooled refrigerant stream in at least one work
10 producing expander, thereby producing an expanded, cooled refrigerant stream;
 - (e) mixing part or all of the expanded, cooled refrigerant stream with a make-up refrigerant stream in a separator, thereby condensing heavy hydrocarbon components from the make-up refrigerant stream and forming a gaseous expanded, cooled refrigerant stream;
 - (f) passing the gaseous expanded, cooled refrigerant stream through a heat
15 exchanger zone to form a warm refrigerant stream;
 - (g) passing the feed gas stream through the heat exchanger zone to cool at least part of the feed gas stream by indirect heat exchange with the expanded, cooled refrigerant stream, thereby forming a liquefied gas stream; and
 - (i) compressing the warm refrigerant stream to produce the compressed refrigerant
20 stream.
2. The method of claim 1, further comprising:
controlling a flow rate of the make-up refrigerant stream into the separator to maintain at least one pressure at a suction side of a compressor at a target value.
3. The method of claim 1 or claim 2, further comprising:
25 collecting the condensed heavy hydrocarbon components in the separator; and
discharging the condensed heavy hydrocarbon components to maintain a desired liquid level in the separator.
4. The method of any one of claims 1-3, further comprising:
prior to directing the feed gas stream to the heat exchanger zone, compressing the feed
30 gas stream to a pressure no greater 1,600 psia (1.1×10^7 Pa), and then cooling it by indirect heat exchange with an ambient temperature air or water.
5. The method of any one of claims 1-4, wherein the feed gas stream is cooled to a temperature below an ambient temperature by indirect heat exchange within an external cooling unit prior to directing the feed gas stream to the heat exchanger zone.

6. The method of any one of claims 1-5, wherein the compressed, cooled refrigerant stream is cooled to a temperature below the ambient temperature by indirect heat exchange within an external cooling unit prior to expanding the compressed, cooled refrigerant stream in the at least one work producing expander.
- 5 7. The method of any one of claims 1-6, wherein the make-up refrigerant stream comprises a portion of the feed gas stream, a boil-off gas obtained from the liquefied gas stream, or any combination thereof, optionally wherein the make-up refrigerant stream comprises a mixture of methane with at least one component having a molecular weight heavier or lighter than methane.
- 10 8. A method for liquefying a feed gas stream rich in methane in a system having a first heat exchanger zone and a second heat exchanger zone, comprising:
- (a) providing a compressed refrigerant stream with a pressure greater than or equal to 1,500 psia (1.0×10^7 Pa);
 - (b) cooling the compressed refrigerant stream by indirect heat exchange with an
15 ambient temperature air or water to produce a compressed, cooled refrigerant stream;
 - (c) directing the compressed, cooled refrigerant stream to the second heat exchanger zone to additionally cool the compressed, cooled refrigerant stream below ambient temperature to produce a compressed, additionally cooled refrigerant stream;
 - (d) expanding the compressed, additionally cooled refrigerant stream in at least one
20 work producing expander, thereby producing an expanded, cooled refrigerant stream;
 - (e) routing part or all of the expanded, cooled refrigerant stream to at least one separator, such as a separation vessel, and mixing said expanded, cooled refrigerant stream with a make-up refrigerant gas stream, to thereby condition the make-up refrigerant gas stream by condensing heavy hydrocarbon components therefrom and producing a gaseous overhead
25 refrigerant stream;
 - (f) combining the gaseous overhead refrigerant stream with the remaining expanded, cooled refrigerant stream to form a cold primary refrigerant mixture;
 - (g) passing the cold primary refrigerant mixture through the first heat exchanger zone to form a warm refrigerant stream, whereby the warm refrigerant stream has a temperature that
30 is cooler by at least 5 °F (-15.0 °C) of the highest fluid temperature within the heat exchanger zone, and wherein a heat exchanger type of the first heat exchanger zone is different from a heat exchanger type of the second heat exchanger zone;
 - (h) passing the feed gas stream through the first heat exchanger zone to cool at least part of the feed gas stream by indirect heat exchange with the cold primary refrigerant mixture,

thereby forming a liquefied gas stream; and

(i) compressing the warm refrigerant stream to produce the compressed refrigerant stream.

9. The method of claim 8, further comprising:

5 controlling a flow rate of the make-up refrigerant gas stream into the separator to maintain at least one pressure at a suction side of a compressor at a target value.

10. The method of claim 8 or claim 9, further comprising:

collecting the condensed heavy hydrocarbon components in the separator; and

discharging the condensed heavy hydrocarbon components to maintain a desired liquid

10 level in the separator.