

(19) World Intellectual Property Organization
International Bureau



PCT



(43) International Publication Date
9 April 2009 (09.04.2009)

(10) International Publication Number
WO 2009/045570 A1

(51) International Patent Classification:
F42C 9/14 (2006.01)

[US/US]; 505 Deenstill Road, Davenport, Florida 33836 (US).

(21) International Application Number: PCT/US2008/065262

(74) **Agent: SMITH, Ronald E.**; 180 Pine Avenue North,
Oldsmar, Florida 34677 (US).

(22) International Filing Date: 30 May 2008 (30.05.2008)

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(25) **Filing Language:** English

(26) **Publication Language:** English

(30) Priority Data:
11/809,735 1 June 2007 (01.06.2007) US

(71) Applicant (for all designated States except US): **DSE, INC.** [US/US]; 5201 S. Westshore Blvd., Tampa, Florida 33611 (US).

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,


(72) Inventor; and

(75) **Inventor/Applicant (for US only):** TAYLOR, Norman C.

[Continued on next page]

(54) Title: MECHANICAL SELF DESTRUCT FOR RUNAWAY ESCAPEMENTS

FIG. 1



(57) Abstract: An escapement fuze self-destruct mechanism for a projectile includes a drive weight that maintains a biasing member in a compressed state by centrifugal force when a projectile's RPM speed is above a preselected threshold. When the RPM speed falls below the preselected threshold, the biasing member exerts sufficient counter-rotational force to overcome the centrifugal force exerted by the drive weight. The biasing member expands to an uncompressed state and displaces the drive weight into position for mechanically implementing self-destruction of the projectile if a rotor is fully armed or for rendering the projectile "safe" if the rotor is in any position other than fully armed.



FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MT, NL,
NO, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG,
CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

— before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments

— with information concerning one or more priority claims
considered void