

Apparatus for and method of recording information signals on a record carrier.

The invention relates to an apparatus for recording information signals in a track on a longitudinal record carrier, comprising

- input means for receiving an information signal,
- processing means for processing the information signal so as to make the information signal
- 5 suitable for recording in at least one track on said record carrier,
- writing means for writing, after processing, the information signal in said at least one track on said record carrier, starting from a start position viewed in the length direction of the record carrier and in a direction towards one of the end positions of the record carrier, to a method of recording the information signals on said record carrier and to a record carrier.

10

An apparatus as defined in the opening paragraph is known from WO 96/18,188 A2, document D1 in the list of related documents, that can be found at the end of this description. The known apparatus records a plurality of information signals in an interleaved

15 way in a plurality of tracks on the record carrier.

The invention aims at providing an improved recording apparatus for recording a plurality of information signals. The apparatus in accordance with the invention is

20 characterized in that the portion of the record carrier between said start position and said one end position is fictitiously divided into a first sub portion lying adjacent the start position and a second sub portion lying adjacent the end position of the record carrier, and that the apparatus is adapted to record a first portion of a first information signal as blocks of information intermittently in said at least one track in said first subportion of the record

25 carrier, starting from said start position, and to record a second portion of the said first information signal continuously in said second subportion of the record carrier.

The invention is based on the following recognition. In order to decrease the access time to various information signals recorded on a record carrier, it is well known to

start the recording of the information signals from one location, the so-called start position on the record carrier. This is, amongst others, described in unpublished European patent application no. 96202074.9, document D2 in the list of related documents. The number of information signals that can be recorded from this start position is thus limited and related to the number of tracks on the record carrier. In accordance with the invention, the number of information signals that can be recorded and retrieved, starting from the start position can be increased by an interleaved recording of the information signals. Further, information signals of relatively long lengths and relatively short lengths could be recorded on the record carrier. Therefore, the portion of the record carrier between the start position and one end position is fictitiously divided into a first and a second subportion. Interleaved recording is realized in the first subportion, which is so long that relatively short information signals can be recorded in their entirety in the first subportion. Longer information signals, that are that long that they need to be recorded in the second subportion as well, will be recorded in this subportion in a continuous way, so as to improve 'storage utilization', and thereby 'save storage space' on the record carrier.

These and other aspects of the invention will be apparent from and elucidated with respect to the embodiments described hereafter in the figure description, in which figure 1 shows schematically the record carrier, figure 2 shows an apparatus in accordance with the invention, figure 3 shows the record carrier obtained with the apparatus of figure 2 in more detail.

25

Figure 1 shows the record carrier 2, schematically over its total length. The start end of the record carrier 2 is indicated by BOT (beginning-of-tape) and the final end is indicated by EOT (end-of-tape). A lead-in portion and a lead-out portion are shown, being the portions between the start end (BOT) of the record carrier and the line L_1 and the final end (EOT) of the record carrier and the line L_2 respectively. A data area for recording the information signal is available between the lead-in portion and the lead-out portion of the record carrier 2.

Tracking signals may be recorded in the record carrier in order to enable recording of the information so as to obtain information tracks T_1 to T_n , as shown in figure

1. Reference is made to the documents D3 to D7 which further describe the tracking signals and the use of such tracking signal. Where necessary, those documents are assumed to be incorporated by reference in the present application.

Figure 2 shows an embodiment of an apparatus for recording an information
5 signal on the record carrier 2 of figure 1, which has tracking signals prerecorded on it. Figure 3 shows how the information signal is recorded on the record carrier 2. The apparatus of figure 2 has an input terminal 30 for receiving the information signal. The input terminal is coupled to an input of a formatter unit 32, which converts the information signal into a format suitable for recording on the record carrier 2. An output of the formatter unit 32 is
10 coupled to a write unit 33 comprising a write/read head 34. The formatted information signal is supplied to the write/read head 34 and recorded in one of the tracks $T_1, T_2, \dots T_n$ on the record carrier 1. The record carrier as shown in figure 2 is supposed to be transported in directions indicated by the arrow 31.

The head 34 is further adapted to read tracking signals recorded in the record
15 carrier. The tracking signals are supplied to a filter unit 36, which has a bandpass filter characteristic with a centre frequency equal to the specific frequency of the tracking signals. As the frequency of the tracking signals is low relative to the frequency content of the formatted information signal, it is possible to read the tracking signals from the record carrier, while writing the formatted information signal into the track T_1 .

20 A generator unit 38 is present for generating a control signal in response to the tracking signals read by the head 34. This control signal is supplied to an input 50 of an actuator unit 40. The actuator unit 40 actuates a movable mounting 42 on which the head 34 is mounted. The movable mounting can have any form. One preferred embodiment of a mounting is described in EP patent application no. 95202926.2, document D3 of the list of
25 related documents, filed recently in the name of applicant, but not yet published. Further, the functioning of the tracking servo mechanism is extensively described in document D6 of the list of related documents.

A control unit 42 is present for controlling a motor transport unit 44. By
controlling the motor transport unit, the record carrier 2 is transported in one of the two
30 directions shown by the arrow 31.

Figure 3 shows an example of the record carrier after having recorded an information signal, such as a movie on the record carrier 2. The width of the record carrier is largely exaggerated in order to better explain the record carrier and the functioning of the apparatus. Tracks T_1 to T_n are shown in this example.

As can be seen, the total length of the record carrier between the start location, which is the line s , and the end of the record carrier, which is the line L_2 , is divided into a first subportion, denoted P_1 and a second subportion, denoted P_2 . The subportions may be of equal or different lengths.

5 When recording a movie on the record carrier, recording starts in track T_1 , at the start location indicated by the line s .

It should be noted here, that the start location could be at the beginning of the record carrier, which generally will be preceded by a small area for recording a table of contents. In this situation, information signals are always recorded starting from left and
10 going to the right in figure 3. When having reached the end of a track, recording can continue in another track, by changing the direction of transport of the record carrier and recording the information signal from the right and going to the left in figure 3.

The start position need not be at the beginning of the record carrier and could, as an example, be located half way the total length of the record carrier. In such situation,
15 information signals can be recorded in the first half of the record carrier, by starting recording at the start position and into the direction of the beginning of the record carrier, or in the second half of the record carrier, by starting recording at the start position and into the direction of the end of the record carrier. A table of contents will then be located half way the record carrier, between the first half and the second half in which information signals are
20 recorded.

The result of the recording of a first information signal on the record carrier 2 is shown in figure 3. The direction of recording is indicated by the arrows in figure 3. Prior to starting recording, the write head 34 is, or is positioned in, the start position s . Next, recording of the information signal in track T_1 is started. In a first recording mode, the
25 formatter unit 32 generates blocks of data of the information signal. Those blocks of data, denoted $B_{1,1}$, $B_{1,2}$, $B_{1,3}$, $B_{1,4}$, are intermittently recorded the track T_1 , as far as located in the first subportion P_1 . The first block generated comprises an 'begin-of-file' word BOF. As the total first information signal to be recorded is longer than the amount of information that can be recorded in the blocks $B_{1,1}$ to $B_{1,4}$, the apparatus is switched into a second recording
30 mode upon reaching the boundary between the first and the second subportion P_1 and P_2 respectively. In the second recording mode, the apparatus continuously records the remaining portion of the first information signal in the second subportion P_2 , by continuously recording the first information signal in the first track T_1 . Upon reaching the end of the record carrier 2, the direction of transport of the record carrier is reversed and the write head is positioned

on the track T_2 . The continuous recording mode is continued by recording the remaining portion of the first information signal in the second track, until recording is terminated by generating an 'end-of-file' word EOF1.

It should be noted here that, if the first information signal is longer, such that recording in the second track T_2 has not yet terminated when again reaching the boundary between the first and second subportion P_1 and P_2 respectively, recording is continued, preferably by reversing the direction of transport of the record carrier 2 and positioning the write head 34 on the track T_3 . In another embodiment, recording could be continued in the portion of the second track T_2 , located in the first subportion P_1 .

It should further be noted that the use and recording of BOF and EOF words is not strictly necessary. It may be possible to identify the beginning position and the end position of an information signal recorded, by eg. the (sync) block numbers of the first and last block of the information signal recorded.

The distance between two subsequent datablocks recorded can be bridged either at the nominal recording transport speed of the record carrier, or at an increased transport speed.

Suppose an information signal, having a bitrate of p (which equals eg. 4) Mbit/s, should be recorded on the record carrier, whilst the bitrate of the 'transmission channel' via the recording medium is q (which equals eg. 12) Mbit/s. Blocks of information of the information signal can now be buffered in a buffer (not shown) at the rate of p Mbit/s and read out from the buffer at the rate of q Mbit/s, realizing a time compression of q/p (which equals 3 in the present example). The time compressed blocks are now recorded in the track on the record carrier. When maintaining the record carrier speed during the time intervals in which no time compressed blocks are written on the record carrier, the distance between the time compressed blocks recorded in the track is $q/p-1$ times the length of the time compressed blocks recorded on the record carrier. Thus, in the present example, two other information signals of 4 Mbit/s, or one other information signal of 8 Mbit/s, can be recorded in an interleaved way in the first subportion, as will be explained hereafter.

Next, a second information signal is to be recorded on the record carrier 2. This is shown in figure 4. Prior to starting recording, the write head 34 is, or is positioned in, the start position s . Next, recording of the second information signal in track T_1 is started. In the first recording mode, the formatter unit 32 generates blocks of data of the second information signal. Those blocks of data, denoted $B_{2,1}$, $B_{2,2}$, $B_{2,3}$ are intermittently recorded the track T_1 , as far as located in the first subportion P_1 . The first block $B_{2,1}$ again

comprises the 'begin-of-file' word BOF2. The blocks are recorded in the empty portions between the blocks $B_{1,1}$, $B_{1,2}$, $B_{1,3}$, $B_{1,4}$ of the first information signal. As there is no more information of the second information signal than the information already stored in the blocks $B_{2,1}$, $B_{2,2}$, $B_{2,3}$, recording is terminated. Thus, the block $B_{2,3}$ comprises the 'end-of-file' word, denoted EOF2.

Next, a third information signal is to be recorded on the record carrier 2. This is shown in figure 5. Prior to starting recording, the write head 34 is, or is positioned in, the start position s . Next, recording of the third information signal in track T_1 is started. In the first recording mode, the formatter unit 32 generates blocks of data of the third information signal. Those blocks of data, denoted $B_{3,1}$, $B_{3,2}$, $B_{3,3}$, $B_{3,4}$ are intermittently recorded the track T_1 , as far as located in the first subportion P_1 . The first block $B_{3,1}$ again comprises the 'begin-of-file' word, denoted BOF3. The blocks are recorded in the empty portions between the blocks of the first and second information signals already recorded in the track T_1 . As the total third information signal to be recorded is longer than the amount of information that can be recorded in the blocks $B_{3,1}$ to $B_{3,4}$, the apparatus is switched into a second recording mode upon reaching the boundary between the first and the second subportion P_1 and P_2 respectively. In the second recording mode, the apparatus continuously records the remaining portion of the first information signal in the second subportion P_2 .

The remaining portion of the third information signal cannot be recorded in the track T_1 , as the track T_1 is already occupied by the recorded first information signal. Therefore, the write head 34 is positioned on an empty track, such as the track T_3 and the remaining portion of the third information signal is continuously recorded in the third track T_3 . Recording is terminated by generating an 'end-of-file' word EOF3.

Next, a fourth information signal is to be recorded on the record carrier 2. This is shown in figure 6. Prior to starting recording, the write head 34 is, or is positioned in, the start position s . Next, recording of the fourth information signal is started. It is assumed that recording is started in the track T_4 , as shown in figure 6. In the first recording mode, the formatter unit 32 generates blocks of data of the fourth information signal. Those blocks of data, denoted $B_{4,1}$, $B_{4,2}$, $B_{4,3}$, $B_{4,4}$ are intermittently recorded the track T_4 , as far as located in the first subportion P_1 . The first block $B_{4,1}$ again comprises a 'begin-of-file' word, denoted BOF4. As the total fourth information signal to be recorded is longer than the amount of information that can be recorded in the blocks $B_{4,1}$ to $B_{4,4}$, the apparatus is switched into a second recording mode upon reaching the boundary between the first and the second subportion P_1 and P_2 respectively. In the second recording mode, the apparatus

continuously records the remaining portion of the first information signal in the second subportion P_2 .

It is assumed that the remaining portion of the third information signal cannot be recorded in any of the tracks T_1 to T_{n-2} . Therefore, the write head 34 is positioned on an empty track, which is the track T_{n-1} and recording of the fourth information signal is continued by continuously recording the fourth information signal in the track T_{n-1} . Upon reaching the end of the record carrier 2, the direction of transport of the record carrier is reversed and the write head is positioned on the track T_n . The continuous recording mode is continued by recording the fourth information signal in the track T_n , until reaching the boundary between the first and the second subportions. Recording of the fourth information signal is now continued by continuously recording the information signal in the portion of the track T_n located in the first subportion of the record carrier, without changing the transport direction of the record carrier.

Upon reaching the start location s , recording is continued by positioning the write head 34 on the track T_{n-1} and reversing the direction of transport of the record carrier, so that the fourth information signal can be recorded in the portion of the track T_{n-1} located in the first subportion P_1 of the record carrier 2. Upon again reaching the start location s , recording can be continued by positioning the write head 34 on the track T_{n-2} and reversing the direction of transport of the record carrier again, so that the remaining portion of the fourth information signal can be recorded in the portion of the track T_{n-2} located in the first subportion P_1 of the record carrier 2.

It should be noted here, that the distance between successive blocks of information of one and the same information signal in a track is such that, upon reproduction, a continuous datastream can be regenerated.

Whilst the invention has been described with reference to preferred embodiments thereof, it is to be understood that these are not limitative examples. Thus, various modifications may become apparent to those skilled in the art, without departing from the scope of the invention, as defined by the claims. Thus, although the invention has been described with reference to the recording of an information signal in one track, it may be clear that the recording in a plurality of tracks is equally well within the scope of the present invention. Further, in the above figure description, it has been explained how information signals can be recorded in a portion of the record carrier located between the start position s and the end of the record carrier. It will be clear that by mirror imaging the concept described, information signals can be recorded between said start position and the beginning

of the record carrier, namely in the situation where the start location is somewhere halfway the total length of the record carrier, such as is well known in the art, see WO 95/34,892 A1, document D8 in the list of related documents.

The blocks recorded in the first subportion need not all have the same length.

- 5 Further, the location of the boundary between the first and second subportions can be appropriately chosen.

Further, the invention lies in each and every novel feature or combination of features.

- 10 In accordance with the invention, a record carrier can be obtained with a short access time to an increased number of recorded information signals. In the example described above, when a read head for reading information from a track, such as the track T_1 , is located at the start position s , it can more or less instantaneously access three information signals from the track T_1 for reproduction. Further, the invention results in an improved utilization of the storage capacity on the record carrier.

Related documents.

- (D1) WO 96/18,188 A2 (PHN 15.140), which corresponds to US ser. no. 08/569,5-27.
- 5 (D2) EP patent appln. no. 96202074.9 (PHN 15.902), filing date 22.07.96, which corresponds to US ser. no.
- (D3) EP pat. appln. no. 95202926.2 (PHN 15.520), filing date 30.10.95, which corresponds to US ser. no. 08/738.563.
- (D4) EP pat. appln. no. 95203028.6 (PHN 15.543), filing date 08.11.95, which corresponds to US ser. no. 08/744.802.
- 10 (D5) EP pat. appln. no. 95203029.4 (PHN 15.545), filing date 08.11.95, which corresponds to US ser. no. 08/744.801.
- (D6) EP pat. appln. no. 95203192.0 (PHN 15.563), filing date 21.11.95, which corresponds to US ser. no. 08/744.798.
- (D7) EP pat. appln. no. 95203380.1 (PHN 15.594), filing date 07.12.95, which
15 corresponds to US ser. no. 08/759,668.
- (D8) WO 95/34,892 A1.

CLAIMS

1. Apparatus for recording information signals in a track on a record carrier, comprising
- input means for receiving an information signal,
 - processing means for processing the information signal so as to make the information signal
- 5 suitable for recording in at least one track on said record carrier,
- writing means for writing, after processing, the information signal in said at least one track on said record carrier, starting from a start position viewed in the length direction of the record carrier and in a direction towards one of the end positions of the record carrier, characterized in that the portion of the record carrier between said start position and said one
- 10 end position is fictitiously divided into a first sub portion lying adjacent the start position and a second sub portion lying adjacent the end position of the record carrier, and that the apparatus is adapted to record a first portion of a first information signal as blocks of information intermittently in said at least one track in said first subportion of the record carrier, starting from said start position, and to record a second portion of the said first
- 15 information signal continuously in said second subportion of the record carrier.
2. Apparatus as claimed in claim 1, characterized in that the apparatus is adapted to record at least a first portion of a second information signal as blocks of information intermittently in said at least one track in said first subportion of the record carrier, in between the blocks of information of the first information signal, starting from said start
- 20 position.
3. Apparatus as claimed in claim 2, characterized in that the apparatus is adapted to record the second information signal in its entirety as blocks of information intermittently in said at least one track in said first subportion of the record carrier, in between the blocks of information of the first information signal, starting from said start position.
- 25 4. Apparatus as claimed in claim 1, characterized in that the apparatus is adapted to record at least a first portion of a second information signal as blocks of information intermittently in said at least one track in said first subportion of the record carrier, in between the blocks of information of the first information signal, starting from said start position, and to record a second portion of the said second information signal continuously in



at least one other track in said second subportion of the record carrier.

5. Apparatus as claimed in claim 1, characterized in that the apparatus is adapted to record said second portion of the said first information signal continuously in one or more of the tracks in said second subportion of the record carrier, in a direction towards the said one end position of the record carrier, to continue the recording of said second portion of the said first information signal continuously in one or more other tracks in said second subportion of the record carrier, in a direction towards the start position.

6. Apparatus as claimed in claim 5, characterized in that the apparatus is adapted to continue the recording of said second portion of the said first information signal continuously in said one or more other tracks in said first subportion of the record carrier, in the direction towards the start position.

7. Apparatus as claimed in claim 6, characterized in that the apparatus is adapted to continue the recording of said second portion of the said first information signal continuously in one or more of again other tracks in said first subportion of the record carrier, in the direction towards the said one end position of the record carrier.

8. Apparatus as claimed in claim 7, characterized in that the apparatus is adapted to continue the recording of the said second portion of the said first information signal continuously in one or more of once again other tracks in said first subportion of the record carrier in the direction towards the said start position.

9. Apparatus as claimed in claim 5, characterized in that the apparatus is adapted to continue the recording of said second portion of the said first information signal continuously in one or more of again other tracks in said second subportion of the record carrier, in the direction towards the said one end position of the record carrier.

10. Method of recording information signals in a track on a record carrier, comprising the steps of

- receiving an information signal,
- processing the information signal so as to make the information signal suitable for recording in at least one track on said record carrier,
- writing, after processing, the information signal in said at least one track on said record carrier, starting from a start position viewed in the length direction of the record carrier and in a direction towards one of the end positions of the record carrier,

characterized in that the portion of the record carrier between said start position and said one end position is fictitiously divided into a first sub portion lying adjacent the start position and a second sub portion lying adjacent the end position of the record carrier, and that the



method comprises the steps of recording a first portion of a first information signal as blocks of information intermittently in said at least one track in said first subportion of the record carrier, starting from said start position, and recording a second portion of the said first information signal continuously in said second subportion of the record carrier.

- 5 11. Record carrier having an information signal recorded on it in a track on the record carrier, the portion of the record carrier between a start position and one end position of the record carrier being fictitiously divided into a first sub portion lying adjacent the start position and a second sub portion lying adjacent the end position of the record carrier, a first portion of the information signal being intermittently recorded as blocks of information in
10 said first subportion of the record carrier, starting from said start position, and a second portion of the information signal being continuously recorded in said second subportion of the record carrier.



1/3




FIG. 1




FIG. 2

2/3




FIG. 3




FIG. 4




FIG. 5





FIG. 6



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : G11B 5/008, 20/12	A2	(11) International Publication Number: WO 98/44485 (43) International Publication Date: 8 October 1998 (08.10.98)
(21) International Application Number: PCT/IB98/00275 (22) International Filing Date: 5 March 1998 (05.03.98) (30) Priority Data: 97200978.1 3 April 1997 (03.04.97) EP (34) Countries for which the regional or international application was filed: NL et al. (71) Applicant: KONINKLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL). (71) Applicant (for SE only): PHILIPS NORDEN AB [SE/SE]; Kottbygatan 7, Kista, S-164 85 Stockholm (SE). (72) Inventor: TREFFERS, Menno, Anne; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). (74) Agent: VAN DER KRUK, Willem, L.; Internationaal Oc- trooibureau B.V., P.O. Box 220, NL-5600 AE Eindhoven (NL).	(81) Designated States: JP, SG, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>Without international search report and to be republished upon receipt of that report.</i>	

(54) Title: APPARATUS FOR AND METHOD OF RECORDING INFORMATION SIGNALS ON A RECORD CARRIER



(57) Abstract

An apparatus for recording information signals in a track (T_i) on a record carrier (2) is disclosed, comprising an input terminal (30) for receiving an information signal, a signal processing unit (32) for processing the information signal so as to make the information signal suitable for recording in at least one track on said record carrier, and a writing unit (33) for writing, after processing, the information signal in said at least one track on said record carrier, starting from a start position (s) viewed in the length direction of the record carrier and in a direction towards one of the end positions of the record carrier. The portion of the record carrier (2) between said start position (s) and said one end position (L₂) is fictitiously divided into a first sub portion lying (P₁) adjacent the start position and a second sub portion (P₂) lying adjacent the end position of the record carrier. When recording a first information signal, a first portion of a first information signal is recorded by intermittently recording blocks of information (B_{1,1}, B_{1,2}, B_{1,3}, ...) in said track (T₁) in said first subportion (P₁) of the record carrier, starting from said start position (s). A second portion of the said first information signal is continuously recorded in said second subportion of the record carrier.