

04/09/02
2002053361

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

CORRECTED VERSION

(19) World Intellectual Property Organization
International Bureau



162162

(43) International Publication Date
12 September 2002 (12.09.2002)

PCT

(10) International Publication Number
WO 02/070191 A1

(51) International Patent Classification⁷: **B23K 35/36**,
H01L 21/56, 23/29

(21) International Application Number: PCT/US01/47898

(22) International Filing Date:
13 December 2001 (13.12.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
09/755,146 8 January 2001 (08.01.2001) US

(71) Applicant (for all designated States except US): **HENKEL
LOCTITE CORPORATION** [US/US]; Bauman, Steven,
C., 1001 Trout Brook Crossing, Rocky Hill, CT 06067
(US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **KONARSKI, Mark,**

K. [US/US]; 4 Merritt Lane, Old Saybrook, CT 06475
(US). **KRUG, John, P.** [US/US]; Unit D2, 400 Washing-
ton Street, Middletown, CT 06457 (US).


(74) Agent: **BAUMAN, Steven, C.**; Loctite Corporation, 1001
Trout Brook Crossing, Rocky Hill, CT 06067 (US).

(81) Designated States (national): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NO, NZ, PH, PL, PT, RO, RU, SD, SE, SG, SI,
SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU,
ZA, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR,
GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent

[Continued on next page]

(54) Title: FLUXING UNDERFILL COMPOSITIONS



(57) Abstract: This invention relates to fluxing underfill compositions useful for fluxing metal surfaces in preparation for providing an electrical connection and sealing the space between semiconductor devices, such as chip size or chip scale packages ("CSPs"), ball grid arrays ("BGAs"), land grid arrays ("LGAs"), flip chip assemblies ("FCs") and the like, each of which having a semiconductor chip, such as large scale integration ("LSI"), or semiconductor chips themselves and a circuit board to which the devices or chips, respectively, are electrically interconnected. The inventive fluxing underfill composition begins to cure at about the same temperature that solder used to establish the electrical interconnection melts.

WO 02/070191 A1



ACTION

WO 02/070191 A1

(BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR,
NE, SN, TD, TG).

(15) Information about Correction:

see PCT Gazette No. 52/2002 of 27 December 2002, Sec-
tion II

Published:

— *with international search report*

(48) Date of publication of this corrected version:

27 December 2002

*For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.*