



- (51) International Patent Classification:
A62C 35/68 (2006.01)
- (21) International Application Number:
PCT/US2014/063925
- (22) International Filing Date:
4 November 2014 (04.11.2014)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
61/899,855 4 November 2013 (04.11.2013) US
61/962,427 7 November 2013 (07.11.2013) US
- (71) Applicant: TYCO FIRE PRODUCTS LP [US/US]; 1400
Pennbrook Parkway, Lansdale, PA 19446 (US).
- (72) Inventors: RINGER, Yoram; 499 Elmgrove Avenue,
Providence, RI 02906 (US). YANG, Su; 87 Warrington
Street, Providence, RI 02907 (US).
- (81) Designated States (*unless otherwise indicated, for every
kind of national protection available*): AE, AG, AL, AM,
AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY,

BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM,
DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT,
HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR,
KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG,
MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM,
PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC,
SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN,
TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

- (84) Designated States (*unless otherwise indicated, for every
kind of regional protection available*): ARIPO (BW, GH,
GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ,
TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU,
TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE,
DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU,
LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK,
SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, KM, ML, MR, NE, SN, TD, TG).

Published:

- *without international search report and to be republished
upon receipt of that report (Rule 48.2(g))*

(54) Title: INTEGRATED FLUID CONTROL VALVE AND VALVE ACTUATOR ASSEMBLY




Fig. 1A

(57) Abstract: Systems and methods of an integrated fluid control valve and valve actuator assembly are provided. The assembly includes a pressure operated fluid control valve for controlling the flow of liquid from a liquid supply piping system into a sprinkler piping system of a fire protection system when transitioning the fire protection system from a stand-by state to an actuated state. The control valve defines a valve chamber for holding a pressurized fluid to prevent the flow of fluid through the control valve. A valve actuator is coupled to the fluid control valve housing for setting of the fluid control valve in an unactuated ready state and for operating the fluid control valve automatically and/or manually. Automatic control devices can be placed in fluid communication with the valve actuator to maintain and control operation of the valve actuator for controlled operation of the fluid control valve.