

Claims

1. A resource configuration method, comprising:

receiving, by a terminal, first configuration information and/or ~~second~~ third configuration information sent by a network device, the first configuration information being configured to indicate a first time period ~~corresponding to~~ of a first search space and the ~~second configuration information being configured to indicate a second time period corresponding to~~ where first Up Link (UL)/Down Link (DL) configuration information is located, and the third configuration information being configured to determine a starting slot location of the first UL/DL configuration information in the first time period; and

~~selecting, by the terminal, one piece of configuration information from the first configuration information and/or the second configuration information as target configuration information, and~~ receiving, by the terminal, the first UL/DL configuration information based on the first ~~a~~ time period and the starting slot location in the first time period ~~corresponding to the target configuration information.~~

2. ~~The method as claimed in claim 1, wherein selecting, by the terminal, one piece of configuration information from the first configuration information and/or the second configuration information as the target configuration information comprises:~~

~~in a case where the terminal receives the first configuration information sent by the network device, determining, by the terminal, the first configuration information as the target configuration information, or~~

~~in a case where the terminal receives the second configuration information sent by the network device, determining, by the terminal, the second configuration information as the target configuration information, or~~

~~in a case where the terminal receives the first configuration information and second configuration information sent by the network device, determining, by the terminal, the second configuration information as the target configuration information.~~

3. ~~The method as claimed in any one of claims 1 to 2, further comprising:~~

~~receiving, by the terminal, third configuration information sent by the network device, the third configuration information being configured for determining a time-domain starting location of the first UL/DL configuration information in the time period corresponding to the target configuration information; and~~

~~starting receiving, by the terminal, the first UL/DL configuration information from the time-domain starting location in the time period corresponding to the target configuration information.~~

42. The method as claimed in claim 31, wherein ~~that the third configuration information is configured for determining the time domain starting location of the first UL/DL configuration information in the time period corresponding to the target configuration information comprises that:~~

~~_the third configuration information is configured for determining a starting slot location of the first UL/DL configuration information in the time period corresponding to the target configuration information; or,~~

the third configuration information is further configured to determine~~for determining~~ a slot offset of the first UL/DL configuration information relative to a reference slot in the first time period ~~corresponding to the target configuration information.~~

53. The method as claimed in ~~any one of claims 3 to 4~~claim 1, wherein receiving, by the terminal, the third configuration information sent by the network device comprises:

receiving, by the terminal, the third configuration information sent by the network device through Radio Resource Control (RRC) signaling or common control signaling or dedicated control signaling.

~~6. A resource configuration method, comprising:~~

~~receiving, by a terminal, third configuration information sent by a network device, the third configuration information being configured for determining a time domain starting location of first Up Link (UL)/Down Link (DL) configuration information in a target time period; and~~

~~starting receiving, by the terminal, the first UL/DL configuration information from the time domain starting location in the target time period.~~

7. The method as claimed in claim 6, wherein ~~that the third configuration information is configured for determining the time domain starting location of the first UL/DL configuration information in the target time period comprises that:~~

~~the third configuration information is configured for determining a starting slot location of the first UL/DL configuration information in the target time period; or,~~

~~the third configuration information is configured for determining a slot offset of the first UL/DL configuration information relative to a reference slot in the target time period.~~

8. The method as claimed in ~~any one of claims 6 to 7~~, wherein ~~receiving, by the terminal, the third configuration information sent by the network device comprises:~~

~~receiving, by the terminal, the third configuration information sent by the network device through Radio Resource Control (RRC) signaling or common control signaling or dedicated control signaling.~~

94. A resource configuration device, comprising:

a first receiving unit, configured to receive first configuration information ~~and/or second configuration information~~ sent by a network device, the first configuration information being configured to indicate a first time period ~~corresponding to~~ of a first search space ~~and the second configuration information being configured to indicate a second time period corresponding to~~ where first Up Link (UL)/Down Link (DL) configuration information is located;

a third receiving unit, configured to receive third configuration information sent by the network device, the third configuration information being configured to determine a starting slot location of the first UL/DL configuration information in the first time period ~~a selection unit, configured to select one piece of configuration information from the first configuration information and/or the second configuration information as target configuration information;~~
and

a second receiving unit, configured to receive the first UL/DL configuration information based on a the first time period and the starting slot location in the first time period corresponding to the target configuration information.

10. The device as claimed in claim 9, wherein the selection unit is configured to determine, in a case where a terminal receives the first configuration information sent by the network device, the first configuration information as the target configuration information, or

~~the selection unit is configured to determine, in a case where the terminal receives the second configuration information sent by the network device, the second configuration information as the target configuration information, or~~

~~the selection unit is configured to determine, in a case where the terminal receives the first configuration information and second configuration information sent by the network device, the second configuration information as the target configuration information.~~

11. The device as claimed in any one of claims 9 to 10, further comprising:

~~a third receiving unit, configured to receive third configuration information sent by the network device, the third configuration information being configured for determining a time-domain starting location of the first UL/DL configuration information in the time period corresponding to the target configuration information, wherein~~

~~the second receiving unit is configured to start receiving the first UL/DL configuration information from the time-domain starting location in the time period corresponding to the target configuration information.~~

125. The device as claimed in claim 114, wherein that the third configuration information is configured for determining the time-domain starting location of the first UL/DL configuration

information in the time period corresponding to the target configuration information comprises that:

~~the third configuration information is configured for determining a starting slot location of the first UL/DL configuration information in the time period corresponding to the target configuration information; or,~~

the third configuration information is further configured to determine~~for determining~~ a slot offset of the first UL/DL configuration information relative to a reference slot in the first time period ~~corresponding to the target configuration information.~~

136. The device as claimed in claim 125, wherein the reference slot is determined based on one of the following manners:

the reference slot is determined based on a configuration of a protocol; or,

the reference slot is determined based on a configuration of the network device.

147. The device as claimed in ~~any one of claims 11 to 13~~claim 4, wherein the third receiving unit is configured to receive the third configuration information sent by the network device through Radio Resource Control (RRC) signaling or common control signaling or dedicated control signaling.

15. ~~The device as claimed in any one of claims 9 to 14, wherein the first search space is a search space for a Group Common Physical Downlink Control Channel (GC-PDCCH), and the first UL/DL configuration information is dynamic Slot Format Indication (SFI) information, the dynamic SFI information being borne in the GC-PDCCH.~~

16. ~~A resource configuration device, comprising:~~

~~a third receiving unit, configured to receive third configuration information sent by a network device, the third configuration information being configured for determining a time-domain starting location of first Up Link (UL)/Down Link (DL) configuration information in a target time period; and~~

~~a second receiving unit, configured to start receiving the first UL/DL configuration information from the time domain starting location in the target time period.~~

17. The device as claimed in claim 16, wherein that the third configuration information is configured for determining the time-domain starting location of the first UL/DL configuration information in the target time period comprises that:

~~the third configuration information is configured for determining a starting slot location of the first UL/DL configuration information in the target time period; or,~~

~~the third configuration information is configured for determining a slot offset of the first UL/DL configuration information relative to a reference slot in the target time period.~~

~~18. The device as claimed in claim 17, wherein the reference slot is determined based on one of the following manners:~~

~~the reference slot is determined based on a configuration of a protocol; or,~~

~~the reference slot is determined based on a configuration of the network device.~~

~~19. The device as claimed in any one of claims 16 to 18, wherein the third receiving unit is configured to receive the third configuration information sent by the network device through Radio Resource Control (RRC) signaling or common control signaling or dedicated control signaling.~~

~~20. The device as claimed in any one of claims 16 to 19, wherein the first UL/DL configuration information is dynamic Slot Format Indication (SFI) information.~~