


INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification G01K 3/04		A1	(11) International Publication Number WO 99/36755
			(43) International Publication Date 22 July 1999 (22 07 99)
(21) International Application Number PCT/GB99/00044		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG)	
(22) International Filing Date 18 January 1999 (18 01 99)		Published With international search report	
(30) Priority Data: 9800814 7 16 January 1998 (16 01 98) GB			
(71) Applicant (for all designated States except US): FOOD GUARDIAN LIMITED [GB/GB], Ashfields, Leigh Sinton, Malvern Worcestershire WR13 5DH (GB)			
(72) Inventors; and (75) Inventors/Applicants (for US only): MOULE, Robert [GB/GB] Chygurno Lamorna, Penzance TR19 6XH (GB) MOULE Simon [GB/GB], 42 Endymion Road, London N4 1EQ (GB).			
(74) Agent: ATKINSON, Peter, Birch Marks & Clerk, Sussex House 53-85 Mosley Street, Manchester M2 3LG (GB).			

(54) Title BARRIER MATERIALS AND PRODUCTS PRODUCED THEREWITH

(57) Abstract

A marking element (1) for indicating whether a pre-defined temperature condition has been maintained. The element comprises a first material (7) capable of flowing above a predetermined temperature



separated from a second absorbent material (5, 10) by a heat disruptable barrier layer (4). The first and second materials are such that when the barrier layer is punctured and the predetermined temperature is exceeded the first material flows in the second material to produce a detectable change. The heat disruptable barrier layer (4) is comprised of a heat disruptable material (8) associated with an element (9) capable of being inductively heated by electromagnetic energy to effect disruption of said material thereby to activate the marking element.



162162



G00002

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KF	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						