



Description

The present invention relates to the purification of carboxylic acids and in particular to a process for removing iodide and oxidisable impurities from carboxylic acids, preferably acetic acid.

5 The liquid phase carbonylation of methanol is a well known industrially operated process and is widely operated commercially. The carbonylation process, which is typically catalysed by rhodium and methyl iodide, is described in detail in, for example, UK patent number GB 1233121. European patent application number EP 87870 describes a modification of this process in which acetic acid is coproduced with acetic anhydride, from mixtures of methanol, methyl acetate and water under anhydrous conditions.

10 A problem with acetic acid produced by processes such as those described in GB 1233121 and EP-A-87870 is that even after purification by conventional distillation it still contains oxidisable impurities and relatively large amounts (typically 100 ppb - 2ppm) of iodide impurities. For certain applications, e.g. in the subsequent conversion of the acetic acid into vinyl acetate, these impurities are detrimental and need to be removed.

15 UK patent GB 1201260 relates to purification of formic acid by treatment with hydrogen peroxide to reduce colour-forming impurities. Soviet patent number SU 1437363 relates to purification of acetic acid being regenerated in the production of cellulose acetates and acetic anhydride by treating with hydrogen peroxide in the presence of polyphosphoric acid or a salt thereof. Japanese laid open patent application number H2-134342 relates to decolourisation of acetic acid with hydrogen peroxide or percarboxylic acid.

20 None of these publications addresses the problem of removing iodide impurities from carboxylic acids.

European patent publication number EP-A-0013551 relates to a process for removing iodine from organic compounds in which the compounds are treated at 50 to 200 °C with oxidising agents such as oxygen or hydrogen peroxide and the reaction mixture is brought into contact with an adsorption agent for example active carbon. The compounds envisaged for treatment are in particular the products of oxidative
25 acylation of olefins. EP-A-0013551 does not describe purification of carboxylic acids produced by carbonylation to remove iodide and oxidisable impurities. EP-A-0013551 does not describe recovering purified carboxylic acid from hydrogen-peroxide-treated-acid by distillation or evaporation.

UK patent number GB 1293774 describes a process for the purification of carboxylic acids contaminated with trace amounts of halides by treating with an inorganic oxidising agent and subjecting the treated
30 acid to distillation. According to GB 1293774, the oxidising agent contains an alkali metal and/or chromium or a metal of Groups VIIB of the periodic table according to Deming. The preferred treating agents contain sodium or potassium and manganese or chromium; potassium and sodium permanganate being especially preferred.

European patent number EP 0217191B describes a process for the separation of iodine and its
35 compounds from the carbonylation products obtained in the carbonylation of dimethyl ether, methyl acetate or methanol. The process of EP 0217191B comprises treating the carbonylation products at temperatures of 20 °C to 200 °C with peracetic acid, diacetyl peroxide or compounds forming these under the reaction conditions and then separating the product by distillation. This is said to reduce iodine contents to less than 20 ppb in the carbonylation products.

40 PCT application WO 92/03403 published 5 March 1992 but claiming a priority date of 15 August 1990 describes a process for the purification of a mixture of acetic anhydride and acetic acid obtained from carbonylation processes utilising iodine and/or iodide compounds by contacting the mixture with (1) a peroxide and (2) hydrogen in the presence of a supported palladium catalyst.

Such processes are not entirely satisfactory. The problem to be solved therefore is to provide a process
45 for removing iodide and oxidisable impurities from carboxylic acids which have been prepared by carbonylation. Thus, according to the present invention there is provided a process for purifying impure carboxylic acid which has been prepared by the carbonylation of a suitable reactant in the presence of a carbonylation catalyst and an iodide promoter and which contains iodide and oxidisable impurities, which process comprises the steps of: (a) contacting the impure carboxylic acid with hydrogen peroxide, and not
50 contacting the impure carboxylic acid with hydrogen in the presence of a supported palladium catalyst, and (b) recovering purified carboxylic acid having a reduced content of iodide and oxidisable impurities from the product of step (a) by distillation or evaporation.

The process of the present invention is suitable for removing iodide and oxidisable impurities from
55 carboxylic acids having up to 6 carbon atoms preferably acetic acid, propionic acid and/or butyric acids, more preferably acetic acid.

Processes for preparing carboxylic acids by carbonylation are known in the art. Suitably the acid is produced by the carbonylation of an alkyl ester of a carboxylic acid, an alkanol, an alkyl halide and/or a dialkyl ether in the presence of a Group VIII metal carbonylation catalyst, for example rhodium or iridium



and in the presence of an iodide promoter. Acetic acid may be prepared by carbonylation of methanol, methyl acetate, methyl halide and/or dimethyl ether. Suitable processes for preparing acetic acid are described in GB 1233121 and EP-A-87870, the contents of which are hereby incorporated by reference. Suitably the carboxylic acid is separated from the carbonylation catalyst and iodide promoter by distillation and/or evaporation before purification by the process of the present invention. Distillation to remove the bulk of the iodide and/or oxidisable impurities prior to contacting with hydrogen peroxide may also be used depending upon the concentrations of the impurities.

The iodide impurities comprise iodine-containing compounds, for example, methyl iodide, butyl iodide, hexyl iodide and inorganic iodides, typically at 100 ppb to 2 ppm total iodine in the acid.

The exact nature of the oxidisable impurities is not known, but their presence causes the carboxylic acid to have a permanganate time of less than 2 hours and so fail the permanganate test as herein defined.

The process of the present invention can reduce iodide impurities from about 500 ppb to below 50 ppb and oxidisable impurities sufficiently for the carboxylic acid to pass the permanganate test.

The hydrogen peroxide is used as an aqueous solution, preferably at 50-60% w/v.

The amount of hydrogen peroxide used will depend upon the amount of iodide and oxidisable impurities in the carboxylic acid but will generally be in the range 10 to 10000 ppm by weight of the impure carboxylic acid, preferably 100 to 5000 ppm.

Preferably, the impure carboxylic acid is contacted with hydrogen peroxide in the presence of a strong acid. Suitable strong acids for use in the present invention comprise sulphuric acid, methane sulphonic acid, para-toluene sulphonic acid, trifluoroacetic acid, phosphoric acid and strong acid ion exchange resins such as Amberlyst 15. A preferred strong acid is sulphuric acid.

The strong acid may be used without dilution but conveniently may be used as a solution in the carboxylic acid. The amount of sulphuric acid used in step (a) may be in the range 10 to 1000 ppm.

The temperature at which step (a) is performed should be high enough to prevent the carboxylic acid freezing at one extreme or boiling at the other. The temperature will depend upon a number of factors. In particular, the higher the temperature the faster the reaction between the hydrogen peroxide and the impurities but also the faster it decomposes. Typically, for acetic acid, the temperature will be in the range 20 to 118°C although higher temperatures may be used if the process is operated at superatmospheric pressure.

The step (a) of the process may be operated at subatmospheric, atmospheric or superatmospheric pressure, preferably atmospheric pressure.

The contact time of the impure carboxylic acid with the hydrogen peroxide will depend upon such factors as the concentration of impurities and reagents, and the temperature, but will generally be in the range 1 minute to 24 hours, preferably 10 minutes to 5 hours.

In step (b) the purified carboxylic acid is recovered by distillation or evaporation, preferably as a liquid side draw from a multistage fractional distillation column, with small heads and base bleeds. A residues concentrator may be used on the base bleed from the distillation column to reduce the volume of residues, with return of acid to the distillation column.

It is possible to perform steps (a) and (b) together by adding the hydrogen peroxide and optional strong acid to a distillation column. Preferably the steps may be performed separately in sequence rather than simultaneously.

The process of the present invention may be performed as a batch or continuous process. A batch process generally produces better quality product acid but on an industrial scale a continuous process is generally preferred.

When sulphuric acid is used as the strong acid in step (a) the separated carboxylic acid in step (b) may contain sulphur impurities. Contamination of the purified carboxylic acid by these sulphur impurities may be reduced by the use of a suitable metal salt in the distillation/evaporation step (b). Suitable metal salts are carboxylate salts such as acetate salts and/or are nitrate salts, for example potassium, silver and/or calcium carboxylate eg acetate and/or nitrate. Suitable salts are also potassium and/or magnesium hydroxide and/or copper (I) oxide. Carboxylate salts may be added to step (b) as such or may be formed in situ by the addition of hydroxides. Preferred salts are potassium carboxylate, particularly acetate and silver nitrate. More than one salt may be used. Suitably the metal salt is present at from about 1% w/w to about 10% w/w, preferably from about 1% w/w to about 7% w/w in the kettle/reboiler of the step (b) distillation column.

Contamination of the purified carboxylic acid by excess peroxide may be reduced by the use of a suitable metal salt in the distillation/evaporation step (b). Suitable metal salts are salts of the carboxylic acid for example carboxylate salts of potassium, silver and/or calcium. Suitable metal salts are also salts such as potassium and/or magnesium hydroxide and/or copper (I) oxide. Carboxylate salts may be added to step (b) as such or may be formed in situ by the addition of hydroxide salts. A preferred metal salt is

potassium carboxylate, particularly potassium acetate. More than one salt may be used. Suitably the metal salt is present at from about 1% w/w to about 15% w/w, preferably about 1% w/w to about 10% w/w in the kettle/reboiler of the step (b) distillation column/evaporator. The metal salts used to reduce peroxide carryover may also be used to reduce sulphur carryover if sulphuric acid is used in step (a).

5 The invention will now be illustrated by reference to the following examples.

10 In the examples iodide impurities were measured by neutron activation analysis. The permanganate times were measured at room temperature by adding 0.1 ml of 0.02 M potassium permanganate to 2 ml of sample and 10 ml of distilled water; the permanganate time being the time required for the pink colour of the permanganate to be discharged. A permanganate time of greater than 2 hours was taken as a pass of the test. Water concentrations were determined by automatic Karl Fischer titration. Sulphur contents were determined by X-ray diffraction (XRF) with a limit of detection of 2 ppm. Samples with very low (ppb) levels of iodide impurities were analysed for sulphur content by microcoulometry down to 0.2 ppm.

Continuous Treatment Experiments

15 Continuous treatment of impure acetic acid prepared by carbonylation was studied using a heated stirred treater vessel from which liquid product was passed to the reboiler of a 12 actual stage distillation column. The distillation column had a purified acid liquid product take-off at stage 4 counted from the base of the column. The distillation column had a pumped heads reflux and small head and base take-off bleeds.

The results of treatment with and without sulphuric acid are

Table 1
Purification of Acetic Acid According to the Present Invention

Experiment No.	Reference	Impure Acetic Acid		Treatment			Product Acetic Acid		
		Peranganate Time (mins)	Iodide Impurities	Reagents	Temp. °C	Time hour	Permanganate Time	Iodide Impurities (ppb)	Sulphur (ppm)
1	AC4/15	20	ca 2ppm	1000ppm H ₂ O ₂	115	1	2-3 hours	137	-
2	AC4/13	20	ca 2ppm	500ppm H ₂ O ₂	115	1	1hr 50 mins	228	-
3	AC4/12	20	ca 2ppm	250ppm H ₂ O ₂	115	1	1 hour	309	-
4	AC4/11	20	ca 2ppm	100ppm H ₂ O ₂	115	1	0.5-1 hour	258	-
5	AC4/16B	20	ca 2ppm	500ppm H ₂ O ₂	75	1	0.5-1 hour	265	-
6	AC4/17	20	ca 2ppm	500ppm H ₂ O ₂ /250ppm H ₂ SO ₄	115	1	>24 hours	94	-
7	AC4/27	70	695ppb	250ppm H ₂ O ₂ /50ppm H ₂ SO ₄	115	1	>6 hours	45	<2
8	AC4/34	10	224ppb	500ppm H ₂ O ₂ /50ppm H ₂ SO ₄	115	1	17 hours	27	-

given in Table 1. Referring to Table 1, it will be seen that treatment with 1000 ppm hydrogen peroxide alone at 115°C produces acid which passes the permanganate test. Table 1 also shows the benefits of using a strong acid such as sulphuric acid. Thus referring to Table 1 it will be seen that treating impure

acetic acid with 500 ppm hydrogen peroxide reduces iodide impurity levels from about 2 ppm to 230 ppb. If 250 ppm sulphuric acid is added to the 500 ppm hydrogen peroxide treatment the level of iodide impurities is further reduced to 94 ppb, comparable with that obtained using 1000 ppm hydrogen peroxide alone. The permanganate time is also improved by the addition of sulphuric acid. Extended operation with sulphuric acid feed to the treater and with a residue concentrator taking residue from the distillation column base bleed and returning acid to the distillation column, resulted in an increase in sulphur impurities in the purified acid.

To show that treatment of impure acetic acid with hydrogen peroxide and sulphuric acid is different from treatment with peracetic acid, comparative experiments A-D were performed using different levels of peracetic acid in place of hydrogen peroxide/sulphuric acid and the results are shown in Table 2. For impure acetic acid containing 224 ppb iodide impurities comparison of experiment AC4/34 in Table 1 with comparison experiment AC4/43 in Table 2 shows, that although 500 ppm hydrogen peroxide has a comparable active oxygen content to 1120 ppm peracetic acid, the presence of 50 ppm sulphuric acid causes a significant improvement in the permanganate time of the treated acid to 17 hours, compared to 2 hours for acid treated with 1140 ppm peracetic acid.

Batch Experiments

In batch experiments, acetic acid prepared by carbonylation was heated in a flask to 115°C before the treatment reagents were added via a syringe directly into the liquid. The mixture was then heated for 1 hour before 85% of the acid was distilled from the flask and analysed. A series of batch experiments were performed using different strong acids. The results are given in Table 3. Referring to Table 3 it will be seen by comparison of Experiment 9

Table 2
Comparative Experiment

Comparative Experiment No.	Reference	Impure Acetic Acid		Treatment			Product Acetic Acid	
		Permanganate Time (mins)	Iodide Impurities (ppb)	Reagents	Temp. °C	Time hours	Permanganate Time (mins)	Iodide Impurities (ppb)
A	AC4/43	10	224	1400ppm CH ₃ CO ₃ H	115	2	120	30
B	AC4/42	10	224	400ppm CH ₃ CO ₃ H	115	2	ca 40	N/A
C	AC4/40	10	224	280ppm CH ₃ CO ₃ H	115	2	ca 20	N/A
D	AC4/41	10	224	280ppm CH ₃ CO ₃ H	100	2	ca 20	N/A

Table 3

Experiment No.	Treatment	Product Acetic Acid Permanganate Time (hours)
9	500ppm H ₂ O ₂	>6
10	140ppm H ₂ O ₂	2.5
11	140ppm H ₂ O ₂ 50ppm H ₂ SO ₄	9.5
12	140ppm H ₂ O ₂ 50ppm H ₃ PO ₄	2
13	140ppm H ₂ O ₂ 250ppm H ₃ PO ₄	6
14	70ppm H ₂ O ₂	0.7
15	70ppm H ₂ O ₂ 50ppm MSA	3.5
16	70ppm H ₂ O ₂ 50ppm TFA	0.8
17	70ppm H ₂ O ₂ 1% Amberlyst 15	1.5
Comp. P	140ppm H ₂ O ₂ 1% acetic anhydride	2.3

MSA = Methane sulphonic acid

TFA = Trifluoroacetic acid

Amberlyst 15 = strong acid ion exchange resin

with Experiment 2 in Table 1 that a batch process produces a better quality product than does a continuous process.

Additives to Reduce Sulphur Impurities

A series of batch experiments were performed by batch distilling the reboiler contents from a continuous treatment distillation column or a solution prepared to simulate such contents by heating together acetic acid, hydrogen peroxide and sulphuric acid. The batch distillations were performed in the absence and presence of various metal salts. Kettle and distillate fractions were analysed for sulphur content during the distillation and the results are shown in Tables 4(a) to (f). The results show all the salts tested, potassium acetate, silver nitrate, calcium nitrate, magnesium hydroxide and copper (I) oxide to be effective in reducing sulphur contamination of the purified acid.

Two continuous experiments were performed using the previously described continuous treatment apparatus. Impure acetic acid containing 224ppb iodide and having a permanganate time of 0.2 hour was treated at 115°C with 500 ppm hydrogen peroxide and 50ppm sulphuric acid in the treater with a residence time of 1 hour before being passed to the distillation column. A metal salt (75ppm potassium acetate or 20ppm silver nitrate) was added to the distillation column reboiler. The results are shown in Table 5. The iodide impurity removal in the presence of silver nitrate was marginally better than in the presence of potassium acetate. A solid (analysed by IR to be a sulphate salt) was found in the distillation column reboiler. The heads bleed from the distillation column contained less than 2ppm sulphur when the salts were used.

Table 4Batch Testing of Metal Salts to Reduce Sulphur Impurities(a) Experiment 18 - No Metal Salt

Fraction	Sulphur in kettle ppm	Sulphur in Distillate Fraction ppm
3	approx 350	2
6	" 570	<2
9	" 850	2
12	" 1100	3
14	1710	11
18	4430	44
21	34000	550

(b) Experiment 19 - 1% Potassium Acetate Added

Fraction	Sulphur in kettle ppm	Sulphur in Distillate Fraction ppm
1	500	<2
5	730	<2
10	1250	<2
14	2780	<2
16	5290	<2

(c) Experiment 20 - 1% Silver Nitrate Added

Fraction	Sulphur in kettle ppm	Sulphur in Distillate Fraction ppm
1	500	2
5	730	2
10	1600	<2
12	3315	<2
14	8825	<2

(d) Experiment 21 - 1% Calcium Nitrate Added

Fraction	Sulphur in kettle ppm	Sulphur in Distillate Fraction ppm
1	500	<2
5	730	2
10	1250	2
14	2780	<2
16	5290	2

(e) Experiment 22 - 1% Magnesium Hydroxide Added

Fraction	Sulphur in kettle ppm	Sulphur in Distillate Fraction ppm
1	500	<2
5	685	<2
10	1080	<2
14	2070	<2
16	3965	<2

(f) Experiment 23 - 1% Copper I Oxide Added

Fraction	Sulphur in kettle ppm	Sulphur in Distillate Fraction ppm
1	500	2
5	785	2
10	1900	2
12	4480	2

Table 5

Continuous Treatment - Addition of Metal Salts to Reduce SulphurImpurities

Run No.	Reboiler Feed	Reboiler Contents	Time on Stream/ days	Product Acid		
				Permanganate Time (hours)	Total Iodide (ppb)	Sulphur (ppm)
115	75 ppm KOAc	3.5% KOAc	1 1/2	>6	11	N/A
			4 1/2	>6	41	N/A
			7	6	14	N/A
			9	3 1/2	N/A	N/A
			9 1/2	6	N/A	N/A
			10 1/2	3.5	N/A	<0.2
			11	2.5	N/A	<0.2
			11 1/2	2.5	23	<0.2
			13	5	16	N/A
115 RUN AVERAGES			-	about 6	16	<0.2

116	20 ppm AgNO ₃	1% AgNO ₃	1	>7	2	<0.3
			3	>6	5	<0.3
			6 1/2	>5	13	<0.3
			7 1/2	6	12	<0.3
			9	>6	12	<0.3
			11	5	16	<0.3
116 RUN AVERAGES			-	about 6	11	<0.3

Table 5 continued

Notes (1) Treater conditions - Temperature = 115°C

Residence time = 1 hour

H₂O₂ treatment = 500ppm

H₂SO₄ treatment = 50ppm

(2) The run averages reflect all the analytical data obtained over the operating period (only some of which is shown in the Table).

(3) Impure acetic acid feed - Total iodides by NAA = 224ppb

Permanganate time = 0.2hrs

Additives to Reduce Excess Peroxide

A batch experiment was performed to show that metal salts can be used to reduce excess peroxide after the treatment of impure carboxylic acid with hydrogen peroxide.

500ml of acetic acid was batch treated with 500ppm hydrogen peroxide and 50ppm sulphuric acid at 115°C for 1 hour. After this time the peroxide concentration was found to be 220ppm (as hydrogen peroxide). 425mls of the acid was then distilled off. The peroxide concentration of the distillate was 199ppm.

An identical sample was treated in the same manner as above, where after 1 hour the peroxide concentration was 236ppm. Potassium acetate was then added to the acetic acid to yield a total concentration of 7% w/w before 425mls of distillate was collected, the peroxide concentration of which was 34ppm.

It is envisaged that in a continuous process the metal salt would be added to the distillation/evaporation stage (b) to reduce excess peroxide carryover into the purified acid product. Such metal salts may also reduce sulphur carryover if sulphuric acid is used in step (a).

Claims

1. A process for purifying impure carboxylic acid which has been produced by carbonylation of a suitable reactant in the presence of a carbonylation catalyst and an iodide promoter and which acid contains iodide and oxidisable impurities characterised in that the process comprises the steps of:

(a) contacting the impure carboxylic acid with hydrogen peroxide, and not contacting the impure carboxylic acid with hydrogen in the presence of a supported palladium catalyst, and

(b) recovering purified carboxylic acid having a reduced content of iodide and oxidisable impurities from the product of step (a) by distillation or evaporation.

2. A process as claimed in claim 1 characterised in that the carboxylic acid has up to 6 carbon atoms.

3. A process as claimed in claim 2 characterised in that the carboxylic acid comprises acetic acid.

4. A process as claimed in any one of the preceding claims characterised in that the step (a) is performed in the presence of a strong acid.

5. A process as claimed in claim 4 characterised in that the strong acid comprises sulphuric acid.

6. A process as claimed in claim 5 characterised in that step (b) is performed in the presence of a metal salt to reduce sulphur contamination of the purified carboxylic acid.

7. A process as claimed in claim 6 characterised in that the metal salt comprises carboxylate and/or nitrate salts of potassium, calcium and/or silver and/or comprises potassium and/or magnesium hydroxide and/or copper (I) oxide.

8. A process as claimed in claim 7 characterised in that the metal salt comprise potassium acetate.
9. A process as claimed in any one of the preceding claims characterised in that step (b) is performed in the presence of a metal salt to reduce peroxide contamination of the purified carboxylic acid.
10. A process as claimed in claim 9 characterised in that the metal salt comprises a carboxylate salt of potassium, silver and/or calcium and/or comprises potassium and/or magnesium hydroxide, and/or copper (I) oxide.
11. A process as claimed in claim 10 characterised in that the metal salt comprises potassium acetate.
12. A process as claimed in any one of the preceding claims characterised in that step (b) comprises a fractional distillation with heads and base bleeds and a liquid side draw of purified carboxylic acid.
13. A process as claimed in any one of the preceding claims in which steps (a) and (b) are performed together in a distillation column.

Patentansprüche

1. Verfahren zur Reinigung einer unreinen Carbonsäure, die durch Carbonylierung eines geeigneten Ausgangsstoffs in Gegenwart eines Carbonylierungskatalysators und eines Iodidpromotors hergestellt worden ist und Iodidverunreinigungen und oxidierbare Verunreinigungen enthält, dadurch gekennzeichnet, daß das Verfahren die folgenden Schritte umfaßt:
 - (a) Inberührungbringen der unreinen Carbonsäure mit Wasserstoffperoxid und nicht Inberührungbringen der unreinen Carbonsäure mit Wasserstoff in Gegenwart eines Palladiumkatalysators auf Träger und
 - (b) Gewinnen einer gereinigten Carbonsäure, die einen reduzierten Gehalt an Jodidverunreinigungen und oxidierbaren Verunreinigungen hat, aus dem Produkt der Stufe (a) durch Destillation oder Verdampfung.
2. Verfahren nach Anspruch 1, dadurch gekennzeichnet, daß die Carbonsäure bis zu 6 Kohlenstoffatome aufweist.
3. Verfahren nach Anspruch 2, dadurch gekennzeichnet, daß die Carbonsäure Essigsäure umfaßt.
4. Verfahren nach einem der vorgehenden Ansprüche, dadurch gekennzeichnet, daß Stufe (a) in Gegenwart einer starken Säure durchgeführt wird.
5. Verfahren nach Anspruch 4, dadurch gekennzeichnet, daß die starke Säure Schwefelsäure umfaßt.
6. Verfahren nach Anspruch 5, dadurch gekennzeichnet, daß Stufe (b) in Gegenwart eines Metallsalzes zur Verringerung einer Schwefelverunreinigung der gereinigten Carbonsäure erfolgt.
7. Verfahren nach Anspruch 6, dadurch gekennzeichnet, daß das Metallsalz Carboxylat- und/oder Nitratsalze von Kalium, Calcium und/oder Silber und/oder Kalium- und/oder Magnesiumhydroxid und/oder Kupfer(I)-oxid umfaßt.
8. Verfahren nach Anspruch 7, dadurch gekennzeichnet, daß das Metallsalz Kaliumacetat umfaßt.
9. Verfahren nach einem der vorhergehenden Ansprüche, dadurch gekennzeichnet, daß Stufe (b) in Gegenwart eines Metallsalzes zur Verringerung einer Peroxidverunreinigung der gereinigten Carbonsäure durchgeführt wird.
10. Verfahren nach Anspruch 9, dadurch gekennzeichnet, daß das Metallsalz ein Carboxylatsalz von Kalium, Silber und/oder Calcium und/oder Kalium- und/oder Magnesiumhydroxid und/oder Kupfer(I)-oxid umfaßt.
11. Verfahren nach Anspruch 10, dadurch gekennzeichnet, daß das Metallsalz Kaliumacetat umfaßt.

12. Verfahren nach einem der vorhergehenden Ansprüche, dadurch gekennzeichnet, daß Stufe (b) eine fraktionierte Destillation mit Köpfen und Basisausläufen und eine Flüssigkeitseitenentnahme von gereinigter Carbonsäure umfaßt.

5 13. Verfahren nach einem der vorhergehenden Ansprüche, in dem die Stufen (a) und (b) zusammen in einer Destillationssäule durchgeführt werden.

Revendications

10 1. Procédé de purification d'acide carboxylique impur qui a été produit par carbonylation d'un corps réactionnel convenable en présence d'un catalyseur de carbonylation et d'un promoteur formé d'un iodure, et qui contient des impuretés du type iodure et des impuretés oxydables, caractérisé en ce qu'il comprend les étapes consistant :

15 (a) à mettre en contact l'acide carboxylique impur avec du peroxyde d'hydrogène sans mise en contact de l'acide carboxylique impur avec de l'hydrogène en présence d'un catalyseur au palladium sur un support, et

(b) à isoler l'acide carboxylique purifié ayant une teneur réduite en iodure et impuretés oxydables du produit de l'étape (a) par distillation ou évaporation.

20 2. Procédé suivant la revendication 1, caractérisé en ce que l'acide carboxylique a jusqu'à 6 atomes de carbone.

3. Procédé suivant la revendication 2, caractérisé en ce que l'acide carboxylique comprend l'acide acétique.

25 4. Procédé suivant l'une quelconque des revendications précédentes, caractérisé en ce que l'étape (a) est mise en oeuvre en présence d'un acide fort.

5. Procédé suivant la revendication 4, caractérisé en ce que l'acide fort comprend l'acide sulfurique.

30 6. Procédé suivant la revendication 5, caractérisé en ce que l'étape (b) est mise en oeuvre en présence d'un sel métallique pour réduire la contamination par le soufre de l'acide carboxylique purifié.

35 7. Procédé suivant la revendication 6, caractérisé en ce que le sel métallique comprend des carboxylates et/ou nitrates de potassium, calcium et/ou argent et/ou comprend de l'hydroxyde de potassium et/ou de magnésium et/ou de l'oxyde de cuivre (I).

8. Procédé suivant la revendication 7, caractérisé en ce que le sel métallique comprend l'acétate de potassium.

40 9. Procédé suivant l'une quelconque des revendications précédentes, caractérisé en ce que l'étape (b) est mise en oeuvre en présence d'un sel métallique pour réduire la contamination par le peroxyde de l'acide carboxylique purifié.

45 10. Procédé suivant la revendication 9, caractérisé en ce que le sel métallique comprend un carboxylate de potassium, d'argent et/ou de calcium et/ou comprend de l'hydroxyde de potassium et/ou de magnésium et/ou de l'oxyde de cuivre (I).

50 11. Procédé suivant la revendication 10, caractérisé en ce que le sel métallique comprend l'acétate de potassium.

12. Procédé suivant l'une quelconque des revendications précédentes, caractérisé en ce que l'étape (b) comprend une distillation fractionnée avec des purges en tête et à la base et un prélèvement latéral de liquide formé d'acide carboxylique purifié.

55 13. Procédé suivant l'une quelconque des revendications précédentes, dans lequel les étapes (a) et (b) sont conduites ensemble dans une colonne de distillation.