

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
16 October 2008 (16.10.2008)

PCT

(10) International Publication Number
WO 2008/124454 A1

(51) International Patent Classification:
F04D 25/16 (2006.01)

Road, Varysburg, NY 14167 (US). **CZECHOWSKI, Edward S.** [US/US]; 7900 Michael Road, Orchard Park, NY 14127 (US).

(21) International Application Number:
PCT/US2008/059169

(74) Agent: **SWANSON, Tait R.**; 7915 FM 1960 West, Suite 330, Houston, TX 77070 (US).

(22) International Filing Date: 2 April 2008 (02.04.2008)

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/921,547 3 April 2007 (03.04.2007) US

(71) Applicant (*for all designated States except US*):
CAMERON INTERNATIONAL CORPORATION [US/US]; 4646 W. Sam Houston Parkway North, Houston, Texas 77041 (US).

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): **SMALL, Robert** [US/US]; 115 Chaumont Drive, Williamsville, NY 14221 (US). **KOLODZIEJ, Robert M.** [US/US]; 2173 Maxon

[Continued on next page]

(54) Title: INTEGRAL SCROLL AND GEARBOX FOR A COMPRESSOR WITH SPEED CHANGE OPTION




FIG. 1
PRIOR ART

(57) Abstract: The volute is cast integrally with the gearbox base to allow closer radial tolerances to be used to improve efficiency. In the preferred embodiment, compressors for multi-stage compression are assembled with intercoolers and the integral volute is cast together with the impeller housing and the lower gearbox housing and the associated intercooler. Efficiency increases of 2% or more are achievable. In multistage applications, efficiency gains in the early stages are compounded in each subsequent stage. Speed changes that change center distance between bull gear and pinion are accommodated by an offset opening in the inlet and diffuser that can line up with the impeller shaft as well as an offset opening in the fluid seal despite a pinion gear change, by reorientation and remounting of those parts.



FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MT, NL,
NO, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG,
CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— *with international search report*

Declarations under Rule 4.17:

- *as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))*
- *as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii))*