



(51) International Patent Classification:
G01L 21/30 (2006.01)

(21) International Application Number:

PCT/US2016/013219

(22) International Filing Date:

13 January 2016 (13.01.2016)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

62/103,968 15 January 2015 (15.01.2015) US
62/191,140 10 July 2015 (10.07.2015) US

(71) Applicant: **MKS INSTRUMENTS, INC.** [US/US]; 2
Tech Drive, Suite 201, Andover, MA 01810 (US).

(72) Inventors: **KELLY, Brandon, J.**; 1317 Lupine Court,
Longmont, CO 80503 (US). **PERCY, Clinton, L.**; c/o Mks
Instruments, Inc., 6450 Dry Creek Parkway, Longmont,
CO 80503 (US). **HEINBUCH, Scott, C.**; 801 Swallow
Road, Fort Collins, CO 80525 (US). **BRUCKER, Ger-
ardo, A.**; 2214 Harvard Court, Longmont, CO 80503 (US).

SWINNEY, Timothy, C.; 2856 Des Moines Drive, Fort
Collins, CO 80525 (US). **PIWONKA-CORLE, Timothy,
R.**; 2100 Mesa Drive, Boulder, CO 80304 (US).

(74) Agents: **SMITH, James, M.** et al.; Hamilton, Brook,
Smith & Reynolds, P.C., 530 Virginia Rd, P.O. Box 9133,
Concord, MA 01742-9133 (US).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY,
BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM,
DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT,
HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR,
KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG,
MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM,
PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC,
SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN,
TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ,
TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU,
TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE,

[Continued on next page]

(54) Title: POLYMER COMPOSITE VACUUM COMPONENTS

(57) Abstract: A gauge having a hous-
ing formed of a polymer material and
one or more electrical feedthrough pins
disposed in the housing. The electrical
feedthrough pins can be oriented sub-
stantially perpendicular to each other
and have complex shapes.




FIG. 1A



DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT,
LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE,
SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA,
GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

— *before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments (Rule 48.2(h))*

Published:

— *with international search report (Art. 21(3))*

(88) Date of publication of the international search report:

8 December 2016