

WHAT IS CLAIMED IS:

1. An interface assembly comprising a mask assembly ~~for an interface for~~ used in providing positive pressure respiratory therapy, the mask assembly comprising:

a mask seal; and

a mask shell that supports the mask seal;

wherein the mask assembly is configured to be fully positioned lower than a bridge of a nose of a face of a user and to provide an exposed bridge of the nose of the user, the mask shell comprising a central portion and a pair of wings sweeping rearwardly of the central portion, an opening for a connector being formed in the mask shell in the central portion, the mask seal being connected to the mask shell, the mask seal comprising at least one oral opening on a lower portion and at least one nasal opening on an upper portion, the at least one oral opening being positioned opposite of the opening for the connector and the at least one nasal opening being positioned between the opening for the connector and the oral opening in a front to back direction, the upper portion of the mask seal comprising a first paddle, a second paddle, and a nasal region having an upper support surface being positioned between the first paddle and the second paddle such that an upwardly-open valley is defined by the first paddle, the upper support surface and the second paddle, at least a portion of the at least one nasal opening being positioned on the upper support surface within the valley, the valley being configured to provide an exposed tip of the nose of the user;

wherein the mask seal comprises one or more decoupling features that decouple movement of the nasal-upper portion and the ~~oral-lower~~ portion to allow relative rotational movement therebetween ~~at least~~ about a lateral axis that extends in a direction that is substantially perpendicular to a longitudinal axis extending in the front to back direction of the mask seal,

the interface assembly further comprising a movement limiting arrangement that limits the movement of the upper portion of the mask seal.

2. The interface mask-assembly of Claim 1, wherein the nasal-upper portion of the mask seal comprises at least one nasal element configured to engage a nare of the user.

3. The interface mask-assembly of Claim 2, wherein the at least one nasal element comprises a pair of nasal pillows that sealingly engage a respective one of the nares of the user.

4. The interface mask-assembly of any one of Claim 1-3, wherein the one or more decoupling features comprises an upper wall portion positioned directly above a lower wall portion that are movable toward and away from one another.

5. The interface mask-assembly of Claim 4, wherein the upper wall portion and the lower wall portion are generally linear to define a V-shape in cross-section.

6. The interface mask-assembly of Claim 4, wherein at least one of the upper wall portion and the lower wall portion have a curved shape in cross-section.

7. The interface mask-assembly of any one of Claims 1-3, wherein the one or more decoupling features comprises a first wall portion and a second wall portion that are arranged at an angle relative to one another.

8. The interface mask-assembly of Claim 7, wherein the first wall portion and the second wall portion cooperate to define an L-shape in cross-section.

9. The interface mask-assembly of Claim 8, further comprising a curved wall portion between the second wall portion and a portion of a wall of the mask wall-seal adjacent the decoupling feature.

10. The interface mask-assembly of Claim 8, wherein the first wall portion is shaped similarly to match a front wall of the nasal-upper portion of the mask assembly.

11. The interface mask-assembly of any one of Claims 1-9, wherein the one or more decoupling features includes at least a first portion and a second portion positioned on opposite lateral sides of the mask assembly.

12. The interface mask-assembly of Claim 11, further comprising a rigid connection portion between the first portion and the second portion of the decoupling feature.

13. The interface mask-assembly of Claim 12, further comprising a rigid strip portion positioned above the first portion and the second portion of the decoupling feature.

14. The interface mask-assembly of Claim 11, wherein the decoupling feature further comprise additional portions on each lateral side arranged in a stacked configuration with the first portion and the second portion.

15. The interface mask-assembly of Claim 14, wherein the additional portions of each stacked configuration taper in size from the lowermost to the uppermost portions.

16. The interface mask-assembly of any one of Claims 1-15, wherein the one or more decoupling features extends at least to a transition between a side surface and a user-facing surface of the mask assembly.

17. The interface mask-assembly of Claim 16, wherein the decoupling feature extends into the user-facing surface of the mask assembly.

18. The interface mask-assembly of Claim 17, wherein the decoupling feature defines an invert point at or near the transition.

19. The interface mask-assembly of Claim 18, wherein the decoupling feature tapers in height and/or depth toward the invert point.

20. The interface mask-assembly of any one of Claim 1-19, wherein the one or more decoupling features comprises a corrugated arrangement.

~~21. The mask assembly of any one of Claim 1-20, in combination with an interface component, the combination further comprising a movement limiting arrangement that limits movement of the upper portion of the mask seal.~~

22.21. The interface assembly combination of Claim ~~21~~1, wherein the movement limiting arrangement comprises one of a ratchet assembly, a cowling and a tether.

23.22. An interface for use in providing positive pressure respiratory therapy, the interface comprising:

a mask assembly comprising a mask seal and a mask shell, the mask assembly configured to be positioned on a face of a user covering the nose and mouth of the user, the mask shell comprising a central portion and a pair of wings sweeping rearwardly of the central portion, an opening for a connector being formed in the mask shell in the central portion, the mask seal being connected to the mask shell, the mask seal comprising a lower portion and an upper portion, at least one nasal opening being positioned on the upper portion, at least one oral opening being positioned on the lower portion opposite of the opening for the connector, the mask assembly comprising one or more features that decouple movement of the upper portion and the lower portion to allow relative rotational movement therebetween ~~at least~~ about a

lateral axis that extends in a direction that is substantially perpendicular to a longitudinal axis extending in the front to back direction of the mask seal, the upper portion of the mask seal comprising a first paddle, a second paddle, and a nasal region having an upper support surface being positioned between the first paddle and the second paddle such that an upwardly-open valley is defined by the first paddle, the upper support surface and the second paddle, at least a portion of the at least one nasal opening being positioned on the upper support surface within the valley, the valley being configured to provide an exposed tip of the nose of the user;

a frame assembly coupled to the mask assembly, the frame assembly configured for connection to a headgear;

a movement limiting arrangement that limits movement of the upper portion of the mask seal relative to the lower portion of the mask seal.

24.23. The interface of Claim 23.22, wherein the movement limiting arrangement comprises one of a ratchet assembly, a cowling and a tether.

25.24. The interface of Claim 23.22, wherein the movement limiting arrangement is a ratchet assembly having a first ratchet portion coupled to the mask seal and a second ratchet portion coupled to the frame.

26.25. The interface of any one of Claims 23-25.22-24, wherein the movement limiting arrangement is centrally located.

27.26. The interface of any one of Claim 23-25.22-24, wherein the movement limiting arrangement comprises portions located on one or both lateral sides of the mask assembly.

28.27. The interface of any one of Claims 23-25.22-24, wherein the movement limiting arrangement allows downward movement of the upper portion of the mask seal.

29.28. The interface of Claim 28.27, wherein the movement limiting arrangement limits, inhibits or prevents upward movement of the upper portion of the mask seal when the upper portion is expanded or when a gas pressure within the mask seal is at or above a threshold gas pressure.

30.29. The interface of Claim 29.28, wherein the movement limiting arrangement permits upward movement of the upper portion of the mask seal when the upper portion is

not expanded or when the gas pressure within the mask seal is below a threshold gas pressure.

34.30. The interface of Claim ~~23~~22, wherein the movement limiting arrangement comprises portions located on one or both lateral sides of the frame assembly.