

FOAMING ADDITIVE FOR SOIL CONDITIONING IN THE PRESENCE OF MECHANISED EXCAVATION FOR TUNNEL CONSTRUCTION

The present invention relates to foaming additives used for conditioning soil excavated with a tunnel boring machine. Said additives can be classified as readily biodegradable, and are characterised by the long half-life of the foam generated, which gives rise to longer-lasting soil conditioning and better stability of the tunnel face. The additives described in the present invention possess high stability even in the presence of brine.

Prior art

Currently, tunnels can be excavated by two main technologies:

- use of explosives (the conventional method);
- use of mechanical equipment.

The first method involves cyclical application of the operations described below, which allow the advance of the tunnel:

1) Using a Jumbo machine, a series of holes are drilled in the tunnel face and packed with explosive; the arrangement of the holes and the amount of explosive are calibrated in such a way as to demolish the desired portion of rock without damaging the portions thereof which will act as natural supports for the excavation;

2) The excavated material (called “muck”) is removed with bulldozers and trucks;

3) The excavation is supported by ribs and shotcrete.

This method is based on eliminating the right portion of rock, so as to redistribute around the excavation the forces known as the “arch effect”, which partly supports the consolidating action of the reinforcing rods and shotcrete.

The second construction technique can be divided into two main categories: the partial-face system and the full-face system (which involves excavating the entire tunnel diameter at the same time). In the first case, operations proceed as

already described for the conventional method with roadheaders and rock breakers (instead of explosive), gradually forming the shape of the tunnel which will subsequently be lined with reinforced concrete. In the second case the advance is effected with a complex machine called a Tunnel Boring Machine (TBM), also
 5 known as a “mole”, which, as well as performing the excavation, supports and prevents collapses of the face, carries away muck (by means of a screw conveyor and a conveyor belt), and places the final tunnel lining, consisting of prefabricated reinforced concrete segments. This type of machine can excavate nearly all types of geological material, including compact rock (hard-rock TBM), fractured rock
 10 (single or double-shield TBM), loose soil and under aquifers (EPB - Earth Pressure Balance machine).

A TBM consists of:

- 1) The head, namely the front part in direct contact with the tunnel face, which serves to excavate, support the face, collect and convey muck to an evacuation
 15 system;
- 2) A system for transporting the muck out of the tunnel (such as a conveyor belt);
- 3) A excavation chamber located between the cutterhead and the muck conveyance system in which the excavated material is collected; the material exits
 20 from the chamber on a screw conveyor or auger, and is placed on a roller conveyor.
- 4) A tunnel lining system.

The cutterhead is equipped with different tools and is designed based on the geology to be excavated. The tools are generally of three different types: cutters, scrapers and rippers.

25 In the TBM, the advance can take place with the excavation chamber constantly and completely full of suitably conditioned excavated material, in order to guarantee homogenous, uniform distribution of the soil pressure on the tunnel face and prevent pressure drops between one stroke and the next. In some cases,

depending on the geological and hydraulic conditions, it is possible to advance with empty or partially empty excavation chamber. In the EPB-TBM it is common practice to apply a conditioning agent to the soil or rock excavated, in different portions of the TBM: tunnel face, excavation chamber and screw conveyor.

5 Known stabilising agents include bentonite and polymer suspensions. They can cause problems in some soils, because they considerably increase the water content of the soil, producing very liquid systems that are difficult to extract. Moreover some soils (such as clays) can become sticky and difficult to remove to the point of clogging the cutterhead, with a substantial loss of efficiency.

10 In the latest developments of this technology, polymer foams have been suggested. They have the considerable advantage that they greatly reduce the input of water into the soil. A standard foaming agent formulation comprises a foaming agent and a stabilising agent.

15 Thus, in operation, the foam is directly injected into the cutterhead at the excavation interface.

EP 1027528 discloses a boring method wherein the composition of the aqueous material injected into the tunnel face consists of a polyethylene oxide with a molecular weight ranging between 2 and 8 million and an anionic surfactant containing sulphate.

20 EP 0070074 describes a foaming additive consisting of an alkylpolysaccharide surfactant and a sulphate or sulphonate and/or carboxylate cosurfactant.

US 5851960 discloses an excavation method that uses a drilling fluid consisting of a rehydrated clay, water and a foaming surfactant.

25 US 6172010 discloses an aqueous foaming additive consisting of a surfactant and a polymer characterised by opposite charges, to obtain a stable foam.

US 6802673 describes an aqueous foaming additive consisting of an anionic surfactant and a β -naphthalene sulphonate formaldehyde condensate.

US 4442018 discloses the composition of an additive for the production of a stable foam in aqueous phase consisting of an acrylic acid polymer, a C12-C14 and C16 alcohol, a C4 and C5 alcohol, sodium laurylsulphate or alpha-olefin sulphonate, and water.

5 **Description of the invention**

The present invention relates to a novel foaming additive designed to be added in percentages of 0.1-4% by weight to an aqueous solution, able to generate foam to be injected into the tunnel face. Said foam is used on the face to soften the soil and allow faster extraction, and in the conditioning chamber to maintain the
10 stability of the tunnel face.

The high stability of the foam generated, expressed as half-life, allows the conditioning in the excavation chamber to be maintained for longer.

The additive according to the invention, in the form of an aqueous solution classifiable as readily biodegradable, comprises at least one surfactant in
15 percentages ranging between 5 and 40% by weight, and at least one biopolymer in percentages ranging between 0.01 and 5% by weight. The percentage of water can range from 55% to 94.09% by weight. The surfactant can be anionic, cationic or non-ionic, preferably anionic. The preferred anionic surfactants are alkyl sulphate salts and alkyl heterosulphates, in particular the sodium salts. An alkyl ethoxy
20 sulphate salt having a C₁₀-C₁₄ alkyl chain and an ethoxylation number ranging from 1 to 9 is particularly preferred as anionic surfactant.

The term "biopolymers" refers to polymers degradable due to the effect of micro-organisms such as bacteria, fungi or seaweed. They are mainly water-soluble polysaccharides able to increase the viscosity of an aqueous system in a pH range
25 between 4 and 12. The preferred biopolymers are xanthan gum and guar gum.

The foaming additive according to the invention is classifiable as readily biodegradable according to the OECD 301 guidelines.

The foaming additive according to the invention is characterised by high

stability, even in the presence of brine.

The foaming additive can also contain other compounds used to deal with specific problems such as clogging due to clayey soils, to prevent high consumption of the cutters fitted in the cutterhead, or to reduce the quantity of soluble salts in the water present in the excavation soil.

A further object of the invention is the use of the additive to generate foam able to condition excavation soils. The additive is preferably added, in percentages ranging from 0.1 to 4.0% by weight, to the water pumped into a foam generator.

The characteristics and advantages of the additive according to the invention are more particularly described in the examples below. The percentages of the ingredients are expressed by weight.

Example 1

The foaming additives have the following compositions:

	<i>Parts by weight (%)</i>			
	Sample 1	Sample 2	Sample 3	Sample 4
Sodium lauryl ether sulphate	20.0	20.0	20.0	12.0
Xanthan gum	0.0	0.5	2.0	0.3
Biocide	0.2	0.2	0.2	0.2
Water	79.8	79.3	77.8	87.5

Table 1: composition of samples

The stability of the foam generated by an aqueous solution prepared by adding 2% by weight of foaming additive to 5000 g of water is evaluated. The stability is expressed as the half-life, which indicates the time required for the weight of the foam to halve. The test is conducted by evaluating the time in which water amounting to half the weight/volume of the foam is released in a 250 ml cylinder.

The foam is formed by a generator that conveys the flow of liquid at a constant airflow into a glass ball mixer.

	<i>Half-life (sec)</i>
Sample 1	540
Sample 2	730
Sample 3	1800
Sample 4	690

Table 2: half-life

The figures set out in Table 2 indicate that the stability of the foam increases when the dose of biopolymer is increased. The biological degradation results of sample 4 according to OECD 301 classify the product as readily biodegradable with a value of 84% after 28 days.

Example 2

The foaming additives have the compositions reported in Table 1.

The aggregate used to evaluate the stability of the conditioning is a standard quartz with a well-defined particle-size distribution curve (0.06-0.25 mm).

The foam used to condition the matrix is generated by mechanical mixing at 2000 rpm starting from an aqueous solution prepared with 65 g of water and 0.65 g of foaming additive.

The evaluation involves adding the foams generated with the foaming additives reported in Table 1 to three 1000 g samples of standard quartz, and homogenising the mixture in a Hobart mixer for 3 minutes at standard speed. The matrix conditioning is expressed as the viscosity value, measured with a Brookfield DV-I Prime viscometer, using spindle D and a speed of 5 rpm. The viscosity of the conditioned matrix is evaluated at time 0 and 60 minutes after mixing. A smaller difference in the values obtained after 60 minutes compared with the initial figure suggests better conditioning by the foam used.

The results are set out in Table 3:

	<i>Viscosity (Pa*s)</i>	
	0 minutes	60 minutes
Water	Not evaluatable	
Sample 1	145	325
Sample 2	150	240
Sample 3	145	200
Sample 4	155	300

Table 3: viscosity of conditioned quartz.

The test conducted with the addition of water alone gave rise to a cohesionless
5 matrix; the viscosity measurement was not significant.

The data set out in Table 3 indicate an improvement in the stability of the soil
conditioning when foams with long half-lives are used.

Example 3

10 The foaming additives have the following compositions:

	<i>Parts by weight (%)</i>		
	Sample 5	Sample 6	Sample 7
Sodium lauryl ether sulphate	15.0	15.0	15.0
Guar gum	0.0	0.1	0.5
Water	85.0	84.9	84.5

Table 4: composition of samples

The stability of the foam generated by an aqueous solution prepared by
adding 2% by weight of foaming additive to 5000 g of water is evaluated. The
stability is expressed as the half-life, which indicates the time required for the weight
15 of the foam to halve. The test is conducted by evaluating the time in which water
amounting to half the weight/volume of the foam is released in a 250 ml cylinder.

The foam is formed by a generator using a constant airflow.

	<i>Half-life (sec)</i>
Sample 5	480
Sample 6	530
Sample 7	560

Table 5: half-life

The figures set out in Table 5 indicate that the stability of the foam increases when the dose of biopolymer is increased.

Example 4

5 The foaming additives have the following compositions:

	<i>Parts by weight (%)</i>				
	Sample 8	Sample 9	Sample 10	Sample 11	Sample 12
Sodium lauryl ether sulphate	10.0	10.0	0.0	0.0	5.0
Sodium lauryl sulphate	0.0	0.0	10.0	10.0	0.0
Cocamide MEA	0.0	0.0	0.0	0.0	5.0
Guar gum	0.1	5.0	0.0	0.5	0.5
Water	89.9	85.0	90.0	89.5	89.5

Table 6: composition of samples

10 The stability of the foam generated by an aqueous solution prepared by adding 2% by weight of foaming additive to 5000 g of water is evaluated. The stability is expressed as the half-life, which indicates the time required for the weight of the foam to halve. The test is performed by evaluating the time in which water amounting to half the weight/volume of the foam is released in a 250 ml cylinder.

The foam is formed by a generator that conveys the flow of liquid at a constant airflow into a glass ball mixer.

	<i>Half-life (sec)</i>
Sample 8	600
Sample 9	7200
Sample 10	450
Sample 11	860
Sample 12	650

Table 7: half-life

The figures set out in Table 7 indicate that the stability of the foam increases when the dose of biopolymer in the additive is increased.

Example 5

5 The foaming additives have the following compositions:

	<i>Parts by weight (%)</i>		
	Sample 13	Sample 14	Sample 15
Sodium lauryl ether sulphate	12.0	12.0	12.0
Xanthan gum	0.0	0.3	2.0
Water	88.0	87.7	86.0

Table 8: composition of samples

The stability of the foam generated by an aqueous solution prepared by adding 2% by weight of foaming additive to 5000 g of brine is evaluated. The brine used is characterised by a sodium chloride concentration of 2%. The stability is expressed as the half-life, which indicates the time required for the weight of the foam to halve. The test is conducted by evaluating the time in which water amounting to half the weight/volume of the foam is released in a 250 ml cylinder.

15 The foam is formed by a generator that conveys the flow of liquid at a constant airflow into a glass ball mixer.

	<i>Half-life (sec)</i>
Sample 13	510
Sample 14	650
Sample 15	1720

Table 9: half-life

The figures set out in Table 9 indicate that the stability of the foam generated by a brine solution increases when the quantity of biopolymer in the additive is increased.

5 **Example 6**

The foaming additives have the following compositions:

	<i>Parts by weight (%)</i>	
	Sample 16	Sample 17
Sodium lauryl ether sulphate (ethoxylation number 2)	10.0	1.0
Sodium alkyl ether sulphate (ethoxylation number 7)	-	10.0
Xanthan gum	-	0.3
Water	90	88.7

Table 10: composition of samples

10 The stability of the foam generated by an aqueous solution prepared by adding 2% by weight of foaming additive to 5000 g of brine is evaluated. The stability is expressed as the half-life, which indicates the time required for the weight of the foam to halve. The test is conducted by evaluating the time in which water amounting to half the weight/volume of the foam is released in a 250 ml cylinder.

15 The foam is formed by a generator that conveys the flow of liquid at a constant airflow into a glass ball mixer.

	<i>Half-life (sec)</i>
Sample 16	450
Sample 17	560

Table 11: Half-life

The figures set out in Table 11 show a stable foam when a sodium alkyl ether sulphate characterised by an ethoxylation number of 7 is used as surfactant.

CLAIMS

1. A liquid foaming additive for use in mechanised excavation by a tunnel boring machine, containing 5-40% by weight of one or more surfactants, 0.01-5 5% by weight of one or more biopolymers and 55-94.99% of water.
2. A foaming additive according to claim 1 wherein the surfactant is anionic, cationic, non-ionic or amphoteric.
3. A foaming additive according to claim 2 wherein the surfactant is anionic.
4. A foaming additive according to claim 3 wherein the anionic surfactant is
10 an alkyl ethoxy sulphate or laureth sulphate salt.
5. An additive as claimed in claim 4, wherein the anionic surfactant is an alkyl ethoxy sulphate salt having a C₁₀-C₁₄ alkyl chain and an ethoxylation number ranging from 1 to 9.
6. A foaming additive according to claim 5 wherein the salt is the sodium
15 salt.
7. A foaming additive according to one or more of claims 1 to 6 wherein the biopolymers are polysaccharides.
8. A foaming additive according to claim 7 wherein the biopolymer is xanthan gum or guar gum.
- 20 9. Use of the additive of claims 1-8 to generate foam capable of conditioning excavated soil.
10. Use according to claim 9 wherein the additive is added, in percentages ranging from 0.1 to 4.0% by weight, to water pumped into a foam generator.