PACKER FOR ALTERNATE FLOW CHANNEL GRAVEL PACKING AND METHOD FOR COMPLETING A WELLBORE

CROSS REFERENCE TO RELATED APPLICATIONS

[0001] This application claims the benefit of U.S. Provisional Application 61/424,427, filed December 17, 2010.

BACKGROUND OF THE INVENTION

[0002] This section is intended to introduce various aspects of the art, which may be associated with exemplary embodiments of the present disclosure. This discussion is believed to assist in providing a framework to facilitate a better understanding of particular aspects of the present disclosure. Accordingly, it should be understood that this section should be read in this light, and not necessarily as admissions of prior art.

Field of the Invention

[0003] The present disclosure relates to the field of well completions. More specifically, the present invention relates to the isolation of formations in connection with wellbores that have been completed using gravel-packing. The application also relates to a downhole packer that may be set within either a cased hole or an open-hole wellbore and which incorporates Alternate Path® technology.

Discussion of Technology

[0004] In the drilling of oil and gas wells, a wellbore is formed using a drill bit that is urged downwardly at a lower end of a drill string. After drilling to a predetermined depth, the drill string and bit are removed and the wellbore is lined with a string of casing. An annular area is thus formed between the string of casing and the formation. A cementing operation is typically conducted in order to fill or “squeeze” the annular area with cement. The combination of cement and casing strengthens the wellbore and facilitates the isolation of the formation behind the casing.

[0005] It is common to place several strings of casing having progressively smaller outer diameters into the wellbore. The process of drilling and then cementing progressively smaller strings of casing is repeated several times until the well has reached total depth. The final string of casing, referred to as a production casing, is cemented in place and perforated. In some instances, the final string of casing is a liner, that is, a string of casing that is not tied back to the surface.

[0006] As part of the completion process, a wellhead is installed at the surface. The wellhead controls the flow of production fluids to the surface, or the injection of fluids into the wellbore. Fluid gathering and processing equipment such as pipes, valves and separators are also provided. Production operations may then commence.

[0007] It is sometimes desirable to leave the bottom portion of a wellbore open. In open-hole completions, a production casing is not extended through the producing zones and perforated; rather, the producing zones are left uncased, or "open." A production string or "tubing" is then positioned inside the wellbore extending down below the last string of casing and across a subsurface formation.

[0008] There are certain advantages to open-hole completions versus cased-hole completions. First, because open-hole completions have no perforation tunnels, formation fluids can converge on the wellbore radially 360 degrees. This has the benefit of eliminating the additional pressure drop associated with converging radial flow and then linear flow through particle-filled perforation tunnels. The reduced pressure drop associated with an open-hole completion virtually guarantees that it will be more productive than an unstimulated, cased hole in the same formation.

[0009] Second, open-hole techniques are oftentimes less expensive than cased hole completions. For example, the use of gravel packs eliminates the need for cementing, perforating, and post-perforation clean-up operations.

[0010] A common problem in open-hole completions is the immediate exposure of the wellbore to the surrounding formation. If the formation is unconsolidated or heavily sandy, the flow of production fluids into the wellbore may carry with it formation particles, e.g., sand and fines. Such particles can be erosive to production equipment downhole and to pipes, valves and separation equipment at the surface.

[0011] To control the invasion of sand and other particles, sand control devices may be employed. Sand control devices are usually installed downhole across formations to retain solid materials larger than a certain diameter while allowing fluids to be produced. A sand control device typically includes an elongated tubular body, known as a base pipe, having numerous slotted openings. The base pipe is then typically wrapped with a filtration medium such as a screen or wire mesh.

[0012] To augment sand control devices, particularly in open-hole completions, it is common to install a gravel pack. Gravel packing a well involves placing gravel or other particulate matter around the sand control device after the sand control device is hung or otherwise placed in the wellbore. To install a gravel pack, a particulate material is delivered downhole by means of a carrier fluid. The carrier fluid with the gravel together forms a gravel slurry. The slurry dries in place, leaving a circumferential packing of gravel. The gravel not only aids in particle filtration but also helps maintain formation integrity.

[0013] In an open-hole gravel pack completion, the gravel is positioned between a sand screen that surrounds a perforated base pipe and a surrounding wall of the wellbore. During production, formation fluids flow from the subterranean formation, through the gravel,

through the screen, and into the inner base pipe. The base pipe thus serves as a part of the production string.

[0014] A problem historically encountered with gravel-packing is that an inadvertent loss of carrier fluid from the slurry during the delivery process can result in premature sand or gravel bridges being formed at various locations along open-hole intervals. For example, in an inclined production interval or an interval having an enlarged or irregular borehole, a poor distribution of gravel may occur due to a premature loss of carrier fluid from the gravel slurry into the formation. Premature sand bridging can block the flow of gravel slurry, causing voids to form along the completion interval. Thus, a complete gravel-pack from bottom to top is not achieved, leaving the wellbore exposed to sand and fines infiltration.

[0015] The problems of sand bridging has been addressed through the use of Alternate Path® Technology, or "APT." Alternate Path® Technology employs shunt tubes (or shunts) that allow the gravel slurry to bypass selected areas along a wellbore. Such alternate path technology is described, for example, in U.S. Pat. No. 5,588,487 entitled "Tool for Blocking Axial Flow in Gravel-Packed Well Annulus," and U.S. Pat. No. 7,938,184 entitled "Wellbore Method and Apparatus for Completion, Production, and Injection". Additional references which discuss bypass technology include U.S. Pat. No. 4,945,991; U.S. Pat. No. 5,113,935; U.S. Pat. No. 7,661,476; and M.D. Barry, *et al.*, "Open-hole Gravel Packing with Zonal Isolation," SPE Paper No. 110,460 (November 2007).

[0016] The efficacy of a gravel pack in controlling the influx of sand and fines into a wellbore is well-known. However, it is also sometimes desirable with open-hole completions to isolate selected intervals along the open-hole portion of a wellbore in order to control the inflow of fluids. For example, in connection with the production of condensable hydrocarbons, water may sometimes invade an interval. This may be due to the presence of native water zones, coning (rise of near-well hydrocarbon-water contact), high permeability streaks, natural fractures, or fingering from injection wells. Depending on the mechanism or cause of the water production, the water may be produced at different locations and times during a well's lifetime. Similarly, a gas cap above an oil reservoir may expand and break through, causing gas production with oil. The gas breakthrough reduces gas cap drive and suppresses oil production.

[0017] In these and other instances, it is desirable to isolate an interval from the production of formation fluids into the wellbore. Annular zonal isolation may also be desired for production allocation, production/injection fluid profile control, selective stimulation, or water or gas control. However, the design and installation of open-hole packers is highly problematic due to under-reamed areas, areas of washout, higher pressure differentials, frequent pressure cycling, and irregular borehole sizes. In addition, the longevity of zonal

isolation is a consideration as the water/gas coning potential often increases later in the life of a field due to pressure drawdown and depletion.

[0018] Therefore, a need exists for an improved sand control system that provides bypass technology for the placement of gravel that bypasses a packer. A need further exists for a packer assembly that provides isolation of selected subsurface intervals along an open-hole wellbore. Further, a need exists for a packer that utilizes alternate path channels, and that provides a hydraulic seal to an open-hole wellbore before any gravel is placed around the sealing element.

SUMMARY OF THE INVENTION

[0019] A specially-designed downhole packer is first offered herein. The downhole packer may be used to seal an annular region between a tubular body and a surrounding open-hole wellbore. The downhole packer may be placed along a string of sand control devices, and set before a gravel packing operation begins.

[0020] In one embodiment, the downhole packer comprises an inner mandrel. The inner mandrel defines an elongated tubular body. In addition, the downhole packer has at least one alternate flow channel along the inner mandrel. Further, the downhole packer has a sealing element external to the inner mandrel. The sealing element resides circumferentially around the inner mandrel.

[0021] The downhole packer further includes a movable piston housing. The piston housing is initially retained around the inner mandrel. The piston housing has a pressure-bearing surface at a first end, and is operatively connected to the sealing element. The piston housing may be released and caused to move along the inner mandrel. Movement of the piston housing actuates the sealing element into engagement with the surrounding open-hole wellbore.

[0022] Preferably, the downhole packer further includes a piston mandrel. The piston mandrel is disposed between the inner mandrel and the surrounding piston housing. An annulus is preserved between the inner mandrel and the piston mandrel. The annulus beneficially serves as the at least one alternate flow channel through the packer.

[0023] The downhole packer may also include one or more flow ports. The flow ports provide fluid communication between the alternate flow channel and the pressure-bearing surface of the piston housing. The flow ports are sensitive to hydrostatic pressure within the wellbore.

[0024] In one embodiment, the downhole packer also includes a release sleeve. The release sleeve resides along an inner surface of the inner mandrel. Further, the downhole packer includes a release key. The release key is connected to the release sleeve. The release key is movable between a retaining position wherein the release key engages and

retains the moveable piston housing in place, to a releasing position wherein the release key disengages the piston housing. When disengaged, absolute pressure acts against the pressure-bearing surface of the piston housing and moves the piston housing to actuate the sealing element.

[0025] In one aspect, the downhole packer also has at least one shear pin. The at least one shear pin may be one or more set screws. The shear pin or pins releasably connects the release sleeve to the release key. The shear pin or pins is sheared when a setting tool is pulled up the inner mandrel and slides the release sleeve.

[0026] In one embodiment, the downhole packer also has a centralizer. The centralizer may be operable in response to manipulation of the packer or sealing mechanism, or in other embodiments be operable separately from manipulating the packer or sealing mechanism.

[0027] A method for completing a wellbore is also provided herein. The wellbore may include a lower portion completed as an open-hole. In one aspect, the method includes providing a packer. The packer may be in accordance with the packer described above. For example, the packer will have an inner mandrel, alternate flow channels around the inner mandrel, and a sealing element external to the inner mandrel. The sealing element is preferably an elastomeric cup-type element

[0028] The method also includes connecting the packer to a tubular body, and then running the packer and connected tubular body into the wellbore. The packer and connected tubular body are placed along the open-hole portion of the wellbore. Preferably, the tubular body is a sand screen, with the sand screen comprising a base pipe, a surrounding filter medium, and alternate flow channels. Alternatively, the tubular body may be a blank pipe comprising alternate flow channels. The alternate flow channels may be either internal or external to the filter medium or the blank pipe, as the case may be.

[0029] The base pipe of the sand screen may be made up of a plurality of joints. For example, the packer may be connected between two of the plurality of joints of the base pipe.

[0030] The method also includes setting the packer. This is done by actuating the sealing element of the packer into engagement with the surrounding open-hole portion of the wellbore. As an alternative, the packer may be set along a non-perforated joint of casing. Thereafter, the method includes injecting a gravel slurry into an annular region formed between the tubular body and the surrounding wellbore, and then further injecting the gravel slurry through the alternate flow channels to allow the gravel slurry to bypass the sealing element. In this way, the open-hole portion of the wellbore is gravel-packed below the packer. In one aspect, the wellbore is gravel packed above and below the packer after the packer has been completely set in the open-hole wellbore.

[0031] In one embodiment herein, the packer is a first mechanically-set packer that is part of a packer assembly. In this instance, the packer assembly may comprise a second mechanically-set packer constructed in accordance with the first packer. The step of further injecting the gravel slurry through the alternate flow channels allows the gravel slurry to bypass the sealing element of the packer assembly so that the open-hole portion of the wellbore is gravel-packed above and below the packer assembly after the first and second mechanically-set packers have been set in the wellbore.

[0032] The method may further include running a setting tool into the inner mandrel of the packer, and releasing the movable piston housing from its retained position. The method then includes communicating hydrostatic pressure to the piston housing through the one or more flow ports. Communicating hydrostatic pressure moves the released piston housing and actuates the sealing element against the surrounding wellbore.

[0033] It is preferred that the setting tool is part of a washpipe used for gravel packing. In this instance, running the setting tool comprises running a washpipe into a bore within the inner mandrel of the packer, with the washpipe having a setting tool thereon. The step of releasing the movable piston housing from its retained position then comprises pulling the washpipe with the setting tool along the inner mandrel. The release sleeve moves to shear the at least one shear pin and shift the release sleeve. This further serves to free the at least one release key, and release the piston housing.

[0034] The method may also include producing hydrocarbon fluids from at least one interval along the open-hole portion of the wellbore.

BRIEF DESCRIPTION OF THE DRAWINGS

[0035] So that the manner in which the present inventions can be better understood, certain illustrations, charts and/or flow charts are appended hereto. It is to be noted, however, that the drawings illustrate only selected embodiments of the inventions and are therefore not to be considered limiting of scope, for the inventions may admit to other equally effective embodiments and applications.

[0036] Figure 1 is a cross-sectional view of an illustrative wellbore. The wellbore has been drilled through three different subsurface intervals, each interval being under formation pressure and containing fluids.

[0037] Figure 2 is an enlarged cross-sectional view of an open-hole completion of the wellbore of Figure 1. The open-hole completion at the depth of the three illustrative intervals is more clearly seen.

[0038] Figure 3A is a cross-sectional side view of a packer assembly, in one embodiment. Here, a base pipe is shown, with surrounding packer elements. Two mechanically set packers are shown in spaced-apart relation.

[0039] Figure 3B is a cross-sectional view of the packer assembly of Figure 3A, taken across lines 3B-3B of Figure 3A. Shunt tubes are seen within the packer assembly.

[0040] Figure 3C is a cross-sectional view of the packer assembly of Figure 3A, in an alternate embodiment. In lieu of shunt tubes, transport tubes are seen manifolded around the base pipe.

[0041] Figure 4A is a cross-sectional side view of the packer assembly of Figure 3A. Here, sand control devices, or sand screens, have been placed at opposing ends of the packer assembly. The sand control devices utilize external shunt tubes.

[0042] Figure 4B provides a cross-sectional view of the packer assembly of Figure 4A, taken across lines 4B-4B of Figure 4A. Shunt tubes are seen outside of the sand screen to provide an alternative flowpath for a particulate slurry.

[0043] Figure 5A is another cross-sectional side view of the packer assembly of Figure 3A. Here, sand control devices, or sand screens, have again been placed at opposing ends of the packer assembly. However, the sand control devices utilize internal shunt tubes.

[0044] Figure 5B provides a cross-sectional view of the packer assembly of Figure 5A, taken across lines 5B-5B of Figure 5A. Shunt tubes are seen within the sand screen to provide an alternative flowpath for a particulate slurry.

[0045] Figure 6A is a cross-sectional side view of one of the mechanically-set packers of Figure 3A. The mechanically-set packer is in its run-in position.

[0046] Figure 6B is a cross-sectional side view of the mechanically-set packer of Figure 3A. Here, the mechanically-set packer element is in its set position.

[0047] Figure 6C is a cross-sectional view of the mechanically-set packer of Figure 6A. The view is taken across line 6C-6C of Figure 6A.

[0048] Figure 6D is a cross-sectional view of the mechanically-set packer of Figure 6A. The view is taken across line 6D-6D of Figure 6B.

[0049] Figure 6E is a cross-sectional view of the mechanically-set packer of Figure 6A. The view is taken across line 6E-6E of Figure 6A.

[0050] Figure 6F is a cross-sectional view of the mechanically-set packer of Figure 6A. The view is taken across line 6F-6F of Figure 6B.

[0051] Figure 7A is an enlarged view of the release key of Figure 6A. The release key is in its run-in position along the inner mandrel. The shear pin has not yet been sheared.

[0052] Figure 7B is an enlarged view of the release key of Figure 6B. The shear pin has been sheared, and the release key has dropped away from the inner mandrel.

[0053] Figure 7C is a perspective view of a setting tool as may be used to latch onto a release sleeve, and thereby shear a shear pin within the release key.

[0054] Figures 8A through 8J present stages of a gravel packing procedure using one of the packer assemblies of the present invention, in one embodiment. Alternate flowpath

channels are provided through the packer elements of the packer assembly and through the sand control devices.

[0055] Figure 8K shows the packer assembly and gravel pack having been set in an open-hole wellbore following completion of the gravel packing procedure from Figures 8A through 8N.

[0056] Figure 9A is a cross-sectional view of a middle interval of the open-hole completion of Figure 2. Here, a straddle packer has been placed within a sand control device across the middle interval to prevent the inflow of formation fluids.

[0057] Figure 9B is a cross-sectional view of middle and lower intervals of the open-hole completion of Figure 2. Here, a plug has been placed within a packer assembly between the middle and lower intervals to prevent the flow of formation fluids up the wellbore from the lower interval.

[0058] Figure 10 is a flowchart showing steps that may be performed in connection with a method for completing an open-hole wellbore, in one embodiment.

[0059] Figure 11 is a flowchart that provides steps for a method of setting a packer, in one embodiment. The packer is set in an open-hole wellbore, and includes alternate flow channels.

DETAILED DESCRIPTION OF CERTAIN EMBODIMENTS

Definitions

[0060] As used herein, the term "hydrocarbon" refers to an organic compound that includes primarily, if not exclusively, the elements hydrogen and carbon. Hydrocarbons generally fall into two classes: aliphatic, or straight chain hydrocarbons, and cyclic, or closed ring hydrocarbons, including cyclic terpenes. Examples of hydrocarbon-containing materials include any form of natural gas, oil, coal, and bitumen that can be used as a fuel or upgraded into a fuel.

[0061] As used herein, the term “hydrocarbon fluids” refers to a hydrocarbon or mixtures of hydrocarbons that are gases or liquids. For example, hydrocarbon fluids may include a hydrocarbon or mixtures of hydrocarbons that are gases or liquids at formation conditions, at processing conditions or at ambient conditions (15° C and 1 atm pressure). Hydrocarbon fluids may include, for example, oil, natural gas, coal bed methane, shale oil, pyrolysis oil, pyrolysis gas, a pyrolysis product of coal, and other hydrocarbons that are in a gaseous or liquid state.

[0062] As used herein, the term “fluid” refers to gases, liquids, and combinations of gases and liquids, as well as to combinations of gases and solids, and combinations of liquids and solids.

[0063] As used herein, the term "subsurface" refers to geologic strata occurring below the earth's surface.

[0064] The term "subsurface interval" refers to a formation or a portion of a formation wherein formation fluids may reside. The fluids may be, for example, hydrocarbon liquids, hydrocarbon gases, aqueous fluids, or combinations thereof.

[0065] As used herein, the term "wellbore" refers to a hole in the subsurface made by drilling or insertion of a conduit into the subsurface. A wellbore may have a substantially circular cross section, or other cross-sectional shape. As used herein, the term "well", when referring to an opening in the formation, may be used interchangeably with the term "wellbore."

[0066] The term "tubular member" refers to any pipe, such as a joint of casing, a portion of a liner, or a pup joint.

[0067] The term "sand control device" means any elongated tubular body that permits an inflow of fluid into an inner bore or a base pipe while filtering out predetermined sizes of sand, fines and granular debris from a surrounding formation.

[0068] The term "alternate flow channels" means any collection of manifolds and/or shunt tubes that provide fluid communication through or around a downhole tool such as a packer to allow a slurry to by-pass the packer or any premature sand bridge in an annular region and continue gravel packing below, or above and below, the tool.

Description of Specific Embodiments

[0069] The inventions are described herein in connection with certain specific embodiments. However, to the extent that the following detailed description is specific to a particular embodiment or a particular use, such is intended to be illustrative only and is not to be construed as limiting the scope of the inventions.

[0070] Certain aspects of the inventions are also described in connection with various figures. In certain of the figures, the top of the drawing page is intended to be toward the surface, and the bottom of the drawing page toward the well bottom. While wells commonly are completed in substantially vertical orientation, it is understood that wells may also be inclined and or even horizontally completed. When the descriptive terms "up and down" or "upper" and "lower" or similar terms are used in reference to a drawing or in the claims, they are intended to indicate relative location on the drawing page or with respect to claim terms, and not necessarily orientation in the ground, as the present inventions have utility no matter how the wellbore is orientated.

[0071] **Figure 1** is a cross-sectional view of an illustrative wellbore **100**. The wellbore **100** defines a bore **105** that extends from a surface **101**, and into the earth's subsurface **110**. The wellbore **100** is completed to have an open-hole portion **120** at a lower end of the

wellbore **100**. The wellbore **100** has been formed for the purpose of producing hydrocarbons for commercial sale. A string of production tubing **130** is provided in the bore **105** to transport production fluids from the open-hole portion **120** up to the surface **101**.

[0072] The wellbore **100** includes a well tree, shown schematically at **124**. The well tree **124** includes a shut-in valve **126**. The shut-in valve **126** controls the flow of production fluids from the wellbore **100**. In addition, a subsurface safety valve **132** is provided to block the flow of fluids from the production tubing **130** in the event of a rupture or catastrophic event above the subsurface safety valve **132**. The wellbore **100** may optionally have a pump (not shown) within or just above the open-hole portion **120** to artificially lift production fluids from the open-hole portion **120** up to the well tree **124**.

[0073] The wellbore **100** has been completed by setting a series of pipes into the subsurface **110**. These pipes include a first string of casing **102**, sometimes known as surface casing or a conductor. These pipes also include at least a second **104** and a third **106** string of casing. These casing strings **104**, **106** are intermediate casing strings that provide support for walls of the wellbore **100**. Intermediate casing strings **104**, **106** may be hung from the surface, or they may be hung from a next higher casing string using an expandable liner or liner hanger. It is understood that a pipe string that does not extend back to the surface (such as casing string **106**) is normally referred to as a "liner."

[0074] In the illustrative wellbore arrangement of **Figure 1**, intermediate casing string **104** is hung from the surface **101**, while casing string **106** is hung from a lower end of casing string **104**. Additional intermediate casing strings (not shown) may be employed. The present inventions are not limited to the type of casing arrangement used.

[0075] Each string of casing **102**, **104**, **106** is set in place through cement **108**. The cement **108** isolates the various formations of the subsurface **110** from the wellbore **100** and each other. The cement **108** extends from the surface **101** to a depth "**L**" at a lower end of the casing string **106**. It is understood that some intermediate casing strings may not be fully cemented.

[0076] An annular region **204** is formed between the production tubing **130** and the casing string **106**. A production packer **206** seals the annular region **204** near the lower end "**L**" of the casing string **106**.

[0077] In many wellbores, a final casing string known as production casing is cemented into place at a depth where subsurface production intervals reside. However, the illustrative wellbore **100** is completed as an open-hole wellbore. Accordingly, the wellbore **100** does not include a final casing string along the open-hole portion **120**.

[0078] In the illustrative wellbore **100**, the open-hole portion **120** traverses three different subsurface intervals. These are indicated as upper interval **112**, intermediate interval **114**, and lower interval **116**. Upper interval **112** and lower interval **116** may, for example, contain

valuable oil deposits sought to be produced, while intermediate interval **114** may contain primarily water or other aqueous fluid within its pore volume. This may be due to the presence of native water zones, high permeability streaks or natural fractures in the aquifer, or fingering from injection wells. In this instance, there is a probability that water will invade the wellbore **100**.

[0079] Alternatively, upper **112** and intermediate **114** intervals may contain hydrocarbon fluids sought to be produced, processed and sold, while lower interval **116** may contain some oil along with ever-increasing amounts of water. This may be due to coning, which is a rise of near-well hydrocarbon-water contact. In this instance, there is again the possibility that water will invade the wellbore **100**.

[0080] Alternatively still, upper **112** and lower **116** intervals may be producing hydrocarbon fluids from a sand or other permeable rock matrix, while intermediate interval **114** may represent a non-permeable shale or otherwise be substantially impermeable to fluids.

[0081] In any of these events, it is desirable for the operator to isolate selected intervals. In the first instance, the operator will want to isolate the intermediate interval **114** from the production string **130** and from the upper **112** and lower **116** intervals so that primarily hydrocarbon fluids may be produced through the wellbore **100** and to the surface **101**. In the second instance, the operator will eventually want to isolate the lower interval **116** from the production string **130** and the upper **112** and intermediate **114** intervals so that primarily hydrocarbon fluids may be produced through the wellbore **100** and to the surface **101**. In the third instance, the operator will want to isolate the upper interval **112** from the lower interval **116**, but need not isolate the intermediate interval **114**. Solutions to these needs in the context of an open-hole completion are provided herein, and are demonstrated more fully in connection with the proceeding drawings.

[0082] In connection with the production of hydrocarbon fluids from a wellbore having an open-hole completion, it is not only desirable to isolate selected intervals, but also to limit the influx of sand particles and other fines. In order to prevent the migration of formation particles into the production string **130** during operation, sand control devices **200** have been run into the wellbore **100**. These are described more fully below in connection with **Figure 2** and with **Figures 8A** through **8J**.

[0083] Referring now to **Figure 2**, the sand control devices **200** contain an elongated tubular body referred to as a base pipe **205**. The base pipe **205** typically is made up of a plurality of pipe joints. The base pipe **205** (or each pipe joint making up the base pipe **205**) typically has small perforations or slots to permit the inflow of production fluids.

[0084] The sand control devices **200** also contain a filter medium **207** wound or otherwise placed radially around the base pipes **205**. The filter medium **207** may be a wire

mesh screen or wire wrap fitted around the base pipe **205**. The filter medium **207** prevents the inflow of sand or other particles above a pre-determined size into the base pipe **205** and the production tubing **130**.

[0085] In addition to the sand control devices **200**, the wellbore **100** includes one or more packer assemblies **210**. In the illustrative arrangement of **Figures 1** and **2**, the wellbore **100** has an upper packer assembly **210'** and a lower packer assembly **210''**. However, additional packer assemblies **210** or just one packer assembly **210** may be used. The packer assemblies **210'**, **210''** are uniquely configured to seal an annular region (seen at **202** of **Figure 2**) between the various sand control devices **200** and a surrounding wall **201** of the open-hole portion **120** of the wellbore **100**.

[0086] **Figure 2** is an enlarged cross-sectional view of the open-hole portion **120** of the wellbore **100** of **Figure 1**. The open-hole portion **120** and the three intervals **112**, **114**, **116** are more clearly seen. The upper **210'** and lower **210''** packer assemblies are also more clearly visible proximate upper and lower boundaries of the intermediate interval **114**, respectively. Finally, the sand control devices **200** along each of the intervals **112**, **114**, **116** are shown.

[0087] Concerning the packer assemblies themselves, each packer assembly **210'**, **210''** may have at least two packers. The packers are preferably set through a combination of mechanical manipulation and hydraulic forces. The packer assemblies **210** represent an upper packer **212** and a lower packer **214**. Each packer **212**, **214** has an expandable portion or element fabricated from an elastomeric or a thermoplastic material capable of providing at least a temporary fluid seal against the surrounding wellbore wall **201**.

[0088] The elements for the upper **212** and lower **214** packers should be able to withstand the pressures and loads associated with a gravel packing process. Typically, such pressures are from about 2,000 psi to 3,000 psi. The elements of the packers **212**, **214** should also withstand pressure load due to differential wellbore and/or reservoir pressures caused by natural faults, depletion, production, or injection. Production operations may involve selective production or production allocation to meet regulatory requirements. Injection operations may involve selective fluid injection for strategic reservoir pressure maintenance. Injection operations may also involve selective stimulation in acid fracturing, matrix acidizing, or formation damage removal.

[0089] The sealing surface or elements for the mechanically set packers **212**, **214** need only be on the order of inches to affect a suitable hydraulic seal. In one aspect, the elements are each about 6 inches (15.2 cm) to about 24 inches (70.0 cm) in length.

[0090] The elements for the packers **212**, **214** are preferably cup-type elements. Cup-type elements are well known for use in cased-hole completions. However, they generally are not known for use in open-hole completions as they are not engineered to expand into

engagement with an open-hole diameter. The preferred cup-type nature of the sealing surfaces of the packer elements **212**, **214** will assist in maintaining at least a temporary seal against the wall **201** of the intermediate interval **114** (or other interval) as pressure increases during the gravel packing operation.

[0091] The upper **212** and lower **214** packers are set prior to a gravel pack installation process. As described more fully below, the packers **212**, **214** may be set by sliding a release sleeve. This, in turn, allows hydrostatic pressure to act downwardly against a piston mandrel. The piston mandrel acts down upon a centralizer and/or packer elements, causing the same to expand against the wellbore wall **201**. The expandable portions of the upper **212** and lower **214** packers are expanded into contact with the surrounding wall **201** so as to straddle the annular region **202** at a selected depth along the open-hole completion **120**.

[0092] **Figure 2** shows a mandrel at **215**. This may be representative of the piston mandrel, and other mandrels used in the packers **212**, **214** as described more fully below.

[0093] The upper **212** and lower **214** packers may generally be mirror images of each other, except for the release sleeves or other engagement mechanisms. Unilateral movement of a shifting tool (shown in and discussed in connection with **Figures 7A** and **7B**) will allow the packers **212**, **214** to be activated in sequence or simultaneously. The lower packer **214** is activated first, followed by the upper packer **212** as the shifting tool is pulled upward through an inner mandrel (shown in and discussed in connection with **Figures 6A** and **6B**). A short spacing is preferably provided between the upper **212** and lower **214** packers.

[0094] The packer assemblies **210'**, **210''** help control and manage fluids produced from different zones. In this respect, the packer assemblies **210'**, **210''** allow the operator to seal off an interval from either production or injection, depending on well function. Installation of the packer assemblies **210'**, **210''** in the initial completion allows an operator to shut-off the production from one or more zones during the well lifetime to limit the production of water or, in some instances, an undesirable non-condensable fluid such as hydrogen sulfide.

[0095] Packers historically have not been installed when an open-hole gravel pack is utilized because of the difficulty in forming a seal along an open-hole portion, and because of the difficulty in forming a complete gravel pack above and below the packer. Related patent applications, U.S. Publication Nos. 2009/0294128 and 2010/0032158 disclose apparatus' and methods for gravel-packing an open-hole wellbore after a packer has been set at a completion interval. Zonal isolation in open-hole, gravel-packed completions may be provided by using a packer element and secondary (or "alternate") flow paths to enable both zonal isolation and alternate flow path gravel packing.

[0096] Certain technical challenges have remained with respect to the methods disclosed in U.S. Pub Nos. 2009/0294128 and 2010/0032158, particularly in connection with

the packer. The applications state that the packer may be a hydraulically actuated inflatable element. Such an inflatable element may be fabricated from an elastomeric material or a thermoplastic material. However, designing a packer element from such materials requires the packer element to meet a particularly high performance level. In this respect, the packer element needs to be able to maintain zonal isolation for a period of years in the presence of high pressures and/or high temperatures and/or acidic fluids. As an alternative, the applications state that the packer may be a swelling rubber element that expands in the presence of hydrocarbons, water, or other stimulus. However, known swelling elastomers typically require about 30 days or longer to fully expand into sealed fluid engagement with the surrounding rock formation. Therefore, improved packers and zonal isolation apparatus' are offered herein.

[0097] **Figure 3A** presents an illustrative packer assembly **300** providing an alternate flowpath for a gravel slurry. The packer assembly **300** is seen in cross-sectional side view. The packer assembly **300** includes various components that may be utilized to seal an annulus along the open-hole portion **120**.

[0098] The packer assembly **300** first includes a main body section **302**. The main body section **302** is preferably fabricated from steel or from steel alloys. The main body section **302** is configured to be a specific length **316**, such as about 40 feet (12.2 meters). The main body section **302** comprises individual pipe joints that will have a length that is between about 10 feet (3.0 meters) and 50 feet (15.2 meters). The pipe joints are typically threadedly connected end-to-end to form the main body section **302** according to length **316**.

[0099] The packer assembly **300** also includes opposing mechanically-set packers **304**. The mechanically-set packers **304** are shown schematically, and are generally in accordance with mechanically-set packer elements **212** and **214** of **Figure 2**. The packers **304** preferably include cup-type elastomeric elements that are less than 1 foot (0.3 meters) in length. As described further below, the packers **304** have alternate flow channels that uniquely allow the packers **304** to be set before a gravel slurry is circulated into the wellbore.

[0100] A short spacing **308** is provided between the mechanically-set packers **304**. The spacing is seen at **308**. When the packers **304** are mirror-images of one another, the cup-type elements are able to resist fluid pressure from either above or below the packer assembly.

[0101] The packer assembly **300** also includes a plurality of shunt tubes. The shunt tubes are seen in phantom at **318**. The shunt tubes **318** may also be referred to as transport tubes or jumper tubes. The shunt tubes **318** are blank sections of pipe having a length that extends along the length **316** of the mechanically-set packers **304** and the spacing **308**. The shunt tubes **318** on the packer assembly **300** are configured to couple to and form a seal with shunt tubes on connected sand screens as discussed further below.

[0102] The shunt tubes **318** provide an alternate flowpath through the mechanically-set packers **304** and the intermediate spacing **308**. This enables the shunt tubes **318** to transport a carrier fluid along with gravel to different intervals **112**, **114** and **116** of the open-hole portion **120** of the wellbore **100**.

[0103] The packer assembly **300** also includes connection members. These may represent traditional threaded couplings. First, a neck section **306** is provided at a first end of the packer assembly **300**. The neck section **306** has external threads for connecting with a threaded coupling box of a sand screen or other pipe. Then, a notched or externally threaded section **310** is provided at an opposing second end. The threaded section **310** serves as a coupling box for receiving an external threaded end of a sand screen or other tubular member.

[0104] The neck section **306** and the threaded section **310** may be made of steel or steel alloys. The neck section **306** and the threaded section **310** are each configured to be a specific length **314**, such as 4 inches (10.2 cm) to 4 feet (1.2 meters) (or other suitable distance). The neck section **306** and the threaded section **310** also have specific inner and outer diameters. The neck section **306** has external threads **307**, while the threaded section **310** has internal threads **311**. These threads **307** and **311** may be utilized to form a seal between the packer assembly **300** and sand control devices or other pipe segments.

[0105] A cross-sectional view of the packer assembly **300** is shown in **Figure 3B**. **Figure 3B** is taken along the line **3B-3B** of **Figure 3A**. Various shunt tubes **318** are placed radially and equidistantly around the base pipe **302**. A central bore **305** is shown within the base pipe **302**. The central bore **305** receives production fluids during production operations and conveys them to the production tubing **130**.

[0106] **Figure 4A** presents a cross-sectional side view of a zonal isolation apparatus **400**, in one embodiment. The zonal isolation apparatus **400** includes the packer assembly **300** from **Figure 3A**. In addition, sand control devices **200** have been connected at opposing ends to the neck section **306** and the notched section **310**, respectively. Shunt tubes **318** from the packer assembly **300** are seen connected to shunt tubes **218** on the sand control devices **200**. The shunt tubes **218** represent packing tubes that allow the flow of gravel slurry between a wellbore annulus and the tubes **218**. The shunt tubes **218** on the sand control devices **200** optionally include valves **209** to control the flow of gravel slurry such as to packing tubes (not shown).

[0107] **Figure 4B** provides a cross-sectional side view of the zonal isolation apparatus **400**. **Figure 4B** is taken along the line **4B-4B** of **Figure 4A**. This is cut through one of the sand screens **200**. In **Figure 4B**, the slotted or perforated base pipe **205** is seen. This is in accordance with base pipe **205** of **Figures 1** and **2**. The central bore **105** is shown within the base pipe **205** for receiving production fluids during production operations.

[0108] An outer mesh **220** is disposed immediately around the base pipe **205**. The outer mesh **220** preferably comprises a wire mesh or wires helically wrapped around the base pipe **205**, and serves as a screen. In addition, shunt tubes **218** are placed radially and equidistantly around the outer mesh **205**. This means that the sand control devices **200** provide an external embodiment for the shunt tubes **218** (or alternate flow channels).

[0109] The configuration of the shunt tubes **218** is preferably concentric. This is seen in the cross-sectional view of **Figure 3B**. However, the shunt tubes **218** may be eccentrically designed. For example, Figure 2B in U.S. Pat. No. 7,661,476 presents a "Prior Art" arrangement for a sand control device wherein packing tubes 208A and transport tubes 208b are placed external to the base pipe 202 and surrounding filter medium 204.

[0110] In the arrangement of **Figures 4A** and **4B**, the shunt tubes **218** are external to the filter medium, or outer mesh **220**. The configuration of the sand control device **200** may be modified. In this respect, the shunt tubes **218** may be moved internal to the filter medium **220**.

[0111] **Figure 5A** presents a cross-sectional side view of a zonal isolation apparatus **500**, in an alternate embodiment. In this embodiment, sand control devices **200** are again connected at opposing ends to the neck section **306** and the notched section **310**, respectively, of the packer assembly **300**. In addition, shunt tubes **318** on the packer assembly **300** are seen connected to shunt tubes **218** on the sand control assembly **200**. However, in **Figure 5A**, the sand control assembly **200** utilizes internal shunt tubes **218**, meaning that the shunt tubes **218** are disposed between the base pipe **205** and the surrounding screen **220**.

[0112] **Figure 5B** provides a cross-sectional side view of the zonal isolation apparatus **500**. **Figure 5B** is taken along the line **B-B** of **Figure 5A**. This is cut through one of the sand screens **200**. In **Figure 5B**, the slotted or perforated base pipe **205** is again seen. This is in accordance with base pipe **205** of **Figures 1** and **2**. The central bore **105** is shown within the base pipe **205** for receiving production fluids during production operations.

[0113] Shunt tubes **218** are placed radially and equidistantly around the base pipe **205**. The shunt tubes **218** reside immediately around the base pipe **205**, and within a surrounding filter medium **220**. This means that the sand control devices **200** of **Figures 5A** and **5B** provide an internal embodiment for the shunt tubes **218**.

[0114] An annular region **225** is created between the base pipe **205** and the surrounding outer mesh or filter medium **220**. The annular region **225** accommodates the inflow of production fluids in a wellbore. The outer wire wrap **220** is supported by a plurality of radially extending support ribs **222**. The ribs **222** extend through the annular region **225**.

[0115] **Figures 4A** and **5A** present arrangements for connecting sand control joints to a packer assembly. Shunt tubes **318** (or alternate flow channels) within the packers fluidly

connect to shunt tubes **218** along the sand screens **200**. However, the zonal isolation apparatus arrangements **400**, **500** of **Figures 4A-4B** and **5A-5B** are merely illustrative. In an alternative arrangement, a manifolding system may be used for providing fluid communication between the shunt tubes **218** and the shunt tubes **318**.

[0116] **Figure 3C** is a cross-sectional view of the packer assembly **300** of **Figure 3A**, in an alternate embodiment. In this arrangement, the shunt tubes **218** are manifolded around the base pipe **302**. A support ring **315** is provided around the shunt tubes **318**. It is again understood that the present apparatus and methods are not confined by the particular design and arrangement of shunt tubes **318** so long as slurry bypass is provided for the packer assembly **210**. However, it is preferred that a concentric arrangement be employed.

[0117] It should also be noted that the coupling mechanism for the sand control devices **200** with the packer assembly **300** may include a sealing mechanism (not shown). The sealing mechanism prevents leaking of the slurry that is in the alternate flowpath formed by the shunt tubes. Examples of such sealing mechanisms are described in U.S. Patent No. 6,464,261; Intl. Pat. Application No. WO 2004/094769; Intl. Pat. Application No. WO 2005/031105; U.S. Pat. Publ. No. 2004/0140089; U.S. Pat. Publ. No. 2005/0028977; U.S. Pat. Publ. No. 2005/0061501; and U.S. Pat. Publ. No. 2005/0082060.

[0118] As noted, the packer assembly **300** includes a pair of mechanically-set packers **304**. When using the packer assembly **300**, the packers **304** are beneficially set before the slurry is injected and the gravel pack is formed. This requires a unique packer arrangement wherein shunt tubes are provided for an alternate flow channel.

[0119] The packers **304** of **Figure 3A** are shown schematically. However, **Figures 6A** and **6B** provide more detailed views of a mechanically-set packer **600** that may be used in the packer assembly of **Figure 3A**, in one embodiment. The views of **Figures 6A** and **6B** provide cross-sectional side views. In **Figure 6A**, the packer **600** is in its run-in position, while in **Figure 6B** the packer **600** is in its set position.

[0120] The packer **600** first includes an inner mandrel **610**. The inner mandrel **610** defines an elongated tubular body forming a central bore **605**. The central bore **605** provides a primary flow path of production fluids through the packer **600**. After installation and commencement of production, the central bore **605** transports production fluids to the bore **105** of the sand screens **200** (seen in **Figures 4A** and **4B**) and the production tubing **130** (seen in **Figures 1** and **2**).

[0121] The packer **600** also includes a first end **602**. Threads **604** are placed along the inner mandrel **610** at the first end **602**. The illustrative threads **604** are external threads. A box connector **614** having internal threads at both ends is connected or threaded on threads **604** at the first end **602**. The first end **602** of inner mandrel **610** with the box connector **614** is called the box end. The second end (not shown) of the inner mandrel **610** has external

threads and is called the pin end. The pin end (not shown) of the inner mandrel **610** allows the packer **600** to be connected to the box end of a sand screen or other tubular body such as a stand-alone screen, a sensing module, a production tubing, or a blank pipe.

[0122] The box connector **614** at the box end **602** allows the packer **600** to be connected to the pin end of a sand screen or other tubular body such as a stand-alone screen, a sensing module, a production tubing, or a blank pipe.

[0123] The inner mandrel **610** extends along the length of the packer **600**. The inner mandrel **610** may be composed of multiple connected segments, or joints. The inner mandrel **610** has a slightly smaller inner diameter near the first end **602**. This is due to a setting shoulder **606** machined into the inner mandrel. As will be explained more fully below, the setting shoulder **606** catches a release sleeve **710** in response to mechanical force applied by a setting tool.

[0124] The packer **600** also includes a piston mandrel **620**. The piston mandrel **620** extends generally from the first end **602** of the packer **600**. The piston mandrel **620** may be composed of multiple connected segments, or joints. The piston mandrel **620** defines an elongated tubular body that resides circumferentially around and substantially concentric to the inner mandrel **610**. An annulus **625** is formed between the inner mandrel **610** and the surrounding piston mandrel **620**. The annulus **625** beneficially provides a secondary flow path or alternate flow channels for fluids.

[0125] In the arrangement of **Figures 6A** and **6B**, the alternate flow channels defined by the annulus **625** are external to the inner mandrel **610**. However, the packer could be reconfigured such that the alternate flow channels are within the bore **605** of the inner mandrel **610**. In either instance, the alternate flow channels are "along" the inner mandrel **610**.

[0126] The annulus **625** is in fluid communication with the secondary flow path of another downhole tool (not shown in **Figures 6A** and **6B**). Such a separate tool may be, for example, the sand screens **200** of **Figures 4A** and **5A**, or a blank pipe, or other tubular body. The tubular body may or may not have alternate flow channels.

[0127] The packer **600** also includes a coupling **630**. The coupling **630** is connected and sealed (e.g., via elastomeric "o" rings) to the piston mandrel **620** at the first end **602**. The coupling **630** is then threaded and pinned to the box connector **614**, which is threadedly connected to the inner mandrel **610** to prevent relative rotational movement between the inner mandrel **610** and the coupling **630**. A first torque bolt is shown at **632** for pinning the coupling to the box connector **614**.

[0128] In one aspect, a NACA (National Advisory Committee for Aeronautics) key **634** is also employed. The NACA key **634** is placed internal to the coupling **630**, and external to a threaded box connector **614**. A first torque bolt is provided at **632**, connecting the coupling

630 to the NACA key **634** and then to the box connector **614**. A second torque bolt is provided at **636** connecting the coupling **630** to the NACA key **634**. NACA-shaped keys can (a) fasten the coupling **630** to the inner mandrel **610** via box connector **614**, (b) prevent the coupling **630** from rotating around the inner mandrel **610**, and (c) streamline the flow of slurry along the annulus **612** to reduce friction.

[0129] Within the packer **600**, the annulus **625** around the inner mandrel **610** is isolated from the main bore **605**. In addition, the annulus **625** is isolated from a surrounding wellbore annulus (not shown). The annulus **625** enables the transfer of gravel slurry from alternative flow channels (such as shunt tubes **218**) through the packer **600**. Thus, the annulus **625** becomes the alternative flow channel(s) for the packer **600**.

[0130] In operation, an annular space **612** resides at the first end **602** of the packer **600**. The annular space **612** is disposed between the box connector **614** and the coupling **630**. The annular space **612** receives slurry from alternate flow channels of a connected tubular body, and delivers the slurry to the annulus **625**. The tubular body may be, for example, an adjacent sand screen, a blank pipe, or a zonal isolation device.

[0131] The packer **600** also includes a load shoulder **626**. The load shoulder **626** is placed near the end of the piston mandrel **620** where the coupling **630** is connected and sealed. A solid section at the end of the piston mandrel **620** has an inner diameter and an outer diameter. The load shoulder **626** is placed along the outer diameter. The inner diameter has threads and is threadedly connected to the inner mandrel **610**. At least one alternate flow channel is formed between the inner and outer diameters to connect flow between the annular space **612** and the annulus **625**.

[0132] The load shoulder **626** provides a load-bearing point. During rig operations, a load collar or harness (not shown) is placed around the load shoulder **626** to allow the packer **600** to be picked up and supported with conventional elevators. The load shoulder **626** is then temporarily used to support the weight of the packer **600** (and any connected completion devices such as sand screen joints already run into the well) when placed in the rotary floor of a rig. The load may then be transferred from the load shoulder **626** to a pipe thread connector such as box connector **614**, then to the inner mandrel **610** or base pipe **205**, which is pipe threaded to the box connector **614**.

[0133] The packer **600** also includes a piston housing **640**. The piston housing **640** resides around and is substantially concentric to the piston mandrel **620**. The packer **600** is configured to cause the piston housing **640** to move axially along and relative to the piston mandrel **620**. Specifically, the piston housing **640** is driven by the downhole hydrostatic pressure. The piston housing 640 may be composed of multiple connected segments, or joints.

[0134] The piston housing **640** is held in place along the piston mandrel **620** during run-in. The piston housing **640** is secured using a release sleeve **710** and release key **715**. The release sleeve **710** and release key **715** prevent relative translational movement between the piston housing **640** and the piston mandrel **620**. The release key **715** penetrates through both the piston mandrel **620** and the inner mandrel **610**.

[0135] **Figures 7A** and **7B** provide enlarged views of the release sleeve **710** and the release key **715** for the packer **600**. The release sleeve **710** and the release key **715** are held in place by a shear pin **720**. In **Figure 7A**, the shear pin **720** has not been sheared, and the release sleeve **710** and the release key **715** are held in place along the inner mandrel **610**. However, in **Figure 7B** the shear pin **720** has been sheared, and the release sleeve **710** has been translated along an inner surface **608** of the inner mandrel **610**.

[0136] In each of **Figures 7A** and **7B**, the inner mandrel **610** and the surrounding piston mandrel **620** are seen. In addition, the piston housing **640** is seen outside of the piston mandrel **620**. The three tubular bodies representing the inner mandrel **610**, the piston mandrel **620**, and the piston housing **640** are secured together against relative translational or rotational movement by four release keys **715**. Only one of the release keys **715** is seen in **Figure 7A**; however, four separate keys **715** are radially visible in the cross-sectional view of **Figure 6E**, described below.

[0137] The release key **715** resides within a keyhole **615**. The keyhole **615** extends through the inner mandrel **610** and the piston mandrel **620**. The release key **715** includes a shoulder **734**. The shoulder **734** resides within a shoulder recess **624** in the piston mandrel **620**. The shoulder recess **624** is large enough to permit the shoulder **734** to move radially inwardly. However, such play is restricted in **Figure 7A** by the presence of the release sleeve **710**.

[0138] It is noted that the annulus **625** between the inner mandrel **610** and the piston mandrel **620** is not seen in **Figure 7A** or **7B**. This is because the annulus **625** does not extend through this cross-section, or is very small. Instead, the annulus **625** employs separate radially-spaced channels that preserve the support for the release keys **715**, as seen best in **Figure 6E**. Stated another way, the large channels making up the annulus **625** are located away from the material of the inner mandrel **610** that surrounds the keyholes **615**.

[0139] At each release key location, a keyhole **615** is machined through the inner mandrel **610**. The keyholes **615** are drilled to accommodate the respective release keys **715**. If there are four release keys **715**, there will be four discrete bumps spaced circumferentially to significantly reduce the annulus **625**. The remaining area of the annulus **625** between adjacent bumps allows flow in the alternate flow channel **625** to by-pass the release key **715**.

[0140] Bumps may be machined as part of the body of the inner mandrel **610**. More specifically, material making up the inner mandrel **610** may be machined to form the bumps. Alternatively, bumps may be machined as a separate, short release mandrel (not shown), which is then threaded to the inner mandrel **610**. Alternatively still, the bumps may be a separate spacer secured between the inner mandrel **610** and the piston mandrel **620** by welding or other means.

[0141] It is also noted here that in **Figure 6A**, the piston mandrel **620** is shown as an integral body. However, the portion of the piston mandrel **620** where the keyholes **615** are located may be a separate, short release housing. This separate housing is then connected to the main piston mandrel **620**.

[0142] Each release key **715** has an opening **732**. Similarly, the release sleeve **710** has an opening **722**. The opening **732** in the release key **715** and the opening **722** in the release sleeve **710** are sized and configured to receive a shear pin. The shear pin is seen at **720**. In **Figure 7A**, the shear pin **720** is held within the openings **732**, **722** by the release sleeve **710**. However, in **Figure 7B** the shear pin **720** has been sheared, and only a small portion of the pin **720** remains visible.

[0143] An outer edge of the release key **715** has a ruggled surface, or teeth. The teeth for the release key **715** are shown at **736**. The teeth **736** of the release key **715** are angled and configured to mate with a reciprocal ruggled surface within the piston housing **640**. The mating ruggled surface (or teeth) for the piston housing **640** are shown at **646**. The teeth **646** reside on an inner face of the piston housing **640**. When engaged, the teeth **736**, **646** prevent movement of the piston housing **640** relative to the piston mandrel **620** or the inner mandrel **610**. Preferably, the mating ruggled surface or teeth **646** reside on the inner face of a separate, short outer release sleeve, which is then threaded to the piston housing **640**.

[0144] Returning now to **Figures 6A** and **6B**, the packer **600** includes a centralizing member **650**. The centralizing member **650** is actuated by the movement of the piston housing **640**. The centralizing member **650** may be, for example, as described in U.S. Patent Publication No. 2011/0042106.

[0145] The packer **600** further includes a sealing element **655**. As the centralizing member **650** is actuated and centralizes the packer **600** within the surrounding wellbore, the piston housing **640** continues to actuate the sealing element **655** as described in U.S. Patent Publication No. 2009/0308592.

[0146] In **Figure 6A**, the centralizing member **650** and sealing element **655** are in their run-in position. In **Figure 6B**, the centralizing member **650** and connected sealing element **655** have been actuated. This means the piston housing **640** has moved along the piston mandrel **620**, causing both the centralizing member **650** and the sealing element **655** to engage the surrounding wellbore wall.

[0147] An anchor system as described in WO 2010/084353 may be used to prevent the piston housing **640** from going backward. This prevents contraction of the cup-type element **655**.

[0148] As noted, movement of the piston housing **640** takes place in response to hydrostatic pressure from wellbore fluids, including the gravel slurry. In the run-in position of the packer **600** (shown in **Figure 6A**), the piston housing **640** is held in place by the release sleeve **710** and associated piston key **715**. This position is shown in **Figure 7A**. In order to set the packer **600** (in accordance with **Figure 6B**), the release sleeve **710** must be moved out of the way of the release key **715** so that the teeth **736** of the release key **715** are no longer engaged with the teeth **646** of the piston housing **640**. This position is shown in **Figure 7B**.

[0149] To move the release the release sleeve **710**, a setting tool is used. An illustrative setting tool is shown at **750** in **Figure 7C**. The setting tool **750** defines a short cylindrical body **755**. Preferably, the setting tool **750** is run into the wellbore with a washpipe string (not shown). Movement of the washpipe string along the wellbore can be controlled at the surface.

[0150] An upper end **752** of the setting tool **750** is made up of several radial collet fingers **760**. The collet fingers **760** collapse when subjected to sufficient inward force. In operation, the collet fingers **760** latch into a profile **724** formed along the release sleeve **710**. The collet fingers **760** include raised surfaces **762** that mate with or latch into the profile **724** of the release key **710**. Upon latching, the setting tool **750** is pulled or raised within the wellbore. The setting tool **750** then pulls the release sleeve **710** with sufficient force to cause the shear pins **720** to shear. Once the shear pins **720** are sheared, the release sleeve **710** is free to translate upward along the inner surface **608** of the inner mandrel **610**.

[0151] As noted, the setting tool **750** may be run into the wellbore with a washpipe. The setting tool **750** may simply be a profiled portion of the washpipe body. Preferably, however, the setting tool **750** is a separate tubular body **755** that is threadedly connected to the washpipe. In **Figure 7C**, a connection tool is provided at **770**. The connection tool **770** includes external threads **775** for connecting to a drill string or other run-in tubular. The connection tool **770** extends into the body **755** of the setting tool **750**. The connection tool **770** may extend all the way through the body **755** to connect to the washpipe or other device, or it may connect to internal threads (not seen) within the body **755** of the setting tool **750**.

[0152] Returning to **Figures 7A** and **7B**, the travel of the release sleeve **710** is limited. In this respect, a first or top end **726** of the release sleeve **710** stops against the shoulder **606** along the inner surface **608** of the inner mandrel **610**. The length of the release sleeve **710** is short enough to allow the release sleeve **710** to clear the opening **732** in the release

key **715**. When fully shifted, the release key **715** moves radially inward, pushed by the ruggled profile in the piston housing **640** when hydrostatic pressure is present.

[0153] Shearing of the pin **720** and movement of the release sleeve **710** also allows the release key **715** to disengage from the piston housing **640**. The shoulder recess **624** is dimensioned to allow the shoulder **734** of the release key **715** to drop or to disengage from the teeth **646** of the piston housing **640** once the release sleeve **710** is cleared. Hydrostatic pressure then acts upon the piston housing **640** to translate it downward relative to the piston mandrel **620**.

[0154] After the shear pins **720** have been sheared, the piston housing **640** is free to slide along an outer surface of the piston mandrel **620**. To accomplish this, hydrostatic pressure from the annulus **625** acts upon a shoulder **642** in the piston housing **640**. This is seen best in **Figure 6B**. The shoulder **642** serves as a pressure-bearing surface. A fluid port **628** is provided through the piston mandrel **620** to allow fluid to access the shoulder **642**. Beneficially, the fluid port **628** allows a pressure higher than hydrostatic pressure to be applied during gravel packing operations. The pressure is applied to the piston housing **640** to ensure that the packer elements **655** engage against the surrounding wellbore.

[0155] The packer **600** also includes a metering device. As the piston housing **640** translates along the piston mandrel **620**, a metering orifice **664** regulates the rate the piston housing translates along the piston mandrel therefore slowing the movement of the piston housing and regulating the setting speed for the packer **600**. To further understand features of the illustrative mechanically-set packer **600**, several additional cross-sectional views are provided. These are seen at **Figures 6C**, **6D**, **6E**, and **6F**.

[0156] First, **Figure 6C** is a cross-sectional view of the mechanically-set packer of **Figure 6A.** The view is taken across line **6C-6C** of **Figure 6A**. Line **6C-6C** is taken through one of the torque bolts **636**. The torque bolt **636** connects the coupling **630** to the NACA key **634**.

[0157] **Figure 6D** is a cross-sectional view of the mechanically-set packer of **Figure 6A**. The view is taken across line **6D-6D** of **Figure 6B**. Line **6D-6D** is taken through another of the torque bolts **632**. The torque bolt **632** connects the coupling **630** to the box connector **614**, which is threaded to the inner mandrel **610**.

[0158] **Figure 6E** is a cross-sectional view of the mechanically-set packer **600** of **Figure 6A**. The view is taken across line **6E-6E** of **Figure 6A**. Line **6E-E** is taken through the release key **715**. It can be seen that the release key **715** passes through the piston mandrel **620** and into the inner mandrel **610**. It is also seen that the alternate flow channel **625** resides between the release keys **715**.

[0159] **Figure 6F** is a cross-sectional view of the mechanically-set packer **600** of **Figure 6A**. The view is taken across line **6F-6F** of **Figure 6B**. Line **6F-6F** is taken through the fluid

ports **628** within the piston mandrel **620**. As the fluid moves through the fluid ports **628** and pushes the shoulder **642** of the piston housing **640** away from the ports **628**, an annular gap **672** is created and elongated between the piston mandrel **620** and the piston housing **640**.

[0160] Once the bypass packer **600** is set, gravel packing operations may commence. **Figures 8A** through **8J** present stages of a gravel packing procedure, in one embodiment. The gravel packing procedure uses a packer assembly having alternate flow channels. The packer assembly may be in accordance with packer assembly **300** of **Figure 3A**. The packer assembly **300** will have mechanically-set packers **304**. These mechanically-set packers **304** may be in accordance with packer **600** of **Figures 6A** and **6B**.

[0161] In **Figures 8A** through **8J**, sand control devices are utilized with an illustrative gravel packing procedure. In **Figure 8A**, a wellbore **800** is shown. The illustrative wellbore **800** is a horizontal, open-hole wellbore. The wellbore **800** includes a wall **805**. Two different production intervals are indicated along the horizontal wellbore **800**. These are shown at **810** and **820**. Two sand control devices **850** have been run into the wellbore **800**. Separate sand control devices **850** are provided in each production interval **810**, **820**. Fluids in the wellbore **800** have been displaced using a clean fluid **814**.

[0162] Each of the sand control devices **850** is comprised of a base pipe **854** and a surrounding sand screen **856**. The base pipe **854** has slots or perforations to allow fluid to flow into the base pipe **854**. The sand control devices **850** also each include alternate flow paths. These may be in accordance with shunt tubes **218** from either **Figure 4B** or **Figure 5B**. Preferably, the shunt tubes are internal shunt tubes disposed between the base pipes **854** and the sand screens **856** in the annular region shown at **852**.

[0163] The sand control devices **850** are connected via an intermediate packer assembly **300**. In the arrangement of **Figure 8A**, the packer assembly **300** is installed at the interface between production intervals **810** and **820**. More than one packer assembly **300** may be incorporated.

[0164] In addition to the sand control devices **850**, a washpipe **840** has been lowered into the wellbore **800**. The washpipe **840** is run into the wellbore **800** below a crossover tool or a gravel pack service tool (not shown) which is attached to the end of a drill pipe **835** or other working string. The washpipe **840** is an elongated tubular member that extends into the sand screens **850**. The washpipe **840** aids in the circulation of the gravel slurry during a gravel packing operation, and is subsequently removed. Attached to the washpipe **840** is a shifting tool, such as the shifting tool **750** presented in **Figure 7C**. The shifting tool **750** is positioned below the packer **300**.

[0165] In **Figure 8A**, a crossover tool **845** is placed at the end of the drill pipe **835**. The crossover tool **845** is used to direct the injection and circulation of the gravel slurry, as discussed in further detail below.

[0166] A separate packer **815** is connected to the crossover tool **845**. The packer **815** and connected crossover tool **845** are temporarily positioned within a string of production casing **830**. Together, the packer **815**, the crossover tool **845**, the elongated washpipe **840**, the shifting tool **750**, and the gravel pack screens **850** are run into the lower end of the wellbore **800**. The packer **815** is then set in the production casing **830**. The crossover tool **845** is then released from the packer **815** and is free to move as shown in **Figure 8B**.

[0167] In **Figure 8B**, the packer **815** is set in the production casing string **830**. This means that the packer **815** is actuated to extend slips and an elastomeric sealing element against the surrounding casing string **830**. The packer **815** is set above the intervals **810** and **820**, which are to be gravel packed. The packer **815** seals the intervals **810** and **820** from the portions of the wellbore **800** above the packer **815**.

[0168] After the packer **815** is set, as shown in **Figure 8B**, the crossover tool **845** is shifted up into a reverse position. Circulation pressures can be taken in this position. A carrier fluid **812** is pumped down the drill pipe **835** and placed into an annulus between the drill pipe **835** and the surrounding production casing **830** above the packer **815**. The carrier fluid is a gravel carrier fluid, which is the liquid component of the gravel packing slurry. The carrier fluid **812** displaces the clean displacement fluid **814** above the packer **815**, which may be an oil-based fluid such as the conditioned NAF. The carrier fluid **812** displaces the displacement fluid **814** in the direction indicated by arrows "**C**."

[0169] Next, the packers **304** are set, as shown in **Figure 8C**. This is done by pulling the shifting tool located below the packer assembly **300** on the washpipe **840** and up past the packer assembly **300**. More specifically, the mechanically-set packers **304** of the packer assembly **300** are set. The packers **304** may be, for example, packer **600** of **Figures 6A** and **6B**. The packer **600** is used to isolate the annulus formed between the sand screens **856** and the surrounding wall **805** of the wellbore **800**. The washpipe **840** is lowered to a reverse position. While in the reverse position, as shown in **Figure 8D**, the carrier fluid **812** with gravel may be placed within the drill pipe **835** and utilized to force the clean displacement fluid **814** through the washpipe **840** and up the annulus formed between the drill pipe **835** and production casing **830** above the packer **815**, as shown by the arrows "**C**.'

[0170] In **Figures 8D** through **8F**, the crossover tool **845** may be shifted into the circulating position to gravel pack the first subsurface interval **810**. In **Figure 8D**, the carrier fluid with gravel **816** begins to create a gravel pack within the production interval **810** above the packer **300** in the annulus between the sand screen **856** and the wall **805** of the open-hole wellbore **800**. The fluid flows outside the sand screen **856** and returns through the washpipe **840** as indicated by the arrows "**D**."

[0171] In **Figure 8E**, a first gravel pack **860** begins to form above the packer **300**. The gravel pack **860** is forming around the sand screen **856** and towards the packer **815**. Carrier

fluid **812** is circulated below the packer **300** and to the bottom of the wellbore **800**. The carrier fluid **812** without gravel flows up the washpipe **840** as indicated by arrows "**C**."

[0172] In **Figure 8F**, the gravel packing process continues to form the gravel pack **860** toward the packer **815**. The sand screen **856** is now being fully covered by the gravel pack **860** above the packer **300**. Carrier fluid **812** continues to be circulated below the packer **300** and to the bottom of the wellbore **800**. The carrier fluid **812** *sans* gravel flows up the washpipe **840** as again indicated by arrows "**C**."

[0173] Once the gravel pack **860** is formed in the first interval **810** and the sand screens above the packer **300** are covered with gravel, the carrier fluid with gravel **816** is forced through the shunt tubes (shown at **318** in **Figure 3B**). The carrier fluid with gravel **816** forms the gravel pack **860** in **Figures 8G** through **8J**.

[0174] In **Figure 8G**, the carrier fluid with gravel **816** now flows within the production interval **820** below the packer **300**. The carrier fluid **816** flows through the shunt tubes and packer **300**, and then outside the sand screen **856**. The carrier fluid **816** then flows in the annulus between the sand screen **856** and the wall **805** of the wellbore **800**, and returns through the washpipe **840**. The flow of carrier fluid with gravel **816** is indicated by arrows "**D**," while the flow of carrier fluid in the washpipe **840** without the gravel is indicated at **812**, shown by arrows "**C**."

[0175] It is noted here that slurry only flows through the bypass channels along the packer sections. After that, slurry will go into the alternate flow channels in the next, adjacent screen joint. Alternate flow channels have both transport and packing tubes manifolded together at each end of a screen joint. Packing tubes are provided along the sand screen joints. The packing tubes represent side nozzles that allow slurry to fill any voids in the annulus. Transport tubes will take the slurry further downstream.

[0176] In **Figure 8H**, the gravel pack **860** is beginning to form below the packer **300** and around the sand screen **856**. In **Figure 8I**, the gravel packing continues to grow the gravel pack **860** from the bottom of the wellbore **800** up toward the packer **300**. In **Figure 8J**, the gravel pack **860** has been formed from the bottom of the wellbore **800** up to the packer **300**. The sand screen **856** below the packer **300** has been covered by gravel pack **860**. The surface treating pressure increases to indicate that the annular space between the sand screens **856** and the wall **805** of the wellbore **800** is fully gravel packed.

[0177] **Figure 8K** shows the drill string **835** and the washpipe **840** from **Figures 8A** through **8J** having been removed from the wellbore **800**. The casing **830**, the base pipes **854**, and the sand screens **856** remain in the wellbore **800** along the upper **810** and lower **820** production intervals. Packer **300** and the gravel packs **860** remain set in the open hole wellbore **800** following completion of the gravel packing procedure from **Figures 8A** through **8J**. The wellbore **800** is now ready for production operations.

[0178] As mentioned above, once a wellbore has undergone gravel packing, the operator may choose to isolate a selected interval in the wellbore, and discontinue production from that interval. To demonstrate how a wellbore interval may be isolated, **Figures 9A** and **9B** are provided.

[0179] First, **Figure 9A** is a cross-sectional view of a wellbore **900A**. The wellbore **900A** is generally constructed in accordance with wellbore **100** of **Figure 2**. In **Figure 9A**, the wellbore **900A** is shown intersecting through a subsurface interval **114**. Interval **114** represents an intermediate interval. This means that there is also an upper interval **112** and a lower interval **116** (seen in **Figure 2**, but not shown in **Figure 9A**).

[0180] The subsurface interval **114** may be a portion of a subsurface formation that once produced hydrocarbons in commercially viable quantities but has now suffered significant water or hydrocarbon gas encroachment. Alternatively, the subsurface interval **114** may be a formation that was originally a water zone or aquitard or is otherwise substantially saturated with aqueous fluid. In either instance, the operator has decided to seal off the influx of formation fluids from interval **114** into the wellbore **900A**.

[0181] A sand screen **200** has been placed in the wellbore **900A**. Sand screen **200** is in accordance with the sand control device **200** of **Figure 2**. In addition, a base pipe **205** is seen extending through the intermediate interval **114**. The base pipe **205** is part of the sand screen **200**. The sand screen **200** also includes a mesh screen, a wire-wrapped screen, or other radial filter medium **207**. The base pipe **205** and surrounding filter medium **207** preferably comprise a series of joints connected end-to-end. The joints are ideally about 5 to 45 feet in length.

[0182] The wellbore **900A** has an upper packer assembly **210'** and a lower packer assembly **210''**. The upper packer assembly **210'** is disposed near the interface of the upper interval **112** and the intermediate interval **114**, while the lower packer assembly **210''** is disposed near the interface of the intermediate interval **114** and the lower interval **116**. Each packer assembly **210'**, **210''** is preferably in accordance with packer assembly **300** of **Figures 3A** and **3B**. In this respect, the packer assemblies **210'**, **210''** will each have opposing mechanically-set packers **304**. The mechanically-set packers are shown in **Figure 9A** at **212** and **214**. The mechanically-set packers **212**, **214** may be in accordance with packer **600** of **Figures 6A** and **6B**. The packers **212**, **214** are spaced apart as shown by spacing **216**.

[0183] The dual packers **212**, **214** are mirror images of each other, except for the release sleeves (e.g., release sleeve **710** and associated shear pin **720**). As noted above, unilateral movement of a shifting tool (such as shifting tool **750**) shears the shear pins **720** and moves the release sleeves **710**. This allows the packer elements **655** to be activated in sequence, the lower one first, and then the upper one.

[0184] The wellbore **900A** is completed as an open-hole completion. A gravel pack has been placed in the wellbore **900A** to help guard against the inflow of granular particles. Gravel packing is indicated as spackles in the annulus **202** between the filter media **207** of the sand screen **200** and the surrounding wall **201** of the wellbore **900A**.

[0185] In the arrangement of **Figure 9A**, the operator desires to continue producing formation fluids from upper **112** and lower **116** intervals while sealing off intermediate interval **114**. The upper **112** and lower **116** intervals are formed from sand or other rock matrix that is permeable to fluid flow. To accomplish this, a straddle packer **905** has been placed within the sand screen **200**. The straddle packer **905** is placed substantially across the intermediate interval **114** to prevent the inflow of formation fluids from the intermediate interval **114**.

[0186] The straddle packer **905** comprises a mandrel **910**. The mandrel **910** is an elongated tubular body having an upper end adjacent the upper packer assembly **210'**, and a lower end adjacent the lower packer assembly **210''**. The straddle packer **905** also comprises a pair of annular packers. These represent an upper packer **912** adjacent the upper packer assembly **210'**, and a lower packer **914** adjacent the lower packer assembly **210''**. The novel combination of the upper packer assembly **210'** with the upper packer **912**, and the lower packer assembly **210''** with the lower packer **914** allows the operator to successfully isolate a subsurface interval such as intermediate interval **114** in an open-hole completion.

[0187] Another technique for isolating an interval along an open-hole formation is shown in **Figure 9B**. **Figure 9B** is a side view of a wellbore **900B**. Wellbore **900B** may again be in accordance with wellbore **100** of **Figure 2**. Here, the lower interval **116** of the open-hole completion is shown. The lower interval **116** extends essentially to the bottom **136** of the wellbore **900B** and is the lowermost zone of interest.

[0188] In this instance, the subsurface interval **116** may be a portion of a subsurface formation that once produced hydrocarbons in commercially viable quantities but has now suffered significant water or hydrocarbon gas encroachment. Alternatively, the subsurface interval **116** may be a formation that was originally a water zone or aquitard or is otherwise substantially saturated with aqueous fluid. In either instance, the operator has decided to seal off the influx of formation fluids from the lower interval **116** into the wellbore **100**.

[0189] To accomplish this, a plug **920** has been placed within the wellbore **100**. Specifically, the plug **920** has been set in the mandrel **215** supporting the lower packer assembly **210''**. Of the two packer assemblies **210'**, **210''**, only the lower packer assembly **210''** is seen. By positioning the plug **920** in the lower packer assembly **210''**, the plug **920** is able to prevent the flow of formation fluids up the wellbore **200** from the lower interval **116**.

[0190] It is noted that in connection with the arrangement of **Figure 9B**, the intermediate interval **114** may comprise a shale or other rock matrix that is substantially impermeable to fluid flow. In this situation, the plug **920** need not be placed adjacent the lower packer assembly **210''**; instead, the plug **920** may be placed anywhere above the lower interval **116** and along the intermediate interval **114**. Further, in this instance the upper packer assembly **210'** need not be positioned at the top of the intermediate interval **114**; instead, the upper packer assembly **210'** may also be placed anywhere along the intermediate interval **114**. If the intermediate interval **114** is comprised of unproductive shale, the operator may choose to place blank pipe across this region, with alternate flow channels, i.e. transport tubes, along the intermediate interval **114**.

[0191] A method **1000** for completing a wellbore is also provided herein. The method **1000** is presented in **Figure 10**. **Figure 10** provides a flowchart presenting steps for a method **1000** of completing a wellbore, in various embodiments. Preferably, the wellbore is an open-hole wellbore.

[0192] The method **1000** includes providing a zonal isolation apparatus. This is shown at Box **1010** of **Figure 10**. The zonal isolation apparatus is preferably in accordance with the components described above in connection with **Figure 2**. In this respect, the zonal isolation apparatus may first include a sand screen. The sand screen will represent a base pipe and a surrounding mesh or wound wire. The zonal isolation apparatus will also have at least one packer assembly. The packer assembly will have at least one mechanically-set packer, with the mechanically-set packer having alternate flow channels.

[0193] Preferably, the packer assembly will have at least two mechanically set packers. Alternate flow channels will travel through each of the mechanically-set packers. Preferably, the zonal isolation apparatus will comprise at least two packer assemblies separated by sand screen joints or blank joints or some combination thereof.

[0194] The method **1000** also includes running the zonal isolation apparatus into the wellbore. The step of running the zonal isolation apparatus into the wellbore is shown at Box **1020**. The zonal isolation apparatus is run into a lower portion of the wellbore, which is preferably completed as an open-hole.

[0195] The open-hole portion of the wellbore may be completed substantially vertically. Alternatively, the open-hole portion may be deviated, or even horizontal.

[0196] The method **1000** also includes positioning the zonal isolation apparatus in the wellbore. This is shown in **Figure 10** at Box **1030**. The step of positioning the zonal isolation apparatus is preferably done by hanging the zonal isolation apparatus from a lower portion of a string of production casing. The apparatus is positioned such that the sand screen is adjacent one or more selected production intervals along the open-hole portion of

the wellbore. Further, a first of the at least one packer assembly is positioned above or proximate the top of a selected subsurface interval.

[0197] In one embodiment, the wellbore traverses through three separate intervals. These include an upper interval from which hydrocarbons are produced, and a lower interval from which hydrocarbons are no longer being produced in economically viable volumes. Such intervals may be formed of sand or other permeable rock matrix. The intervals may also include an intermediate interval from which hydrocarbons are not produced. The formation along the intermediate interval may be formed of shale or other substantially impermeable material. The operator may choose to position the first of the at least one packer assembly near the top of the lower interval or anywhere along the non-permeable intermediate interval.

[0198] In one aspect, the at least one packer assembly is placed proximate a top of an intermediate interval. Optionally, a second packer assembly is positioned proximate the bottom of a selected interval such as the intermediate interval. This is shown in Box **1035**.

[0199] The method **1000** next includes setting the mechanically set packer elements in each of the at least one packer assembly. This is provided in Box **1040**. Mechanically setting the upper and lower packer elements means that an elastomeric (or other) sealing member engages the surrounding wellbore wall. The packer elements isolate an annular region formed between the sand screens and the surrounding subsurface formation above and below the packer assemblies.

[0200] Beneficially, the step of setting the packer of Box **1040** is provided before slurry is injected into the annular region. Setting the packer provides a hydraulic and mechanical seal to the wellbore before any gravel is placed around the elastomeric element. This provides a better seal during the gravel packing operation.

[0201] The step of Box **1040** may be accomplished by using the packer **600** of **Figures 6A** and **6B**. The open-hole, mechanically-set packer **600** enables gravel pack completions to gain the current flexibility of standalone screen (SAS) applications by providing future zonal isolation of unwanted fluids while enjoying the benefits of reliability of an alternate path gravel pack completion.

[0202] **Figure 11** is a flowchart that provides steps that may be used, in one embodiment, for a method **1100** of setting a packer. The method **110** first includes providing the packer. This is shown at Box **1110**. The packer may be in accordance with packer **600** of **Figures 6A** and **6B**. Thus, the packer is a mechanically-set packer that is set against an open-hole wellbore to seal an annulus.

[0203] Fundamentally, the packer will have an inner mandrel, and alternate flow channels around the inner mandrel. The packer may further have a movable piston housing and an elastomeric sealing element. The sealing element is operatively connected to the

piston housing. This means that sliding the movable piston housing along the packer (relative to the inner mandrel) will actuate the sealing element into engagement with the surrounding wellbore.

[0204] The packer may also have a port. The port is in fluid communication with the piston housing. Hydrostatic pressure within the wellbore communicates with the port. This, in turn, applies fluid pressure to the piston housing. Movement of the piston housing along the packer in response to hydrostatic pressure causes the elastomeric sealing element to be expanded into engagement with the surrounding wellbore.

[0205] It is preferred that the packer also have a centralizing system. An example is the centralizer **660** of **Figures 6A** and **6B**. It is also preferred that mechanical force used to actuate the sealing element be applied by the piston housing through the centralizing system. In this way, both the centralizers and the sealing element are set through the same hydrostatic force.

[0206] The method **1100** also includes connecting the packer to a tubular body. This is provided at Box **1120**. The tubular body may be a blank pipe or a downhole sensing tool equipped with alternate flow channels. However, it is preferred that the tubular body be a sand screen equipped with alternate flow channels.

[0207] Preferably, the packer is one of two mechanically-set packers having cup-type sealing elements. The packer assembly is placed within a string of sand screens or blanks equipped with alternate flow channels.

[0208] Regardless of the arrangement, the method **1100** also includes running the packer and the connected tubular body into a wellbore. This is shown at Box **1130**. In addition, the method **1100** includes running a setting tool into the wellbore. This is provided at Box **1140**. Preferably, the packer and connected sand screen are run first, followed by the setting tool. The setting tool may be in accordance with exemplary setting tool **750** of **Figure 7C**. Preferably, the setting tool is part of or is run in with a washpipe.

[0209] The method **1100** next includes moving the setting tool through the inner mandrel of the packer. This is shown at Box **1150**. The setting tool is translated within the wellbore through mechanical force. Preferably, the setting tool is at the end of a working string such as coiled tubing.

[0210] Movement of the setting tool through the inner mandrel causes the setting tool to shift a sleeve along the inner mandrel. In one aspect, shifting the sleeve will shear one or more shear pins. In any aspect, shifting the sleeve releases the piston housing, permitting the piston housing to shift or to slide along the packer relative to the inner mandrel. As noted above, this movement of the piston housing permits the sealing element to be actuated against the wall of the surrounding open-hole wellbore.

[0211] In connection with the moving step of Box **1150**, the method **1100** also includes communicating hydrostatic pressure to the port. This is seen in Box **1160**. Communicating hydrostatic pressure means that the wellbore has sufficient energy stored in a column of fluid to create a hydrostatic head, wherein the hydrostatic head acts against a surface or shoulder on the piston housing. The hydrostatic pressure includes pressure from fluids in the wellbore, whether such fluids are completion fluids or reservoir fluids, and may also include pressure contributed downhole by a reservoir. Because the shear pins (including set screws) have been sheared, the piston housing is free to move.

[0212] Returning back to **Figure 10**, the method **1000** for completing an open-hole wellbore also includes injecting a particulate slurry into the annular region. This is demonstrated in Box **1050**. The particulate slurry is made up of a carrier fluid and sand (and/or other) particles. One or more alternate flow channels allow the particulate slurry to bypass the sealing elements of the mechanically-set packers. In this way, the open-hole portion of the wellbore is gravel-packed below, or above and below (but not between), the mechanically-set packer elements.

[0213] It is noted that the sequence for annulus pack-off may vary. For example, if a premature sand bridge is formed during gravel packing, the annulus above the bridge will continue to be gravel packed via fluid leak-off through the sand screen due to the alternate flow channels. In this respect, some slurry will flow into and through the alternate flow channels to bypass the premature sand bridge and deposit a gravel pack. As the annulus above the premature sand bridge is nearly completely packed, slurry is increasingly diverted into and through the alternate flow channels. Here, both the premature sand bridge and the packer will be bypassed so that the annulus is gravel packed below the packer.

[0214] It is also possible that a premature sand bridge may form below the packer. Any voids above or below the packer will eventually be packed by the alternate flow channels until the entire annulus is fully gravel packed.

[0215] During pumping operations, once gravel covers the screens above the packer, slurry is diverted into the shunt tubes, then passes through the packer, and continues to pack below the packer via the shunt tubes (or alternate flow channels) with side ports allowing slurry to exit into the wellbore annulus. The hardware provides the ability to seal off bottom water, selectively complete or gravel pack targeted intervals, perform a stacked open-hole completion, or isolate a gas/water-bearing sand following production. The hardware further allows for selective stimulation, selective water or gas injection, or selective chemical treatment for damage removal or sand consolidation.

[0216] The method **1000** further includes producing production fluids from intervals along the open-hole portion of the wellbore. This is provided at Box **1060**. Production takes place for a period of time.

[0217] In one embodiment of the method **1000**, flow from a selected interval may be sealed from flowing into the wellbore. For example, a plug may be installed in the base pipe of the sand screen above or near the top of a selected subsurface interval. This is shown at Box **1070**. Such a plug may be used at or below the lowest packer assembly, such as the second packer assembly from step **1035**.

[0218] In another example, a straddle packer is placed along the base pipe along a selected subsurface interval to be sealed. This is shown at Box **1075**. Such a straddle may involve placement of sealing elements adjacent upper and lower packer assemblies (such as packer assemblies **210'**, **210''** of **Figure 2** or **Figure 9A**) along a mandrel.

[0219] Other embodiments of sand control devices **200** may be used with the apparatuses and methods herein. For example, the sand control devices may include stand-alone screens (SAS), pre-packed screens, or membrane screens. The joints may be any combination of screen, blank pipe, or zonal isolation apparatus.

[0220] The downhole packer may be used for formation isolation in contexts other than production. For example, the method may further comprise injecting a solution from an earth surface, through the inner mandrel below the packer, and into a subsurface formation. The solution may be, for example, and aqueous solution, an acidic solution, or a chemical treatment. The method may then further comprise circulating the aqueous solution, the acidic solution, or the chemical treatment to clean a near-wellbore region along the open-hole portion of the wellbore. This may be done before or after production operations begin. Alternatively, the solution may be an aqueous solution, and the method may further comprise continuing to inject the aqueous solution into the subsurface formation as part of an enhanced oil recovery operation. This would preferably be in lieu of production from the wellbore.

[0221] While it will be apparent that the inventions herein described are well calculated to achieve the benefits and advantages set forth above, it will be appreciated that the inventions are susceptible to modification, variation and change without departing from the spirit thereof. Improved methods for completing an open-hole wellbore are provided so as to seal off one or more selected subsurface intervals. An improved zonal isolation apparatus is also provided. The inventions permit an operator to produce fluids from or to inject fluids into a selected subsurface interval.

CLAIMS

1. A method for completing a wellbore in a subsurface formation, the method comprising:

providing a packer, the packer comprising:

an inner mandrel,

alternate flow channels along the inner mandrel,

a movable piston housing retained around the inner mandrel,

one or more flow ports providing fluid communication between the alternate flow channels and a pressure-bearing surface of the piston housing, and

a sealing element external to the inner mandrel;

connecting the packer to a tubular body;

running the packer and connected tubular body into the wellbore;

running a setting tool into the inner mandrel of the packer;

manipulating the setting tool to mechanically release the movable piston housing from its retained position;

setting the packer by communicating hydrostatic pressure to the piston housing through the one or more flow ports, thereby moving the released piston housing to actuate the sealing element into engagement with the surrounding wellbore;

injecting a gravel slurry into an annular region formed between the tubular body and the surrounding wellbore; and

injecting the gravel slurry through the alternate flow channels to allow the gravel slurry to at least partially bypass the sealing element so that the wellbore is gravel-packed within the annular region below the packer.

2. The method of claim **1**, wherein the injecting steps take place after the packer has been set in the wellbore.

3. The method of claim **2**, wherein:

the wellbore has a lower end defining an open-hole portion;

the packer and tubular body are run into the wellbore along the open-hole portion;

the packer is set within the open-hole portion of the wellbore;

the tubular body is (i) a sand screen comprising a base pipe, alternate flow channels, and a surrounding filter medium, or (ii) a blank pipe having alternate flow channels; and

the base pipe or the blank pipe is made up of a plurality of joints.

4. The method of claim **3**, further comprising:

connecting the packer between two of the plurality of joints of the base pipe.

5. The method of claim **3**, wherein the packer is a first mechanically-set packer that is part of a packer assembly.

6. The method of claim **5**, wherein the packer assembly comprises:

the first mechanically-set packer; and

a second mechanically-set packer spaced apart from the first mechanically-set packer, the second mechanically-set packer being substantially a mirror image of or substantially identical to the first mechanically-set packer.

7. The method of claim **6**, wherein each of the first and second packers further comprises:

a movable piston housing retained around the inner mandrel; and

one or more flow ports providing fluid communication between the alternate flow channels and a pressure-bearing surface of the piston housing.

8. The method of claim **7**, further comprising:

running a setting tool into the inner mandrel of each of the packers;

manipulating the setting tool to mechanically release the movable piston housing from its retained position along each of the respective first and second packers; and

communicating hydrostatic pressure to the piston housings through the one or more flow ports, thereby moving the released piston housings and actuating the sealing element of each of the first and second packers against the surrounding wellbore.

9. The method of claim **8**, wherein:

running the setting tool comprises running a washpipe into a bore within the inner mandrels of the respective first and second packers, the washpipe having the setting tool thereon; and

releasing the movable piston housing from its retained position comprises pulling the washpipe with the setting tool along the inner mandrels of the respective first and second packers, thereby shifting release sleeves in each of the first and second packers, and shearing respective shear pins.

10. The method of claim **3**, further comprising:

producing hydrocarbon fluids from at least one interval along the open-hole portion of the wellbore.

11. The method of claim **3**, wherein:

the packer further comprises a centralizer; and

setting the packer further comprises actuating the centralizer into engagement with the surrounding open-hole portion of the wellbore.

12. The method of claim **2**, wherein the step of injecting the gravel slurry through the alternate flow channels comprises bypassing the sealing element so that the open-hole portion of the wellbore is gravel-packed above and below the packer after the packer has been set in the wellbore.

13. The method of claim **1**, wherein:

the packer further comprises a release sleeve along an inner surface of the inner mandrel; and

manipulating the setting tool comprises pulling the setting tool through the inner mandrel to shift the release sleeve.

14. The method of claim **13**, wherein shifting the release sleeve shears at least one shear pin.

15. The method of claim **14**, wherein:

running the setting tool comprises running a washpipe into a bore within the inner mandrel of the packer, the washpipe having the setting tool thereon; and

releasing the movable piston housing from its retained position comprises pulling the washpipe with the setting tool along the inner mandrel, thereby shifting the release sleeve and shearing the at least one shear pin.

16. The method of claim **15**, wherein the sealing element is an elastomeric cup-type element.

17. The method of claim **15**, wherein:

the packer further comprises a centralizer; and

releasing the piston housing further actuates the centralizer into engagement with the surrounding open-hole portion of the wellbore.

18. The method of claim **17**, wherein communicating hydrostatic pressure to the piston housing moves the piston housing to actuate the centralizer, which in turn actuates the sealing element against the surrounding wellbore.

19. The method of claim **1**, wherein setting the packer comprises setting the packer along either a non-perforated joint of casing, or an open-hole portion.

20. A downhole packer for sealing an annular region between a tubular body and a surrounding wellbore, comprising:

an inner mandrel;

an alternate flow channel along the inner mandrel;

a sealing element external to the inner mandrel and residing circumferentially around the inner mandrel;

a movable piston housing retained around the inner mandrel, the movable piston housing having a pressure-bearing surface at a first end, and being operatively connected to the sealing element, wherein the piston housing acts against the sealing element in response to hydrostatic pressure;

one or more flow ports providing fluid communication between the alternate flow channels and the pressure-bearing surface of the piston housing;

a release sleeve along an inner surface of the inner mandrel; and

a release key connected to the release sleeve, the release key being movable between a retaining position wherein the release key engages and retains the moveable piston housing in place, to a releasing position wherein the release key disengages the piston housing, thereby permitting the hydrostatic pressure to act against the pressure-bearing surface of the piston housing and move the piston housing along the inner mandrel to actuate the sealing element.

21. The downhole packer of claim **20**, further comprising:

at least one shear pin releasably connecting the release sleeve to the release key.

22. The downhole packer of claim **20**, wherein the sealing element is an elastomeric cup-type element.

23. The downhole packer of claim **20**, wherein the sealing element is about 6 inches (15.2 cm) to 24 inches (61 cm) in length.

24. The downhole packer of claim **23**, further comprising:

a centralizer having extendable fingers, the fingers extending in response to movement of the piston housing.

25. The downhole packer of claim **24**, wherein:

the centralizer is disposed around the inner mandrel between the piston housing and the sealing element; and

the downhole packer is configured so that force applied by the piston housing against the centralizer actuates the sealing element against the surrounding wellbore.

26. The downhole packer of claim **20**, further comprising:

a piston mandrel disposed circumferentially around the inner mandrel;

an annulus provided between the inner mandrel and the surrounding piston mandrel, wherein the annulus defines the alternate flow channel; and

wherein the one or more flow ports is disposed within the piston mandrel.

27. The downhole packer of claim **26**, wherein the piston housing and the sealing element reside circumferentially around the piston mandrel.

28. The downhole packer of claim **26**, further comprising:

a metering orifice configured to regulate a rate at which the piston housing translates along the piston mandrel, thereby slowing the movement of the piston housing and regulating the setting speed for the packer.

29. The downhole packer of claim **26**, further comprising:

a load shoulder disposed around the piston mandrel at an upper end, and configured to support the packer during make-up with a working string.

30. The downhole packer of claim **26**, further comprising:

a coupling connected to the piston mandrel at the upper end, the coupling defining a tubular body configured to receive the inner mandrel, and to form a part of the alternate flow channel between the inner mandrel and the surrounding coupling.

31. A method for setting a packer within a wellbore, comprising:

providing a packer, the packer comprising:

an inner mandrel,

alternate flow channels along the inner mandrel,

a movable piston housing retained around the inner mandrel,

one or more flow ports providing fluid communication between the alternate flow channels and a pressure-bearing surface of the piston housing, and

a sealing element external to the inner mandrel;

connecting the packer to a tubular body;

running the packer and connected tubular body into the wellbore;

running a setting tool into the inner mandrel of the packer;

pulling the setting tool to mechanically shift a release sleeve from a retained position along the inner mandrel of the packer, thereby releasing the piston housing for axial movement; and

communicating hydrostatic pressure to the piston housing through the one or more flow ports, thereby axially moving the released piston housing and actuating the sealing element against the surrounding wellbore.

32. The method of claim **31**, wherein:

the wellbore has a lower end defining an open-hole portion;

running the packer into the wellbore comprises running the packer into the open-hole portion of the wellbore;

the tubular body is (i) a sand screen comprising a base pipe, alternate flow channels, and a surrounding filter medium, or (ii) a blank pipe comprising alternate flow channels; and

the method further comprises:

injecting a gravel slurry into an annular region formed between the tubular body and the surrounding open-hole portion of the wellbore, and

further injecting the gravel slurry through the alternate flow channels to allow the gravel slurry to bypass the sealing element so that the open-hole portion of the wellbore is gravel-packed below the packer after the packer has been set in the wellbore.

33. The method of claim **32**, wherein the step of further injecting the gravel slurry through the alternate flow channels comprises bypassing the sealing element so that the open-hole portion of the wellbore is gravel-packed above and below the packer after the packer has been set in the wellbore.

34. The method of claim **32**, wherein:

shifting the release sleeve shears at least one shear pin;

running the setting tool comprises running a washpipe into a bore within the inner mandrel of the packer, the washpipe having the setting tool thereon; and

releasing the movable piston housing from its retained position comprises pulling the washpipe with the setting tool along the inner mandrel, thereby shifting the release sleeve and shearing the at least one shear pin.

35. The method of claim **34**, wherein the packer further comprises one or more flow ports providing fluid communication between the alternate flow channels and a pressure-bearing surface of the piston housing.

36. The method of claim **35**, wherein:

the packer further comprises a centralizer; and

releasing the piston housing further actuates the centralizer into engagement with the surrounding open-hole portion of the wellbore.

37. The method of claim **32**, wherein the step of further injecting the gravel slurry through the alternate flow channels comprises bypassing the sealing element so that the open-hole portion of the wellbore is gravel-packed above and below the packer after packer has been set in the wellbore.

38. The method of claim **32**, further comprising:

producing formation fluids from a subsurface formation below the packer and up through the inner mandrel of the packer to an earth surface.

39. The method of claim **32**, further comprising:

injecting a solution from an earth surface, through the inner mandrel below the packer, and into a subsurface formation.

40. The method of claim **39**, wherein:

the solution is aqueous solution, an acidic solution, or a chemical treatment; and

the method further comprises circulating the aqueous solution, the acidic solution, or the chemical treatment to clean a near-wellbore region along the wellbore.

41. The method of claim **39**, wherein:

the solution is aqueous solution; and

the method further comprises continuing to inject the aqueous solution into the subsurface formation as part of an enhanced oil recovery operation.