(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau

(43) International Publication Date
25 March 2004 (25.03.2004)

PCT

(10) International Publication Number
WO 2004/024215 A2

(51) International Patent Classification[7]: A61M

(21) International Application Number:
PCT/US2003/029273

(22) International Filing Date:
16 September 2003 (16.09.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
10/247,781 16 September 2002 (16.09.2002) US

(71) Applicant: **FUTURA MEDICAL TECHNOLOGIES, INC.** [US/US]; 380 Stevens Avenue, Suite 212, Solana Beach, CA 92072 (US).

(72) Inventors: **MONTALVO, Rudy**; 4635 Gershwin Place, Woodland Hills, CA 91364 (US). **FEITH, Raymond, P.**; 14731 Ranchview Terrace, Chino Hills, CA 91709 (US). **MCCONNELL-MONTALVO, Susan**; 4635 Gershwin Place, Woodland Hills, CA 91364 (US). **MARANO-FORD, April**; 2052 West 11th Street, Upland, CA 91786 (US).


(74) Agent: **MCCONAGHY, John, D.**; Fulbright & Jaworski L.L.P., 865 South Figueroa, Twenty-Ninth Floor, Los Angeles, CA 90017-2571 (US).

(81) Designated States *(national)*: AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States *(regional)*: ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),

[Continued on next page]

(54) Title: SYRINGE WITH RETRACTABLE NEEDLE ASSEMBLY



(57) Abstract: A hypodermic syringe employing a plunger (30) slidably disposed within a barrel (80). The plunger (30) has a mounting hole (50) extending through the seal end (34) thereof to receive a mandrel (56). The mandrel (56) has a flexible flange (64) to be releasably engaged with the plunger (30). A spring element (140) withdraws the mandrel (56) into a cavity (44) within the plunger (30) upon full extension of the plunger (30) within the barrel (80). The barrel (80) includes a hub retainer (86) at the forward end thereof and a needle hub (100) retained therein. The mandrel (56) includes barbed tines (66, 68) with surfaces having axes of the conical surfaces that are displaced from one another such that movement of the tines (66) toward one another also brings the axes closer. A catch (144) associated with the back end of the spring element (140) coupled with the mandrel (56) at the other end cooperates with shoulders on smooth surfaces within the cavities to retain tension within the spring element. The hub retainer (86) and the needle hub (100) cooperate to insure that the needle hub (100) is constrained to limited motion such that the mandrel (56) will fully engage the needle hub (100).

WO 2004/024215 A2

Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— *without international search report and to be republished upon receipt of that report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.