

Description

The present invention relates to an electrical connector and more particularly to an electrical connector of plug-and-socket type which permits the insertion of the male plug into the female socket with a reduced insertion force.

As is well known, electrical connectors of plug-and-socket type have been widely used. The male plug has pin terminals each having parallel opposite sides and converging slant surfaces whereas the female socket has contacts each having contact pieces and being adapted to accommodate the corresponding pin terminal, keeping the parallel opposite sides and converging slant surfaces of the pin terminal in resilient contact with the contact pieces of the contact.

Fig. 6 shows such a conventional electrical connector of plug-and-socket type. As shown, the tapering end of a pin terminal 1' has opposite slant surfaces 2' and 3' symmetrical with respect to the center axis C' of the pin terminal rod. Likewise, a pair of contact pieces are symmetrical with respect to the center axis C' of the contact. Fig. 5 shows how the insertion force (ordinate) varies with the insertion depth (abscissa).

As seen from this graph, as the pin terminal proceeds towards the final contact position with the tangential angle increasing, the insertion force increases until it has reached its peak value F_1 . This value is generally called "insertion force". When the parallel opposite sides of the pin terminal reach the contact pieces the insertion force is reduced. The tangential angle which the contact pieces then make with the pin terminal is at a maximum. The pin is trimmed exactly into a desired curved surface by removing stretched portions from the punched piece or by reshaping somewhat deformed portions of the punched piece. This work is difficult, and therefore pin terminals each having more or less different curvatures on its opposite sides are likely to result. Thus, the insertion force cannot reach its peak value on each side at a controlled time. Stated otherwise, the precise shaping of curved surfaces on the opposite sides of the pin terminal requires the corresponding precision in punching dies used, and in subsequent trimming work.

The present invention provides an electrical connector of low-insertion force type in which insertion force reaches its peak value earlier on one side of a pin terminal than on the other side, the tip end of the pin terminal having such a simple shape that the tip end can be easily formed into a desired shape which is exact enough to assure that the insertion force reaches its peak value on either side at controlled times.

The present invention also provides an electrical connector of low-insertion force type which permits of mass production of electrical connectors of exactly the same insertion force characteristics.

Thus, according to the invention, an electrical connector of low-insertion force comprises a male plug having at least one pin terminal and a female socket having at least one contact comprising a pair of symmetrical contact pieces, which are adapted to come into resilient contact with the opposite sides of the corresponding pin terminal. The slope of each of said pin terminal sides is reduced to zero, and then the insertion force levels off. This final constant value is indicated at F_0 .

As seen from Fig. 6, the tapering end of the pin terminal 1' has opposite slant surfaces 2', 3' formed symmetrically at a same angle θ_1, θ_2 with respect to the center line C' of the pin terminal 1'. This arrangement causes the insertion force to rise simultaneously on either side of the pin terminal, and therefore, the resultant insertion force is twice as strong as the insertion force on either side, as indicated in solid lines in Fig. 5.

US Patent 4,679,890 proposes an electrical connector which is so designed that the insertion force to be applied between one side of a pin terminal and one of the contact pieces of an associated contact reaches its peak value at a time different from when the insertion force to be applied between the other side of the pin terminal and the other contact piece reaches its peak value. This connector comprises a male plug having terminal pins and a female socket having contacts. Each terminal pin has curved surfaces of different curvatures on its opposite sides, and each contact has a pair of contact pieces arranged symmetrically with respect to the center axis of the contact. This arrangement prevents the simultaneous rise of the insertion forces on the opposite sides of the pin terminal and prevents the doubling of the resultant insertion force, attaining insertion of the pin terminal into the contact with a relatively low insertion force.

The US Patent electrical connector however, has problems to be solved. A pin terminal is punched out from a piece of metal sheet with the aid of upper and lower punching dies, each having a curved blade. The punched piece of metal is a terminal so designed that the insertion force to be applied between one side of the corresponding pin terminal and one of the contact pieces reaches its peak value at a time different from when the insertion force to be applied between the other side of the corresponding pin terminal and the other contact piece reaches its peak value.

The improvement according to the present invention is that each of said pin terminals has a tapered end ending with a flat nose, said tapered end comprising a first slant surface extending from one end of said flat nose to said one side of pin terminal and a second slant surface extending from the other end of said flat nose to said the other side of pin terminal, said first and second slant surfaces being inclined at a same angle with respect to the center axis of said pin terminal, and the center of equi-divisinal point of said flat

nose being positioned somewhat beyond the center axis of said pin terminal, thereby positioning said first and second slant surfaces asymmetrical with respect to the center axis of said pin terminal so as to put at different places, the intersections at which said first and second slant surfaces intersect with said one and the other sides of pin terminal, thus causing the insertion forces on said first and second slant surfaces to reach their peak values at different times.

According to one embodiment of the present invention said male plug has a single pin terminal. According to another embodiment of the present invention said male plug has a plurality of pin terminals.

When the pin terminal of the male plug is inserted between the opposite contact pieces of the female socket, the insertion force reaches its peak value on one side of the pin terminal earlier than on the other side, preventing simultaneous rise of the insertion forces on the opposite sides of the pin terminal to their peak values, hence permitting insertion of the pin terminal into the contact with a reduced insertion force.

Advantageously, the tip end of the pin terminal can be easily formed into a precise shape as required partly because the slant and consecutive sides of the pin terminal is straight rather than curved and partly because the slant surfaces are inclined at the same angle. This also, is advantageous to the shaping of punching dies into precise shape and precise dimensions. To give a pin terminal a precise shape as required, it suffices that the intersections at which the slant surfaces intersect with the parallel sides of the pin terminal, are precisely positioned.

One way of carrying out the present invention will now be described in detail with reference to drawings which show one specific embodiment. In the drawings:

FIG. 1 is a longitudinal section of the male plug and female socket of an electrical connector in accordance with the present invention;

FIG. 2 is a side view of a pin terminal as viewed from a position 90° apart from that which is viewed in Figure 1;

FIG. 3 is an enlarged side view of the pin terminal, showing the asymmetrical arrangement of opposite slant surfaces with respect to the center axis;

FIG. 4 is a graph showing how the insertion force varies with the insertion depth in the electrical connector of the present invention;

FIG. 5 is a graph showing how the insertion force varies with the insertion depth in a conventional electrical connector; and

FIG. 6 is an enlarged longitudinal section of the contact pieces of the connector showing the symmetrical arrangement of the contact pieces with respect to the center axis of the contact.

Referring to Figs. 1 to 4, a male plug 1 has pin terminals 2, and a female socket 3 has contacts 5 each comprising a pair of opposite resilient contact pieces

4 and 5. In this particular embodiment two pin terminals are used. A single pin terminal or a plurality of terminals are used. In these drawings less important parts are omitted only for the sake of the simplicity of the drawings.

Fig. 2 is a side view of a pin terminal as viewed from a position 90° apart from that which is viewed in Fig. 1.

Each pin terminal 2 has a tapered end A ending with a flat nose B. The tapered end A comprises a first slant surface 6 extending from one end D of the flat nose B to one side 8 of the pin terminal 2 and a second slant surface 7 extending from the other end E of the flat nose B to the other side 10 of the pin terminal 2. The first and second slant surfaces 6, 7 are inclined at a same angle θ_3 , θ_4 with respect to the center axis C of the pin terminal 2, and the center or equidivisional point of the flat nose B is positioned somewhat beyond the center axis C of the pin terminal 2, thereby positioning the first and second slant surfaces asymmetrical with the center axis C of the pin terminal 2 so as to put at different places, the intersections 9 and 11 at which the first and second slant surfaces 6 and 7 intersect with one and the other sides 8 and 10 of the pin terminal 2 respectively, thus causing the insertion forces on the first and second slant surfaces to reach their peak values at different controlled times.

Fig. 3 shows an enlarged side view of the tapering end of the pin terminal 2.

When the pin terminal 2 is inserted into a pair of contact pieces 4 and 5 of the contact, first, the insertion force reaches its peak value on the side on which the slant surface 6 of the pin terminal 2 comes to contact with the contact piece 5 of the contact, as seen from the curve S_1 (broken lines) in Fig. 4.

In a certain length of time the insertion force reaches its peak value on the side on which the slant surface 7 of the pin terminal 2 comes to contact with the contact piece 4 of the contact, as seen from the curve S_2 (broken lines) in Fig. 4. The resultant insertion force S_3 is indicated by the curve S , solid lines. As seen from this curve, the peak value F , of the resultant insertion force curve S_3 is far less than the double of the peak value of the insertion force on each side of the pin terminal 2. Thus, the pin terminal 2 can be inserted into the contact with a reduced insertion force.

Claims

1. An electrical connector of low insertion force comprising a male plug (1) having at least one pin terminal (2) and a female socket (3) having at least one contact comprising a pair of symmetrical contact pieces (4 and 5) which are adapted to come into resilient contact with the opposite sides

nose being positioned somewhat beyond the center axis of said pin terminal, thereby positioning said first and second slant surfaces asymmetrical with respect to the center axis of said pin terminal so as to put at different places, the intersections at which said first and second slant surfaces intersect with said one and the other sides of pin terminal, thus causing the insertion forces on said first and second slant surfaces to reach their peak values at different times.

According to one embodiment of the present invention said male plug has a single pin terminal. According to another embodiment of the present invention said male plug has a plurality of pin terminals.

When the pin terminal of the male plug is inserted between the opposite contact pieces of the female socket, the insertion force reaches its peak value on one side of the pin terminal earlier than on the other side, preventing simultaneous rise of the insertion forces on the opposite sides of the pin terminal to their peak values, hence permitting insertion of the pin terminal into the contact with a reduced insertion force.

Advantageously, the tip end of the pin terminal can be easily formed into a precise shape as required partly because the slant and consecutive sides of the pin terminal is straight rather than curved and partly because the slant surfaces are inclined at the same angle. This also, is advantageous to the shaping of punching dies into precise shape and precise dimensions. To give a pin terminal a precise shape as required, it suffices that the intersections at which the slant surfaces intersect with the parallel sides of the pin terminal, are precisely positioned.

One way of carrying out the present invention will now be described in detail with reference to drawings which show one specific embodiment. In the drawings:

FIG. 1 is a longitudinal section of the male plug and female socket of an electrical connector in accordance with the present invention;

FIG. 2 is a side view of a pin terminal as viewed from a position 90° apart from that which is viewed in Figure 1;

FIG. 3 is an enlarged side view of the pin terminal, showing the asymmetrical arrangement of opposite slant surfaces with respect to the center axis;

FIG. 4 is a graph showing how the insertion force varies with the insertion depth in the electrical connector of the present invention;

FIG. 5 is a graph showing how the insertion force varies with the insertion depth in a conventional electrical connector; and

FIG. 6 is an enlarged longitudinal section of the contact pieces of the connector showing the symmetrical arrangement of the contact pieces with respect to the center axis of the contact.

Referring to Figs. 1 to 4, a male plug 1 has pin terminals 2, and a female socket 3 has contacts 5 each comprising a pair of opposite resilient contact pieces

4 and 5. In this particular embodiment two pin terminals are used. A single pin terminal or a plurality of terminals are used. In these drawings less important parts are omitted only for the sake of the simplicity of the drawings.

Fig. 2 is a side view of a pin terminal as viewed from a position 90° apart from that which is viewed in Fig. 1.

Each pin terminal 2 has a tapered end A ending with a flat nose B. The tapered end A comprises a first slant surface 6 extending from one end D of the flat nose B to one side 8 of the pin terminal 2 and a second slant surface 7 extending from the other end E of the flat nose B to the other side 10 of the pin terminal 2. The first and second slant surfaces 6, 7 are inclined at a same angle θ_3, θ_4 with respect to the center axis C of the pin terminal 2, and the center or equidivisional point of the flat nose B is positioned somewhat beyond the center axis C of the pin terminal 2, thereby positioning the first and second slant surfaces asymmetrical with the center axis C of the pin terminal 2 so as to put at different places, the intersections 9 and 11 at which the first and second slant surfaces 6 and 7 intersect with one and the other sides 8 and 10 of the pin terminal 2 respectively, thus causing the insertion forces on the first and second slant surfaces to reach their peak values at different controlled times.

Fig. 3 shows an enlarged side view of the tapering end of the pin terminal 2.

When the pin terminal 2 is inserted into a pair of contact pieces 4 and 5 of the contact, first, the insertion force reaches its peak value on the side on which the slant surface 6 of the pin terminal 2 comes to contact with the contact piece 5 of the contact, as seen from the curve S_1 (broken lines) in Fig. 4.

In a certain length of time the insertion force reaches its peak value on the side on which the slant surface 7 of the pin terminal 2 comes to contact with the contact piece 4 of the contact, as seen from the curve S_2 (broken lines) in Fig. 4. The resultant insertion force S_3 is indicated by the curve S , solid lines. As seen from this curve, the peak value F, of the resultant insertion force curve S_3 is far less than the double of the peak value of the insertion force on each side of the pin terminal 2. Thus, the pin terminal 2 can be inserted into the contact with a reduced insertion force.

Claims

1. An electrical connector of low insertion force comprising a male plug (1) having at least one pin terminal (2) and a female socket (3) having at least one contact comprising a pair of symmetrical contact pieces (4 and 5) which are adapted to come into resilient contact with the opposite sides



(8, 10) of the corresponding pin terminal (2), each of said pin terminals being so designed that the insertion force to be applied between one side (8) of the corresponding pin terminal (2) and one of the contact pieces (5) reaches its peak value at a time different from when the insertion force to be applied between the other side (10) of the corresponding pin terminal (2) and the other contact piece (4) reaches its peak value, characterized in that each of said pin terminals has a tapered end A ending with a flat nose B, said tapered end A comprising a first slant surface (6) extending from one end D of said flat nose B to said one side (8) of pin terminal (2) and a second slant surface (7) extending from the other end E of said flat nose B to said the other side (10) of pin terminal (2), said first and second slant surfaces (6, 7) being inclined at a same angle with respect to the center axis C of said pin terminal (2), and the center of equi-divisional point of said flat nose B being positioned somewhat beyond the center axis C of said pin terminal (2), thereby positioning said first and second slant surfaces asymmetrical with respect to the center axis C of said pin terminal (2) so as to put at different places, the intersections at which said first and second slant surface (6 and 7) intersect with said one and the other sides (8 and 10) of pin terminal (2), thus causing the insertion forces on said first and second slant surfaces to reach their peak values at different times.

2. An electrical connector of low insertion force according to claim 1 wherein said male plug (1) has a single pin terminal (2).
3. An electrical connector of low insertion force according to claim 1 wherein said male plug (1) has a plurality of pin terminals (2).

Patentansprüche

1. Elektrischer Verbinder von geringer Einsteckkraft, bestehend aus einem Stecker (1) mit zumindest einem Steckstift (2) und einer Steckdose (3) mit zumindest einem Kontakt mit einem Paar symmetrischer Kontaktstücke (4 und 5), die so eingerichtet sind, daß sie mit den gegenüberliegenden Seiten (8, 10) des entsprechenden Steckstiftes (2) in federnden Kontakt kommen, wobei jeder der Steckstifte so ausgelegt ist, daß die zwischen einer Seite (8) des entsprechenden Steckstiftes (2) und einem der Kontaktstücke (5) aufzubringende Einsteckkraft ihren Spitzenwert zu einem Zeitpunkt erreicht, der unterschiedlich ist zu dem, an dem die zwischen der anderen Seite (10) des entsprechenden Steckstiftes (2) und dem anderen Kontaktstück (4) aufzubringende

Einsteckkraft ihren Spitzenwert erreicht, dadurch gekennzeichnet, daß jeder der Steckstifte ein in einer flachen Nase B auslaufendes verjüngtes Ende A aufweist, das verjüngte Ende A eine sich von einem Ende D der flachen Nase B zu der einen Seite (8) des Steckstiftes (2) erstreckende erste Schrägfläche (6) und eine sich von dem anderen Ende E der flachen Nase B zu der anderen Seite (10) des Steckstiftes (2) erstreckende zweite Schrägfläche (7) umfaßt, die erste und die zweite Schrägfläche (6, 7) unter dem gleichen Winkel in bezug auf die Mittelachse C des Steckstiftes (2) geneigt sind und die Mitte oder der Gleichteilungspunkt der flachen Nase B etwas über die Mittelachse C des Steckstiftes (2) hinaus positioniert ist, wodurch die erste und die zweite Schrägfläche asymmetrisch in bezug auf die Mittelachse C des Steckstiftes (2) positioniert sind, so daß die Schnittpunkte, an denen sich die erste und die zweite Schrägfläche (6 und 7) mit der einen und der anderen Seite (8 und 10) des Steckstiftes (2) schneiden, an unterschiedliche Stellen gelegt sind, was bewirkt, daß die Einsteckkräfte an der ersten und der zweiten Schrägfläche ihre Spitzenwerte zu unterschiedlichen Zeitpunkten erreichen.

2. Elektrischer Verbinder von geringer Einsteckkraft nach Anspruch 1, bei dem der Stecker (1) einen einzigen Steckstift (2) besitzt.
3. Elektrischer Verbinder von geringer Einsteckkraft nach Anspruch 1, bei dem der Stecker (1) eine Mehrzahl von Steckstiften (2) besitzt.

Revendications

1. Connecteur électrique à faible force d'insertion, constitué d'une fiche (1) comportant au moins une broche (2) et une prise femelle (3) comportant au moins un contact constitué d'une paire d'éléments de contact symétriques (4, 5) qui sont conçus pour venir en contact élastique avec les côtés opposés (8, 10) de la broche correspondante (2), chaque broche étant conçue de façon telle que la force d'insertion à appliquer entre un côté (8) de la broche correspondante (2) et l'un des éléments de contact (5) atteigne sa valeur de pic à un moment différent de celui où l'autre élément de contact (4), lorsque la force d'insertion est appliquée sur l'autre côté de la broche (2) atteint sa valeur de pic, caractérisé en ce que chacune des broches comporte une extrémité tronconique (A) se terminant par un nez plat (B), ladite extrémité tronconique (A) étant constituée d'une première surface inclinée (6) s'étendant d'une extrémité (D) dudit nez plat (B) vers l'autre côté (8) de la



- broche (2), et une seconde surface inclinée (7) s'étendant de l'autre extrémité (E) dudit nez plat (B) vers l'autre côté (10) de la broche (2), lesdites première et seconde surfaces inclinées (6,7) étant inclinées d'un même angle, par rapport à l'axe central (C) de la broche (2), et le centre du point d'équidivision du nez plat (B) étant positionné sensiblement au-delà de l'axe central (C) de ladite broche (2), positionnant ainsi lesdites première et seconde surfaces inclinées de façon dissymétrique par rapport à l'axe central (C) de la broche, de façon à disposer en des endroits différents les contacts des première et seconde surfaces inclinées (6,7) avec l'un et l'autre des côtés (8,10) de la broche (2), amenant ainsi les forces d'insertion sur lesdites première et seconde surfaces inclinées à atteindre leur valeur de pic à des moments différents.
- 5
- 10
- 15
- 20
- 25
- 30
- 35
- 40
- 45
- 50
- 55
- 5

