

METHOD FOR RETRIEVING A TUMOR CONTOUR OF AN IMAGE PROCESSING SYSTEM

BACKGROUND OF THE INVENTION

1. Field of the Invention

5 The present invention relates to a method for retrieving a tumor contour of an image processing system and, more particularly, to a method for retrieving a tumor contour of an image processing system that includes a memory storing a grayscale image and a processor.

2. Description of Related Art

10 Owing to the non-invasive image-information technique, ultrasonography becomes one of the most acceptable medical tools without serious side effect, and an important radiography for retrieving information from patients applied in clinical diagnosis and medical application.

Moreover, since advanced ultrasonography can provide real-time medical
15 imaging with high resolution, it is widely applied in medical examination and diagnosis of tumoral changes.

For example, by way of analyzing the ultrasonographic image in detail, the properties of the tumor can be easily identified by doctors. Thus, ultrasonography can advantageously reduce frequency of tumoral biopsy.
20 In ultrasonography, an imaging contour of a tumor is a principal index for the diagnosis of benignancy and malignancy. If the imaging contour of a tumor obtained from ultrasonography can approximate the real appearance of the tumor, it is beneficial to promote the accuracy of the examination of tumors at the initial stage. In clinical researches, professional doctors often

provide the diagnosis of a tumor through description or checklist after the ultrasonographic images are output and checked. However, referring to the same image of the tumor, diagnostic variation between different diagnoses of different doctors still occur.

5 Therefore, as the technique of computer-aided diagnosis and reading-out of tumor image develops, the identification of tumors assisted by a computer is gradually accomplished in clinical application. Basically, the prerequisite of the examination or identification of tumors is to determine the site of an imaged tumor, i.e. to determine the contour of the
10 imaged tumor. Conventionally, the researchers delineate an imaged tumor to determine the contour of the tumor. However, the definition of the image, the recognition of the researchers for the boundary of the tumor, and the operational condition of the researchers all incur the variation of the determination of the contour of the tumor, and then undesirably affect the
15 examination or identification of the tumor.

One of the advantages for diagnosing the contour of a tumor aided by a computer is that most of the people who know the location of the imaged tumor can depict similar or even the same contour of the tumor. In other words, people are not required to carefully delineate a tumor but only
20 approximately depict the boundary of the tumor with naked eyes. Then, the computer can provide the real boundary of the tumor by algorithm. Hence, the computer-aided diagnosis is invariably highlighted in the research of medical image processing. For example, in 1987, Michael Kass et al. set forth Snake algorithm, in which an initial boundary was determined first

and then an optimal boundary was found out sequentially by algorithm. Therefore, Snake algorithm now becomes one of the well-known methods in medical image processing.

Snake algorithm, also called “active contour method”, currently
5 becomes the most widely used algorithm in the research of medical image processing. In Snake algorithm, the principal step is to find out delineation of a region with the minimal constraint of the outside region to the delineated region and the minimal influence of the inside image to the delineated region. Owing to the minimal constraint and influence, the
10 delineated region appears as movement of a snake, and performs expansion and contraction.

Snake algorithm can automatically search data in neighboring regions, locally consider data in each region, and retrieve data according to a feature by surrounding a region based on spatial consecution. The
15 advantage illustrated above is the reason why Snake algorithm is called an “active contour method”. Snake algorithm is suitable to retrieve data from a line segment, a boundary, and a contour, to dynamically track, and to three-dimensionally comparison. As long as the initially delineated region is near to the contour of the interesting image, Snake algorithm can propose
20 a final contour by recursive calculation. As shown in FIG. 1, the contour of the airplane is retrieved by the conventional Snake algorithm.

When Snake algorithm is applied in an image having a clear boundary, especially in an image having high contrast difference between outside and inside neighborhoods of the boundary, an acceptable result can

be obtained. However, the tumor image often has an indistinct boundary or hypoechoicity, or even has no hypoechoicity such that the applied Snake algorithm needs to be modified to depict the contour clearly. Generally, Snake algorithm is applied to investigate the consecution, curvature, and
5 local gradient energy of each point in the regions ($n \times n$ mask) surrounding an predetermined point. However, if the regions surrounding the predetermined point are indistinct, the search result of the regions surrounding the predetermined point is poor in Snake algorithm. If most regions surrounding the main predetermined points are indistinct, Snake
10 algorithm cannot propose acceptable results. On the other hand, if calculating regions surrounding the predetermined point is expanded, Snake algorithm consumes long calculating time and still provides unsatisfactory results for large-scaled indistinct images. Furthermore, the calculation of Snake algorithm requires a depicted contour of an initial
15 region given by the researchers. Once the initial region is improperly determined and the image is indistinct, Snake algorithm cannot output an outstanding result in the ultrasonographic imaging of a tumor.

In conclusion, the conventional delineation of a tumor needs to be carefully made by hands of medical professionals. By contrast, Snake
20 algorithm requires an initial approximate contour of a clear predetermined region instead of delineation by hand, and then a subsequent calculation performs the approaching of the real contour in Snake algorithm. Nevertheless, if the input initial contour depicted by hand is required to very close to the actual contour of the predetermined region, it is

time-consuming delineation is inevitable. On the other hand, if the input initial contour is quite different from the contour of the predetermined region, the calculation of the approaching is time-consuming since Snake algorithm falls into no boundary calculation at the same time. Hence, Snake algorithm is not suitable to be applied in an image which is not clear.

SUMMARY OF THE INVENTION

Embodiments of the present invention seek to provide a method for retrieving a tumor contour of an image processing system that includes a memory storing a grayscale image and a processor.

A method of retrieving a tumor contour implemented in an image processing system that includes a memory storing a grayscale image, a display screen, an input device, and a processor, according to an embodiment of the present invention comprises: receiving an input tumor contour of the grayscale image; defining a tumor contour annular region and a plurality of reference segments of the grayscale image, wherein the input tumor contour is in the tumor contour annular region, and each of the plurality of reference segments is across the tumor contour annular region and includes a plurality of measured points; retrieving a tumor contour suggestion point on each of the plurality of reference segments; and linking all the tumor contour suggestion points on all of the reference segments, for forming the tumor contour.

A method of retrieving a tumor contour implemented in an image processing system that includes a memory storing a grayscale image, a display screen, an input device and a processor, according to another embodiment of the present invention comprises: receiving an input tumor contour of the grayscale image; defining a tumor

contour annular region and a plurality of reference segments of the grayscale image, wherein the input tumor contour is in the tumor contour annular region, and each of the plurality of reference segments is across the tumor contour annular region and includes a plurality of measured points;

- 5 retrieving a modulated tumor contour suggestion point on each of the plurality of reference segments; and linking all the modulated tumor contour suggestion points on all of the reference segments, for forming the modulated tumor contour;

- wherein the modulated tumor contour suggestion point on each of
- 10 the plurality of reference segments is obtained by the following steps: normalizing the value of all the measured points on the reference segment retrieved by a moving variance retrieving method, the value of all the measured points on the reference segment retrieved by a contrast retrieving method, the value of all the measured points on the reference segment
- 15 retrieved by a distance retrieving method, the value of all the measured points on the reference segment retrieved by a gradient EWMA difference retrieving method, and the value of all the measured points on the reference segment retrieved by an angle retrieving method into value between 0 and 1; determining modulating criteria for each of the aforementioned retrieving
- 20 methods; calculating a weighting parameter for each the measured points on the reference segment, by multiplying product corresponding to each of the aforementioned retrieving methods together, wherein each of the products is obtained by multiple the normalized value of the measured point for the number of times equal to the modulating criteria of the corresponding

retrieving method, respectively; and retrieving the coordinate of the tumor contour suggestion point on the reference segment by calculating the average coordinate, from the sum of the product obtained by multiplying the coordinate of each of the measured points on the reference segment with
5 the corresponding weighting parameter, respectively;

wherein in the moving variance retrieving method, each of the plurality of reference segments includes a plurality of local segments and each of the plurality of local segments includes a plurality of moving horizons; each of the plurality of local segments consists of one of the
10 plurality of measured points, at least one measured point before and at least one measured point after the one of the plurality of measured points, and each of the plurality of moving horizons consists of one of the plurality of measured points in the corresponding local segment and at least one measured point after the one of the plurality of measured points; and the
15 value of all the measured points on the reference segment are retrieved by the moving variance retrieving method comprising the steps of: calculating a gradient variance of the grayscale image in the plurality of local segments and an average gradient variance of the grayscale image in the plurality of moving horizons; calculating the ratio of the gradient variance of the
20 grayscale image in the plurality of local segments to the average gradient variance of the grayscale image in the plurality of moving horizons; and retrieving the measured point corresponding to the maximum ratio as the tumor contour suggestion point;

wherein in the contrast retrieving method, a center of gravity of the

input tumor contour is retrieved and a plurality of contrast reference segments is defined, each of the plurality of contrast reference segments extends from the center of the gravity to of the corresponding reference segments, respectively; and the value of all the measured points on the
5 reference segment are retrieved by the contrast retrieving method comprising the steps of: calculating gradients of the grayscale image in the plurality of reference segments and an average gradient of the grayscale image in the plurality of contrast reference segments; calculating the differences between the gradients of the grayscale image in the plurality of
10 reference segments and an average gradient of the grayscale image in the plurality of contrast reference segments; and retrieving the measured point corresponding to the maximum difference as the tumor contour suggestion point;

wherein in the distance retrieving method, the value of all the
15 measured points on the reference segment are retrieved in sequence by the distance retrieving method comprising the steps of: when there are no tumor contour suggestion points before, taking one of the plurality of measured points on the first reference segment as a first point, or when there is one tumor contour suggestion point before, taking a last tumor contour
20 suggestion point on one of the plurality of reference segments as the first point; taking one of the plurality of measured points on the next reference segment as a second point; and retrieving the measured point on the next reference segment, having the minimum distance between the first point and the second point as the tumor contour suggestion point on the next

reference point;

wherein in the gradient EWMA difference retrieving method, the value of all the measured points on the reference segment are retrieved in sequence by the gradient EWMA difference retrieving method comprising the steps of: when there are no tumor contour suggestion points before, taking one of plurality of measured points on the first reference segment as a reference list; or when there is one tumor contour suggestion point before, taking all of the pervious tumor contour suggestion points as the reference list; providing an EWMA weighting formula; determining the weighting factor of the EWMA weighting formula and receiving the EWMA value of the reference list by the gradients of grayscale image of each of the measured points or the tumor contour suggestion points in the reference list; using the EWMA value of the reference list and the gradients of grayscale image of each of the plurality of measured points on the next reference segment as the input variables of the EWMA weighting formula; defining the output of the EWMA weighting formula as the EWMA value of each of the plurality of measured points on the next reference segment; and taking the one of plurality of measured points on the next reference segment, having the minimum difference between the gradient of grayscale image thereof and the EWMA value thereof, as the tumor contour suggestion point on the next reference segment;

wherein in the angle retrieving method, the value of all the measured points on the reference segment are retrieved in sequence by the angle retrieving method comprising the steps of: when there are no tumor

contour suggestion point before a last tumor contour suggestion point, defining one of the plurality of measured points on the first reference segment as a first point, and one of the plurality of measured points on the second reference segment as a second point; or when there is one tumor
5 contour suggestion point before the last tumor contour suggestion point, defining the tumor contour suggestion point before the last tumor contour suggestion point as the first point, and defining the last tumor contour suggestion point as the second point; defining a vector going from the first point to the second point as a first vector, and vectors going from the second
10 point to each of the plurality of measured points on a next reference segment as a plurality of second vectors; calculating the cosine values of the angles included by the first vector and the plurality of second vectors, respectively; and taking the one of plurality of measured points on the second next reference segment, being the end point of the second vector
15 corresponding to the angle having maximum cosine value, as the tumor contour suggestion point on the second next reference segment.

Accordingly, by applying the method for retrieving a tumor contour of an image processing system of the present invention, a doctor can rapidly and accurately identify the contour of a tumor in a grayscale image. Besides,
20 since the tumor contour can be formed on the grayscale image based on the calculation of one of the five kinds of the retrieving method, i.e. the moving variance retrieving method, the contrast retrieving method, the distance retrieving method, the gradient EWMA difference retrieving method, and the angle retrieving method, the time spent in calculation of the tumor

contour of the image processing system can be minimized, and the similarity of the tumor contour compared with the actual contour of the tumor is maximized.

In a method of retrieving a tumor contour implemented in an image processing system that includes a memory storing a grayscale image, a display screen, an input device and a processor, according to another embodiment of the present invention, each of the plurality of reference segments includes a plurality of local segments and each of the plurality of local segments includes a plurality of moving horizons, wherein each of the plurality of local segments consists of one of the plurality of measured points, at least one measured point before and at least one measured point after the one of the plurality of measured points. Besides, each of the plurality of moving horizons consists of one of the plurality of measured points in the corresponding local segment and at least one measured point after the one of the plurality of measured points.

Moreover, the tumor contour suggestion point can be retrieved by a moving variance retrieving method comprising the steps of: calculating a gradient variance of the grayscale image in the plurality of local segments and an average gradient variance of the grayscale image in the plurality of moving horizons; calculating the ratio of the gradient variance of the grayscale image in the plurality of local segments to the average gradient variance of the grayscale image in the plurality of moving horizons; and retrieving the measured point corresponding to the maximum ratio as the tumor contour suggestion point.

In a method of retrieving a tumor contour implemented in an image processing

system that includes a memory storing a grayscale image, a display screen, an input device and a processor, according to an embodiment of the present invention, a center of gravity of the input tumor contour is retrieved and a plurality of contrast reference segments is defined. Besides, each of the plurality of contrast reference segments extends from the center of the gravity to of the corresponding reference segments, respectively.

Moreover, the tumor contour suggestion point can be retrieved by a contrast retrieving method comprising the steps of: calculating gradients of the grayscale image in the plurality of reference segments and an average gradient of the grayscale image in the plurality of contrast reference segments; calculating the differences between the gradients of the grayscale image in the plurality of reference segments and an average gradient of the grayscale image in the plurality of contrast reference segments; and retrieving the measured point corresponding to the maximum difference as the tumor contour suggestion point.

In a method of retrieving a tumor contour implemented in an image processing system that includes a memory storing a grayscale image, a display screen, an input device and a processor, according to an embodiment of the present invention, the tumor contour suggestion point can be retrieved in sequence by a distance retrieving method comprising the steps of: when there are no tumor contour suggestion points before, taking one of the plurality of measured points on the first reference segment as a first point, or when there is one tumor contour suggestion point before, taking a last tumor contour suggestion point on one of the plurality of reference segments as the first point; taking

one of the plurality of measured points on the next reference segment as a second point; and retrieving the measured point on the next reference segment, having the minimum distance between the first point and the second point as the tumor contour suggestion point on the next reference point.

In a method of retrieving a tumor contour implemented in an image processing system that includes a memory storing a grayscale image, a display screen, an input device and a processor, according to another embodiment of the present invention, the tumor contour suggestion point can be retrieved in sequence by a gradient EWMA difference retrieving method comprising the steps of: when there are no tumor contour suggestion points before, taking one of plurality of measured points on the first reference segment as a reference list; or when there is one tumor contour suggestion point before, taking all of the previous tumor contour suggestion points as the reference list; providing an EWMA weighting formula; determining the weighting factor of the EWMA weighting formula and receiving the EWMA value of the reference list by the gradients of grayscale image of each of the measured points or the tumor contour suggestion points in the reference list; using the EWMA value of the reference list and the gradients of grayscale image of each of the plurality of measured points on the next reference segment as the input variables of the EWMA weighting formula; defining the output of the EWMA weighting formula as the EWMA value of each of the plurality of measured points on the next reference segment; and taking the one of plurality of measured points on the next reference segment, having the

minimum difference between the gradient of grayscale image thereof and the EWMA value thereof, as the tumor contour suggestion point on the next reference segment.

In a method of retrieving a tumor contour implemented in an image processing system that includes a memory storing a grayscale image, a display screen, an input device and a processor, according to an embodiment of the present invention, the tumor contour suggestion point can be retrieved in sequence by an angle retrieving method comprising the steps of: when there are no tumor contour suggestion point before a last tumor contour suggestion point, defining one of the plurality of measured points on the first reference segment as a first point, and one of the plurality of measured points on the second reference segment as a second point; or when there is one tumor contour suggestion point before the last tumor contour suggestion point, defining the tumor contour suggestion point before the last tumor contour suggestion point as the first point, and defining the last tumor contour suggestion point as the second point; defining a vector going from the first point to the second point as a first vector, and vectors going from the second point to each of the plurality of measured points on a next reference segment as a plurality of second vectors; calculating the cosine values of the angles included by the first vector and the plurality of second vectors, respectively; and taking the one of plurality of measured points on the second next reference segment, being the end point of the second vector corresponding to the angle having maximum cosine value, as the tumor contour suggestion point on the second next reference segment.

Other embodiments, advantages, and novel features of the invention will become more apparent from the following detailed description when taken in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is combination of schematic views of the process for retrieving contour of airplanes according to Snake algorithm.

FIG. 2 is a system configuration diagram according to a preferred example of the present invention.

FIG. 3 is a schematic diagram for showing a tumor contour retrieving method according to a preferred example of the present invention.

FIG. 4 is a flowchart of the method for retrieving a tumor contour of an image processing system according to the first embodiment of the present invention.

FIG. 5 is a flowchart displaying the moving variance retrieving method for retrieving the tumor contour suggestion point.

FIG. 6 is a schematic view for showing the local segments and the moving horizons according to Example 1 of the present invention.

FIG. 7 is a line chart for showing the gradients of the grayscale images and corresponding moving variances of all points on the reference segment according to Example 1 of the present invention.

FIG. 8 is a gradient cross-sectional view of grayscale images of the tumor from the gravity center of the tumor to the outer crosspoint on the reference segment.

FIG. 9 is a flowchart displaying the contrast retrieving method for retrieving the tumor contour suggestion point.

FIG. 10 is a flowchart displaying the distance retrieving method for retrieving the tumor contour suggestion point.

5 FIG. 11 is a flowchart displaying the gradient EWMA difference retrieving method for retrieving the tumor contour suggestion point.

FIG. 12 is a flowchart displaying the angle retrieving method for retrieving the tumor contour suggestion point.

FIG. 13 is a flowchart of the method for retrieving a tumor contour
10 of an image processing system according to the second embodiment of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Please refer to FIGs. 2 and 3. FIG. 2 shows a system configuration diagram for illustrating a method for retrieving a tumor contour for an
15 image processing system according to a preferred example of the present invention. FIG. 3 is a schematic diagram for showing a method for retrieving a tumor contour for an image processing system according to a preferred example of the present invention.

As shown in FIG. 2, the image processing system 1 includes a
20 memory 11, a processor 12, a display screen 13 and an input device 14. The memory 11 can store an unprocessed image 111 and a predetermined line segment 112. Herein, the unprocessed image 111 means an ultrasound image without being processed by the method for retrieving a tumor contour according to the present invention, and can be input through the

input device 14. Furthermore, FIG. 3 shows a tumor region 20. The processed image can be output through the display screen 13.

Please refer to FIG. 4, which is a flowchart of the method for retrieving a tumor contour of an image processing system according to the first embodiment of the present invention. The method for retrieving a tumor contour for an image processing system that includes a memory storing a grayscale image and a processor according to the first embodiment of the present invention comprises:

- Step SA: receiving an input tumor contour of the grayscale image;
- 10 Step SB: defining a tumor contour annular region and a plurality of reference segments of the grayscale image, wherein the input tumor contour is in the tumor contour annular region, and each of the plurality of reference segments is across the tumor contour annular region and includes a plurality of measured points;
- 15 Step SC: retrieving a tumor contour suggestion point on each of the plurality of reference segments; and

Step SD: linking all the tumor contour suggestion points on all of the reference segments, for forming the tumor contour.

First, in Step SA, an input tumor contour 2 consisting of plural input contour points 21 is input on an unprocessed image 111. A user or a doctor can input the input tumor contour 2 by roughly rather than accurately hand-drawing the tumor contour. Herein, the input tumor contour 2 represented by LI_i consists of input contour points 21, in which the number of the input contour points 21 is represented by n_i ($i = 1, 2, \dots, n$; i, n

$\in N$). In addition, the j th input contour point 21 of the i th input tumor contour 2 is represented by $PI_{ij} = (X_{PI_{ij}}, Y_{PI_{ij}})$ ($LI_i = \{PI_{i1}, PI_{i2}, \dots, PI_{ij}\}, j = 1, 2, \dots, n_i, j \in N$).

Subsequently, in Step SB, both a tumor contour annular region and a plurality of reference segments of the grayscale image are defined. Besides, the input tumor contour is in the tumor contour annular region, and each of the plurality of reference segments is across the tumor contour annular region and includes a plurality of measured points. For instance, a gravity center 3 of the input tumor contour 2 is retrieved. Herein, the gravity center 3 of the i th input tumor contour (i.e. the gravity center 3 of all PI_{ij}) is represented by B_i , as shown in the formula (1-1).

$$B_i = \left(\frac{\sum_{j=1}^{n_i} X_{PI_{ij}}}{n_i}, \frac{\sum_{j=1}^{n_i} Y_{PI_{ij}}}{n_i} \right) \dots (1-1)$$

Next, the gravity center 3 and each input contour point 21 are linked individually through an extended line, and thereby plural reference lines 4 are defined. Then, a reference segment 41 containing its corresponding input contour point 21 is retrieved from each of the plural reference lines 4 (Step SB). In detail, the reference segment 41 is determined from each of the reference lines 4 by defining the predetermined line segment 112 at the

directions towards and away from the gravity center 3 with respect to the input contour point 21 as a basis point. The predetermined line segment 112 determines the length of the reference segment 41 and directly affects the processing time and accuracy.

5 In other words, the input contour point 21 is taken as a basis point, and the predetermined line segment 112 is used as a radius being a specific physical distance from the input contour point 21. The predetermined line segment 112 is represented by r ($r \in \mathbb{N}$). $\overline{B_i P_{ij}}$ is a line that links the gravity center 3 and the j th input contour point 21 of the i th input tumor contour 2. The j th input contour point 21 is used as a center and then a circle with a specific radius (i.e. the predetermined line segment 112, r) can be formed. The circle and the line $\overline{B_i P_{ij}}$ cross at two points, an outer crosspoint $O_{ij} = (X_{O_{ij}}, Y_{O_{ij}})$ and an inner crosspoint $\Pi_{ij} = (X_{\Pi_{ij}}, Y_{\Pi_{ij}})$. The j th reference segment 41 corresponding to the j th input contour point 21 of the i th input tumor contour 2 is the line $\overline{O_{ij} \Pi_{ij}}$, containing the measured points 22 of which the number is a_{ij} . The j th reference line segment 42 is the line $\overline{B_i \Pi_{ij}}$. Herein, $a_{ij}, h_{ij} \in \mathbb{N}$ and $a_{ij} \leq 2r+1$.

Then, in Step SC, a tumor contour suggestion point 441 is retrieved from each reference segment 41.

At final, by linking all the tumor contour suggestion points on all of the reference segments, the tumor contour is thus formed (Step SD).

5

Example1

In this example, the step SC of the method for retrieving a tumor contour of an image processing system that includes a memory storing a grayscale image and a processor according to the first embodiment of the present invention, the tumor contour suggestion point on each of the plurality of reference segments can be retrieved by a moving variance retrieving method. As shown in FIG. 5, the moving variance retrieving method comprises the steps of:

calculating a gradient variance of the grayscale image in the plurality of local segments and an average gradient variance of the grayscale image in the plurality of moving horizons;

calculating the ratio of the gradient variance of the grayscale image in the plurality of local segments to the average gradient variance of the grayscale image in the plurality of moving horizons; and

retrieving the measured point corresponding to the maximum ratio as the tumor contour suggestion point.

Moreover, in the above-mentioned moving variance retrieving method, each of the plurality of reference segments includes a plurality of local segments and each of the plurality of local segments includes a

plurality of moving horizons, wherein each of the plurality of local segments consists of one of the plurality of measured points, at least one measured point before and at least one measured point after the one of the plurality of measured points. Besides, each of the plurality of moving horizons consists of one of the plurality of measured points in the corresponding local segment and at least one measured point after the one of the plurality of measured points.

In this example, moving variance is applied to observe the value variance of the entire region caused by the value variance around a partial segment of the entire region. Moving variance applied in the present invention is a primary index of features. Through moving variance applied in the first example, the tumor contour suggestion point can be directly obtained from the reference segment 41 by algorithm.

With reference to FIGs. 3 and 5, each reference segment 41 contains a plurality of measured points 22, a plurality of local segments and a plurality of moving horizons. In the present example, the plural measured points mean plural image pixel points. Each of the plural local segments consists of one of the plural measured points 22, the former one or more measured points 22, and the latter one or more measured points 22. Each of the plural moving horizons consists of one of the plural measured point 22 and the latter one or more measured points 22 in the corresponding plural local segments.

That is, in the case that the number of points in the former/latter segment with respect to AI_{ijk} on the reference segment 41 (i.e. $\overline{OI_{ij} \Pi_{ij}}$) is p ,

the segment containing $(2 \times p + 1)$ image pixel points is called a local segment. Since each point on the reference segment 41 has a local segment, the number of measured points on the reference segment 41 is equal to that of the local segments. Regarding moving horizons, in the case that the
5 number of AI_{ijk} in the local segment plus the latter points is q , since the local segment contains $(2 \times p + 1)$ image pixel points, there are $(2 \times p + 1 - (q - 1) = 2 \times p - q + 2)$ horizons. Herein, each horizon containing q image pixel points is called a moving horizon.

However, the method for retrieving a tumor contour suggestion
10 point 411 according to Example 1 of the present invention is carried out as follows. First, the gradient variances of the grayscale images in the plural local segments and the average gradient variance of the grayscale images in the plural moving horizons are respectively calculated. Then, the ratios of the gradient variances of the grayscale images in the plural local segments
15 to the average gradient variance of the grayscale images in the plural moving horizons are respectively calculated. Subsequently, the measured point 22 corresponding to the maximum ratio is retrieved as a tumor contour suggestion point 411.

In the case of the image pixel values in the k th local segment on the
20 reference segment 41 ($\overline{OI_{ij}II_{ij}}$) being $G_{ijk-p}, G_{ijk-p+1}, \dots, G_{ijk+p-1}, G_{ijk+p}$, the gradient variance of the grayscale image in the local segment is represented by RL_{ijk} ($RL_{ijk} = \text{varp}[G_{ijk-p}, G_{ijk+p}]$, $p \in \mathbb{N}$). Since the local segment containing the former and latter points with respect to AI_{ijk}

may be beyond the range of the reference segment 41 (i.e. $\overline{OI_{ij}II_{ij}}$), extended auxiliary points, before and after the original reference segment 41, should be formed so as to observe the gradient variance of the grayscale images of all points in the local segment. In detail, with reference to FIG. 6, there is a schematic view to show the local segments and the moving horizons according to Example 1 of the present invention. The squares with continuous lines mean measured points 22 on the reference segment 41, and the squares with dashed lines mean the extended auxiliary points. In addition, the red square frame is AI_{ijk} point, the red rectangular frame is a local segment corresponding to AI_{ijk} point, and the brackets are moving horizons. As shown in FIG. 6, in the case of $k = 2$, $p = 4$ and $q = 3$, the local segment corresponding to the second measured point on the reference segment contains $(2 \times 4 + 1 = 9)$ points, and $(4 - 3 + 2 = 7)$ moving horizons.

In the case of the image pixel values in the g th moving horizon on the local segment being $G_{ijk-p+g-1}, G_{ijk-p+g}, \dots, G_{ijk-p+g+q-1}, G_{ijk-p+g+q-2}$, the gradient variance of the grayscale image in the moving horizon is represented by $RM_{ijk g}$ ($RM_{ijk g} = \text{varp}[G_{ijk-p+g-1}, G_{ijk-p+g+q-2}]$). The average gradient variance of the grayscale images in the moving horizons is represented by $\overline{RM_{ijk}}$, as shown in the formula (1-2).

$$\overline{RM_{ijk}} = \frac{\sum_{g=1}^{2 \times p - q + 2} RM_{ijk g}}{2 \times p - q + 2} \dots\dots\dots(1-2)$$

Herein, $q, g \in \mathbb{N}$. In order to allow a local segment to have two or more moving horizons, $q \leq 2 \times p - 1$.

Moreover, the moving variance of AI_{ijk} on the measures line 41
 $(\overline{OI_{ij}II_{ij}})$ is defined as the ratio of RL_{ijk} (the gradient variance of the
 5 grayscale image in the local segment corresponding to AI_{ijk}) to $\overline{RM_{ijk}}$
 (the average gradient variance of the grayscale images in the moving
 horizons of the local segment), represented by MV_{ijk} , as shown in the
 formula (1-3).

$$MV_{ijk} = \frac{RL_{ijk}}{\overline{RM_{ijk}}} \dots\dots\dots(1-3)$$

10 Herein, the larger the value of MV_{ijk} is, the higher the possibility of
 the point being the tumor contour suggestion point is. If $q = 1$, the moving
 variance does not regard the moving horizon ($MV_{ijk} = RL_{ijk}$).

Hereafter, the application of moving variance in the present
 invention will be illustrated. Please refer to Table 1 and FIG. 7. Table 1
 15 shows the gradients of the grayscale images and moving variances of points
 on the reference segment according to Example 1 of the present invention,
 in which the parameters p and q are set as 5 and 2, respectively. In Table 1,
 the serial number k of each measured point 22 is shown in the first column,
 the gradient G_{ijk} of the grayscale image of each measured point 22 is shown
 20 in the second column, and MV_{ijk} of each measured point 22 is shown in the

third column. FIG. 7 is a line chart displaying the gradients of the grayscale images and corresponding moving variances of all points on the reference segment according to Example 1 of the present invention. Herein, the line I for the gradients of the grayscale images and the line II for the moving variances can indicate that various gradients of grayscale images produce various moving variances due to surrounding variance.

Meanwhile, with reference to FIG. 8, there is a gradient cross-sectional view of grayscale images of the tumor from the gravity center of the tumor to the outer crosspoint on the reference segment. Herein, the line a shows the gradients of the grayscale images, the line b shows the average gradient of the grayscale images of the reference segment 41, and the line c shows the average gradient of the grayscale images of the reference line segment 42. FIG. 8 indicates that the average gradient of the grayscale images of the reference segment 41 is smaller than that of the reference line segment 42 owing to low-echogenic ring. In FIG. 7, the three locations where the gradient variances of the grayscale images are larger on the reference segment 41 are circled. In the term of the moving variances, the 10th point according to the circle 1 is the largest, the 11th point is larger than the 8th point, and the 17th point is the smallest.

Additionally, regarding the gradient cross-sectional view of grayscale images of the tumor from the gravity center of the tumor to the outer crosspoint on the reference segment 41 (FIG. 8), it can be found that the values from the 7th point to the 20th point are shown in a concave line, which is lower than the average gradient of the grayscale images of the

reference line segment. This concave line corresponds to the low-echogenic ring of the ultrasound image. Moreover, although the gradient variance of the grayscale images in the circle 2 is large, the moving variance according to the circle 2 is lower than those according to the circles 1 and 3 due to the

5 gradients of the surrounding images. Based on moving variances, the best suggestion point on the reference segment is the 10th point than the 11th point, the 8th point and the 17th point.

k	1	2	3	4	5
G_{ijk}	77	79	78	79	94
MV_{ijk}	4.996216	5.431265	5.72553	4.359829	5.065877

k	6	7	8	9	10
G_{ijk}	93	93	88	78	64
MV_{ijk}	8.586214	11.91848	13.55545	12.59645	17.43012

k	11	12	13	14	15
G_{ijk}	50	52	56	65	62
MV_{ijk}	14.88913	10.87886	6.907269	4.268695	4.830066

k	16	17	18	19
G_{ijk}	60	65	67	69
MV_{ijk}	11.60418	13.1099	7.002381	6.10648

Table 1

10 Example 2

In this example, the step SC of the method for retrieving a tumor contour of an image processing system that includes a memory storing a grayscale image and a processor according to the first embodiment of the

present invention, the tumor contour suggestion point on each of the plurality of reference segments can be retrieved by a contrast retrieving method. As shown in FIG. 9, the contrast retrieving method comprises the steps of:

5 calculating gradients of the grayscale image in the plurality of reference segments and an average gradient of the grayscale image in the plurality of contrast reference segments;

 calculating the differences between the gradients of the grayscale image in the plurality of reference segments and an average gradient of the
10 grayscale image in the plurality of contrast reference segments; and

 retrieving the measured point corresponding to the maximum difference as the tumor contour suggestion point.

 Moreover, in the above-mentioned contrast retrieving method, a center of gravity of the input tumor contour is retrieved and a plurality of
15 contrast reference segments is defined. Besides, each of the plurality of contrast reference segments extends from the center of the gravity to of the corresponding reference segments, respectively.

 In this example of the present invention, the contrast principle is applied to assign the location of a tumor from an ultrasound image through
20 naked eyes. Based on the center of the tumor, the tumor boundary can be discriminated through the gradient variance of the grayscale images from the center of the tumor to the probable boundary and the region around the boundary, in addition to the low-echogenic ring in the ultrasound image caused by spongy inflammation due to compression and infiltration

between the tumor and tissues around the tumor. Thereby, the contrast principle refers to that the degree of visional difference between each point in a range and the desired region is observed. Contrast applied in the present invention is a primary index of features. Through the contrast method
5 applied in the second example of the present invention, the tumor contour suggestion point can be directly obtained from the reference segment 41 by algorithm.

With reference to FIGs. 3 and 9, each reference segment 41 contains a plurality of measured points 22, and each of the plural reference lines 4
10 contains a reference line segment 42. The reference line segment 42 is from the gravity center 3 to the end of the reference segment 41 closer to the gravity center 3. However, the method for retrieving the tumor contour suggestion point 411 according to Example 2 of the present invention is carried out as follows. First, the gradients of the grayscale images of the
15 plural measured points 22 and the average gradient of the grayscale images in the reference line segment 42 are respectively calculated. Next, the differences between the gradients of the grayscale images of the plural measured points 22 and the gradient average of the grayscale images in the reference line segment of the corresponding reference line 4 are
20 respectively calculated. Then, the measured point 22 corresponding to the maximum difference is retrieved as a tumor contour suggestion point 411.

Herein, the average gradient of the grayscale images in the reference line segment 42 ($\overline{B_i H_{ij}}$) is represented by $\overline{G_{ij}}$, as shown in the

formula (2-1).

$$\overline{G_{ijl}} = \frac{\sum_{l=1}^{h_{ij}} G_{ijl}}{h_{ij}} \quad (2-1)$$

In addition, the contrast of the point AI_{ijk} on the reference segment 41 ($OI_{ij}II_{ij}$) is defined as the difference between the gradient of the grayscale image of such point and the average gradient ($\overline{G_{ijl}}$) of the grayscale images on the reference line segment 42 ($\overline{B_l II_{ij}}$) corresponding to such point, represented by C_{ijk} ($C_{ijk} = |G_{ijk} - \overline{G_{ijl}}|$). The larger C_{ijk} is, the higher the possibility of the point being the tumor contour suggestion point 411 is.

Hereafter, the application of the contrast principle in the present invention will be explained through data. Please refer to Table 2. Table 2 shows the gradients of the grayscale images and contrast of points on the reference segment according to Example 2 of the present invention, in which the average gradient of the grayscale images in the reference line segment 42 is 77.4. In Table 2, the serial number k of each measured point 22 on the reference segment 41 ($OI_{ij}II_{ij}$) is shown in the first column, the gradient G_{ijk} of the grayscale image of each measured point 22 is shown in the second column, and C_{ijk} of each measured point 22 is shown in the third

column. The average gradient of the grayscale image s in the reference line

segment 42 ($\overline{B_t II_{ij}}$) in Table 2 is 77.4.

Accordingly, through Table 2, it can be known that the 11th point is the largest, the 12th point is larger than the 13th point and the 16th point is the smallest, in the term of contrast. Please refer to FIG. 7 together with Table 2. Although the 5th point in the circle 2 presents the largest gradient of the grayscale image and the gradient variance of the grayscale images in the circle 2 is large, the gradient of the grayscale image in the circle 2 is closer to the average gradient of the grayscale images in the reference line segment. Thereby, the contrast at the 5th point in the circle 2 is lower than those at the 11th point in the red circle 1 and the 16th point in the circle 3. Based on contrast, the best suggestion point on the reference segment 41 is the 11th point than the 12th point, the 13th point and the 16th point.

k	1	2	3	4	5
G_{ijk}	77	79	78	79	94
C_{ijk}	0.4	1.6	0.6	1.6	16.6

k	6	7	8	9	10
G_{ijk}	93	93	88	78	64
C_{ijk}	15.6	15.6	10.6	0.6	13.4

k	11	12	13	14	15
G_{ijk}	50	52	56	65	62
C_{ijk}	27.4	25.4	21.4	12.4	15.4

k	16	17	18	19
G_{ijk}	60	65	67	69
C_{ijk}	17.4	12.4	10.4	8.4

Table 2

Example 3

In this example, the step SC of the method for retrieving a tumor
5 contour of an image processing system that includes a memory storing a
grayscale image and a processor according to the first embodiment of the
present invention, the tumor contour suggestion point on each of the
plurality of reference segments can be retrieved in sequence by a distance
retrieving method. As shown in FIG. 10, the distance retrieving method
10 comprises the steps of:

when there are no tumor contour suggestion points before, taking
one of the plurality of measured points on the first reference segment as a
first point, or when there is one tumor contour suggestion point before,

taking a last tumor contour suggestion point on one of the plurality of reference segments as the first point; taking one of the plurality of measured points on the next reference segment as a second point; and

retrieving the measured point on the next reference segment, having
5 the minimum distance between the first point and the second point as the tumor contour suggestion point on the next reference point.

In this example, the distance is used as the main consideration wherein the distance between two suggestion points respectively selected from two reference segments 41 are considered. In detail, after a former
10 suggestion point is selected from the former reference segment 41, the distances from the former suggestion point to each measured point selected from the later reference segment 41 are considered. The physical meaning of the aforesaid is that the distance from the later suggestion point to the former suggestion point should be shorter than that of other measured
15 points to the former suggestion point. The distance used in the present invention is an auxiliary index of features. In other words, a former suggestion point requires to be indicated, and then the algorithm is performed to retrieve a later suggestion data point selected from the later reference segment 41.

20 With reference to FIGs. 3 and 10, at first, based on the method of moving variance described in Example 1, at least one initial suggestion point 411 is retrieved from the contour. Then, the initial suggestion point 411 is used as a reference point, and a point retrieved from the reference line 4 and nearest to the initial suggestion point 411 with a minimum linear

distance, is used as a subsequent suggestion point. Other suggestion points are retrieved from other reference segments in the abovementioned manner.

Besides, the distant of the point AI_{ijk} on the reference segment 41 ($\overline{OI_{ij}II_{ij}}$) is defined as the physical distance (D_{ijk}) from the measured point 22 to the initial suggestion point 411. The relation of the abovementioned parameters is shown as the following formula 3-1.

$$D_{ijk} = \sqrt{(x_{PS_{ij'-1}} - x_{AI_{ijk}})^2 + (y_{PS_{ij'-1}} - y_{AI_{ijk}})^2}$$

..... (formula 3-1)

Since the measured point 22 on the first reference segment 41 has no former reference point for calculation, j is 2 or more. As D_{ijk} decreases, the possibility of the point to be the desirable suggestion point 411 increases.

The following description explains the effect of the distance applied in the present invention by actual data. With reference to the following Table 3, Table 3 shows the conversion from the image coordinate of each point on the reference segment of the present example to the distance, where the coordinates of the initial suggestion point in the image is (237, 193). In the first row of Table 3, k is the number of each measured point 22

on the reference segment $\overline{OI_{ij+1}II_{ij+1}}$. The second and third rows show the

coordinate ($x_{AI_{ij+1k}}, y_{AI_{ij+1k}}$) of each measure point 22. Furthermore, the fourth row shows the corresponding D_{ij+1k} of each measured point 22. In Table 3, the corresponding suggestion point is the initial suggestion point

(237,193) on the reference line $\overline{B_i II_{ij}}$ obtained by the moving variance.

As listed in Table 3, the points 10 and 11 show the shortest distance, and the following are the points 12, 9, and 13 in order.

Another reason why the distance value is an auxiliary index of
5 features is that the result of retrieving the former suggestion point
dramatically affects the corresponding distance of each point on the later
reference segment and the result of retrieving the later suggestion point.
For example, when the values of MV_{ijk} and C_{ijk} are used, although two
suggestion points locating on distinct sites and having difference distances
10 are probably retrieved respectively from the neighboring two reference
segments, D_{ijk} is supposed to affect the neighboring two reference
segments and then two suggestion points close to each other are retrieved.

k	1	2	3	4	5
$x_{AI_{ij+1k}}$	227	228	229	230	231
$y_{AI_{ij+1k}}$	196	195	195	195	194
D_{ij+1k}	10.440	9.220	8.246	7.280	6.083

k	6	7	8	9	10
$x_{AI_{ij+1k}}$	232	233	234	235	236
$y_{AI_{ij+1k}}$	194	194	193	193	193
D_{ij+1k}	5.099	4.123	3.000	2.000	1.000

k	11	12	13	14	15
$x_{AI_{ij+1k}}$	237	238	239	240	241
$y_{AI_{ij+1k}}$	192	192	192	191	191
D_{ij+1k}	1.000	1.414	2.236	3.606	4.472

k	16	17	18	19
$x_{AI_{ij+1k}}$	242	243	244	245
$y_{AI_{ij+1k}}$	191	190	190	190
D_{ij+1k}	5.385	6.708	7.616	8.544

Table 3

Example 4

In this example, the step SC of the method for retrieving a tumor contour of an image processing system that includes a memory storing a grayscale image and a processor according to the first embodiment of the present invention, the tumor contour suggestion point on each of the plurality of reference segments can be retrieved in sequence by a gradient EWMA difference retrieving method. As shown in FIG. 11, the gradient EWMA difference retrieving method comprises the steps of:

10 when there are no tumor contour suggestion points before, taking one of plurality of measured points on the first reference segment as a reference list; or when there is one tumor contour suggestion point before, taking all of the pervious tumor contour suggestion points as the reference list;

15 providing an EWMA weighting formula;

 determining the weighting factor of the EWMA weighting formula and receiving the EWMA value of the reference list by the gradients of grayscale image of each of the measured points or the tumor contour suggestion points in the reference list;

20 using the EWMA value of the reference list and the gradients of grayscale image of each of the plurality of measured points on the next reference segment as the input variables of the EWMA weighting formula;

 defining the output of the EWMA weighting formula as the EWMA value of each of the plurality of measured points on the next reference

segment; and

taking the one of plurality of measured points on the next reference segment, having the minimum difference between the gradient of grayscale image thereof and the EWMA value thereof, as the tumor contour
5 suggestion point on the next reference segment.

In this example, the gradient exponentially weighted moving average difference (gradient EWMA difference) between the grayscale images is used as the main consideration. EWMA is a statistic of a moving average with memory, and is weighed based on the importance of the
10 historical data valued by the programmer. Therefore, older historical data may be placed with more or less importance by EWMA. In detail, the concept is to consider the gradient EWMA difference between the grayscale images of the neighboring two suggestion points. The physical meaning of the aforesaid description is that the gradient EWMA difference between the
15 grayscale images of the former and later suggestion points should be less than that between the grayscale images of other measured points and the former suggestion point. The gradient EWMA difference between the grayscale images also belongs an auxiliary index of features. In other words, a former suggestion point requires to be indicated, and then the
20 algorithm is performed to retrieve a later suggestion data point selected from the later reference segment 41.

With reference to FIGs. 3 and 11, each of the reference segments 41 includes a plurality of measured points 22. Basically, the method for retrieving a suggestion point 411 from the contour is described as follows.

First, based on the method of moving variance described in Example 1, at least one initial suggestion point 411 is retrieved from the contour. Then, the gradient of the grayscale images of the measured points 22 and the EWMA of at least one initial suggestion point 411 are respectively
5 calculated. Subsequently, the differences between the gradient of the grayscale images of the measured points 22 and the EWMA of at least one initial suggestion point 411 are calculated. The minimal difference is chosen, and the corresponding measured point 22 is retrieved as a suggestion point 411. Other suggestion points are retrieved from other
10 reference segments in the abovementioned manner.

Basically, the EWMA of the point AI_{ijk} on the reference segment
41 $(\overline{OI_{ij}II_{ij}})$ is defined as the weight-interpolated value (Z_{ijk}) , which is obtained from the gradient of the grayscale image of the measured point 22 and the EWMA of the former suggestion point. The EWMA of the
15 reference segment $\overline{OI_{ij}II_{ij}}$ obtained from the aforesaid method for retrieving the former suggestion point is represented by $Z_{ij'}$. The relation of the abovementioned variants is shown as the following formula 4-1.

$$Z_{ijk} = \lambda G_{ijk} + (1 - \lambda) Z_{ij'-1}, \quad 0 < \lambda \leq 1 \dots \dots \dots (\text{formula 4-1})$$

Since the measured point on the first reference segment has no former
20 reference point for calculation, Z_{i1k} is equal to Z_{i1} and G_{i1} .

The following formula illustrates that the weighting adjustment of the EWMA will affect the importance of the historical data.

$$Z_{ijk} = \lambda G_{ijk} + (1 - \lambda) Z_{ij'-1}$$

$$\begin{aligned}
&= \lambda G_{ijk} + (1-\lambda) [\lambda G_{ij'-1} + (1-\lambda) Z_{ij'-2}] \\
&= \dots \\
&= \lambda G_{ijk} + \lambda (1-\lambda) G_{ij'-1} + \lambda (1-\lambda)^2 G_{ij'-2} + \dots + \lambda (1-\lambda)^{(j'-1)} G_{i2} + \\
&(1-\lambda)^{j'} G_{i1}
\end{aligned}$$

$$\begin{aligned}
&= \lambda G_{ijk} + \sum_{z=1}^{j'-2} \lambda (1-\lambda)^z G_{i(j'-z)} + (1-\lambda)^{j'} G_{i1}
\end{aligned}$$

In the formula, as λ increases, it indicates that the neighboring data have more weighting effect to the output data; by contrast, as λ decreases, it indicates that the old and new historical data have more similar weighting effect to the output data. For example, when $j = j' = 4$, if $\lambda = 0.9$, Z_{i4k} can be shown as $Z_{i4k} = 0.9G_{i4k} + 0.09G_{i3} + 0.009G_{i2} + 0.001G_{i1}$. This indicates Z_{i4k} is greatly affected by G_{i4k} . By contrast, if $\lambda = 0.1$, Z_{i4k} can be shown as $Z_{i4k} = 0.1G_{i4k} + 0.09G_{i3} + 0.081G_{i2} + 0.729G_{i1}$. It can be seen that G_{i2} , G_{i3} , and G_{i4k} similarly affect Z_{i4k} .

Moreover, the gradient EWMA difference of the grayscale images means that the gradient EWMA difference of the point AI_{ijk} is on the

reference segment $41 \left(\overline{OI_{ij} II_{ij}} \right)$, and it is defined as the difference (E_{ijk})

between the gradient of the grayscale image and the EWMA (Z_{ijk}) of the

point AI_{ijk} . $E_{ijk} = |G_{ijk} - Z_{ijk}|$. As E_{ijk} decreases, the possibility of

the point to be the desirable suggestion point increases. Since the measured point on the first reference segment has no former reference point for

calculation, j is 2 or more.

The following description explains the effect of the gradient EWMA difference of the grayscale images applied in the present invention by actual data. With reference to the following Table 4, Table 4 shows the conversion from the coordinates of each point (in the image) on the reference segment to the gradient EWMA difference of the grayscale images in the present example, wherein the EWMA of the initial suggestion point is 64. In the first row of Table 4, k is the number of each measured point on the reference segment $\overline{OI_{ij+1}II_{ij+1}}$. The second row shows the gradient (G_{ij+1k}) of the grayscale image of each measure point. The third row shows the corresponding E_{ij+1k} of each measure point. In Table 4, the Z_{ij} of the suggestion point is the EWMA (Z_{ij}) of the suggestion point on the reference line $\overline{B_i II_{ij}}$ obtained by the moving variance. As listed in Table 4, the points 15, 17, and 18 show the minimum gradient EWMA difference of the grayscale images, and the following are the points 12 and 19 in order.

k	1	2	3	4	5
G_{ij+1k}	77	81	79	78	92
E_{ij+1k}	2.6	3.4	3	2.8	5.6

k	6	7	8	9	10
G_{ij+1k}	94	93	87	88	78
E_{ij+1k}	6	5.8	4.6	4.8	2.8

k	11	12	13	14	15
G_{ij+1k}	53	50	52	61	65
E_{ij+1k}	2.2	2.8	2.4	0.6	0.2

k	16	17	18	19
G_{ij+1k}	62	65	65	67
E_{ij+1k}	0.4	0.2	0.2	0.6

Table 4

Example 5

In this example, the step SC of the method for retrieving a tumor contour of an image processing system that includes a memory storing a grayscale image and a processor according to the first embodiment of the present invention, the tumor contour suggestion point on each of the plurality of reference segments can be retrieved in sequence by an angle retrieving method. As shown in FIG. 12, the angle retrieving method comprises the steps of:

when there are no tumor contour suggestion point before a last tumor contour suggestion point, defining one of the plurality of measured points on the first reference segment as a first point, and one of the plurality

of measured points on the second reference segment as a second point; or
when there is one tumor contour suggestion point before the last tumor
contour suggestion point, defining the tumor contour suggestion point
before the last tumor contour suggestion point as the first point, and
5 defining the last tumor contour suggestion point as the second point;

defining a vector going from the first point to the second point as a
first vector, and vectors going from the second point to each of the plurality
of measured points on a next reference segment as a plurality of second
vectors;

10 calculating the cosine values of the angles included by the first
vector and the plurality of second vectors, respectively; and

taking the one of plurality of measured points on the second next
reference segment, being the end point of the second vector corresponding
to the angle having maximum cosine value, as the tumor contour suggestion
15 point on the second next reference segment.

In this example, the angle is used as the main consideration wherein
the relative position of the neighboring three suggestion points is
considered. Since the contour of the tumor belongs a continuous curved
track, the position and angle differences between the distant of the point

20 AI_{ijk} on the reference segment 41 ($\overline{OI_{ij}II_{ij}}$) and the third suggestion point,
should be as small as possible. In other words, using vectors for illustration,
the cosine of the included angle between the vectors going from the first to
second suggestion points and those going from the second to third

suggestion points should be smaller than the cosine of the included angle between the vectors going from the first to second suggestion points and those going from the second suggestion point to the measured point. As the included angle decreases, the cosine thereof ($\cos\theta$) increases. Besides, due to $\cos\theta$ in quadrants I and IV is positive, the continuity required by the contour of the tumor and the minor curvature between the neighboring two suggestion points can be expressed. The angle used in the present invention is an auxiliary index of features. In other words, a former two suggestion points are required, and then the algorithm is performed to retrieve a third suggestion data point selected from the next reference segment.

With reference to FIGs. 3 and 12, each of the reference segments 41 includes a plurality of measured points 22. Basically, the method for retrieving a suggestion point 411 from the contour is described as follows. First, based on the method of moving variance described in Example 1, first and second suggestion points 411 are retrieved from the neighboring two reference segments 41 of the reference line 4. Then, the vector going from the first to second suggestion points, and that going from the second suggestion point to the measured points on the neighboring reference segment 41 are calculated respectively as the first and second vectors. Subsequently, the cosines of the included angle between the first and second vectors are calculated. Among the cosines of the included angle, the maximal cosine is chosen, and the corresponding measured point 22 on the neighboring measure line segment is retrieved as a suggestion point 412. Other suggestion points are retrieved from other reference segments in the

abovementioned manner.

Basically, the cosine of the angle of the point AI_{ijk} on the reference segment 41 ($OI_{ij}II_{ij}$) is defined as the cosine (A_{ijk}) of the included angle

between the vectors of $\overline{PS_{ij'-2}PS_{ij'-1}}$ and $\overline{PS_{ij'-1}AI_{ijk}}$. The relationship of

5 the abovementioned parameters is shown as the following formula 5-1.

$A_{ijk} =$

$$\frac{(x_{PS_{ij'-1}} - x_{PS_{ij'-2}})(x_{AI_{ijk}} - x_{PS_{ij'-1}}) + (y_{PS_{ij'-1}} - y_{PS_{ij'-2}})(y_{AI_{ijk}} - y_{PS_{ij'-1}})}{\sqrt{(x_{PS_{ij'-1}} - x_{PS_{ij'-2}})^2 + (y_{PS_{ij'-1}} - y_{PS_{ij'-2}})^2} \sqrt{(x_{AI_{ijk}} - x_{PS_{ij'-1}})^2 + (y_{AI_{ijk}} - y_{PS_{ij'-1}})^2}}$$

.....(formula 5 - 1)

As the A_{ijk} increases, the possibility of the point to be the desirable
10 suggestion point increases. Since the measured points on the first and reference segments has no former reference point for calculation, J is 3 or more.

The following description explains the effect of the angle applied in the present invention by actual data. With reference to the following Table
15 5, Table 5 shows the conversion from the coordinates (in the image) to the angle of each point on the reference segment. The coordinates (in the image) of the suggestion point $PS_{ij'}$ is (237,193), and that of the suggestion point $PS_{ij'+1}$ is (236,193). In the first row of Table 5, k is the number of each measured point on the reference segment $\overline{OI_{ij+2}II_{ij+2}}$. The second and third

rows show the coordinate ($x_{AI_{ij+2k}}, y_{AI_{ij+2k}}$)(in the image) of each measure point. The fourth row shows the corresponding A_{ij+2k} of each measure point. In Table 5, the corresponding suggestion point PS_{ij} on the reference line $\overline{B_i II_{ij}}$ obtained by the moving variance is the coordinate (237,193), and the corresponding suggestion point PS_{ij+1} on the reference line $\overline{B_i II_{ij+1}}$ obtained by the moving variance is the coordinate (236,193).

As listed in Table 5, the points 4, 5, and 6 show the largest angle, and the points with angles next to the largest angle are the points 1, 2, and 3 in order. Another reason why the angle value is an auxiliary index of features is that the coordinate (in the image) belongs discrete integer data. Generally, one point in a physical coordinate system has many surrounding azimuthal points (360° azimuthal angles) but one point in an integer coordinate system has only eight surrounding points (eight directions in a plane) in total. Hence, if the two reference segments are too close, the azimuthal angle is supposed to be limited by the influence of the distance, and thus the vector of the included angle subsequently output probably becomes acceptable.

k	1	2	3	4	5
$x_{AI_{ij+2k}}$	227	228	229	230	231
$y_{AI_{ij+2k}}$	194	194	194	193	193
A_{ij+2k}	0.994	0.992	0.990	1.000	1.000

k	6	7	8	9	10
$x_{AI_{ij+2k}}$	232	233	234	235	236
$y_{AI_{ij+2k}}$	193	192	192	192	192
A_{ij+2k}	1.000	0.949	0.894	0.707	0.000

k	11	12	13	14	15
$x_{AI_{ij+2k}}$	237	238	239	240	241
$y_{AI_{ij+2k}}$	191	191	191	190	190
A_{ij+2k}	-0.447	-0.707	-0.832	-0.800	-0.857

k	16	17	18	19
$x_{AI_{ij+2k}}$	242	243	244	245
$y_{AI_{ij+2k}}$	190	189	189	189
A_{ij+2k}	-0.894	-0.868	-0.894	-0.914

Table 5

Please refer to FIG. 13, which is a flowchart of the method for

retrieving a tumor contour of an image processing system according to the second embodiment of the present invention. The method for retrieving a tumor contour for an image processing system that includes a memory storing a grayscale image and a processor according to the second
5 embodiment of the present invention comprises:

Step SA: receiving an input tumor contour of the grayscale image;

Step SB: defining a tumor contour annular region and a plurality of reference segments of the grayscale image, wherein the input tumor contour is in the tumor contour annular region, and each of the plurality of reference
10 segments is across the tumor contour annular region and includes a plurality of measured points;

Step SC: retrieving a modulated tumor contour suggestion point on each of the plurality of reference segments; and

Step SD: linking all the modulated tumor contour suggestion points
15 on all of the reference segments, for forming the modulated tumor contour.

Besides, in step SC, the modulated tumor contour suggestion point on each of the plurality of reference segments is obtained by the following steps:

Step C1: normalizing the value of all the measured points on the
20 reference segment retrieved by a moving variance retrieving method, the value of all the measured points on the reference segment retrieved by a contrast retrieving method, the value of all the measured points on the reference segment retrieved by a distance retrieving method, the value of all the measured points on the reference segment retrieved by a gradient

EWMA difference retrieving method, and the value of all the measured points on the reference segment retrieved by an angle retrieving method into value between 0 and 1;

Step C2: determining modulating criteria for each of the
5 aforementioned retrieving methods; calculating a weighting parameter for
each the measured points on the reference segment, by multiplying product
corresponding to each of the aforementioned retrieving methods together,
wherein each of the products is obtained by multiple the normalized value
of the measured point for the number of times equal to the modulating
10 criteria of the corresponding retrieving method, respectively; and

Step C3: retrieving the coordinate of the tumor contour suggestion
point on the reference segment by calculating the average coordinate, from
the sum of the product obtained by multiplying the coordinate of each of the
measured points on the reference segment with the corresponding
15 weighting parameter, respectively.

However, in the moving variance retrieving method applied in Step
C1, each of the plurality of reference segments includes a plurality of local
segments and each of the plurality of local segments includes a plurality of
moving horizons; each of the plurality of local segments consists of one of
20 the plurality of measured points, at least one measured point before and at
least one measured point after the one of the plurality of measured points,
and each of the plurality of moving horizons consists of one of the plurality
of measured points in the corresponding local segment and at least one
measured point after the one of the plurality of measured points; and the

value of all the measured points on the reference segment are retrieved by the moving variance retrieving method comprising the steps of: calculating a gradient variance of the grayscale image in the plurality of local segments and an average gradient variance of the grayscale image in the plurality of moving horizons; calculating the ratio of the gradient variance of the grayscale image in the plurality of local segments to the average gradient variance of the grayscale image in the plurality of moving horizons; and retrieving the measured point corresponding to the maximum ratio as the tumor contour suggestion point.

10 On the other hand, in the contrast variance retrieving method applied in Step C1, a center of gravity of the input tumor contour is retrieved and a plurality of contrast reference segments is defined, each of the plurality of contrast reference segments extends from the center of the gravity to of the corresponding reference segments, respectively; and the value of all the measured points on the reference segment are retrieved by the contrast retrieving method comprising the steps of: calculating gradients of the grayscale image in the plurality of reference segments and an average gradient of the grayscale image in the plurality of contrast reference segments; calculating the differences between the gradients of the grayscale image in the plurality of reference segments and an average gradient of the grayscale image in the plurality of contrast reference segments; and retrieving the measured point corresponding to the maximum difference as the tumor contour suggestion point.

 In the distance retrieving method applied in Step C1, the value of all

the measured points on the reference segment are retrieved in sequence by the distance retrieving method comprising the steps of: when there are no tumor contour suggestion points before, taking one of the plurality of measured points on the first reference segment as a first point, or when there
5 is one tumor contour suggestion point before, taking a last tumor contour suggestion point on one of the plurality of reference segments as the first point; taking one of the plurality of measured points on the next reference segment as a second point; and retrieving the measured point on the next reference segment, having the minimum distance between the first point
10 and the second point as the tumor contour suggestion point on the next reference point.

In the gradient EWMA difference retrieving method applied in Step C1, the value of all the measured points on the reference segment are retrieved in sequence by the gradient EWMA difference retrieving method
15 comprising the steps of: when there are no tumor contour suggestion points before, taking one of plurality of measured points on the first reference segment as a reference list; or when there is one tumor contour suggestion point before, taking all of the pervious tumor contour suggestion points as the reference list; providing an EWMA weighting formula; determining the
20 weighting factor of the EWMA weighting formula and receiving the EWMA value of the reference list by the gradients of grayscale image of each of the measured points or the tumor contour suggestion points in the reference list; using the EWMA value of the reference list and the gradients of grayscale image of each of the plurality of measured points on the next

reference segment as the input variables of the EWMA weighting formula;
defining the output of the EWMA weighting formula as the EWMA value
of each of the plurality of measured points on the next reference segment;
and taking the one of plurality of measured points on the next reference
5 segment, having the minimum difference between the gradient of grayscale
image thereof and the EWMA value thereof, as the tumor contour
suggestion point on the next reference segment.

At last, in the angle retrieving method applied in Step C1, the value
of all the measured points on the reference segment are retrieved in
10 sequence by the angle retrieving method comprising the steps of: when
there are no tumor contour suggestion point before a last tumor contour
suggestion point, defining one of the plurality of measured points on the
first reference segment as a first point, and one of the plurality of measured
points on the second reference segment as a second point; or when there is
15 one tumor contour suggestion point before the last tumor contour
suggestion point, defining the tumor contour suggestion point before the
last tumor contour suggestion point as the first point, and defining the last
tumor contour suggestion point as the second point; defining a vector going
from the first point to the second point as a first vector, and vectors going
20 from the second point to each of the plurality of measured points on a next
reference segment as a plurality of second vectors; calculating the cosine
values of the angles included by the first vector and the plurality of second
vectors, respectively; and taking the one of plurality of measured points on
the second next reference segment, being the end point of the second vector

corresponding to the angle having maximum cosine value, as the tumor contour suggestion point on the second next reference segment.

Since the above-mentioned 5 kinds of retrieving method have been described in Examples 1 to 5, the detailed explanation of these 5 kinds of
5 retrieving method is omitted herein.

The abovementioned steps in the methods for retrieving a tumor contour of an image processing system of the present invention can be performed by computer programs. The software written for the methods for retrieving a tumor contour of an image processing system of the present
10 invention can be stored in any recording media capable of being recognized or read by a microprocessing unit, or in any articles and devices including the recording medium. The articles are not limited, and can be hard discs, flexible discs, compact discs, ZIP, MO, IC chips, random-access memory (RAM), or any articles including the recording media known by one skilled
15 in the art. As the methods for retrieving a tumor contour of an image processing system is completely disclosed herein, one skill known the computer language can understand how to write software and computer programs. Accordingly, the detail referring to the software and computer programs related to the methods for retrieving a tumor contour of an image
20 processing system of the present invention is not described herein.

Although the present invention has been explained in relation to its preferred embodiment, it is to be understood that many other possible modifications and variations can be made without departing from the scope of the invention as hereinafter claimed.

What is claimed is:

1. A method of retrieving a tumor contour implemented in an image processing system that includes a memory storing a grayscale image, a display screen, an input device and a processor performing method steps, comprising: receiving an input tumor contour of the grayscale image;
5 defining a tumor contour annular region and a plurality of reference segments of the grayscale image, wherein the input tumor contour is in the tumor contour annular region, and each of the plurality of reference segments is across the tumor contour annular region and includes a plurality of measured points; retrieving a tumor contour suggestion point on each of the plurality of
10 reference segments; and linking all the tumor contour suggestion points on all of the reference segments, for forming the tumor contour, wherein each of the plurality of reference segments includes a plurality of local segments and each of the plurality of local segments includes a plurality of moving horizons; wherein each of the plurality of local segments consists of one of the plurality of measured points, at least one measured point before and at least one measured
15 point after the one of the plurality of measured points, and each of the plurality of moving horizons consists of one of the plurality of measured points in the corresponding local segment and at least one measured point after the one of the plurality of measured points; and wherein the tumor contour suggestion point is retrieved by a moving variance retrieving method comprising the steps of: calculating a gradient variance of the grayscale image in the plurality of local
20 segments and an average gradient variance of the grayscale image in the plurality of moving horizons; calculating the ratio of the gradient variance of the grayscale image in the plurality of local segments to the average gradient variance of the grayscale image in the plurality of moving horizons; and retrieving the measured point corresponding to the maximum ratio as the tumor contour suggestion point.
- 25 2. A method of retrieving a tumor contour implemented in an image processing system that includes a memory storing a grayscale image, a display screen, an input device and a processor performing method steps, comprising: receiving an input tumor contour of the grayscale image; defining a tumor contour annular region and a plurality of reference segments of the grayscale image, wherein the input tumor contour is in the tumor contour annular region, and each of the
30 plurality of reference segments is across the tumor contour annular region and includes a plurality of measured points; retrieving a modulated tumor contour suggestion point on each of the plurality of reference segments; and linking all the modulated tumor contour suggestion points on all of the reference segments, for forming the modulated tumor contour; wherein the modulated tumor contour suggestion point on each of the plurality of reference segments is obtained by the

following steps: normalizing the value of all the measured points on the reference segment retrieved by a moving variance retrieving method, the value of all the measured points on the reference segment retrieved by a contrast retrieving method, the value of all the measured points on the reference segment retrieved by a distance retrieving method, the value of all the measured points on the reference segment retrieved by a gradient EWMA difference retrieving method, and the value of all the measured points on the reference segment retrieved by an angle retrieving method into value between 0 and 1; determining modulating criteria for each of the aforementioned retrieving methods; calculating a weighting parameter for each the measured points on the reference segment, by multiplying product corresponding to each of the aforementioned retrieving methods together, wherein each of the products is obtained by multiple the normalized value of the measured point for the number of times equal to the modulating criteria of the corresponding retrieving method, respectively; and retrieving the coordinate of the tumor contour suggestion point on the reference segment by calculating the average coordinate, from the sum of the product obtained by multiplying the coordinate of each of the measured points on the reference segment with the corresponding weighting parameter, respectively; wherein in the moving variance retrieving method, each of the plurality of reference segments includes a plurality of local segments and each of the plurality of local segments includes a plurality of moving horizons; each of the plurality of local segments consists of one of the plurality of measured points, at least one measured point before and at least one measured point after the one of the plurality of measured points, and each of the plurality of moving horizons consists of one of the plurality of measured points in the corresponding local segment and at least one measured point after the one of the plurality of measured points; and the value of all the measured points on the reference segment are retrieved by the moving variance retrieving method comprising the steps of: calculating a gradient variance of the grayscale image in the plurality of local segments and an average gradient variance of the grayscale image in the plurality of moving horizons; calculating the ratio of the gradient variance of the grayscale image in the plurality of local segments to the average gradient variance of the grayscale image in the plurality of moving horizons; and retrieving the measured point corresponding to the maximum ratio as the tumor contour suggestion point; wherein in the contrast retrieving method, a center of gravity of the input tumor contour is retrieved and a plurality of contrast reference segments is defined, each of the plurality of contrast reference segments extends from the center of the gravity to of the corresponding reference segments, respectively; and the value of all the measured points on the reference segment are retrieved by the contrast retrieving method comprising the steps of: calculating gradients of the grayscale image in the plurality of reference segments and an average

gradient of the grayscale image in the plurality of contrast reference segments; calculating the differences between the gradients of the grayscale image in the plurality of reference segments and an average gradient of the grayscale image in the plurality of contrast reference segments; and retrieving the measured point corresponding to the maximum difference as the tumor contour suggestion point; wherein in the distance retrieving method, the value of all the measured points on the reference segment are retrieved in sequence by the distance retrieving method comprising the steps of: when there are no tumor contour suggestion points before, taking one of the plurality of measured points on the first reference segment as a first point, or when there is one tumor contour suggestion point before, taking a last tumor contour suggestion point on one of the plurality of reference segments as the first point; taking one of the plurality of measured points on the next reference segment as a second point; and retrieving the measured point on the next reference segment, having the minimum distance between the first point and the second point as the tumor contour suggestion point on the next reference point; wherein in the gradient EWMA difference retrieving method, the value of all the measured points on the reference segment are retrieved in sequence by the gradient EWMA difference retrieving method comprising the steps of: when there are no tumor contour suggestion points before, taking one of plurality of measured points on the first reference segment as a reference list; or when there is one tumor contour suggestion point before, taking all of the pervious tumor contour suggestion points as the reference list; providing an EWMA weighting formula; determining the weighting factor of the EWMA weighting formula and receiving the EWMA value of the reference list by the gradients of grayscale image of each of the measured points or the tumor contour suggestion points in the reference list; using the EWMA value of the reference list and the gradients of grayscale image of each of the plurality of measured points on the next reference segment as the input variables of the EWMA weighting formula; defining the output of the EWMA weighting formula as the EWMA value of each of the plurality of measured points on the next reference segment; and taking the one of plurality of measured points on the next reference segment, having the minimum difference between the gradient of grayscale image thereof and the EWMA value thereof, as the tumor contour suggestion point on the next reference segment; wherein in the angle retrieving method, the value of all the measured points on the reference segment are retrieved in sequence by the angle retrieving method comprising the steps of: when there are no tumor contour suggestion point before a last tumor contour suggestion point, defining one of the plurality of measured points on the first reference segment as a first point, and one of the plurality of measured points on the second reference segment as a second point; or when there is one tumor contour suggestion point before the last tumor contour suggestion point, defining the tumor

contour suggestion point before the last tumor contour suggestion point as the first point, and defining the last tumor contour suggestion point as the second point; defining a vector going from the first point to the second point as a first vector, and vectors going from the second point to each of the plurality of measured points on a next reference segment as a plurality of second
5 vectors; calculating the cosine values of the angles included by the first vector and the plurality of second vectors, respectively; and taking the one of plurality of measured points on the second next reference segment, being the end point of the second vector corresponding to the angle having maximum cosine value, as the tumor contour suggestion point on the second next reference segment.

10 3. A method of retrieving a tumor contour implemented in an image processing system that includes a memory storing a grayscale image, a display screen, an input device and a processor performing method steps, comprising: receiving an input tumor contour of the grayscale image; defining a tumor contour annular region and a plurality of reference segments of the grayscale
15 image, wherein the input tumor contour is in the tumor contour annular region, and each of the plurality of reference segments is across the tumor contour annular region and includes a plurality of measured points; retrieving a tumor contour suggestion point on each of the plurality of reference segments; and linking all the tumor contour suggestion points on all of the reference segments, for forming the tumor contour, wherein a center of gravity of the input tumor contour is retrieved and a plurality of contrast reference segments is defined, each of the plurality of contrast
20 reference segments extends from the center of the gravity to of the corresponding reference segments, respectively; and wherein the tumor contour suggestion point is retrieved by a contrast retrieving method comprising the steps of: calculating gradients of the grayscale image in the plurality of reference segments and an average gradient of the grayscale image in the plurality of contrast reference segments; calculating the differences between the gradients of the grayscale
25 image in the plurality of reference segments and an average gradient of the grayscale image in the plurality of contrast reference segments; and retrieving the measured point corresponding to the maximum difference as the tumor contour suggestion point.

4. A method of retrieving a tumor contour implemented in an image processing system that includes a memory storing a grayscale image, a display screen, an input device and a processor
30 performing method steps, comprising: receiving an input tumor contour of the grayscale image; defining a tumor contour annular region and a plurality of reference segments of the grayscale image, wherein the input tumor contour is in the tumor contour annular region, and each of the plurality of reference segments is across the tumor contour annular region and includes a plurality of measured points; retrieving a tumor contour suggestion point on each of the plurality of

reference segments; and linking all the tumor contour suggestion points on all of the reference segments, for forming the tumor contour, wherein the tumor contour suggestion point is retrieved in sequence by a distance retrieving method comprising the steps of: when there are no tumor contour suggestion points before, taking one of the plurality of measured points on the first reference segment as a first point, or when there is one tumor contour suggestion point before, taking a last tumor contour suggestion point on one of the plurality of reference segments as the first point; taking one of the plurality of measured points on the next reference segment as a second point; and retrieving the measured point on the next reference segment, having the minimum distance between the first point and the second point as the tumor contour suggestion point on the next reference point.

5. A method of retrieving a tumor contour implemented in an image processing system that includes a memory storing a grayscale image, a display screen, an input device and a processor performing method steps, comprising: receiving an input tumor contour of the grayscale image; defining a tumor contour annular region and a plurality of reference segments of the grayscale image, wherein the input tumor contour is in the tumor contour annular region, and each of the plurality of reference segments is across the tumor contour annular region and includes a plurality of measured points; retrieving a tumor contour suggestion point on each of the plurality of reference segments; and linking all the tumor contour suggestion points on all of the reference segments, for forming the tumor contour, wherein the tumor contour suggestion point is retrieved in sequence by a gradient EWMA difference retrieving method comprising the steps of: when there are no tumor contour suggestion points before, taking one of plurality of measured points on the first reference segment as a reference list; or when there is one tumor contour suggestion point before, taking all of the pervious tumor contour suggestion points as the reference list; providing an EWMA weighting formula; determining the weighting factor of the EWMA weighting formula and receiving the EWMA value of the reference list by the gradients of grayscale image of each of the measured points or the tumor contour suggestion points in the reference list; using the EWMA value of the reference list and the gradients of grayscale image of each of the plurality of measured points on the next reference segment as the input variables of the EWMA weighting formula; defining the output of the EWMA weighting formula as the EWMA value of each of the plurality of measured points on the next reference segment; and taking the one of plurality of measured points on the next reference segment, having the minimum difference between the gradient of grayscale image thereof and the EWMA value thereof, as the tumor contour suggestion point on the next reference segment.

6. A method of retrieving a tumor contour implemented in an image processing system that includes a memory storing a grayscale image, a display screen, an input device and a processor performing method steps, comprising: receiving an input tumor contour of the grayscale image; defining a tumor contour annular region and a plurality of reference segments of the grayscale
5 image, wherein the input tumor contour is in the tumor contour annular region, and each of the plurality of reference segments is across the tumor contour annular region and includes a plurality of measured points; retrieving a tumor contour suggestion point on each of the plurality of reference segments; and linking all the tumor contour suggestion points on all of the reference segments, for forming the tumor contour, wherein the tumor contour suggestion point is retrieved
10 in sequence by an angle retrieving method comprising the steps of: when there are no tumor contour suggestion point before a last tumor contour suggestion point, defining one of the plurality of measured points on the first reference segment as a first point, and one of the plurality of measured points on the second reference segment as a second point; or when there is one tumor contour suggestion point before the last tumor contour suggestion point, defining the tumor
15 contour suggestion point before the last tumor contour suggestion point as the first point, and defining the last tumor contour suggestion point as the second point; defining a vector going from the first point to the second point as a first vector, and vectors going from the second point to each of the plurality of measured points on a next reference segment as a plurality of second vectors; calculating the cosine values of the angles included by the first vector and the plurality of second vectors, respectively; and taking the one of plurality of measured points on the second
20 next reference segment, being the end point of the second vector corresponding to the angle having maximum cosine value, as the tumor contour suggestion point on the second next reference segment.

METHOD FOR RETRIEVING A TUMOR CONTOUR OF AN IMAGE PROCESSING SYSTEM

ABSTRACT OF THE DISCLOSURE

5 The present invention related to a method for retrieving a tumor
contour of an image processing system that includes a memory storing a
grayscale image and a processor, comprising: receiving an input tumor
contour of the grayscale image; defining a tumor contour annular region
and a plurality of reference segments of the grayscale image, wherein the
10 input tumor contour is in the tumor contour annular region, and each of the
plurality of reference segments is across the tumor contour annular region
and includes a plurality of measured points; retrieving a tumor contour
suggestion point on each of the plurality of reference segments; and linking
all the tumor contour suggestion points on all of the reference segments, for
15 forming the tumor contour. Accordingly, by applying the method of the
present invention, a doctor can rapidly and accurately identify the contour
of a tumor in a grayscale image.

Fig. 4