SG9608158-3
RTMP's copy

REPLACED SHEETS SG
☑ Description : paged 1 to paged 65
☑ Claim(s) : paged 66 to paged 85
☑ Drawing(s) : paged - to paged -
☑ Abstract : paged - to paged -

DEVELOPER REPLENISHING DEVICE AND DEVELOPER CONTAINER FOR USE THEREWITH

BACKGROUND OF THE INVENTION

The present invention relates to a developing device included in a copier, facsimile apparatus, printer or similar image forming apparatus and, more particularly, to a developer replenishing device for replenishing the developing device with a developer, and a developer container for use therewith.

There has been extensively used a copier, facsimile apparatus, printer or similar electrophotographic image forming apparatus which electrostatically forms a latent image on a photoconductive element, develops the latent image with charged color particles, i.e., developer, and then transfers the developed image to a paper. It is a common practice with this type of apparatus to supplement a fresh developer when a developer stored in a vessel is consumed. A device for replenishing the developer may be implemented with a hollow cylindrical container storing the developer, as taught in, for example, Japanese Patent Laid-Open Publication (Kokai) Nos. 59-188678 and 60-146265. The container is substantially entirely open at one end thereof to form a

This Sheet Has Been Replaced

developer outlet and is rotated about the longitudinal axis thereof to sequentially discharge the developer, or powder, to the vessel of the image forming apparatus via the outlet. To replace the container with a new container filled with a fresh developer, a holder positioned horizontally on the body of the image forming apparatus is rotated downward to a vertical position about one end thereof. In this condition, the empty container is removed from the holder, and then a new container is mounted to the holder. Subsequently, the holder is again rotated to the horizontal position where the new container can replenish the apparatus with the developer. Before the new container is put on the holder maintained in the vertical position, the container is positioned such that the opening, or developer outlet, thereof faces upward, and then a cap closing the opening is removed. The container without the cap is mounted to the holder with the opening facing upward, so that the powder filling the container may not fall.

However, the prerequisite with the conventional scheme described above is that the length of the holder should not be greater than the height of the apparatus since the holder has to be rotated between the horizontal position and the vertical position about one end thereof. Generally, the apparatus is provided with as small a height as possible to meet the demand for a miniature configuration, requiring the holder

This Sheet Has Been Replaced

and, therefore, the container to be as short as possible. As a result, the quantity of developer available with a single container is reduced, resulting in the frequent replacement of the container. In any case, the conventional replenishing device cannot be reduced in size and suffers from design limitations in relation to the internal arrangement of an image forming apparatus.

In the light of the above, we conducted a series of studies and experiments in order to implement an arrangement for allowing a person to replace the cylindrical container while maintaining the holder in the horizontal position. However, since the container is substantially fully open at one end thereof, the developer stored therein falls via the outlet of the container when the container is mounted to the holder. We, therefore, have proposed in Japanese Patent Laid-Open Publication No. 3-2881 a developer replenishing device using a container which is closed at both ends thereof and formed with a developer outlet in the circumferential wall thereof adjacent one of the closed ends. This kind of container is placed on a holder with the outlet facing upward. However, considering the fact that an image forming apparatus is used by ordinary clerks, it is likely that the container is inadvertently mounted to the holder with the outlet facing downward. Then, the developer will fall from the container and smear the apparatus and floor. In addition,

This Sheet Has Been Replaced

a dead space is produced between the outlet and the adjoining end of the container, requiring the container to be provided with an additional length matching the dead space.

SUMMARY OF THE INVENTION

It is, therefore, an object of the present invention to provide a new and improved developer replenishing device free from the drawbacks discussed above.

It is another object of the present invention to provide a developer replenishing device which prevents a developer from falling from a container despite that the container is set in a horizontal position.

It is another object of the present invention to provide a new and improved developer container for use with such a developer replenishing device.

It is another object of the present invention to provide a developer container capable of replenishing a developing device installed in an image forming apparatus with all the developer stored therein.

In accordance with the present invention, in a developer container for use with a developer replenishing device a holder for holding the developer container to allow a developer to be discharged from a mouth portion of the developer container into the developer replenishing device, and a drive unit for causing the developer container held by

This Sheet Has Been Replaced

the holder to rotate about the axis thereof, there is provided a hollow cylindrical main body having the mouth portion on one end. The mouth portion is smaller in diameter than a shoulder portion which forms a circumferential wall adjacent the one end. A guide portion is provided on a part of the shoulder portion for guiding the developer stored in the developer container to the mouth portion.

Also, in accordance with the present invention, in a toner bottle for use with a toner replenishing device having a bottle holder into which a mouth portion of the toner bottle may fit for discharge of a toner in the toner bottle into the toner replenishing device, and a drive unit which rotatably drives the toner bottle when the toner bottle is mounted to the toner replenishing device, there are provided a main body comprising a substantially hollow container having, adjacent one end of the toner bottle, a first diameter portion, a discharge mouth at the one end, the discharge mouth comprising the mouth portion and having a second diameter substantially smaller than the first diameter, and a circumferential and radially extending ramp surface configuration of the peripheral surface of the main body at the one end and connecting radially between the first diameter portion and a radial position no greater than the second diameter portion.

This Sheet Has Been Replaced

Further, in accordance with the present invention, in toner bottle for use with a toner replenishing device having a bottle holder into which a mouth portion of the toner bottle may fit for discharge of a toner in the toner bottle into the toner replenishing device, and a drive unit which rotatably drives the toner bottle about a longitudinal axis thereof when the toner bottle is mounted to the toner replenishing device, there are provided a main body comprising a substantially hollow container, and a rotational force transfer projection or recess on the radially extending surface of the main body and cooperating with the bottle holder for transferring the rotation of the bottle holder to the toner bottle.

Moreover, in accordance with the present invention, in toner bottle for use with a toner replenishing device having a mouth portion for discharge of toner in the toner bottle into the toner replenishing device, and a drive unit which rotatably drives the toner bottle when the toner bottle is mounted to the toner replenishing device, there are provided a main body comprising a substantially hollow container having, adjacent one end of the bottle, a first diameter portion, a discharge mouth at the one end, the discharge mouth comprising the mouth portion and having a second diameter substantially smaller than the first diameter, and a circumferential and radially extending ramp surface configuration of the main body at the one end and connecting radially between the first

This Sheet Has Been Replaced

diameter portion and a radial position no greater than the second diameter portion such that a controllable quantity of toner in the toner bottle is raised radially from the first diameter portion to the second diameter portion for feeding the controllable quantity of toner to the discharge mouth when the toner bottle is rotated by the drive unit.

In addition, in accordance with the present invention, a device for replenishing a developing device of an image forming apparatus with a developer comprises a developer container containing a developer and having a mouth portion, and a holder communicated to a developer replenishing section for holding the developer container while orienting the mouth portion toward the developer replenishing section. The holder is rotatable about one end in a substantially horizontal plane.

BRIEF DESCRIPTION OF THE DRAWINGS

The above and other objects, features and advantages of the present invention will become more apparent from the following detailed description taken with the accompanying drawings in which:

FIGS. 1A and 1B are respectively a section and a front view, showing a copier to which the present invention is applicable;

This Sheet Has Been Replaced



FIG. 2 is a section showing the general construction of a developing device incorporated in the copier;

FIGS. 3A and 3B are respectively a section and a fragmentary enlarged view, showing a toner bottle for use with the copier;

FIGS. 4A-4C show a sequence of steps for removing a lid from the toner bottle;

FIG. 5A is a section showing a specific configuration of the lid;

FIGS. 5B and 5C are perspective views each showing another specific configuration of the lid;

FIG. 5D is a perspective view showing a thin flat piece to be attached to the lid of the toner bottle;

FIG. 5E is a section showing the lid with the thin flat piece attached thereto;

FIG. 6 is a section showing a toner supply unit included in an embodiment of the present invention;

FIGS. 7 and 8 are exploded perspective views each showing a particular part of the toner supply unit;

FIG. 9A, 9B, 10A, 10B, 11A and 11B are sections each showing a collet chuck included in the toner supply unit;

FIG. 12A is an exploded perspective view showing another part of the toner supply unit;

FIG. 12B is a sectional perspective view of the toner bottle;

This Sheet Has Been Replaced



FIG. 13A is a section of the collet chuck;

FIGS. 13B and 13C are sections each showing another specific configuration of the toner bottle;

FIGS. 14A-14E are perspective views each showing a specific constituent part included in a core shown in FIG. 7;

FIG. 15 is a graph indicative of a relation between the force necessary for a person to operate the toner supply unit and the diameter of the mouth of the toner bottle;

FIG. 16 is a perspective view showing a stop cover and a collet shaft included in a modified embodiment;

FIGS. 17A-17D demonstrate the operation of the modified embodiment;

FIGS. 18A-18D show another operation of the modified embodiment;

FIG. 19A is a perspective view showing the lid;

FIG. 19B is a section of the lid shown in FIG. 19A;

FIG. 19C illustrates forces to act on the lid when the lid is attached and detached;

FIG. 19D is a section showing another specific configuration of the lid;

FIG. 20A is a front view of the toner bottle to which a cap is attached;

FIGS. 20B-20F each shows the toner bottle of FIG. 20A in a particular view;

This Sheet Has Been Replaced




FIG. 20G is a plan view of the toner bottle from which the cap is removed.

FIG. 21A is a section along line A-A of FIG. 20A;

FIG. 21B is a perspective view of the toner bottle;

FIG. 21C is an enlarged section of a part of the toner bottle shown in FIG. 21A;

FIG. 21D is a section along line A1-A3 of FIG. 23C;

FIG. 22A is a front view demonstrating how the toner bottle guides a toner with raised portions thereof;

FIG. 22B is a front view of the toner bottle rotated 90 degrees from the position of FIG. 22A;

FIG. 22C is a side elevation of the toner bottle shown in FIG. 22A, as seen from the right;

FIG. 22D is a side elevation of the toner bottle shown in FIG. 22B, as seen from the right;

FIG. 23A is a front view of the toner bottle rotated 90 degrees from the position shown in FIG. 23B;

FIG. 23B is a front view of the toner bottle rotated 90 degrees from the position shown in FIG. 23A;

FIG. 23C is a side elevation of the toner bottle shown in FIG. 23A, as seen from the right;

FIG. 23D is a side elevation of the toner bottle shown in FIG. 23B, as seen from the right;

FIGS. 24A-24C each shows a modified form of the toner bottle in a particular view.

This Sheet Has Been Replaced



FIG. 25 is a graph indicative of a relationship between the rotation speed of the toner bottle and the quantity of toner left in the bottle without being discharged;

FIGS. 26A and 26B each demonstrates a particular operation available with a modified collet chuck;

FIG. 27 is a front view of another specific arrangement of the toner supply unit held in a toner replenishing position;

FIG. 28 is a plan view of the toner supply unit shown in FIG. 27;

FIG. 29A is a side elevation of the unit shown in FIG. 27, as seen from the right;

FIG. 29B is a fragmentary enlarged view as seen in a direction A shown in FIG. 28;

FIG. 30 is a front view of the toner supply unit held in a position for mounting a toner bottle;

FIG. 31A is an exploded perspective view of a collet chuck and a core included in the unit of FIG. 27;

FIG. 31B is a front view of the core;

FIGS. 32A and 32B each demonstrates a specific operation of the collet chuck shown in FIG. 31A;

FIG. 33 is a fragmentary enlarged view of a toner bottle for use with the toner supply unit of FIG. 27;

FIG. 34A is a front view showing a modified toner bottle for used with the toner supply unit of FIG. 27;

This Sheet Has Been Replaced



FIG. 34B is a side elevation of the toner bottle, as seen from the right;

FIG. 34C is a section of a gear link associated with the toner bottle;

FIG. 34D is a view as seen in a direction A shown in FIG. 34C;

FIGS. 35A-35E show a sequence of steps for producing a toner bottle in accordance with the present invention;

FIG. 36A is a perspective view of a toner bottle and an annular link included in a modification of the present invention;

FIG. 36B shows the toner bottle inserted into the annular link;

FIGS. 37 and 38 are perspective views each showing a toner bottle and an annular link included in another modification of the present invention;

FIG. 39A is a perspective view showing another specific configuration of the toner bottle;

FIG. 39B is a fragmentary view of the toner bottle;

FIG. 39C is a plan view of the toner bottle;

FIG. 40A is a perspective view showing another specific configuration of the toner bottle;

FIG. 40B is a fragmentary view of the toner bottle;

FIG. 40C is a plan view of the toner bottle;

This Sheet Has Been Replaced



FIG. 41 is a perspective view of a toner bottle and an annular link included in another modification of the present invention;

FIGS. 42A shows the internal arrangement of the annular link shown in FIG. 41;

FIG. 42B is a section of the annular link; and

FIG. 42C shows the toner bottle inserted into the annular link.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

A preferred embodiment of the present invention will be described which is applied to an electrophotographic copier belonging to a family of image forming apparatuses.

Referring to FIG. 1A, the copier has a glass platen 1 on the top thereof for laying a document to be copied. An optical unit 2 is disposed below the glass platen 1 and includes a lamp 2a for illuminating the document, a mirror 2b, and a lens, not shown. A photoconductive element in the form of a drum 3 is rotatably located below the optical unit 2. Arranged around the drum 3 are a main charger 4, a developing unit 5, a transfer charger 6, a cleaning unit 7, a discharger 8 and other conventional units for implementing an electrophotographic process. A fixing unit 9 is positioned at the left-hand side of the drum 3, as viewed in the figure, for fixing a toner image transferred from the drum 3 to a paper

This Sheet Has Been Replaced

by the transfer charger 6. A paper feed section 10 is provided in the lower portion of the copier and loaded with a stack of papers 10a. The papers 10a are sequentially fed from the paper feed section 10 to the drum 3. The operation of this kind of copier is well known in the art and will not be described specifically.

As shown in FIG. 2, the developing unit 5 is a conventional dry process unit using a two component type developer, i.e., a toner and carrier mixture. The developing unit 5 has a casing 5a accommodating developing rollers 11, a paddle wheel 12 for agitation, a mixing roller 13, a separator 14, a horizontally extending screw 15 for agitation, etc. A hopper 16 is contiguous with the casing 5 and disposed above such constituents of the developing unit 5. A toner is supplied from the hopper 16 into the developing unit 5. A screw conveyor 18 is accommodated in the hopper 16 and made up of a shaft 34 and a spiral member 35 affixed to the shaft 34. The screw conveyor 18 conveys a toner from a toner supply unit 17 while agitating it, as will be described in detail later. A toner supply roller 19 is disposed in a portion where the hopper 16 is communicated to the developing unit 5, and it is rotated in response to the output signal of a toner concentration sensor, not shown.

As shown in FIG. 1A, the toner supply unit 17 is located in the upper front portion of the copier and includes a bottle

This Sheet Has Been Replaced

holder 21. The bottle holder 21 plays the role of holding means for holding a toner bottle, or developer container, 20. As shown in FIG. 1B, the bottle holder 21 is mounted on a shaft 22, FIG. 1A, which is located at the right end of the unit 17. The bottle holder 21 is rotatable about 90 degrees about the axis Z of the shaft 22 in a substantially horizontal plane. Specifically, the bottle holder 21 is movable between two positions A and B, as illustrated. In the position A, the left portion of the bottle holder 21 is pulled out toward the front end of the copier to allow the bottle 20 to be mounted thereto. In the position B, the entire unit 17 remains parallel to the front end of the copier. The bottle holder 21 is formed with an opening in the bottom wall thereof for letting a toner to fall therethrough. At least in the position B, the bottom opening of the bottle holder 21 is positioned above a toner receiving portion 16a, FIG. 2, included in the hopper 16 and extending to the front end of the copier. Preferably, the toner supply unit 17 is located inwardly of a front cover, not shown, which covers the front end of the copier; when the front cover is opened, the unit 17 can be pulled out to the position A.

FIG. 3A shows a specific configuration of the toner bottle 20 while FIG. 3B shows a mouth portion 23 forming the outlet of the bottle 20. As shown, the bottle 20 is substantially cylindrical and provided with the mouth portion

This Sheet Has Been Replaced

23 at substantially the center of one end thereof. The mouth portion 23 has a smaller diameter than the cylinder constituting the bottle 20 and has a circular section. In the specific configuration, the mouth portion 23 is formed at the end of a collar 24 extending out from the cylinder 20 and is plugged by a lid 25. A mushroom-like lug 26 protrudes from the center of the lid 25. A spiral guide groove 27 is formed in the inner periphery of the cylinder 20, as in the bottle taught in previously mentioned Japanese Patent Laid-Open Publication No. 59-188678. When the bottle 20 is rotated about the longitudinal axis thereof, the spiral groove 27 guides the toner contained in the bottle 20 toward the mouth portion 23. Annular ribs 28 are formed on the outer periphery of the collar 24. A cap 29 (see FIG. 12A) closes the entire collar 24 while mating with the ribs 28 during the transport of the bottle 20. In this sense, the ribs 28 constitute an engaging portion. For this purpose, the cap 29 is provided with lugs or grooves on the inner periphery thereof which are complementary to the ribs 28.

FIGS. 4A-4C show a mechanism 32 for removing the lid 25 from the mouth portion 23 of the bottle 20. As shown, the mechanism 32 is made up of a collet chuck, or retaining means, 30 and moving means, not shown, for moving the chuck 30 toward and away from the bottle 20. The collet chuck 30 has a chucking portion 33 at the tip thereof and is supported

This Sheet Has Been Replaced



by a hole 31a formed in a wall 31 which forms a part of the bottle holder 21. When the collet chuck 30 is in a free state, the chucking portion 33 is held open, as shown in FIG. 4A. FIG. 4B shows a condition wherein the bottle 20 has been put in a predetermined position on the bottle holder 21. When the collet chuck 30 is moved away from the bottle 20 by the moving means, the peripheral larger diameter portion of the chuck 30 is pressed by the wall of the hole 31a with the result that the chucking portion 33 is squeezed to retain the lug 26 of the lid 25. Subsequently, as shown in FIG. 4C, the chuck 30 moves the lid 25 to a position where the mouth portion 23 of the bottle 20 is fully uncovered, chucking the lug 26 of the lid 25.

The mechanism 32 described above is provided on the toner supply unit 17 and allows the bottle 20 to be mounted to the bottle holder 21 with the mouth portion 23 thereof sealed by the lid 25. Hence, despite that the bottle 20 is set on the bottle holder 21 in a substantially horizontal position, as shown in FIGS. 1A and 1B, the toner is prevented from falling from the mouth portion 23.

When the toner in the bottle 20 is entirely consumed, the empty bottle 20 is taken out of the bottle holder 21. At this instant, the moving means may move the collet chuck 30 toward the bottle 20 to fit the lid 25 in the mouth portion 23. Then, when the bottle 20 is removed from the bottle holder

This Sheet Has Been Replaced


21, the mouth portion 23 will have been closed by the lid 25. This prevents the toner deposited on the mouth portion 23 from falling and smearing the hands and clothes of the person replacing the bottle 20.

FIG. 5A shows a modified form of the mouth portion 23 of the bottle 20. As shown, the cap, e.g., screw cap 29 to be fitted on the color 24 of the mouth portion 23 is formed with a hole 29a in the end wall thereof. The lid 25 having the lug 26 is removably received in the hole 29a of the cap 29.

FIGS. 5B and 5C each shows a modification of the lid 25 shown in FIG. 3B or 5A. It is likely that an inexperienced person intends to remove the lid 25 of a new toner bottle 20 by nipping the lug 26 of the lid 25 without using the collet chuck 30. This is apt to cause a fresh toner from falling from the bottle 20. To eliminate this, the lids 25 shown in FIGS. 5B and 5C are each provided with an annular obstruction 26a or pin-like obstructions 26b around the lug 26. The obstructions 26a and 26b prevent the easy access of the person's fingers to the lug 26.

FIG. 5D shows a cover 150 which is a specific substitute for the obstruction 26a or obstructions 26b. As shown, the cover 150 is made up of a thin flat piece 151 for concealing the portion of the lid 25 surrounding the lug 26, and an annular wall 152 extending out from the outer edge of the thin piece 151. A hole 151a is formed in the center of the

This Sheet Has Been Replaced




piece 151 and slightly greater in diameter than the lug 26 of the lid 25. A number of slits 151b extend radially from the edge of the hole 151a. As shown in FIG. 5E, when the cover 150 is fitted on the lid 25, only the tip of the lug 25 is visible. This prevents even an inexperienced person from mistaking the tip of the lug 25 for a member for removing the lid 25.

The toner supply unit 17 will be described more specifically. FIG. 6 shows the unit 17 held in the position B while FIGS. 7 and 8 shows it including some modified parts. The unit 17 is so constructed as to hold the bottle 20 and rotate it in synchronism with the rotation of the toner supply roller 19. As a result, a fresh toner is sequentially supplemented to the toner receiving portion 16a of the hopper 16a via the mouth portion 23 of the bottle 20.

As shown in FIG. 6, the toner receiving portion 16a is implemented as a top-open trough and extends to the front from a side wall of the hopper 16 located at the operating side. A shaft 34 extends from the inside of the hopper 16 and extends throughout the center of the trough 16a. A spiral member, or toner feed plate, 35 is affixed to the shaft 34 for conveying the toner dropped from the mouth portion 23 of the bottle 20 to the hopper 16. The shaft 34 and spiral member 35 constitute the previously mentioned screw conveyor 18, FIG. 2. The bottle holder 21 is rotatably supported by the

This Sheet Has Been Replaced



front wall of the copier and capable of holding the bottle 20 in a substantially horizontal position. A locking mechanism 36 positions the bottle 20 on the bottle holder 21 in the axial direction of the bottle 20. A motor 37 causes the bottle 20 set on the bottle holder 21 to rotate about the axis thereof. An annular gear link 38 transmits the rotation of the motor 37 to the bottle 20. The previously stated collet chuck 30 chucks the lid 25 of the bottle 20 held on the bottle holder 21. A core 39 is slidably coupled over the collet chuck 30. A cam device 40 moves the collet chuck 30 toward and away from the bottle 20.

As shown in FIGS. 7 and 8, the bottle holder 21 is mounted on a movable bracket 41. A stationary bracket 42 is affixed to the front wall of the copier and has a lower pin 43 and an upper pin 44, FIG. 6, studded thereon. The movable bracket 41 is rotatably supported by the lower pin 43 and rotatably retained by the upper pin 44. Therefore, the bracket 41 is rotatable about a substantially vertical axis extending through the upper and lower pins 43 and 44. As shown in FIG. 8, the stationary bracket 42 is rotatably supported by stays 45 fastened to the front wall by screws and is affixed to the front wall by screws 46.

The bottle holder 21 further includes a lid-like seat 47 for covering the end of the mouth portion 23 of the bottle 20. A cylindrical stop cover 48 is disposed in the seat 47 to cover

This Sheet Has Been Replaced



the mouth portion 23 of the bottle 20 in an air-tight condition. The stop cover 48 has a link receiving portion rotatably accommodating the gear link 38, and a core receiving portion accommodating the core 39. The core receiving portion has a slightly great inside diameter than the mouth portion 23 of the bottle 20. The core receiving portion is formed with an opening 49, FIG. 6, in the bottom wall thereof for letting the toner to fall, and a hole and a boss 50 on the end wall thereof for slidably supporting the collet chuck 30. An auger-like spring 51 is also accommodated in the core receiving portion to constantly bias the core 39 toward the bottle 20. The core 39 shown in FIG. 7 is a modification and has an advantage which will be described later. In FIG. 7, the reference numeral 48a designates a link stop for stopping an annular link formed at the edge of the open end that faces the bottle 20.

The locking mechanism 36 described above positions the bottle 20 in the axial direction of the bottle 20. The mechanism 36 has a locking member 52 and a spring 53 acting on the locking member 52. The locking member 52 is rotatably supported at the base end thereof by a member included in the bottle holder 21, e.g., the stop cover 48 shown in FIGS. 6 and 7. The free end of the locking member 52 is so shaped as to mate with an engaging portion, i.e., a projection or recess formed in the outer periphery of the bottle 20. The

This Sheet Has Been Replaced

spring 53 constantly biases the locking member 52 toward the outer periphery of the bottle 20. In the configuration shown in FIG. 6, the engaging portion of the bottle 20 is implemented as a ring 54 having a right-angled triangular cross-section defined by a substantially vertical contact surface 54a and a slant 54b extending from the surface 54a toward the mouth portion 23. The contact surface 54a may be overhung in such a manner as to incline toward the rear end of the bottle 20.

As shown in FIG. 6 or 8, the motor 37 for driving the bottle 20 may be mounted on the movable bracket 41 together with a gear 55. Alternatively, the motor 37 may be affixed to the copier body at a position where it can be engaged with the gear link 38 when the bottle holder 21 is brought to the position B.

The gear link 38 is formed with gear teeth 56 meshing with the gear 55 associated with the motor 37 and is provided with an inside diameter greater than the outside diameter of the bottle 20. A hole is formed in the end wall of the gear link 38 to allow the collar 24 of the bottle 20 to extend therethrough. As shown in FIG. 6, the above-mentioned end wall of the gear link 38 is provided with, for example, a plurality of radially extending ribs (referred to as link ribs hereinafter) 58 capable of mating with ribs (referred to as

This Sheet Has Been Replaced



bottle ribs hereinafter) 57 provided on the bottle 20 (see FIG. 34D).

In the specific arrangement shown in FIG. 6, the stop cover 48 is formed with an opening in the lower portion thereof to allow the gear 55 of the motor 37 to mesh with the gear teeth 56 of the gear link 38. An annular seal 59 is fitted around the hole of the previously mentioned end wall to seal the gap between the outer periphery of the collar 24 of the bottle 20 and the stop cover 48, thereby preventing the toner coming out of the mouth portion 23 from depositing on, for example, the outer periphery of the bottle 20. At the same time, the seal 59 cleans the outer periphery of the collar 24 when the bottle 20 is replaced with a new toner bottle. The seal 59 is so bent as to be convex toward the collet chuck 30, so that the bottle 20 can be set with ease.

There are also shown in FIG. 7 a seal 60 made of sponge or similar soft material and adhered to the end of the gear link 38, a flexible thin seal (e.g. 0.188 mm thick) 61 adhered to the same end over the seal 60, and a shutter 107 for closing the opening which is formed in the seat 47 of the bottle holder 21 for letting the toner to fall. Usually, the shutter 107 is held in a position where an opening formed therein is aligned with the opening of the seat 47. In the event of maintenance, a serviceman may rotate the shutter

This Sheet Has Been Replaced



107 by holding a thumb piece 108 in order to close the opening of the seat 47.

As shown in FIG. 7, the collet chuck 30 is formed with a plurality of slits 62 to have the chucking portion 33 thereof squeezed by an external force. In the illustrative embodiment, as shown in FIG. 9A, in an unstressed position, the chucking portion 33 is open over a distance D_1 greater than the the maximum diameter d_1 of the tip of the lug 26 of the lid 25. The chuck 30 includes a larger diameter portion 63 adjoining the chucking portion 33, and a smaller diameter portion 64 following the larger diameter portion 63. In an unstressed position, the larger diameter portion 63 has an outside diameter greater than the outside diameter D_2 of the smaller diameter portion 64.

The core 39 is made up of a flange 66 capable of abutting against a flange 65 provided on the lid 25, and a cylindrical slider 67 on and along which the chuck 30 is slidable. The slider 67 has an inside diameter D_3 greater than the outside diameter D_2 of the smaller diameter portion 64 of the chuck 30 and smaller than the outside diameter of the larger diameter portion 63 when the portion 63 is not stressed. In this configuration, when the core 39 is brought to the larger diameter portion 63 of the chuck 30, the former runs onto the latter to reduce the opening of the chucking portion 33, as indicated by a dash-and-dots line in FIG. 9B.

This Sheet Has Been Replaced



The resulting opening D'_1 of the chucking portion 33 is selected to be at least smaller than the maximum diameter d_1 of the lug 26 and, preferably, equal to the diameter d_2 of the root of the lug 26.

The cam device 40 shown in FIG. 6 is constructed as follows. When the bottle holder 21 is moved from the position B to the position A, the cam device 40 moves the chuck 30 away from the bottle 20. Also, when the bottle holder 21 is moved from the position A to the position B, the cam device 40 moves the chuck 30 toward the bottle 20. In the illustrative embodiment, the cam device 40 has a flat cam member 68 and a roller 70 which is rotatably mounted on a chuck shaft 69. The chuck shaft 69 is affixed to the rear end of the chuck 30.

As shown in FIGS. 10A and 10B, the cam member 68 has a first surface 71 for guiding the roller 70 from the side adjoining the center of rotation Z of the bottle holder 21 is located, and a second surface 72 for guiding it from the side opposite to the center of rotation Z. As shown in FIG. 10B specifically, when the bottle holder 21 is moved from the position B to the position A, the first surface 71 guides the roller 70 such that the chuck 30 biased toward the bottle 20 by the spring 51 via the core 39, which is engaged with the larger diameter portion 63 of the chuck 30, moves away from the bottle 20. When the bottle holder 21 is moved from the

This Sheet Has Been Replaced



position A to the position B, the first surface 71 guides the roller 70 such that the chuck 30 biased by the spring 51 moves toward the bottle 20.

As shown in FIG. 11B specifically, just before the movement of the bottle holder 21 from the position A to the position B completes, the core 39 abuts against the edge of the collar 24 of the bottle 20 positioned by the locking mechanism 36. As a result, the core 39 is released from the larger diameter portion 63 of the chuck 30, preventing the force of the spring 51 from acting on the chuck 30. From this instant to the instant when the movement of the bottle holder 21 to the position B completes, the second surface 72 of the cam member 68 guides the roller 70 such that the 30 approaches the bottle 20.

The cam device 40 is located in the vicinity of the axis of rotation of the bottle holder 21, as stated above. Hence, when the person intending to replace the bottle 20 pulls or pushes the bottle holder 21 between the positions A and B, the point of the holder 21 where the resulting force acts and the center of rotation Z are spaced apart a greater distance than the engaging point of the cam 71 or 72 and roller 70 and the center of rotation Z. This allows the bottle holder 21 to be move by a relatively small force, based on leverage.

In the above construction, while an ordinary copying operation is under way, the toner supply unit 17 has the

This Sheet Has Been Replaced



bottle holder 21 thereof located at the position B. To position the bottle holder 21 at the position B, it is preferable that a locking mechanism, e.g., one using a magnet be provided on the front wall of the copier and bottle holder 21. As shown in FIG. 6, in the position B, the bottle 20 set on the bottle holder 21 is positioned with the ring 54 thereof abutted against the end of the locking member 52 of the locking mechanism 36. In this condition, the bottle ribs 57 of the bottle 20 are engaged with the link ribs 58 of the gear link 38. As shown in FIGS. 10A and 10B, the collet chuck 30 assumes a position remotest from the bottle 20. In this position, the core 39 biased by the spring 51 is positioned at the larger diameter portion 63 of the chuck 30 to squeeze the chucking portion 33. As a result, the chucking portion 33 unseals the mouth portion 23 of the bottle 20, chucking the lug 26, i.e., lid 25. The toner receiving portion 16a, FIG. 6, of the hopper 16 is disposed below the opening 49 of the stop cover 48.

As the toner concentration in the developing unit decreases due to repeated development, the toner supply roller 19 starts rotating in response to the output signal of a toner concentration sensor, not shown. At the same time, the motor 37 starts rotating. The rotation of the motor 37 is transmitted to the bottle 20 via the gear 55 and gear link 38, thereby causing the bottle 20 to rotate. The spiral guide groove 27 formed in the inner periphery of the bottle 20

This Sheet Has Been Replaced



sequentially drives the toner toward the mouth portion 23 of the bottle 20 until it falls from the portion 23. The toner dropped from the bottle 20 is received by the toner receiving portion 16a of the hopper 16 via the opening 49 of the stop cover 48. Then, the screw conveyor 18 conveys the toner from the toner receiving portion 16a to the hopper 16 deeper into the copier. This operation is continued until the toner concentration in the developing unit increases to a predetermined value, i.e., until the toner supply roller 19 stops rotating. Alternatively, the bottle 20 may be rotated at an adequate time when the toner in the hopper 16 decreases.

As shown in FIGS. 12A and 12B, a projection 73 may be provided on the toner bottle 20 at a position where it can face a part of the locking member 52 of the above-described positioning mechanism. Then, when the bottle 20 is rotated, the projection 73 contacts a part of the locking member 52 and raises the free end of the member 52 against the action of the spring 53, FIG. 7, but only to such a degree that the member 52 is not fully released from the ring 54. Subsequently, as the projection 73 moves away from the locking member 52, the member 52 is restored and hits against the outer periphery of the bottle 20, causing the wall of the bottle 20 to vibrate. This is successful in increasing the fluidity of the toner in the bottle 20 and, therefore, causing a greater quantity of toner to flow out of the bottle

This Sheet Has Been Replaced




20 via the mouth portion 23. In addition, a minimum of toner is caused to adhere to the inner periphery of the bottle 20.

In FIGS. 12A and 12B, the particular configuration of the bottle 20 around the mouth portion 23 promotes the efficient discharge of the toner from the bottle 20, as will be described in detail later.

To remove the bottle 20 from the bottle holder 21 for replacement or similar purpose, the bottle holder 21 is moved from the position B to the position A. While the bottle holder 21 is in movement, the cam device 40 guides the roller 70 with the first surface thereof such that the collet chuck 30 carrying the lid 25 therewith moves toward the mouth portion 23 of the bottle 20. Consequently, the flange 66 of the core 39 abuts against the edge of the collar 24 of the bottle 20 via the flange 65 of the lid 25. Even after the movement of the core 39 has been restricted by the collar 24, the cam device 40 guides the roller 70 with the second surface thereof to continuously move the chuck 30 until the larger diameter portion 63 of the chuck 30 has been released from the core 39. As a result, the chucking portion 33 is opened due to the restoring force of the chuck 30, releasing the lug 26 of the lid 25. By the procedure described so far, the lid 25 is inserted into the collar 24 of the toner bottle 20, thereby sealing the mouth portion 23. When the bottle holder 21 is fully brought to the position A, the chucking portion 33 of the chuck 30 is

This Sheet Has Been Replaced



open over a distance greater than the maximum diameter D_1 of the lug 26 of the lid 25, as shown in FIGS. 9A, 11A and 11B.

Subsequently, when the bottle holder 21 is held in the position A, the locking member 52 of the locking mechanism 36 is manually pulled up away from the bottle 20 against the action of the spring 53 until the member 52 has been released from the ring 54 of the bottle 20. Then, the bottle 20 is pulled out from the stop cover 48 and taken out from the bottle holder 21.

The locking member 52 is constantly biased toward the bottle 20 by the spring 53. Hence, when the locking member 52 being manually pulled up, as mentioned above, is released, the free end thereof will drop and again mates with the ring 54 of the bottle 20. Therefore, it is necessary to maintain the free end of the locking member 52 in the lifted position in the event when the bottle 20 should be pulled out. To meet this requisite, the bottle 20 should preferably be automatically displaced when the locking member 52 is lifted away from the bottle 20. FIG. 13 shows a specific implementation in which the spring 51 forces out the toner bottle 20 via the core 39 when the bottle 20 is released from the locking mechanism 36. As shown, the height of the collar 24, as well as other factors, is selected such that when the bottle 20 is positioned by the locking mechanism 36, the edge of the collar 24 protrudes a predetermined quantity S from

This Sheet Has Been Replaced




the stop cover 48. In this configuration, at the moment when the locking member 52 is lifted away from the ring 54 of the bottle 20, the core 39 is moved by the spring 51 until the flange 66 thereof hits against the gear link 38. As a result, the bottle 20 is forced out by the predetermined quantity S.

Assume that in the initial state of movement of the core 39 and before the lug 26 of the lid 25 has been fully released from the chucking portion 33 of the collet chuck 30, the core 39 has engaged with the larger diameter portion 63 of the chuck 30 and squeezed the chucking portion 33. Then, the lid 25 is continuously held by the chuck 30, i.e., the mouth portion 23 of the bottle 20 is open even when the bottle 20 is pulled out. As a result, the toner deposited on the inner surface of the mouth portion 23 is apt to fall and smear the hands an cloths. Moreover, when the chucking portion 33 is so squeezed, it is likely that when a new toner bottle 20 is set, the lug 25 of its lid 25 cannot enter the chucking portion 33.

In the light of this, the above-mentioned quantity S should preferably be selected such that even after the flange 66 of the core 39 has abutted against the gear link 38, the core 39 does not contact the larger diameter portion 6 of the chuck 30, thereby maintaining the chucking portion 33 open. Specifically, the gear link 38 should preferably be positioned such that when the bottle 20 is released from the locking mechanism 36, the core 39 abuts against the gear link 38

This Sheet Has Been Replaced



before it engages with the larger diameter portion 63 of the chuck 30. While the gear link 38 is used to restrict the movement of the core 39, it may be replaced with an exclusive member for restriction.

At the position A, the empty bottle 20 is replaced with a new bottle 20. Specifically, a new bottle 20 is filled with a fresh toner and has the mouth portion 23 thereof sealed by a seal 25. The new bottle 20 is mounted to the bottle holder 21 with the head portion thereof facing the stop cover 48. Then, the head portion of the bottle 20 is inserted into the stop cover 48. At this instant, the locking member 52 of the locking mechanism 36 catches the ring 54 of the bottle 20 being moved into the stop cover 48. As a result, the toner bottle 20 is positioned on the bottle holder 21. In the illustrative embodiment, while the bottle 20 is moved deeper into the stop cover 48, the free end of the locking member 52 runs onto the slant 54b of the ring 54. This, coupled with the fact that the ring 54 raises the inclined surface of the member 52, makes it needless to lift the locking member 52 manually.

The core 39 is held in a position where it does not contact the larger diameter portion 63 of the chuck 30 in the stop cover 48, as stated earlier. Hence, the chucking portion 33 of the chuck 30 is left open. It follows that the lug 26 of

This Sheet Has Been Replaced



the lid 25 can be moved into the chucking portion 33 smoothly.

Assume an arrangement wherein when the bottle 20 is forced out by the core 39, as stated previously, the chucking portion 33 of the chuck 30 is closed after the lug 26 of the lid 25 has been released from the chucking portion 33. In such a case, the lid 25 should preferably be configured such that the flange 65 thereof is protruded sufficiently more than the lug 26. Then, when a new bottle 20 is inserted into the stop cover 48, the edge of the color 24 pushes the flange 66 of the core 39 via such a flange 65 of the lid to release the core 39 from the larger diameter portion 63 of the chuck 30, thereby opening the chucking portion 33. In this condition, the lug 26 of the lid 25 enters the chucking portion 33 which is open then.

Thereafter, the bottle holder 21 is moved from the position A to the position B. At this instant, the cam device 40 guides the roller 70 with the first cam surface thereof such that the chuck 30 carrying the lid 25 therewith moves away from the mouth portion 23 of the bottle 20. In the initial stage of movement, the chuck 30 has the larger diameter portion 63 thereof brought into engagement with the core 39 and has the chucking portion 33 squeezed thereby. As a result, the chucking portion 33 chucks the lug 26 of the lid 25. Even after this, the core 39 and larger diameter portion

This Sheet Has Been Replaced



63 are continuously engaged by the force of the spring 51, so that the chucking portion 33 holds the lid 25 continuously. Consequently, the lid 25 is removed from the mouth portion 23 to thereby unseal it. In this way, the bottle holder 21 is fully moved to the position B, as shown in FIGS. 6, 10A and 10B. In the position B, a fresh toner is sequentially supplemented from the bottle 20 while the bottle 20 is in rotation.

As stated above, with the toner supply unit 17 of the embodiment, it is possible to replace the bottle 20 simply by moving the bottle holder 21 and then replacing the bottle 20. At this instant, the toner is prevented from leaking from the mouth portion 23 of the bottle 20.

As shown in FIG. 13B, the flange 65 of the lid 25 should preferably be provided with an outside diameter d_2 which is smaller than the outside diameter d_3 of the collar 24. Otherwise, when the bottle 20 is moved into and out of the stop cover 38, the flange 65 is apt to contact the seal 59 fitted on the inner periphery of the stop cover 38, causing the lid 25 to be removed. Further, as shown in FIG. 13C, the cap 29 is fitted on the bottle 20 over the lid 25. The cap 29 prevents the lid 25 from being accidentally removed from the bottle 20 when the bottle 20 is transported, particularly on highland or by aircraft. In addition, since the cap 29 protects the lid 25, it is not necessary for the lid 25 to be rigidly

This Sheet Has Been Replaced



coupled with the collar 24, reducing the force required of the automatic lid attaching and detaching mechanism.

A modified form of the core 39 shown in FIG. 7 will be described with reference to FIGS. 14A-14E. As shown in FIG. 14A, the core 39 has a cylindrical drum portion 74 having a diameter slightly smaller than the inside diameter of the stop cover 48. Flanges are provided on the circumferential surface of the drum portion 74 to form a plurality of annular recesses. Annular seal members 75, FIGS. 14B and 14C, are fitted in the individual annular recesses of the drum portion 74 and arranged side by side in the axial direction of the drum portion 74. The seal members 75 seal the gap between the outer periphery of the core 39 and the inner periphery of the stop cover 48. As shown in FIG. 14B, each seal member 75 may be implemented as an elongate member having an adhesive layer 75a and having opposite ends thereof abutted against each other. Alternatively, as shown in FIG. 14C, the seal member 75 may be implemented as a ring and adhered to the drum portion 74. Preferably, the seal members 75 having the configuration shown in FIG. 14B should be positioned such that their portions where opposite ends are abutted are deviated in the axial direction of the core 39. Also, the annular seal member 75 shown in FIG. 14C should preferably be constituted by an elastic member 75b enriched in elasticity mainly in the circumferential direction, e.g., a non-

This Sheet Has Been Replaced



foam elastic body, and an elastic body 75c provided on the elastic body 75b and enriched in elasticity mainly in the direction of thickness, e.g., a foam elastic body.

The core 39 shown in FIG. 14A is formed with a boss 77 at the end thereof which abuts against the flange 65 of the lid 25. A hole for the collet chuck 30 to extend is formed throughout the core 39 in the boss 77. The boss 77 also serves to position a flat annular end seal 78 shown in FIG. 14D or 14E when the seal 78 is fitted on the end of the flange by adhesion. The end seal 78 may be implemented by a single material, as shown in FIG. 14D, or by a plurality of annular elements adhered to each other. It is preferable that at least the front end 78a of the end seal 78 be constituted by silicone resin, fluorine resin or similar resin having, for example, small surface energy, so that the toner may not deposit thereon easily.

A reference will be made to FIGS. 15-18 for describing an improved implementation for reducing the force to be manually exerted on the bottle holder 21. Assume that the toner is deposited on the inner periphery of the collar 24 of the bottle 20 and the portion of the lid 25 contacting it. Then, the force necessary for the lid 25 to be inserted into and removed from the mouth portion 23 of the bottle 20 is increased. As a result, the force necessary for the bottle holder 21 to be pushed from the position A to the position B

This Sheet Has Been Replaced



(causing the lid 25 to be removed from the mouth 23 portion) and the force necessary for it to be pulled from the position B to the position A (causing the lid 25 to be inserted into the mouth portion 23) are increased.

The pushing force and pulling force mentioned above were measured with three different types of toner supply units 17 (referred to as types 1 to 3 hereinafter) different in the shape of the collet chuck 30 and that of the core 39, and with toner bottles 20 having various mouth diameters. A toner was deposited on, for example, the inner periphery of the collars 24 of such bottles 20. FIG. 15 is indicative of the results of measurement. In FIG. 15, the abscissa and the ordinate indicate respectively the diameter of the mouth portion 23 of the bottle 20 and the force needed to move the bottle holder 21. The graph includes dash-and-dot lines representative of the results of measurement. Among them, a dash-and-dot line marked with arrows and a dash-and-dot line marked with dots are associated with types 1 and 2, respectively; a dash-and-dot line marked with crosses is associated with type 3. The pushing forces measured with the type 1 are distributed in a region A_1 indicated by a brace, while the pulling forces also measured with the type 1 are distributed in a region B_1. The pushing forces measured with the type 2 are distributed in a region A_2 while the pulling forces measured with the type 2 are distributed in a region

This Sheet Has Been Replaced

B_2. Although distributions measured with the type 3 are not shown in the graph, the pushing forces measured lie in the regions A_1 and A_2 while the pulling forces lie in the regions B_1 and B_2 and below them. Defective insertion occurred in a region C indicated by hatching (enclosed by a horizontal line representative of a force of 2200 g and an inclined line representative of the upper limit of the region A_2).

As FIG. 15 indicates, the required pushing force is greater than the required pulling force and should be, for example, greater than 2 kg. Further, when the pulling force exceeds, for example, 2.2 kg due to the diameter of the mouth portion 23 and the configuration of the collet chuck 30 and core 39, the lid 25 is inserted defectively.

FIG. 16 is a fragmentary view of an improved mechanism which causes, when the lid 25 is attached to or detached from the mouth portion 23 of the bottle 20, the lid 25 to rotate about the axis thereof. As a result, the lid 25 is attached to and detached from the mouth portion 23 smoothly, reducing the pushing force and pulling force. To cause the lid 25 to rotate about the axis thereof, the boss 50 of the stop cover 48, in which the chuck 30 slides, is formed with a cam slit 79 for causing the chuck 30 to rotate while moving toward and away from the bottle 20. A pin 80 is studded on the chuck shaft 69 of the chuck 30 and movably received in the cam slit 79.

This Sheet Has Been Replaced

FIGS. 17A and 17B correspond to FIGS. 10A and 10B, respectively, and show the improved mechanism in a condition wherein the bottle holder 21 is located at the position B. FIG. 10C is an enlarged view of the mechanism, as seen in the direction indicated by an arrow A in FIG. 17B. FIG. 17D is an enlarged view of the mechanism, as seen in the direction indicated by an arrow B in FIG. 17B. As shown, the pin 80 is positioned in the outermost portion of the cam slit 79 formed in the circumferential lowermost portion of the boss 50, which is indicated by a dash-and-dot line L_1 in FIG. 17C. The innermost end of the cam slit 79 assumes a position indicated by a dash-and-dot line L_2, FIG. 10C, which is deviated a predetermined angle α, e.g., 90 degrees from the position L_1. While the pin 80 moves from the outermost portion to the innermost portion of the cam slit 79, as indicated by a dash-and-dots line C in FIG. 17C, the slit 79 causes the pin 80 to rotate the predetermined angle α about the axis of the boss 50, as indicated by FIG. 17D. FIGS. 18A and 18B correspond to FIGS. 11A and 11B, respectively, and show the mechanism in the condition wherein the bottle holder 21 is located at the position A. FIG. 18C is an enlarged view as seen in the direction indicated by an arrow A in FIG. 18G. FIG. 18D is an enlarged view as seen in the direction indicated by an arrow B in FIG. 18B.

This Sheet Has Been Replaced

In operation, when the bottle holder 21 is moved from the position B toward the position A, the chuck shaft 69 of the chuck 30 moves toward the toner bottle 20 while sliding within the boss 50 of the stop cover 48. At the same time, the pin 80 rotates the predetermined angle α about the axis of the boss 50 of the stop cover 48 by being guided by the cam slit 79, as indicated by the line C in FIG. 17C. As a result, the lid 25 held by the chuck 30 is sequentially inserted into the collar 24 of the bottle 20 while rotating about the axis of the boss 50.

Conversely, when the bottle holder 21 is moved from the position A toward the position B, the chuck shaft 69 moves away from the bottle 20 while sliding within the boss 50 of the stop cover 48. At this instant, the pin 80 rotates the angle α about the axis of the boss 50 in the opposite direction by being guided by the cam slit 79. Consequently, the lid 25 held by the chuck 30 is removed from the collar 24 of the bottle 20 while rotating about the axis of the boss 50.

As stated above, the lid 25 is inserted and removed from the mouth portion 23 of the bottle 20 while rotating about the axis of the boss 50 of the stop cover 48. This promotes smooth insertion and removal of the lid 25 from the mouth portion 23 and, therefore, reduces the required forces for pushing and pulling the bottle holder 21, compared to the case wherein the lid 25 does not rotate.

This Sheet Has Been Replaced



Another improved mechanism for reducing the forces necessary for the bottle holder 21 to be pushed and pulled will be described with reference to FIGS. 19A-19D. FIGS. 19A and 19B show a specific configuration of the lid 25 which promotes easy attachment and detachment of the lid 25 to the mouth portion 23 of the toner bottle 20. As shown, the lid 25 has an annular wall portion 81 which contacts the inner periphery of the collar 24, a bottom wall portion 82, and an inclined wall portion 83 connecting the two wall portions 81 and 82. The wall portion 83 is inclined a predetermined angle, preferably less than 45 degrees. The bottom wall portion 82 has a diameter smaller than the outside diameter of the annular wall 81.

Preferably, the inclined wall 83 has a thickness t smaller than the thickness T of the bottom wall 82, e.g., one half of the thickness T ($t \approx 1/2 \cdot T$). As a result, when the collet chuck 30 inserts the lid 25 into the mouth portion 23, the forces f_1 and f'_1 (see FIG. 19C) necessary for the circumferential wall of the lid 25 to press the collar 24 are reduced, compared to a case wherein the thicknesses t and T are equal. Also, when the chuck 30 pulls out the lid 25 from the mouth 23, the forces f_2 and f'_2 (see FIG. 19C) exerted by the collar 24 on the circumferential wall of the lid 25 are reduced. This prevents the lid 25 from being inserted in or


This Sheet Has Been Replaced

pulled out from the mouth portion 23 defectively due to the deformation thereof.

If desired, the surface of the bottom wall portion 82 of the lid 25 that contacts the toner may be provided with undulations. Then, although the toner may have aggregated during storage, it can start being discharged easily when the lid 25 is removed. The undulations may be implemented by wavy ribs formed on the above-mentioned surface of the bottom wall portion 82.

Further, as shown in FIG. 19D, the outer surface of the annular wall portion 81 may be provided with a saw-toothed portion 84. When the lid 25 is inserted into the mouth portion 23, the saw-toothed portion 84 will scrape off the toner deposited on the inner periphery of the collar 24 of the bottle 20 and drive it into the bottle 20. As a result, the force necessary for the lid 25 to be inserted into the collar 24 is maintained constant. This eliminates an occurrence that the force necessary for the lid 25 to be into the mouth portion 23 is increased by 1.5 times due to the toner deposited on the inner surface of the collar 24. For example, a chuck 30 and lid 25 combination could be selected which reduced, when the mouth portion 23 had a diameter of 39. 90 mm, the force for pulling the lid 25 to 950 g at maximum when the toner was not deposited and to 1570 g at maximum even when the toner was deposited. Also, such a combination reduced the force

This Sheet Has Been Replaced



necessary for the lid 25 to be inserted to 1370 g at maximum when the toner was not deposited and to 1770 g at maximum when the toner was deposited.

Referring to FIGS. 20A-24C, a specific configuration of a part of the bottle 20 adjacent the mouth portion 23 will be described which allows the toner to be discharged in a desirable manner. In the figures, the bottle ribs 57 to receive a rotating force from the ring are not shown (see FIGS. 34A and 34B).

Briefly, the bottle 20 shown in the figures is configured such that when the bottle 20 is set on the bottle holder 21 in a substantially horizontal position with the mouth portion 23 oriented sideways, the toner existing in the lower portion of the cylindrical body of the bottle 20 is raised to the mouth portion 23 by the rotation of the bottle 20 and then discharged via the mouth portion 23. As a result, the toner is desirably driven out of the bottle 20 via the mouth portion 23 which has a smaller diameter than the cylindrical body of the bottle 20. Specifically, the end or shoulder of the bottle 20, where the mouth portion 23 is provided, has the inner periphery thereof partly raised to the edge of the mouth portion 23 to thereby form a portion 85 indicated by hatching. The raised portion 85 moves the toner upward when the bottle 20 is in rotation, as will be described specifically later. As shown in FIG. 21A, since the end wall and circumferential

This Sheet Has Been Replaced




wall of the bottle 20 have substantially the same thickness, the internal configuration of the bottle 20 directly appears on the outer periphery also. For this reason, in the other figures (e.g. FIG. 20E), the reference numerals attached to the inner periphery of the bottle 20 are also used to designate the corresponding portions of the outer periphery.

Further, the bottle 20 has another raised portion 86 contiguous with the raised portion 85 in the circumferential direction, as indicated by hatching different in direction from the hatching indicative of the portion 86 in FIG. 21B. Specifically as shown in FIG. 21A, the inner peripheral portion of the circumferential wall contiguous with the raised portion 85 in the circumferential direction is raised toward the axis, or center line of rotation, L of the bottle 20 over the edge of the mouth portion 23. As shown in FIG. 20G, when the bottle 20 is seen from the outside in the axial direction, i.e., along the center line L with the cap and lid thereof removed, the raised portion 86 appears in the mouth portion 23.

Preferably, the contiguous raised portions 85 and 86 should be provided with a ramp surface configuration which protrudes more toward the axis L as the distance thereof from the mouth portion 23 increases. Further, as shown in FIG. 21D, it is preferable that the raised portions 85 and 86 be provided with concavity which at least partly appears, in a section containing the axis L, as a curve whose center of

This Sheet Has Been Replaced



curvature C_1 is close to the axis L. FIG. 21D is a section along line A4-A2 of FIG. 23C and representative of the raised portion 85. FIG. 21 is a fragmentary enlarged view of FIG. 21A and a section along line A1-A3 of FIG. 23C. As shown in FIG.21D, the raised portion 86 should preferably have the end portion thereof provided with convexity appearing, in the section containing the axis L, as a curve whose center of curvature C_2 is remote from the axis L. The curve with the center of curvature C2 allows the toner to be forced out to the collar 24 smoothly. Moreover, it is preferable that the raised portions 85 be contiguous with the spiral guide groove 27. Then, the toner guided along the guide groove 27, which has a constant width, to the vicinity of the mouth portion 23 will be continuously raised to the edge of the mouth portion 23 and then guided to the raised portion 86.

FIG. 24A shows a preferred configuration of a wall *a* forming the guide groove 27 of the bottle 20. As shown, the wall *a* includes a portion *b* for driving the toner in the guiding direction indicated by an arrow A (i.e. toward the mouth portion 23). The portion *b* protrudes toward the axis of the bottle 20 at an angle θ1 substantially perpendicular to the flat inner periphery of the bottle 20, e.g., 80 degrees to 90 degrees. The other portion *c* of the wall *a*, which the toner being conveyed gets over, protrudes toward the axis of the bottle 20 at a small angle θ2, e.g., less than 30 degrees,

This Sheet Has Been Replaced

preferably 10 degrees to 30 degrees and in the guiding direction A. The wall *a* with such a configuration causes the toner to fall from the inner periphery thereof easily while the bottle 21 is in rotation, thereby allowing a minimum of toner to remain in the bottle 20.

How the raised portions 85 and 86 guide the toner will be described with reference to FIGS. 22A-22D and 23A-23D. FIGS. 22C and 23C are side elevations, as viewed from the right, of the bottle 20 shown in front views in FIGS. 22A and 23A, respectively. FIGS. 22D and 23D are side elevations, as viewed from the right, of the bottle 20 shown in front views in FIGS. 22B and 23B, respectively. It is to be noted that FIGS. 22B and 23B show the bottle 20 in a position rotated 90 degrees from the position shown in FIGS. 22A and 23A. The arrow K is indicative of the direction in which the bottle 20 is rotated by the toner supply unit 17.

In the condition shown in FIGS. 22A and 22C, the maximum diameter portion of the shoulder is located at the bottom in the vertical direction. Hence, the guide groove 27 guides the toner to the bottom of the maximum diameter portion of the head portion of the bottle 20. As shown in FIGS. 22B and 22D, when the bottle 20 is rotated 90 degrees in the direction K, the boundary between the maximum diameter portion of the shoulder and the raised portion 85 is positioned at the bottom in the vertical direction; the toner


This Sheet Has Been Replaced



from the guide groove 27 partly rides on the raised portion 85. As shown in FIGS. 23A and 23C, while the bottle 20 is further rotated 90 degrees in the direction K toward the position of FIGS. 23A and 23C, the raised portion 85 raises the toner to the edge of the mouth portion 23 as if it were a spoon. When the bottle 20 is further rotated 90 degrees in the direction K to around the position of FIGS. 23B and 23D, the toner is partly transferred from the raised portion 85 to the inclined raised portion 86. As a result, the toner is guided by the raised portion 86 toward the outside of the bottle 20 in the direction L and then discharged via the mouth portion 23.

As best shown in FIG. 23C, the raised portion 85 itself is provided with a spoon-like concave configuration. When the bottle 20 has such a configuration adjacent the mouth portion 23, the toner powder is prevented from dropping from the mouth portion 23 in masses and raising a cloud in the hopper 16. That is, the toner powder is discharged little by little from the bottle 20 in a loose state. Moreover, hardly any of the toner is left in the bottle 20. In addition, while the bottle 20 is in rotation, only a so-to-speak spoonful of toner is scooped up to the mouth portion 23. As a result, a constant amount of toner is discharged from the mouth portion 23 at all times.

This Sheet Has Been Replaced




As shown in FIG. 24B, two pairs of raised portions 85 and 86 may be formed on the inner periphery of the shoulder of the bottle 20. In this case, the toner will be discharged in a quantity twice as great as the quantity available with a single pair of raised portions 85 and 86 for the same quantity of rotation of the bottle 20.

Further, as shown in FIG. 24C, the outer periphery of the bottle 20 may additionally include a grip portion L_1 having a diameter Φ_1 smaller than the diameter Φ_0 (greater than 100 mm) of the other portion. The outside diameter Φ_1 of the grip portion L_1 should advantageously be 80 mm to 100 mm; the length should advantageously be 80 mm to 100 mm. In FIG. 24C, the wall *a* forming the guide groove 27 has the same inner peripheral configuration as the configuration shown in FIG. 24A. In FIG. 24C, the arrow *a* is indicative of the toner being entrained by the inner periphery of the bottle 20 upward due to the rotation of the bottle 21, while the arrow *b* is indicative of the toner falling therealong.

FIG. 25 is a graph indicative of a relation between the rotation speed (number of rotations per minute) of the bottle 20 during toner supply and the amount of toner left in the bottle 20 without being discharged. As shown, the amount of toner left in the bottle 20 depends on the rotation speed. For example, assuming that the allowable amount of toner to remain in the bottle 20 is up to 50 g, it is preferable to


This Sheet Has Been Replaced



rotate the bottle 20 thirty rotations to forty rotations for a minute. Of course, the adequate rotation speed of the bottle 20 for reducing the amount of remaining toner is determined by, for example, the diameter of the mouth portion 23 and the configuration of the raised portions 85 and 86. In practice, therefore, the adequate rotation speed is determined by experiments beforehand, and the bottle 20 is rotated at such a speed.

In the illustrative embodiment, the toner supply unit 17 is constructed such that the collet chuck 30 retains the lug 26 of the lid 25 when the tip thereof is squeezed. Alternatively, as shown in FIG. 26A, the chuck 30 may cause the tip thereof to abut against the inner periphery of the annular wall of the lid 25 and retain the lid 25 when opened. FIG. 26B shows a condition wherein the tip of such a chuck 30 has been squeezed to release the lid 25. In the chuck 30 shown in FIGS. 26A and 26B, the the slit has a rear portion 87 which is broader than the front or tip portion. A pin 88 is studded in a predetermined position of, for example, the stop cover 48. When the chuck 30 is moved relative to the pin 88 such that the pin 88 enters the narrower tip portion of the slit, the slit, i.e., the tip portion thereof is opened. When the chuck 30 is moved such that the pin 88 enters the rear portion 87 of the slit, the tip of the chuck 30 does not contact the lid 25. FIGS. 26A and 26B show respectively a position matching

This Sheet Has Been Replaced



the position B of the bottle holder 21 and a position matching the position A of the same.

Referring to FIGS. 27-30, a modified form of the toner supply unit 17 will be described. In the figures, the same or similar constituents as or to the constituents of the previous configuration are designated by the same reference numerals.

In the modification, the toner supply unit 17 is also rotatable substantially 90 degrees between the positions A and B in a substantially horizontal plane about the center of rotation Z, FIG. 1B. To rotatably support the bottle holder 21 about the center of rotation Z, the mechanism described previously may also be used. Again, the toner supply unit 17 has the locking mechanism for positioning the bottle 20 on the bottle holder 21, motor 37 for rotating the bottle 20, gear link 38 for transmitting the rotation of the motor 37 to the bottle 20, collet chuck 30 for retaining the lid 25 of the bottle 20, core 39 slidably mounted on the chuck 30, and cam device for moving the chuck 30 back and forth.

The modification differs from the previous embodiment, as follows. To begin with, in the previous embodiment, the cam device for moving the chuck 30 back and forth is located adjacent the center of rotation Z of the bottle holder 21. By contrast, in the modification, the cam device is located at a position comparatively remote from the center of rotation Z in the longitudinal direction of the bottle holder 21.

This Sheet Has Been Replaced

Specifically, as shown in FIGS. 27 and 28, the cam device, generally 93, has a cam member 97 affixed to the portion of a copier front wall 96 that will face the end of the bottle holder 21 remote from the center of rotation Z when the holder 21 is held in the position B (referred to as movable end hereinafter). In addition, the cam device 93 has a roller 95 mounted on the movable end of the bottle holder 21 and provided with a flange. Specifically, the roller 95 is rotatably mounted on a plate 94 which is in turn affixed to a bracket 89. The bracket 89 is affixed to the bottle holder 21 or the movable bracket 41 in the vicinity of the rear end of the bottle 20 (opposite to the end where the mouth portion 23 is positioned) in such a manner as to be movable toward and away from the rear end of the bottle 20. The bracket 89 and an arm member 99 fastened to the rear end of the chuck 30 by a screw 98 are connected together by a shaft 100 extending in the lengthwise direction of the bottle holder 21.

The cam member 97 is made up of a pair of fence members 97a and 97b facing each other. The fence members 97a and 97b guide the roller 95 from the side and support the flange of the roller 95 from below the roller 95. The fence members 97a and 97b are configured such that the distance from the center of rotation Z decreases with the decrease in the distance to the front wall 96 decreases. As shown in FIG. 29B, the front end portion of the fence member 97a is

This Sheet Has Been Replaced

inclined downward toward the front end such that the roller 95 can start contacting it smoothly just before the bottle holder 21 is fully moved from the position A to the position B.

The bracket 89 has a boss 89a on the vertical wall thereof. A rod 90 is slidably received in a hole surrounded by the boss 89a of the bracket 89. An abutment 91 is affixed to the rod 90 and capable of abutting against the rear end of the bottle 20. A spring is loaded between the vertical wall of the bracket 89 and the abutment 91 and constantly biases them away from each other.

In operation, when the bottle holder 21 is held in the position B, the roller with the flange 95 is held in a position closest to the base end of the bottle holder 21 by the cam member 97, as shown in FIGS. 27 and 28. The collet chuck 30 connected to the roller 95 by the shaft 100 is also located at a position closest to the base end of the bottle holder 21. In this condition, the chuck 30 retains the lid 25 at a position remote from the mouth portion 23 of the bottle 20, thereby allowing the toner from being discharged from the mouth portion 23. The bottle 20 has the rear end thereof urged by the abutment 91 and spring 92 toward the base end of the bottle holder 21. The end of the bottle 20 having the mouth portion 23 is abutted against the end of the stop cover 48. Therefore, the bottle 20 is positioned in the longitudinal direction of the bottle holder 21. In this sense, the abutment

This Sheet Has Been Replaced

91, as well as the members associated therewith, constitute a mechanism for positioning the bottle 20 on the bottle holder 21.

When the bottle holder 21 is moved from the position B to the position A, the roller 95 is guided by the cam member 97 toward the movable end of the bottle holder 21. At the same time, the chuck 30 is moved toward the mouth portion 23 of the bottle 20. While the roller 95 is so guided by the cam member 97, the lid 25 held by the chuck 30 is fully inserted into the mouth portion 23 when the distance between the bracket 89 and the stop cover 48 is shorter than the sum of the length of the bottle 20 and the unstressed length of the spring 92 and when the abutment 91 is positioning the bottle 20. If desired, to generate a sufficient force for inserting the lid 25, a cam member, not shown, may be provided against which the rear end of the rod 90 abuts when the bottle holder 21 is moved from the position B to the position A. Then, the rod 90, compared to the bracket 89, will be continuously urged toward the chuck 30 and cause the rear end of the bottle 21 to abut against the abutment 91 of the rod 90.

As the bottle holder 21 is further moved toward the position A, the roller 95 is released from the cam member 97. FIG. 30 shows a condition wherein the bottle holder 21 has arrived at the position A. In this condition, the mouth portion 23 of the bottle 20 has been fully sealed by the lid 25, the

This Sheet Has Been Replaced



chucking portion of the chuck 30 has been opened wide enough to release the lug 26 of the lid 25, and the abutment 91 has been moved away from the rear end of the bottle 20.

Assume that the chuck 30 has been accidentally retracted toward the base end of the bottle holder 21 after the roller 95 had been released from the cam member 97. Then, the larger diameter portion 63 of the chuck 30 (see FIG. 31A) will be engaged with and squeezed by the core 39 which is stopped by the stop cover 48, chucking the lug 26 of the lid 25. This obstructs the removal of the bottle 20 and the insertion of a new bottle 20. In the light of this, as shown in FIG. 28, a cam member 101 is additionally located adjacent the center of rotation Z and provided with a particular cam surface. Specifically, while the roller 95 and cam member 97 are released from each other, the cam surface of the cam member 101 restricts the rear end of the chuck 30 such that the chuck 30 does not retract toward the base end of the bottle holder 21. The cam member 101 may also implement the relative position of the chuck 30 and core 39 for opening the chucking portion 33 thereof, if desired.

When the bottle holder 21 is moved from the position A to the position B, the roller 95 is brought into contact with the cam member 97. Subsequently, the bracket 89 and chuck 30 are each moved toward the base end of the bottle holder 21. As a result, the bottle 20 is positioned on the bottle

This Sheet Has Been Replaced


holder 21 while the lid 25 is removed from the bottle 20. The resulting condition is shown in FIGS. 27 and 28.

Another difference between the previously described toner supply unit 17 and the toner supply unit 17 described above is as follows. The previous toner supply unit 17 maintains the chucking portion 33 of the chuck 30 sufficiently open by setting up a condition which prevents an external force tending to squeeze the portion 33 from acting. By contrast, the toner supply unit 17 described above applies an external force tending to open the chucking portion 33 to the portion 33 positively.

Specifically, as shown in FIG. 31A, the chuck 30 has a slit portion 30a positioned at the rear of a slit portion 30b contiguous with the portion 30a and having a greater width than the portion 30a. The chuck 30 is slidable in the bore formed in the core 39. As shown in FIG. 31B, the inner periphery of the core 39 is formed with projections 102 which are received in the individual (three in this case) slits of the chuck 30. Further, the chuck 30 has a portion 103 even larger in diameter than the larger diameter portion 63, and a substantially vertical abutment or shoulder 104 between the portions 103 and 63.

The core 39 shown in FIG. 31A is substantially identical with the core 39 of FIG. 14A except for the projections 102. In FIG. 31A, the reference numeral 105 designates the

This Sheet Has Been Replaced




opposite ends of each seal member which are abutted against each other.

FIGS. 32A and 32B are views representative of a relation between the above-stated chuck 32 and the core 39 and the position of the chucking portion 33. Specifically, FIG. 32A shows a condition wherein the core 39 is abutted against and stopped by the stop cover 48 (not shown) when, for example, the bottle holder 21 is held in the position A. In this condition, the projections 102 of the core 39 are positioned in the individual narrow slit portions 30a, opening the chucking portion 33 positively by wedging them. On the other hand, FIG. 32B shows a condition wherein the collet chuck 33 is retracted a certain distance due to the contact of the roller 95 and cam member 97 when, for example, the bottle holder 21 is brought from the position A to the position B. In this condition, the boss of the core 39 biased by the spring 51 is stopped by the shoulders 104 of the chuck 30, squeezing the chucking portion 33.

Furthermore, the previous toner supply unit 17 transmits the rotation of the gear link 38 to the bottle 20 by forming the bottle ribs 57 on the end of the bottle 20 having the mouth portion 23 and forming the link ribs 58 on the end of the gear link 38. On the other hand, as shown in FIG. 33, the modified toner supply unit 17 provides the bottle 20 with a recess 106 in place of the bottle rib 57 and causes the link

This Sheet Has Been Replaced



rib 58 to mate with the recess 58. However, a transmission mechanism similar to the mechanism of the previous embodiment may also be used, as shown in FIG. 34A-34D. FIG. 34D shows the inner peripheral configuration of the gear link 38, as viewed in the direction indicated by an arrow A in FIG. 34C.

Assume that the bottle rib 57 is formed on the outer periphery of the bottle 20, as shown in FIGS. 34A and 34B, and that the bottle 20 is molded by use of resin. Then, as shown in FIGS. 35A-35E, it is preferable to form the bottle rib 57 in a parting line portion between mold parts. This allows the bottle 20 to have a relatively thick wall at the portion where the rib 57 is positioned, compared to a case wherein the rib 57 is located in any other position. Any desired number of ribs 57 may be formed if they are provided at the parting portions of cooperative mold parts. Specifically, two parting lines are available with the two bisected mold parts shown in FIGS. 35A-35E. Four parting lines will be available when four mold parts are used.

The recess 106, FIG. 33, formed in the bottle 20 is a specific implementation for transmitting the rotation of the gear link 38 to the bottle 20. Alternatively, at the shoulder of the bottle 20, the part of the outer periphery corresponding to the inner peripheral raised portion 85 may be brought into engagement with the link rib 58 or similar engaging portion

This Sheet Has Been Replaced

of the gear link 38, as shown in FIGS. 36A and 36B by way of example. As shown in FIG. 36A, the gear link 38 has an engaging portion 200 engageable with the portion 85a of the outer surface of the bottle 20 corresponding to the inner raised portion 85. When the head portion of the bottle 20 is inserted into the gear link 38, the engaging portion 200 engages with the portion 85a of the bottle 20. FIG. 36B shows the portion 85a of the bottle 20 and the portion 200 of the gear link 38 abutting against each other. In FIG. 36B, the reference numeral 200a designates the surface of the portion 200 directly contacting the portion 85a. When the portions 85a and 200 substantially perpendicular to the direction of rotation are brought into engagement, the bottle 20 is caused to rotated about the axis thereof together with the gear link 38. This kind of drive transmission makes it needless to form the bottle rib 57 or similar projection on the bottle 20 and, therefore, reduces the production cost of the bottle 20. In addition, drive transmission is insured since the engaging portion 200 of the gear link 38 abuts against the portion 85a of the bottle 20.

As shown in FIG. 37, the bottle 20 may be provided with two contact surfaces on the end thereof. As shown, a contact surface 201 is formed at a position 180 degrees spaced apart from the above-stated portion 85a in the direction of rotation of the bottle 20. The gear link 38 is formed with two


This Sheet Has Been Replaced

engaging portions 200 engaging the surfaces 85a and 201 of the bottle 20, respectively. In this case, the inner periphery of the bottle 20 corresponding to the additional contact surface 201 may also be configured as a raised portion for raising the toner.

FIGS. 38 and 39A-39C show another specific configuration of the bottle 20. As shown, the bottle 20 has two raised portions 85 (represented by the corresponding outer peripheral portions 85a) which are spaced apart 180 degrees in the direction of rotation of the bottle 20 and symmetrical to each other with respect to the axis of the bottle. In the figures, the same portions as the portions of any one of the previous specific configurations are designated by the same reference numerals. In this configuration, while the bottle 20 performs one rotation, the toner is guided twice to the mouth portion 23 along the raised portions 85. Hence, when only a small quantity of toner is left in the bottle 20, it can be discharged from the mouth portion 23 more positively. Moreover, since the bottle 20 and the gear link 38 are engaged with each other at two spaced positions, the sure drive transmission from the link 38 to the bottle 20 is further promoted.

Generally, the characteristic of a toner, e.g., chargeability and color depend on the developing unit. Therefore, it is necessary to prevent a bottle 20 containing a

This Sheet Has Been Replaced



toner different in characteristic from an expected toner from being mounted to the toner supply unit 17. For this purpose, the bottle 20 shown in FIG. 38 and 39A-39C is provided with a lug 204 in a portion thereof extending from the circumferential edge of the color 24 to a shoulder 205. The lug 204 is sized and positioned in matching relation to the characteristic of the toner to be contained in the bottle 20. The end wall of the gear link 38 is formed with a recess in the inner surface thereof which can receive the lug 204 of a bottle 20, containing an expected toner, when the bottle 20 is inserted into the link 38. When a bottle containing an unexpected toner is put on the toner supply unit 17, it cannot be fully inserted into the gear link 38 since the lug 204 does not match the recess of the link 38 in size or position. If desired, the bottle 20 and the gear link 38 may be provided with the recess and the lug, respectively.

The bottle 20 may be provided with three or more engaging portions engageable with the gear link 38 or three or more raised portions 85 in order to more surely transmit the rotation of the link 38 to the bottle 20 or to further promote the discharge of a small quantity of toner remaining in the bottle 20. Again, such engaging portions or raised portions should preferably be located at equally spaced locations in the direction of rotation of the bottle 20. Specifically, FIGS. 40A-40C show the bottle 20 having the raised portions


This Sheet Has Been Replaced



(represented by the outer surfaces 85a corresponding thereto) and engaging portions 203 which alternate with each other at angular intervals of 90 degrees. In these figures, the same portions as the portions of any one of the specific bottle configurations shown and described are designated by the same reference numerals.

The gear link 38 may be provided with a greater number of engaging portions than the bottle 20 in order to promote smooth insertion of the front end of the bottle into the gear link 38. Specifically, as shown in FIG. 41, the bottle 20, like the bottle 20 shown in FIG. 39, has two raised portions 85 spaced about 180 degrees and symmetrical to each other; the outer surfaces 85a of the raised portions 85 are each used as an engaging surface. The end wall of the gear link 38 is formed with four arcuate rims 202 on the inner periphery thereof. The rims 202 are convex toward the axis of the gear link 38, as viewed in a cross-section, and arranged symmetrically with respect to the axis of the link 38. As shown in FIG. 42B, the rims 202 are each inclined an angle α at the upper edge 202b thereof facing the bottle inlet of the gear link 38. Assume that when the bottle 20 is inserted into the gear link 38, the portions of the bottle 20 between the circumferential edge of the collar 24 and the shoulders 205 abut against the upper edges 202b of the rims 202. Then, such portions of the bottle 20 slide on the rims 202 along the

This Sheet Has Been Replaced



inclination α while rotating about the axis thereof. As a result, the bottle 20 is inserted into the gear link 38 smoothly. For smooth insertion, the angle α should preferably be less than 30 degrees. Each rim 202 has a surface 202a facing the axis of the gear link 38. Such surfaces 202a of the rims 202 abut against the outer surfaces 85a of the bottle to transmit the rotation of the gear link 38 to the bottle 20.

In summary, it will be seen that the present invention has various unprecedented advantages, as enumerated below.

(1) Holding means for holding a developer container is rotatable in a substantially horizontal plane for the replacement of a developer container. This eliminates the requisite that holding means and developer container each should have a length smaller than the height of an image forming apparatus, particular to a conventional system which requires the holding means to move both horizontally and vertically. Hence, the developer container can be provided with a sufficient length.

(2) A lid is automatically attached to and detached from a mouth portion included in the developer container. Therefore, only if a person mounts the developer container to the holding means, a developer can be replenished. This not only facilitates the replacement of the developer container, but also prevents the developer from falling from the mouth portion of the developer container. In addition, the developer

This Sheet Has Been Replaced

deposited on, for example, the inner surface of the mouth portion is prevented from falling to the outside.

(3) While the holding means is held in a position for mounting the developer container, the container can be removed with the mouth portion thereof sealed by a lid. This also prevents the developer deposited on the inner surface of the mouth portion from falling to the outside.

(4) The developer can be discharged from the developer container via the mouth portion effectively. In addition, the quantity of developer to be left unused on the inner periphery of the container is reduced.

(5) Drive transmission to the developer container is insured.

(6) In the event of replacement of the developer container, the holding means can be moved between the above-mentioned loading position and a toner replenishing position by a minimum of force. Further, when a motor, solenoid or similar actuator is used to move the holding means, use can be made of a miniature actuator.

(7) The developer container can be surely unlocked in position and, therefore, can be surely released from the holding means.

(8) The developer container can have the mouth portion thereof reduced in size, compared to a conventional container having a mouth portion whose diameter is substantially equal

This Sheet Has Been Replaced



to the maximum diameter of the inner surface of the shoulder. The small sized mouth portion allows a minimum of developer to deposit on the inner surface thereof and prevents the developer from flying around or falling accidentally as far as possible. When the container is transported, for example, the lid closing the mouth portion of the container can be as miniature as the mouth portion. Hence, the lid can be attached and detached by a small force, facilitating manual attachment and detachment. This is also true when a mechanism for attaching and detaching the lid automatically is installed in a developer replenishing device. In addition, such a mechanism is reduced in size.

(9) A shoulder forming a part of the developer container and having a greater diameter than the mouth portion has the inner surface thereof partly raised to the edge of the mouth portion. When the container is rotated, the inner surface of the raised portion raises the developer around the shoulder to the mouth portion, thereby causing the toner to fall via the mouth portion. As a result, the whole developer stored in the container can be used for development. Moreover, since the rate of discharge of the developer via the mouth portion is determined by, for example, the size of the raised portion, the developer can be discharged via the mouth portion stably.

(10) A person intending to replace the developer container is prevented from removing the lid of the developer

This Sheet Has Been Replaced



container by accident. Otherwise, the developer would fall from the container to smear the surroundings.

Various modifications will become possible for those skilled in the art after receiving the teachings of the present disclosure without departing from the scope thereof.

This Sheet Has Been Replaced



Patent Claims

1. A developer container for use with a developer replenishing device having holding means for holding said developer container to allow a developer to be discharged from a mouth portion of said developer container into said developer replenishing device, and driving means for causing said developer container held by said holding means to rotate about an axis of said developer container, said developer container comprising:

a hollow cylindrical main body having said mouth portion on one end, said mouth portion being smaller in diameter than a shoulder portion which forms a circumferential wall adjacent said one end; and

guide means provided on a part of said shoulder portion for guiding said developer stored in said developer container to said mouth portion as said main body is rotated.

2. A developer container as claimed in claim 1, wherein said guide means comprises:

at least one first raised portion formed in a part of said shoulder portion and rising from said shoulder portion to an edge of said mouth portion; and

at least one second raised portion formed in a part of said shoulder portion contiguously with said first raised portion and rising toward the axis of said developer

This Sheet Has Been Replaced



* C L M S *

container, about which said developer container is rotatable, over said edge of said mouth portion.

3. A developer container as claimed in claim 2, wherein said first and second raised portions comprise respectively a first and a second ramp surface portion each rise more in a direction of said axis as a distance from said mouth portion increases.

4. A developer container as claimed in claim 3, wherein said first and second ramp surface portions are recessed such that at least a part thereof appears, in a section along a plane containing said axis, as a curve whose center of curvature is close to said axis.

5. A developer container as claimed in claim 4, wherein said second ramp surface portion has a convex end portion which appears, in a section along said plane, as a curve whose center of curvature is remote from said axis.

6. A developer container as claimed in claim 5, wherein said guide means comprises:

two first raised portions formed in the part of said shoulder portion and rising from said shoulder portion to the edge of said mouth portion, said two first raised portions being provided on said shoulder portion at two positions 180 degrees spaced apart from each other in a direction of rotation of said developer container; and

This Sheet Has Been Replaced

* C L M S *

two second raised portions formed in the part of said shoulder portion contiguously with said two first raised portions respectively and rising toward the axis of said developer container over the edge of said mouth portion, said two second raised portions being provided on said shoulder at two positions 180 degrees apart from each other in the direction of rotation of said developer container.

7. A developer container as claimed in claim 1, wherein the axis of said developer container is aligned with an axis of said mouth portion of said developer container.

8. A developer container as claimed in claim 1, wherein said mouth portion of said developer container has a circular section.

9. A developer container as claimed in claim 5, wherein at least one spiral guide groove is formed in inner periphery of a circumferential wall of said developer container for guiding said developer to said first and second ramp surface portions.

10. A developer container as claimed in claim 9, wherein said guide groove comprises:

a first inclined wall which said developer gets over; and

a second inclined wall for conveying said developer from said first inclined wall to said first and second ramp surface portions.

This Sheet Has Been Replaced

* C L M S *

11. A developer container as claimed in claim 9, wherein said main body is formed with a grip portion smaller in diameter than said shoulder portion.

12. A developer container as claimed in claim 2, further comprising a driven portion engageable with a drive portion of said driving means for causing said developer container to rotate.

13. A developer container as claimed in claim 12, wherein said driven portion comprises a projection formed on said one end of said main body and engageable with an engaging member included in said drive portion.

14. A developer container as claimed in claim 12, wherein said driven portion comprises a recess formed in said one end of said main body and engageable with an engaging member included in said drive portion.

15. A developer container as claimed in claim 12, wherein said driven portion comprises an outer surface of said first raised portion engageable with an engaging portion included in said drive portion.

16. A developer container as claimed in claim 15, wherein said driven portion further comprises a contact surface engageable with said engaging portion of said drive portion and provided on said shoulder portion at a position 180 degrees spaced apart from said outer surface of said first raised portion in a direction of rotation of said

This Sheet Has Been Replaced



developer container, said contact surface having a function for guiding said developer to said mouth portion.

17. A developer container as claimed in claim 2, further comprising a positioning portion to be positioned on said holding means by a locking member included in said holding means.

18. A developer container as claimed in claim 17, wherein said positioning portion comprises an engaging portion formed in a predetermined position on an outer surface of a circumferential wall of said main body and engageable with said locking member.

19. A developer container as claimed in claim 18, wherein said engaging portion is convex.

20. A developer container as claimed in claim 18, wherein said engaging portion is concave.

21. A developer container as claimed in claim 17, further comprising a projection formed on an outer surface of said circumferential wall and facing said positioning portion, said projection causing said locking member of said holding means to hit against said outer surface of said circumferential wall as said developer container is rotated.

22. A developer container as claimed in claim 2, further comprising an annular collar protruding outward from said mouth portion of said developer container.

This Sheet Has Been Replaced



* C L M S *

23. A developer container as claimed in claim 22, wherein a plurality of projections are formed on an outer surface of a circumferential wall of said collar.

24. A developer container as claimed in claim 22, further comprising a lid for closing said mouth portion.

25. A developer container as claimed in claim 24, wherein said lid comprises a bottom wall portion to seal said mouth portion, and a circumferential wall portion to fit in said mouth portion.

26. A developer container as claimed in claim 25, wherein said lid comprises a lug extending out from substantially the center of said bottom wall portion to be chucked when said lid is attached or detached.

27. A developer container as claimed in claim 26, wherein said lid further comprises preventing means located in a space between an inner surface of said circumferential wall and said lug for preventing a person from nipping said lug.

28. A developer container as claimed in claim 27, wherein said preventing means comprises an annular obstruction surrounding said lug.

29. A developer container as claimed in claim 27, wherein said preventing means comprises a plurality of elongate pin-like members studded around said lug.

This Sheet Has Been Replaced

30. A developer container as claimed in claim 27, wherein said preventing means comprises a concealing member concealing said lug.

31. A developer container as claimed in claim 30, wherein said concealing member comprises a thin flat piece concealing neighborhood of said lug. and an annular portion formed integrally with an outer peripheral portion of said thin flat piece.

32. A developer container as claimed in claim 31, wherein said thin flat piece is formed with a hole at the center thereof which is slightly greater in diameter than said lug, and a number of slits extending radially outward from said hole.

33. A developer container as claimed in claim 25, wherein said lid further comprises a connecting portion connecting said bottom wall portion and said circumferential wall portion and inclined in a direction in which said lid may be removed.

34. A developer container as claimed in claim 33, wherein said connecting portion is thinner than said bottom wall.

35. A developer container as claimed in claim 33, wherein said lid further comprises a portion having a saw-toothed section and formed on a surface of said circumferential wall to fit in said mouth portion.

This Sheet Has Been Replaced

36. A toner bottle for use with a toner replenishing device having a bottle holder into which a mouth portion of said toner bottle may fit for discharge of a toner in said toner bottle into said toner replenishing device, and a drive unit which rotatably drives said toner bottle when said toner bottle is mounted to said toner replenishing device, said toner bottle comprising:

a main body comprising a substantially hollow container having, adjacent one end of said toner bottle, a first diameter portion;

a discharge mouth at said one end, said discharge mouth comprising said mouth portion and having a second diameter substantially smaller than said first diameter; and

a circumferential and radially extending ramp surface configuration of the peripheral surface of said main body at said one end and connecting radially between said first diameter portion and a radial position no greater than said second diameter portion.

37. A toner bottle as claimed in claim 36, wherein said ramp surface portion rises to a radial position smaller than said first diameter so as to define a metering edge above which a metered amount of toner must flow to reach said mouth position.

This Sheet Has Been Replaced

38. A toner bottle as claimed in claim 37, wherein said ramp surface portion is curved in the circumferential direction..

39. A toner bottle as claimed in claim 38, wherein said ramp surface portion is concavely shaped to define a toner holding spoon portion.

40. A toner bottle for use with a toner replenishing device having a bottle holder into which a mouth portion of said toner bottle may fit for discharge of a toner in said toner bottle into said toner replenishing device, and a drive unit which rotatably drives said toner bottle about a longitudinal axis thereof when said toner bottle is mounted to said toner replenishing device, said toner bottle comprising:

a main body comprising a substantially hollow container; and

a rotational force transfer projection or recess on a radially extending surface of said main body and cooperating with said bottle holder for transferring rotation of said bottle holder to said toner bottle.

41. A toner bottle for use with a toner replenishing device having a mouth portion for discharge of toner in said toner bottle into said toner replenishing device, and a drive unit which rotatably drives said toner bottle when said toner bottle is mounted to said toner replenishing device, said toner bottle comprising:

This Sheet Has Been Replaced

* C L M S *

a main body comprising a substantially hollow container having, adjacent one end of said bottle, a first diameter portion;

a discharge mouth at said one end, said discharge mouth comprising said mouth portion and having a second diameter substantially smaller than said first diameter; and

a circumferential and radially extending ramp surface configuration of said main body at said one end and connecting radially between said first diameter portion and a radial position no greater than said second diameter portion such that a controllable quantity of toner in said toner bottle is raised radially from said first diameter portion to said second diameter portion for feeding said controllable quantity of toner to said discharge mouth when said toner bottle is rotated by said drive unit.

42 A toner bottle as claimed in claim 41, further comprising said toner in said bottle.

43. A toner bottle as claimed in claim 41, further comprising a rotation prevention projection on a radially extending surface of said main body adjacent said one end.

44. A toner bottle as claimed in claim 43, further comprising a spiral member formed on said main body for conveying said toner toward said mouth portion.

This Sheet Has Been Replaced

45. A toner bottle as claimed in claim 44, wherein said spiral member defines an edge of said ramp surface configuration.

46. A device for replenishing a developing device of an image forming apparatus with a developer, comprising:

a developer container containing a developer and having a mouth portion; and

holding means communicated to a developer replenishing section for holding said developer container while orienting said mouth portion toward said developer replenishing section;

said holding means being rotatable about one end in a substantially horizontal plane.

47. A device as claimed in claim 46, further comprising detaching means for detaching a lid from said developer container which is held by said holding means with said mouth portion closed by said lid.

48. A device as claimed in claim 47, further comprising attaching means for attaching said lid to said mouth portion of said developer carrier to thereby seal said mouth portion.

49. A device as claimed in claim 48, wherein said holding means is movable between a first position where said developer container may be mounted to said holding means easily, and a second position where said holding means is communicable to said developer replenishing section.

This Sheet Has Been Replaced

* C L M S *

50. A device as claimed in claim 49, further comprising control means for controlling said detaching means and said attaching means such that, at least when said holding means is located at said first position, said lid is fully attached to said mouth portion while, at least when said holding means is located at said second position, said lid is fully detached from said mouth portion.

51. A device as claimed in claim 49, wherein said detaching means and said attaching means each comprises :

retaining means selectively assuming an operative position for retaining said lid or an inoperative position for releasing said lid; and

moving means for moving at least one of said retaining means and said developer container toward and away from the other.

52. A device as claimed in claim 51, further comprising:

urging means for urging said developer container toward said mouth portion in a direction for causing said retaining means or said developer container to move; and

positioning means for positioning said developer container in contact with said mouth portion.

53. A device as claimed in claim 52, further comprising driving means for causing said developer container held by said holding means to rotate about a longitudinal axis thereof.

This Sheet Has Been Replaced

54. A device as claimed in claim 53, wherein said driving means comprises a motor, and transmitting means for transmitting rotation of said motor to said developer container.

55. A device as claimed in claim 54, wherein said transmitting means comprises an annular gear link rotatable about said axis of said developer container, and comprising an engaging portion engageable with an engaging portion formed on a shoulder portion of one end, adjacent said mouth portion, of a hollow cylindrical main body of said developer container.

56. A device as claimed in claim 55, wherein said engaging portion of said gear link comprises an link rib engageable with a bottle rib formed on said one end of said developer container where said engaging portion is provided.

57. A device as claimed in claim 55, wherein said engaging portion of said gear link comprises an engaging portion engageable with an outer surface of at least one raised portion which is formed in a part of said shoulder portion and raised from said shoulder portion of said main body to an edge of said mouth portion.

58. A device as claimed in claim 57, wherein said engaging portion of said gear link is further engageable with a contact surface provided on said shoulder portion at a position 180 degrees spaced apart from said outer surface of said raisd portion in a direction of rotation of said developer

This Sheet Has Been Replaced

* C L M S *

container, said contact surface having a function for guiding said developer to said mouth portion.

59. A device as claimed in claim 57, wherein said engaging portion of said gear link comprises two engaging portions engageable with outer surfaces of two raised portions provided on said shoulder portion at two positions 180 degrees apart from each other in a direction of rotation of said developer container.

60. A device as claimed in claim 51, further comprising rotating means for rotating said retaining means about said longitudinal axis of said developer container when said lid is detached from or attached to said mouth portion.

61. A device as claimed in claim 51, further comprising a cam device for causing said moving means to move when said image forming apparatus and a predetermined portion of said holding means are moved relative to each other between said first and second positions.

62. A device as claimed in claim 61, further comprising restricting means for restricting movement of said moving means at said first position such that said holding means urges said lid against said mouth portion.

63. A device as claimed in claim 61, wherein said holding means is rotatable about a shaft adjoining one end of said holding means, said cam device adjoining said shaft.

This Sheet Has Been Replaced

64. A device as claimed in claim 48, wherein said detaching means comprises:

a collet chuck for retaining said lid by chucking a lug extending out from said lid;

moving means for causing at least one of said collet chuck and said developer container to move toward and away from the other; and

control means for opening, when said collet chuck and said developer carrier are spaced apart a predetermined distance, a chucking portion of said collet chuck to allow said lug to enter, and squeezing, as the distance is increased by said moving means, said chucking portion to retain said lug of said lid.

65. A device as claimed in claim 64, wherein said control means comprises:

a larger diameter portion on periphery of said collet chuck;

a core slidably coupled over a smaller diameter portion of said collet chuck opposite to said chucking portion with respect to said larger diameter portion;

biasing means for constantly biasing said core toward said mouth portion of said developer container;

an engaging portion on said core for squeezing said chucking portion of said collet chuck; and

This Sheet Has Been Replaced

restricting means for restricting movement of said core against a force of said biasing means.

66. A device as claimed in claim 65, further comprising:

positioning means for positioning, against the force of said biasing means, said developer container held by said holding means at a position where an edge of said mouth portion functions as said restricting means; and

a restricting member functioning, when said developer container is removed from said holding means, as said restricting means by restricting movement of said core at a position remote from said edge of said mouth portion of said developer container which is positioned by said positioning means.

67. A device as claimed in claim 66, wherein an engaging portion is formed on a circumferential wall of said developer container, said positioning means being movable between an operative position for causing said engaging portion to engage with said engaging portion of said developer container and an inoperative position remoter from said circumferential wall than said operative position.

68. A device as claimed in claim 64, wherein said detaching means further comprises:

a cover supporting said collet chuck in such a manner as to allow said collet chuck to move toward and away from said developer container which is held in a predetermined position

This Sheet Has Been Replaced

* C L M S *

of said holding means, said cover comprising an end wall having a hole throughout which said collet chuck extends, and a circumferential wall surrounding said collet chuck;

a core slidably coupled over said collet chuck and constantly biased toward said developer container, said core comprising an end portion capable of abutting against a flange included in said lid; and

an end seal for sealing a gap between said end portion and said flange of said lid.

69. A device as claimed in claim 68, wherein said end seal is provided with a multi-stage seal structure.

70. A device as claimed in claim 69, wherein said end seal comprises a plurality of elongate rectangular seal elements each having opposite ends thereof abutted against each other while surrounding said core, said seal members, which adjoin in an axial direction of aid core, being deviated, in a circumferential direction of said core, from each other in the position where the opposite ends are abutted.

71. A device as claimed in claim 68, wherein at least a surface of said end seal is made of 4-fluoro ethyrene polymer.

72. A device as claimed in claim 68, wherein said end seal comprises an annular seal member made up of a first elastic material enriched in elasticity mainly in a circumferential direction and and a second elastic material provided on said first elastic material and enriched in

This Sheet Has Been Replaced

* C L M S *

elasticity mainly in a direction of thickness, said seal member being fitted on a circumferential surface of said core.

73. A device as claimed in claim 48, wherein said attaching means comprises:

a collet chuck for chucking a lug extending out from said lid;

moving means for causing at least one of said collet chuck and said developer container to move toward and away from the other; and

releasing means for opening a chucking portion of said collet chuck to release said lug when or before or after a distance between said collet chuck and said developer container is reduced by said moving means to fully seal said mouth portion by said lid retained by said collet chuck.

74. A device as claimed in claim 73, wherein said releasing means comprises:

a core slidably mounted on said collet chuck and constantly biased by biasing means toward said mouth portion of said developer container;

a projection on said core and received in a slit formed in said collet chuck, said projection wedging, when brought to a rear narrow portion of said slid, said collet chuck to thereby open a chucking portion of said collet chuck; and

This Sheet Has Been Replaced



restricting means for restricting, when said distance is reduced by said moving means until or before or after said lid fully closes said mouth portion, movement of said core against a force of said biasing means to thereby displace said projection from a broad portion of said lid to said narrow portion.

75. A device as claimed in claim 73, wherein said attaching means further comprises:

a cover supporting said collet chuck in such a manner as to allow said collet chuck to move toward and away from said developer container which is held in a predetermined position of said holding means, said cover comprising an end wall having a hole throughout which said collet chuck extends, and a circumferential wall surrounding said collet chuck;

a core slidably coupled over said collet chuck and constantly biased toward said developer container, said core comprising an end portion capable of abutting against a flange included in said lid; and

an end seal for sealing a gap between said end portion and said flange of said lid.

76. A device as claimed in claim 75, wherein said end seal is provided with a multi-stage seal structure.

77. A device as claimed in claim 76, wherein said end seal comprises a plurality of elongate rectangular seal elements each having opposite ends thereof abutted against

This Sheet Has Been Replaced



* C L M S *

each other while surrounding said core, said seal members, which adjoin in an axial direction of said core, being deviated, in a circumferential direction of said core, from each other in the position where the opposite ends are abutted.

78. A device as claimed in claim 77, wherein at least a surface of said end seal is made of 4-ethyrene fluoride resin.

79. A device as claimed in claim 77, wherein said end seal comprises an annular seal member made up of a first elastic material enriched in elasticity mainly in a circumferential direction and and a second elastic material provided on said first elastic material and enriched in elasticity mainly in a direction of thickness, said seal member being fitted on a circumferential surface of said core.

This Sheet Has Been Replaced

ABSTRACT OF THE DISCLOSURE

DEVELOPER REPLENISHING DEVICE AND DEVELOPER CONTAINER FOR USE THEREWITH

A developer replenishing device for replenishing a developing device with a developer, and a developer container for use therewith. The developer container, or toner bottle, has a mouth portion at one end thereof which is smaller in diameter than a hollow cylindrical main body. At the end of the bottle provided with the mouth, a shoulder has the inner periphery thereof partly raised to the edge of the mouth portion to form a raised portion for scooping up a toner. In addition, a part of the inner periphery of the circumferential wall of the bottle which is contiguous with the raised portion is also raised toward the axis of the bottle about which the bottle is rotatable, thereby forming another raised portion. When the bottle is mounted to a bottle holder, which is included in the replenishing device, substantially horizontally with the mouth portion oriented sideways, the bottle is rotated to raise the toner from the bottom of the main body to the mouth portion. As a result, the toner is discharged to the outside via the mouth portion smoothly.

This Sheet Has Been Replaced



FIG. 1A





FIG. 1B



This Sheet Has Been Replaced




FIG. 2

This Sheet Has Been Replaced

FIG. 3A





FIG. 3B



This Sheet Has Been Replaced

FIG. 4A




FIG. 4B





FIG. 4C



This Sheet Has Been Replaced

FIG. 5A




FIG. 5B




FIG. 5C




FIG. 5D





FIG. 5E



This Sheet Has Been Replaced





FIG. 6


This Sheet Has Been Replaced

FIG. 7



This Sheet Has Been Replaced

FIG. 8



This Sheet Has Been Replaced

FIG. 9A





FIG. 9B



This Sheet Has Been Replaced

FIG. 10A





FIG. 10B



This Sheet Has Been Replaced

FIG. 11A





FIG. 11B



This Sheet Has Been Replaced

FIG. 12A






FIG. 12B



This Sheet Has Been Replaced

FIG. 13A



This Sheet Has Been Replaced

FIG. 13B





FIG. 13C



This Sheet Has Been Replaced

FIG. 14A




FIG. 14B




FIG. 14C




FIG. 14D





FIG. 14E



This Sheet Has Been Replaced

FIG. 15





FIG. 16



This Sheet Has Been Replaced

FIG. 17A




FIG. 17B




FIG. 17D





FIG. 17C



This Sheet Has Been Replaced

FIG. 18A




FIG. 18B




FIG. 18C





FIG. 18D



This Sheet Has Been Replaced

FIG. 19A




FIG. 19B




FIG. 19C





FIG. 19D



This Sheet Has Been Replaced




FIG. 20A




FIG. 20B




FIG. 20C




FIG. 20D

FIG. 20E




FIG. 20F





FIG. 20G



This Sheet Has Been Replaced



FIG. 21A




FIG. 21B




FIG. 21C





FIG. 21D



This Sheet Has Been Replaced

FIG. 22A




FIG. 22C




FIG. 22B





FIG. 22D



This Sheet Has Been Replaced

FIG. 23A




FIG. 23B




FIG. 23C





FIG. 23D



This Sheet Has Been Replaced

FIG. 24A




FIG. 24B





FIG. 24C



This Sheet Has Been Replaced

FIG. 25




FIG. 26A





FIG. 26B



This Sheet Has Been Replaced





FIG. 27

This Sheet Has Been Replaced

FIG. 28



This Sheet Has Been Replaced

FIG. 29A





FIG. 29B



This Sheet Has Been Replaced




FIG. 30

This Sheet Has Been Replaced

FIG. 31A





FIG. 31B



This Sheet Has Been Replaced

FIG. 32A






FIG. 32B



This Sheet Has Been Replaced

FIG. 33



This Sheet Has Been Replaced

FIG. 34A





FIG. 34B



This Sheet Has Been Replaced

FIG. 34C




FIG. 34D




FIG. 35A




FIG. 35B




FIG. 35C




FIG. 35D





FIG. 35E



This Sheet Has Been Replaced

FIG. 36A





FIG. 36B



This Sheet Has Been Replaced

FIG. 37





FIG. 38



This Sheet Has Been Replaced

FIG. 39A




FIG. 39B





FIG. 39C



This Sheet Has Been Replaced

FIG. 40A




FIG. 40B






FIG. 40C



This Sheet Has Been Replaced

FIG. 41



This Sheet Has Been Replaced

FIG. 42A




FIG. 42B





FIG. 42C



This Sheet Has Been Replaced

REPLACED SHEETS SG
☐ Description : paged ..... to paged .....
☑ Claim(s) : paged 73 to paged 85
☐ Drawing(s) : paged ..... to paged .....
☐ Abstract : paged 86 to paged —

REPLACEMENT SHEETS SG
☑ Description : paged 1 to paged 65
☑ Claim(s) : paged 66 to paged 85
☑ Drawing(s) : paged 1/40 to paged 40/40
☑ Abstract : paged 86 to paged —
DATE OF RECEIPT 19 FEB 1997

DEVELOPER REPLENISHING DEVICE AND DEVELOPER CONTAINER FOR USE THEREWITH

REPLACEMENT SHEET
19 FEB 1997

BACKGROUND OF THE INVENTION

The present invention relates to a developing device included in a copier, facsimile apparatus, printer or similar image forming apparatus and, more particularly, to a developer replenishing device for replenishing the developing device with a developer, and a developer container for use therewith.

There has been extensively used a copier, facsimile apparatus, printer or similar electrophotographic image forming apparatus which electrostatically forms a latent image on a photoconductive element, develops the latent image with charged color particles, i.e., developer, and then transfers the developed image to a paper. It is a common practice with this type of apparatus to supplement a fresh developer when a developer stored in a vessel is consumed. A device for replenishing the developer may be implemented with a hollow cylindrical container storing the developer, as taught in, for example, Japanese Patent Laid-Open Publication (Kokai) Nos. 59-188678 and 60-146265. The container is substantially entirely open at one end thereof to form a

REPLACEMENT SHEET
19 FEB 1997

developer outlet and is rotated about the longitudinal axis thereof to sequentially discharge the developer, or powder, to the vessel of the image forming apparatus via the outlet. To replace the container with a new container filled with a fresh developer, a holder positioned horizontally on the body of the image forming apparatus is rotated downward to a vertical position about one end thereof. In this condition, the empty container is removed from the holder, and then a new container is mounted to the holder. Subsequently, the holder is again rotated to the horizontal position where the new container can replenish the apparatus with the developer. Before the new container is put on the holder maintained in the vertical position, the container is positioned such that the opening, or developer outlet, thereof faces upward, and then a cap closing the opening is removed. The container without the cap is mounted to the holder with the opening facing upward, so that the powder filling the container may not fall.

However, the prerequisite with the conventional scheme described above is that the length of the holder should not be greater than the height of the apparatus since the holder has to be rotated between the horizontal position and the vertical position about one end thereof. Generally, the apparatus is provided with as small a height as possible to meet the demand for a miniature configuration, requiring the holder

REPLACEMENT SHEET
19 FEB 1997

and, therefore, the container to be as short as possible. As a result, the quantity of developer available with a single container is reduced, resulting in the frequent replacement of the container. In any case, the conventional replenishing device cannot be reduced in size and suffers from design limitations in relation to the internal arrangement of an image forming apparatus.

In the light of the above, we conducted a series of studies and experiments in order to implement an arrangement for allowing a person to replace the cylindrical container while maintaining the holder in the horizontal position. However, since the container is substantially fully open at one end thereof, the developer stored therein falls via the outlet of the container when the container is mounted to the holder. We, therefore, have proposed in Japanese Patent Laid-Open Publication No. 3-2881 a developer replenishing device using a container which is closed at both ends thereof and formed with a developer outlet in the circumferential wall thereof adjacent one of the closed ends. This kind of container is placed on a holder with the outlet facing upward. However, considering the fact that an image forming apparatus is used by ordinary clerks, it is likely that the container is inadvertently mounted to the holder with the outlet facing downward. Then, the developer will fall from the container and smear the apparatus and floor. In addition,

REPLACEMENT SHEET
19 FEB 1997

a dead space is produced between the outlet and the adjoining end of the container, requiring the container to be provided with an additional length matching the dead space.

SUMMARY OF THE INVENTION

It is, therefore, an object of the present invention to provide a new and improved developer replenishing device free from the drawbacks discussed above.

It is another object of the present invention to provide a developer replenishing device which prevents a developer from falling from a container despite that the container is set in a horizontal position.

It is another object of the present invention to provide a new and improved developer container for use with such a developer replenishing device.

It is another object of the present invention to provide a developer container capable of replenishing a developing device installed in an image forming apparatus with all the developer stored therein.

In accordance with the present invention, in a developer container for use with a developer replenishing device a holder for holding the developer container to allow a developer to be discharged from a mouth portion of the developer container into the developer replenishing device, and a drive unit for causing the developer container held by

REPLACEMENT SHEET
19 FEB 1997

the holder to rotate about the axis thereof, there is provided a hollow cylindrical main body having the mouth portion on one end. The mouth portion is smaller in diameter than a shoulder portion which forms a circumferential wall adjacent the one end. A guide portion is provided on a part of the shoulder portion for guiding the developer stored in the developer container to the mouth portion.

Also, in accordance with the present invention, in a toner bottle for use with a toner replenishing device having a bottle holder into which a mouth portion of the toner bottle may fit for discharge of a toner in the toner bottle into the toner replenishing device, and a drive unit which rotatably drives the toner bottle when the toner bottle is mounted to the toner replenishing device, there are provided a main body comprising a substantially hollow container having, adjacent one end of the toner bottle, a first diameter portion, a discharge mouth at the one end, the discharge mouth comprising the mouth portion and having a second diameter substantially smaller than the first diameter, and a circumferential and radially extending ramp surface configuration of the peripheral surface of the main body at the one end and connecting radially between the first diameter portion and a radial position no greater than the second diameter portion.

REPLACEMENT SHEET
19 FEB 1997

Further, in accordance with the present invention, in toner bottle for use with a toner replenishing device having a bottle holder into which a mouth portion of the toner bottle may fit for discharge of a toner in the toner bottle into the toner replenishing device, and a drive unit which rotatably drives the toner bottle about a longitudinal axis thereof when the toner bottle is mounted to the toner replenishing device, there are provided a main body comprising a substantially hollow container, and a rotational force transfer projection or recess on the radially extending surface of the main body and cooperating with the bottle holder for transferring the rotation of the bottle holder to the toner bottle.

Moreover, in accordance with the present invention, in toner bottle for use with a toner replenishing device having a mouth portion for discharge of toner in the toner bottle into the toner replenishing device, and a drive unit which rotatably drives the toner bottle when the toner bottle is mounted to the toner replenishing device, there are provided a main body comprising a substantially hollow container having, adjacent one end of the bottle, a first diameter portion, a discharge mouth at the one end, the discharge mouth comprising the mouth portion and having a second diameter substantially smaller than the first diameter, and a circumferential and radially extending ramp surface configuration of the main body at the one end and connecting radially between the first

REPLACEMENT SHEET
19 FEB 1997

diameter portion and a radial position no greater than the second diameter portion such that a controllable quantity of toner in the toner bottle is raised radially from the first diameter portion to the second diameter portion for feeding the controllable quantity of toner to the discharge mouth when the toner bottle is rotated by the drive unit.

In addition, in accordance with the present invention, a device for replenishing a developing device of an image forming apparatus with a developer comprises a developer container containing a developer and having a mouth portion, and a holder communicated to a developer replenishing section for holding the developer container while orienting the mouth portion toward the developer replenishing section. The holder is rotatable about one end in a substantially horizontal plane.

BRIEF DESCRIPTION OF THE DRAWINGS

The above and other objects, features and advantages of the present invention will become more apparent from the following detailed description taken with the accompanying drawings in which:

FIGS. 1A and 1B are respectively a section and a front view, showing a copier to which the present invention is applicable;

REPLACEMENT SHEET
19 FEB 1997

FIG. 2 is a section showing the general construction of a developing device incorporated in the copier;

FIGS. 3A and 3B are respectively a section and a fragmentary enlarged view, showing a toner bottle for use with the copier;

FIGS. 4A-4C show a sequence of steps for removing a lid from the toner bottle;

FIG. 5A is a section showing a specific configuration of the lid;

FIGS. 5B and 5C are perspective views each showing another specific configuration of the lid;

FIG. 5D is a perspective view showing a thin flat piece to be attached to the lid of the toner bottle;

FIG. 5E is a section showing the lid with the thin flat piece attached thereto;

FIG. 6 is a section showing a toner supply unit included in an embodiment of the present invention;

FIGS. 7 and 8 are exploded perspective views each showing a particular part of the toner supply unit;

FIG. 9A, 9B, 10A, 10B, 11A and 11B are sections each showing a collet chuck included in the toner supply unit;

FIG. 12A is an exploded perspective view showing another part of the toner supply unit;

FIG. 12B is a sectional perspective view of the toner bottle;

REPLACEMENT SHEET
19 FEB 1997

FIG. 13A is a section of the collet chuck;

FIGS. 13B and 13C are sections each showing another specific configuration of the toner bottle;

FIGS. 14A-14E are perspective views each showing a specific constituent part included in a core shown in FIG. 7;

FIG. 15 is a graph indicative of a relation between the force necessary for a person to operate the toner supply unit and the diameter of the mouth of the toner bottle;

FIG. 16 is a perspective view showing a stop cover and a collet shaft included in a modified embodiment;

FIGS. 17A-17D demonstrate the operation of the modified embodiment;

FIGS. 18A-18D show another operation of the modified embodiment;

FIG. 19A is a perspective view showing the lid;

FIG. 19B is a section of the lid shown in FIG. 19A;

FIG. 19C illustrates forces to act on the lid when the lid is attached and detached;

FIG. 19D is a section showing another specific configuration of the lid;

FIG. 20A is a front view of the toner bottle to which a cap is attached;

FIGS. 20B-20F each shows the toner bottle of FIG. 20A in a particular view;

REPLACEMENT SHEET
19 FEB 1997

FIG. 20G is a plan view of the toner bottle from which the cap is removed.

FIG. 21A is a section along line A-A of FIG. 20A;

FIG. 21B is a perspective view of the toner bottle;

FIG. 21C is an enlarged section of a part of the toner bottle shown in FIG. 21A;

FIG. 21D is a section along line A1-A3 of FIG. 23C;

FIG. 22A is a front view demonstrating how the toner bottle guides a toner with raised portions thereof;

FIG. 22B is a front view of the toner bottle rotated 90 degrees from the position of FIG. 22A;

FIG. 22C is a side elevation of the toner bottle shown in FIG. 22A, as seen from the right;

FIG. 22D is a side elevation of the toner bottle shown in FIG. 22B, as seen from the right;

FIG. 23A is a front view of the toner bottle rotated 90 degrees from the position shown in FIG. 23B;

FIG. 23B is a front view of the toner bottle rotated 90 degrees from the position shown in FIG. 23A;

FIG. 23C is a side elevation of the toner bottle shown in FIG. 23A, as seen from the right;

FIG. 23D is a side elevation of the toner bottle shown in FIG. 23B, as seen from the right;

FIGS. 24A-24C each shows a modified form of the toner bottle in a particular view.

REPLACEMENT SHEET
19 FEB 1997

FIG. 25 is a graph indicative of a relationship between the rotation speed of the toner bottle and the quantity of toner left in the bottle without being discharged;

FIGS. 26A and 26B each demonstrates a particular operation available with a modified collet chuck;

FIG. 27 is a front view of another specific arrangement of the toner supply unit held in a toner replenishing position;

FIG. 28 is a plan view of the toner supply unit shown in FIG. 27;

FIG. 29A is a side elevation of the unit shown in FIG. 27, as seen from the right;

FIG. 29B is a fragmentary enlarged view as seen in a direction A shown in FIG. 28;

FIG. 30 is a front view of the toner supply unit held in a position for mounting a toner bottle;

FIG. 31A is an exploded perspective view of a collet chuck and a core included in the unit of FIG. 27;

FIG. 31B is a front view of the core;

FIGS. 32A and 32B each demonstrates a specific operation of the collet chuck shown in FIG. 31A;

FIG. 33 is a fragmentary enlarged view of a toner bottle for use with the toner supply unit of FIG. 27;

FIG. 34A is a front view showing a modified toner bottle for used with the toner supply unit of FIG. 27;

REPLACEMENT SHEET
19 FEB 1997

FIG. 34B is a side elevation of the toner bottle, as seen from the right;

FIG. 34C is a section of a gear link associated with the toner bottle;

FIG. 34D is a view as seen in a direction A shown in FIG. 34C;

FIGS. 35A-35E show a sequence of steps for producing a toner bottle in accordance with the present invention;

FIG. 36A is a perspective view of a toner bottle and an annular link included in a modification of the present invention;

FIG. 36B shows the toner bottle inserted into the annular link;

FIGS. 37 and 38 are perspective views each showing a toner bottle and an annular link included in another modification of the present invention;

FIG. 39A is a perspective view showing another specific configuration of the toner bottle;

FIG. 39B is a fragmentary view of the toner bottle;

FIG. 39C is a plan view of the toner bottle;

FIG. 40A is a perspective view showing another specific configuration of the toner bottle;

FIG. 40B is a fragmentary view of the toner bottle;

FIG. 40C is a plan view of the toner bottle;

REPLACEMENT SHEET
19 FEB 1997

FIG. 41 is a perspective view of a toner bottle and an annular link included in another modification of the present invention;

FIGS. 42A shows the internal arrangement of the annular link shown in FIG. 41;

FIG. 42B is a section of the annular link; and

FIG. 42C shows the toner bottle inserted into the annular link.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

A preferred embodiment of the present invention will be described which is applied to an electrophotographic copier belonging to a family of image forming apparatuses.

Referring to FIG. 1A, the copier has a glass platen 1 on the top thereof for laying a document to be copied. An optical unit 2 is disposed below the glass platen 1 and includes a lamp 2a for illuminating the document, a mirror 2b, and a lens, not shown. A photoconductive element in the form of a drum 3 is rotatably located below the optical unit 2. Arranged around the drum 3 are a main charger 4, a developing unit 5, a transfer charger 6, a cleaning unit 7, a discharger 8 and other conventional units for implementing an electrophotographic process. A fixing unit 9 is positioned at the left-hand side of the drum 3, as viewed in the figure, for fixing a toner image transferred from the drum 3 to a paper

REPLACEMENT SHEET
19 FEB 1997

by the transfer charger 6. A paper feed section 10 is provided in the lower portion of the copier and loaded with a stack of papers 10a. The papers 10a are sequentially fed from the paper feed section 10 to the drum 3. The operation of this kind of copier is well known in the art and will not be described specifically.

As shown in FIG. 2, the developing unit 5 is a conventional dry process unit using a two component type developer, i.e., a toner and carrier mixture. The developing unit 5 has a casing 5a accommodating developing rollers 11, a paddle wheel 12 for agitation, a mixing roller 13, a separator 14, a horizontally extending screw 15 for agitation, etc. A hopper 16 is contiguous with the casing 5 and disposed above such constituents of the developing unit 5. A toner is supplied from the hopper 16 into the developing unit 5. A screw conveyor 18 is accommodated in the hopper 16 and made up of a shaft 34 and a spiral member 35 affixed to the shaft 34. The screw conveyor 18 conveys a toner from a toner supply unit 17 while agitating it, as will be described in detail later. A toner supply roller 19 is disposed in a portion where the hopper 16 is communicated to the developing unit 5, and it is rotated in response to the output signal of a toner concentration sensor, not shown.

As shown in FIG. 1A, the toner supply unit 17 is located in the upper front portion of the copier and includes a bottle

REPLACEMENT SHEET
19 FEB 1997

holder 21. The bottle holder 21 plays the role of holding means for holding a toner bottle, or developer container, 20. As shown in FIG. 1B, the bottle holder 21 is mounted on a shaft 22, FIG. 1A, which is located at the right end of the unit 17. The bottle holder 21 is rotatable about 90 degrees about the axis Z of the shaft 22 in a substantially horizontal plane. Specifically, the bottle holder 21 is movable between two positions A and B, as illustrated. In the position A, the left portion of the bottle holder 21 is pulled out toward the front end of the copier to allow the bottle 20 to be mounted thereto. In the position B, the entire unit 17 remains parallel to the front end of the copier. The bottle holder 21 is formed with an opening in the bottom wall thereof for letting a toner to fall therethrough. At least in the position B, the bottom opening of the bottle holder 21 is positioned above a toner receiving portion 16a, FIG. 2, included in the hopper 16 and extending to the front end of the copier. Preferably, the toner supply unit 17 is located inwardly of a front cover, not shown, which covers the front end of the copier; when the front cover is opened, the unit 17 can be pulled out to the position A.

FIG. 3A shows a specific configuration of the toner bottle 20 while FIG. 3B shows a mouth portion 23 forming the outlet of the bottle 20. As shown, the bottle 20 is substantially cylindrical and provided with the mouth portion

REPLACEMENT SHEET
19 FEB 1997

23 at substantially the center of one end thereof. The mouth portion 23 has a smaller diameter than the cylinder constituting the bottle 20 and has a circular section. In the specific configuration, the mouth portion 23 is formed at the end of a collar 24 extending out from the cylinder 20 and is plugged by a lid 25. A mushroom-like lug 26 protrudes from the center of the lid 25. A spiral guide groove 27 is formed in the inner periphery of the cylinder 20, as in the bottle taught in previously mentioned Japanese Patent Laid-Open Publication No. 59-188678. When the bottle 20 is rotated about the longitudinal axis thereof, the spiral groove 27 guides the toner contained in the bottle 20 toward the mouth portion 23. Annular ribs 28 are formed on the outer periphery of the collar 24. A cap 29 (see FIG. 12A) closes the entire collar 24 while mating with the ribs 28 during the transport of the bottle 20. In this sense, the ribs 28 constitute an engaging portion. For this purpose, the cap 29 is provided with lugs or grooves on the inner periphery thereof which are complementary to the ribs 28.

FIGS. 4A-4C show a mechanism 32 for removing the lid 25 from the mouth portion 23 of the bottle 20. As shown, the mechanism 32 is made up of a collet chuck, or retaining means, 30 and moving means, not shown, for moving the chuck 30 toward and away from the bottle 20. The collet chuck 30 has a chucking portion 33 at the tip thereof and is supported

REPLACEMENT SHEET
19 FEB 1997

by a hole 31a formed in a wall 31 which forms a part of the bottle holder 21. When the collet chuck 30 is in a free state, the chucking portion 33 is held open, as shown in FIG. 4A. FIG. 4B shows a condition wherein the bottle 20 has been put in a predetermined position on the bottle holder 21. When the collet chuck 30 is moved away from the bottle 20 by the moving means, the peripheral larger diameter portion of the chuck 30 is pressed by the wall of the hole 31a with the result that the chucking portion 33 is squeezed to retain the lug 26 of the lid 25. Subsequently, as shown in FIG. 4C, the chuck 30 moves the lid 25 to a position where the mouth portion 23 of the bottle 20 is fully uncovered, chucking the lug 26 of the lid 25.

The mechanism 32 described above is provided on the toner supply unit 17 and allows the bottle 20 to be mounted to the bottle holder 21 with the mouth portion 23 thereof sealed by the lid 25. Hence, despite that the bottle 20 is set on the bottle holder 21 in a substantially horizontal position, as shown in FIGS. 1A and 1B, the toner is prevented from falling from the mouth portion 23.

When the toner in the bottle 20 is entirely consumed, the empty bottle 20 is taken out of the bottle holder 21. At this instant, the moving means may move the collet chuck 30 toward the bottle 20 to fit the lid 25 in the mouth portion 23. Then, when the bottle 20 is removed from the bottle holder

REPLACEMENT SHEET
19 FEB 1997

21, the mouth portion 23 will have been closed by the lid 25. This prevents the toner deposited on the mouth portion 23 from falling and smearing the hands and clothes of the person replacing the bottle 20.

FIG. 5A shows a modified form of the mouth portion 23 of the bottle 20. As shown, the cap, e.g., screw cap 29 to be fitted on the color 24 of the mouth portion 23 is formed with a hole 29a in the end wall thereof. The lid 25 having the lug 26 is removably received in the hole 29a of the cap 29.

FIGS. 5B and 5C each shows a modification of the lid 25 shown in FIG. 3B or 5A. It is likely that an inexperienced person intends to remove the lid 25 of a new toner bottle 20 by nipping the lug 26 of the lid 25 without using the collet chuck 30. This is apt to cause a fresh toner from falling from the bottle 20. To eliminate this, the lids 25 shown in FIGS. 5B and 5C are each provided with an annular obstruction 26a or pin-like obstructions 26b around the lug 26. The obstructions 26a and 26b prevent the easy access of the person's fingers to the lug 26.

FIG. 5D shows a cover 150 which is a specific substitute for the obstruction 26a or obstructions 26b. As shown, the cover 150 is made up of a thin flat piece 151 for concealing the portion of the lid 25 surrounding the lug 26, and an annular wall 152 extending out from the outer edge of the thin piece 151. A hole 151a is formed in the center of the

REPLACEMENT SHEET
19 FEB 1997

piece 151 and slightly greater in diameter than the lug 26 of the lid 25. A number of slits 151b extend radially from the edge of the hole 151a. As shown in FIG. 5E, when the cover 150 is fitted on the lid 25, only the tip of the lug 25 is visible. This prevents even an inexperienced person from mistaking the tip of the lug 25 for a member for removing the lid 25.

The toner supply unit 17 will be described more specifically. FIG. 6 shows the unit 17 held in the position B while FIGS. 7 and 8 shows it including some modified parts. The unit 17 is so constructed as to hold the bottle 20 and rotate it in synchronism with the rotation of the toner supply roller 19. As a result, a fresh toner is sequentially supplemented to the toner receiving portion 16a of the hopper 16a via the mouth portion 23 of the bottle 20.

As shown in FIG. 6, the toner receiving portion 16a is implemented as a top-open trough and extends to the front from a side wall of the hopper 16 located at the operating side. A shaft 34 extends from the inside of the hopper 16 and extends throughout the center of the trough 16a. A spiral member, or toner feed plate, 35 is affixed to the shaft 34 for conveying the toner dropped from the mouth portion 23 of the bottle 20 to the hopper 16. The shaft 34 and spiral member 35 constitute the previously mentioned screw conveyor 18, FIG. 2. The bottle holder 21 is rotatably supported by the

REPLACEMENT SHEET
19 FEB 1997

front wall of the copier and capable of holding the bottle 20 in a substantially horizontal position. A locking mechanism 36 positions the bottle 20 on the bottle holder 21 in the axial direction of the bottle 20. A motor 37 causes the bottle 20 set on the bottle holder 21 to rotate about the axis thereof. An annular gear link 38 transmits the rotation of the motor 37 to the bottle 20. The previously stated collet chuck 30 chucks the lid 25 of the bottle 20 held on the bottle holder 21. A core 39 is slidably coupled over the collet chuck 30. A cam device 40 moves the collet chuck 30 toward and away from the bottle 20.

As shown in FIGS. 7 and 8, the bottle holder 21 is mounted on a movable bracket 41. A stationary bracket 42 is affixed to the front wall of the copier and has a lower pin 43 and an upper pin 44, FIG. 6, studded thereon. The movable bracket 41 is rotatably supported by the lower pin 43 and rotatably retained by the upper pin 44. Therefore, the bracket 41 is rotatable about a substantially vertical axis extending through the upper and lower pins 43 and 44. As shown in FIG. 8, the stationary bracket 42 is rotatably supported by stays 45 fastened to the front wall by screws and is affixed to the front wall by screws 46.

The bottle holder 21 further includes a lid-like seat 47 for covering the end of the mouth portion 23 of the bottle 20. A cylindrical stop cover 48 is disposed in the seat 47 to cover

REPLACEMENT SHEET
19 FEB 1997

the mouth portion 23 of the bottle 20 in an air-tight condition. The stop cover 48 has a link receiving portion rotatably accommodating the gear link 38, and a core receiving portion accommodating the core 39. The core receiving portion has a slightly great inside diameter than the mouth portion 23 of the bottle 20. The core receiving portion is formed with an opening 49, FIG. 6, in the bottom wall thereof for letting the toner to fall, and a hole and a boss 50 on the end wall thereof for slidably supporting the collet chuck 30. An auger-like spring 51 is also accommodated in the core receiving portion to constantly bias the core 39 toward the bottle 20. The core 39 shown in FIG. 7 is a modification and has an advantage which will be described later. In FIG. 7, the reference numeral 48a designates a link stop for stopping an annular link formed at the edge of the open end that faces the bottle 20.

The locking mechanism 36 described above positions the bottle 20 in the axial direction of the bottle 20. The mechanism 36 has a locking member 52 and a spring 53 acting on the locking member 52. The locking member 52 is rotatably supported at the base end thereof by a member included in the bottle holder 21, e.g., the stop cover 48 shown in FIGS. 6 and 7. The free end of the locking member 52 is so shaped as to mate with an engaging portion, i.e., a projection or recess formed in the outer periphery of the bottle 20. The

REPLACEMENT SHEET
19 FEB 1997

spring 53 constantly biases the locking member 52 toward the outer periphery of the bottle 20. In the configuration shown in FIG. 6, the engaging portion of the bottle 20 is implemented as a ring 54 having a right-angled triangular cross-section defined by a substantially vertical contact surface 54a and a slant 54b extending from the surface 54a toward the mouth portion 23. The contact surface 54a may be overhung in such a manner as to incline toward the rear end of the bottle 20.

As shown in FIG. 6 or 8, the motor 37 for driving the bottle 20 may be mounted on the movable bracket 41 together with a gear 55. Alternatively, the motor 37 may be affixed to the copier body at a position where it can be engaged with the gear link 38 when the bottle holder 21 is brought to the position B.

The gear link 38 is formed with gear teeth 56 meshing with the gear 55 associated with the motor 37 and is provided with an inside diameter greater than the outside diameter of the bottle 20. A hole is formed in the end wall of the gear link 38 to allow the collar 24 of the bottle 20 to extend therethrough. As shown in FIG. 6, the above-mentioned end wall of the gear link 38 is provided with, for example, a plurality of radially extending ribs (referred to as link ribs hereinafter) 58 capable of mating with ribs (referred to as

REPLACEMENT SHEET
19 FEB 1997

bottle ribs hereinafter) 57 provided on the bottle 20 (see FIG. 34D).

In the specific arrangement shown in FIG. 6, the stop cover 48 is formed with an opening in the lower portion thereof to allow the gear 55 of the motor 37 to mesh with the gear teeth 56 of the gear link 38. An annular seal 59 is fitted around the hole of the previously mentioned end wall to seal the gap between the outer periphery of the collar 24 of the bottle 20 and the stop cover 48, thereby preventing the toner coming out of the mouth portion 23 from depositing on, for example, the outer periphery of the bottle 20. At the same time, the seal 59 cleans the outer periphery of the collar 24 when the bottle 20 is replaced with a new toner bottle. The seal 59 is so bent as to be convex toward the collet chuck 30, so that the bottle 20 can be set with ease.

There are also shown in FIG. 7 a seal 60 made of sponge or similar soft material and adhered to the end of the gear link 38, a flexible thin seal (e.g. 0.188 mm thick) 61 adhered to the same end over the seal 60, and a shutter 107 for closing the opening which is formed in the seat 47 of the bottle holder 21 for letting the toner to fall. Usually, the shutter 107 is held in a position where an opening formed therein is aligned with the opening of the seat 47. In the event of maintenance, a serviceman may rotate the shutter

REPLACEMENT SHEET
19 FEB 1997

107 by holding a thumb piece 108 in order to close the opening of the seat 47.

As shown in FIG. 7, the collet chuck 30 is formed with a plurality of slits 62 to have the chucking portion 33 thereof squeezed by an external force. In the illustrative embodiment, as shown in FIG. 9A, in an unstressed position, the chucking portion 33 is open over a distance D_1 greater than the the maximum diameter d_1 of the tip of the lug 26 of the lid 25. The chuck 30 includes a larger diameter portion 63 adjoining the chucking portion 33, and a smaller diameter portion 64 following the larger diameter portion 63. In an unstressed position, the larger diameter portion 63 has an outside diameter greater than the outside diameter D_2 of the smaller diameter portion 64.

The core 39 is made up of a flange 66 capable of abutting against a flange 65 provided on the lid 25, and a cylindrical slider 67 on and along which the chuck 30 is slidable. The slider 67 has an inside diameter D_3 greater than the outside diameter D_2 of the smaller diameter portion 64 of the chuck 30 and smaller than the outside diameter of the larger diameter portion 63 when the portion 63 is not stressed. In this configuration, when the core 39 is brought to the larger diameter portion 63 of the chuck 30, the former runs onto the latter to reduce the opening of the chucking portion 33, as indicated by a dash-and-dots line in FIG. 9B.

REPLACEMENT SHEET
19 FEB 1997

The resulting opening D'_1 of the chucking portion 33 is selected to be at least smaller than the maximum diameter d_1 of the lug 26 and, preferably, equal to the diameter d_2 of the root of the lug 26.

The cam device 40 shown in FIG. 6 is constructed as follows. When the bottle holder 21 is moved from the position B to the position A, the cam device 40 moves the chuck 30 away from the bottle 20. Also, when the bottle holder 21 is moved from the position A to the position B, the cam device 40 moves the chuck 30 toward the bottle 20. In the illustrative embodiment, the cam device 40 has a flat cam member 68 and a roller 70 which is rotatably mounted on a chuck shaft 69. The chuck shaft 69 is affixed to the rear end of the chuck 30.

As shown in FIGS. 10A and 10B, the cam member 68 has a first surface 71 for guiding the roller 70 from the side adjoining the center of rotation Z of the bottle holder 21 is located, and a second surface 72 for guiding it from the side opposite to the center of rotation Z. As shown in FIG. 10B specifically, when the bottle holder 21 is moved from the position B to the position A, the first surface 71 guides the roller 70 such that the chuck 30 biased toward the bottle 20 by the spring 51 via the core 39, which is engaged with the larger diameter portion 63 of the chuck 30, moves away from the bottle 20. When the bottle holder 21 is moved from the

REPLACEMENT SHEET
19 FEB 1997

position A to the position B, the first surface 71 guides the roller 70 such that the chuck 30 biased by the spring 51 moves toward the bottle 20.

As shown in FIG. 11B specifically, just before the movement of the bottle holder 21 from the position A to the position B completes, the core 39 abuts against the edge of the collar 24 of the bottle 20 positioned by the locking mechanism 36. As a result, the core 39 is released from the larger diameter portion 63 of the chuck 30, preventing the force of the spring 51 from acting on the chuck 30. From this instant to the instant when the movement of the bottle holder 21 to the position B completes, the second surface 72 of the cam member 68 guides the roller 70 such that the 30 approaches the bottle 20.

The cam device 40 is located in the vicinity of the axis of rotation of the bottle holder 21, as stated above. Hence, when the person intending to replace the bottle 20 pulls or pushes the bottle holder 21 between the positions A and B, the point of the holder 21 where the resulting force acts and the center of rotation Z are spaced apart a greater distance than the engaging point of the cam 71 or 72 and roller 70 and the center of rotation Z. This allows the bottle holder 21 to be move by a relatively small force, based on leverage.

In the above construction, while an ordinary copying operation is under way, the toner supply unit 17 has the

REPLACEMENT SHEET
19 FEB 1997

bottle holder 21 thereof located at the position B. To position the bottle holder 21 at the position B, it is preferable that a locking mechanism, e.g., one using a magnet be provided on the front wall of the copier and bottle holder 21. As shown in FIG. 6, in the position B, the bottle 20 set on the bottle holder 21 is positioned with the ring 54 thereof abutted against the end of the locking member 52 of the locking mechanism 36. In this condition, the bottle ribs 57 of the bottle 20 are engaged with the link ribs 58 of the gear link 38. As shown in FIGS. 10A and 10B, the collet chuck 30 assumes a position remotest from the bottle 20. In this position, the core 39 biased by the spring 51 is positioned at the larger diameter portion 63 of the chuck 30 to squeeze the chucking portion 33. As a result, the chucking portion 33 unseals the mouth portion 23 of the bottle 20, chucking the lug 26, i.e., lid 25. The toner receiving portion 16a, FIG. 6, of the hopper 16 is disposed below the opening 49 of the stop cover 48.

As the toner concentration in the developing unit decreases due to repeated development, the toner supply roller 19 starts rotating in response to the output signal of a toner concentration sensor, not shown. At the same time, the motor 37 starts rotating. The rotation of the motor 37 is transmitted to the bottle 20 via the gear 55 and gear link 38, thereby causing the bottle 20 to rotate. The spiral guide groove 27 formed in the inner periphery of the bottle 20

REPLACEMENT SHEET
19 FEB 1997

sequentially drives the toner toward the mouth portion 23 of the bottle 20 until it falls from the portion 23. The toner dropped from the bottle 20 is received by the toner receiving portion 16a of the hopper 16 via the opening 49 of the stop cover 48. Then, the screw conveyor 18 conveys the toner from the toner receiving portion 16a to the hopper 16 deeper into the copier. This operation is continued until the toner concentration in the developing unit increases to a predetermined value, i.e., until the toner supply roller 19 stops rotating. Alternatively, the bottle 20 may be rotated at an adequate time when the toner in the hopper 16 decreases.

As shown in FIGS. 12A and 12B, a projection 73 may be provided on the toner bottle 20 at a position where it can face a part of the locking member 52 of the above-described positioning mechanism. Then, when the bottle 20 is rotated, the projection 73 contacts a part of the locking member 52 and raises the free end of the member 52 against the action of the spring 53, FIG. 7, but only to such a degree that the member 52 is not fully released from the ring 54. Subsequently, as the projection 73 moves away from the locking member 52, the member 52 is restored and hits against the outer periphery of the bottle 20, causing the wall of the bottle 20 to vibrate. This is successful in increasing the fluidity of the toner in the bottle 20 and, therefore, causing a greater quantity of toner to flow out of the bottle

REPLACEMENT SHEET
19 FEB 1997

20 via the mouth portion 23. In addition, a minimum of toner is caused to adhere to the inner periphery of the bottle 20.

In FIGS. 12A and 12B, the particular configuration of the bottle 20 around the mouth portion 23 promotes the efficient discharge of the toner from the bottle 20, as will be described in detail later.

To remove the bottle 20 from the bottle holder 21 for replacement or similar purpose, the bottle holder 21 is moved from the position B to the position A. While the bottle holder 21 is in movement, the cam device 40 guides the roller 70 with the first surface thereof such that the collet chuck 30 carrying the lid 25 therewith moves toward the mouth portion 23 of the bottle 20. Consequently, the flange 66 of the core 39 abuts against the edge of the collar 24 of the bottle 20 via the flange 65 of the lid 25. Even after the movement of the core 39 has been restricted by the collar 24, the cam device 40 guides the roller 70 with the second surface thereof to continuously move the chuck 30 until the larger diameter portion 63 of the chuck 30 has been released from the core 39. As a result, the chucking portion 33 is opened due to the restoring force of the chuck 30, releasing the lug 26 of the lid 25. By the procedure described so far, the lid 25 is inserted into the collar 24 of the toner bottle 20, thereby sealing the mouth portion 23. When the bottle holder 21 is fully brought to the position A, the chucking portion 33 of the chuck 30 is

REPLACEMENT SHEET
19 FEB 1997

open over a distance greater than the maximum diameter D_1 of the lug 26 of the lid 25, as shown in FIGS. 9A, 11A and 11B.

Subsequently, when the bottle holder 21 is held in the position A, the locking member 52 of the locking mechanism 36 is manually pulled up away from the bottle 20 against the action of the spring 53 until the member 52 has been released from the ring 54 of the bottle 20. Then, the bottle 20 is pulled out from the stop cover 48 and taken out from the bottle holder 21.

The locking member 52 is constantly biased toward the bottle 20 by the spring 53. Hence, when the locking member 52 being manually pulled up, as mentioned above, is released, the free end thereof will drop and again mates with the ring 54 of the bottle 20. Therefore, it is necessary to maintain the free end of the locking member 52 in the lifted position in the event when the bottle 20 should be pulled out. To meet this requisite, the bottle 20 should preferably be automatically displaced when the locking member 52 is lifted away from the bottle 20. FIG. 13 shows a specific implementation in which the spring 51 forces out the toner bottle 20 via the core 39 when the bottle 20 is released from the locking mechanism 36. As shown, the height of the collar 24, as well as other factors, is selected such that when the bottle 20 is positioned by the locking mechanism 36, the edge of the collar 24 protrudes a predetermined quantity S from

REPLACEMENT SHEET
19 FEB 1997

the stop cover 48. In this configuration, at the moment when the locking member 52 is lifted away from the ring 54 of the bottle 20, the core 39 is moved by the spring 51 until the flange 66 thereof hits against the gear link 38. As a result, the bottle 20 is forced out by the predetermined quantity S.

Assume that in the initial state of movement of the core 39 and before the lug 26 of the lid 25 has been fully released from the chucking portion 33 of the collet chuck 30, the core 39 has engaged with the larger diameter portion 63 of the chuck 30 and squeezed the chucking portion 33. Then, the lid 25 is continuously held by the chuck 30, i.e., the mouth portion 23 of the bottle 20 is open even when the bottle 20 is pulled out. As a result, the toner deposited on the inner surface of the mouth portion 23 is apt to fall and smear the hands an cloths. Moreover, when the chucking portion 33 is so squeezed, it is likely that when a new toner bottle 20 is set, the lug 25 of its lid 25 cannot enter the chucking portion 33.

In the light of this, the above-mentioned quantity S should preferably be selected such that even after the flange 66 of the core 39 has abutted against the gear link 38, the core 39 does not contact the larger diameter portion 6 of the chuck 30, thereby maintaining the chucking portion 33 open. Specifically, the gear link 38 should preferably be positioned such that when the bottle 20 is released from the locking mechanism 36, the core 39 abuts against the gear link 38

REPLACEMENT SHEET
19 FEB 1997

before it engages with the larger diameter portion 63 of the chuck 30. While the gear link 38 is used to restrict the movement of the core 39, it may be replaced with an exclusive member for restriction.

At the position A, the empty bottle 20 is replaced with a new bottle 20. Specifically, a new bottle 20 is filled with a fresh toner and has the mouth portion 23 thereof sealed by a seal 25. The new bottle 20 is mounted to the bottle holder 21 with the head portion thereof facing the stop cover 48. Then, the head portion of the bottle 20 is inserted into the stop cover 48. At this instant, the locking member 52 of the locking mechanism 36 catches the ring 54 of the bottle 20 being moved into the stop cover 48. As a result, the toner bottle 20 is positioned on the bottle holder 21. In the illustrative embodiment, while the bottle 20 is moved deeper into the stop cover 48, the free end of the locking member 52 runs onto the slant 54b of the ring 54. This, coupled with the fact that the ring 54 raises the inclined surface of the member 52, makes it needless to lift the locking member 52 manually.

The core 39 is held in a position where it does not contact the larger diameter portion 63 of the chuck 30 in the stop cover 48, as stated earlier. Hence, the chucking portion 33 of the chuck 30 is left open. It follows that the lug 26 of

REPLACEMENT SHEET
19 FEB 1997

the lid 25 can be moved into the chucking portion 33 smoothly.

Assume an arrangement wherein when the bottle 20 is forced out by the core 39, as stated previously, the chucking portion 33 of the chuck 30 is closed after the lug 26 of the lid 25 has been released from the chucking portion 33. In such a case, the lid 25 should preferably be configured such that the flange 65 thereof is protruded sufficiently more than the lug 26. Then, when a new bottle 20 is inserted into the stop cover 48, the edge of the color 24 pushes the flange 66 of the core 39 via such a flange 65 of the lid to release the core 39 from the larger diameter portion 63 of the chuck 30, thereby opening the chucking portion 33. In this condition, the lug 26 of the lid 25 enters the chucking portion 33 which is open then.

Thereafter, the bottle holder 21 is moved from the position A to the position B. At this instant, the cam device 40 guides the roller 70 with the first cam surface thereof such that the chuck 30 carrying the lid 25 therewith moves away from the mouth portion 23 of the bottle 20. In the initial stage of movement, the chuck 30 has the larger diameter portion 63 thereof brought into engagement with the core 39 and has the chucking portion 33 squeezed thereby. As a result, the chucking portion 33 chucks the lug 26 of the lid 25. Even after this, the core 39 and larger diameter portion

REPLACEMENT SHEET
19 FEB 1997

63 are continuously engaged by the force of the spring 51, so that the chucking portion 33 holds the lid 25 continuously. Consequently, the lid 25 is removed from the mouth portion 23 to thereby unseal it. In this way, the bottle holder 21 is fully moved to the position B, as shown in FIGS. 6, 10A and 10B. In the position B, a fresh toner is sequentially supplemented from the bottle 20 while the bottle 20 is in rotation.

As stated above, with the toner supply unit 17 of the embodiment, it is possible to replace the bottle 20 simply by moving the bottle holder 21 and then replacing the bottle 20. At this instant, the toner is prevented from leaking from the mouth portion 23 of the bottle 20.

As shown in FIG. 13B, the flange 65 of the lid 25 should preferably be provided with an outside diameter d_2 which is smaller than the outside diameter d_3 of the collar 24. Otherwise, when the bottle 20 is moved into and out of the stop cover 38, the flange 65 is apt to contact the seal 59 fitted on the inner periphery of the stop cover 38, causing the lid 25 to be removed. Further, as shown in FIG. 13C, the cap 29 is fitted on the bottle 20 over the lid 25. The cap 29 prevents the lid 25 from being accidentally removed from the bottle 20 when the bottle 20 is transported, particularly on highland or by aircraft. In addition, since the cap 29 protects the lid 25, it is not necessary for the lid 25 to be rigidly

REPLACEMENT SHEET
19 FEB 1997

coupled with the collar 24, reducing the force required of the automatic lid attaching and detaching mechanism.

A modified form of the core 39 shown in FIG. 7 will be described with reference to FIGS. 14A-14E. As shown in FIG. 14A, the core 39 has a cylindrical drum portion 74 having a diameter slightly smaller than the inside diameter of the stop cover 48. Flanges are provided on the circumferential surface of the drum portion 74 to form a plurality of annular recesses. Annular seal members 75, FIGS. 14B and 14C, are fitted in the individual annular recesses of the drum portion 74 and arranged side by side in the axial direction of the drum portion 74. The seal members 75 seal the gap between the outer periphery of the core 39 and the inner periphery of the stop cover 48. As shown in FIG. 14B, each seal member 75 may be implemented as an elongate member having an adhesive layer 75a and having opposite ends thereof abutted against each other. Alternatively, as shown in FIG. 14C, the seal member 75 may be implemented as a ring and adhered to the drum portion 74. Preferably, the seal members 75 having the configuration shown in FIG. 14B should be positioned such that their portions where opposite ends are abutted are deviated in the axial direction of the core 39. Also, the annular seal member 75 shown in FIG. 14C should preferably be constituted by an elastic member 75b enriched in elasticity mainly in the circumferential direction, e.g., a non-

REPLACEMENT SHEET
19 FEB 1997

foam elastic body, and an elastic body 75c provided on the elastic body 75b and enriched in elasticity mainly in the direction of thickness, e.g., a foam elastic body.

The core 39 shown in FIG. 14A is formed with a boss 77 at the end thereof which abuts against the flange 65 of the lid 25. A hole for the collet chuck 30 to extend is formed throughout the core 39 in the boss 77. The boss 77 also serves to position a flat annular end seal 78 shown in FIG. 14D or 14E when the seal 78 is fitted on the end of the flange by adhesion. The end seal 78 may be implemented by a single material, as shown in FIG. 14D, or by a plurality of annular elements adhered to each other. It is preferable that at least the front end 78a of the end seal 78 be constituted by silicone resin, fluorine resin or similar resin having, for example, small surface energy, so that the toner may not deposit thereon easily.

A reference will be made to FIGS. 15-18 for describing an improved implementation for reducing the force to be manually exerted on the bottle holder 21. Assume that the toner is deposited on the inner periphery of the collar 24 of the bottle 20 and the portion of the lid 25 contacting it. Then, the force necessary for the lid 25 to be inserted into and removed from the mouth portion 23 of the bottle 20 is increased. As a result, the force necessary for the bottle holder 21 to be pushed from the position A to the position B

REPLACEMENT SHEET
19 FEB 1997

(causing the lid 25 to be removed from the mouth 23 portion) and the force necessary for it to be pulled from the position B to the position A (causing the lid 25 to be inserted into the mouth portion 23) are increased.

The pushing force and pulling force mentioned above were measured with three different types of toner supply units 17 (referred to as types 1 to 3 hereinafter) different in the shape of the collet chuck 30 and that of the core 39, and with toner bottles 20 having various mouth diameters. A toner was deposited on, for example, the inner periphery of the collars 24 of such bottles 20. FIG. 15 is indicative of the results of measurement. In FIG. 15, the abscissa and the ordinate indicate respectively the diameter of the mouth portion 23 of the bottle 20 and the force needed to move the bottle holder 21. The graph includes dash-and-dot lines representative of the results of measurement. Among them, a dash-and-dot line marked with arrows and a dash-and-dot line marked with dots are associated with types 1 and 2, respectively; a dash-and-dot line marked with crosses is associated with type 3. The pushing forces measured with the type 1 are distributed in a region A_1 indicated by a brace, while the pulling forces also measured with the type 1 are distributed in a region B_1. The pushing forces measured with the type 2 are distributed in a region A_2 while the pulling forces measured with the type 2 are distributed in a region

REPLACEMENT SHEET
19 FEB 1997

B_2. Although distributions measured with the type 3 are not shown in the graph, the pushing forces measured lie in the regions A_1 and A_2 while the pulling forces lie in the regions B_1 and B_2 and below them. Defective insertion occurred in a region C indicated by hatching (enclosed by a horizontal line representative of a force of 2200 g and an inclined line representative of the upper limit of the region A_2).

As FIG. 15 indicates, the required pushing force is greater than the required pulling force and should be, for example, greater than 2 kg. Further, when the pulling force exceeds, for example, 2.2 kg due to the diameter of the mouth portion 23 and the configuration of the collet chuck 30 and core 39, the lid 25 is inserted defectively.

FIG. 16 is a fragmentary view of an improved mechanism which causes, when the lid 25 is attached to or detached from the mouth portion 23 of the bottle 20, the lid 25 to rotate about the axis thereof. As a result, the lid 25 is attached to and detached from the mouth portion 23 smoothly, reducing the pushing force and pulling force. To cause the lid 25 to rotate about the axis thereof, the boss 50 of the stop cover 48, in which the chuck 30 slides, is formed with a cam slit 79 for causing the chuck 30 to rotate while moving toward and away from the bottle 20. A pin 80 is studded on the chuck shaft 69 of the chuck 30 and movably received in the cam slit 79.

REPLACEMENT SHEET
19 FEB 1997

FIGS. 17A and 17B correspond to FIGS. 10A and 10B, respectively, and show the improved mechanism in a condition wherein the bottle holder 21 is located at the position B. FIG. 10C is an enlarged view of the mechanism, as seen in the direction indicated by an arrow A in FIG. 17B. FIG. 17D is an enlarged view of the mechanism, as seen in the direction indicated by an arrow B in FIG. 17B. As shown, the pin 80 is positioned in the outermost portion of the cam slit 79 formed in the circumferential lowermost portion of the boss 50, which is indicated by a dash-and-dot line L_1 in FIG. 17C. The innermost end of the cam slit 79 assumes a position indicated by a dash-and-dot line L_2, FIG. 10C, which is deviated a predetermined angle α, e.g., 90 degrees from the position L_1. While the pin 80 moves from the outermost portion to the innermost portion of the cam slit 79, as indicated by a dash-and-dots line C in FIG. 17C, the slit 79 causes the pin 80 to rotate the predetermined angle α about the axis of the boss 50, as indicated by FIG. 17D. FIGS. 18A and 18B correspond to FIGS. 11A and 11B, respectively, and show the mechanism in the condition wherein the bottle holder 21 is located at the position A. FIG. 18C is an enlarged view as seen in the direction indicated by an arrow A in FIG. 18G. FIG. 18D is an enlarged view as seen in the direction indicated by an arrow B in FIG. 18B.

REPLACEMENT SHEET
19 FEB 1997

In operation, when the bottle holder 21 is moved from the position B toward the position A, the chuck shaft 69 of the chuck 30 moves toward the toner bottle 20 while sliding within the boss 50 of the stop cover 48. At the same time, the pin 80 rotates the predetermined angle α about the axis of the boss 50 of the stop cover 48 by being guided by the cam slit 79, as indicated by the line C in FIG. 17C. As a result, the lid 25 held by the chuck 30 is sequentially inserted into the collar 24 of the bottle 20 while rotating about the axis of the boss 50.

Conversely, when the bottle holder 21 is moved from the position A toward the position B, the chuck shaft 69 moves away from the bottle 20 while sliding within the boss 50 of the stop cover 48. At this instant, the pin 80 rotates the angle α about the axis of the boss 50 in the opposite direction by being guided by the cam slit 79. Consequently, the lid 25 held by the chuck 30 is removed from the collar 24 of the bottle 20 while rotating about the axis of the boss 50.

As stated above, the lid 25 is inserted and removed from the mouth portion 23 of the bottle 20 while rotating about the axis of the boss 50 of the stop cover 48. This promotes smooth insertion and removal of the lid 25 from the mouth portion 23 and, therefore, reduces the required forces for pushing and pulling the bottle holder 21, compared to the case wherein the lid 25 does not rotate.

REPLACEMENT SHEET
19 FEB 1997

Another improved mechanism for reducing the forces necessary for the bottle holder 21 to be pushed and pulled will be described with reference to FIGS. 19A-19D. FIGS. 19A and 19B show a specific configuration of the lid 25 which promotes easy attachment and detachment of the lid 25 to the mouth portion 23 of the toner bottle 20. As shown, the lid 25 has an annular wall portion 81 which contacts the inner periphery of the collar 24, a bottom wall portion 82, and an inclined wall portion 83 connecting the two wall portions 81 and 82. The wall portion 83 is inclined a predetermined angle, preferably less than 45 degrees. The bottom wall portion 82 has a diameter smaller than the outside diameter of the annular wall 81.

Preferably, the inclined wall 83 has a thickness t smaller than the thickness T of the bottom wall 82, e.g., one half of the thickness T ($t \approx 1/2 \cdot T$). As a result, when the collet chuck 30 inserts the lid 25 into the mouth portion 23, the forces f_1 and f'_1 (see FIG. 19C) necessary for the circumferential wall of the lid 25 to press the collar 24 are reduced, compared to a case wherein the thicknesses t and T are equal. Also, when the chuck 30 pulls out the lid 25 from the mouth 23, the forces f_2 and f'_2 (see FIG. 19C) exerted by the collar 24 on the circumferential wall of the lid 25 are reduced. This prevents the lid 25 from being inserted in or

REPLACEMENT SHEET
19 FEB 1997

pulled out from the mouth portion 23 defectively due to the deformation thereof.

If desired, the surface of the bottom wall portion 82 of the lid 25 that contacts the toner may be provided with undulations. Then, although the toner may have aggregated during storage, it can start being discharged easily when the lid 25 is removed. The undulations may be implemented by wavy ribs formed on the above-mentioned surface of the bottom wall portion 82.

Further, as shown in FIG. 19D, the outer surface of the annular wall portion 81 may be provided with a saw-toothed portion 84. When the lid 25 is inserted into the mouth portion 23, the saw-toothed portion 84 will scrape off the toner deposited on the inner periphery of the collar 24 of the bottle 20 and drive it into the bottle 20. As a result, the force necessary for the lid 25 to be inserted into the collar 24 is maintained constant. This eliminates an occurrence that the force necessary for the lid 25 to be into the mouth portion 23 is increased by 1.5 times due to the toner deposited on the inner surface of the collar 24. For example, a chuck 30 and lid 25 combination could be selected which reduced, when the mouth portion 23 had a diameter of 39. 90 mm, the force for pulling the lid 25 to 950 g at maximum when the toner was not deposited and to 1570 g at maximum even when the toner was deposited. Also, such a combination reduced the force

REPLACEMENT SHEET
19 FEB 1997

necessary for the lid 25 to be inserted to 1370 g at maximum when the toner was not deposited and to 1770 g at maximum when the toner was deposited.

Referring to FIGS. 20A-24C, a specific configuration of a part of the bottle 20 adjacent the mouth portion 23 will be described which allows the toner to be discharged in a desirable manner. In the figures, the bottle ribs 57 to receive a rotating force from the ring are not shown (see FIGS. 34A and 34B).

Briefly, the bottle 20 shown in the figures is configured such that when the bottle 20 is set on the bottle holder 21 in a substantially horizontal position with the mouth portion 23 oriented sideways, the toner existing in the lower portion of the cylindrical body of the bottle 20 is raised to the mouth portion 23 by the rotation of the bottle 20 and then discharged via the mouth portion 23. As a result, the toner is desirably driven out of the bottle 20 via the mouth portion 23 which has a smaller diameter than the cylindrical body of the bottle 20. Specifically, the end or shoulder of the bottle 20, where the mouth portion 23 is provided, has the inner periphery thereof partly raised to the edge of the mouth portion 23 to thereby form a portion 85 indicated by hatching. The raised portion 85 moves the toner upward when the bottle 20 is in rotation, as will be described specifically later. As shown in FIG. 21A, since the end wall and circumferential

REPLACEMENT SHEET
19 FEB 1997

wall of the bottle 20 have substantially the same thickness, the internal configuration of the bottle 20 directly appears on the outer periphery also. For this reason, in the other figures (e.g. FIG. 20E), the reference numerals attached to the inner periphery of the bottle 20 are also used to designate the corresponding portions of the outer periphery.

Further, the bottle 20 has another raised portion 86 contiguous with the raised portion 85 in the circumferential direction, as indicated by hatching different in direction from the hatching indicative of the portion 86 in FIG. 21B. Specifically as shown in FIG. 21A, the inner peripheral portion of the circumferential wall contiguous with the raised portion 85 in the circumferential direction is raised toward the axis, or center line of rotation, L of the bottle 20 over the edge of the mouth portion 23. As shown in FIG. 20G, when the bottle 20 is seen from the outside in the axial direction, i.e., along the center line L with the cap and lid thereof removed, the raised portion 86 appears in the mouth portion 23.

Preferably, the contiguous raised portions 85 and 86 should be provided with a ramp surface configuration which protrudes more toward the axis L as the distance thereof from the mouth portion 23 increases. Further, as shown in FIG. 21D, it is preferable that the raised portions 85 and 86 be provided with concavity which at least partly appears, in a section containing the axis L, as a curve whose center of

REPLACEMENT SHEET
19 FEB 1997

curvature C_1 is close to the axis L. FIG. 21D is a section along line A4-A2 of FIG. 23C and representative of the raised portion 85. FIG. 21 is a fragmentary enlarged view of FIG. 21A and a section along line A1-A3 of FIG. 23C. As shown in FIG.21D, the raised portion 86 should preferably have the end portion thereof provided with convexity appearing, in the section containing the axis L, as a curve whose center of curvature C_2 is remote from the axis L. The curve with the center of curvature C2 allows the toner to be forced out to the collar 24 smoothly. Moreover, it is preferable that the raised portions 85 be contiguous with the spiral guide groove 27. Then, the toner guided along the guide groove 27, which has a constant width, to the vicinity of the mouth portion 23 will be continuously raised to the edge of the mouth portion 23 and then guided to the raised portion 86.

FIG. 24A shows a preferred configuration of a wall *a* forming the guide groove 27 of the bottle 20. As shown, the wall *a* includes a portion *b* for driving the toner in the guiding direction indicated by an arrow A (i.e. toward the mouth portion 23). The portion *b* protrudes toward the axis of the bottle 20 at an angle θ1 substantially perpendicular to the flat inner periphery of the bottle 20, e.g., 80 degrees to 90 degrees. The other portion *c* of the wall *a*, which the toner being conveyed gets over, protrudes toward the axis of the bottle 20 at a small angle θ2, e.g., less than 30 degrees,

REPLACEMENT SHEET
19 FEB 1997

preferably 10 degrees to 30 degrees and in the guiding direction A. The wall *a* with such a configuration causes the toner to fall from the inner periphery thereof easily while the bottle 21 is in rotation, thereby allowing a minimum of toner to remain in the bottle 20.

How the raised portions 85 and 86 guide the toner will be described with reference to FIGS. 22A-22D and 23A-23D. FIGS. 22C and 23C are side elevations, as viewed from the right, of the bottle 20 shown in front views in FIGS. 22A and 23A, respectively. FIGS. 22D and 23D are side elevations, as viewed from the right, of the bottle 20 shown in front views in FIGS. 22B and 23B, respectively. It is to be noted that FIGS. 22B and 23B show the bottle 20 in a position rotated 90 degrees from the position shown in FIGS. 22A and 23A. The arrow K is indicative of the direction in which the bottle 20 is rotated by the toner supply unit 17.

In the condition shown in FIGS. 22A and 22C, the maximum diameter portion of the shoulder is located at the bottom in the vertical direction. Hence, the guide groove 27 guides the toner to the bottom of the maximum diameter portion of the head portion of the bottle 20. As shown in FIGS. 22B and 22D, when the bottle 20 is rotated 90 degrees in the direction K, the boundary between the maximum diameter portion of the shoulder and the raised portion 85 is positioned at the bottom in the vertical direction; the toner

REPLACEMENT SHEET
19 FEB 1997

from the guide groove 27 partly rides on the raised portion 85. As shown in FIGS. 23A and 23C, while the bottle 20 is further rotated 90 degrees in the direction K toward the position of FIGS. 23A and 23C, the raised portion 85 raises the toner to the edge of the mouth portion 23 as if it were a spoon. When the bottle 20 is further rotated 90 degrees in the direction K to around the position of FIGS. 23B and 23D, the toner is partly transferred from the raised portion 85 to the inclined raised portion 86. As a result, the toner is guided by the raised portion 86 toward the outside of the bottle 20 in the direction L and then discharged via the mouth portion 23.

As best shown in FIG. 23C, the raised portion 85 itself is provided with a spoon-like concave configuration. When the bottle 20 has such a configuration adjacent the mouth portion 23, the toner powder is prevented from dropping from the mouth portion 23 in masses and raising a cloud in the hopper 16. That is, the toner powder is discharged little by little from the bottle 20 in a loose state. Moreover, hardly any of the toner is left in the bottle 20. In addition, while the bottle 20 is in rotation, only a so-to-speak spoonful of toner is scooped up to the mouth portion 23. As a result, a constant amount of toner is discharged from the mouth portion 23 at all times.

REPLACEMENT SHEET
19 FEB 1997

As shown in FIG. 24B, two pairs of raised portions 85 and 86 may be formed on the inner periphery of the shoulder of the bottle 20. In this case, the toner will be discharged in a quantity twice as great as the quantity available with a single pair of raised portions 85 and 86 for the same quantity of rotation of the bottle 20.

Further, as shown in FIG. 24C, the outer periphery of the bottle 20 may additionally include a grip portion L_1 having a diameter Φ_1 smaller than the diameter Φ_0 (greater than 100 mm) of the other portion. The outside diameter Φ_1 of the grip portion L_1 should advantageously be 80 mm to 100 mm; the length should advantageously be 80 mm to 100 mm. In FIG. 24C, the wall *a* forming the guide groove 27 has the same inner peripheral configuration as the configuration shown in FIG. 24A. In FIG. 24C, the arrow *a* is indicative of the toner being entrained by the inner periphery of the bottle 20 upward due to the rotation of the bottle 21, while the arrow *b* is indicative of the toner falling therealong.

FIG. 25 is a graph indicative of a relation between the rotation speed (number of rotations per minute) of the bottle 20 during toner supply and the amount of toner left in the bottle 20 without being discharged. As shown, the amount of toner left in the bottle 20 depends on the rotation speed. For example, assuming that the allowable amount of toner to remain in the bottle 20 is up to 50 g, it is preferable to

REPLACEMENT SHEET
19 FEB 1997

rotate the bottle 20 thirty rotations to forty rotations for a minute. Of course, the adequate rotation speed of the bottle 20 for reducing the amount of remaining toner is determined by, for example, the diameter of the mouth portion 23 and the configuration of the raised portions 85 and 86. In practice, therefore, the adequate rotation speed is determined by experiments beforehand, and the bottle 20 is rotated at such a speed.

In the illustrative embodiment, the toner supply unit 17 is constructed such that the collet chuck 30 retains the lug 26 of the lid 25 when the tip thereof is squeezed. Alternatively, as shown in FIG. 26A, the chuck 30 may cause the tip thereof to abut against the inner periphery of the annular wall of the lid 25 and retain the lid 25 when opened. FIG. 26B shows a condition wherein the tip of such a chuck 30 has been squeezed to release the lid 25. In the chuck 30 shown in FIGS. 26A and 26B, the the slit has a rear portion 87 which is broader than the front or tip portion. A pin 88 is studded in a predetermined position of, for example, the stop cover 48. When the chuck 30 is moved relative to the pin 88 such that the pin 88 enters the narrower tip portion of the slit, the slit, i.e., the tip portion thereof is opened. When the chuck 30 is moved such that the pin 88 enters the rear portion 87 of the slit, the tip of the chuck 30 does not contact the lid 25. FIGS. 26A and 26B show respectively a position matching

REPLACEMENT SHEET
19 FEB 1997

the position B of the bottle holder 21 and a position matching the position A of the same.

Referring to FIGS. 27-30, a modified form of the toner supply unit 17 will be described. In the figures, the same or similar constituents as or to the constituents of the previous configuration are designated by the same reference numerals.

In the modification, the toner supply unit 17 is also rotatable substantially 90 degrees between the positions A and B in a substantially horizontal plane about the center of rotation Z, FIG. 1B. To rotatably support the bottle holder 21 about the center of rotation Z, the mechanism described previously may also be used. Again, the toner supply unit 17 has the locking mechanism for positioning the bottle 20 on the bottle holder 21, motor 37 for rotating the bottle 20, gear link 38 for transmitting the rotation of the motor 37 to the bottle 20, collet chuck 30 for retaining the lid 25 of the bottle 20, core 39 slidably mounted on the chuck 30, and cam device for moving the chuck 30 back and forth.

The modification differs from the previous embodiment, as follows. To begin with, in the previous embodiment, the cam device for moving the chuck 30 back and forth is located adjacent the center of rotation Z of the bottle holder 21. By contrast, in the modification, the cam device is located at a position comparatively remote from the center of rotation Z in the longitudinal direction of the bottle holder 21.

REPLACEMENT SHEET
19 FEB 1997

Specifically, as shown in FIGS. 27 and 28, the cam device, generally 93, has a cam member 97 affixed to the portion of a copier front wall 96 that will face the end of the bottle holder 21 remote from the center of rotation Z when the holder 21 is held in the position B (referred to as movable end hereinafter). In addition, the cam device 93 has a roller 95 mounted on the movable end of the bottle holder 21 and provided with a flange. Specifically, the roller 95 is rotatably mounted on a plate 94 which is in turn affixed to a bracket 89. The bracket 89 is affixed to the bottle holder 21 or the movable bracket 41 in the vicinity of the rear end of the bottle 20 (opposite to the end where the mouth portion 23 is positioned) in such a manner as to be movable toward and away from the rear end of the bottle 20. The bracket 89 and an arm member 99 fastened to the rear end of the chuck 30 by a screw 98 are connected together by a shaft 100 extending in the lengthwise direction of the bottle holder 21.

The cam member 97 is made up of a pair of fence members 97a and 97b facing each other. The fence members 97a and 97b guide the roller 95 from the side and support the flange of the roller 95 from below the roller 95. The fence members 97a and 97b are configured such that the distance from the center of rotation Z decreases with the decrease in the distance to the front wall 96 decreases. As shown in FIG. 29B, the front end portion of the fence member 97a is

REPLACEMENT SHEET
19 FEB 1997

inclined downward toward the front end such that the roller 95 can start contacting it smoothly just before the bottle holder 21 is fully moved from the position A to the position B.

The bracket 89 has a boss 89a on the vertical wall thereof. A rod 90 is slidably received in a hole surrounded by the boss 89a of the bracket 89. An abutment 91 is affixed to the rod 90 and capable of abutting against the rear end of the bottle 20. A spring is loaded between the vertical wall of the bracket 89 and the abutment 91 and constantly biases them away from each other.

In operation, when the bottle holder 21 is held in the position B, the roller with the flange 95 is held in a position closest to the base end of the bottle holder 21 by the cam member 97, as shown in FIGS. 27 and 28. The collet chuck 30 connected to the roller 95 by the shaft 100 is also located at a position closest to the base end of the bottle holder 21. In this condition, the chuck 30 retains the lid 25 at a position remote from the mouth portion 23 of the bottle 20, thereby allowing the toner from being discharged from the mouth portion 23. The bottle 20 has the rear end thereof urged by the abutment 91 and spring 92 toward the base end of the bottle holder 21. The end of the bottle 20 having the mouth portion 23 is abutted against the end of the stop cover 48. Therefore, the bottle 20 is positioned in the longitudinal direction of the bottle holder 21. In this sense, the abutment

REPLACEMENT SHEET
19 FEB 1997

91, as well as the members associated therewith, constitute a mechanism for positioning the bottle 20 on the bottle holder 21.

When the bottle holder 21 is moved from the position B to the position A, the roller 95 is guided by the cam member 97 toward the movable end of the bottle holder 21. At the same time, the chuck 30 is moved toward the mouth portion 23 of the bottle 20. While the roller 95 is so guided by the cam member 97, the lid 25 held by the chuck 30 is fully inserted into the mouth portion 23 when the distance between the bracket 89 and the stop cover 48 is shorter than the sum of the length of the bottle 20 and the unstressed length of the spring 92 and when the abutment 91 is positioning the bottle 20. If desired, to generate a sufficient force for inserting the lid 25, a cam member, not shown, may be provided against which the rear end of the rod 90 abuts when the bottle holder 21 is moved from the position B to the position A. Then, the rod 90, compared to the bracket 89, will be continuously urged toward the chuck 30 and cause the rear end of the bottle 21 to abut against the abutment 91 of the rod 90.

As the bottle holder 21 is further moved toward the position A, the roller 95 is released from the cam member 97. FIG. 30 shows a condition wherein the bottle holder 21 has arrived at the position A. In this condition, the mouth portion 23 of the bottle 20 has been fully sealed by the lid 25, the

REPLACEMENT SHEET
19 FEB 1997

chucking portion of the chuck 30 has been opened wide enough to release the lug 26 of the lid 25, and the abutment 91 has been moved away from the rear end of the bottle 20.

Assume that the chuck 30 has been accidentally retracted toward the base end of the bottle holder 21 after the roller 95 had been released from the cam member 97. Then, the larger diameter portion 63 of the chuck 30 (see FIG. 31A) will be engaged with and squeezed by the core 39 which is stopped by the stop cover 48, chucking the lug 26 of the lid 25. This obstructs the removal of the bottle 20 and the insertion of a new bottle 20. In the light of this, as shown in FIG. 28, a cam member 101 is additionally located adjacent the center of rotation Z and provided with a particular cam surface. Specifically, while the roller 95 and cam member 97 are released from each other, the cam surface of the cam member 101 restricts the rear end of the chuck 30 such that the chuck 30 does not retract toward the base end of the bottle holder 21. The cam member 101 may also implement the relative position of the chuck 30 and core 39 for opening the chucking portion 33 thereof, if desired.

When the bottle holder 21 is moved from the position A to the position B, the roller 95 is brought into contact with the cam member 97. Subsequently, the bracket 89 and chuck 30 are each moved toward the base end of the bottle holder 21. As a result, the bottle 20 is positioned on the bottle

REPLACEMENT SHEET
19 FEB 1997

holder 21 while the lid 25 is removed from the bottle 20. The resulting condition is shown in FIGS. 27 and 28.

Another difference between the previously described toner supply unit 17 and the toner supply unit 17 described above is as follows. The previous toner supply unit 17 maintains the chucking portion 33 of the chuck 30 sufficiently open by setting up a condition which prevents an external force tending to squeeze the portion 33 from acting. By contrast, the toner supply unit 17 described above applies an external force tending to open the chucking portion 33 to the portion 33 positively.

Specifically, as shown in FIG. 31A, the chuck 30 has a slit portion 30a positioned at the rear of a slit portion 30b contiguous with the portion 30a and having a greater width than the portion 30a. The chuck 30 is slidable in the bore formed in the core 39. As shown in FIG. 31B, the inner periphery of the core 39 is formed with projections 102 which are received in the individual (three in this case) slits of the chuck 30. Further, the chuck 30 has a portion 103 even larger in diameter than the larger diameter portion 63, and a substantially vertical abutment or shoulder 104 between the portions 103 and 63.

The core 39 shown in FIG. 31A is substantially identical with the core 39 of FIG. 14A except for the projections 102. In FIG. 31A, the reference numeral 105 designates the

REPLACEMENT SHEET
19 FEB 1997

opposite ends of each seal member which are abutted against each other.

FIGS. 32A and 32B are views representative of a relation between the above-stated chuck 32 and the core 39 and the position of the chucking portion 33. Specifically, FIG. 32A shows a condition wherein the core 39 is abutted against and stopped by the stop cover 48 (not shown) when, for example, the bottle holder 21 is held in the position A. In this condition, the projections 102 of the core 39 are positioned in the individual narrow slit portions 30a, opening the chucking portion 33 positively by wedging them. On the other hand, FIG. 32B shows a condition wherein the collet chuck 33 is retracted a certain distance due to the contact of the roller 95 and cam member 97 when, for example, the bottle holder 21 is brought from the position A to the position B. In this condition, the boss of the core 39 biased by the spring 51 is stopped by the shoulders 104 of the chuck 30, squeezing the chucking portion 33.

Furthermore, the previous toner supply unit 17 transmits the rotation of the gear link 38 to the bottle 20 by forming the bottle ribs 57 on the end of the bottle 20 having the mouth portion 23 and forming the link ribs 58 on the end of the gear link 38. On the other hand, as shown in FIG. 33, the modified toner supply unit 17 provides the bottle 20 with a recess 106 in place of the bottle rib 57 and causes the link

REPLACEMENT SHEET
19 FEB 1997

rib 58 to mate with the recess 58. However, a transmission mechanism similar to the mechanism of the previous embodiment may also be used, as shown in FIG. 34A-34D. FIG. 34D shows the inner peripheral configuration of the gear link 38, as viewed in the direction indicated by an arrow A in FIG. 34C.

Assume that the bottle rib 57 is formed on the outer periphery of the bottle 20, as shown in FIGS. 34A and 34B, and that the bottle 20 is molded by use of resin. Then, as shown in FIGS. 35A-35E, it is preferable to form the bottle rib 57 in a parting line portion between mold parts. This allows the bottle 20 to have a relatively thick wall at the portion where the rib 57 is positioned, compared to a case wherein the rib 57 is located in any other position. Any desired number of ribs 57 may be formed if they are provided at the parting portions of cooperative mold parts. Specifically, two parting lines are available with the two bisected mold parts shown in FIGS. 35A-35E. Four parting lines will be available when four mold parts are used.

The recess 106, FIG. 33, formed in the bottle 20 is a specific implementation for transmitting the rotation of the gear link 38 to the bottle 20. Alternatively, at the shoulder of the bottle 20, the part of the outer periphery corresponding to the inner peripheral raised portion 85 may be brought into engagement with the link rib 58 or similar engaging portion

REPLACEMENT SHEET
19 FEB 1997

of the gear link 38, as shown in FIGS. 36A and 36B by way of example. As shown in FIG. 36A, the gear link 38 has an engaging portion 200 engageable with the portion 85a of the outer surface of the bottle 20 corresponding to the inner raised portion 85. When the head portion of the bottle 20 is inserted into the gear link 38, the engaging portion 200 engages with the portion 85a of the bottle 20. FIG. 36B shows the portion 85a of the bottle 20 and the portion 200 of the gear link 38 abutting against each other. In FIG. 36B, the reference numeral 200a designates the surface of the portion 200 directly contacting the portion 85a. When the portions 85a and 200 substantially perpendicular to the direction of rotation are brought into engagement, the bottle 20 is caused to rotated about the axis thereof together with the gear link 38. This kind of drive transmission makes it needless to form the bottle rib 57 or similar projection on the bottle 20 and, therefore, reduces the production cost of the bottle 20. In addition, drive transmission is insured since the engaging portion 200 of the gear link 38 abuts against the portion 85a of the bottle 20.

As shown in FIG. 37, the bottle 20 may be provided with two contact surfaces on the end thereof. As shown, a contact surface 201 is formed at a position 180 degrees spaced apart from the above-stated portion 85a in the direction of rotation of the bottle 20. The gear link 38 is formed with two

REPLACEMENT SHEET
19 FEB 1997

engaging portions 200 engaging the surfaces 85a and 201 of the bottle 20, respectively. In this case, the inner periphery of the bottle 20 corresponding to the additional contact surface 201 may also be configured as a raised portion for raising the toner.

FIGS. 38 and 39A-39C show another specific configuration of the bottle 20. As shown, the bottle 20 has two raised portions 85 (represented by the corresponding outer peripheral portions 85a) which are spaced apart 180 degrees in the direction of rotation of the bottle 20 and symmetrical to each other with respect to the axis of the bottle. In the figures, the same portions as the portions of any one of the previous specific configurations are designated by the same reference numerals. In this configuration, while the bottle 20 performs one rotation, the toner is guided twice to the mouth portion 23 along the raised portions 85. Hence, when only a small quantity of toner is left in the bottle 20, it can be discharged from the mouth portion 23 more positively. Moreover, since the bottle 20 and the gear link 38 are engaged with each other at two spaced positions, the sure drive transmission from the link 38 to the bottle 20 is further promoted.

Generally, the characteristic of a toner, e.g., chargeability and color depend on the developing unit. Therefore, it is necessary to prevent a bottle 20 containing a

REPLACEMENT SHEET
19 FEB 1997

toner different in characteristic from an expected toner from being mounted to the toner supply unit 17. For this purpose, the bottle 20 shown in FIG. 38 and 39A-39C is provided with a lug 204 in a portion thereof extending from the circumferential edge of the color 24 to a shoulder 205. The lug 204 is sized and positioned in matching relation to the characteristic of the toner to be contained in the bottle 20. The end wall of the gear link 38 is formed with a recess in the inner surface thereof which can receive the lug 204 of a bottle 20, containing an expected toner, when the bottle 20 is inserted into the link 38. When a bottle containing an unexpected toner is put on the toner supply unit 17, it cannot be fully inserted into the gear link 38 since the lug 204 does not match the recess of the link 38 in size or position. If desired, the bottle 20 and the gear link 38 may be provided with the recess and the lug, respectively.

The bottle 20 may be provided with three or more engaging portions engageable with the gear link 38 or three or more raised portions 85 in order to more surely transmit the rotation of the link 38 to the bottle 20 or to further promote the discharge of a small quantity of toner remaining in the bottle 20. Again, such engaging portions or raised portions should preferably be located at equally spaced locations in the direction of rotation of the bottle 20. Specifically, FIGS. 40A-40C show the bottle 20 having the raised portions

REPLACEMENT SHEET
19 FEB 1997

(represented by the outer surfaces 85a corresponding thereto) and engaging portions 203 which alternate with each other at angular intervals of 90 degrees. In these figures, the same portions as the portions of any one of the specific bottle configurations shown and described are designated by the same reference numerals.

The gear link 38 may be provided with a greater number of engaging portions than the bottle 20 in order to promote smooth insertion of the front end of the bottle into the gear link 38. Specifically, as shown in FIG. 41, the bottle 20, like the bottle 20 shown in FIG. 39, has two raised portions 85 spaced about 180 degrees and symmetrical to each other; the outer surfaces 85a of the raised portions 85 are each used as an engaging surface. The end wall of the gear link 38 is formed with four arcuate rims 202 on the inner periphery thereof. The rims 202 are convex toward the axis of the gear link 38, as viewed in a cross-section, and arranged symmetrically with respect to the axis of the link 38. As shown in FIG. 42B, the rims 202 are each inclined an angle α at the upper edge 202b thereof facing the bottle inlet of the gear link 38. Assume that when the bottle 20 is inserted into the gear link 38, the portions of the bottle 20 between the circumferential edge of the collar 24 and the shoulders 205 abut against the upper edges 202b of the rims 202. Then, such portions of the bottle 20 slide on the rims 202 along the

REPLACEMENT SHEET
19 FEB 1997

inclination α while rotating about the axis thereof. As a result, the bottle 20 is inserted into the gear link 38 smoothly. For smooth insertion, the angle α should preferably be less than 30 degrees. Each rim 202 has a surface 202a facing the axis of the gear link 38. Such surfaces 202a of the rims 202 abut against the outer surfaces 85a of the bottle to transmit the rotation of the gear link 38 to the bottle 20.

In summary, it will be seen that the present invention has various unprecedented advantages, as enumerated below.

(1) Holding means for holding a developer container is rotatable in a substantially horizontal plane for the replacement of a developer container. This eliminates the requisite that holding means and developer container each should have a length smaller than the height of an image forming apparatus, particular to a conventional system which requires the holding means to move both horizontally and vertically. Hence, the developer container can be provided with a sufficient length.

(2) A lid is automatically attached to and detached from a mouth portion included in the developer container. Therefore, only if a person mounts the developer container to the holding means, a developer can be replenished. This not only facilitates the replacement of the developer container, but also prevents the developer from falling from the mouth portion of the developer container. In addition, the developer

REPLACEMENT SHEET
19 FEB 1997

deposited on, for example, the inner surface of the mouth portion is prevented from falling to the outside.

(3) While the holding means is held in a position for mounting the developer container, the container can be removed with the mouth portion thereof sealed by a lid. This also prevents the developer deposited on the inner surface of the mouth portion from falling to the outside.

(4) The developer can be discharged from the developer container via the mouth portion effectively. In addition, the quantity of developer to be left unused on the inner periphery of the container is reduced.

(5) Drive transmission to the developer container is insured.

(6) In the event of replacement of the developer container, the holding means can be moved between the above-mentioned loading position and a toner replenishing position by a minimum of force. Further, when a motor, solenoid or similar actuator is used to move the holding means, use can be made of a miniature actuator.

(7) The developer container can be surely unlocked in position and, therefore, can be surely released from the holding means.

(8) The developer container can have the mouth portion thereof reduced in size, compared to a conventional container having a mouth portion whose diameter is substantially equal

REPLACEMENT SHEET
19 FEB 1997

to the maximum diameter of the inner surface of the shoulder. The small sized mouth portion allows a minimum of developer to deposit on the inner surface thereof and prevents the developer from flying around or falling accidentally as far as possible. When the container is transported, for example, the lid closing the mouth portion of the container can be as miniature as the mouth portion. . Hence, the lid can be attached and detached by a small force, facilitating manual attachment and detachment. This is also true when a mechanism for attaching and detaching the lid automatically is installed in a developer replenishing device. In addition, such a mechanism is reduced in size.

(9) A shoulder forming a part of the developer container and having a greater diameter than the mouth portion has the inner surface thereof partly raised to the edge of the mouth portion. When the container is rotated, the inner surface of the raised portion raises the developer around the shoulder to the mouth portion, thereby causing the toner to fall via the mouth portion. As a result, the whole developer stored in the container can be used for development. Moreover, since the rate of discharge of the developer via the mouth portion is determined by, for example, the size of the raised portion, the developer can be discharged via the mouth portion stably.

(10) A person intending to replace the developer container is prevented from removing the lid of the developer

REPLACEMENT SHEET
19 FEB 1997

container by accident. Otherwise, the developer would fall from the container to smear the surroundings.

Various modifications will become possible for those skilled in the art after receiving the teachings of the present disclosure without departing from the scope thereof.

REPLACEMENT SHEET
19 FEB 1997



Patent Claims

1. A developer container for use with a developer replenishing device having holding means for holding said developer container to allow a developer to be discharged from a mouth portion of said developer container into said developer replenishing device, and driving means for causing said developer container held by said holding means to rotate about an axis of said developer container, said developer container comprising:

a hollow cylindrical main body having said mouth portion on one end, said mouth portion being smaller in diameter than a shoulder portion which forms a circumferential wall adjacent said one end; and

guide means provided on a part of said shoulder portion for guiding said developer stored in said developer container to said mouth portion as said main body is rotated.

2. A developer container as claimed in claim 1, wherein said guide means comprises:

at least one first raised portion formed in a part of said shoulder portion and rising from said shoulder portion to an edge of said mouth portion; and

at least one second raised portion formed in a part of said shoulder portion contiguously with said first raised portion and rising toward the axis of said developer

REPLACEMENT SHEET
19 FEB 1997

container, about which said developer container is rotatable, over said edge of said mouth portion.

3. A developer container as claimed in claim 2, wherein said first and second raised portions comprise respectively a first and a second ramp surface portion each rise more in a direction of said axis as a distance from said mouth portion increases.

4. A developer container as claimed in claim 3, wherein said first and second ramp surface portions are recessed such that at least a part thereof appears, in a section along a plane containing said axis, as a curve whose center of curvature is close to said axis.

5. A developer container as claimed in claim 4, wherein said second ramp surface portion has a convex end portion which appears, in a section along said plane, as a curve whose center of curvature is remote from said axis.

6. A developer container as claimed in claim 5, wherein said guide means comprises:

two first raised portions formed in the part of said shoulder portion and rising from said shoulder portion to the edge of said mouth portion, said two first raised portions being provided on said shoulder portion at two positions 180 degrees spaced apart from each other in a direction of rotation of said developer container; and

REPLACEMENT SHEET
19 FEB 1997

* C L M S *

two second raised portions formed in the part of said shoulder portion contiguously with said two first raised portions respectively and rising toward the axis of said developer container over the edge of said mouth portion, said two second raised portions being provided on said shoulder at two positions 180 degrees apart from each other in the direction of rotation of said developer container.

7. A developer container as claimed in claim 1, wherein the axis of said developer container is aligned with an axis of said mouth portion of said developer container.

8. A developer container as claimed in claim 1, wherein said mouth portion of said developer container has a circular section.


9. A developer container as claimed in claim 5, wherein at least one spiral guide groove is formed in inner periphery of a circumferential wall of said developer container for guiding said developer to said first and second ramp surface portions.

10. A developer container as claimed in claim 9, wherein said guide groove comprises:

a first inclined wall which said developer gets over; and

a second inclined wall for conveying said developer from said first inclined wall to said first and second ramp surface portions.

REPLACEMENT SHEET
19 FEB 1997



11. A developer container as claimed in claim 9, wherein said main body is formed with a grip portion smaller in diameter than said shoulder portion.

12. A developer container as claimed in claim 2, further comprising a driven portion engageable with a drive portion of said driving means for causing said developer container to rotate.

13. A developer container as claimed in claim 12, wherein said driven portion comprises a projection formed on said one end of said main body and engageable with an engaging member included in said drive portion.

14. A developer container as claimed in claim 12, wherein said driven portion comprises a recess formed in said one end of said main body and engageable with an engaging member included in said drive portion.

15. A developer container as claimed in claim 12, wherein said driven portion comprises an outer surface of said first raised portion engageable with an engaging portion included in said drive portion.

16. A developer container as claimed in claim 15, wherein said driven portion further comprises a contact surface engageable with said engaging portion of said drive portion and provided on said shoulder portion at a position 180 degrees spaced apart from said outer surface of said first raised portion in a direction of rotation of said

REPLACEMENT SHEET
19 FEB 1997

* C L M S *

developer container, said contact surface having a function for guiding said developer to said mouth portion.

17. A developer container as claimed in claim 2, further comprising a positioning portion to be positioned on said holding means by a locking member included in said holding means.

18. A developer container as claimed in claim 17, wherein said positioning portion comprises an engaging portion formed in a predetermined position on an outer surface of a circumferential wall of said main body and engageable with said locking member.


19. A developer container as claimed in claim 18, wherein said engaging portion is convex.

20. A developer container as claimed in claim 18, wherein said engaging portion is concave.

21. A developer container as claimed in claim 17, further comprising a projection formed on an outer surface of said circumferential wall and facing said positioning portion, said projection causing said locking member of said holding means to hit against said outer surface of said circumferential wall as said developer container is rotated.

22. A developer container as claimed in claim 2, further comprising an annular collar protruding outward from said mouth portion of said developer container.

REPLACEMENT SHEET
19 FEB 1997



23. A developer container as claimed in claim 22, wherein a plurality of projections are formed on an outer surface of a circumferential wall of said collar.

24. A developer container as claimed in claim 22, further comprising a lid for closing said mouth portion.

25. A developer container as claimed in claim 24, wherein said lid comprises a bottom wall portion to seal said mouth portion, and a circumferential wall portion to fit in said mouth portion.

26. A developer container as claimed in claim 25, wherein said lid comprises a lug extending out from substantially the center of said bottom wall portion to be chucked when said lid is attached or detached.

27. A developer container as claimed in claim 26, wherein said lid further comprises preventing means located in a space between an inner surface of said circumferential wall and said lug for preventing a person from nipping said lug.

28. A developer container as claimed in claim 27, wherein said preventing means comprises an annular obstruction surrounding said lug.

29. A developer container as claimed in claim 27, wherein said preventing means comprises a plurality of elongate pin-like members studded around said lug.

REPLACEMENT SHEET
19 FEB 1997

* C L M S *

30. A developer container as claimed in claim 27, wherein said preventing means comprises a concealing member concealing said lug.

31. A developer container as claimed in claim 30, wherein said concealing member comprises a thin flat piece concealing neighborhood of said lug. and an annular portion formed integrally with an outer peripheral portion of said thin flat piece.

32. A developer container as claimed in claim 31, wherein said thin flat piece is formed with a hole at the center thereof which is slightly greater in diameter than said lug, and a number of slits extending radially outward from said hole.

33. A developer container as claimed in claim 25, wherein said lid further comprises a connecting portion connecting said bottom wall portion and said circumferential wall portion and inclined in a direction in which said lid may be removed.

34. A developer container as claimed in claim 33, wherein said connecting portion is thinner than said bottom wall.

35. A developer container as claimed in claim 33, wherein said lid further comprises a portion having a saw-toothed section and formed on a surface of said circumferential wall to fit in said mouth portion.

REPLACEMENT SHEET
19 FEB 1997

* C L M S *

36. A toner bottle for use with a toner replenishing device having a bottle holder into which a mouth portion of said toner bottle may fit for discharge of a toner in said toner bottle into said toner replenishing device, and a drive unit which rotatably drives said toner bottle when said toner bottle is mounted to said toner replenishing device, said toner bottle comprising:

a main body comprising a substantially hollow container having, adjacent one end of said toner bottle, a first diameter portion;

a discharge mouth at said one end, said discharge mouth comprising said mouth portion and having a second diameter substantially smaller than said first diameter; and

a circumferential and radially extending ramp surface configuration of the peripheral surface of said main body at said one end and connecting radially between said first diameter portion and a radial position no greater than said second diameter portion.

37. A toner bottle as claimed in claim 36, wherein said ramp surface portion rises to a radial position smaller than said first diameter so as to define a metering edge above which a metered amount of toner must flow to reach said mouth position.

This Sheet Has Been Replaced

REPLACEMENT SHEET
19 FEB 1997

* C L M S *

38. A toner bottle as claimed in claim 37, wherein said ramp surface portion is curved in the circumferential direction..

39. A toner bottle as claimed in claim 38, wherein said ramp surface portion is concavely shaped to define a toner holding spoon portion.

40. A toner bottle for use with a toner replenishing device having a bottle holder into which a mouth portion of said toner bottle may fit for discharge of a toner in said toner bottle into said toner replenishing device, and a drive unit which rotatably drives said toner bottle about a longitudinal axis thereof when said toner bottle is mounted to said toner replenishing device, said toner bottle comprising:

a main body comprising a substantially hollow container; and

a rotational force transfer projection or recess on a radially extending surface of said main body and cooperating with said bottle holder for transferring rotation of said bottle holder to said toner bottle.

41. A toner bottle for use with a toner replenishing device having a mouth portion for discharge of toner in said toner bottle into said toner replenishing device, and a drive unit which rotatably drives said toner bottle when said toner bottle is mounted to said toner replenishing device, said toner bottle comprising:

This Sheet Has Been Replaced

REPLACEMENT SHEET
19 FEB 1997

* C L M S *

a main body comprising a substantially hollow container having, adjacent one end of said bottle, a first diameter portion;

a discharge mouth at said one end, said discharge mouth comprising said mouth portion and having a second diameter substantially smaller than said first diameter; and

a circumferential and radially extending ramp surface configuration of said main body at said one end and connecting radially between said first diameter portion and a radial position no greater than said second diameter portion such that a controllable quantity of toner in said toner bottle is raised radially from said first diameter portion to said second diameter portion for feeding said controllable quantity of toner to said discharge mouth when said toner bottle is rotated by said drive unit.

42 A toner bottle as claimed in claim 41, further comprising said toner in said bottle.

43. A toner bottle as claimed in claim 41, further comprising a rotation prevention projection on a radially extending surface of said main body adjacent said one end.

44. A toner bottle as claimed in claim 43, further comprising a spiral member formed on said main body for conveying said toner toward said mouth portion.

This Sheet Has Been Replaced

REPLACEMENT SHEET
19 FEB 1997

* C L M S *

45. A toner bottle as claimed in claim 44, wherein said spiral member defines an edge of said ramp surface configuration.

46. A device for replenishing a developing device of an image forming apparatus with a developer, comprising:

a developer container containing a developer and having a mouth portion; and

holding means communicated to a developer replenishing section for holding said developer container while orienting said mouth portion toward said developer replenishing section;

said holding means being rotatable about one end in a substantially horizontal plane.

47. A device as claimed in claim 46, further comprising detaching means for detaching a lid from said developer container which is held by said holding means with said mouth portion closed by said lid.

48. A device as claimed in claim 47, further comprising attaching means for attaching said lid to said mouth portion of said developer carrier to thereby seal said mouth portion.

49. A device as claimed in claim 48, wherein said holding means is movable between a first position where said developer container may be mounted to said holding means easily, and a second position where said holding means is communicable to said developer replenishing section.

This Sheet Has Been Replaced

REPLACEMENT SHEET
19 FEB 1997

* C L M S *

50. A device as claimed in claim 49, further comprising control means for controlling said detaching means and said attaching means such that, at least when said holding means is located at said first position, said lid is fully attached to said mouth portion while, at least when said holding means is located at said second position, said lid is fully detached from said mouth portion.

51. A device as claimed in claim 49, wherein said detaching means and said attaching means each comprises :

retaining means selectively assuming an operative position for retaining said lid or an inoperative position for releasing said lid; and

moving means for moving at least one of said retaining means and said developer container toward and away from the other.

52. A device as claimed in claim 51, further comprising:

urging means for urging said developer container toward said mouth portion in a direction for causing said retaining means or said developer container to move; and

positioning means for positioning said developer container in contact with said mouth portion.

53. A device as claimed in claim 52, further comprising driving means for causing said developer container held by said holding means to rotate about a longitudinal axis thereof.

This Sheet Has Been Replaced

REPLACEMENT SHEET
19 FEB 1997

* C L M S *

54. A device as claimed in claim 53, wherein said driving means comprises a motor, and transmitting means for transmitting rotation of said motor to said developer container.

55. A device as claimed in claim 54, wherein said transmitting means comprises an annular gear link rotatable about said axis of said developer container, and comprising an engaging portion engageable with an engaging portion formed on a shoulder portion of one end, adjacent said mouth portion, of a hollow cylindrical main body of said developer container.

56. A device as claimed in claim 55, wherein said engaging portion of said gear link comprises an link rib engageable with a bottle rib formed on said one end of said developer container where said engaging portion is provided.

57. A device as claimed in claim 55, wherein said engaging portion of said gear link comprises an engaging portion engageable with an outer surface of at least one raised portion which is formed in a part of said shoulder portion and raised from said shoulder portion of said main body to an edge of said mouth portion.

58. A device as claimed in claim 57, wherein said engaging portion of said gear link is further engageable with a contact surface provided on said shoulder portion at a position 180 degrees spaced apart from said outer surface of said raisd portion in a direction of rotation of said developer

This Sheet Has Been Replaced

REPLACEMENT SHEET
19 FEB 1997

* C L M S *

container, said contact surface having a function for guiding said developer to said mouth portion.

59. A device as claimed in claim 57, wherein said engaging portion of said gear link comprises two engaging portions engageable with outer surfaces of two raised portions provided on said shoulder portion at two positions 180 degrees apart from each other in a direction of rotation of said developer container.

60. A device as claimed in claim 51, further comprising rotating means for rotating said retaining means about said longitudinal axis of said developer container when said lid is detached from or attached to said mouth portion.

61. A device as claimed in claim 51, further comprising a cam device for causing said moving means to move when said image forming apparatus and a predetermined portion of said holding means are moved relative to each other between said first and second positions.

62. A device as claimed in claim 61, further comprising restricting means for restricting movement of said moving means at said first position such that said holding means urges said lid against said mouth portion.

63. A device as claimed in claim 61, wherein said holding means is rotatable about a shaft adjoining one end of said holding means, said cam device adjoining said shaft.

This Sheet Has Been Replaced

REPLACEMENT SHEET
19 FEB 1997

* C L M S *

64. A device as claimed in claim 48, wherein said detaching means comprises:

a collet chuck for retaining said lid by chucking a lug extending out from said lid;

moving means for causing at least one of said collet chuck and said developer container to move toward and away from the other; and

control means for opening, when said collet chuck and said developer carrier are spaced apart a predetermined distance, a chucking portion of said collet chuck to allow said lug to enter, and squeezing, as the distance is increased by said moving means, said chucking portion to retain said lug of said lid.

65. A device as claimed in claim 64, wherein said control means comprises:

a larger diameter portion on periphery of said collet chuck;


a core slidably coupled over a smaller diameter portion of said collet chuck opposite to said chucking portion with respect to said larger diameter portion;

biasing means for constantly biasing said core toward said mouth portion of said developer container;

an engaging portion on said core for squeezing said chucking portion of said collet chuck; and

This Sheet Has Been Replaced

REPLACEMENT SHEET
19 FEB 1997



restricting means for restricting movement of said core against a force of said biasing means.

66. A device as claimed in claim 65, further comprising:

positioning means for positioning, against the force of said biasing means, said developer container held by said holding means at a position where an edge of said mouth portion functions as said restricting means; and

a restricting member functioning, when said developer container is removed from said holding means, as said restricting means by restricting movement of said core at a position remote from said edge of said mouth portion of said developer container which is positioned by said positioning means.

67. A device as claimed in claim 66, wherein an engaging portion is formed on a circumferential wall of said developer container, said positioning means being movable between an operative position for causing said engaging portion to engage with said engaging portion of said developer container and an inoperative position remoter from said circumferential wall than said operative position.

68. A device as claimed in claim 64, wherein said detaching means further comprises:

a cover supporting said collet chuck in such a manner as to allow said collet chuck to move toward and away from said developer container which is held in a predetermined position

This Sheet Has Been Replaced



REPLACEMENT SHEET
19 FEB 1997

* C L M S *

of said holding means, said cover comprising an end wall having a hole throughout which said collet chuck extends, and a circumferential wall surrounding said collet chuck;

a core slidably coupled over said collet chuck and constantly biased toward said developer container, said core comprising an end portion capable of abutting against a flange included in said lid; and

an end seal for sealing a gap between said end portion and said flange of said lid.

69. A device as claimed in claim 68, wherein said end seal is provided with a multi-stage seal structure.

70. A device as claimed in claim 69, wherein said end seal comprises a plurality of elongate rectangular seal elements each having opposite ends thereof abutted against each other while surrounding said core, said seal members, which adjoin in an axial direction of aid core, being deviated, in a circumferential direction of said core, from each other in the position where the opposite ends are abutted.

71. A device as claimed in claim 68, wherein at least a surface of said end seal is made of 4-fluoro ethyrene polymer.

72. A device as claimed in claim 68, wherein said end seal comprises an annular seal member made up of a first elastic material enriched in elasticity mainly in a circumferential direction and and a second elastic material provided on said first elastic material and enriched in

This Sheet Has Been Replaced

REPLACEMENT SHEET
19 FEB 1997

* C L M S *

elasticity mainly in a direction of thickness, said seal member being fitted on a circumferential surface of said core.

73. A device as claimed in claim 48, wherein said attaching means comprises:

a collet chuck for chucking a lug extending out from said lid;

moving means for causing at least one of said collet chuck and said developer container to move toward and away from the other; and

releasing means for opening a chucking portion of said collet chuck to release said lug when or before or after a distance between said collet chuck and said developer container is reduced by said moving means to fully seal said mouth portion by said lid retained by said collet chuck.

74. A device as claimed in claim 73, wherein said releasing means comprises:

a core slidably mounted on said collet chuck and constantly biased by biasing means toward said mouth portion of said developer container;

a projection on said core and received in a slit formed in said collet chuck, said projection wedging, when brought to a rear narrow portion of said slid, said collet chuck to thereby open a chucking portion of said collet chuck; and

This Sheet Has Been Replaced

REPLACEMENT SHEET
19 FEB 1997

* C L M S *

restricting means for restricting, when said distance is reduced by said moving means until or before or after said lid fully closes said mouth portion, movement of said core against a force of said biasing means to thereby displace said projection from a broad portion of said lid to said narrow portion.

75. A device as claimed in claim 73, wherein said attaching means further comprises:

a cover supporting said collet chuck in such a manner as to allow said collet chuck to move toward and away from said developer container which is held in a predetermined position of said holding means, said cover comprising an end wall having a hole throughout which said collet chuck extends, and a circumferential wall surrounding said collet chuck;

a core slidably coupled over said collet chuck and constantly biased toward said developer container, said core comprising an end portion capable of abutting against a flange included in said lid; and

an end seal for sealing a gap between said end portion and said flange of said lid.

76. A device as claimed in claim 75, wherein said end seal is provided with a multi-stage seal structure.

77. A device as claimed in claim 76, wherein said end seal comprises a plurality of elongate rectangular seal elements each having opposite ends thereof abutted against

This Sheet Has Been Replaced

* C L M S *

each other while surrounding said core, said seal members, which adjoin in an axial direction of said core, being deviated, in a circumferential direction of said core, from each other in the position where the opposite ends are abutted.

78. A device as claimed in claim 77, wherein at least a surface of said end seal is made of 4-ethyrene fluoride resin.

79. A device as claimed in claim 77, wherein said end seal comprises an annular seal member made up of a first elastic material enriched in elasticity mainly in a circumferential direction and and a second elastic material provided on said first elastic material and enriched in elasticity mainly in a direction of thickness, said seal member being fitted on a circumferential surface of said core.

REPLACEMENT SHEET
19 FEB 1997

This Sheet Has Been Replaced

ABSTRACT OF THE DISCLOSURE

DEVELOPER REPLENISHING DEVICE AND DEVELOPER CONTAINER FOR USE THEREWITH

A developer replenishing device for replenishing a developing device with a developer, and a developer container for use therewith. The developer container, or toner bottle, has a mouth portion at one end thereof which is smaller in diameter than a hollow cylindrical main body. At the end of the bottle provided with the mouth, a shoulder has the inner periphery thereof partly raised to the edge of the mouth portion to form a raised portion for scooping up a toner. In addition, a part of the inner periphery of the circumferential wall of the bottle which is contiguous with the raised portion is also raised toward the axis of the bottle about which the bottle is rotatable, thereby forming another raised portion. When the bottle is mounted to a bottle holder, which is included in the replenishing device, substantially horizontally with the mouth portion oriented sideways, the bottle is rotated to raise the toner from the bottom of the main body to the mouth portion. As a result, the toner is discharged to the outside via the mouth portion smoothly.

FIGURE 1B

This Sheet Has Been Replaced

REPLACEMENT SHEET
19 FEB 1997

REPLACEMENT SHEET
19 FEB 1997

FIG. 1A





FIG. 1B



REPLACEMENT SHEET
19 FEB 1997




FIG. 2

FIG. 3A





FIG. 3B



REPLACEMENT SHEET
19 FEB 1997

FIG. 4A




FIG. 4B






FIG. 4C



REPLACEMENT SHEET
19 FEB 1997

FIG. 5A



REPLACEMENT SHEET
19 FEB 1997

FIG. 5B




FIG. 5C




FIG. 5D





FIG. 5E







FIG. 6

REPLACEMENT SHEET
19 FEB 1997

FIG. 7



REPLACEMENT SHEET

19 FEB 1997




FIG. 8

REPLACEMENT SHEET
19 FEB 1997

FIG. 9A





FIG. 9B



REPLACEMENT SHEET
19 FEB 1997

FIG. 10A





FIG. 10B



REPLACEMENT SHEET
19 FEB 1997

FIG. 11A





FIG. 11B



REPLACEMENT SHEET
19 FEB 1997

FIG. 12A






FIG. 12B



REPLACEMENT SHEET
19 FEB 1997

FIG. 13A



REPLACEMENT SHEET
19 FEB 1997

FIG. 13B





FIG. 13C



REPLACEMENT SHEET
19 FEB 1997

FIG. 14A




FIG. 14B




FIG. 14C




FIG. 14D





FIG. 14E



REPLACEMENT SHEET
19 FEB 1997

FIG. 15





FIG. 16



REPLACEMENT SHEET
19 FEB 1997

FIG. 17A





FIG. 17B



REPLACEMENT SHEET

19 FEB 1997

FIG. 17D




FIG. 17C




FIG. 18A





FIG. 18B



REPLACEMENT SHEET
19 FEB 1997

FIG. 18C




FIG. 18D




FIG. 19A




FIG. 19B





FIG. 19C



REPLACEMENT SHEET
19 FEB 1997

FIG. 19D




FIG. 20A




FIG. 20B




FIG. 20C




FIG. 20D




FIG. 20E




FIG. 20F





FIG. 20G



REPLACEMENT SHEET
19 FEB 1997

FIG. 21A




FIG. 21B




FIG. 21C





FIG. 21D



REPLACEMENT SHEET
19 FEB 1997




FIG. 22C




FIG. 22D




FIG. 22A




FIG. 22B

REPLACEMENT SHEET
19 FEB 1997




FIG. 23C




FIG. 23D




FIG. 23A




FIG. 23B

REPLACEMENT SHEET
19 FEB 1997

FIG. 24A




FIG. 24B





FIG. 24C



REPLACEMENT SHEET
19 FEB 1997

FIG. 25




FIG. 26A





FIG. 26B



REPLACEMENT SHEET
19 FEB 1997




FIG. 27

REPLACEMENT SHEET
19 FEB 1997




FIG. 28

REPLACEMENT SHEET
19 FEB 1997

FIG. 29A





FIG. 29B



REPLACEMENT SHEET
19 FEB 1997




FIG. 30

REPLACEMENT SHEET
19 FEB 1997

FIG. 31A





FIG. 31B



REPLACEMENT SHEET
19 FEB 1997

FIG. 32A






FIG. 32B



REPLACEMENT SHEET
19 FEB 1997

FIG. 33



REPLACEMENT SHEET
19 FEB 1997

FIG. 34B




FIG. 34D




FIG. 34A





FIG. 34C



REPLACEMENT SHEET
19 FEB 1997

FIG. 35A




FIG. 35B




FIG. 35C




FIG. 35D





FIG. 35E



REPLACEMENT SHEET
19 FEB 1997

FIG. 36A





FIG. 36B



REPLACEMENT SHEET
19 FEB 1997

FIG. 37





FIG. 38



REPLACEMENT SHEET
19 FEB 1997

FIG. 39A




FIG. 39B





FIG. 39C



REPLACEMENT SHEET
19 FEB 1997

FIG. 40A




FIG. 40B






FIG. 40C



REPLACEMENT SHEET
19 FEB 1997

FIG. 41



REPLACEMENT SHEET
19 FEB 1997

FIG. 42A




FIG. 42B





FIG. 42C



REPLACEMENT SHEET
19 FEB 1997

REPLACEMENT SHEET
20 FEB 1998

REPLACEMENT SHEETS SG
☐ Description : paged ..... to paged .....
☐ Claim(s) : paged ..... to paged .....
☐ Drawing(s) : paged ..... to paged .....
☑ Abstract : paged 73 to paged .....
DATE OF RECEIPT 20 FEB 1998

ABSTRACT OF THE DISCLOSURE

DEVELOPER REPLENISHING DEVICE AND DEVELOPER CONTAINER FOR USE THEREWITH

A developer replenishing device for replenishing a developing device with a developer, and a developer container for use therewith. The developer container, or toner bottle, has a mouth portion at one end thereof which is smaller in diameter than a hollow cylindrical main body. At the end of the bottle provided with the mouth, a shoulder has the inner periphery thereof partly raised to the edge of the mouth portion to form a raised portion for scooping up a toner. In addition, a part of the inner periphery of the circumferential wall of the bottle which is contiguous with the raised portion is also raised toward the axis of the bottle about which the bottle is rotatable, thereby forming another raised portion. When the bottle is mounted to a bottle holder, which is included in the replenishing device, substantially horizontally with the mouth portion oriented sideways, the bottle is rotated to raise the toner from the bottom of the main body to the mouth portion. As a result, the toner is discharged to the outside via the mouth portion smoothly.

FIGURE 1B

replace 73-85