CLAIMS

1. A computing device, comprising:

a near-field communication (NFC) interface;

memory configured to store instructions; and

one or more processors coupled with the memory, the one or more processors operable to execute the instructions that, when executed, cause the one or more processors to:

receive data and a checksum value in one or more messages from a contactless card via the NFC interface;

determine a second checksum value based on the data;

determine whether the checksum value and the second checksum match; and

in response to the checksum value not matching the second checksum value, increase power for the NFC interface to receive the data and the checksum value again from the contactless card via the NFC interface, wherein the one or more processors are configured to repeatedly increase the power to continue to receive the data and the checksum value until the checksum value matches the second checksum value or a timeout event occurs.

2. The computing device of claim 1, wherein the one or more messages are NFC data exchange format (NDEF) messages.

3. The computing device of claim 1, wherein the data and the checksum value are received in the one or more messages based on an NFC read operation.

4. The computing device of claim 1, wherein the instructions are further configured to cause the one or more processors to:

determine an amount of the data not received based on the second checksum value; and

increase the power for the NFC interface to an amount proportional to the amount of the data not received.

5. The computing device of claim 1, wherein a first adjustment of the power includes the one or more processors to increase power for the NFC interface from a first power level to a

second power level such that a magnetic field emitted from the NFC interface is increased or strengthened.

6. The computing device of claim 5, wherein the instructions are further configured to cause the one or more processors to:

receive one or more subsequent messages from the contactless card at the second power level;

determine that data and checksum value in the one or more subsequent message is received correctly based on the checksum value and a calculated checksum value performed on the data; and

decrease the power to the NFC interface.

7. The computing device of claim 5, wherein the instructions are further configured to cause the one or more processors to automatically decrease the power to the NFC interface after a predetermined period of time.

8. The computing device of claim 1, wherein the power, after each increase, is: (i) a fraction of a maximum power providable to the NFC interface, wherein the fraction of the maximum power is inversely proportional to a percentage of the one or more messages that was correctly received; or (ii) the maximum power providable to the NFC interface.

9. A computer-implemented method, comprising:

receiving, via an NFC interface of a computing device, data and a checksum value in one or more messages in an NFC exchange from a contactless card;

generating, by the computing device, a second checksum value based on the data and a checksum algorithm;

determining, by the computing device, the second checksum value does not match the checksum value; and

increasing, by the computing device, power for the NFC interface;

initiating, by the computing device, another NFC exchange to receive another instance of the data and the checksum value from the contactless card via the NFC interface; and

repeatedly increasing the power and receiving instances of the data and the checksum value from the contactless card until the checksum value matches a newly calculated checksum or a timeout event occurs.

10. The computer-implemented method of claim 9, wherein the one or more messages are NFC data exchange format (NDEF) messages.

11. The computer-implemented method of claim 9, wherein the data and the checksum value are received in the one or more messages based on an NFC read operation in the NFC exchange.

12. The computer-implemented method of claim 9, comprising:

determining, by the computing device, an amount of the data not received based on the second checksum; and

increasing, by the computing device, the power for the NFC interface to an amount proportional to the amount of the data not received.

13. The computer-implemented method of claim 9, wherein each adjustment of the power includes the one or more processors to increase power for the NFC interface such that a magnetic field emitted from the NFC interface is increased or strengthened.

14. The computer-implemented method of claim 13, comprising:

receiving, by the computing device, one or more subsequent messages from the contactless card at the second power level;

determining, by the computing device, that data and checksum in the one or more subsequent messages is received correctly based on the checksum value and a calculated checksum value performed on the data; and

decreasing the power to the NFC interface.

15. The computer-implemented method of claim 14, comprising automatically decreasing the power to the NFC interface after a predetermined period of time.

16. The computer-implemented method of claim 9, wherein the power, after each increase, is: (i) a fraction of a maximum power providable to the NFC interface, wherein the

fraction of the maximum power is inversely proportional to a percentage of the one or more messages that was correctly received; or (ii) the maximum power providable to the NFC interface.