

FEMALE URINATION RECEIVER

TECHNICAL FIELD OF THE INVENTION

This invention relates to a receiver for urine samples and also to a female urination receiver

BACKGROUND ART

Urine is an important diagnostic tool for measuring health and well-being of patients. The clinical information obtained from a urine specimen is influenced by the collection method, timing and handling.

A midstream clean catch Specimen is the preferred type of specimen for culture and sensitivity testing because of the reduced incidence of cellular and microbial contamination.

However, despite the importance of urine samples, their method of collection is very seldom conducted within the required protocols of hygiene and sterility.

In fact, urine samples are generally obtained by direct urination into a sample bottle or via a jug or the like into such a bottle with neither the jug nor the sample bottle being stored under sterile conditions. The collection of the sample may be accompanied by spillage or overflow and is generally unhygienic.

Furthermore, urine samples obtained in this way generally include the initial flow of excreted urine, which may not be as representative a sample as a sample from the middle of an excretion. The initial sample may include bacteria or other microorganisms that are not actually present in the urine. It is preferable to obtain a mid-stream urine flow for the purposes of obtaining more precise results.

Due to the above identified problems, even the simple dipstick tests conducted in a Doctors Surgery rooms can yield unreliable results.

In addition to the above, there is also a need for a urinating receiver that conforms to the shape of the female anatomy, and that can be used in a variety of instances, where access to a lavatory is limited. For example, during a long motorcar trip or even on a walking trip, or for Post-operative conditions as well as incontinence which provide serious difficulties for female sufferers.

It is an object of this invention to provide a urine receiver that, at least partially, alleviates some of the above mentioned problems.

DISCLOSURE OF THE INVENTION

According to the invention a urine receiver essentially for females is provided which includes an open top of saddle shape which at least approximates the configuration of the inside of the thighs, labia, or other convenient zone.

The receiver may be provided with a handle such as a jug handle as well as a spout for easy disposing of the contents.

The receiver may also have a closable outlet located in the base for discharge of the contents, or for collecting samples of urine.

The outlet closure may include a retractable plug.

A sample container may be attachable to the outlet for collecting the urine sample.

The container and the outlet may comprise a bayonet joint so that the sample container may be easily connected and disconnected from the receiver.

Alternatively the sample container may be connected to the outlet by a threaded screw connection.

Connection of the sample container to the outlet of the receiver may cause the plug to be retracted into an open position, allowing the urine to drain into the sample container.

The sample container may be a special purpose sterile container, sealed by a membrane that is pierced on connection of the container to the receiver. Alternatively, and in another embodiment of the invention the sample container may be a standard, non sterile sample bottle. The sample container may additionally include a lid for sealing the container once the sample has been obtained.

In order to provide instant pH and other pertinent detection, the receiver may include a holder for litmus or other indicators, and a suitable spillage protector for the spout.

The holder may include channels located along the interior wall of the receiver, alternatively the holder may include a separate insert receivable in the receiver. The insert may be shaped to additionally support a filter and/or sponge conforming in shape to the inside of the receiver, for absorbing the initial stream of urine and prevent unwanted ingress of microorganisms or other dirt.

The sponge may be constructed of cellulose or other absorbable material.

The insert may be located on a ledge extending around the interior of the receiver and may include a solid base sloping towards an aperture through which the urine not absorbed by the sponge, may flow.

The walls of the receiver may be transparent to allow the indicator strip to be viewed without removing it from the receiver.

A replaceable rim element adapted to fit the rim and to form a seal with the zone during use, may also be provided.

The rim element may be flexible as well as compressible so that it can seal well with a minimum of pressure being applied.

This avoids, or at least minimises soiling of the user's hands, clothes and surrounding floor, furniture and the like.

Where the receiver is to be used by various different users over a period of time, a new rim element may be provided for each new user, thus improving hygienic conditions.

A support base may be provided, on which the receiver may be located when not in use.

BRIEF DESCRIPTION OF THE DRAWINGS

An embodiment of the invention is described below with reference to the accompanying drawings, in which:

Figure 1 is an isometric projection of the receiver including the lid and support base,

Figure 2 is a side view of the receiver located on the support base,

Figure 3 is a top view of the receiver according to the invention,

Figure 4 is a bottom view,

Figure 5 is a top view of the filter/sponge insert,

and

Figure 6 is a view of a sample bottle for use with the receiver.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

In the drawings, a receiver 10 includes a saddle-shaped opening 12 with a rim 14. The receiver includes a pouring spout 20 and a handle 22.

A lid 16 is also provided to seal the receiver 10 and prevent spillage or contamination of the contents during the time lapse between providing the sample and testing of the sample

The receiver 10 is mounted on a support base 18 by a bayonet joint so that it is easily attached and removed when necessary

Referring to figures 3 and 4, an outlet 19 is located at the base of the receiver 10, for draining the urine away.

The outlet 19 includes a plug 24 biased in the closed position by a spring (not shown) and openable from the exterior of the receiver 10.

Referring to figure 5, an insert 30 for supporting a filter pad and/or sponge (not shown) is removably located inside the receiver 10, referring to figure 5, the insert includes a solid base 32, that slopes towards an aperture 34, through which the overflow urine (mid-stream urine) may flow, once the initial drops of urine have been absorbed by the sponge/filter (not shown). The insert additionally includes a channel shaped extension 36 for receiving an indicator strip, commonly referred to as a "dip stick" such as litmus. The insert includes a spillage protector 38 for covering the spout opening.

Referring to figure 6, a sample container 40 is attachable to the receiver outlet 16 for collecting the urine sample. The container 40 and the outlet 19 comprise a bayonet joint indicated by reference 42 so that the sample container may be easily connected and disconnected to and from the receiver.

In an alternative embodiment of the invention (not shown) the sample container may be connected to the outlet by a threaded screw connection.

Connection of the sample container 40 to the outlet 19 causes the plug 24 to be pushed up into an open position, allowing the urine to drain into the sample container 40.

In this embodiment of the invention, the sample container 40 is a special purpose sterile container, sealed by a membrane (not shown) that is pierced on connection of the container to the receiver 10. The sample container additionally includes a rubber lid 44 for sealing the container once the sample has been obtained.

Alternatively, and in another embodiment of the invention the sample container may be a standard, non sterile sample bottle

A rim element (not shown) that has the same shape as the rim and has a channel to engage the rim may be removably located on the rim 12. The element includes a channel that fits over the rim 12 of the receiver.

The element is both flexible and compressible so that an excellent seal is achieved in the zone of application, as described above, with minimum pressure having to be applied. In addition the degree of compression provides that the element seals with a large variety of configurations of the zone so that it can be used for a large number of different females. It may be necessary to provide a junior- size receiver.

It will be appreciated that the receiver 10 of the invention may be also conveniently used by males, in which case the rim element is not necessary.

In use, according to one embodiment of the invention, when a urine sample is required, a patient will be handed the sterilised receiver, into which the insert 30 containing new dipstick and cellulose sponge has been inserted. The outlet of the receiver will be in the closed position.

The patient will void her/his bladder into the receiver 10, and cover the receiver with the lid 16. The full receiver will be handed to the doctor or nurse, who will be able to see the dipstick through the transparent wall of the receiver 10.

Should further testing be required by a laboratory, the doctor or nurse will attach a sample container 40 to the outlet 19 of the receiver, via the bayonet joint 42, piercing the protective membrane on the sample container and opening the plug 24 in the process. In this manner, the urine drains into the sample container. Once the sample container 40 is full the container is removed from the receiver and the plug is biased back into its closed position by the outlet spring,

preventing leakage of excess urine, which may be disposed of into a suitable receptacle when convenient. The sample container is sealed with the rubber stopper lid 44 and sent for further testing.

Numerous other embodiments of the invention are possible, for example where the receiver is to be used purely for voiding the bladder in instances where a lavatory is not available, the receiver may be connected to a larger container.

CLAIMS:

1. A urine receiver characterised in that the receiver includes an open top of saddle shape which at least approximates the configuration of the inside of the thighs, labia, or other convenient zone.
2. The receiver according to claim 1 characterised in that the receiver includes a handle and a spout for easy disposing of the contents.
3. The receiver according to either of claims 1 or 2 characterised in that the receiver includes a closable outlet located in the base for discharge of the contents, or for collection of samples of urine.
4. The receiver according to claim 3 characterised in that the outlet closure includes a retractable plug.
5. The receiver according to either of claims 3 or 4, characterised in that a sample container is attachable to the outlet for collecting the urine sample.
6. The receiver according to claim 5, characterised in that the sample container and the outlet comprise a bayonet joint so that the sample container is easily connected and disconnected to the receiver.
7. The receiver according to claim 5, characterised in that the sample container and the outlet are connected by a threaded screw connection.
8. The receiver according to any of claims 5 to 7 characterised in that connection of the sample container to the outlet causes retraction of the plug into an open position, allowing the urine to drain into the sample container.
9. The receiver according to any of claims 5 to 8 characterised in that the sample container is a special purpose sterile container, sealed by a membrane that is pierceable on connection of the container to the receiver.
10. The receiver according to any of claims 5 to 8 characterised in that the sample container is a standard, non sterile bottle.

11. The receiver according to any of claims 5 to 10 characterised in that the sample container additionally includes a lid for sealing the container once the sample has been obtained.
12. The receiver according to any of claims 1 to 11 characterised in that the receiver includes a holder for litmus or other indicators.
13. The receiver according to claim 12 characterised in that the indicator holder comprises channels located along the interior wall of the receiver.
14. The receiver according to claim 12 characterised in that the indicator holder comprises a separate insert receivable inside the receiver.
15. The receiver according to claim 14 characterised in that the insert is shaped to alternatively or additionally support a filter and/or sponge conforming in shape to the inside of the receiver, for absorbing the initial stream of urine and prevent unwanted ingress of microorganisms or other dirt.
16. The receiver according to claim 15 characterised in that the sponge is constructed of cellulose or other absorbent material.
17. The receiver according to any of claims 14 to 16 characterised in that the insert is located just under the spout of the receiver.
18. The receiver according to any of claims 14 to 17 characterised in that the insert is supported by a ridge extending around the interior of the receiver.
19. The receiver according to any of claims 14 to 18 characterised in that the insert includes a solid base sloping towards an aperture through which the urine not absorbed by the sponge, may flow.
20. The receiver according to any of claims 14 to 19, characterised in that the insert includes a suitable spillage protector for the spout.
21. The receiver according to any of claims 1 to 20, characterised in that the receiver includes a removable support base, on which the receiver may be located when not in use.

- 22. The receiver according to any of claims 1 to 21, characterised in that the receiver includes a replaceable rim element adapted to fit the rim and to form a seal with the zone during use.
- 23. The receiver according to claim 22, characterised in that the rim element is flexible as well as compressible so that it can seal well with a minimum of pressure being applied.
- 24. The receiver according to any of claims 1 to 23, characterised in that the receiver includes a removable lid.