

【DESCRIPTION】

【Invention Title】

AIR POCKET-TYPE MASSAGE DEVICE

【Technical Field】

5 The present invention relates to an air pocket-type massage device capable of changing a position of a massage module using a position adjusting means according to a change in stature of a user when a part of the body, particularly, the calves, of the user are massaged.

【Background Art】

10 As a conventional massage device, Korean Patent Registration No. 10-1288410 (July 16, 2013, hereinafter, referred to as prior art) discloses “Auto heat massage chair for preventing of varicose veins and calf diet”.

 The prior art is configured to include an airbag that is sealed, contractible, and expandable and provided on one side of the auto heat massage chair, a sheet
15 heating element provided on one side surface portion of the airbag to be in surface-contact with the one side surface of the airbag, and heating air inside the sealed airbag by heating the whole of the one side surface in surface-contact with the airbag to expand the airbag; and a pressurizer provided on the other side surface portion of the sheet heating element not to be in contact with the airbag and pressurizing the
20 sheet heating element.

 According to the prior art, airbag-pressure massage and thermal treatment effects may be obtained only using a simple configuration without additional elements such as an air compressor and a heater by heating air inside the sealed airbag to expand the airbag and providing the thermal treatment effect using the

heated air.

Also, the prior art is configured to include a supporter for mounting calves or feet thereon and airbags at the supporters to perform a massage operation.

However, in the prior art, since the supporters always remain in a protruded state, a volume of the device is large and it is not easy to store and handle the device and an external aesthetic of the device is not good.

Also, since each user has a different stature, a length of calves may be different. Accordingly, since acupressure points of a user of tall stature and a user of short stature may be different, when positions of the airbags are fixed, like in the prior art, it is impossible to position the airbags at precise acupressure points, thereby reducing a massage effect as well as decreasing user satisfaction.

[Prior document]

[Patent document]

(Patent document 1) Korean Patent Registration No. 10-1288410 (July 16, 2013)

【Disclosure of Invention】

【Technical Problem】

It is an aspect of the present invention to flexibly correspond to a change in stature of a user by changing a position of a massage module using a position adjusting means according to the change in the stature of the user when parts of the body, particularly, the calves, of the user are massaged.

It is another aspect of the present invention to maximize massage effects by gathering the legs of the user not to deviate from each other during a massage operation by making contact points between air pockets and the calves of the user different using air pockets with different widths in the massage module.

It is still another aspect of the present invention to accommodate deformation between expansion and contraction of the air pockets using a flexible sheath which the air pockets are built into so that a volume of a massage device is reduced and storage or handling of the massage device is facilitated.

5 **【Technical Solution】**

According to one aspect of the present invention, an air pocket-type massage device includes a bed portion that supports a part of a body of a user, a massage module disposed on the bed portion and including a plurality of air pockets, and a position adjusting means provided at the bed portion to change a position of the
10 massage module.

A transfer module may include a transfer plate on which the air pockets of the massage module are mounted, a guide provided at the bed portion, and a transfer portion provided at the transfer plate to move along the guide.

The massage module may include a plurality of narrow first air pockets
15 disposed at an inner side and a plurality of wide second air pockets corresponding to the first air pockets and disposed at an outer side.

The massage module may further include a flexible sheath, which the air pockets are built into, configured to be stretchable according to an operation of the air pockets.

20 A wrinkled portion may be further provided on one side of the flexible sheath.

【Advantageous Effects】

According to embodiments of the present invention, an air pocket-type massage device can increase user convenience by removing an inconvenience caused by a difference in statures of users by flexibly corresponding to a change in stature of
25 a user by changing a position of a massage module using a position adjusting means

according to the change in stature of the user when parts of the body, particularly, the calves, of the user are massaged.

According to embodiments of the present invention, massage effects can be maximized by gathering the legs of the user not to deviate from each other during a
5 massage operation by making contact points between air pockets and the calves of the user different using air pockets with different widths in the massage module.

According to embodiments of the present invention, since it is possible to change the position of the massage module according to a difference in statures of users, an optimal arrangement structure can be configured using a minimal quantity
10 of air pockets without considering differences in statures of users such that not only the quantity of air pockets can be reduced but also costs thereof can be reduced.

According to embodiments of the present invention, deformation between expansion and contraction of the air pockets can be accommodated by using a flexible sheath which the air pockets are built into so that a volume of a massage
15 device is reduced and storage or handling of the massage device is facilitated.

According to embodiments of the present invention, since a massage operation is performed on a plane, a user may sit or lie in a comfortable position, and accordingly an efficient massage effect can be obtained.

【Brief Description of Drawings】

20 FIG. 1 is a perspective view of an air pocket-type massage device according to one embodiment of the present invention;

FIG. 2 is an enlarged perspective view of a massage module configured as an air pocket according to one embodiment of the present invention;

FIG. 3 is a cross-sectional view illustrating an operational state of the
25 massage module according to one embodiment of the present invention; and

FIG. 4 is a plane view of a position adjusting means according to one embodiment of the present invention.

【Best Mode for Invention】

An air pocket-type massage device according to one embodiment of the present invention will be described with reference to the attached drawings.

As shown in FIGS. 1 to 4, the air pocket-type massage device according to one embodiment of the present invention includes a bed portion 100, a massage module 200 including a plurality of air pockets 210 and 220, and a position adjusting means 300 that allows transfer of the massage module 200.

First, as shown in FIG. 1, the bed portion 100 is configured to allow a user to lie or sit thereon and supports the upper body or lower body of the user.

For this, the bed portion may be manufactured in various shapes, and for example, may be horizontally disposed in a bed or mattress shape or may include a back, a seat, and a leg supporter disposed below the seat, like a chair.

In the present invention, as shown in FIG. 1, the bed portion 100 configured to have a bed or mattress shape and include a first bed portion 110 that supports the upper body of the user with both sides to which supporting members 130 are connected and a second bed portion 120 that supports the lower body of the user will be described as an example.

In this case, for convenience of use or handling, the bed portion 100 may be configured in a shape in which the first bed portion 110 and the first bed portion 110 are folded or may be configured to allow the second bed portion 120 to slide from the first bed portion 110 and be unfolded or folded as shown in FIG. 1.

Here, when the bed portion is configured as a sliding type, a support 140 may be provided at the second bed portion 110 and an automatic sliding module may be

provided at the support 140 to be automatically driven or directly unfolded or folded by the user with hands as necessary.

Accordingly, when the bed portion according to one embodiment of the present invention is unfolded, since the upper body of the user is positioned at the first bed portion 110 and the lower body, particularly, the calves, of the user are
5 positioned at the second bed portion 120, a massage operation is performed on a horizontal plane.

Next, as shown in FIGS. 1 to 3, the massage module 200 according to one embodiment of the present invention includes the plurality of air pockets 210 and
10 performs the massage operation by contracting and expanding the air pockets 210.

First, the massage module 200 according to one embodiment of the present invention includes an air compressor (not shown) for injecting air into each of the air pockets 210, and the air compressor is connected to each of the air pockets 210 through an injection tube.

15 The air pockets according to one embodiment of the present invention massage the lower body, particularly, the calves of the user.

In this case, in a conventional air pocket-type massage device, when an air pocket is expanded, the air pocket and a part in contact with the calf of the user are positioned at the same level. Accordingly, the legs of the user may be spread during
20 the massage operation.

Accordingly, in the present invention, the legs of the user may be collected not to be spread during the massage operation as describe above by improving a size and an arrangement structure of the air pockets as follows.

For this, the air pockets of the massage module 200 include narrow first air
25 pockets 210 disposed at an inner side and wide second air pockets 220 disposed at an

outer side corresponding to the first air pockets 210.

First, widths of the first and second air pockets 210 and 220 refer to approximately lateral lengths when the air pockets are viewed from the front as shown in FIG. 3.

5 Accordingly, the width of the first air pocket 210 is formed to be smaller than that of the second air pocket 220.

When air is supplied to the air pockets and the air pockets are expanded as shown in FIG. 3, the first air pockets 210 disposed at the inner side come into contact with internal lower points of the calves of the user and the second air pockets 220
10 come into contact with external upper points of the calves of the user.

That is, since the first air pockets 210 apply forces to the calves upwards from the inner side at the same time that the second air pockets 220 apply forces to the calves downwards from the outer side, the legs of the user are naturally collected inward by the pressures by the second air pockets 220.

15 When the air pockets 210 and 220 are expanded and generate the same pressure, the first air pockets 210 support the lower points of the calves as levers, and in this state, the second air pockets 220 apply pressure toward the tops of the calves. Accordingly, the overall force is applied inwards.

As a result, when the air pockets according to one embodiment of the present
20 invention massages the legs of the user while the acupressure points of the first and second air pockets 210 and 220 are different, not only are the legs of the user prevented from being spread but massage effects may also be increased.

Also, in the massage module 200 according to one embodiment of the present invention, since the first air pockets 210 and the second air pockets 220 have
25 different widths, a difference in acupressure areas is generated. Accordingly, the

plurality of first air pockets 210 having a relatively narrow width are provided to have acupuncture areas corresponding to those of the second air pockets 220.

In addition, the air pockets of the massage module 200 according to one embodiment of the present invention are disposed above a transfer plate 310, which
5 will be described below, and a mounting portion 240 on which the calves are placed is disposed between the first and second air pockets 210 and 220.

In this case, the air pockets 210 and 220 are built into a flexible sheath 230 connected to one side of the transfer plate 310.

Wrinkled portions 231 are connected to an outer side of the flexible sheath
10 230. The wrinkled portions 231 accommodate operations of the air pockets 210 and 220 through stretchability when the air pockets 210 and 220 are contracted and expanded.

The wrinkled portions 231 may be preferably formed of a material having an elastic force such as rubber, spandex, and the like to have stretchability.

15 When the air pockets 210 and 220 are contracted as shown in FIG. 3(a), the wrinkled portions 231 of the flexible sheath 230 remains in a contracted state. When the air pockets 210 and 220 are contracted as shown in FIG. 3(b), the wrinkled portions 231 of the flexible sheath 230 are elongated. Here, the calves of the user positioned at the mounting portion 240 are pressurized and a process in which the
20 wrinkled portions 231 are contacted with a contraction of the air pockets 210 and 220 is repeated again to perform the massage operation.

In addition, as shown in FIG. 1, the second bed portion 120 according to one embodiment of the present invention includes a heating portion 250 and supplies heat to the legs of the user to additionally provide a heat treatment effect during massage
25 to further increase a massage effect.

Accordingly, the heating portion 250 includes heating wires that are arranged in the whole second bed portion 120 and may be divided into heating wires disposed above and below the mounting portion 240 between the air pockets 210 and 220 and a heating wire disposed on the mounting portion 240.

5 In this case, the heating wires of the heating portion 250 may be separately or simultaneously controlled. For example, the heating wires positioned above and below the mounting portion 240 may be simultaneously operated and only the heating wire disposed on the mounting portion 240 may be independently operated. Otherwise, all of the heating wires may be simultaneously operated and each of the
10 heating wires disposed on each part may be controlled to be independently operated as necessary.

Furthermore, the heating portion may include a lamp, a plate-shaped heating body, or the like, which are not shown in the drawing, disposed in addition to the above-described heating wires to perform the same function.

15 Meanwhile, as shown in FIG. 4, the position adjusting means 300 may change the position of the massage module 200 to provide convenience of the massage operation.

Generally, males and females who are users have a difference in statures, and there is a difference in statures of people of the same gender.

20 In this case, when a user lies on the bed portion, there is a large difference in positions of calves C depending on users. Here, when the position of the massage module 200 is fixed, the user has an inconvenience of having to position his or herself to place his or her calves C on the massage module 200 during the massage operation.

25 When a size of the bed portion is limited, a tall user's head may be deviate

from the bed portion or be positioned at a corner to double the inconvenience.

When the position of the massage module 200 is fixed and the air pockets are arranged based on tall users to allow both tall users and short users to use the massage module 200, in consideration of a difference in statures of the users, the
5 short users partially use the air pockets, and costs may be increased due to unnecessarily installed air pockets.

Conversely, in a case in which the number of air pockets is reduced based on the short users, when tall users use the massage module 200, the calves C of the users partially receive acupuncture in such a way that it is impossible to increase massage
10 effects, and satisfaction in the device may be decreased.

Accordingly, in the present invention, to solve the problems, the position adjusting means 300 capable of changing and adjusting the position of the massage module 200 is provided.

The position adjusting means 300 according to the present invention includes
15 the transfer plate 310 on which the air pockets 210 and 220 of the massage module 200 are mounted, a guide 320 provided at the bed portion, and transfer portion 330 provided at the transfer plate 310 to move along the guide 320.

First, the transfer plate 310 of the position adjusting means 300 is disposed above the bed portion, and in more detail, the second bed portion 120 and the first
20 and second air pockets 210 and 220 are mounted on a top surface thereof.

In addition, the guide 320 of the position adjusting means 300 is mounted on the top surface of the second bed portion 120 as one pair of rails, and the transfer portion 330 of the position adjusting means 300 is mounted below the transfer plate 310 and disposed above the guide 320.

25 In this case, the transfer portion 330 may not only be a driving body with

various shapes such as a roller, an LM guide, a geared motor, a ball screw, and the like but also a manual type through which a user may change the position of the message module 200 or an automatic type through which the position of the message module 200 may be changed by operating a remote control or a controller mounted
5 on the message device.

According to the position adjusting means 300 configured as described above, since the position of the message module 200 is changed according to a stature of a user to allow the message module 200 to move to a precise position of an acupuncture point which is different for each user, message effects as well as
10 convenience of the user may be increased, and also a customized message operation is possible.

Also, since an adequate number of air pockets may be disposed regardless to a difference in statures of users, the number of air pockets may be reduced, and accordingly costs thereof may be reduced.

15 With respect to this, as shown in FIGS. 2 and 3, organizing two narrow first air pockets 210 as a group for one wide second air pocket 220 is an appropriate arrangement structure for increasing message effects while reducing a quantity of air pockets. However, as necessary, the arrangement structure of air pockets may be changed or the quantity thereof may be increased or decreased.

20 Unlike an existing message device, the above-described air pocket-type message device may accommodate and support the lower body of a user without an additional structure to improve external aesthetics.

Also, since it is unnecessary to install an additional structure, manufacturing costs may be reduced, the message device may be configured to have a compact
25 structure, and convenience of storing or handling the message device may also be

increased.

To control the air pocket-type massage device according to one embodiment of the present invention, the massage module disposed on the first bed portion is controlled by a controller, and a sub controller is provided at an automatic sliding
5 module provided at the support of the second bed portion.

In this case, the sub controller controls and adjusts the automatic sliding module, the air compressor, the position adjusting means, the heating portion, and the like.

Although the air pocket-type massage device according to one embodiment
10 of the present invention has been mainly described above with particular shapes and directions with reference to the attached drawings, it should be understood that various modification and changes of the present invention may be made by one of ordinary skill in the art and that the modifications and changes are included in the scope of the present invention.

15 [Description of Reference Numerals]

C: Calves

100: Bed portion

110: First bed portion

120: Second bed portion

130: Supporting member

140: Support

20 200: Massage module

210: First air pockets

220: Second air pockets

230: Flexible sheath

231: Wrinkled portion

240: Mounting portion

250: Heating portion

300: Position adjusting means

25 310: Transfer plate

320: Guide

330: Transfer portion

【CLAIMS】

【Claim 1】

An air pocket-type massage device comprising:

a bed portion 100 that supports a part of a body of a user;

5 a massage module 200 disposed on the bed portion 100 and comprising a plurality of air pockets; and

 a position adjusting means 300 comprising a transfer plate on which the air pockets of the massage module 200 are mounted and provided at the bed portion 100 to change a position of the massage module 200,

10 wherein the massage module 200 comprises a pair of first air pockets 210 disposed obliquely outwardly at the center of the transfer plate and a pair of second air pockets 220 disposed obliquely inwardly at the periphery of the transfer plate so as to face the first air pocket 210,

 wherein, the transfer plate is provided with a heating part 250 supplying heat
15 to a planar mounting portion 240 formed between the first air pocket 210 and the second air pocket 220.

【Claim 2】

 The air pocket-type massage device of claim 1, wherein the position adjusting means 300 comprises a guide 320 provided at the bed portion, and a transfer portion
20 330 provided at the transfer plate 310 to move along the guide 320.

【Claim 3】

 The air pocket-type massage device of claim 1, wherein the first air pocket 210 is formed in a narrow-width type, and the second air pocket 220 is formed in a

wide-width type including a larger size than the first air pocket 210.

【Claim 4】

The air pocket-type massage device of claim 3, wherein the massage module 200 further comprises a flexible sheath 230, which the air pockets 210 and 220 are
5 built into, configured to be stretchable according to an operation of the air pockets 210 and 220.

【Claim 5】

The air pocket-type massage device of claim 4, further comprising a wrinkled portion 231 provided on one side of the flexible sheath 230.

10