

Description

The invention relates to a lens cap opening and closing mechanism comprising a lens support frame having an outer periphery and a central aperture, two barrier plates for opening and closing said central aperture, opening springs arranged to continuously bias said barrier plates in a position in which said central aperture is open and means for selectively moving a movable member to close said central aperture with said barrier plates.

Such a lens cap opening and closing mechanism is known from DE-A-32 20 265 as well as from US-A-4,457,604.

The invention is therefore based on the object of specifying a lens cap opening and closing mechanism of the type initially mentioned in which barrier plates can be driven in a simple manner.

According to the invention, this object is achieved by the features specified in claim 1.

DISCLOSURE OF INVENTION

A lens cap opening mechanism is provided which is adapted to be used with a lens support frame having an outer periphery, a central opening, and at least one barrier plate for selectively closing the opening. The mechanism comprises a movable member positioned in a peripheral opening of the frame, with the member being engaged with the at least one barrier plate. Means are provided for selectively moving the member inwardly of the frame to close the opening with the at least one barrier plate.

In an other aspect of the present invention a lens shutter type of auto focus camera is provided which has a zoom lens which is continuously movable between an extreme wide angle position and an extreme telephoto position. The lens is movable beyond the extreme wide angle position into a closed position in which the photographing lens is completely collapsed and in which lens barriers are provided to close an opening in a lens barrier block.

In a further aspect of the present invention, a lens shutter type of camera is provided having a zoom lens driven by a motor, means for driving the zoom lens continuously between an extreme wide angle position and an extreme telephoto position, as well as means for driving the zoom lens beyond the extreme wide angle position in order to close an opening in a lens barrier block.

The camera includes a zoom lens which can be moved by a driving motor into a collapsed lens position rearwardly of an extreme wide angle lens position. The lens is supported by an exterior frame having a central photographic opening and one or more barriers are provided for selectively closing the central opening. The camera comprises means for moving the barriers to close the opening when the lens is

moved into the collapsed lens position and for opening the barriers in all other lens positions.

Other objects, features and advantages of the present invention will hereinafter be described.

BRIEF DESCRIPTION OF DRAWINGS

The above and other objects, features, and advantages of the present invention will be described in greater detail with respect to the accompanying drawings, in which like reference numerals represent similar elements throughout the several views, and wherein:

Figs. 1 und 2 are sectional views of a first embodiment of an optical barrier mechanism, as viewed along a plane which is perpendicular to an optical axis, when in its open position with the central lens frame opening being open;

Fig. 2 is a sectional view similar to that of Fig. 1 but illustrating the optical barrier mechanism when it is in its closed position;

Fig. 3 is a sectional view of a second embodiment of an optical barrier mechanism formed in accordance with the present invention, the view being similar to that of the first embodiment of the optical barrier mechanism illustrated in Fig. 1;

Fig. 4 is a sectional view of the optical barrier mechanism of Fig. 3 in its closed position, similar to the view of the embodiment of Fig. 2;

Fig. 5 is a front elevational view of a camera formed in accordance with the present invention; Fig. 6 is a longitudinal sectional view of a lens barrel block and two photographing optical lenses formed in accordance with the present invention;

Fig. 7 is a developed view of the camming grooves in a "flattened" cam ring used to surround the front and rear lens element groups of the photographic optical system of the camera of Fig. 5;

Fig. 8 is an exploded perspective view of a lens barrel block used in the camera of Fig. 5.

BEST MODE FOR CARRYING OUT THE INVENTION

The present invention will now be described below in greater detail, with specific reference to the accompanying drawings which illustrate a variety of embodiments and features of the present invention.

The description will be generally provided in accordance with the following general sub headings:

A. Barrier, i.e., Lens Cap, Mechanism

B. The Overall Camera Construction for a Lens Shutter Type of Camera

A. Barrier, i.e., Lens Cap, Mechanism

The barrier lens cap mechanism is best illustrated in Figs. 6, 8 and 1-4.

Barrier mechanism 30 opens and closes a pair of barriers 31, (see Fig. 8) which are located forwardly of the front lens element group L1 of the photographic (zooming) lens system, and which are closed with the assistance of rotational force which is produced when cam ring 14 rotates within retracting or storing cam section 20b (see Fig. 7) in which the lens is collapsed.

Fig. 1 and 2 illustrate a first embodiment of the barrier mechanism. In this embodiment, barrier mechanism 30 opens and closes a photographic opening 22b at the opening of frame 22 via pivoted barrier elements 31. The barrier elements are pivoted, via pins 32, in a substantially symmetrical fashion with respect to the photographic opening 22b of the front lens group support frame 22.

Barriers 31 are disposed in a symmetrically opposite position with respect to each other and include respective barrier plate portions 31a which can be moved so as to project into the path of the photographing optical axis, as well as driving arm portions 31b which are positioned on the opposite sides of the barriers from the side on which barrier plate portions 31a are located. Driving arm portions 31b are generally attached to the inner front surface of barrier assembly 30 by pins 33. Driving arm portions 31b include pins 33 which are engaged by operational arms 34a of opening and closing springs 34, as shown in Figs. 1 and 2. In other words, pins 33 are adapted to slide within, and/or be moved by, respective fork-shaped end portions of the driving arms.

Opening and closing springs 34 are comprised, e.g., of molded synthetic resin and include the Y-shaped spring arm 34b and driving arm portions 34c. In addition to the fork-shaped operational arms 34a which engage pins 33. Each of the springs is pivoted to the barrier mechanism 30 by a respective pin 35. Spring arms 34b bear against the inner wall of the front lens group support frame 22 in order to continuously bias barrier plate portions 31a, via operational arm 34a, into positions in which barrier plate portions 31a are located away from the optical axis of the photographing optical assembly, and in which the front aperture 22b of the frame 22 remains in an open position.

Driving arms 34c come into engagement with opposed flange portions 36a of pin 36, which is movably fitted in a radial direction within front lens group support frame 22. As shown in Figs. 1 and 2, pin 36 is engaged by a free end of an operational lever 38 which is pivoted to front securing plate 13 via pin 37, through an operational aperture 39 of the front group lens support frame 22. Although a pivotable actuating lever is illustrated in the embodiments of Figs. 1-4, any structure which can move pin 36 inwardly in a radial

direction would be satisfactory.

Pin 36 occupies a substantially radially projecting position, under the influence of the spring force of spring 34, when no external force is applied to pin 36, as is illustrated in Fig. 1. In this position, the barrier plate portions 31a are located away from the photographing optical axis or path, and aperture 22b remains in an open position.

A restricting projection or abutment 40 is provided on the inner wall of cam ring 14, which is adapted to bear against the outer end of the operational lever (or other analogous structure) 38 when the cam ring rotates in its fixed axial position into a predetermined position in order to press pin 36 radially inwardly; this occurs when cam ring 14 (pin 17) rotates within the opening and closing section 20a of zooming cam groove 20.

With such an arrangement of the barrier mechanism, when projection 40 is not in engagement with operational lever 38, barrier plates 31a of barriers 31 open photographic opening 22b. Specifically, cam ring 14 causes rollers or pins 17 to engage any groove section other than opening and closing section 20a of zooming cam groove 20, with barriers 31 thus being opened.

To the contrary, when zooming motor is driven by a lock switch (not shown in the drawings) to rotate cam ring 14, so that roller 17 will move into and engage opening and closing section 20a of zooming cam groove 20 from lens collapsing or retracting groove section 20b, projection 40 will push opening and closing pin 36, via operational lever 38, in the radial direction, and barriers 31 will rotate through their engagement with spring drive arms 34c and operational arms 34a to move the barrier plate portions 31a into the optical path of the lens system. As a result, the photographic opening 22b will be closed so as to protect front lens element group L1. Namely, front lens groups support frame 22 closes barriers 31 after the frame has been collapsed from the rearmost position from which a picture can be taken.

When a picture is to be taken, zooming motor 5 is reversed so as to rotate cam ring 14, so that the zooming cam groove 20 will be rotated from a position in which opening and closing section 20a is engaged by roller(s) 17 towards a position in which lens collapsible section 20b is so engaged. This causes barriers 31 to open and the front lens group L1 is moved into a position in which a picture can be taken.

Figs. 3 and 4 illustrate a second embodiment of a mechanism used in a lens shutter type of camera in accordance with the present invention. As shown in Figs. 3 and 4, this barrier mechanism 30 is basically identical to the embodiment illustrated in Figs. 1 and 2. Specifically, barrier mechanism 30 in Figs. 3 and 4 also include a pair of barriers 31, 31 which are positioned in a substantially symmetrical fashion with respect to the photographic opening 22b of front lens

group support frame 22. Barriers 31, 31 are pivoted to frame 22 via pins 32 in order to open and close photographic opening 22b. However, details of construction of the barrier mechanism in this embodiment are different from those in the first embodiment discussed above.

Barriers 31, 31 which are illustrated in Figs. 3 and 4 are symmetrically disposed with respect to each other and include barrier plate portions 31a which can be projected onto the photography optical axis, and driving arms 31b which lie or are disposed on opposite sides of the barrier plate portions 31a; and the barriers are pivotably attached to the frame by pins 32.

Driving arms 31b include operational pins 133 which are engaged to, and which are adapted to abut or contact, a single wire spring 134 having elastic leg portions 134a. A free end of each of the elastic leg portions 134a is adapted to contact a respective pin 133 in order that barrier plate portions 31a will be continuously biased into an open position in which the photographic aperture 22b is opened and the barriers located away from the optical axis and the aperture. Thus, when no external force is applied to barriers, they constantly maintain the photographing aperture in an open condition.

Wire spring 134 is made from metal and has a central, U-shaped portion 134b which bears against a support pin 135 provided on front lens group support frame 22. Wire spring 134 has a constant spring force which force will not vary in accordance with changes in temperature, humidity or other environmental parameters. Accordingly, it is therefore possible to bias barriers 31 in a direction in which a photographing aperture is maintained in an open position by a substantially constant spring force.

Operational pins 133 are engaged by respective driving free ends 136a of a pair of right and left driving arms 136, which are spaced from each other and which are adapted to open barriers 31, by overcoming the biasing force exerted by wire spring 134. The free ends 136a of each of the driving arms 136 bears against a respective inner side of a respective operational pin 133, which is located away from the outer side of each pin against which one elastic leg portion 134a bears. Driving arms 136 are pivoted to lens support frame 22 via pins 137. Driving arms include operational arm portions 136b located on opposite sides of the driving arms from free ends 136a, with a pin 137 provided between them to pivot the arm to frame 22, such that operational arm portions 136b will engage flange portions 138a of pin 138, which is radially movably fitted within an opening 39 in frame 22. Pin 138 includes a head (unreferenced) which is adapted to bear against the free end of operational lever 141; the lever is pivoted to front securing plate 13 by pin 140, and the head can extend, when depressed, through an opening 39 of frame 22. The opening and closing pin 138 is normally maintained in a position in

which it projects outwardly from the inner periphery of frame 22, and is radially movable by lever 141 into a position in which the head of pin 138 is forced inwardly through opening 39, overcoming the influence of wire spring 134. Thus when an external force is applied to pin 138, it moves radially inwardly against the force of spring 134, as seen in Fig. 4.

As in the first embodiment, the cam ring 14 can be provided, along its inner wall, with a narrowing projection 40 attached to its interior peripheral surface which is adapted to push the operational lever 141 inwardly so that it will engage operational arm portions 136b (via pin flanges 138a) when cam ring 14 rotates so that roller 17 is positioned within opening and closing section 20a of zooming cam groove 20. Other suitable actuating structure could also be used.

With such an arrangement of the barrier mechanism, barriers 31 serve to open the photographing aperture when the restriction projection 40 does not engage operational lever 141. Specifically, barriers 31 open when roller 17 is located within any of the sections of the zooming cam groove other than opening and closing groove section 20a. To the contrary, when roller 17 is moved to engage the opening and closing section 20a, after it has been positioned within lens collapsible section 20b of zooming cam groove 20 (via rotation of actuating cam ring 14 effected by zooming motor), projection 40 will push the opening and closing pin 138 in a radially inward direction, via operational lever 141, in order to rotate barriers 31, via driving arms 136 and operational pins 133, so that barrier plate portions 31a will be brought into the optical path of the lens system. In this condition, the photographic opening will be closed so as to protect the front lens element group L1. Namely, after front lens group support frame 22 is collapsed from the most extreme rearward position i.e., the extreme wide angle position, in which a picture can be taken, the photographic aperture will then be closed by barriers 31.

When a picture is taken, zooming motor will be reversed to rotate cam ring 14 from a position in which opening and closing section 20a is engaged by roller 17 to a position in which lens collapsible section 20b is so engaged, in order to open barriers 31, so that the front lens element group L1 will move into a position in which a picture can be taken.

B. Overall Camera Construction for a Lens Shutter Type of Camera

The overall construction of a lens shutter type of camera formed in accordance with the present invention is well illustrated in Figs. 5-8. A lens shutter type of camera formed in accordance with the present invention essentially comprises a zoom lens barrel block 1, a finder and strobe block 2 (hereinafter referred to as a finder block), and a zooming motor which is used for the zooming operation of the photograph-

ing optical system. All of these elements are secured to a base 6 which forms an immovable portion of the camera body.

Base 6 includes, as is best illustrated in Fig. 6, a lens barrel supporting plate portion 6a which lies in a plane which is perpendicular to the optical axis of the lens. Support plate 6 extends beyond the side edge of plate 6a in order to support finder assembly 8 and strobe assembly 9. Lens barrel block 1 is supported on lens barrel support plate portion 6a, which has a central opening (unreferenced) for receiving the lens barrel block.

Lens barrel block 1 is adapted to be actuated by zooming motor, and the construction of this block will be described hereinbelow with more specific reference to Figs. 6-8. A rear securing plate 11 is mounted to lens barrel support plate portion 6a of base 6 by fastening screws 10, as is best illustrated in Fig. 6. Rear securing plate 11 includes four guide rods 12 which are attached to and through bores in the rear portion of the guide plate and which are located about the optical axis of the photographing optical system and parallel to this axis. A front securing plate 13 is secured to the front ends of guide rods 12; these guide rods and plates are the main securing elements for lens barrel block 1.

A rotatable cam ring 14 is positioned between front and rear securing plates 13 and 11, respectively; a sector gear 15 is provided about a substantial portion (but preferably not the entire 360°) of the outer periphery of cam ring 14; this gear can be attached to the cam ring by conventional means, e.g., via set screws 15a, as seen in Fig. 6; Gear 15 can be a sector gear which will cover a predetermined range of rotational movement of cam ring 14; The cam ring is itself provided with zooming cam grooves 20 and 21 (see Fig. 7) which are used to engage the front and rear lens element groups, respectively.

Fig. 7 is a schematic or developed view of zooming cam grooves 20 and 21 of ring 14. Cam groove 21, used to engage the rear lens element group, includes an extreme wide angle fixing section 21a, a variable magnification section 21b inclined upwardly (as seen in Fig. 7) from section 21a, and an extreme telephoto fixing section 21c. Cam groove 20, used for the front lens element group, includes a section 20a for opening and closing barrier block 30, a lens retraction section 20b, an extreme wide angle fixing section 20c, a variable magnification section 20d, an extreme telephoto fixing section 20e, a macro transfer section 20f, and an extreme macro fixing section 20g.

When the term macro is used throughout this specification, it refers to a "close-up" photographing configuration for the camera. Previously, the term "macro" has occasionally been used to mean "bigger than life"; however, the term macro has been used throughout this specification as an equivalent term for close-up, and whenever it is used it should be taken

to have such a meaning unless indicated to the contrary herein.

The total angle ϕ_1 of the rotational displacement of cam ring opening and closing section 20a, lens retraction section 20b, and extreme wide angle fixing section 20c of zooming cam groove 20 is identical to angle ϕ_1 of the extreme wide angle fixing section 21a of zooming cam groove 21. Angle ϕ_2 of the variable magnification, i.e., variable power, section 20d of zooming cam groove 20 is identical to angle ϕ_2 of the variable magnification, i.e., variable power, section 21b of zooming cam groove 21. Further, the total angle ϕ_3 of the extreme telephoto fixing section 20e, the macro position fixing section 20g, and the macro transfer section 20f, is equal to the angle ϕ_3 of the extreme telephoto fixing section 21c. In the illustrated embodiment, the zooming range is between approximately 35mm and approximately 70mm.

A roller 17, as illustrated in both Figs. 6 and 8, is positioned within zooming cam groove 20; this roller is attached to a front lens group frame 16. A roller 19 of rear lens group frame 18 is positioned within zooming cam groove 21, again as illustrated in Figs. 6 and 8. Front lens group frame 16 and rear lens group frame 18 are movably guided by guide rods 12, and a decorative frame 22 and shutter block 23 are secured to the front lens group frame 16 via set screws 22a, as best seen in the exploded view of Fig. 8, as well as in the cross-sectional view of Fig. 6.

The front lens frame 24 which supports front lens element group L1 is engaged by shutter block 23 via helicoid 25, which is shown in Fig. 8. Front lens frame 24 includes an arm 24a which engages lens feeding lever 23a of shutter block 23 (see Fig. 6), so that when lens feeding lever 23a rotates in a circumferential direction in order to rotate front lens frame 24, the front lens frame will move along the direction of the optical axis of the photographing optical system under the guidance of helicoid 25. Rear lens element-group L2 is directly attached to rear lens group frame 18, as seen in Fig. 6. One desired configuration of lens groups L1 and L2, as illustrated in Fig. 6, are disclosed in commonly assigned U.S. Patent Application Serial No. 935,982, filed on November 28, 1986, the disclosure of which is expressly incorporated by reference herein.

The structure of shutter block 23 is known per se. This shutter block rotates lens feeding lever 23a over a predetermined angular displacement in accordance with a detection signal which is received by the shutter block from the distance measuring device, as described hereinafter, via a pulse motor which is incorporated within the camera body and which is adapted to open shutter sector 23b, which has been closed for a predetermined time, and to thereafter return lens feeding lever 23a into its original position after the shutter has again closed. This type of shutter block is disclosed, e.g., in unexamined Japanese Published



Patent Application (KOKAI) No. 60-235,126, dated November 21, 1985, the disclosure of which is expressly incorporated by reference herein. The present camera utilizes such a shutter block in the fundamental way disclosed therein.

Finder block 2 includes finder assembly 8 and strobe assembly 9. The finder device and the strobe device are adapted to vary, respectively, the field of finder view and the illumination angle, i.e., the intensity of the strobe, in accordance with variance in the focal length of the lens barrel block 1. Zooming motor is used as a power source both for finder control and strobe control; only a single motor need therefore be used.

Claims

1. A lens cap opening and closing mechanism (30) comprising:
 - a lens support frame (22) having an outer periphery and a central aperture (22b);
 - two barrier plates (31) for opening and closing said central aperture (22b);
 - opening springs (34b; 134) arranged to continuously bias said barrier plates (31) in a position in which said central aperture (22b) is open;
 - means (38; 141) for selectively moving a movable member (36; 138) to close said central aperture (22b) with said barrier plates (31), characterised by
 - two driving arms (34a, 34c; 136) each one being engaged with one of said barrier plates (31) at one end of said arms (34a; 136a) and being engaged with said movable member (36; 138) at another end of said arms (34c; 136b), and wherein said movable member (36; 138) moves inwardly of said frame (22) within a peripheral opening (39) of said frame (22) for closing said central aperture (22b).
2. A mechanism in accordance with claim 1, wherein said frame (22) is cylindrical and said member (36, 138) is radially movable within said peripheral frame opening (39).
3. A mechanism in accordance with one of claims 1 or 2, further comprising a pivotable lever (38, 141) located on the exterior of said frame, said pivotable lever having a free end which is normally located adjacent to one end of said movable member (36, 138).
4. A mechanism in accordance with claim 3, further comprising a projection (40) along the interior of a rotatable lens barrel (1) comprising means (40) for pivoting said lever (38, 141) to force said movable member (36, 138) radially inwardly of said frame (22) and for thereby closing said central aperture (22b) with each said barrier plate (31).
5. A mechanism in accordance with claim 4, wherein said lens barrel (1) is manually rotatable.
6. A mechanism in accordance with claim 4, wherein said lens barrel (1) is rotatable by a motor (5).
7. A mechanism in accordance with one of claims 4 to 6, wherein said projection (40) is on the interior of a rotatable cam ring (14).
8. A mechanism in accordance with one of claims 1 to 7, wherein said lens support frame (22) includes a front portion, and wherein said barrier plates (31) are positioned inside of said frame (22) directly behind said front frame central aperture (22b), with an annular securement plate (13) positioned behind said barrier plates (31).
9. A mechanism in accordance with claim 8, wherein said driving arms (34) are resilient Y-shaped arms (34) which have forked ends (34a) which receive pins (33) attached to said barrier plates (31).
10. A mechanism in accordance with claim 8, wherein said driving arms (136) have free ends (136a) abutting pins (133) on respective barrier plates (31), wherein when said movable member (138) is moved radially inwardly of said frame (22) said movable member (138) comprises means (138a) for overcoming the biasing force applied to said barrier plates (31) by a single spring wire (134).
11. A camera having a mechanism as claimed in any of the preceding claims, further having a photographing zoom lens (L1) movable into a completely collapsed lens position rearwardly of an extreme wide angle lens position, said lens (L1) being supported by said lens support frame (22).
12. A camera in accordance with claim 11, further comprising a driving motor (5) for driving said zoom lens (L1) into said collapsed lens position.
13. A camera in accordance with claim 11 or 12, further comprising means (136, 138, 138a, 140) for closing said barrier plates (31) by moving said movable member (138) on said frame (22) radially inwardly after said lens (L1) has moved into said completely collapsed position.
14. A camera in accordance with claim 11, wherein said aperture closing means (30) comprises means for closing said aperture whenever said zoom lens is moved into said collapsed lens position.

Patent Application (KOKAI) No. 60-235,126, dated November 21, 1985, the disclosure of which is expressly incorporated by reference herein. The present camera utilizes such a shutter block in the fundamental way disclosed therein.

Finder block 2 includes finder assembly 8 and strobe assembly 9. The finder device and the strobe device are adapted to vary, respectively, the field of finder view and the illumination angle, i.e., the intensity of the strobe, in accordance with variance in the focal length of the lens barrel block 1. Zooming motor is used as a power source both for finder control and strobe control; only a single motor need therefore be used.

Claims

1. A lens cap opening and closing mechanism (30) comprising:
 - a lens support frame (22) having an outer periphery and a central aperture (22b);
 - two barrier plates (31) for opening and closing said central aperture (22b);
 - opening springs (34b; 134) arranged to continuously bias said barrier plates (31) in a position in which said central aperture (22b) is open;
 - means (38; 141) for selectively moving a movable member (36; 138) to close said central aperture (22b) with said barrier plates (31), characterised by
 - two driving arms (34a, 34c; 136) each one being engaged with one of said barrier plates (31) at one end of said arms (34a; 136a) and being engaged with said movable member (36; 138) at another end of said arms (34c; 136b), and wherein said movable member (36; 138) moves inwardly of said frame (22) within a peripheral opening (39) of said frame (22) for closing said central aperture (22b).
2. A mechanism in accordance with claim 1, wherein said frame (22) is cylindrical and said member (36, 138) is radially movable within said peripheral frame opening (39).
3. A mechanism in accordance with one of claims 1 or 2, further comprising a pivotable lever (38, 141) located on the exterior of said frame, said pivotable lever having a free end which is normally located adjacent to one end of said movable member (36, 138).
4. A mechanism in accordance with claim 3, further comprising a projection (40) along the interior of a rotatable lens barrel (1) comprising means (40) for pivoting said lever (38, 141) to force said movable member (36, 138) radially inwardly of said

frame (22) and for thereby closing said central aperture (22b) with each said barrier plate (31).

5. A mechanism in accordance with claim 4, wherein said lens barrel (1) is manually rotatable.
6. A mechanism in accordance with claim 4, wherein said lens barrel (1) is rotatable by a motor (5).
7. A mechanism in accordance with one of claims 4 to 6, wherein said projection (40) is on the interior of a rotatable cam ring (14).
8. A mechanism in accordance with one of claims 1 to 7, wherein said lens support frame (22) includes a front portion, and wherein said barrier plates (31) are positioned inside of said frame (22) directly behind said front frame central aperture (22b), with an annular securement plate (13) positioned behind said barrier plates (31).
9. A mechanism in accordance with claim 8, wherein said driving arms (34) are resilient Y-shaped arms (34) which have forked ends (34a) which receive pins (33) attached to said barrier plates (31).
10. A mechanism in accordance with claim 8, wherein said driving arms (136) have free ends (136a) abutting pins (133) on respective barrier plates (31), wherein when said movable member (138) is moved radially inwardly of said frame (22) said movable member (138) comprises means (138a) for overcoming the biasing force applied to said barrier plates (31) by a single spring wire (134).
11. A camera having a mechanism as claimed in any of the preceding claims, further having a photographing zoom lens (L1) movable into a completely collapsed lens position rearwardly of an extreme wide angle lens position, said lens (L1) being supported by said lens support frame (22).
12. A camera in accordance with claim 11, further comprising a driving motor (5) for driving said zoom lens (L1) into said collapsed lens position.
13. A camera in accordance with claim 11 or 12, further comprising means (136, 138, 138a, 140) for closing said barrier plates (31) by moving said movable member (138) on said frame (22) radially inwardly after said lens (L1) has moved into said completely collapsed position.
14. A camera in accordance with claim 11, wherein said aperture closing means (30) comprises means for closing said aperture whenever said zoom lens is moved into said collapsed lens position.



ition from any non-collapsed lens position.

15. Camera having a mechanism as claimed in any of the claims 1 to 10, characterized in that

- said lens support frame (22) is linearly movably supported so that the frame (22) goes into a completely collapsed position which is further rearward from an extreme rear wide angle lens position;
- a motor-driven (5) lens driving ring (14) is disposed around the lens supporting frame (22) between said extreme rear wide angle lens position and said completely collapsed position by a rotation of a collapsing range (20b) of said ring (14);
- the two barrier plates (31) are closed in association with a rotation of an opening/closing range (20a) of said ring (14) whereby said opening/closing range (20a) is continuously formed from said collapsing range (20b).

Patentansprüche

1. Objektivdeckelöffnungs- und Schließmechanismus (30) mit:
einem einen äußeren Umfang und eine zentrale Öffnung (22b) habenden Linsenhalterahmen (22);
zwei Abdeckplatten (31) zum Öffnen und Schließen der zentralen Öffnung (22b);
Öffnungsfedern (34b; 134), die angeordnet sind, um die besagten Abdeckplatten (31) kontinuierlich in einer Stellung vorzuspannen, in der die zentrale Öffnung (22b) geöffnet ist;
einer Vorrichtung (38; 141) zum wahlweisen Bewegen eines beweglichen Teiles (36; 138), um die besagte zentrale Öffnung (22b) mit den besagten Abdeckplatten (31) zu schließen, gekennzeichnet durch zwei Antriebshebelarme (34a, 34c; 136), von denen jeder an einem Hebelarmende (34a; 136a) jeweils mit einer der Abdeckplatten (31) in Eingriff steht und am anderen Hebelarmende (35c; 136b) mit dem besagten beweglichen Teil (36; 138) in Eingriff steht, wobei das bewegliche Teil (36; 138) zum Schließen der besagten zentralen Öffnung (22b) durch eine periphere Öffnung (39) des Rahmens (22) hindurch in den Rahmen (22) hinein bewegt wird.
2. Mechanismus nach Anspruch 1, wobei der Rahmen (22) zylindrisch ist und das bewegliche Teil (36, 138) radial durch die besagte periphere Rahmenöffnung (39) hindurch bewegbar ist.
3. Mechanismus nach einem der Ansprüche 1 oder 2, außerdem mit einem schwenkbaren, außer-

halb des Rahmens befindlichen Hebel (38, 141), wobei der schwenkbare Hebel ein freies Ende hat, das normalerweise an ein Ende des beweglichen Teils (36, 138) angrenzend angeordnet ist.

4. Mechanismus nach Anspruch 3, außerdem mit einem Vorsprung (40) entlang dem Innern eines drehbaren Objektivtubus (1), mit Mitteln (40) zum Schwenken des besagten Hebels (38, 41), um das besagte bewegliche Teil (36, 138) radial ins Innere des besagten Rahmens (22) zu drücken und um dadurch die zentrale Öffnung (22b) mit den besagten Abdeckplatten (31) zu schließen.
5. Mechanismus nach Anspruch 4, wobei der besagte Objektivtubus (1) manuell drehbar ist.
6. Mechanismus nach Anspruch 4, wobei der besagte Objektivtubus (1) durch einen Motor (5) drehbar ist.
7. Mechanismus nach einem der Ansprüche 4 bis 6, wobei der besagte Vorsprung (40) sich im Innenbereich eines drehbaren Nockenrings (14) befindet.
8. Mechanismus nach einem der Ansprüche 1 bis 7, wobei der besagte Linsenhalterahmen (22) einen Frontbereich einschließt und wobei die besagten Abdeckplatten (31) innerhalb des besagten Rahmens (22) unmittelbar hinter der zentralen Frontöffnung (22b) des Rahmens positioniert sind mit einer ringförmigen Sicherheitsplatte (13), die hinter den besagten Abdeckplatten (31) angeordnet ist.
9. Mechanismus nach Anspruch 8, wobei die besagten Antriebshebelarme (34) federnde Y-förmige Hebelarme (34) sind, die gegabelte, an den besagten Abdeckplatten (31) angebrachte Stifte (33) aufnehmende Enden (34a) haben.
10. Mechanismus nach Anspruch 8, wobei die besagten Antriebshebelarme (136) frei Enden (136a) haben, die an Stiften (133) an den jeweiligen Abdeckplatten (31) anliegen, wobei das bewegliche Teil (138) Mittel (138a) umfaßt, um bei einer radial in den besagten Rahmen (22) gerichteten Bewegung eine Vorspannkraft zu überwinden, die von einer einzelnen Drahtfeder (134) auf die besagten Abdeckplatten (31) aufgebracht wird.
11. Kamera mit einem Mechanismus, wie er in einem der vorhergehenden Ansprüche beansprucht ist, außerdem mit einem Varioaufnahmeobjektiv (L1), das in eine vollständig zurückgezogene Objektivstellung hinter die Extremweitwinkelstel-



lung bewegbar ist, wobei dieses Objektiv (L1) von dem besagten Linsenhalterahmen (22) gehalten wird.

12. Kamera nach Anspruch 11, außerdem mit einem Antriebsmotor (5) zum Antreiben des Varioobjektivs (L1) in die besagte eingefahrene Objektivstellung.

13. Kamera nach einem der Ansprüche 11 oder 12, außerdem mit Mitteln (136, 138, 138a, 140) zum Schließen der Abdeckplatten (31) durch Bewegen des besagten beweglichen Teiles (138) an dem besagten Rahmen (22) radial nach innen, nachdem das besagte Objektiv (L1) in die besagte vollständig zurückgezogene Stellung bewegt worden ist.

14. Kamera nach Anspruch 11, wobei der besagte Öffnungs/Schließmechanismus (30) Mittel hat, um die besagte Öffnung immer zu schließen, wenn das Objektiv aus irgendeiner nicht zurückgezogenen Objektivstellung in die zurückgezogene Objektivstellung bewegt worden ist.

15. Kamera mit einem Mechanismus wie in irgendeinem der Ansprüche 1 bis 10 beansprucht, dadurch gekennzeichnet, daß

- besagter Linsenhalterahmen (22) linear beweglich gehalten wird, so daß der Rahmen (22) in eine vollständig eingefahrene Stellung geht, die sich weiter rückwärts von einer extrem rückwärtigen Weitwinkelstellung befindet;
- ein motorbetriebener (5) Linsenantriebsring (14) um den Linsenhalterahmen (22) herum angeordnet ist zwischen der extrem rückwärtigen Weitwinkelobjektivstellung und der besagten vollständig eingefahrenen Stellung durch eine Rotation eines Einfahrbereichs (20b) des besagten Ringes (14);
- die zwei Abdeckplatten (31) in Übereinstimmung mit einer Rotation eines Öffnungs/Schließbereiches (20a) des besagten Ringes (14) geschlossen werden, wobei der besagte Öffnungs/Schließbereich (20a) unterbrechungsfrei an den besagten Zurückziehbereich (20b) anschließend ausgebildet ist.

Revendications

1. Mécanisme d'ouverture et de fermeture de bouchon d'objectif (30) comprenant :
une monture support de lentille (22) ayant une périphérie extérieure et une ouverture cen-

trale (22b) ;

deux lames de protection (31) pour ouvrir et fermer ladite ouverture centrale (22b) ;

des ressorts d'ouverture (34b ; 134) agencés pour rappeler de manière continue lesdites lames de protection (31) dans une position dans laquelle ladite ouverture centrale (22b) est ouverte ;

un moyen (38 ; 141) pour déplacer de manière sélective un élément mobile (36 ; 138) pour fermer ladite ouverture centrale (22b) à l'aide desdites lames de protection (31), caractérisé par :

deux bras d'entraînement (34a, 34c ; 136) chacun étant en prise avec l'une desdites lames de protection (31) à une extrémité desdits bras (34a ; 136a), et étant en prise avec ledit élément mobile (36 ; 138) à l'autre extrémité desdits bras (34c ; 136b), et en ce que ledit élément mobile (36 ; 138) se déplace vers l'intérieur de ladite monture (22) dans une ouverture périphérique (39) de ladite monture (22) pour fermer ladite ouverture centrale (22b).

2. Mécanisme selon la revendication 1, dans lequel ladite monture (22) est cylindrique et ledit élément (36, 138) est mobile radialement à l'intérieur de ladite ouverture périphérique de monture (39).

3. Mécanisme selon l'une des revendications 1 ou 2, comprenant en outre un levier pivotant (38, 141) situé sur l'extérieur de ladite monture, ledit levier pivotant ayant une extrémité libre qui est normalement placée adjacente à une extrémité dudit élément mobile (36, 138).

4. Mécanisme selon la revendication 3, comprenant en outre une saillie (40) le long de l'intérieur d'un barillet d'objectif mobile en rotation (1) comprenant un moyen (40) pour faire pivoter ledit levier (38, 141) pour forcer ledit élément mobile (36, 138) radialement vers l'intérieur de ladite monture (22) et pour fermer ainsi ladite ouverture centrale (22b) à l'aide de chacune desdites lames de protection (31).

5. Mécanisme selon la revendication 4, dans lequel ledit barillet d'objectif (1) est mobile en rotation manuellement.

6. Mécanisme selon la revendication 4, dans lequel ledit barillet d'objectif (1) est mobile en rotation à l'aide d'un moteur (5).

7. Mécanisme selon l'une des revendications 4 à 6, dans lequel ladite saillie (40) se trouve sur l'intérieur d'une bague à cames mobile en rotation (14).



8. Mécanisme selon l'une des revendications 1 à 7, dans lequel ladite monture support de lentille (22) comprend une partie avant, et dans lequel lesdites lames de protection (31) sont situées à l'intérieur de ladite monture (22) directement derrière ladite ouverture centrale de monture (22b), avec une plaque de fixation annulaire (13) placée derrière lesdites lames de protection (31). 5
9. Mécanisme selon la revendication 8, dans lequel lesdits bras d'entraînement (34) sont des bras élastiques en forme de Y (34) qui ont des extrémités en forme de fourche (34a) qui reçoivent des ergots (33) fixés auxdites lames de protection (31). 10
10. Mécanisme selon la revendication 8, dans lequel lesdits bras d'entraînement (136) ont des extrémités libres (136a) en butée contre des ergots (133) sur les lames de protection (31) respectives, dans lequel ledit élément mobile (138) se déplace radialement vers l'intérieur de ladite monture (22), et dans lequel ledit élément mobile (138) comprend un moyen (138a) pour surmonter la force de rappel appliquée auxdites lames de protection (31) par un seul fil formant ressort (134). 15
11. Appareil photo comportant un mécanisme selon l'une quelconque des revendications précédentes, comprenant en outre une lentille de photographie zoom (L1) mobile entre une position de lentille complètement rétractée vers l'arrière et une position de lentille d'extrémité grand angle, ladite lentille (L1) étant supportée par ladite monture support de lentille (22). 20
12. Appareil photo selon la revendication 11, comprenant en outre un moteur d'entraînement (5) pour amener ladite lentille de zoom (L1) dans ladite position de lentille rétractée. 25
13. Appareil photo selon la revendication 11 ou 12, comprenant en outre un moyen (136, 138, 138a, 140) pour fermer lesdites lames de protection (31) en déplaçant ledit élément mobile (138) sur ladite monture (22) radialement vers l'intérieur après que ladite lentille (L1) a été amenée dans ladite position totalement rétractée. 30
14. Appareil photo selon la revendication 11, dans lequel ledit moyen de fermeture d'ouverture (30) comprend un moyen pour fermer ladite ouverture chaque fois que ladite lentille de zoom est amenée dans ladite position de lentille rétractée à partir de n'importe quelle position de lentille non rétractée. 35
15. Appareil photo comportant un mécanisme selon 40

l'une quelconque des revendications 1 à 10, caractérisé:

en ce que ladite monture support de lentille (22) est supportée de manière à être mobile de façon rectiligne de sorte que la monture (22) va dans une position totalement rétractée qui est davantage vers l'arrière qu'une position d'extrémité grand angle arrière ;

en ce qu'une bague d'entraînement de lentille (14) entraînée par moteur (5) est disposée autour de la monture support de lentille (22) entre ladite position d'extrémité grand angle arrière et ladite position complètement rétractée par rotation d'une plage de rétraction (20b) de ladite bague (14) ;

en ce que les deux lames de protection (31) sont fermées en association avec la rotation d'une plage d'ouverture/fermeture (20a) de ladite bague (14), ce par quoi ladite plage d'ouverture/fermeture (20a) est formée de manière continue à partir de ladite plage de rétraction (20b). 45