FLEX SUPPORT AND SEAL APPARATUS FOR A DISC DRIVE

Field of the Invention

The present invention relates generally to the field of disc drive data storage devices, and more particularly but not by way of limitation, to a flex support and seal apparatus for interconnecting read/write head wires of a disc drive to a printed circuit board.

Background of the Invention

Modern disc drives are commonly used in computer environments ranging from super computers through notebook computers, to store large amounts of data in a form that can be made readily available to a user. A typical disc drive generally comprises a head/disc assembly (HDA) which houses mechanical elements of the disc drive, and a printed circuit board (PCB) which incorporates electronic portions of the disc drive. The PCB is affixed to an exterior surface of the HDA.

The HDA houses one or more magnetic discs that are rotated at a constant speed by a spindle motor. Each disc surface has a data recording surface divided into a series of generally concentric data tracks radially spaced across a band having an inner diameter and an outer diameter.

The data stored within the data tracks on the disc are in the form of magnetic flux transitions. The flux transitions are induced by an array of read/write heads. Typically, each data track is divided into a number of data sectors that store fixed sized data blocks.

Each read/write head includes an interactive element such as a magnetic transducer that senses the magnetic transitions on a selected data track to read the data stored on the track. To write data to the disc surface, the read/write head generates an electrically induced, short duration magnetic field that induces

magnetic transitions on the selected data track.

In addition to the read/write heads, the actuator assembly generally includes head wires, which conduct electrical signals from the read/write heads to a flex circuit that, in turn, conducts the electrical signals to a read/write channel located on the disc drive PCB. Normally, the electrical signal paths are routed through one or more connectors en route to the read/write channel. However, in so doing, contacts of the connectors typically induce added inductance and capacitance into the circuit, thereby causing a change in inductance per unit length along the signal path. This change in inductance per unit length along the signal path frequently results in a parasitic electrical degradation of the signal. Several approaches have been used to accommodate the data signal interconnect needs of a disc drive, but in general, these approaches have been silent regarding resolution of parasitic electrical signal degradation problems caused by changes in inductance per unit length along the signal path.

In the process of interconnecting the flex circuit and the PCB, one previous approach makes use of an apparatus with a three connector combination configuration. The first connector is a flex circuit connector (the connector body housing female connector pins) which is soldered directly to the flex circuit. The second connector is a pass-through connector (the connector body housing male pins, the male pins having a top portion protruding from a top side of the connector body and a bottom portion protruding from a bottom side of the connector body) which mounts to a basedeck of the HDA, with the bottom portions of the male pins extending from a slot in the basedeck. The third connector is a printed circuit board connector (a connector body housing female connector pins) which is soldered directly to the PCB. An advantage of this configuration is that the flex circuit remains internal to the HDA.

Under this three-connector combination approach the flex circuit connector is mounted to a flex circuit mounting bracket. Then the flex circuit connector connects to the pass-through connector internal to the HDA. Contact between the flex circuit connector and the pass-through connector is maintained

by physically securing the flex circuit mounting bracket and the pass-through connector to the basedeck. External to the basedeck, the pass-through connector connects to the printed circuit board connector. The printed circuit board connector is mounted to the PCB of the disc drive, and the PCB is then fastened to the basedeck. Attaching the disc drive PCB to the basedeck provides the means of maintaining physical contact between the pass-through connector and the printed circuit board connector. An example of this configuration is disclosed in U.S. Patent No. 5,757,580 issued to Andress et al.

Another approach of forming the connection is to feed the flex circuit external to the HDA. Typically the flex circuit passes between the basedeck and a gasket mounted on a cover which mates with the basedeck. Once the flex circuit is external to the HDA, the flex circuit commonly mates with an edge connector that is soldered to the PCB of the disc drive. Disadvantages of this external feed approach include exposure of the flex circuit to damage during handling and difficulties encountered in automated production processes. The production difficulties tend to arise when trying to locate, secure and connect the non-rigid flex circuit via automated means.

Normally, under this external feed approach, the flex circuit is secured to an alignment member which lends support to the flex circuit and provides a means to maintain registration of the contact pads of the flex circuit in relation to female connector pins of a connector soldered to the PCB. The PCB is then fastened to the basedeck to maintain stability of the connection. An example of an adaptation of this approach is disclosed by U.S. Patent No. 5,403,202 to Roehling.

As is known in the art, quality, space constraints, mass production requirements, component costs and component performance (for both mechanical and electrical characteristics) are key factors that influence the choice of an interconnection solution to facilitate connection between the flex circuit and the disc drive PCB.

It is evident from the Roehling U.S. 5,403,202 reference that the prominent key factor driving the signal interconnection selection was the space constraint challenges presented by disc drives having the disclosed 1.3 inch form factor.

In contrast, the three-connector combination approach has generally been driven by a desire to minimize the exposure of the flex circuit to handling and use damage while maximizing the interconnect configuration for automated production processes. Under the three-connector combination approach the flex circuit is confined internal to the HDA of the disc drive, resolving the problem of exposing the flex circuit to handling and environmental damage, while use of the pass-through male pinned connector promotes ease of production.

Advancements in bit transfer rate technologies, with transfer rates in the range of one gigabit per second and the resultant pico-second range rise and fall signal time, has driven the interconnection electrical performance characteristics of the connection as a key factor of read/write signal management. Parasitic electrical signal degradation, due to changes in inductance and capacitance per unit length along the signal path, begins to dominate as the key electrical performance factor to be addressed by read/write signal interconnection technology as bit transfer rates approach the gigabit per second range.

The signal management burdens within read/write signal interconnection technology, brought about by the emergence of transfer rates in the gigabit per second range, coupled with the remaining key factors of quality, mechanical performance, space constraints, automation considerations and component costs, have collectively converged to generate an unmet need in the industry for an improved flex-to-PCB connector that minimizes the parasitic electrical signal degradation effects created by changes in inductance per unit length seen by the read/write signal along the signal path.

Summary of the Invention

The present invention is directed to a flex circuit support and seal apparatus for interconnecting read/write head wires and a printed circuit board in a disc drive.

In accordance with preferred embodiments, the flex circuit support and seal apparatus extends through a connector aperture of a basedeck. A compressible, dielectric seal adjacent the basedeck provides a seal between the basedeck and a rigid dielectric support bracket of the flex circuit support and seal apparatus. The support bracket has a connector portion that provides support for an attached flex circuit that conducts electrical signals between the printed circuit board and the read/write heads. The connector aperture allows passage of the connector portion with the attached flex circuit while preventing passage of the seal. The support bracket with the attached flex circuit is secured to the basedeck through the use of fasteners.

These and various other features and advantages which characterize the present invention will be apparent from a reading of the following detailed description and a review of the associated drawings.

Brief Description of the Drawings

FIG. 1 is a top view of a disc drive constructed in accordance with preferred embodiments of the present invention, the top cover thereof being partially cut-away.

FIG. 2 is a perspective view of the rigid dielectric support bracket of FIG. 1.

FIG. 3 is an exploded perspective view of the flex circuit support and seal apparatus of FIG. 2.

FIG. 4 is a partial cut-away view of a portion of the flex circuit support and seal apparatus of FIG. 3 mounted in the basedeck of FIG. 1.

FIG. 5 is a perspective view of an alternative embodiment of the rigid dielectric support bracket.

FIG. 6 is a perspective view of the support bracket of FIG. 5 with the flex circuit of FIG. 1 attached thereto.

FIG. 7 is a side view of a compressible, deformable resilient dielectric seal.

FIG. 8 is a top plan view of the resilient dielectric seal of FIG. 7.

FIG. 9 is a top plan view of a portion of the basedeck of FIG. 1.

FIG. 10 is a cross-sectional view taken along line 10-10 in FIG. 9.

FIG. 11 is a semi-detailed, partial cut-away, partial cross-sectional view of another embodiment of the flex circuit support and seal apparatus.

Detailed Description

Referring to the drawings in general, and more particularly to FIG. 1, shown therein is disc drive 100 constructed in accordance with preferred embodiments of the present invention. The disc drive 100 includes a head/disc assembly (HDA) 102, which includes a basedeck 104 to which various disc drive components are mounted, a gasket 106, a top cover 108 (partially cutaway), and fasteners 110. Joined together, the basedeck 104, gasket 106, top cover 108 and fasteners 110 (one shown) form a sealed internal environment for the HDA 102. It will be understood that numerous details of construction of the disc drive 100 are not included in the following description as such are well known to those skilled in the art and are believed to be unnecessary for purposes of the present discussion.

Mounted to the basedeck 104 is a disc pack assembly 112 having a spindle motor assembly 114 with a plurality of alternately stacked discs 116 and disc spacers (not shown) disposed about a spindle motor hub 118 and secured by a clamp 120. Adjacent the discs 116 is an actuator assembly 122 which pivots about a cartridge bearing assembly 124. The actuator assembly 122 has a centrally disposed E-block member (not shown) on which a plurality of rigid actuator arms 128 (one shown) are provided. The actuator arms 128 support flexible load arm assemblies 130, each of which in turn supports a read/write

head 132, each read/write head 132 corresponding to a respective surface of one of the discs 116.

Each disc 116 has a data recording surface divided into concentric circular data tracks (not shown), and the read/write heads 132 are positioned adjacent the data tracks to read data from, or write data to the tracks. The data tracks collectively form a data portion on the disc surface defined on its outer extremity by a guard band 134 and on its inner extremity by a landing zone 136.

The actuator assembly 122 is pivotally positioned by a voice coil motor assembly (VCM) 138. The VCM 138 comprises an actuator coil assembly 140 supported by the E-block member and immersed in the magnetic field generated by a magnet assembly 142. The magnet assembly 142 comprises a pair of opposing magnets (not shown) each supported by a pole piece 144. The pole piece 144, constructed from a magnetically permeable material such as steel provides a flux path to complete the magnetic circuit of the VCM 138. The magnet assembly 142 is mounted to the basedeck 104 and to the top cover 108.

When controlled current is passed through the actuator coil assembly 140, an electromagnetic field is established which interacts with the magnetic circuit of the VCM 138 to cause the actuator coil assembly 140 to move relative to the magnet assembly 142 in accordance with the well-known Lorentz relationship.

To provide the requisite electrical conduction paths between the read/write heads 132 and disc drive read/write circuitry (not shown), read/write head wires (not separately shown) are routed on the actuator assembly 122. The read/write head wires run from the read/write heads 132 along the load arm assemblies 130 and the actuator arms 128 to a flex stiffener 146 of a flex circuit support and seal apparatus 148. At the flex stiffener 146, the read/write head wires are soldered to corresponding conductive pads (not shown) of a flex circuit 150. The flex circuit support and seal apparatus 148 comprises the flex stiffener 146, a printed circuit board (PCB) 152, the flex circuit 150 with a conductor portion 154, a rigid dielectric support bracket 156 with a base portion 158 and a connector portion 160 bi-directionally extending vertically from the base portion

158. The flex circuit support and seal apparatus 148 is connected to the basedeck 104 through the use of fasteners 161.

FIG. 2 is perspective view of the support bracket 156. The conductor portion 154 of the flex circuit 150 is in contact with, and is secured by, the connector portion 160 of the support bracket 156. The base portion 158 and the connector portion 160 have a connector aperture 162 (as shown in FIG. 2) for passage of the conductor portion 154 between the base portion 158 and the connector portion 160 of the support bracket 156.

The support bracket 156 further provides a pair of flex circuit attachment pegs 164 extending horizontally from the connector portion 160 and parallel to the base portion 158 for securing the flex circuit 150. The connector portion 160 has a self-adjusting tension portion 166 for keeping the flex circuit 150 taut when attached to the support bracket 156. The support bracket 156 also has strain relief portions 168 vertically extending from the base portion 158 adjacent the attached flex circuit 150. Additionally, the base portion 158 has a pair of mounting apertures 170 disposed and diagonally opposed in the base portion 158 to provide means for securing the dielectric support bracket 156 to the basedeck 104 via the fasteners 161. The connector portion 160 provides rigid support for the conductor portion 154 of the flex circuit 150.

The support bracket 156 forms a "t" shape configuration, the vertical member of the "t" shape comprising the connector portion 160 with the self-adjusting tension portion 166 of the connector portion 160 and the strain relief portion 168, while the base portion 158 comprises the horizontal member of the "t" configuration. The connector portion 160 preferably has a thickness of substantially twenty times the thickness of the flex circuit 150. To complete the horizontal portion of the "t" shape configuration, the base portion 158 forms the mounting apertures 170 and provides the alignment pegs 172 extending from the base portion 158.

Preferably the mounting apertures 170 are disposed diagonally opposed each other to promote a uniform compressive force when the base portion 158 is

secured to the basedeck 104 by the fasteners 161.

FIG. 3 is an exploded perspective view of the flex circuit support and seal apparatus 148 showing a portion of the basedeck 104, the support bracket 156, the flex circuit 150, the flex stiffener 146, the fasteners 161 and an elongated "o-ring" type resilient dielectric gasket seal 174.

The basedeck 104 has a pair of alignment apertures 176 used during the assembly process to align the support bracket 156 to the basedeck 104, and a pair of threaded containment apertures 178 that engage the fasteners 161 to secure the support bracket 156 to the basedeck 104. The basedeck 104 further forms a flex support and seal exit slot (connector slot) 180 to provide passage for the connector portion 160 of the support bracket 156 with the attached conductor portion 154 of the flex circuit 150 from inside the HDA 102 to be extensibly disposed external to the HDA 102.

The flex circuit 150 has a pair of flex alignment apertures 182, a flexible dielectric carrier 184, a stiffener portion 186, conductors 188 and a lead portion 190. When assembled, the conductor portion 154 attaches to the connector portion 160; the seal gasket 174 surrounds the attached conductor portion 154 and comes to rest between the base portion 158 of the support bracket 156 and the basedeck 104. Upon passing the fasteners 161 through the mounting apertures 170, threading the fasteners 161 into the threaded containment apertures 178 and torquing the fasteners 161, the gasket seal 174 compresses and fills any voids between the basedeck 104 and the flex circuit support and seal apparatus 148, thereby sealing the connector slot 180.

The lead portion 190 has several conductive solder pads 192 as appropriate for soldering to read/write head wires (not shown) to electrically connect the read/write heads 132 to the flex circuit 150. The solder pads 192 are supported by the flex stiffener 146, the flex stiffener 146 providing wire channels (not separately shown) for routing the read/write wires to the solder pads 192. In forming the electrical connection a plurality of conductive traces 194 disposed on the flex circuit 150 serve to electrically connect the conductors 188 of the

conductor portion 154 of the flex circuit 150 to the read/write heads 132 via the read/write head wires (not shown).

First ends of the read/write head wires are soldered to the read/write heads 132, and second ends of the read/write head wires are soldered to the solder pads 192 on the lead portion 190 of the flex circuit 150. The conductor portion 154 of the flex circuit 150 is supported by the connector portion 160 of the support bracket 156 and together pass through the connector slot 180 of the basedeck 104 and are extensible from the HDA 102.

FIG. 4 is a partial cut-away side view of the flex circuit support and seal apparatus 148 of FIG. 1, showing the connector portion 160 and the base portion 158 of the support bracket 156 along with the attached flex circuit 150. The flex circuit 150 wraps around the self-adjusting tension portion 166 and conforms to the connector portion 160. The partial cut-away view of the flex circuit 150 exposes the semi-flexible resilient dielectric stiffener portion 186 that provides rigidity for the flex circuit 150 needed to support the conductors 188 during electrical connections and facilitates the passage of the conductor portion 154 through the connector aperture 162. The partial cut-away view of the flex circuit 150 also shows the conductors 188 electrically connected to the conductive traces 194 disposed on the flex circuit. The conductive traces 194 serve to electrically connect the conductors 188 to the solder pads 192 of the lead portions.

As mentioned, the read/write head wires are soldered to, and interconnect the read/write heads 132 and the solder pads 192 of the flex circuit 150. The solder pads 192 are secured in place by the flex stiffener 146 while the PCB 152 attaches to the flex circuit 150 and is used to process electrical signals.

The conductor portion 154 of the flex circuit 150 is supported by the connector portion 160 of the support bracket 156 and together pass through the connector slot 180 in the basedeck 104. The flex circuit 150 together with the connector portion 160 of the support bracket 156 are surrounded by the gasket seal 174, and the gasket seal 174 remains adjacent both the basedeck 104 and the base portion 158 while the connector portion 160 with the attached conductor

portion 154 extend from the internal portion of the HDA 102 by passing through the connector slot 180. FIG. 4 further shows the gasket seal 174 engaging the flex circuit 150, the support bracket 156 and the basedeck 104 to provide the bottom seal portion of the internal environment of the HDA 102.

FIG. 5 is a perspective view of a second embodiment of a rigid dielectric support bracket 200. The support bracket 200 has a base portion 202 and a connector portion 204, the base portion 202 providing attachment means for attaching the support bracket 200 to the basedeck 104. The base portion 202 has a pair of mounting apertures 206 for securing the support bracket 200 to the basedeck 104 via the fasteners 161.

The connector portion 204 extends bi-directionally and vertically from the base portion 202 for securing the flex circuit 150, the connector portion 204 providing a pair of attachment pegs 208 for attaching the flex circuit 150 to the connector portion 204. The attachment pegs 208 extend from the connector portion 204 parallel to the base portion 202 and are used when attaching the flex circuit 150 to the support bracket 200. The base portion 202 further forms a conductor slot 210 through which the conductor portion 154 of flex circuit 150 passes when being attached to the support bracket 200.

FIG. 6 shows a perspective view of the flex circuit 150 attached to the support bracket 200 of FIG. 5. Specifically, FIG. 6 shows the attachment pegs 208 extending through appropriately sized apertures (not separately designated) to secure the flex circuit 150 to the connector portion 204. Also shown is the passage of the conductor portion 154 of the flex circuit 150 through the conductor slot 210. thereby disposing the conductors 188 below the base portion 202. The conductors 188 are electrically connected to the conductive traces 194.

FIG. 7 is a side view of a second compressible, resilient dielectric gasket seal 212. When mounted in the disc drive 100, the seal gasket 212 is adjacent to and positioned between the support bracket 200 and the basedeck 104. The gasket seal 212 forms a main body connector aperture 214 for receiving and allowing the connector portion 204 with the attached conductor portion 154 to

enter and pass through. The main body connector aperture 214 of the gasket seal 212 provides and maintains a compression fit adjacent the conductor portion 154 of the flex circuit 150. The gasket seal 212 additionally provides a nesting portion 216 that conforms to the basedeck 104 and encloses the main body connector aperture 214, thereby providing the bottom seal when compressed during assembly of the HDA 102.

FIG. 8 shows the gasket seal 212 of FIG. 7 to have a pair mounting apertures 218 that align with the corresponding mounting apertures 206 of the base portion 202 of the support bracket 200 to allow the passage of fasteners 161 during attachment the support bracket 200 to the basedeck 104.

The gasket seal 212 is further shown in FIG. 8 to have a main body portion 220 attached to the nesting portion 216. The main body portion 220 encloses the main body connector aperture 214 and preferably has a thickness substantially equal to twenty times the thickness of the flex circuit 150. The nesting portion 216 is seamlessly attached to the main body portion 220 and also encloses the main body connector aperture 214.

The nesting portion 216 is aligned with the main body portion 220 to assure continuity and registration of the main body connector aperture 214. The nesting portion 216 comprises a base member 224, a top member 226, and an external wall 228 (also shown in FIG. 7). The top member 226 has an inner edge (not separately shown) disposed in a plane aligned parallel to the base member 224 and an outer edge 230. The internal wall extends perpendicularly from the base member 224 and terminates at the inner edge of the top member 226. It should be noted that when mounted in the disc drive 100, the internal wall is adjacent the conductor portion 154 attached to the connector portion 204.

The external wall 228 is attached to the internal wall of the nesting portion 216 at the base member 224 and extends from the base member 224 at an outwardly sloping angle terminating at the outer edge 230 of the top member 226. When mounted in the disc drive 100, the external wall 228 is preferably adjacent the basedeck 104.

FIG. 9 shows a top plan view of a portion of the basedeck 104 to illustrate a pair of fastener receptacle standoffs 232, each enclosing a containment aperture 234. A basedeck nest portion 236 receives the nesting portion 216 of the gasket seal 212. The nest portion 236 additionally provides an insertion slot 238 for allowing the passage of the connector portion 204 with the attached conductor portion 154 while restricting passage of nesting portion 216 of the gasket seal 212.

When mounted, the basedeck nest portion 236 of the basedeck 104 is adjacent the nesting portion 222 of the gasket seal 212 while the receptacle standoffs 232 serve to align the gasket seal 212 and controll the amount of compression experienced by the gasket seal 212 to a post compression, predetermined height sufficient to develop and maintain the bottom seal of the HDA 102.

FIG. 10 shows the receptacle standoffs 232, the containment apertures 234, and the basedeck nest portion 236. The basedeck nest portion 236 is configured to receive the nesting portion 216 of the gasket seal 212. Again, the basedeck nest portion 236 provides a passageway for the connector portion 204 with the attached conductor portion 154 to exit the HDA 102 via a flex circuit support and seal apparatus aperture 238. Additionally, FIG. 10 more clearly shows the receptacle standoffs 232 relative to the basedeck 104, the basedeck nest portion 236 and the flex circuit support and seal apparatus aperture 238.

FIG. 11 depicts a printed circuit board (PCB) 240 attached to the basedeck 104 with a single sided electrical spring connector 242 which has plural conductive spring contacts 244, that are disposed to make electrical contact with the conductors 188. The spring contacts 244 have one end soldered and attached to circuitry in the PCB 240. Thus, the flex circuit support and seal apparatus 148 is mounted to the basedeck 104 and plugged into the spring contacts 240 of the PCB 240 to provide electrical connection to the disc drive 100.

The electrical connection made between the spring contacts 244 of the single sided electrical spring connector 242 and the conductors 188 (not

separately shown in FIG. 11) of the flex circuit 150 substantially form a continuous signal path of uniform electrical characteristics by maintaining uniformity in the capacitance and inductance of the signal path over the entire length of the signal path, thereby minimizing the parasitic electrical signal degradation effects created by changes in capacitance and inductance per unit length seen by the read/write signal along the signal path. The PCB 240 is secured to the basedeck 104 through the use of conventional fasteners (not shown)

In view of the foregoing discussion, it will be recognized that the present invention is directed to an apparatus for interconnecting read/write head wires and a printed circuit board in a disc drive.

In accordance with preferred embodiments, a flex circuit support and seal apparatus 148 extends through a connector aperture 162 in a basedeck 104 for attachment of a flex circuit 150 in a disc drive 100. The flex circuit support and seal apparatus has a rigid dielectric support bracket 156 extensive through the connector aperture, and a compressible, deformable resilient dielectric gasket seal 174 is disposed adjacent the basedeck for providing a seal between the basedeck and the support bracket. The support bracket provides support for an attached flex circuit that conducts electrical signals between a printed circuit board 240 and read/write heads 132 of the disc drive. The flex circuit support and seal apparatus 148 is secured to the basedeck in a conventional manner through the use of fasteners 161 attaching the support bracket with the attached flex circuit to the basedeck.

It will be clear that the present invention is well adapted to carry out the objects and attain the ends and advantages mentioned as well as those inherent therein. While a presently first and second embodiment have been described for purposes of this disclosure, numerous changes may be made which will readily suggest themselves to those skilled in the art and which are encompassed in the spirit of the invention disclosed and as defined in the appended claims.

Claims:

1. Flex circuit support and seal apparatus for interconnecting a read/write head and a printed circuit board of a disc drive, the printed circuit board supported on an exterior surface of the basedeck, the flex circuit support and seal apparatus comprising:

a flex circuit comprising a semi-flexible dielectric backing portion supporting an electrical conductor;

a support bracket, supported adjacent an interior surface of the basedeck, which extends through a connector aperture of the basedeck and supports the conductor of the flex circuit to engage contacts associated with the printed circuit board; and

a gasket seal, adjacent the support bracket and the flex circuit, which seals the connector aperature of the basedeck.

2. The flex circuit support and seal apparatus of claim 1, wherein the support bracket comprises a base portion which is secured to the interior surface of the basedeck and a connector portion which bi-directionally extends from the base portion in a direction substantially normal to the interior surface of the basedeck, wherein a portion of the flex circuit abuts the connector portion and extends through the connector aperture in the basedeck to mate with the contacts associated with the printed circuit board.

3. The flex circuit support and seal apparatus of claim 2, wherein the connector portion comprises at least one alignment peg which extends from the connector portion and through an aperture in the flex circuit to secure the flex circuit to the connector portion.

4. The flex circuit support and seal apparatus of claim 2, wherein the flex circuit is wrapped around opposing sides of the connector portion, wherein the connector portion comprises a self adjusting tension portion, and wherein the self adjusting tension portion keeps the flex circuit taut.

5. The flex circuit support and seal apparatus of claim 2, wherein fasteners secure the base portion to the basedeck, the fasteners compressing the gasket seal between the base portion and the interior surface of the basedeck.

6. A disc drive, comprising:

a printed circuit board housing control electronics for the disc drive; and

a head-disc assembly attached to the printed circuit board, comprising:

a basedeck having opposing interior and exterior surfaces, the printed circuit board mounted to the exterior surface;

a read/write head adjacent a disc recording surface; and

a flex circuit support and seal apparatus which interconnects the read/write head and the printed circuit board, comprising:

a flex circuit comprising a semi-flexible dielectric backing portion supporting an electrical conductor;

a support bracket, supported adjacent the interior surface of the basedeck, which extends through a connector aperture of the basedeck and supports the conductor of the flex circuit to engage contacts associated with the printed circuit board; and

a gasket seal, adjacent the support bracket and the flex circuit, which seals the connector aperature of the basedeck.

7. The disc drive of claim 6, wherein the support bracket comprises a base portion which is secured to the interior surface of the basedeck and a connector portion which bi-directionally extends from the base portion in a

direction substantially normal to the interior surface of the basedeck, wherein a portion of the flex circuit abuts the connector portion and extends through the connector aperture in the basedeck to mate with the contacts associated with the printed circuit board.

8. The disc drive of claim 7, wherein the connector portion comprises at least one alignment peg which extends from the connector portion and through an aperture in the flex circuit to secure the flex circuit to the connector portion.

9. The disc drive of claim 7, wherein the flex circuit is wrapped around opposing sides of the connector portion, wherein the connector portion comprises a self adjusting tension portion, and wherein the self adjusting tension portion keeps the flex circuit taut.

10. The disc drive of claim 7, wherein fasteners secure the base portion to the basedeck, the fasteners compressing the gasket seal between the base portion and the interior surface of the basedeck.