



- (51) International Patent Classification:
G01K 13/00 (2006.01)
- (21) International Application Number:
PCT/GR2012/000047
- (22) International Filing Date:
17 October 2012 (17.10.2012)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
20110100612 31 October 2011 (31.10.2011) GR
- (72) Inventor; and
(71) Applicant : KARABINIS, Apostolos [GR/GR]; 151 Lavriou Av., GR-19002 Peania (GR).
- (74) Agent: NIKOLAIDOU, Despoina; 8 Dimokratias Str., GR-15451 N. Phychiko (GR).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP,

KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).


Published:

- with international search report (Art. 21(3))
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))

- (88) Date of publication of the international search report:
9 January 2014

(54) Title: DIGITAL THERMOMETER OF ANTIMICROBIAL COPPER

Fig.1



(57) Abstract: Digital Thermometer of antimicrobial copper, meant for medical use, consisting externally of the body (1), the battery cover that is the removable part through which the battery is inserted into the thermometer (2), the power button i.e. ON-OFF button (3), the display (4) and the tip, that is the sensor for measuring temperature (5) and is characterized by the fact that the outer surface of these components except of the display, is made of antimicrobial copper, or bears antimicrobial copper. Due to the antimicrobial-bacteriostatic properties of copper and its alloys with antimicrobial properties, it is achieved naturally -without any further interference, i.e. without disinfectants use- the neutralization of pathogenic microbes that infest the thermometer body, therefore it is achieved limitation of their further dispersion.

