



(51) International Patent Classification:
E21B 33/04 (2006.01)

(21) International Application Number:
PCT/US2011/043296

(22) International Filing Date:
8 July 2011 (08.07.2011)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
61/389,435 4 October 2010 (04.10.2010) US

(71) Applicant (for all designated States except US): **DRIL-QUIP, INC.** [US/US]; 13550 Hempstead Hwy., Houston, TX 77040 (US).

(72) Inventor: **REIMERT, Larry** (deceased).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **GROHMANN, Andrew, J.** [US/US]; 17806 Safe Haven Drive, Cypress, TX 77433 (US). **WITWER, Bruce, J.** [US/US]; 10047 Briar Park Trail Lane, Houston, TX 77064 (US).

(74) Agent: **HELMREICH, Loren, G.**; 5851 San Felipe, Suite 975, Houston, TX 77057 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

— with amended claims (Art. 19(1))

Date of publication of the amended claims: 19 July 2012

(54) Title: SEAL ASSEMBLY AND METHOD




FIGURE 3

(57) Abstract: A seal assembly (10) is provided for sealing between an interior surface (14) on a wellhead (12) and a tapered exterior surface (18) on a hanger (16). A unitary seal body (20) includes an upper portion for engagement with a force tool and a lower portion for sealing with the wellhead and the hanger. A first locking ring (24) is movable radially inward for securing the sealing assembly to the hanger, and a second locking ring (22) is movable radially outward for securing the seal assembly to the wellhead. An actuation member (60) including a plurality of downward extending fingers passing through slots in the seal body move downward through a portion of the body to force the first and second locking rings into engagement with the wellhead and the hanger.