

SATELLITE POSITIONING AIDED COMMUNICATION SYSTEM SELECTION

BACKGROUND OF THE INVENTION

CROSS REFERENCE TO RELATED APPLICATIONS

[01] This application claims priority to United States Non-Provisional Patent Application Serial No. 11/022,294, filed on December 22, 2004, entitled "SATELLITE POSITIONING AIDED COMMUNICATION SYSTEM SELECTION" which is a continuation-in-part of United States Patent Application 10/885,507, entitled "AIDED LOCATION COMMUNICATION SYSTEM," by A. Pande, Lionel J. Garin, K. Chadha, L. Peng, G. Zhang, N. Vantalon & Gregory B. Turetzky, filed 7/3/04 which is a Continuation-in-part of PCT patent application PCT/US03/16308 entitled "SEARCH DOMAIN REDUCING FREQUENCY TRANSFER IN A MULTI-MODE GPS USED WITH WIRELESS NETWORKS," by A. Pande, Lionel J. Garin, K. Chadha, L. Peng, G. Zhang, N. Vantalon & Gregory B. Turetzky, Filed on 5/22/03 and Published 12/4/03, which claims priority to Continuation-in-part Patent Application No. 10/155,614, entitled "SEARCH DOMAIN REDUCING FREQUENCY TRANSFER IN A MULTI-MODE GPS USED WITH WIRELESS NETWORKS," by L. Garin, L. Peng, G. Zhang & N. Vantalon that was filed on 5/22/02 and issued as United States Patent No. 6,684,158 on 1/27/04, that claimed priority to Patent Application No. 09/795,871 entitled "INFORMATION TRANSFER IN A MULTI-MODE GPS USED WITH WIRELESS NETWORKS," by Ashutosh Pande, Lionel J. Garin, Kanwar Chadha & Gregory B. Turetzky, filed on 02/28/01 and issued on 07/30/02 as United States Patent Application 6,427,120, all of which are incorporated by reference.

[02] 2. Field of the Invention.

[03] This invention relates generally to mobile communication systems and in particular to combined Satellite Positioning Systems (SATPS) and communication systems.

[04] 3. Related Art.

[05] A Satellite Positioning System (SATPS) such as the Global Positioning System (GPS) maintained by the United States Government is based on radio navigation. The GPS system is a satellite based navigation system having a network of 24 satellites, plus on orbit spares, orbiting 11,000 nautical miles above the Earth, in six evenly distributed orbits. Each GPS satellite orbits the Earth every twelve hours.

[06] A prime function of the GPS satellites is to serve as a clock. Each GPS satellite derives its signals from an on board 10.23 MHz Cesium atomic clock. Each GPS satellite transmits a spread spectrum signal with its own individual pseudo noise (PN) code. By transmitting several signals over the same spectrum using distinctly different PN coding sequences the GPS satellites may share the same bandwidth without interfering with each other. The code used in the GPS system is 1023 bits long and is sent at a rate of 1.023 megabits per second, yielding a time mark, sometimes called a "chip" approximately once every micro-second. The sequence repeats once every millisecond and is called the coarse acquisition code (C/A code). Every 20th cycle the

code can change phase and is used to encode a 1500 bit long message, which contains "almanac" data for the other GPS satellites.

[07] There are 32 PN codes designated by the GPS authority. Twenty-four of the PN codes belong to current GPS satellites in orbit and the 25th PN code is designated as not being assigned to any GPS satellite. The remaining PN codes are spare codes that may be used in new GPS satellites to replace old or failing units. A GPS receiver may, using the different PN sequences, search the signal spectrum looking for a match. If the GPS receiver finds a match, then it has identified the GPS satellite, which generated that signal.

[08] Ground based GPS receivers use a variant of radio range measurement methodology, called trilateration, in order to determine the position of the ground based GPS receiver. The GPS position determination is different from the radio direction finding (RDF) technology of the past in that the radio beacons are no longer stationary; they are satellites moving through space at a speed of about 1.8 miles per second as they orbit the earth. By being space based, the GPS system can be used to establish the position of virtually any point on Earth using methods such as trilateration.

[09] The trilateration method depends on the GPS receiving unit obtaining a time signal from the GPS satellites. By knowing the actual time and comparing it to the time that is received from the GPS satellites, the receiver can calculate the distance to the GPS satellite. If, for example, the GPS satellite is 12,000 miles from the receiver, then the receiver must be located somewhere on the location sphere defined by the radius of 12,000 miles from that GPS satellite. If the GPS receiver then ascertains the

position of a second GPS satellite it can calculate the receiver's location based on a location sphere around the second GPS satellite. The two spheres intersect and form a circle with the GPS receiver being located somewhere within that location circle. By ascertaining the distance to a third GPS satellite the GPS receiver can project a location sphere around the third GPS satellite. The third GPS satellite's location sphere will then intersect the location circle produced by the intersection of the location spheres of the first two GPS satellites at just two points. By determining the location sphere of one more GPS satellite, whose location sphere will intersect one of the two possible location points, the precise position of the GPS receiver is determined to be the location point located on the Earth. The fourth GPS satellite is also used to resolve the clock error in the receiver. As a consequence, the exact time may also be determined, because there is only one time offset that can account for the positions of all the GPS satellites. The trilateration method may yield positional accuracy on the order of 30 meters; however the accuracy of GPS position determination may be degraded due to signal strength and multipath reflections.

[010] As many as 11 GPS satellites may be received by a GPS receiver at one time. In certain environments such as a canyon, some GPS satellites may be blocked out, and the GPS position determining system may depend for position information on GPS satellites that have weaker signal strengths, such as GPS satellites near the horizon. In other cases overhead foliage may reduce the signal strength that is received by the GPS receiver unit. In either case the signal strength may be reduced or totally blocked. In such case, aiding information may be used to aid in location determination.

[011] There are multiple ways of using radio spectrum to communicate. For example in frequency division multiple access (FDMA) systems, the frequency band is divided into a series of frequency slots and different transmitters are allotted different frequency slots. In time division multiple access (TDMA) systems, the time that each transmitter may broadcast is limited to a time slot, such that transmitters transmit their messages one after another, only transmitting during their allotted period. With TDMA, the frequency upon which each transmitter transmits may be a constant frequency or may be continuously changing (frequency hopping).

[012] The GPS system currently employs spread spectrum technology to convey its data to ground units. The use of spread spectrum is especially advantageous in satellite positioning systems. Spread spectrum technology enables GPS receiver units to operate on a single frequency, thus saving the additional electronics that would be needed to switch and tune other bands if multiple frequencies were used. Spread Spectrum also minimizes power consumption requirements of GPS receivers. GPS transmitters for example require 50 watts or less and tolerate substantial interference.

[013] Recently mobile communication devices such as cellular telephones have been incorporating GPS receiver technology using multiple dedicated semiconductor chips to implement a communication portion and other dedicated semiconductor chips to implement a GPS portion of the mobile communication device. Mobile communication device often are capable of using one of multiple communication systems that employ different standards, such as Motorola's StarTac that may communicate over a Amps analog cellular system, CDMA digital cellular system, or a GSM digital cellular

system. Currently mobile communication devices determine how to search between the multiple communication systems using brute-force algorithms. Often these algorithms require significant power and are often less than efficient.

[014] Therefore, there is a need for methods and systems for improving the ability of communication devices to quickly and efficiently locate a communication system that may be employed for communication.

SUMMARY

[015] Approaches consistent with the present invention provide a communication device with the ability to use position information to more efficiently access the communication network and/or the ability of a GPS portion of a communication device to more efficiently acquire a GPS signal. By combining the position of the communication device with a geographic database of communication network boundaries and specific elements, the mobile device can restrict its search to network standards and frequencies that correspond to its local position. The communication device may also save time and energy by knowing in advance not to attempt interaction with networks where access is known to be restricted. Such communication device may have generic hardware implementing generic hardware portions of RF receivers along with software to implement a communication function and a GPS function. Such receivers determine if a communication device, such as a cellular telephone may access a communication network. This approach uses positioning data with geographic information associated with the communication network to search only the cell site

frequencies and communication networks that are in proximity to the communication device. In another approach, the communication network provides aiding information to the GPS function that decreases the time to determine the location of the communication device. The communication device may be equipped with a GPS receiver or receive positioning information from other device via another network.

[016] Other systems, methods, features and advantages of the invention will be or will become apparent to one with skill in the art upon examination of the following figures and detailed description. It is intended that all such additional systems, methods, features and advantages be included within this description, be within the scope of the invention, and be protected by the accompanying claims.

BRIEF DESCRIPTION OF THE FIGURES

[017] The components in the figures are not necessarily to scale, emphasis instead being placed upon illustrating the principles of the invention. In the figures, like reference numerals designate corresponding parts throughout the different views.

[018] FIG. 1 illustrates a mobile station having a software implemented satellite-positioning receiver capable of communication with multiple communication networks.

[019] FIG. 2 is a block diagram of the Mobile Station of FIG. 1.

[020] FIG. 3 is a memory diagram of the memory of the Mobile Station of FIG. 2.

[021] FIG. 4 is a memory division diagram of controller functions of FIG 2.

[022] FIG. 5 is a block diagram of a configurable baseband processor with a number of RF chips.

[023] FIG. 6 illustrates a flow diagram of an approach of position determination executed by the Mobile Station of FIG. 2.

[024] FIG. 7 illustrates a flow diagram of the Mobile Station of FIG. 2 using geographic information to select and access a communication network.

DETAILED DESCRIPTION

[025] Unlike the known approaches previously discussed, a Mobile Station is able to use satellite positioning data along with digital geographic data associated with different communication networks to aid or assist in efficiently and rapidly acquire a communication system or to use a communication system to rapidly acquire GPS satellites. Turning first to FIG. 1, a Mobile Station 102 having a software implemented satellite-positioning receiver capable of communication with multiple communication networks 104 and 106 is illustrated 100. The software implemented satellite-positioning receiver may be a set of programmable hardware and shared memory, such as a software configurable digital signal processor connected to a memory. A preprogrammed set of instructions may be executed that configure the programmable hardware and shared memory as the communication function and/or GPS function, such as a software defined radio and a GPS function to implement Mobile Station 102.

[026] A plurality of satellites 108, 110 and 114 orbit the Earth in a constellation. An example of such a satellite constellation is the global positioning system (GPS) operated by the United States Government. The satellites 108, 110 and 112 transmit positioning signals 116, 118 and 120 that may be received at a GPS enabled device such as Mobile Station 102. The Mobile Station 102 may also communicate with different wireless networks, such as example 104 and 106. Examples of a Mobile Station may include; a cellular telephones, a personal digital assistant (PDA), a pager, a computer, or other portable digital devices. Each communication network may communicate with the Mobile Station 102 using unique signals 122 and 124. Examples

of unique signals used by different communication networks are different types of cellular network communication standards (GSM, TDMA, 800MHz AMPS, 800MHz NAMPS, TACS, 800MHz, 1900MHz CDMA).

[027] In FIG. 2, a block diagram 200 of the Mobile Station 102 of FIG. 1 is shown. The Mobile Station 102 has a tunable transceiver 202 coupled to a GPS antenna 204 and a wireless network antenna 206. In other embodiments, a single antenna implementation may be employed that is tuned between the GPS positioning signals and communication network signals.

[028] The tunable receiver 202 may also be coupled to a controller 208. The controller 208 may be coupled to the tunable receiver 202, memory 210, input device 212, display 214, codec 216. The codec 216 may be coupled to the controller 208, speaker 218, and microphone 220. The GPS signal is received via GPS antenna 204 at the tunable transceiver 202 that is tuned to receive the GPS signal. The controller 208 receives and processes the raw GPS positioning data and the location of the Mobile Station 102 is determined. In an alternate embodiment, the location of the Mobile Station 102 may be preloaded by the user, or received via a network such as Bluetooth or 802.11 network from a GPS server or even another wireless device. In other embodiments, communication and GPS signals may be switched between two separate receivers or transceivers with the received signals being processed by a common controller, such as a microprocessor.

[029] The controller 208 may be configurable via software to have a communication function and a GPS function. The software contained in memory 210 may be accessed

during initialization to start the Mobile Station 102 as a communication device executing the communication function or as a GPS receiver executing the GPS function. In yet another embodiment, the hardware may be configured so both the communication function and GPS function are executed at the same time with multiplexing or sharing of other common hardware, such as areas of memory 210 and the tunable receiver 202. The controller 208 may also configure the tunable receiver 202 to receive data from the communication system or the GPS system.

[030] The controller 208 using the determined location, may access digital geographic data contained in memory 210. The digital geographic data in memory 210 may have communication network information associated with different geographic positions. The communication network information accessed by the controller 208 may then be used to select a communication network which to tune the tunable transceiver 202. Once tuned to a selected communication network, the controller 208 may activate a graphical symbol on the display 214 that indicates a link with the communication network.

[031] Once a connection is established with the communication network, then calls may be placed with audio data being coded and decoded via a codec 216. Audio signals are received at a microphone 220 and digitally encoded by the codec 216 for communication over the communication network. The controller 208 passes digital communication signals received at the tunable transceiver 202 to the codec 216 where they are decoded from digital signals into audio signals. The audio signals are then passed to the speaker 218. In other embodiments, it may be possible that the

positioning link established in the communication network is a communication link, such as a link established using the 802.11 or UWB standard.

[032] Turning to FIG. 3, a memory diagram of the memory 210 of Mobile Station 102 of FIG. 2 is shown. The memory 210 may be random access memory (RAM), read only memory (ROM), electronically programmable memory (EPROM, EEPROM), or a combination of digital memory. The memory may also be optical memory such as found in compact disk (CDs) or similar memory readable using laser light.

[033] The memory 210 may have an area for storing software referred to as program space 302 that controls the operation of the Mobile Station 102. Another area of memory 210 may be used for data input and data output buffering referred to as I/O space 304. Digital geographic data may be stored in a mapping data 306 locations in memory 210. Another area of memory 210 may be reserved for communication network data 308 that associates cell site information with the digital geographic data. The digital geographic data may be downloaded over a network into the memory or contained in a removable memory chip, such as used by GPS chart plotters.

[034] In FIG 4, a diagram 400 of the system memory 210 a division of the memory of Mobile Station 102 is shown. The diagram 400 is in the form of a matrix with subprograms used by the different functions (communication, GPS, Shared, and initializer) listed along the axes. Cell 402 indicates that Input/Output (I/O) area in memory may be shared between the communication function, GPS function, and the initializer function. The Input/Output (I/O) area is typically used to store captured raw data and may be implemented as a receive/transmit data buffer. This data may have

had a carrier signal that is removed prior to the data being processed in the digital domain. The data may be at an intermediate frequency of a few MHz rather than the typical carrier frequency in the GHz range. If the GPS function and communication function are not processing signals at the same time, the I/O memory may also be used as a buffer that is shared between the different functions. The memory is further partitioned into program space with low-level processing programs such as low-level math processing for algorithm processing and common signal processing 404 that may be once again shared between communication functions, GPS functions and the initializer.

[035] Communication software may have an area of memory where the software is loaded and located for use by the communication function and the GPS functions as shown by block 406. Examples of such software may include pre-processing of the data contained in the memory. Both the communication function and the GPS functions perform many similar tasks. For example, both radios may need to perform additional processing on the captured digital signals before they perform correlation. This additional processing may require additional modulation, application of IIR or FIR filtering, narrow-band noise analysis using frequency domain methods. The low-level mathematical functions to perform these tasks are the same in either the communication function or the GPS function of a software defined communication device enabling the software in the memory to be shared. Further, both the communication function and the GPS function may perform detection by correlating incoming data against reference

symbols and may also share low-level functions for these operations can be shared by both the communication function and the GPS function.

[036] Similarly, the GPS function may have a dedicated area of memory 408 for GPS specific software that enable location determination upon acquisition of location messages from satellites or aiding messages for other networks. Another area of memory shown by cell 410 may be dedicated for initialization of the other functions and configuring the memory. The memory may be random access type memory or read only permanent memory (including electronic programmable memory and smart cards). Examples of the type of software stored in this memory may include logic to initialize the configurable hardware for implementing the communication function, logic to initialize the configurable hardware for implementing the GPS function, initialize communication between the GPS function and the communication function.

[037] The memory may also have an area for databases 412 that contain geographic information such as cellular cell locations. The databases may be fixed at the time of manufacturing of the Mobile Station 102 or may receive initial data and periodic updates via the network or via a user interface such as a serial bus connection on a personal computer, Bluetooth connection, or similar point-to-point or point-to-multipoint communication approaches.

[038] Now turning to FIG. 5, a block diagram of a basband process coupled to a number of RF chips in the tunable receiver 202 is shown. Processing of digital signals typically occur in a two parts. The first part is the RF processing that removes the signal from a RF carrier. RF processing may occur within a dedicated chip, often

referred to as a RF chip. The RF chips 502, 504 and 506 may be connected to individual antennas or may jointly share antennas depending on the implementation. The RF chips 502, 504 and 506 are also coupled to a baseband processor 508 that processes the digital signals once the RF carrier has been removed. A resource and savings is achieved by having a baseband processor 508 that is configurable by a controller to function with different RF chips. In other implementations, RF chips such as RF chips for GPS, BlueTooth, cellular, Ethernet, and WiFi may interface with a configurable baseband processor.

[039] In FIG. 6, a flow diagram 600 of an approach of position determination executed by the Mobile Station of FIG. 2 is illustrated. The flow diagram starts 602 with a determination of the communication link status 604. In a cellular communication network, the communication function of the communication device may search for a communication link that is provided by one or more base stations. Once the communication link is identified, communication between the Mobile Station 102 and the network (switch and or server) may occur. The network may provide useful information to aid in rapid position determination 606. Examples of the useful information may include the location of the base station, sometime referred to as a cell tower. Other useful information may also include accurate time that may or may not be synchronized with the GPS network.

[040] If useful information is available 606, then the position determination is constrained to an initial location and satellite Doppler based on the location of the base station 608. The local time estimate may also be updated using the received accurate

time 610. A code phase range may then be constructed, provided the time is sufficiently accurate 612. A GPS search is then preformed using the constrained code phase range if available in 614. If useful information is not available 606 than a traditional GPS search is performed 614 without using additional aiding or assisting information. Upon position determination by the GPS function in the communication device, the memory may be updated 616 with almanac data, ephemeris data, and/or the location of the Mobile Station 102.

[041] In FIG. 7, a flow diagram 700 of an approach network access executed by the Mobile Station 102 of FIG. 2 that determines which communication network to access. The flow diagram starts 702 with the tunable transceiver 202, being tuned to receive GPS signals. The GPS signals are received and the position of the Mobile Station is determined 704. The controller 208 than access the digital geographic database 706 using the determined GPS. Search the database for communication network data associated with the digital geographic data 708. If communication network data is available 710, then the controller than accesses the communication network data associated with the geographic database in order to identify what network and frequencies to initially attempt to access in order to setup a communication link 712. The controller 208 than makes a determination if a communication network is available to be accessed by the mobile station 102 in step 712. If communication network is available 208, than the controller configures the tunable transceiver for the closest network to be accessed 712. In the case of a cellular network, it would be the frequencies associated with the closet base site.

[042] If the closest communication network is not reachable (i.e. a link can not be established) 714, then a check is made to determine if there are any other communication networks or cell sites within the communication network are within range 716. If there are other networks or cell sites are within range, then the next closest is identified 712 and the controller 208 tunes the transceiver 202 to those frequencies 716. If a link with communication network is established 714, then processing is complete 720.

[043] If communication is determined not to be available in either steps 712 or 718, then the transceiver is not tuned and may be placed in a sleep mode to conserve power 722. A timer may be set for the period of sleep 724 and then the GPS position may be determined again 704. The sleep period may only be with respect to the communication network, while the transceiver is awake at predetermined periods to receive and process location information.

[044] Parts of the flow diagram of FIG. 6 and FIG. 7 may be implemented in hardware, software, or a combination of hardware and software. Aspects of the present invention may be implemented as instructions in memory, one skilled in the art will appreciate that all or part of systems and methods consistent with the present invention may be stored on or read from other machine-readable media, for example, secondary storage devices such as hard disks, floppy disks, and CD-ROMs; a signal received from a network; or other forms of ROM or RAM either currently known or later developed.

[045] In the current embodiment, the Mobile Station 102 has been described as a common set of hardware that is configurable by software to function as a software

defined radio having both a communication function and a GPS function. In an alternate embodiment, the Mobile Station 102 may be communication device having dedicated hardware to implement the communication function and other hardware for implementing the GPS function. In yet other implementations, different degrees of hardware reuse may be achieved. In other implementations, the approaches to improving connection time and time required to make a position determination discussed above may be implemented on any type of communication device having some type of GPS function and access directly or indirectly to a geographical database.

[046] The foregoing description of an implementation has been presented for purposes of illustration and description. It is not exhaustive and does not limit the claimed inventions to the precise form disclosed. Modifications and variations are possible in light of the above description or may be acquired from practicing the invention. For example, the described implementation includes software but the invention may be implemented as a combination of hardware and software or in hardware alone. Note also that the implementation may vary between systems. The claims and their equivalents define the scope of the invention.

CLAIMS

What is claimed is:

1. A device, comprising:
 - a receiver that is tunable between receipt of a positioning signal and a communication network signal;
 - a memory with geographic data that is associated with at least one communication network;
 - a controller coupled to the receiver and adapted to access the memory to retrieve the parameters to access the at least one communication network corresponding to positioning data from the receiver, and
 - a timer that is configurable to place the receiver in a sleep mode for a predetermined period of time set by the controller when the at least one communication network is unreachable by the device.
2. The device of claim 1, wherein the geographic data is received at the receiver and stored in the memory by the controller.
3. The device of claim 1 or 2, wherein the controller is configurable by software to function as a satellite positioning device that processes the positioning signals and a communication device that process the communication network signal.
4. The device of any of claims 1 to 3, including a common antenna coupled to the receiver.
5. The device of any of claims 1 to 4, wherein the receiver is a transceiver.

6. The device of any of claims 1 to 5, wherein the geographic data has cell site information.
7. The device of claim 6, where the geographic data further includes a plurality of frequencies associated with a cell site.
8. The device of any of claims 1 to 7, wherein the receiver further includes:
 - a first RF chip associated with the positioning signals;
 - a second RF chip associated with the communication network signal; and
 - a baseband processor configurable for receipt of the positioning signals from the first RF chip and then the communication network signal from the second RF chip.
9. A method of communication, comprising:
 - tuning a receiver between receipt of a positioning signal and a communication network signal;
 - storing in a memory geographic data that is associated with at least one communication network; and
 - processing at a controller coupled to the receiver, positioning data from the receiver and accessing the memory to retrieve the parameters to access the at least one communication network corresponding to the positioning data, and
 - setting a timer to place the receiver in a sleep mode for a predetermined period of time when the at least one communication network is unreachable by the device.

10. The method of claim 9, including:
receiving geographic data at the receiver; and
storing the geographic data in the memory by the controller.
11. The method of claim 9 or 10, further comprising:
configuring the controller with software to function as a satellite positioning device that processes the positioning signals and a communication device that process the communication network signal.
12. The method of any of claims 9 to 11, wherein the geographic data has cell site information.
13. The method of claim 12, wherein the geographic data further includes a plurality of frequencies associated with a cell site.
14. The method of claim 10, wherein tuning further includes:
receiving at a first RF chip associated with the positioning signals;
receiving at a second RF chip associated with the communication network signal;
and
configuring a baseband processor configurable for receipt of the positioning signals from the first RF chip and then the communication network signal from the second RF chip.

15. A signal bearing medium with machine readable instructions which, when executed by a computer, causes the computer to perform the steps of the method according to any of claims 9 to 14.