

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



9905957-3
1903

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04R 9/06, 7/16	A1	(11) International Publication Number: WO 98/53640
		(43) International Publication Date: 26 November 1998 (26.11.98)

(21) International Application Number: PCT/JP98/01650

(22) International Filing Date: 10 April 1998 (10.04.98)

(30) Priority Data:
9/147039 22 May 1997 (22.05.97) JP

(71) Applicants (for all designated States except US): KABUSHIKI KAISHA KENWOOD [JP/JP]; 14-6, Dougenzaka 1-chome, Shibuya-ku, Tokyo 150-0043 (JP). MOGAMI DENKI KABUSHIKI KAISHA [JP/JP]; 954-1, Aza Shiono, Oaza Aramachi, Mamurogawamachi, Mogami-gun, Yamagata 999-5312 (JP).

(72) Inventor; and

(75) Inventor/Applicant (for US only): SAKAMOTO, Yoshio [JP/JP]; 108-6-503, Yokokawa-chou, Hachioji-shi, Tokyo 193-0823 (JP).

(74) Agents: OKABE, Masao et al.; No. 602, Fuji Building, 2-3, Marunouchi 3-chome, Chiyoda-ku, Tokyo 100-0005 (JP).

(81) Designated States: CN, SG, US.

Published
With international search report.

(54) Title: LOUDSPEAKER SUSPENSION DEVICE AND FABRICATING METHOD THEREOF

(57) Abstract

Flat knitted tinsel wires (2h) are sewn on a base cloth (B) of a conductive suspension (1) with a sewing thread (3) and the ends (2ha, 2hb) of the flat knitted tinsel wires extend outward from the conductive suspension (1). In this suspension device, a work load of peeling off the flat knitted tinsel wire ends (2ha and 2hb) from the base cloth (B) is reduced and associated problems are solved. The flat knitted tinsel wires (2h) are sewn on the base cloth (B), with the flat knitted tinsel wire ends (2ha, 2hb) being positioned at base close holes (B1), and thermally pressed and trimmed together with the base cloth (B).

