9705664-2

RTMPS copy

0341974
18 JUL 1996

PCT WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 : G01N 33/18	A1	(11) International Publication Number: WO 96/24056
		(43) International Publication Date: 8 August 1996 (08.08.96)

(21) International Application Number: PCT/US96/00805

(22) International Filing Date: 18 January 1996 (18.01.96)

(30) Priority Data:

9501732.3	30 January 1995 (30.01.95)	GB
08/466,486	6 June 1995 (06.06.95)	US

(71) Applicant: W.R. GRACE & CO.-CONN. [US/US]; 1114 Avenue of the Americas, New York, NY 10036 (US).

(72) Inventors: HERMAN, Patrick; 27, rue de la Gare, F-28230 Droue-sur-Drouette (FR). FAURE, Jean-Marc; Les Peyrouses, F-07130 Cornas (FR). ENGELBERG, Philippe; 2, rue Ampère, F-78420 Carrières-sur-Seín (FR). MERCUSOT, Michel; 21, avenue de la Fauvette, B-1640 Rhode-St.-Genese (BE).

(74) Agent: MAGGIO, Robert, A.; W.R. Grace & Co.-Conn., 7500 Grace Drive, Columbia, MD 21044 (US).

(81) Designated States: AL, AM, AT, AU, AZ, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GE, HU, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AZ, BY, KG, KZ, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).

Published

With international search report.

Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(54) Title: CHLORIDE MONITORING APPARATUS AND PROCESS

(57) Abstract

A chloride analyser includes an inlet valve and filters for process water to be analyzed, as well as a pH electrode to verify the pH value of the incoming liquid before further treatment. A stripper bubbles stripping air through the process water to remove hydrocarbons and hydrogen sulphide therefrom, and the discharge line from said stripper feeds a reaction vessel to which also reagent from a supply vessel is passed. After a suitable reaction time, optionally followed by a further air stripping operation through air supply line, the reaction products are fed via line to an ionometry measuring cell where chloride analysis is carried out using a specific ion selective electrode.