

FLOW METER AND METHOD FOR DETECTING A CABLE FAULT IN A CABLING OF THE FLOW METER

Background of the Invention

5

1. *Field of the Invention*

The present invention relates to a flow meter and method for detecting a cable fault in a cabling of the flow meter.

10 2. *Statement of the Problem*

Vibrating conduit sensors, such as Coriolis mass flow meters, typically operate by detecting motion of a vibrating conduit that contains a flowing material. Properties associated with the material in the conduit, such as mass flow, density and the like, can be determined by processing measurement signals received from
15 motion transducers associated with the conduit. The vibration modes of the vibrating material-filled system generally are affected by the combined mass, stiffness and damping characteristics of the containing conduit and the material contained therein.

A typical Coriolis mass flow meter includes one or more conduits that are
20 connected inline in a pipeline or other transport system and convey material, e.g., fluids, slurries and the like, in the system. Each conduit may be viewed as having a set of natural vibration modes including, for example, simple bending, torsional, radial, and coupled modes. In a typical Coriolis mass flow measurement application, a conduit is excited in one or more vibration modes as a material flows
25 through the conduit, and motion of the conduit is measured at points spaced along the conduit. Excitation is typically provided by an actuator, e.g., an electromechanical device, such as a voice coil-type driver, that perturbs the conduit in a periodic fashion. Mass flow rate may be determined by measuring time delay or phase differences between motions at the transducer locations. Two such
30 transducers (or pickoff sensors) are typically employed in order to measure a vibrational response of the flow conduit or conduits, and are typically located at positions upstream and downstream of the actuator. The two pickoff sensors are connected to electronic instrumentation by cabling, such as two independent pairs

METER ELECTRONICS AND METHODS FOR DETECTING A CABLE FAULT IN A CABLING OF A FLOW METER

Background of the Invention

5

1. *Field of the Invention*

The present invention relates to a flow meter and method for detecting a cable fault in a cabling of the flow meter.

10 2. *Statement of the Problem*

Vibrating conduit sensors, such as Coriolis mass flow meters, typically operate by detecting motion of a vibrating conduit that contains a flowing material. Properties associated with the material in the conduit, such as mass flow, density and the like, can be determined by processing measurement signals received from
15 motion transducers associated with the conduit. The vibration modes of the vibrating material-filled system generally are affected by the combined mass, stiffness and damping characteristics of the containing conduit and the material contained therein.

A typical Coriolis mass flow meter includes one or more conduits that are
20 connected inline in a pipeline or other transport system and convey material, e.g., fluids, slurries and the like, in the system. Each conduit may be viewed as having a set of natural vibration modes including, for example, simple bending, torsional, radial, and coupled modes. In a typical Coriolis mass flow measurement application, a conduit is excited in one or more vibration modes as a material flows
25 through the conduit, and motion of the conduit is measured at points spaced along the conduit. Excitation is typically provided by an actuator, e.g., an electromechanical device, such as a voice coil-type driver, that perturbs the conduit in a periodic fashion. Mass flow rate may be determined by measuring time delay or phase differences between motions at the transducer locations. Two such
30 transducers (or pickoff sensors) are typically employed in order to measure a vibrational response of the flow conduit or conduits, and are typically located at positions upstream and downstream of the actuator. The two pickoff sensors are connected to electronic instrumentation by cabling, such as two independent pairs