

SINGAPORE

**PATENTS ACT 1994
(ACT 21 OF 1994)**

THE PATENT'S RULES 1995


VERIFICATION OF TRANSLATION

I, Françoise HUGLY (name of translator)
of Pré Vulliemin 5 CH - 1400 CHESEAUX-NOREAZ (Switzerland)
..... (translator's address)

hereby declare as follows:

1. I am a translator and am familiar with the French and English language.
2. I am the translator of the documents attached hereto and certify that the following is a true translation of the International Application PCT/CH96/00371..... to the best of my knowledge and belief.

Dated this twentysecond day of April 1998

.....

Signature of Translator

ULTRA-LIGHT ROAD VEHICLE

The present invention concerns an ultra-light road vehicle comprising only a small number of components, specifically a vehicle of the type known as a "city car" for commuting use, in particular electrically propelled, comprising a supporting structure, two front wheels and one rear wheel mounted on this supporting structure by means of suspensions and a separate passenger compartment fitted on to this supporting structure, which comprises a hollow central beam.

Vehicles intended for use as city cars are already known, particularly electrically propelled. They are generally designed on the principle of miniaturization of standard automobiles. Thus they usually consist of a chassis or a self-supporting passenger compartment which fulfils the functions of a cabin for the occupants and a chassis carrying the wheel suspension arms, motor and all the peripheral components providing the drive, steering, safety equipment such as the braking system, etc.

These vehicles generally possess four wheels, which must be far enough apart, both longitudinally and laterally, that is to say, must form a wheelbase and track sufficient to guarantee a minimum degree of stability to the whole. As a consequence, their weight is considerable in spite of the use of lightweight materials, such as composites and thermoplastics, especially where the passenger compartment is concerned. Because of this weight, the quantity of energy required for propulsion is considerable, a particularly serious handicap for an electrically propelled vehicle, since accumulator batteries are heavy. The greater the amount of energy required, the greater will be the size and weight of the necessary batteries. Since the possibilities for weight reduction of standard vehicles are limited, development continues to be oriented towards vehicles propelled by internal combustion engines until such time as lighter batteries come on to the market. At present, the net weight of vehicles of this type is so great that the energy required to provide them with optimum range for the function for which they are intended cannot

be stored in the form of electrical energy, due to the weight of the storage media of this type of energy.

Apart from the problem of weight of present-day vehicles, the number of their component parts poses a further problem. A standard vehicle, relatively small
5 and at the entry end of the range, comprises over 30,000 parts. The price of these parts, and above all their assembly costs, raise the cost of these vehicles to such a point that the concept of the "city car" ceases to be economically viable.

The German publication DE-30 27 072 A1 describes a three-wheeled vehicle
10 comprising a central supporting structure, two rear drive wheels and one front steering-wheel. The passenger seats are arranged on either side of the central supporting structure.

In practice, it becomes apparent that three-wheeled vehicles having two wheels at the rear and one at the front are highly unstable, their road-holding
15 on bends being much inferior to that of three-wheeled vehicles having two wheels at the front and one at the rear.

In addition, arranging the seats on either side of the central supporting structure results in a wide, cumbersome vehicle, incompatible with the concept of the city car.

20 This arrangement can also be dangerous for passengers in case of lateral impact, which may result in their being crushed against the central supporting structure.

The purpose of the present invention is to palliate these disadvantages by proposing a vehicle of the above-mentioned type, designed so as to lighten
25 the basic structure to the maximum extent so that it can be driven by an electric motor, without reducing its effective range below the threshold where the vehicle would cease to be of interest. Its design also minimizes the space it occupies, especially when parking, and it is constructed from a reduced number of component parts.

This purpose is achieved by the vehicle of the invention, characterized in that said hollow central beam is constituted from an extruded section profile made of a lightweight material of constant cross-section, in that the two front wheels provide the steering and the rear wheel provides the propulsion and lies approximately on the axis of said hollow central beam, in that the propulsion motor and energy storage are housed inside the hollow central beam, and in that the separate passenger compartment is fixed as a unit to the hollow central beam.

The vehicle will preferably comprise two front plates and one rear plate, these plates being constructed so as to be lodged at least partially in the profiles sections of said hollow central beam, these plates being adapted to carry the suspensions of the front wheels and the suspension of the rear wheel respectively.

The hollow central beam will preferably have the cross-section of an inverted T over its entire length, the lower surface being extended laterally by two lateral walls symmetrically arranged with respect to the median longitudinal plane of the beam.

This structure presents the advantage of being very economical to manufacture, by extrusion and cutting to desired length. The plates are lodged in the extremities of the hollow central beam and fixed by simple bolts, enabling quick and economical assembly or disassembly. Furthermore, the plates with the wheel suspensions and wheels can be treated as sub-assemblies suitable for pre-fitting, thereby simplifying final assembly of the vehicle.

The hollow central beam can receive accessories or components which are easily accessible by simply removing one or other of the plates.

In the preferred form of construction, the rear plate carries a support for the rear wheel, this support comprising a spring-suspension unit and two suspension arms of which one end is fixed to this plate by an axle and the other end carries the axle of the rear wheel, which is mounted between said

suspension arms.

In this embodiment, the rear plate carries one end of the spring-suspension unit, the other end being connected to the suspension arms of the rear wheel.

According to an advantageous form, the suspension arms of the rear wheel
 5 are pivotable and arranged to enable the vehicle to take up a normal position or a shortened position, the pivoting arms carrying the wheel being arranged approximately in alignment with the axis of the central beam when the vehicle is in normal position, and these arms being inclined with respect to the central beam when the vehicle is in shortened position, this shortened position being
 10 attained by the functioning of the rear wheel simultaneously with locking of the front steering-wheels.

In the preferred form of construction, the pivoting arms are articulated to the rear plate and mounted on a transverse axle carrying an electric motor on the housing of which is fitted a cradle carrying the lower extremity of a spring-
 15 suspension unit of the suspension arms, the upper extremity of which is fixed to an arm rigidly fixed to the rear plate.

The cradle can carry two pins which extend laterally either side of this cradle and are constructed so as to engage with two hooks to lock the vehicle into its normal position. These hooks are pivotable and articulated on a support
 20 carried by a cross-member linked to the two pivoting arms.

To maintain the vehicle in shortened position, the vehicle should preferably be equipped with a locking cylinder mounted between the motor and the cross-member carrying the hooks.

In the preferred form of construction, the vehicle comprises an arched bow
 25 constituting the frame of a seat, the extremities of this bow being provided with two flanges which engage in longitudinal grooves in the side walls of the central beam.

The hollow central beam will preferably comprises a sliding support to contain

at least one accumulator battery for the electric propulsion motor.

According to an advantageous form of embodiment the passenger compartment is a separate cell made of synthetic material, of which at least one wall is double and incorporates air cushions.

- 5 The passenger compartment is advantageously constructed at least partially by a technique of rotational moulding, hollow moulding or blown extrusion.

A part at least of the side walls is double-skinned and incorporates integral air cushions which improve the safety of the occupants by acting as shock dampers and energy absorbers.

- 10 The passenger compartment is preferably mounted on the hollow central beam by means of studs engaged in the grooves.

Advantageous said studs are four in number, two each side of the hollow central beam being fixed, and the other two sliding in said grooves.

- 15 In the preferred embodiment, the hollow central beam contains a sliding support containing at least one accumulator battery as the power supply to the electric motor, and said sliding support is rigidly fixed to the rear plate.

The extruded hollow central beam, closed at both ends, and can advantageously function as a fuel tank to supply an internal combustion engine.

- 20 The passenger compartment will preferably be composed of several components assembled by welding, the welding seams constituting zones of reinforcement. Said passenger compartment constitutes a survival cavity connected to the hollow central beam by studs which are detachable in case of impact.

- 25 In an advantageous form of construction, the passenger compartment comprises lateral protuberances which serve as a step and as an energy absorber, and also has means to emit light from at least one source.

The present invention will be more easily understood by reference to the description of a preferred mode of construction and its variants, and to the attached drawings, in which:

- 5 - figure 1 represents an overall elevation view of an of the ultra-light road vehicle according to the invention,
- figure 2 represents an above view of the vehicle of figure 1,
- figure 3 is a front view of the vehicle of the preceding figures,
- figure 4 shows an exploded view of the vehicle according to the invention as shown in figures 1 to 3,
- 10 - figure 5 shows a perspective view of the chassis of the vehicle according to the invention,
- figure 6 is a front view of the chassis of the vehicle as shown in figure 5,
- figure 7 is a side view of the chassis equipped with its wheels, in normal position,
- 15 - figure 8 is a view similar to that in figure 7, but with the chassis shown in shortened position,
- figure 9 shows the chassis with its wheels, seen from above,
- figures 10 and 11 represent the rear wheel with its suspension, seen in perspective, in the normal and shortened positions of the vehicle
- 20 respectively, and
- figures 12A and 12B show partial cross-sectional views of the passenger compartment or separate cell of the vehicle.

Referring to the figures, the ultra-light road vehicle 10 consists principally, as shown in figures 1 to 3, of a supporting structure or chassis 9 and a

25 passenger compartment or cell 8, a separate unit, mounted on this chassis. It

is equipped with three wheels arranged so that one 15 is located at the rear, approximately on the prolongation of the axis of the chassis, and the other two 17 and 18 at the front, each side of the chassis. The rear wheel provides the propulsion and the front wheels the steering.

- 5 As shown in greater detail in figures 4 and 5, the chassis consists principally of a hollow central beam 12, made from extruded aluminium section having the cross-section of an inverted T, into the respective end profiles of which are inserted a rear plate 13 and two front plates 14.

10 The rear plate 13 carries the rear wheel 15 of the vehicle 10 and a spring-suspension unit 16 for this wheel. The front plates 14 of the vehicle 10 carry the front wheels 17 and 18 and their suspensions, 19 and 20 respectively. An arch-shaped bow constituting the frame 21 of the adjustable back of a seat made of cloth stretched between the arms of the bow is also fixed to the central beam. Specifically, the ends of this bow are equipped with two flange
15 plates 22 each engaging in one of the grooves 23 of two lateral walls 24 of the section constituting said hollow central beam. The flange plates 22, and thus also the bow 21, are locked in position by means of spring loaded pins 25 engaging in holes drilled in the grooves 23.

20 The rear wheel 15 is mounted on an axle 26 the ends of which are supported by a spring-suspension unit 16 composed of two suspension arms 27 which form a oscillating support for this wheel. The two pivoting arms are articulated on to the rear plate 13, at the opposite end to that carrying the axle 26. This spring-suspension unit 16 is so designed as to enable the vehicle to take up a normal position or shortened position which reduces its wheelbase by reason
25 of the fact that the pivoting arms 27, which carry the rear wheel 15, are arranged approximately along the prolongation of the axis of the central beam 12 when the vehicle is in normal position and are inclined with respect to this beam when the vehicle is in its shortened position. The rear plate 13 also carries an electric motor 28 whose output shaft is fitted with a drive pinion or
30 sprocket 29 (see figure 9) intended to be coupled by a chain or belt to a drive pinion or sprocket 30 rigidly fixed to the rear wheel 15.

The spring-suspension unit 16 carries a helicoïdal spring 31 positioned coaxially around a shock absorber 32 mounted between a rigid arm 33 rigidly fixed to the rear plate 13 and a rigid supporting element to be defined below with reference to figures 10 and 11.

- 5 The front wheels 17 and 18 are connected to the chassis by wishbones rigidly fixed to the front plate 14, as shown in detail in figure 6. Each wheel is held by a lower suspension strip 35 pivoting on a part 36 rigidly fixed to the front plate 14, and by an upper suspension wishbone 37 pivoting on an axle 38 fixed by an appropriate support 39 to the same front plate 14. Each of the two upper
- 10 suspension wishbones 37 is fitted with an obliquely mounted bell crank 40, the two bell cranks being linked together by a spring-suspension unit 41 which provides suspension and shock absorption for the whole front of the vehicle. The lower suspension strip 35 should preferably be made of a composite material.
- 15 The vehicle is designed primarily to be electrically propelled. The energy source consists of accumulator batteries housed inside the central beam 12 on a support sliding inside the beam and accessible for example by disassembly of the rear plate.

- Figure 4 shows in greater detail the interior of the central beam 12 and in particular a sliding support 51 containing a row cells 50 formed in this support and designed to accept a series of accumulators 52. For installation and maintenance, the accumulators 52 are first positioned in the cells provided for the purpose, then the sliding support is introduced into the central beam at one end, specifically the rear end, the rear plate 13 being rigidly fixed to the
- 20 sliding support 51, which is guided into the beam. This process is rendered easier by the fact that the sliding support is itself supported by the rear wheel.

Other components, such as the cables of the electrical harness, are also housed in the cavity of the central beam 12.

- The cell or passenger compartment 8, which will be described with reference
- 30 to figures 12A and 12B, is mounted on the central beam 12 by suitable

- fastenings, by engagement in the grooves 23 of the hollow central beam 12 and by bolts or similar means. In practice, and according to an advantageous mode of construction, the cell is fixed by four studs which engage in the grooves of the central beam. Two of these studs, for example the front ones, are fixed by bolts and two, for example the rear studs, are simply restrained without being fixed. In this way, expansion of the cell and changes in length can easily be absorbed. The cell is composed of a carcass of synthetic material, for example a material which lends itself to the techniques of rotational moulding or blown extrusion.
- 10 The cell is designed to contain two seats one behind the other. This arrangement makes possible a good, aerodynamic profile, favouring a reduction in air resistance and therefore in energy consumption.

- Figures 10 and 11 show in detail the rear wheel 15 and the rear suspension arm 16 of the vehicle, seen in perspective when the vehicle is in normal position and shortened position respectively. As these figures show, the rear wheel is supported by the pivoting arms 27 which are jointed to the rear plate 13 by means of a transverse axle 60 which carries the electric motor 28, lodged in the plate 13. This motor is mounted free to turn on this axle by means of a bearing. The housing of this motor carries a cradle 62, constituting said supporting element defined above, which serves as a support for the lower end of the unit combining the spring 31 and shock absorber 32 of spring-suspension unit 16, the upper end of which is jointed on to the rigid arm 33. It should be noted that the cradle 62 comprises two pins 63 extending laterally either side of the central part. These pins 63 are constructed so as to engage with two hooks 64 pivoting on a support 65 mounted on a cross-member 66 coupled to the two pivoting arms 27.

- In the normal position shown in figure 10, the hooks 64 are engaged with the pins 63 so that the suspension, that is the combination of spring 31 and shock absorber 32, is operational, being coupled between the chassis and the suspension arms.

In the shortened position shown in figure 11, the hooks 64 are disengaged from the pins 63, and the wheel support is free to pivot about the axle 60. This is the structure which enables the vehicle to be brought into shortened position, reducing its wheelbase and facilitating parking. When the whole of the device described above is mechanical, this manoeuvre is effected as follows:

- the hooks 64 are unlocked by means of a hydraulic cylinder or cable (not shown)
- pressure is applied simultaneously to the brake pedal (not shown), which locks the front wheels, and to the accelerator pedal which causes the rear wheel to turn. This causes the rear of the vehicle to rise, lifted by the power of the propulsion motor.

The vehicle is maintained in shortened position or in an intermediate position by a pneumatic locking cylinder 67 which is open during the lifting phase and whose opening close at the end of its travel. Reduction of wheelbase by lifting of the rear of the chassis continues until cylinder 67 reaches its end stop (see figure 11).

While the vehicle is locked in this raised position, forward or reverse motion can be engaged for parking or similar manoeuvres. The vehicle can also be driven in shortened position, cylinder 67 transmitting the effort to the suspension of the rear wheel.

To restore the vehicle to its normal position, which corresponds to normal use on the road, a control is provided to unlock the locking cylinder 67 and so allow the vehicle to return to its normal position by the force of gravity.

The system described above is entirely mechanical, but it could also be partly or wholly automated.

The mechanical system is advantageous in that it requires only a minimum of parts and involves the shock absorber, enabling impacts against kerbs or

- other obstacles to be absorbed.

Referring to figures 12A and 12B, the passenger compartment 8 comprises a completely separate cell which can be mounted on the hollow central beam of the vehicle simply by means of bolts. This cell is made out of plastic parts and is multifunctional, comprising at one and the same time the external bodywork, including such elements as supports for headlights and indicators, and the internal passenger compartment, with integral instrument panel, soundproofing and especially seat.

The cross-sectional view 12A shows the overall shape of the cell, which incorporates the instrument panel 80 and windscreen 81. The cross-sectional view 12B shows a lower part 82 and an upper part 83 which are constructed double-skinned with air cushions 84 and 85 incorporated. The side pillars 87 which partly support the windscreen, the rear end 86 of the cell and the floor 88 can also advantageously incorporate hollow zones which constitute air cushions and furthermore contribute to reducing the weight of the cell.

The cell or passenger compartment 8 can advantageously be constructed in several parts, for example three parts which are partially hollow, forming air cushions to absorb shocks. These parts are preferably assembled by welding to create zones of reinforcement along the weld seams.

- 20 The cell can be separated from the chassis by rupture of the studs should they be subjected to severe strain, especially in case of impact. Thanks to the presence of the air cushions, which constitute shock absorbers, the cell can become a survival compartment with less energy to dissipate than the rest of the vehicle, comprising chassis, wheels, motor, etc.
- 25 The cell advantageously comprises lateral protuberances serving as steps and also constituting absorbers of kinetic energy in case of impact, notably by reason of their special shape.

This construction ensures excellent passenger protection in case of impact.

The cell constructed as a hollow moulding can constitute a diffuser of light thanks to several light sources distributed about the bodywork to illuminate all of part of the vehicle at night.

5 The vehicle according to the invention is particularly advantageous for a variety of reasons. For one thing, all the major components are easily disassembled and can be replaced at modest cost in case of damage. Assembly is simple and uses only simple equipment not requiring heavy investment for assembly. It should be noted, in particular, that the wheel
10 suspensions are jointed on to the corresponding plates, enabling the manufacture of pre-fitted sub-assemblies. These plates are lodged in the hollow central beam and fixed with bolts. This mode of assembly enables the vehicle as defined by the invention to be made without recourse to the cumbersome infrastructure which is usual in the motor industry. Assembly is reduced to fitting pre-assembled modules, making it possible in particular to
15 create small assembly plants near to localities of sale and use.

In addition, all the components are made from recyclable materials. At assembly, all working parts are fitted to the chassis, so that the vehicle is mobile in the factory, even without its passenger compartment.

20 Maintenance is very simple and can be carried out by people with no special qualifications.

The vehicle is economical in use and manoeuvring it is within the capacities of anybody.

25 The fact that the passengers sit astride the central beam which really comprises the main component makes it possible to create a vehicle which is simple, comprising less than a tenth of the number of components of a standard vehicle, at a low price, while at the same time possessing remarkable stability and road holding and a particularly high safety factor.



CLAIMS

1. An ultra-light road vehicle comprising only a small number of components, specifically a vehicle of the type known as a "city car" for commuting use, in particular electrically propelled, comprising a supporting
5 structure, two front wheels and one rear wheel mounted by suspensions on this supporting structure and a separate passenger compartment fitted on to the supporting structure, the supporting structure comprising a hollow central beam, characterized in that said hollow central beam (12) is constituted from an extruded section profile made of a lightweight material of constant cross-
10 section, in that the two front wheels (17, 18) provide the steering and the rear wheel (15) provides the propulsion and lies approximately on the axis of said hollow central beam (12), in that the propulsion motor (28) and energy storage are housed inside the hollow central beam (12), and in that the separate passenger compartment is fixed as a unit to the hollow central beam (12).
- 15 2. Vehicle according to claim 1, characterized in that it comprises two front plates (14) and one rear plate (13), these plates being so constructed as to be lodged at least partially in the ends of the profiles of said hollow central beam, and in that these plates are adapted to carry, respectively, the suspensions of the front wheels (17, 18) and the rear wheel (15).
- 20 3. Vehicle according to claim 1, characterized in that the hollow central beam (12) comprises over its whole length the cross-section of an inverted T with its lower surface extended laterally in two lateral walls (24) arranged symmetrically with respect to the longitudinal median plane of this beam.
4. Vehicle according to claim 3, characterized in that the lateral walls (24)
25 each comprise at least one longitudinal groove (23) designed to fix components and/or accessories.
5. Vehicle according to claim 2, characterized in that the rear plate (13) carries a support for the rear wheel, this support including a spring-suspension unit (16) and two suspension arms (27), of which one end is fixed
30 by an axle to this plate and the end carries the axle (26) of the rear wheel (15)



which is located between said suspension arms.

6. Vehicle according to claim 5, characterized in that the rear plate (13) carries one end of the spring-suspension unit (16), the other end being linked to the suspension arms (27) of the rear wheel.

5 7. Vehicle according to claim 5, characterized in that the suspension arms of the rear wheel (15) are pivotable and arranged to enable the vehicle to take up a normal position or a shortened position, said pivoting arms (27) carrying the wheel being located approximately on the prolongation of the axis of the central beam (12) when the vehicle is in its normal position, and these arms
10 being inclined with respect to this central beam when the vehicle is in shortened position, this shortened position being attained by the functioning of the rear drive wheel simultaneously with locking of the front steering-wheels.

8. Vehicle according to claim 5, characterized in that the pivoting arms (27) are articulated on to the rear plate (13) and mounted on a transverse axle
15 (60) carrying an electric motor (28) on the housing of which is mounted a cradle (62) which carries the lower end of the combination of spring (31) and shock absorber (32) of the spring-suspension unit (16), the upper end of which is fixed to an arm (33) rigidly fixed to the rear plate (13).

9. Vehicle according to claim 8, characterized in that the cradle (62)
20 carries two pins (63) which extend laterally either side of this cradle and are constructed so as to engage with two hooks (64) to lock the vehicle into its normal position.

10. Vehicle according to claim 9, characterized in that the hooks (64) are pivoted and articulated on to a support (65) carried on a cross-member (66)
25 coupled to the two pivoting arms (27).

11. Vehicle according to claim 8, characterized in that it comprises a locking cylinder (67) designed to maintain the vehicle in its shortened position.

12. Vehicle according to claim 11, characterized in that the locking cylinder



(67) is mounted between the motor (28) and the cross-member (66) carrying the hooks (64).

13. Vehicle according to claim 4, characterized in that it includes a bow (21) constituting a seat frame, the ends of this bow being equipped with two
5 flange plates (22) each engaging in one of said longitudinal grooves (23).

14. Vehicle according to claim 1, characterized in that the hollow central beam (12) includes a sliding support to contain at least one accumulator (52) as power supply for the propulsive electric motor (28).

15. Vehicle according to claim 1, characterized in that the passenger
10 compartment (8) is a separate cell which is made of synthetic material and at least part of which is double-skinned and incorporates air cushions.

16. Vehicle according to claim 15, characterized in that the passenger compartment (8) is constructed at least partially by a technique of rotational moulding, hollow moulding or blown extrusion.

15 17. Vehicle according to claim 15, characterized in that the passenger compartment (8) is mounted on the hollow central beam (12) by means of studs engaged in the grooves (23).

18. Vehicle according to claim 17, characterized in that said studs are four
20 in number, two each side of the hollow central beam (12) being fixed, and the other two sliding in said grooves (23).

19. Vehicle according to claim 1, characterized in that the hollow central beam (12) contains a sliding support (51) containing at least one accumulator battery (52) providing the power supply for the propulsive electric motor (28).

20. Vehicle according to claim 19, characterized in that said sliding support
25 (51) is rigidly fixed to the rear plate (13).

21. Vehicle according to claim 1, characterized in that the extruded hollow central beam (12), closed at both ends, constitutes a fuel tank for an internal



combustion engine.

22. Vehicle according to claim 15, characterized in that the passenger compartment (8) comprises several component parts assembled by welding, the welding seams constituting zones of reinforcement.
- 5 23. Vehicle according to claim 15, characterized in that the passenger compartment (8) constitutes a survival cell attached to the hollow central beam (12) by studs which are detachable in case of impact.
24. Vehicle according to claim 15, characterized in that the passenger compartment (8) comprises lateral protuberances which serve as a step and
10 as an energy absorber.
25. Vehicle according to claim 15, characterized in that the passenger compartment (8), constructed as a hollow moulding, includes means to diffuse light from at least one source.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6

7/12





FIG. 7






FIG. 9





FIG. 10






FIG. 12A

FIG. 12B


PCTORGANISATION MONDIALE DE LA PROPRIÉTÉ INTELLECTUELLE
Bureau international

DEMANDE INTERNATIONALE PUBLIÉE EN VERTU DU TRAITE DE COOPERATION EN MATIÈRE DE BREVETS (PCT)

(51) Classification internationale des brevets ⁶ : B62D 61/08, 31/00, 47/00, 21/04	A1	(11) Numéro de publication internationale: WO 97/15484 (43) Date de publication internationale: 1er mai 1997 (01.05.97)
(21) Numéro de la demande internationale: PCT/CH96/00371 (22) Date de dépôt international: 22 octobre 1996 (22.10.96) (30) Données relatives à la priorité: 95/12951 23 octobre 1995 (23.10.95) FR (71)(72) Déposant et inventeur: THULIEZ, Jean-Luc [CH/CH]; Montagu 30, CH-2520 La Neuveville (CH). (74) Mandataire: NITHARDT, Roland; Cabinet Roland Nithardt, Y-Parc/Chemin de la Sallaz, CH-1400 Yverdon-les-Bains (CH).		(81) Etats désignés: AU, BR, CA, CN, CZ, GE, IL, JP, KP, KR, MX, NO, NZ, PL, RO, SG, TR, US, VN, brevet européen (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Publiée <i>Avec rapport de recherche internationale.</i> <i>Avant l'expiration du délai prévu pour la modification des revendications, sera republiée si de telles modifications sont reçues.</i>

(54) Title: ULTRA-LIGHT ROAD VEHICLE**(54) Titre: VEHICULE ROUTIER ULTRA-LEGER****(57) Abstract**

An ultra-light road vehicle such as a so-called 'town car', particularly an electrically powered one, wherein the weight of the basic construction is minimised so that the vehicle may be powered by batteries while having a standard degree of autonomy for the class of vehicles in question, and the space requirement of said vehicle is reduced for easier parking. For this purpose, said vehicle comprises a chassis (9) with a central hollow beam (12) consisting of an extruded profile section made of a lightweight material and forming a housing for batteries (52) and a driving engine (28), a body (8) consisting of a separate sealed hollow assembly mounted on the chassis, and two steerable wheels (17, 18) at the front and a drive wheel (15) at the back connected to the chassis via suspensions. The rear wheel (15) is mounted on pivotable arms (27) so that the vehicle can be converted from a normal position to a shortened position in which the wheel base is reduced. The pivotable arms (27) are substantially aligned with the central beam (12) when the vehicle is in the normal position, and at an angle thereto when the vehicle is in the shortened position.



(57) Abrégé

La présente invention concerne un véhicule routier ultra-léger, notamment un véhicule du type appelé "voiture de ville", en particulier à propulsion électrique, conçu de manière à alléger au maximum sa structure de base pour qu'il puisse être entraîné par des accumulateurs en ayant une autonomie normale pour ce genre de véhicule et à avoir un encombrement réduit pour le stationnement. A cet effet il comporte un châssis (9) formé par une poutre centrale creuse (12) constituée par un profilé extrudé en un matériau léger et servant de logement à des accumulateurs (52) et au moteur de propulsion (28), un habitacle (8) réalisé en corps creux hermétiquement fermé indépendant adapté sur ce châssis, deux roues directrices (17, 18) situées à l'avant et une roue motrice (15) située à l'arrière (15), montées au moyen de suspensions à ce châssis. Le montage de la roue arrière (15) par des branches pivotantes (27) permet au véhicule de prendre une position normale et une position raccourcie qui diminue son empattement, ces branches pivotantes (27) étant disposées sensiblement dans le prolongement de la poutre centrale (12) lorsque le véhicule est dans sa position normale, et inclinées par rapport à cette poutre lorsque le véhicule est dans sa position raccourcie.

UNIQUEMENT A TITRE D'INFORMATION

Codes utilisés pour identifier les Etats parties au PCT, sur les pages de couverture des brochures publiant des demandes internationales en vertu du PCT.

AT	Arménie	GB	Royaume-Uni	MW	Malawi
AT	Autriche	GE	Géorgie	MX	Mexique
AU	Australie	GN	Guinée	NE	Niger
BB	Barbade	GR	Grèce	NL	Pays-Bas
BE	Belgique	HU	Hongrie	NO	Norvège
BF	Burkina Faso	IE	Irlande	NZ	Nouvelle-Zélande
BG	Bulgarie	IT	Italie	PL	Pologne
BJ	Bénin	JP	Japon	PT	Portugal
BR	Brsil	KE	Kenya	RO	Roumanie
BY	Bélarus	KG	Kirghizistan	RU	Fédération de Russie
CA	Canada	KP	République populaire démocratique de Corée	SD	Soudan
CF	République centrafricaine	KR	République de Corée	SE	Suède
CG	Congo	KZ	Kazakhstan	SG	Singapour
CH	Suisse	LI	Liechtenstein	SI	Slovénie
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovaquie
CM	Cameroun	LR	Libéria	SN	Sénégal
CN	Chine	LT	Lituanie	SZ	Swaziland
CS	Tchécoslovaquie	LU	Luxembourg	TD	Tchad
CZ	République tchèque	LV	Lettonie	TG	Togo
DE	Allemagne	MC	Monaco	TJ	Tadjikistan
DK	Danemark	MD	République de Moldova	TT	Trinité-et-Tobago
EE	Estonie	MG	Madagascar	UA	Ukraine
ES	Espagne	ML	Mali	UG	Ouganda
FI	Finlande	MN	Mongolie	US	Etats-Unis d'Amérique
FR	France	MR	Mauritanie	UZ	Ouzbékistan
GA	Gabon			VN	Viet Nam