

METHOD AND DEVICE FOR DUAL NETWORK BACKUP AND WIRELESS COMMUNICATIONS SYSTEM

TECHNICAL FIELD

Embodiments of the present invention relate to the field of wireless communications, and
5 more specifically, to a method and a device for dual network backup and a wireless
communications system.

BACKGROUND

With the rapid development of communications technologies, mobile data services
increase sharply, and how to ensure mobile network reliability is an important issue that an
10 operator faces. Particularly, some private networks, such as a Global System for Mobile
Communications Railway (GSMR, GSM Railway), impose higher requirements on the
mobile network reliability.

To improve the reliability, for a wireless network, a same area is covered by two layers
of networks. Optionally, backup may be performed for a device at a base station level or base
15 station controller level, and a working status is switched by enabling an active device or
enabling a standby device, so as to implement coverage of two networks, namely, an active
network and a standby network, on the same area. However, in the prior art, only one network
works in a same period of time, and a dual network switchover is performed at least at the
base station level. Therefore, normal working of a mobile network cannot be adequately
20 ensured, and the mobile network reliability is not high enough.

SUMMARY

In view of this, embodiments of the present invention provide a method and a device for

dual network backup and a wireless communications system, to solve a problem that mobile network reliability is not high enough.

According to a first aspect, a method for dual network backup is provided, including: generating a one-to-one correspondence between an active cell and a standby cell, where
5 coverage areas of the active cell and the standby cell are the same, the active cell is managed by an active base station that is managed by an active base station controller, and the standby cell is managed by a standby base station that is managed by a standby base station controller; enabling, according to whether a current network is an active network or a standby network,
10 corresponding carriers of the active cell and corresponding carriers of the standby cell to separately work; and querying a network availability status, and performing, when it is determined that the network availability status meets a designated condition, a switchover between the active network and the standby network.

In a first possible implementation manner, different BCCH carriers are configured for the active cell and the standby cell, where the BCCH carriers are carriers, which are used to send
15 a broadcast channel, among cell carriers, and a carrier, except a BCCH carrier, among all carriers of one cell is a non-BCCH carrier.

With reference to the first possible implementation manner of the first aspect, in a second possible implementation manner, when the current network is the active network, the active base station controller enables all carriers of the active cell to work, and the standby base
20 station controller enables a BCCH carrier of the standby cell to work and a non-BCCH carrier to skip working; or

when the current network is the standby network, the standby base station controller enables all carriers of the standby cell to work, and the active base station controller enables all carriers of the active cell to skip working.

25 With reference to the second possible implementation manner of the first aspect, in a third possible implementation manner, when the BCCH carrier of the standby cell is normal, an operation and maintenance link OML link of the standby base station controller of the standby cell is normal, an A-interface link of the standby base station controller is normal, and the standby base station controller is normal, a switchover from the active network to the
30 standby network is performed if one of the following situations is met: a BCCH carrier of the

active cell is faulty; the BCCH carrier of the active cell is normal, but an OML link of the active base station controller of the active cell is faulty, and a delay protection time for OML link interruption expires; and an A-interface link of the active base station controller is faulty, and the active base station controller is faulty.

5 With reference to the third possible implementation manner of the first aspect, in a fourth possible implementation manner, the active base station controller starts a switchover timer, switches a service of the active cell to a neighboring cell of the active cell, sends a switchover request to the standby base station controller, and starts a switchover waiting timer; after receiving the switchover request, the standby base station controller enables all the carriers of
10 the standby cell to work, records a switchover alarm, and sends a switchover response to the active base station controller; after receiving the switchover response, the active base station controller stops the switchover waiting timer, and records a switchover alarm.

 With reference to the second possible implementation manner of the first aspect, in a fifth possible implementation manner, a switchover is performed from the standby network to
15 the active network when the standby network works, a BCCH carrier of the active cell is normal, an OML link of the active base station controller of the active cell is normal, and an A-interface link of the active base station controller is normal.

 With reference to any one of the first to the fifth possible implementation manners of the first aspect, in a sixth possible implementation manner, the non-BCCH carrier of the standby
20 cell is configured as a subset of non-BCCH carriers of the active cell.

 With reference to the first aspect or the foregoing possible implementation manners of the first aspect, in a seventh possible implementation manner, the active base station controller and the standby base station controller are connected by using a same core network, or the active base station controller and the standby base station controller are connected by
25 using different core networks.

 According to a second aspect, a device for dual network backup is provided, including a generating unit, a control unit, and a switchover unit, where the generating unit is configured to generate a one-to-one correspondence between an active cell and a standby cell, where coverage areas of the active cell and the standby cell are the same, the active cell is managed
30 by an active base station that is managed by an active device, and the standby cell is managed

by a standby base station that is managed by a standby device; the control unit is configured to enable, according to whether a current network is an active network or a standby network, corresponding carriers of the active cell and corresponding carriers of the standby cell to separately work; and the switchover unit is configured to query a network availability status, and when it is determined that the network availability status meets a designated condition, perform a switchover between the active network and the standby network.

In a first possible implementation manner, the device further includes a configuring unit, where the configuring unit is configured to configure different BCCH carriers for the active cell and the standby cell, where the BCCH carriers are carriers, which are used to send a broadcast channel, among cell carriers, and a carrier, except a BCCH carrier, among all carriers of one cell is a non-BCCH carrier.

With reference to the first possible implementation manner of the second aspect, in a second possible implementation manner, when the current network is the active network, a control unit of the active device enables all carriers of the active cell to work, and a control unit of the standby device enables a BCCH carrier of the standby cell to work and a non-BCCH carrier to skip working; or when the current network is the standby network, a control unit of the standby device enables all carriers of the standby cell to work, and a control unit of the active device enables all carriers of the active cell to skip working.

With reference to the second possible implementation manner of the second aspect, in a third possible implementation manner, the switchover unit is specifically configured to: when the BCCH carrier of the standby cell is normal, an operation and maintenance link OML link of the standby device of the standby cell is normal, an A-interface link of the standby device is normal, and the standby device is normal, perform a switchover from the active network to the standby network if one of the following situations is met: a BCCH carrier of the active cell is faulty; the BCCH carrier of the active cell is normal, but an OML link of the active device of the active cell is faulty, and a delay protection time for OML link interruption expires; and an A-interface link of the active device is faulty, and the active device is faulty.

With reference to the second aspect or the foregoing possible implementation manners of the second aspect, in a fourth possible implementation manner, the device further includes a sending unit, a receiving unit, and a recording unit, where a switchover unit of the active

device starts a switchover timer, and switches a service of the active cell to a neighboring cell of the active cell, a sending unit of the active device sends a switchover request to the standby device, and the switchover unit of the active device starts a switchover waiting timer; after a receiving unit of the standby device receives the switchover request, the control unit of the
5 standby device enables all the carriers of the standby cell to work, a recording unit of the standby device records a switchover alarm, and a sending unit of the standby device sends a switchover response to the active device; after a receiving unit of the active device receives the switchover response, the switchover unit of the active device stops the switchover waiting timer, and a recording unit of the active device records a switchover alarm.

10 With reference to the second possible implementation manner of the second aspect, in a fifth possible implementation manner, a switchover unit of the standby device is configured to perform a switchover from the standby network to the active network when the standby network works, a BCCH carrier of the active cell is normal, an OML link of the active device of the active cell is normal, and an A-interface link of an active base station controller is
15 normal.

With reference to any one of the first to the fifth possible implementation manners of the second aspect, in a sixth possible implementation manner, the configuring unit configures the non-BCCH carrier of the standby cell as a subset of non-BCCH carriers of the active cell.

With reference to the second aspect or the foregoing possible implementation manners of
20 the second aspect, in a seventh possible implementation manner, the active device and the standby device are connected by using a same core network, or the active device and the standby device are connected by using different core networks.

According to a third aspect, a device for dual network backup is provided, including a processor and a memory, where the memory is configured to store information that the
25 processor executes the following method; and the processor is configured to: generate a one-to-one correspondence between an active cell and a standby cell, where coverage areas of the active cell and the standby cell are the same, the active cell is managed by an active base station that is managed by an active device, and the standby cell is managed by a standby base station that is managed by a standby device; enable, according to whether a current network is
30 an active network or a standby network, corresponding carriers of the active cell and

corresponding carriers of the standby cell to separately work; and query a network availability status, and when it is determined that the network availability status meets a designated condition, perform a switchover between the active network and the standby network.

5 In a first possible implementation manner, the processor is further configured to configure different BCCH carriers for the active cell and the standby cell, where the BCCH carriers are carriers, which are used to send a broadcast channel, among cell carriers, and a carrier, except a BCCH carrier, among all carriers of one cell is a non-BCCH carrier.

10 With reference to the first possible implementation manner of the third aspect, in a second possible implementation manner, when the current network is the active network, a processor of the active device enables all carriers of the active cell to work, and a processor of the standby device enables a BCCH carrier of the standby cell to work and a non-BCCH carrier to skip working; or when the current network is the standby network, a processor of the standby device enables all carriers of the standby cell to work, and a processor of the active device enables all carriers of the active cell to skip working.

15 With reference to the second possible implementation manner of the third aspect, in a third possible implementation manner, the processor is specifically configured to: when the BCCH carrier of the standby cell is normal, an operation and maintenance link OML link of the standby device of the standby cell is normal, an A-interface link of the standby device is normal, and the standby device is normal, perform a switchover from the active network to the standby network if one of the following situations is met: a BCCH carrier of the active cell is faulty; the BCCH carrier of the active cell is normal, but an OML link of the active device of the active cell is faulty, and a delay protection time for OML link interruption expires; and an A-interface link of the active device is faulty, and the active device is faulty.

25 With reference to the third aspect or the foregoing possible implementation manners of the third aspect, in a fourth possible implementation manner, the processor of the active device starts a switchover timer, switches a service of the active cell to a neighboring cell of the active cell, sends a switchover request to the standby device, and starts a switchover waiting timer; after a receiving unit of the standby device receives the switchover request, the processor of the standby device enables all the carriers of the standby cell to work, a memory of the standby device records a switchover alarm, and the processor of the standby device

30

sends a switchover response to the active device; after the processor of the active device receives the switchover response, the processor of the active device stops the switchover waiting timer, and a memory of the active device records a switchover alarm.

With reference to the second possible implementation manner of the third aspect, in a fifth possible implementation manner, the processor of the standby device is configured to perform a switchover from the standby network to the active network when the standby network works, a BCCH carrier of the active cell is normal, an OML link of the active device of the active cell is normal, and an A-interface link of an active base station controller is normal.

With reference to any one of the first to the fifth possible implementation manners of the third aspect, in a sixth possible implementation manner, the processor configures the non-BCCH carrier of the standby cell as a subset of non-BCCH carriers of the active cell.

With reference to the third aspect or the foregoing possible implementation manners of the third aspect, in a seventh possible implementation manner, the active device and the standby device are connected by using a same core network, or the active device and the standby device are connected by using different core networks.

According to a fourth aspect, a wireless communications system is provided, including a base station and any one of the foregoing devices.

In the foregoing technical solutions, a correspondence between an active cell and a standby cell is generated, corresponding carriers are configured, according to whether a current network is an active network or a standby network, to work, and a switchover between the active network and the standby network is performed according to a network availability status, so that mobile network reliability is ensured more adequately at a cell level.

BRIEF DESCRIPTION OF DRAWINGS

To describe the technical solutions in the embodiments of the present invention more clearly, the following briefly introduces the accompanying drawings required for describing the embodiments or the prior art. Apparently, the accompanying drawings in the following description show merely some embodiments of the present invention, and a person of

Telecommunications System).

A user equipment (UE, User Equipment), also referred to as a mobile terminal (Mobile Terminal), a mobile user equipment, and the like, may communicate with one or more core networks (Core Network) through a radio access network (for example, RAN, Radio Access Network). The user equipment may be a mobile terminal, such as a mobile phone (also referred to as a "cellular" phone) and a computer with a mobile terminal. For example, the user equipment may be a portable, pocket-sized, handheld, computer built-in, or in-vehicle mobile apparatus, which exchanges voice and/or data with the radio access network.

A base station may be a base station (BTS, Base Transceiver Station) in the GSM or CDMA, or a base station (NodeB) in the WCDMA; a base station controller may be a base station controller (Base Station Controller, BSC) in the GSM or CDMA, or an RNC (Radio Network Controller) in the WCDMA. The GSM, the UMTS, and the like belong to a radio scope, and the embodiments of the present invention may be used for radio network backup of the GSM, and may also be used for radio network backup of another RAT, which is not limited in the present invention. However, for ease of description, the following embodiments are described by using a BSC, a BTS, and the like in the GSM as examples.

In addition, the terms "system" and "network" may be used interchangeably in this specification. The term "and/or" in this specification describes only an association relationship for describing associated objects and represents that three relationships may exist. For example, A and/or B may represent the following three cases: Only A exists, both A and B exist, and only B exists. In addition, the character "/" in this specification generally indicates an "or" relationship between the associated objects.

Existing technologies for improving mobile network reliability mainly include disaster recovery backup. In a technology, when an active base station controller shuts down, a standby base station controller takes over a service of the active base station controller. The technology is at a base station controller level. For another network element, the active base station controller and the standby base station controller are the same, the active base station controller has an IP address the same as that of the base station controller of which a current status is a standby state, and only one base station controller works in a same period of time.

If a base station controller works normally, but a fault, for example, a carrier fault or an

RSL (Radio Signaling Link, radio signaling link) fault, occurs in a base station or a cell managed by the base station controller, this still causes service interruption at a cell level of a network. It can be seen that the mobile network reliability cannot be well ensured by using the technology in which backup is performed only at the base station controller level. In addition, because only one base station controller works in the same period of time, the base station controller in the standby state is idle, so that device functions cannot be brought into full play and resources are wasted.

In another technology, dual network backup is performed at a site level. In this case, a switchover between an active network and a standby network refers to a switchover between a base station in the active network and a base station in the standby network. For example, when a base station controller in the active network learns that a base station managed by the base station controller will stop working, the base station controller provides a notification for a base station controller in the standby network, and stops power transmission of the base station in the active network; after receiving the notification, the base station controller in the standby network instructs a base station in the standby network to start to work.

The technology is at a base station level, and a base station in another network is enabled only when a base station completely stops working. For example, an active-standby switchover is performed only when all carriers of the base station are faulty or a master control unit of the base station is faulty, and backup cannot be performed in a timely manner for a cell in which a fault already occurs. Therefore, the technology cannot well ensure that the network works normally. In addition, because only one network works in a same period of time, device functions of a base station in a standby network and the like cannot be brought into full play and resources are wasted.

The embodiments of the present invention provide a method for dual network backup, which can adequately ensure mobile network reliability at a cell level.

FIG. 1 is a schematic networking diagram of a wireless communications system according to an embodiment of the present invention. A dual network in this embodiment of the present invention refers to active network devices and standby network devices that are included in the wireless communications system 10. The active network devices include an active base station controller 11 and an active base station 12 managed by the active base

station controller 11. FIG. 1 further shows an active cell 13 managed by the active base station 12. The standby network devices include a standby base station controller 14 and a standby base station 15 managed by the standby base station controller 14. FIG. 1 further shows a standby cell 16 managed by the standby base station 15. The active base station controller 11 and the standby base station controller are separately connected to a core network 18.

In methods for dual network backup in the embodiments of the present invention, a switchover between an active network and a standby network is performed according to a network availability status. The switchover between the active network and the standby network refers to a switchover between working statuses of an active cell of the active network and a standby cell of the standby network. For example, if a switchover from the active network to the standby network is performed, the standby cell 16 of the standby network mainly undertakes work, but the active cell 13 of the active network does not work; if a switchover from the standby network to the active network is performed, the active cell 13 of the active network mainly undertakes the work, but the standby cell 16 of the standby network assists the work or does not work.

An active-standby cell binding relationship is generated, so that a same area is simultaneously covered by a pair of the active cell 13 and the standby cell 16, where the active cell and the standby cell are in a one-to-one correspondence. Among cells managed by one active base station controller, some cells may be configured as the active cell that has the active-standby cell binding relationship, and the remaining cells may exist as independent cells 17. A situation of the standby base station controller is similar, and cells managed by the standby base station controller may include both the standby cell and independent cells 17.

The active base station controller 11 and the standby base station controller 14 may belong to a same core network or different core networks. For brevity, in this embodiment of the present invention, only the core network 18 is used to show any of the foregoing situations, where a communications protocol between network elements is the same as that in the prior art. In Fig. 1, the active base station controller 11 and the standby base station controller 14 are connected by using the core network 18 and an IUR-G (Interface Between two RNCs, interface between two radio network controllers).

In a same network, an interface between a base station controller and a core network is

an A-interface. The base station controller sends information such as a control message, a recorded log, and an alarm to a base station by using an OML (Operation Maintenance Link, operation and maintenance link).

FIG. 2 is a schematic flowchart of a method 20 for dual network backup according to an embodiment of the present invention, including the following content:

S21: Generate a one-to-one correspondence between an active cell and a standby cell, where coverage areas of the active cell and the standby cell are the same, the active cell is managed by an active base station that is managed by an active BSC, and the standby cell is managed by a standby base station that is managed by a standby BSC.

S22: Enable, according to whether a current network is an active network or a standby network, corresponding carriers of the active cell and corresponding carriers of the standby cell to separately work.

S23: Query a network availability status; when it is determined that the network availability status meets a designated condition, perform a switchover between the active network and the standby network.

In this embodiment of the present invention, a correspondence between an active cell and a standby cell is generated, corresponding carriers are configured, according to whether a current network is an active network or a standby network, to work, and a switchover between the active network and the standby network is performed according to a network availability status, so that mobile network reliability is ensured more adequately at a cell level.

FIG. 3 is a schematic flowchart of another method 300 for dual network backup according to an embodiment of the present invention, including the following content:

S305: Generate a one-to-one correspondence between an active cell and a standby cell.

As shown in FIG. 1, a same area is simultaneously covered by two cells, namely, the active cell and the standby cell. Optionally, in addition to the active cell, cells of an active base station may further include some independent cells; in addition to the standby cell, cells of a standby base station may further include some independent cells. The independent cells are cells except the active cell and the standby cell.

S310: Configure different BCCH carriers for the active cell and the standby cell.

A carrier for carrying a BCCH (Broadcast Channel, broadcast channel) of a cell is

referred to as a BCCH carrier, and a frequency channel number of the BCCH carrier is referred to as a BCCH frequency channel number. A carrier, except a BCCH carrier, among all carriers of one cell is referred to as a non-BCCH carrier.

In the method for dual network backup in this embodiment of the present invention, a share non BCCH (SNB, Share Non BCCH) frequency function is used; when all carriers of one active cell of an active network are faulty, a standby carrier of a corresponding standby cell of a standby network takes over work of a non-BCCH carrier of the active cell, to recover some service capacities. In addition, when the active network works, a BCCH carrier of the standby cell of the standby network works, and may carry some services. In a technology using the SNB function, because the active cell of the active network and the standby cell of the standby network are in a one-to-one correspondence, and use different BCCH carriers, the active cell of the active network and the standby cell of the standby network can simultaneously work. Thus, mutual interference is prevented and a waste of frequency channel numbers is also prevented.

In addition, frequency resources may be saved by configuring a non-BCCH carrier of the standby cell as a subset of non-BCCH carriers of the active cell.

S315: Perform configuration verification to ensure that an active-standby relationship is normal.

After the active-standby cell relationship is generated and frequencies of the cells are configured, the configuration verification is performed first, to ensure that a relationship between the active network and the standby network is normal. Preferably, periodical verification may be performed. The active cell and the standby cell are checked; if a configuration error is found, a user may be prompted by using an alarm. For example, base station controllers check, by a periodical handshake, that is, sending a verification message to each other, whether a configuration of the active-standby relationship is correct and whether working statuses of the current active and standby networks are normal. The verification message includes an identifier of a cell at a receive end, an identifier of a cell at a transmit end, an active/standby type (an active cell or a standby cell) configured by the cell at the transmit end, a running status (active or standby) of the cell at the transmit end, and the like. The receive end checks, according to the identifier of the cell at the transmit end, whether a local

end has a cell that is configured in an active-standby relationship with the cell at the transmit end, and may also determine, according to comparison between the active/standby type configured for the cell at the transmit end and an active/standby type of a cell at the local end, whether the cells are configured as both active cells or are configured as both standby cells.

5 These all belong to a scope of the configuration verification. In addition, it may be further determined, according to the running status of the cell at the transmit end, whether the current networks are both in an active state or a standby state. If an error is found in the configuration by means of the verification, a configuration error alarm is reported to prompt the user. If the running status is incorrect, it is determined, according to a decision principle, that a cell at one
10 end is specified to be active, and that a cell at the other end is specified to be standby, so as to ensure a working relationship of one being active and one being standby in the network. The foregoing configuration verification may be performed on schedule after the active network and the standby network are determined.

Next, the method for dual network backup when a switchover from the active network to
15 the standby network is performed is described first.

S320: When the active network mainly undertakes work, all carriers of the active cell work, and only a BCCH carrier of the standby cell works.

This is a working status of each cell when the active network mainly undertakes the work. In the prior art, network radio parameter planning may be performed to enable a user
20 equipment to preferentially camp on the active cell, and to preferentially use a channel of the active cell when a service is initiated.

S330: Query a network availability status.

The network availability status may be queried by means of communication between the base station controllers. Preferably, a periodical query may be performed. Fault and recovery
25 situations of a cell are learned according to the network availability status, so as to execute a switchover between the active network and the standby network. Several examples are listed herein, and this embodiment of the present invention includes, but is limited to, the following situations. In this embodiment of the present invention, the switchover between the active network and the standby network refers to a switchover between working statuses of the
30 active cell of the active network and the standby cell of the standby network.

Availability statuses of all active cells and standby cells may be learned by querying the network availability status. When a BCCH carrier of a cell works normally, an A-interface is normal, and an OML is normal, it is determined that the cell is in an available state, and otherwise, it is determined that a fault occurs in the cell.

- 5 (a) If a BCCH carrier of any cell is faulty, it is considered that a fault occurs in the cell.

When the active network works, a BCCH carrier of the active cell is faulty, and the BCCH carrier of the standby cell is normal, a switchover from the active network to the standby network is performed.

- 10 (b) If a BCCH carrier of a cell is normal, but an OML link of a base station controller in which the cell is located is faulty, and a delay protection time for OML link interruption already expires, it is considered that a fault occurs in the cell.

When the active network works, the BCCH carrier of the active cell is normal, but an OML link of the active base station in which the active cell is located is faulty, and a delay protection time for OML link interruption already expires, it is considered that a fault occurs in the active cell, and a switchover from the active network to the standby network is performed.

- 15 (c) If an A-interface link is faulty, it is considered that faults occur in all cells of the base station controller.

When the active network works, if an A-interface link connecting an active base station controller and a core network is faulty, an IUR-G between the active base station controller and a standby base station controller is faulty, and communication between the active base station controller and the standby base station controller cannot be performed. Therefore, faults occur in all active cells managed by the active base station controller, and a switchover from the active network to the standby network is performed.

- 20 (d) If a base station controller is faulty, it is considered that faults occur in all cells of the base station controller.

When the active network works, if the active base station controller is faulty, the IUR-G between the active base station controller and the standby base station controller is faulty and the communication between the active base station controller and the standby base station controller cannot be performed. Therefore, faults occur in all the active cells managed by the

active base station controller, and a switchover from the active network to the standby network is performed.

When a situation of the active network meets one of the foregoing conditions (a) to (d), the standby network may be enabled to take over the work of the active network. Therefore, a reliability granularity may be refined to a cell, so as to farthest ensure that network coverage is not interrupted.

Compared with an existing backup technology at a base station level, in the prior art, a base station controller needs to interact with a base station by using an OML; when an active network is switched to a standby network, a standby base station needs to be deactivated or a carrier shutdown message needs to be delivered, and the standby base station is relied on to control a carrier module to enable a power amplifier. However, this embodiment of the present invention relies on neither the OML nor an action of the base station. Because BCCH frequencies are inconsistent, interference may not be generated when the BCCH frequencies simultaneously enable power amplifiers or send broadcast messages, and an active-standby state switchover can be implemented only by controlling carrier service access on the base station controller side. An implementation manner in this embodiment of the present invention requires operations only on the base station controller, which is more convenient.

S340: When it is determined that a fault occurs in the active cell, perform a switchover from the active network to the standby network.

When detecting that a fault occurs in the active cell, the active base station controller starts a switchover timer, switches a service of the active cell to another cell, then sends a switchover request to the standby cell, and starts a switchover waiting timer. The base station controller switches traffic, which is of the active cell in which the fault occurs, to a neighboring cell in a timing range of the switchover timer, where the neighboring cell may be an internal neighboring cell or an external neighboring cell, so as to farthest ensure that a call is not affected. The traffic switching refers to transferring of the traffic, and is different from the active-standby network switchover. After the traffic switching is completed, the active base station controller may instruct a cell at a peer end to be changed to be active, and at the same time, starts the switchover waiting timer. After being changed to be active, the cell at the peer end may return a response message to a local end. After receiving a switchover response,

the active cell stops the switchover waiting timer, and reports a switchover alarm to indicate that the switchover is successful. One handshake is completed, and all carriers of the active cell are configured to skip working. If this handshake is not completed when the switchover timer expires, it is considered that the active-standby network switchover fails, and a reported
5 switchover event alarm indicates that the switchover expires. The switchover waiting timer is mainly used to ensure that the active-standby network switchover is completed within a period of time, and a switchover result is displayed in a switchover event alarm.

After the standby cell of the standby base station controller receives the switchover request and determines that the standby cell is in an available state, the standby cell activates
10 all carriers and sets the carriers to be in a working state, reports a switchover alarm, and returns a switchover response to the active cell. When the BCCH carrier of the standby cell is normal, an operation and maintenance link OML link of a base station in which the standby cell is located is normal, an A-interface link of the standby base station controller is normal, and the standby base station controller is normal, the standby cell is in the available state.

However, for a situation in which the active base station controller is faulty, and a
15 handshake message between the active base station controller and the standby base station controller is lost, the standby cell directly sets all the carriers to be in the working state, and it is considered that the active cell does not work any more. In this way, when a fault occurs in the active cell, because the standby cell with a same coverage area is enabled, the service is
20 farthest prevented from being interrupted. Further, when a fault occurs in an independent cell, because there is no dual network backup function, a service in a coverage area of the independent cell is interrupted. Compared with a method for dual network backup at a base station controller level or at a site level in the prior art, this embodiment of the present invention may achieve network reliability at a cell level, so as to farthest ensure that the
25 service is not affected.

Next, the method for dual network backup when a switchover from the standby network to the active network is performed is further described.

S345: When the standby network mainly undertakes work, all carriers of the standby cell work, and all carriers of the active cell do not work.

30 This is a working status of each cell when the standby network mainly undertakes the

work.

S330: Query a network availability status.

The step is the same as the foregoing step S330. Availability statuses of all cells, such as active cells, standby cells, or independent cells, may be learned by querying the network availability status. When a BCCH carrier of a cell works normally, an A-interface is normal, and an OML is normal, it is determined that the cell is in an available state, and otherwise, it is determined that a fault occurs in the cell.

S350: When it is determined that the active cell is available, perform a switchover from the standby network to the active network.

When it is learned, by means of a query, that the active cell is recovered from a faulty state to an available state, a switchover from the standby network to the active network is performed by means of a handshake between the active base station controller and the standby base station controller. A process is reverse to that of S340, and content is similar. After the switchover from the standby network to the active network is performed, all the carriers of the active cell work, and only the BCCH carrier of the standby cell works.

In this embodiment of the present invention, a correspondence between an active cell and a standby cell is generated, different BCCH carriers are configured for the active cell and the standby cell, corresponding carriers of the active cell and the standby cell are configured, according to whether a current network is an active network or a standby network, to work, and a switchover between the active network and the standby network is performed according to a network availability status, so that mobile network reliability is ensured at a cell level, and a BCCH carrier of the standby cell works when the active network works, thereby giving full play to functions of resources of a standby device.

FIG. 4 is a schematic block diagram of a device 40 for dual network backup according to an embodiment of the present invention. The device 40 includes a generating unit 41, a control unit 42, and a switchover unit 43.

The generating unit 41 generates a one-to-one correspondence between an active cell and a standby cell, where coverage areas of the active cell and the standby cell are the same, the active cell is managed by an active base station that is managed by an active device, and the standby cell is managed by a standby base station that is managed by a standby device.

The control unit 42 enables, according to whether a current network is an active network or a standby network, corresponding carriers of the active cell and corresponding carriers of the standby cell to separately work.

5 The switchover unit 43 queries a network availability status, and when it is determined that the network availability status meets a designated condition, performs a switchover between the active network and the standby network.

In this embodiment of the present invention, a correspondence between an active cell and a standby cell is generated, corresponding carriers are configured, according to whether a current network is an active network or a standby network, to work, and a switchover between
10 the active network and the standby network is performed according to a network availability status, so that mobile network reliability is ensured more adequately at a cell level.

FIG. 5 is a schematic block diagram of another device 50 for dual network backup according to an embodiment of the present invention. The device 50 includes a generating unit 51, a control unit 52, a switchover unit 53, a configuring unit 54, a sending unit 55, a
15 receiving unit 56, and a recording unit 57. The generating unit 51, the control unit 52, and the switchover unit 53 of the device 50 are the same as or similar to the generating unit 41, the control unit 42, and the switchover unit 43 of the device 40, and a difference is that the device 50 further includes the configuring unit 54, the sending unit 55, the receiving unit 56, and the recording unit 57.

20 The generating unit 51 generates a one-to-one correspondence between an active cell and a standby cell, where coverage areas of the active cell and the standby cell are the same, the active cell is managed by an active base station that is managed by an active device, and the standby cell is managed by a standby base station that is managed by a standby device.

The control unit 52 enables, according to whether a current network is an active network
25 or a standby network, corresponding carriers of the active cell and corresponding carriers of the standby cell to separately work.

The switchover unit 53 queries a network availability status, and when it is determined that the network availability status meets a designated condition, performs a switchover between the active network and the standby network.

30 Optionally, as a different embodiment, the configuring unit 54 configures different

BCCH carriers for the active cell and the standby cell, where the BCCH carriers are carriers, which are used to send a broadcast channel, among cell carriers, and a carrier, except a BCCH carrier, among all carriers of one cell is a non-BCCH carrier.

Optionally, as a different embodiment, when the current network is the active network, a control unit 52 of the active device enables all carriers of the active cell to work, and a control unit 52 of the standby device enables a BCCH carrier of the standby cell to work and a non-BCCH carrier to skip working; or when the current network is the standby network, a control unit 52 of the standby device enables all carriers of the standby cell to work, and a control unit of the active device enables all carriers of the active cell to skip working. Because different BCCH carriers are configured, the BCCH carriers of the active cell and the standby cell may simultaneously work on the active network, and the standby cell may carry some services of the active network.

Optionally, as a different embodiment, when the BCCH carrier of the standby cell is normal, an operation and maintenance link OML link of the standby device of the standby cell is normal, an A-interface link of the standby device is normal, and the standby device is normal, the switchover unit 53 specifically performs a switchover from the active network to the standby network if one of the following situations is met: a BCCH carrier of the active cell is faulty; the BCCH carrier of the active cell is normal, but an OML link of the active device of the active cell is faulty, and a delay protection time for OML link interruption expires; and an A-interface link of the active device is faulty, and the active device is faulty. When one of the foregoing situations occurs, it is determined that a fault occurs in the active cell of the active network, so that an active-standby network switchover is started.

Optionally, as a different embodiment, a switchover unit 53 of the active device starts a switchover timer, and switches a service of the active cell to a neighboring cell of the active cell, a sending unit of the active device sends a switchover request to the standby device, and the switchover unit of the active device starts a switchover waiting timer; after a receiving unit of the standby device receives the switchover request, the control unit of the standby device enables all the carriers of the standby cell to work, a recording unit of the standby device records a switchover alarm, and a sending unit of the standby device sends a switchover response to the active device; after a receiving unit of the active device receives

the switchover response, the switchover unit of the active device stops the switchover waiting timer, and a recording unit of the active device records a switchover alarm. The switchover from the active network to the standby network is implemented by means of the foregoing switchover process. A switchover from the standby network to the active network is an
5 inverse process of the foregoing switchover process.

Optionally, as a different embodiment, a switchover unit 53 of the standby device performs a switchover from the standby network to the active network when the standby network works, a BCCH carrier of the active cell is normal, an OML link of the active device of the active cell is normal, and an A-interface link of the active base station controller is
10 normal.

Optionally, as a different embodiment, the configuring unit 54 configures the non-BCCH carrier of the standby cell as a subset of non-BCCH carriers of the active cell. Therefore, frequency resources may be saved.

Optionally, as a different embodiment, the active device and the standby device are
15 connected by using a same core network, or the active device and the standby device are connected by using different core networks. The active device and the standby device are connected by using the core network and various existing communications interfaces.

In this embodiment of the present invention, a correspondence between an active cell and a standby cell is generated, different BCCH carriers are configured for the active cell and the
20 standby cell, corresponding carriers of the active cell and the standby cell are configured, according to whether a current network is an active network or a standby network, to work, and a switchover between the active network and the standby network is performed according to a network availability status, so that mobile network reliability is ensured at a cell level, and a BCCH carrier of the standby cell works when the active network works, thereby giving
25 full play to functions of resources of a standby device.

FIG. 6 is a schematic block diagram of another device 60 for dual network backup according to an embodiment of the present invention. The device 60 includes a processor 61 and a memory 62.

The methods disclosed in the foregoing embodiments of the present invention may be
30 applied to the processor 61, or be implemented by a processor 141. The processor 61 may be a

type of integrated circuit chip and has a signal processing capability. In an implementation process, the steps of the foregoing methods may be accomplished by an integrated logic circuit of hardware in the processor 61 or by instructions in a software form. The foregoing processor 61 may be a general purpose processor, a digital signal processor (DSP), an application-specific integrated circuit (ASIC), a field programmable gate array (FPGA), or another programmable logical device, discrete gate or transistor logical device, or discrete hardware component, and may implement or execute the methods, steps, and logical block diagrams that are disclosed in the embodiments of the present invention. The general purpose processor may be a microprocessor or the processor may also be any conventional processor or the like. The steps of the methods disclosed with reference to the embodiments of the present invention may be directly executed and accomplished by means of a hardware decoding processor, or may be executed and accomplished by using a combination of hardware and software modules in the decoding processor. The software module may be located in a mature storage medium in the field, such as a random access memory, a flash memory, a read-only memory, a programmable read-only memory, an electrically-erasable programmable memory, or a register. The storage medium is located in the memory 62, and the processor 61 reads information in the memory 62 and accomplishes the steps in the foregoing methods in combination with the hardware of the processor 61.

The processor 61 generates a one-to-one correspondence between an active cell and a standby cell, where coverage areas of the active cell and the standby cell are the same, the active cell is managed by an active base station that is managed by an active device, and the standby cell is managed by a standby base station that is managed by a standby device; enables, according to whether a current network is an active network or a standby network, corresponding carriers of the active cell and corresponding carriers of the standby cell to separately work; and queries a network availability status, and when it is determined that the network availability status meets a designated condition, performs a switchover between the active network and the standby network.

Optionally, as a different embodiment, the processor 61 configures different BCCH carriers for the active cell and the standby cell, where the BCCH carriers are carriers, which are used to send a broadcast channel, among cell carriers, and a carrier, except a BCCH carrier,

among all carriers of one cell is a non-BCCH carrier.

Optionally, as a different embodiment, when the current network is the active network, a processor 61 of the active device enables all carriers of the active cell to work, and the standby base station controller enables a BCCH carrier of the standby cell to work and a non-BCCH carrier to skip working; or when the current network is the standby network, a processor 61 of the standby device enables all carriers of the standby cell to work, and a processor 61 of the active device enables all carriers of the active cell to skip working. Because different BCCH carriers are configured, the BCCH carriers of the active cell and the standby cell may simultaneously work on the active network, and the standby cell may carry some services of the active network.

Optionally, as a different embodiment, when the BCCH carrier of the standby cell is normal, an operation and maintenance link OML link of the standby device of the standby cell is normal, an A-interface link of the standby device is normal, and the standby device is normal, the processor 61 specifically performs a switchover from the active network to the standby network if one of the following situations is met: a BCCH carrier of the active cell is faulty; the BCCH carrier of the active cell is normal, but an OML link of the active device of the active cell is faulty, and a delay protection time for OML link interruption expires; and an A-interface link of the active device is faulty, and the active device is faulty. When one of the foregoing situations occurs, it is determined that a fault occurs in the active cell of the active network, so that an active-standby network switchover is started.

Optionally, as a different embodiment, the processor 61 of the active device starts a switchover timer, and switches a service of the active cell to a neighboring cell of the active cell; the processor 61 of the active device sends a switchover request to the standby device, and starts a switchover waiting timer; after the processor 61 of the standby device receives the switchover request, the processor 61 of the standby device enables all the carriers of the standby cell to work, a memory 62 of the standby device records a switchover alarm, and the processor 61 of the standby device sends a switchover response to the active device; after the processor 61 of the active device receives the switchover response, the processor 61 of the active device stops the switchover waiting timer, and a memory 62 of the active device records a switchover alarm. The switchover from the active network to the standby network is

implemented by means of the foregoing switchover process. A switchover from the standby network to the active network is an inverse process of the foregoing switchover process.

Optionally, as a different embodiment, the processor 61 of the standby device performs a switchover from the standby network to the active network when the standby network works, a BCCH carrier of the active cell is normal, an OML link of the active device of the active cell is normal, and an A-interface link of the active base station controller is normal.

Optionally, as a different embodiment, the processor 61 configures the non-BCCH carrier of the standby cell as a subset of non-BCCH carriers of the active cell. Therefore, frequency resources may be saved.

Optionally, as a different embodiment, the active device and the standby device are connected by using a same core network, or the active device and the standby device are connected by using different core networks. The active device and the standby device are connected by using the core network and various existing communications interfaces.

In this embodiment of the present invention, a correspondence between an active cell and a standby cell is generated by using a processor, different BCCH carriers are configured for the active cell and the standby cell, corresponding carriers of the active cell and the standby cell are configured, according to whether a current network is an active network or a standby network, to work, and a switchover between the active network and the standby network is performed according to a network availability status, so that mobile network reliability is ensured at a cell level, and a BCCH carrier of the standby cell works when the active network works, thereby giving full play to functions of resources of a standby device.

A person of ordinary skill in the art may be aware that, in combination with the examples described in the embodiments disclosed in this specification, units and algorithm steps may be implemented by electronic hardware or a combination of computer software and electronic hardware. Whether the functions are performed by hardware or software depends on particular applications and design constraint conditions of the technical solutions. A person skilled in the art may use different methods to implement the described functions for each particular application, but it should not be considered that the implementation goes beyond the scope of the present invention.

It may be clearly understood by a person skilled in the art that, for the purpose of

convenient and brief description, for a detailed working process of the foregoing system, apparatus, and unit, reference may be made to a corresponding process in the foregoing method embodiments, and details are not described herein again.

In the several embodiments provided in the present application, it should be understood
5 that the disclosed system, apparatus, and method may be implemented in other manners. For example, the described apparatus embodiment is merely exemplary. For example, the unit division is merely logical function division and may be other division in actual implementation. For example, a plurality of units or components may be combined or integrated into another system, or some features may be ignored or not performed. In addition,
10 the displayed or discussed mutual couplings or direct couplings or communication connections may be implemented through some interfaces. The indirect couplings or communication connections between the apparatuses or units may be implemented in electronic, mechanical, or other forms.

The units described as separate parts may or may not be physically separate, and parts
15 displayed as units may or may not be physical units, may be located in one position, or may be distributed on a plurality of network units. Some or all of the units may be selected according to actual needs to achieve the objectives of the solutions of the embodiments.

In addition, functional units in the embodiments of the present invention may be integrated into one processing unit, or each of the units may exist alone physically, or two or
20 more units are integrated into one unit.

When the functions are implemented in the form of a software functional unit and sold or used as an independent product, the functions may be stored in a computer-readable storage medium. Based on such an understanding, the technical solutions of the present invention essentially, or the part contributing to the prior art, or some of the technical solutions may be
25 implemented in a form of a software product. The software product is stored in a storage medium, and includes several instructions for instructing a computer device (which may be a personal computer, a server, or a network device) to perform all or some of the steps of the methods described in the embodiments of the present invention. The foregoing storage medium includes any medium that can store program code, such as a USB flash drive, a
30 removable hard disk, a read-only memory (ROM, Read-Only Memory), a random access

memory (RAM, Random Access Memory), a magnetic disk, or an optical disc.

The foregoing descriptions are merely specific implementation manners of the present invention, but are not intended to limit the protection scope of the present invention. Any variation or replacement readily figured out by a person skilled in the art within the technical
5 scope disclosed in the present invention shall fall within the protection scope of the present invention. Therefore, the protection scope of the present invention shall be subject to the protection scope of the claims.

CLAIMS

What is claimed is:

1. A method for dual network backup, comprising:

Generating a one-to-one correspondence between an active cell and a standby cell, wherein coverage areas of the active cell and the standby cell are the same, the active cell is managed by an active base station that is managed by an active base station controller, and the standby cell is managed by a standby base station that is managed by a standby base station controller;

Enabling, according to whether a current network is an active network or a standby network, corresponding carriers of the active cell and corresponding carriers of the standby cell to separately work; and

Querying a network availability status, and performing, when it is determined that the network availability status meets a designated condition, a switchover between the active network and the standby network.

2. The method according to claim 1, wherein the method further comprises:

configuring different BCCH carriers for the active cell and the standby cell, wherein the BCCH carriers are carriers, which are used to send a broadcast channel, among cell carriers, and a carrier, except a BCCH carrier, among all carriers of one cell is a non-BCCH carrier.

3. The method according to claim 2, wherein the enabling, according to whether a current network is an active network or a standby network, corresponding carriers of the active cell and corresponding carriers of the standby cell to separately work comprises:

when the current network is the active network, enabling, by the active base station controller, all carriers of the active cell to work, and enabling, by the standby base station controller, a BCCH carrier of the standby cell to work and a non-BCCH carrier to skip working; or

when the current network is the standby network, enabling, by the standby base station controller, all carriers of the standby cell to work, and enabling, by the active base station controller, all carriers of the active cell to skip working.

4. The method according to claim 3, wherein the performing, when it is determined that the network availability status meets a designated condition, a switchover between the active network and the standby network comprises:

when the BCCH carrier of the standby cell is normal, an operation and maintenance link OML link of the standby base station controller of the standby cell is normal, an A-interface link of the standby base station controller is normal, and the standby base station controller is normal, performing a switchover from the active network to the standby network if one of the following situations is met: a BCCH carrier of the active cell is faulty; the BCCH carrier of the active cell is normal, but an OML link of the active base station controller of the active cell is faulty, and a delay protection time for OML link interruption expires; and an A-interface link of the active base station controller is faulty, and the active base station controller is faulty.

5. The method according to claim 4, wherein the performing a switchover from the active network to the standby network comprises:

starting, by the active base station controller, a switchover timer, switching a service of the active cell to a neighboring cell of the active cell, sending a switchover request to the standby base station controller, and starting a switchover waiting timer;

after receiving the switchover request, enabling, by the standby base station controller, all the carriers of the standby cell to work, recording a switchover alarm, and sending a switchover response to the active base station controller; and

after receiving the switchover response, stopping, by the active base station controller, the switchover waiting timer, and recording a switchover alarm.

6. The method according to claim 3, wherein the performing, when it is determined that the network availability status meets a designated condition, a switchover between the active network and the standby network comprises:

performing a switchover from the standby network to the active network when the standby network works, a BCCH carrier of the active cell is normal, an OML link of the active base station controller of the active cell is normal, and an A-interface link of the active base station controller is normal.

7. The method according to any one of claims 2 to 6, wherein the method further

comprises: configuring the non-BCCH carrier of the standby cell as a subset of non-BCCH carriers of the active cell.

8. The method according to any one of claims 1 to 7, wherein:

the active base station controller and the standby base station controller are connected by using a same core network, or the active base station controller and the standby base station controller are connected by using different core networks.

9. A device for dual network backup, comprising a generating unit, a control unit, and a switchover unit, wherein

the generating unit is configured to generate a one-to-one correspondence between an active cell and a standby cell, wherein coverage areas of the active cell and the standby cell are the same, the active cell is managed by an active base station that is managed by an active device, and the standby cell is managed by a standby base station that is managed by a standby device;

the control unit is configured to enable, according to whether a current network is an active network or a standby network, corresponding carriers of the active cell and corresponding carriers of the standby cell to separately work; and

the switchover unit is configured to: query a network availability status; and when it is determined that the network availability status meets a designated condition, perform a switchover between the active network and the standby network.

10. The device according to claim 9, wherein the device further comprises a configuring unit, wherein

the configuring unit is configured to configure different BCCH carriers for the active cell and the standby cell, wherein the BCCH carriers are carriers, which are used to send a broadcast channel, among cell carriers, and a carrier, except a BCCH carrier, among all carriers of one cell is a non-BCCH carrier.

11. The device according to claim 10, wherein:

when the current network is the active network, a control unit of the active device enables all carriers of the active cell to work, and a control unit of the standby device enables a BCCH carrier of the standby cell to work and a non-BCCH carrier to skip working; or

when the current network is the standby network, a control unit of the standby device

enables all carriers of the standby cell to work, and a control unit of the active device enables all carriers of the active cell to skip working.

12. The device according to claim 11, wherein:

the switchover unit is specifically configured to: when the BCCH carrier of the standby cell is normal, an operation and maintenance link OML link of the standby device of the standby cell is normal, an A-interface link of the standby device is normal, and the standby device is normal, perform a switchover from the active network to the standby network if one of the following situations is met: a BCCH carrier of the active cell is faulty; the BCCH carrier of the active cell is normal, but an OML link of the active device of the active cell is faulty, and a delay protection time for OML link interruption expires; and an A-interface link of the active device is faulty, and the active device is faulty.

13. The device according to claim 12, wherein the device further comprises a sending unit, a receiving unit, and a recording unit, wherein

a switchover unit of the active device starts a switchover timer, and switches a service of the active cell to a neighboring cell of the active cell, a sending unit of the active device sends a switchover request to the standby device, and the switchover unit of the active device starts a switchover waiting timer;

after a receiving unit of the standby device receives the switchover request, the control unit of the standby device enables all the carriers of the standby cell to work, a recording unit of the standby device records a switchover alarm, and a sending unit of the standby device sends a switchover response to the active device; and

after a receiving unit of the active device receives the switchover response, the switchover unit of the active device stops the switchover waiting timer, and a recording unit of the active device records a switchover alarm.

14. The device according to claim 11, wherein:

a switchover unit of the standby device is configured to perform a switchover from the standby network to the active network when the standby network works, a BCCH carrier of the active cell is normal, an OML link of the active device of the active cell is normal, and an A-interface link of the active base station controller is normal.

15. The device according to any one of claims 10 to 14, wherein the configuring unit

configures the non-BCCH carrier of the standby cell as a subset of non-BCCH carriers of the active cell.

16. The device according to any one of claims 9 to 15, wherein:

the active device and the standby device are connected by using a same core network, or the active device and the standby device are connected by using different core networks.

17. A device for dual network backup, comprising a processor and a memory, wherein the memory stores information that the processor executes the following method; and

the processor is configured to: generate a one-to-one correspondence between an active cell and a standby cell, wherein coverage areas of the active cell and the standby cell are the same, the active cell is managed by an active base station that is managed by an active device, and the standby cell is managed by a standby base station that is managed by a standby device; enable, according to whether a current network is an active network or a standby network, corresponding carriers of the active cell and corresponding carriers of the standby cell to separately work; and query a network availability status, and when it is determined that the network availability status meets a designated condition, perform a switchover between the active network and the standby network.

18. The device according to claim 17, wherein:

the processor is further configured to configure different BCCH carriers for the active cell and the standby cell, wherein the BCCH carriers are carriers, which are used to send a broadcast channel, among cell carriers, and a carrier, except a BCCH carrier, among all carriers of one cell is a non-BCCH carrier.

19. The device according to claim 18, wherein:

when the current network is the active network, a processor of the active device enables all carriers of the active cell to work, and a processor of the standby device enables a BCCH carrier of the standby cell to work and a non-BCCH carrier to skip working; or

when the current network is the standby network, a processor of the standby device enables all carriers of the standby cell to work, and a processor of the active device enables all carriers of the active cell to skip working.

20. The device according to claim 19, wherein:

the processor is specifically configured to: when the BCCH carrier of the standby cell is

normal, an operation and maintenance link OML link of the standby device of the standby cell is normal, an A-interface link of the standby device is normal, and the standby device is normal, perform a switchover from the active network to the standby network if one of the following situations is met: a BCCH carrier of the active cell is faulty; the BCCH carrier of the active cell is normal, but an OML link of the active device of the active cell is faulty, and a delay protection time for OML link interruption expires; and an A-interface link of the active device is faulty, and the active device is faulty.

21. The device according to claim 20, wherein:

the processor of the active device starts a switchover timer, switches a service of the active cell to a neighboring cell of the active cell, sends a switchover request to the standby device, and starts a switchover waiting timer;

after the processor of the standby device receives the switchover request, the processor of the standby device enables all the carriers of the standby cell to work, a memory of the standby device records a switchover alarm, and the processor of the standby device sends a switchover response to the active device; and

after the processor of the active device receives the switchover response, the processor of the active device stops the switchover waiting timer, and a memory of the active device records a switchover alarm.

22. The device according to claim 19, wherein:

the processor of the standby device performs a switchover from the standby network to the active network when the standby network works, a BCCH carrier of the active cell is normal, an OML link of the active device of the active cell is normal, and an A-interface link of the active base station controller is normal.

23. The device according to any one of claims 18 to 22, wherein the processor configures the non-BCCH carrier of the standby cell as a subset of non-BCCH carriers of the active cell.

24. The device according to any one of claims 17 to 23, wherein:

the active device and the standby device are connected by using a same core network, or the active device and the standby device are connected by using different core networks.

25. A wireless communications system, comprising a base station and the device for dual network backup according to any one of claims 9 to 24.