

Electronic security device

This invention relates to an electronic security device for use, for example, as a door lock.

Various forms of electronic security device are already known, in which a suitably coded key is recognised by an electronic circuit to permit operation of a door bolt. When such a device is used, in a situation where it is desirable regularly to change the code to which the electronic circuit will respond, it becomes necessary to ensure that the circuit and the key currently in use have the same code. This can be achieved by connecting all the electronic circuits to a common control centre, but this is clearly disadvantageous when it is desired to convert the locks of an existing system to electronic locks.

To overcome this problem several solutions have been suggested. One such suggestion is to store in the circuit a fixed sequence of codes and to use each new key to call up the next code of the sequence.

Another suggestion (US-4,207,555) utilizes keys each of which has two codes on it, namely the code currently in use and the next code to be used. This next code is stored in the electronic circuit until a new key is used when it is replaced by a « new » next code.

None of these previously suggested systems provides the ideal solution to the problem. At any given time the « next » code is already established and this casts some doubt on the security of the system.

Another previously suggested system (US-3,761,683) makes use of a changeable data track on the key which is changed to a new code and corresponding data stored in a memory, identified by a fixed code on the key, each time a key is validly used. Such a system is not suitable for use in, for example, a hotel door lock system wherein the only means of communication between a central computer and the lock itself is to be the keys.

Furthermore none of the previously known systems referred to above is suitable for use in, for example, a system of locks for an apartment block in which each key is required to operate a specific apartment door, but also one or more communal door locks.

Accordingly, the invention provides an electronic security device including a memory device for storing a combination code, a key reading device for reading from a key device data representing a combination code and an electronic circuit connected to said memory device and to said key reading device and serving to produce an output for releasing a security device when the combination code from the key reading device matches that in the memory device, said electronic circuit also producing said output if the combination code from the key reading device matches a new combination code, characterised in that the key reading device also reads from the key device calculation data and the electronic circuit includes means for calculating said new combination code based upon the combination code stored in the memory device and the calculation data read from the key device.

For a hotel lock system it is preferred that said electronic circuit further includes means for changing the combination code stored in the memory to said new combination, when said new combination code from the key reading device matches the calculated new combination code.

The invention is particularly (but not exclusively) applicable to hotel door lock systems and it will readily be appreciated that in such an arrangement it gives many advantages over previously proposed systems. In particular each new combination code can be randomly selected — the appropriate calculation data being worked out at the central key issuing station. Each key contains no information relating to previous or future combination codes and this makes it extremely difficult for a would-be thief to analyse the system and forge a key.

For an apartment door lock system, the key device contains combination data appropriate to one specific apartment door lock and each key device contains different calculation data which, when used by the electronic circuit of a communal door lock in combination with the stored combination data in the memory of that lock, provides a « new » combination code matching the key combination code. In this case the communal door lock memory content is not changed following recognition of the « new » combination code.

An example of the invention will now be described with the aid of the accompanying drawings in which :

Figure 1 is a diagrammatic representation of one example of an electronic security device in accordance with the invention and,

Figure 2 is a circuit diagram of an electronic circuit forming a part of the electronic security device shown in Figure 1.

Referring firstly to Figure 1, the electronic security device includes a security device 10 which, in the present example, is in the form of a door lock, having a knob or handle 11 used for withdrawing a bolt 12. The lock includes a clutch whereby the knob or handle 11 is mechanically coupled to the bolt 12 and this clutch is electromagnetically actuated, one electromagnet being impulse energised to unlock the door, i. e. to engage the clutch, and another electromagnet being impulse energised to lock the door, i. e. to disengage the clutch.

The electronic security device also includes a memory 13, a key card reader 14 for reading data from a key card 15 and a logic circuit 16 which controls the lock 10 in accordance with the data read from the card 15 and the data stored in the memory 13.

The key card reader 14 includes a 6×4 array of infrared light emitting diodes and a corresponding

6 x 4 array of infra-red sensing devices arranged so that the sensing devices sense radiation from corresponding respective ones of the emitting diodes, when the latter are energised. Holes punched in the card 15, when inserted in the reader 14, permit radiation from some of the emitting diodes to fall on the corresponding sensing devices in known manner so that a 24-bit parallel binary output is provided, suitable amplifiers being provided in the reader 14 if necessary.

A switch 17 operated by a key card fully inserted into the reader 14 connects the emitting diodes to a power supply, so that the diodes are energised when the switch 17 is operated. The switch 17 also controls the charging of a capacitor 18 via a resistor 19 from the power supply and the eventual discharge of this capacitor 18 into the « lock » input of the lock 10, when the key card 14 is removed from the reader 15.

The logic circuit 16 has an output which controls a transistor switch 20 controlling the discharge of another capacitor 21 into the « unlock » input of the lock 10. A resistor 22 provides a permanent charging path for the capacitor 21.

Turning now to Figure 2 the logic circuit 16 and the memory 13 are shown in more detail therein. The memory 13 consists of a 12-bit latch circuit with its data inputs connected to twelve of the outputs of the reader 14. The logic circuit consists quite simply of two 12-bit digital comparator circuits 24, 25, each having one set of data inputs connected to the same twelve outputs of the reader 14. Comparator 24 has its other data inputs connected to the outputs of the memory 13 and comparator 25 has its other data inputs connected to the outputs of twelve exclusive OR gates 26. Each gate 26 has one input from the memory output another input from an associated one of the other twelve outputs of the reader. The A = B output of comparator 24 provides the « unlock » output of the logic circuit, and the A = B output of comparator 25 is connected to the « CLOCK » input of memory 13.

It will be appreciated that if the twelve output signals of the first twelve outputs the card reader exactly match the twelve bits of data stored in the memory 13, the comparator 13 will produce an « unlock » output causing transistor 20 to turn on so that capacitor 21 discharges into the « unlock » electromagnet. If these outputs match the outputs of gates 26, on the other hand, the output from comparator 25 will clock the memory 13, so that the twelve bit code outputted at the first twelve outputs of the reader will be written into the memory and hold. The output of comparator 24 will then go high to energise the « unlock » electromagnet.

It will be seen that, in the above described embodiment the twelve bit code from the first mentioned twelve outputs of the read represents a « combination code » which has to match that stored in the memory to ensure opening of the door. The twelve bit code from the other twelve outputs of the reader represent a « calculation code » identifying the nature of a mathematical or logical calculation which has to be performed on the existing stored « combination code » to arrive at a new « combination code ». The specific calculation in the present case is the inversion of those bits of the 12-bit memory content which coincide with 1 bits of « calculation data ».

E. G. if the 12, bit word in the memory is :

0011 1101 0101 1011

the lock will open to a key card with this combination code, or to any other key with compatible combination code and calculation data, for example keys with the following codes,

Combination	Calculation
-------------	-------------

0010 0100 1001 1110 0001 1001 1100 0101	
0100 0000 1110 1010 0111 1101 1011 0001	

When electronic security devices are used, for example in a hotel door locking system, each new guest can be given a new key card for his room. A central computer keeps in store a listing of the combination codes currently in use for the rooms and, when a new combination code is required, the computer generates calculation data randomly, operates with this data on the existing combination code drawn from the computer store and either prints out a code to be punched in the new key card, or operates an automatic punch to produce the key card.

The example of the invention described above is a relatively simple one making use of readily available integrated logic circuits. Much higher levels of complexity and sophistication can be obtained if the electronic circuit makes use of a microprocessor instead of logic circuits. With such an arrangement, for example, different levels of keying could be employed, that is to say the key card could also include data identifying the keying level to which that particular key has access. Several different combination codes could be stored and accessed by cards identifying the different levels.

For example the key card could have an array of 10 x 5 hole positions with one column of holes acting to provide strobe pulses to the microprocessor to enable the data represented by the other 4 columns to be read into the microprocessor RAM as the card is inserted. With this arrangement only five emitting diodes and five sensing elements are required. The remaining 10 x 4 array contains 4 bits of « level » data, 24 bits (in 4 bit words) of combination code data and 12 bits (in 4 bit words) of calculation code data. The various « level » data provide different modes of operation of the lock at different keying levels. There may

for example be six levels, each having a corresponding combination code stored in the RAM. Further modes involve different levels of « lock-out » option — i. e. the hotel guest key card may identify a mode of operation in which only his card will open the door, access to the other combination codes being blocked thereby.

- 5 In this example the 12 bits of calculation data are divided up into 6 bit pairs each pair giving calculation data for a corresponding 4-bit word of the combination data. The bit pair identifies one bit of the 4-bit word and that bit is inverted when the calculation is carried out.

For example, if the combination code stored in the appropriate level of the memory is

10 0100 0100 0000 0111 1011 0100

the new key card may have the following combination code

15 0110 1100 0100 1111 1001 0101

coupled with the calculation data

01 11 10 11 01 00.

- 20 This results in the second LSB of the first word, the fourth LSB (or MSB) of the second word, the third LSB of the third word, the fourth LSB of the fourth word, the second LSB of the fifth word and the LSB of the sixth word of the stored combination code being inverted to arrive at the new combination code.

The microprocessor based version of the invention may also be adapted for use in apartment blocks, where it is required to allow the use of a single key by each tenant for opening his own apartment door, for opening his own corridor door (in common with other tenants having apartments opening onto that corridor) and for opening the external door of the block (in common with all tenants of the block). To this end the corridor doors and the external doors have a modification which prevents updating of the memory when a « new code » is recognised. The apartment doors respond to the combination code on each key, but the external door lock has a combination code allocated which is linked to all the combination codes of the other locks such that the calculation data on each key and the combination data stored in the common locks give rise to the combination code of the key in use. In the case of the corridor doors, part of the key combination code is compared with that stored in the lock and the other part with the « new combination code » generated as before from the lock combination code and the key calculation data. The first mentioned part of the combination code for each flat on a corridor is identical.

Claims

1. An electronic security device including a memory device (13) for storing a combination code, a key reading device (14) for reading from a key device (15) data representing a combination code and an electronic circuit (16) connected to said memory device (13) and to said key reading device (14) and serving to produce an output for releasing a security device when the combination code from the key reading device (14) matches that in the memory device (13), said electronic circuit (16) also producing said output if the combination code from the key reading device (14) matches a new combination code, characterised in that the key reading device (14) also reads from the key device (15) calculation data and the electronic circuit (16) includes means (26) for calculating said new combination code based upon the combination code stored in the memory device (13) and the calculation data read from the key device (15).

2. An electronic security device as claimed in claim 1 in which said electronic circuit further includes means for changing the combination code stored in the memory to said new combination, when said new combination code from the key reading device matches the calculated new combination code.

3. A electronic security device as claimed in claim 1 wherein said key device (15) further includes keying level instruction data identifying one of a plurality of keying levels, said memory means (13) includes means for storing a plurality of stored combination codes respectively relating to different ones of said keying level instruction data, for selecting one of said plurality of stored combination codes.

4. An electronic security device as claimed in claim 3 wherein said key device (15) includes at least one « lock-out » keying level instruction data, and said circuit means includes means, responsive to said « lock-out » keying level instruction data, for preventing production of said output upon subsequent receipt of other keying level instruction data.

5. A method of operating an electronic security system which includes a key device (15) with a combination code data, and a lock having a memory device (13), a key reading device (14) and an electronic circuit (16) connected to said key reading device and the memory, the method comprising : (a) storing a combination code in said memory device (13) ; (b) reading said key combination code into said electronic circuit (c) comparing the key combination code with the stored combination code ; (d) producing an output for releasing the lock when said key combination code and said stored combination code match ; (e) comparing the key combination code with a « new » combination code derived by said

for example be six levels, each having a corresponding combination code stored in the RAM. Further modes involve different levels of « lock-out » option — i. e. the hotel guest key card may identify a mode of operation in which only his card will open the door, access to the other combination codes being blocked thereby.

- 5 In this example the 12 bits of calculation data are divided up into 6 bit pairs each pair giving calculation data for a corresponding 4-bit word of the combination data. The bit pair identifies one bit of the 4-bit word and that bit is inverted when the calculation is carried out.

For example, if the combination code stored in the appropriate level of the memory is

10 0100 0100 0000 0111 1011 0100

the new key card may have the following combination code

15 0110 1100 0100 1111 1001 0101

coupled with the calculation data

01 11 10 11 01 00.

- 20 This results in the second LSB of the first word, the fourth LSB (or MSB) of the second word, the third LSB of the third word, the fourth LSB of the fourth word, the second LSB of the fifth word and the LSB of the sixth word of the stored combination code being inverted to arrive at the new combination code.

- The microprocessor based version of the invention may also be adapted for use in apartment blocks, where it is required to allow the use of a single key by each tenant for opening his own apartment door, for opening his own corridor door (in common with other tenants having apartments opening onto that corridor) and for opening the external door of the block (in common with all tenants of the block). To this end the corridor doors and the external doors have a modification which prevents updating of the memory when a « new code » is recognised. The apartment doors respond to the combination code on each key, but the external door lock has a combination code allocated which is linked to all the combination codes of the other locks such that the calculation data on each key and the combination data stored in the common locks give rise to the combination code of the key in use. In the case of the corridor doors, part of the key combination code is compared with that stored in the lock and the other part with the « new combination code » generated as before from the lock combination code and the key calculation data. The first mentioned part of the combination code for each flat on a corridor is identical.

35

Claims

- 40 1. An electronic security device including a memory device (13) for storing a combination code, a key reading device (14) for reading from a key device (15) data representing a combination code and an electronic circuit (16) connected to said memory device (13) and to said key reading device (14) and serving to produce an output for releasing a security device when the combination code from the key reading device (14) matches that in the memory device (13), said electronic circuit (16) also producing said output if the combination code from the key reading device (14) matches a new combination code, characterised in that the key reading device (14) also reads from the key device (15) calculation data and the electronic circuit (16) includes means (26) for calculating said new combination code based upon the combination code stored in the memory device (13) and the calculation data read from the key device (15).
- 50 2. An electronic security device as claimed in claim 1 in which said electronic circuit further includes means for changing the combination code stored in the memory to said new combination, when said new combination code from the key reading device matches the calculated new combination code.
3. A electronic security device as claimed in claim 1 wherein said key device (15) further includes keying level instruction data identifying one of a plurality of keying levels, said memory means (13) includes means for storing a plurality of stored combination codes respectively relating to different ones of said keying level instruction data, for selecting one of said plurality of stored combination codes.
- 55 4. An electronic security device as claimed in claim 3 wherein said key device (15) includes at least one « lock-out » keying level instruction data, and said circuit means includes means, responsive to said « lock-out » keying level instruction data, for preventing production of said output upon subsequent receipt of other keying level instruction data.
5. A method of operating an electronic security system which includes a key device (15) with a combination code data, and a lock having a memory device (13), a key reading device (14) and an electronic circuit (16) connected to said key reading device and the memory, the method comprising : (a) storing a combination code in said memory device (13) ; (b) reading said key combination code into said electronic circuit (c) comparing the key combination code with the stored combination code ; (d) producing an output for releasing the lock when said key combination code and said stored combination code match ; (e) comparing the key combination code with a « new » combination code derived by said
- 65



electronic circuit and (f) producing said releasing output when said key combination code and said « new » combination code match ; characterised in that the « new » combination code is calculated by the electronic circuit by applying to the stored combination code a calculation algorithm defined by calculation data which is read from the key device.

5 6. A method of operating an electronic security system as claimed in claim 5, further comprising the step of changing the stored combination code to the « new » combination code when the key combination code matches the « new » combination code.

7. A method of operating an electronic security system as claimed in claim 5, wherein said key device (15) includes keying level instruction data, said storing step includes storing in said memory (13) a plurality of stored combination codes respectively relating to different ones of said keying levels, and said reading step includes selecting one of said plurality of stored combination codes in accordance with said keying level instruction data read from the key device.

8. A method of operating an electronic security system as claimed in claim 7, wherein said keying level instruction data includes at least one « lock-out » data and said reading step further includes preventing production of said releasing output on subsequent receipt of other keying level instruction data when said « lock-out » data has been read.

Ansprüche

20

1. Elektronische Sicherheitsvorrichtung mit einer Speichervorrichtung (13) zum Speichern eines Kombinationscodes, einer Schlüssellesevorrichtung (14) zum Lesen von einem Kombinationscode repräsentierenden Daten von einer Schlüssellesevorrichtung (15) und mit einer elektronischen Schaltung (16), die mit der Speichervorrichtung (13) und der Schlüssellesevorrichtung (14) verbunden ist und die zur Erzeugung eines Ausgangssignals zur Auslösung bzw. Freigabe einer Sicherheitsvorrichtung dient, wenn der Kombinationscode der Schlüssellesevorrichtung (14) mit dem in der Speichervorrichtung (13) übereinstimmt, wobei die elektronische Schaltung (16) das Ausgangssignal auch dann abgibt, wenn der Kombinationscode der Schlüssellesevorrichtung (14) mit einem neuen Kombinationscode übereinstimmt, dadurch gekennzeichnet, daß die Schlüssellesevorrichtung (14) von der Schlüssellesevorrichtung (15) Berechnungsdaten liest und daß die elektronische Schaltung (16) eine Einrichtung (26) zur Berechnung des neuen Kombinationscodes aufweist, basierend auf dem Kombinationscode, der in der Speichervorrichtung (13) gespeichert ist, und auf dem Berechnungsdaten, die von der Schlüssellesevorrichtung (15) gelesen werden.

2. Elektronische Sicherheitsvorrichtung nach Anspruch 1, dadurch gekennzeichnet, daß die elektronische Schaltung außerdem eine Einrichtung zur Änderung des im Speicher gespeicherten Kombinationscodes in die neue Kombination aufweist, wenn der neue Kombinationscode von der Schlüssellesevorrichtung mit dem berechneten neuen Kombinationscode übereinstimmt.

3. Elektronische Sicherheitsvorrichtung nach Anspruch 1, dadurch gekennzeichnet, daß die Schlüssellesevorrichtung (15) außerdem Schlüssel-Kodierungs-Niveau-Befehlsdaten (keying level instruction data) aufweist zur Identifizierung oder Kennzeichnung eines von einer Vielzahl von Schlüsselkodierungsniveaus, wobei die Speichereinrichtung (13) eine Einrichtung zur Speicherung einer Vielzahl von gespeicherten Kombinationscodes aufweist, die jeweils verschiedenen der Schlüsselkodierungsniveau-Befehlsdaten zugeordnet sind, um eine der Vielzahl der gespeicherten Kombinationscodes auszuwählen.

4. Elektronische Sicherheitsvorrichtung nach Anspruch 3, dadurch gekennzeichnet, daß die Schlüssellesevorrichtung (15) mindestens einen « Aussperr »-Schlüssel-Kodierungsniveau-Befehlsdatenwert aufweist und daß die Schaltungseinrichtung eine auf den « Aussperr »-Schlüssel-Kodierungsniveau-Befehlsdatenwert ansprechende Einrichtung aufweist, um die Erzeugung des Ausgangssignals zu verhindern, wenn darauffolgend die anderen Schlüssel-Kodierungsniveau-Befehlsdaten erhalten werden.

5. Verfahren für den Betrieb eines elektronischen Sicherheitssystems, umfassend eine Schlüssellesevorrichtung (15) mit einem Kombinationscodedatenwert, und mit einem eine Speichervorrichtung (13) aufweisenden Schloß, mit einer Schlüssellesevorrichtung (14) und einer elektronischen Schaltung (16), die mit der Schlüssellesevorrichtung und dem Speicher verbunden ist, wobei das Verfahren aufweist : (a) Speicher eines Kombinationscodes in der Speichervorrichtung (13) ; (b) Lesen des Schlüsselkombinationscodes in der elektronischen Schaltung ; (c) Vergleichen des Schlüsselkombinationscodes mit dem gespeicherten Kombinationscode ; (d) Erzeugung eines Ausgangssignales zur Freigabe des Schlosses, wenn der Schlüsselkombinationscode und der gespeicherte Kombinationscode übereinstimmen ; (e) Vergleichen des Schlüsselkombinationscodes mit einem « neuen » Kombinationscode, abgeleitet durch die elektronische Schaltung und (f) Erzeugung des Freigabeausgangssignals, wenn der Schlüsselkombinationscode und der « neue Kombinationscode » übereinstimmen, dadurch gekennzeichnet, daß der « neue » Kombinationscode durch die elektronische Schaltung berechnet wird durch Anwendung eines Berechnungsalgorithmus auf den gespeicherten Kombinationscode, definiert durch den Berechnungsdatenwert, der von der Schlüssellesevorrichtung abgelesen wird.

6. Verfahren zum Betrieb eines elektronischen Sicherheitssystems nach Anspruch 5, dadurch gekennzeichnet, daß der gespeicherte Kombinationscode in den « neuen » Kombinationscode geändert wird, wenn der Schlüsselkombinationscode mit dem « neuen » Kombinationscode übereinstimmt.



7. Verfahren zum Betrieb eines elektronischen Sicherheitssystems nach Anspruch 5, dadurch gekennzeichnet, daß die Schlüsselvorrichtung (15) Schlüssel-Kodierungsniveau-Befehlsdaten aufweist, daß der Speicherschnitt das Speichern einer Vielzahl von gespeicherten Kombinationscode im Speicher (13) einschließt, die jeweils unterschiedlichen Kodierungsniveaus der Schlüssel-Kodierungsniveaus entsprechen und daß der Leseschnitt die Auswahl einer der Vielzahl der gespeicherten Kombinationscodes in Übereinstimmung mit dem Schlüssel-Kodierungsniveau-Befehlsdatenwert einschließt, der von der Schlüsselvorrichtung abgelesen wird.

8. Verfahren zum Betrieb eines elektronischen Sicherheitssystems nach Anspruch 7, dadurch gekennzeichnet, daß der Schlüssel-Kodierungsniveau-Befehlsdatenwert mindestens einen « Aussperr »-Datenwert umfaßt und daß der Leseschnitt mit einschließt die Veränderung der Erzeugung des Freigabeausgangssignals bei nachfolgendem Erhalten von anderen Schlüssel-Kodierungsniveau-Befehlsdatenwerten, wenn der « Aussperr »-Datenwert aus- bzw. abgelesen wurde.

15 Revendications

1. Dispositif de sûreté électronique comportant un dispositif de mémorisation (13) destiné à emmagasiner un code à combinaison, un dispositif (14) de lecture de clé qui lit sur un dispositif servant de clé (15) une donnée représentant un code à combinaison, et un circuit électronique (16) connecté audit dispositif de mémorisation (13) et audit dispositif (14) de lecture de clé et servant à produire un signal de sortie permettant de libérer un dispositif de sûreté lorsque le code à combinaison émanant du dispositif (14) de lecture de clé est accordé avec celui se trouvant dans le dispositif de mémorisation (13), ledit circuit électronique (16) produisant également ledit signal de sortie si le code à combinaison émanant du dispositif (14) de lecture de clé est accordé avec un nouveau code à combinaison, caractérisé en ce que le dispositif (14) de lecture de clé lit également sur le dispositif servant de clé (15) une donnée de calcul et le circuit électronique (16) comporte un moyen (26) permettant de calculer ledit nouveau code à combinaison à partir du code à combinaison emmagasiné dans le dispositif de mémorisation (13) et de la donnée de calcul lue sur le dispositif servant de clé (15).

2. Dispositif de sûreté électronique selon la revendication 1, dans lequel ledit circuit électronique comporte en outre un moyen permettant de changer le code à combinaison emmagasiné dans la mémoire en ledit nouveau code à combinaison, lorsque ledit nouveau code à combinaison émanant du dispositif de lecture de clé est accordé avec le nouveau code à combinaison calculé.

3. Dispositif de sûreté électronique selon la revendication 1, où ledit dispositif servant de clé (15) comporte également une donnée d'instruction de niveau de codage qui identifie un parmi plusieurs niveaux de codage, ledit moyen de mémorisation (13) comporte un moyen permettant d'emmagasiner plusieurs codes à combinaison emmagasinés respectivement en relation avec certaines, différentes, desdites données d'instruction de niveau de codage, en vue de la sélection de l'un desdits plusieurs codes à combinaison emmagasinés.

4. Dispositif de sûreté électronique selon la revendication 3, où ledit dispositif servant de clé (15) comporte au moins une donnée d'instruction de niveau de codage de « fermeture », et ledit moyen de circuit comporte un moyen répondant à ladite donnée d'instruction de niveau de codage de « fermeture » en empêchant la production dudit signal de sortie lors de la réception ultérieure d'une autre donnée d'instruction de niveau de codage.

5. Procédé permettant de faire fonctionner un système de sûreté électronique qui comporte un dispositif servant de clé (15) portant une donnée de code à combinaison, et une serrure possédant un dispositif de mémorisation (13), un dispositif (14) de lecture de clé et un circuit électronique (16) connecté audit dispositif de lecture de clé et à la mémoire, le procédé comprenant les opérations suivantes : (a) emmagasiner un code à combinaison dans ledit dispositif de mémorisation (13) ; (b) lire ledit code à combinaison de la clé et le fournir audit circuit électronique ; (c) comparer le code à combinaison de la clé avec le code à combinaison emmagasiné ; (d) produire un signal de sortie permettant de débloquent la serrure lorsque ledit code à combinaison de la clé et ledit code à combinaison emmagasiné concordent ; (e) comparer le code à combinaison de la clé avec un « nouveau » code à combinaison produit par ledit circuit électronique ; et (f) produire ledit signal de sortie de déblocage lorsque ledit code à combinaison de la clé et ledit « nouveau » code à combinaison concordent ; caractérisé en ce que le « nouveau » code à combinaison est calculé dans le circuit électronique par application au code à combinaison emmagasiné d'un algorithme de calcul défini par la donnée de calcul qui est lue dans le dispositif servant de clé.

6. Procédé permettant de faire fonctionner un système de sûreté électronique selon la revendication 5, comprenant en outre l'opération consistant à changer le code à combinaison emmagasiné en le « nouveau » code à combinaison lorsque le code à combinaison de la clé concorde avec le « nouveau » code à combinaison.

7. Procédé permettant de faire fonctionner un système de sûreté électronique selon la revendication 5, où ledit dispositif servant de clé (15) comporte une donnée d'instruction de niveau de codage, ladite opération d'emmagasinage comportant l'emmagasinage dans ladite mémoire (13) de plusieurs codes à combinaison emmagasinés se rapportant respectivement à plusieurs, différents, desdits niveaux de



codage, et ladite opération de lecture comportant la sélection de l'un desdits plusieurs codes à combinaison emmagasinés en fonction de ladite donnée d'instruction de niveau de codage lue sur le dispositif servant de clé.

8. Procédé permettant de faire fonctionner un système de sûreté électronique selon la revendication 5
- 7, où ladite donnée d'instruction de niveau de codage comporte au moins une donnée de « fermeture » et ladite opération de lecture comporte en outre le fait d'empêcher la production dudit signal de sortie de déblocage lors de la réception ultérieure d'une autre donnée d'instruction de niveau de codage lorsque ladite donnée de « fermeture » a été lue.

10

15

20

25

30

35

40

45

50

55

60

65

