

METHOD FOR MANUFACTURING A SNACK, A SNACK,
AND FOOD LIKE A SNACK

FIELD OF THE INVENTION

5 The present invention relates to a method for producing a snack (a easy-to-pick food made chiefly of potato or grain), and also to a snack and food like a snack.

BACKGROUND TECHNOLOGY

10 According to a survey of the snack market shares in Japan by material type, products made of potato stood first in the list according for about 58% of the market, products made of corn was the second with about 30%, and products made of wheat came in third with about 9%. In other words, products made of
15 those three materials occupy the majority of the market. Despite the fact that wheat is consumed in the largest quantities in the world, there are very few kinds of snacks made of wheat flour, so that "Kappa Ebisen" (registered trademark) and "Baby Star Ramen" (registered trademark)
20 jointly occupy about 56% of the market of snacks made of wheat.

 In the market environment as described above, sales proceeds of snacks are levelling off, and even though products from new materials other than the above-mentioned three major
25 materials were developed, they have not yet found a firm place

in the market.

On the other hand, in anticipation of aging society spreading on a world scale in the future, people's health-consciousness is becoming increasingly strong in years
5 to come, and as a result, products made with health in mind will be looked for as snacks. Having large amounts of oil content, potato chips are not regarded as good for health. In contrast, the practice of eating bread has been established in many countries in the world and bread may be given a better image
10 of being good for health by using rye or whole wheat flour, or kneading dough mixed with vegetable.

As foods for teatime made of bread as the material, only rusks or applied products of rusks are known. Rusks have long been eaten as pastries and are well established in the market.
15 A method for producing rusks comprises a bread slicing process, a seasoning process, and a drying process. For example, rusks are produced by cutting bread into thin and small slices, and spreading powdered sugar mixed with egg white on the surfaces of the slices, and baking again. The texture of rusks you feel
20 is close to that of biscuits.

Rusks as snacks in sizes easy to pick by hand are available in the market, but the texture you feel is close to biscuits, not the light texture you get from eating potato chips.

A technology closest to the method of the present invention

is described in JP-A-5-227890. The method described in this Patent Gazette comprises mixing one or not less than two kinds of materials selected from wheat flour, corn flour and potato powder with water, transforming the mixture into a viscous α -starch dough, rolling a lump of dough into a sheet dough, pressing cake dies into the sheet of dough to obtain small plates, and then drying the small plates and pressing each plate between convex and concave dies, which are engaged to thereby form a small molded chip. This small chip is further dried and then heated to expand. The above-mentioned Japanese Patent Gazette states that by this method, it is possible to produce cubic snacks in the form of chips, which were hitherto considered difficult to produce.

Meanwhile, as the method for producing foods for teatime made from bread, there is not any other conventional method than the above-mentioned method for producing rusks.

An object of the present invention is to obtain snacks similar in texture of potato chips when they are made from materials other than potato, bread for example.

Another object of the present invention is to provide foods for teatime made from bread as material, other than rusks and applied products of rusks.

DISCLOSURE OF THE INVENTION

To achieve the above objects, the present invention provides a method for producing a snack, which includes a process of heating under pressure, wherein a material comprising bread is placed between a pair of pressurizing
5 surfaces and heated under pressure.

According to this method, by the above-mentioned process of heating under pressure, it is possible to provide a processed product (unseasoned snack) in a plate-shaped body with faces corresponding to the pressurizing surfaces, which has a
10 moisture content less than that of the material. In the above-mentioned process of heating under pressure, by pressuring a material with a moisture content of 20~40 mass% until the thickness thereof is reduced to, for example, not less than 15% and not more than 70% of the original thickness of the
15 material and not less than 1.0mm and not more than 5.0mm, a processed product with a moisture content of not less than 1.0 mass% and not more than 5.9 mass%, for example, can be obtained. The texture of this processed product is close to that of potato chips.

20 The present invention provides a method of producing a snack (first method) comprising a process of heating under pressure, wherein a material comprising bread is placed between a pair of pressurizing surfaces and is heated while a pressure is applied until the moisture content is reduced to a predetermined

value smaller than the original moisture content of the material (not less than 6.0 mass% and below the moisture content of the material, for example). After the process of heating under pressure, the method further comprises a subsequent drying
5 process without applying pressure.

The present invention provides a method of producing a snack (second method) comprising a pressurized heating, wherein a material comprising bread is placed between a pair of pressurizing surfaces and heated while a pressure is applied
10 until the moisture content of the material is reduced to a predetermined value smaller than the original moisture content of the material (not more than 5.9 mass% for example).

In the first and second methods according to the present invention, the pressurization by the pressurizing surfaces does
15 not include rolling by a pair of rollers. In other words, the process of heating under pressure in the first and second methods of the present invention corresponds to a so-called press molding, wherein both pressurizing surfaces come into contact with the full surfaces of the material at the same time.

20 In the first and second method of the present invention, for the pressurizing surfaces, flat or curved surfaces may be used.

A processed product made by using flat surfaces for the pressurizing surfaces and according to the first method is

formed with at least outer edges curled.

A processed product made by using flat surfaces for the pressurizing surfaces and according to the second method is formed in a substantially flat plate shape.

5 A processed product made by using curved surfaces for the pressurizing surfaces and according to the first method is formed to follow the shape of those curved surfaces with curled outer edges. Especially when surfaces curved in a bow shape (bow-shaped surfaces) are used for the pressurized surfaces,
10 a product is in a shape curled such that open-end portions of circular-arc of the bow shape come close together, and a processed product in a stick shape is sometimes obtained if the curling occurs to an excessive degree.

A product made by using curved pressurizing surfaces and
15 according to the second method is formed in a shape that substantially follows the shape of the curved pressurizing surfaces.

The present invention provides a method for producing a snack (third method) comprising rolling out a material
20 comprising bread (compressing the material by passing through a pair of rollers, and subsequently heating the rolled material until the moisture content thereof is reduced to a predetermined value (5.9 mass% for example) smaller than the original value of the material.

According to the third method of the present invention,
by rolling out bread not less than 5mm in thickness between
rollers with a roller gap of not more than 2.0mm (preferably
not more than 1.0mm), the bread is formed in a shape such that
5 at least the outer edges are curled, and a subsequent heating
process reduces the moisture content to a predetermined value
smaller than the original moisture content of the material.

As a result, according to the third method of the present
invention, a processed product (unseasoned snack) is obtained
10 in such a shape that at least the outer edges are curled and
with a moisture content smaller than that of the material. By
rolling out a material with a moisture content of 15~40 mass%,
for example, to a thickness not less than 5% and not more than
30% of the thickness of the material and not less than 1.0mm
15 and not more than 5.0mm, and by carrying out subsequent heating,
a processed product is obtained with a moisture content of not
less than 1.0 mass% and not more than 5.9 mass%. The texture
of this processed product is close to potato chips.

According to the third method of the present invention,
20 a slice cut out of bread not less than 5mm in thickness with
a moisture content of not less than 20.0 mass% is rolled with
a roller gap of not more than 1mm and then heated until the
moisture content is reduced to not more than 5.0 mass%, by which
a processed product is obtained with a texture close to potato

chips.

According to the third method of the present invention, a slice of butter roll cut out to a thickness of not less than 10mm and with a moisture content of 15.0 mass% is rolled out
5 with a roller gap of not more than 1mm, and then heated until the moisture content decreases to not more than 5.0 mass%, with the result that a processed product is obtained with a texture close to potato chips.

According to the first to third methods of the present
10 invention, by using a material comprising bread, it is possible to obtain a "snack made from bread - with a texture close to potato chips." Unlike with potato chips, this snack need not be fried in oil, and therefore matches the health-conscious trend of the times.

15 Among materials used in the methods of the present invention, there are (1) bread without brown-baked crust, (2) brown-baked crusted bread, and (3) crushed bread crumbs. More detailed descriptions of the shape of (1) and (2) above are (4) a sliced bread not less than 1mm (not more than 50mm) in thickness with
20 the brown-baked crust removed and (5) a sliced bread not less than 1mm (not more than 50mm) in thickness with the crust remaining along the outer edges. A more detailed description of the shape of (3) is (6) crumbs made by crushing the brown-baked crust of bread.

The kinds of bread used as material in the present invention include bread, French bread, rolls of bread, nan bread, sweet bun, and any other kinds of bread classified as "bread".

The present invention also provides snacks and food like
5 a snack produced by the methods of the present invention. Note that the above-mentioned foods like snack are foods not classified in foods for teatime (nonessential grocery foods other than meals) and which are manufactured with a texture and a shape suitable as snacks.

10 The methods of the present invention may be applied by using "materials with a moisture (content of not less than 10 mass%, for example)" other than bread. As the "materials with a moisture (content of not less than 10 mass%, for example)", there are foods, similar to bread, which are processed by baking,
15 steaming or the like to a state that products contain air bubbles, and which are made from grains, such as rice, barley, wheat, oat, foxtail millet, barnyard grass, millet, and corn.

BRIEF DESCRIPTION OF THE DRAWINGS

20 Figs. 1A to 1E are diagrams for process-by-process explanation of methods of the first and the fifth embodiments of the present invention;

Fig. 2 is a perspective view showing a shape of a snack obtained by the method of the first embodiment of the present

invention;

Figs. 3A to 3C are diagrams for process-by-process explanation of methods of the second and the sixth embodiments of the present invention;

5 Fig. 4 is a perspective view showing a shape of a snack obtained by the method of the second embodiment of the present invention;

Figs. 5A to 5D are diagrams for process-by-process explanation of methods of the third and the seventh embodiments
10 of the present invention;

Fig. 6 is a perspective view showing a shape of a snack obtained by the method of the third embodiment of the present invention;

Figs. 7A to 7C are diagrams for process-by-process
15 explanation of methods of the fourth and the eighth embodiments of the present invention;

Fig. 8 is a perspective view showing a shape of a snack obtained by the method of the fourth embodiment of the present invention;

20 Fig. 9 is a perspective view showing a shape of a snack obtained by the method of the fifth embodiment of the present invention;

Fig. 10 is a perspective view showing a shape of a snack obtained by the method of the sixth embodiment of the present

invention;

Fig. 11 is a perspective view showing a shape of a snack obtained by the method of the seventh embodiment of the present invention;

5 Fig. 12 is a perspective view showing a shape of a snack obtained by the method of the eighth embodiment of the present invention;

Figs. 13A to 13E are diagrams for process-by-process explanation of the method of the ninth embodiment of the present
10 invention;

Fig. 14 is a perspective view showing a shape of a snack obtained by the method of the ninth embodiment of the present invention;

Figs. 15A to 15C are diagrams for process-by-process
15 explanation of the method of the tenth embodiment of the present invention;

Fig. 16 is a perspective view showing a shape of a snack obtained by the method of the tenth embodiment of the present invention;

20 Figs. 17A to 17D are diagrams for process-by-process explanation of the method of the eleventh embodiment of the present invention;

Fig. 18 is a perspective view showing a shape of a snack obtained by the method of the eleventh embodiment of the present

invention;

Figs. 19A to 19C are diagrams for process-by-process explanation of the method of the twelfth embodiment of the present invention;

5 Fig. 20 is a perspective view showing a shape of a snack obtained by the method of the twelfth embodiment of the present invention;

Figs. 21A and 21B are diagrams for process-by-process explanation of methods of the thirteenth and the fourteenth
10 embodiments of the present invention;

Fig. 22 is a perspective view showing a shape of a snack obtained by the method of the thirteenth embodiment of the present invention; and

Fig. 23 is a perspective view showing a shape of a snack
15 obtained by the method of the fourteenth embodiment of the present invention.

BEST MODE FOR CARRYING OUT THE INVENTION

(First Embodiment)

20 A method for producing a snack according to a first embodiment of the present invention will be described with reference to Figs. 1A to 1E and 2. In this method, a slice cut out of bread with the brown-baked crust removed and in a thickness of not less than 1mm is used as material and placed

between a pair of flat pressurizing surfaces, and heated while a pressure is applied until the moisture content of the material decreases to a predetermined value less than the original moisture content of the material (a value not lower than 6.0 mass% and below the original moisture content of the material, for example), and after the heating, the material is dried without applying pressure. (By additionally carrying out this drying process, a processed product with the curled outer edges is obtained).

First, from bread available on the market (with a moisture content of about 35 mass%, for example), the whole of the brown-baked crust is removed with a slicer. Then, by further cutting this bread with the slicer, a white (crustless) sliced bread with a size of 50mm X 30mm X 10mm (thickness) is obtained.

Next, as shown in Fig. 1A, this bread 1 is heated under pressure in a press device 2. In this pressure unit 2, a pair of flat pressurizing surfaces are composed by an upper surface 21a of a lower part 21 made of steel and a lower surface 22a of an upper part 22 made of steel. The bread 1 is put on the upper surface 21a of the lower part 21 of the press device 2.

Under this condition, as shown in Fig. 1B, the upper part 2 is lowered to press the bread 1 until the gap between the pair of pressurizing surfaces 21a and 22a becomes a predetermined gap t . The gap t is to be set suitably as one thinks fit

according to the thickness of the bread 1 as material and the thickness of a processed product to produce. Under this condition, the bread is heated and pressurized simultaneously by holding it at a predetermined temperature and under a
5 predetermined pressure for a predetermined length of time until the moisture content reaches about 30 mass%, for example.

After the elapse of a predetermined time, as shown in Fig. 1C, the upper part 22 is raised and the pressure is released. Under this condition, though the bread 1 has been pressed into
10 a flat plate shape, because the moisture content is still high, as time passes, the bread changes from a flat shape to a shape that has a slightly curved portion as shown in Fig. 1D.

Then, as shown in Fig. 1E, the bread 1 is extracted and placed in a hot air dryer 3 and held at a predetermined
15 temperature for a predetermined time so as to be dried by hot air until the moisture content of the bread 1 decreases to 5.9 mass% or lower, for example. Therefore, a processed product in a shape that the outer edges are curled is obtained as shown in Fig. 2, for example. Further, by applying seasoning or the
20 like to the processed product, a snack is completed.

Incidentally, the processed product shown in Fig. 2 was obtained as follows. From bread ("Honjikomi" (Brand name) by Fujipan Co., Japan) with a moisture content of 36.3 mass% and an oil content of 2.5 mass%, the whole crust was removed and

a slice was cut out of the bread with a slicer in a size of 50mm
× 30mm × 10mm (thickness), and the slice was used as material.
And the above-mentioned gap t was set at 2mm, conditions of
heating under pressure were 60°C temperature, 4.9×10^{-1} MPa
5 pressure and 90sec holding time, and a drying condition was 90°C
for 30min.

The moisture content of the bread just after the heating
was 29.1 mass%, the thickness of the bread just after the heating
was 1.7mm, the moisture content of the bread (processed product)
10 after the drying was 4.5 mass%, and the thickness of the bread
(processed product) after the drying was 1.7mm. The texture
of the processed product was similar to that of potato chips.
(Second Embodiment)

A method for producing a snack according to a second
15 embodiment of the present invention will be described with
reference to Figs. 3A to 3C and 4. In this method, a slice cut
out of bread as material with the brown-baked crust removed and
in a thickness of not less than 1mm is placed between a pair
of flat pressurizing surfaces and heated under pressure until
20 the moisture content decreases to a predetermined value (not
more than 5.9 mass% for example) less than the original moisture
content of the material.

To begin with, from bread available on the market (bread
with a moisture content of about 35 mass%, for example), the

whole brown-baked crust is removed with a slicer. Then, by cutting the bread with the slicer, a white (crustless) sliced bread with a size of 50mm × 30mm × 10mm (thickness) is obtained.

Then, as shown in Fig. 3A, the bread 1 is heated under
5 pressure by the press device 2. In the press device 2, a pair of flat pressurizing surfaces is composed by the upper surface 21a of the steel-made lower part 21 and the lower surface 22a of the steel-made upper part 22. The bread 1 is placed on the upper surface 21a of the lower part 21 of the press device 2.

10 Under this condition, as shown in Fig. 3B, the upper part 22 is lowered to press the bread 1 until the distance between the pair of pressurizing surfaces 21a and 22a reaches a predetermined gap t . This gap t is to be set suitably at one's discretion according to the thickness of bread 1 as material
15 and the thickness of a processed product to produce. Under this condition, the material is heated and pressurized simultaneously by holding it at a predetermined temperature and a predetermined pressure for a predetermined time until the moisture content decreases to about 5 mass%, for example.

20 After the elapse of a predetermined time, as shown in Fig. 3C, the upper part 22 is raised and the pressurization is stopped. Under this condition, the bread 1 is flattened out into a substantially flat plate shape. Therefore, a processed product in a substantially flat shape is obtained as shown in

Fig. 4, for example. By applying seasoning or the like to this processed product, a snack is completed.

Meanwhile, a processed product shown in Fig. 4 was obtained as follows. From bread ("Honjikomi" (Brand name) by Fujipan Co., Japan) with a moisture content of 36.3 mass% and an oil content of 2.5 mass%, the whole crust was removed and a slice was cut out of the bread with a slicer in a size of 50mm × 30mm × 10mm (thickness), and the slice was used as material. And the above-mentioned gap t was set at 2mm, and conditions of heating under pressure were 130°C temperature, 4.9×10^{-1} MPa pressure and 120sec holding time.

The moisture content of the processed product was 4.8 mass% and the thickness was 1.3mm. The texture of the processed product was similar to potato chips.

15 (Third Embodiment)

A method for producing a snack according to a third embodiment of the present invention will be described with reference to Figs. 5A to 5D and 6. In this method, a slice cut out of bread with the brown-baked crust removed and in a thickness of not less than 1mm is used as material and placed between a pair of curved pressurizing surfaces, and heated under pressure until the moisture content decreases to a predetermined value less than the original moisture content of the material (a value not less than 6.0 mass% and below the

original moisture content of the material, and after the heating, the material is dried without applying pressure (further, a processed product with the curled outer edges is obtained by the above-mentioned drying process).

5 First, from bread available on the market (bread with a moisture content of about 35 mass% for example), the whole brown-baked crust is removed with a slicer. Then, the bread is cut with the slicer to obtain a white (crustless) slice of a size of 50mm × 30mm × 10mm (thickness).

10 Then, as shown in Fig. 5A, the bread 1 is heated under pressure in the press device 2. In this press device 2, bow-shaped concave surfaces 21b are formed at predetermined intervals on the upper surface of a lower part 21 made of steel, and convex surfaces 22b, which correspond to the concave
15 surfaces 21b, are formed on the lower surface of an upper part 22 made of steel. A concave surface 21b and a convex surface 22b compose a pair of pressurizing surfaces curved in a bow shape. The bread 1 is placed on the concave surface 21b of the lower part 21 of the press device 2.

20 Under this condition, as shown in Fig. 5B, the upper part 22 is lowered until the distance between the pair of the concave surface 21b and the convex surface 22b reaches the predetermined gap t to press the bread 1. This gap t is to be set suitably at one's discretion according to the thickness of the bread 1

as material and the thickness of a processed product to produce. Under this condition, the material is heated and pressurized simultaneously by holding it at a predetermined temperature and a predetermined pressure for a predetermined time until the
5 moisture content decreases to about 30 mass% for example.

After the elapse of a predetermined time, as shown in Fig. 5C, the upper part 22 is raised and the pressurization is stopped. Under this condition, the bread 1 is in a bow-shaped plate that has a concave surface 11, which corresponds to the concave
10 surface 21b as one pressurizing surface, and a convex surface 12, which corresponds to the convex surface 22b as the other pressurizing surface. Having a still high moisture content, this bread 1 is in a shape that the concave surface 12 and the convex surface 11 partially deviate from the circular-arc of
15 the bow shape.

Then, as shown in Fig. 5D, the bread 1 is extracted and put in a hot air dryer 3, and held at a predetermined temperature for a predetermined time to be dried by hot air in such a way that the moisture content of the bread 1 decreases to not higher
20 than 5.9 mass%, for example. Thus, a processed product is obtained in a shape curled such that open-end portions of the circular-arc of the bow shape came close together. In some case where the curling occurs to an excessive degree, a stick-shaped processed product may be obtained as shown in Fig. 6. By

applying seasoning or the like to the processed product, a snack can be completed.

Incidentally, the processed product shown in Fig. 6 was obtained as follows. From bread ("Honjikomi" (Brand name) by Fujipan Co., with a moisture content of 36.3 mass% and an oil content of 2.5 mass%, the whole crust was removed and a slice was cut out of the bread with a slicer in a size of 50mm × 30mm × 10mm (thickness), and the slice was used as material. And the above-mentioned gap t was set at 2mm and conditions of heating under pressure were 60°C temperature, 4.9×10^{-1} MPa pressure, and 90 sec holding time, and a drying condition was 90°C for 30min.

The moisture content of the bread just after the pressurized heating is 28.0 mass%, the thickness of the bread just after the pressurized heating was 1.9mm, the moisture content of the bread (processed product) after drying was 4.5 mass% and the thickness of the bread (processed product) was 1.8mm. The texture of the processed product) was similar to that of potato chips.

Processed products in a stick form such as shown in Fig. 6 has an advantage that they can be put in upright position in a container, so that they can be densely packed in a container and are easy to pick up when eating.

(Fourth Embodiment)

A method for producing a snack according to a fourth embodiment of the present invention will be described with reference to Figs. 7A to 7C and 8. This method comprises a pressurized heating, wherein a slice cut out of bread as
5 material with the brown-baked crust removed and in a thickness of not less than 1mm is placed between a pair of pressurizing surfaces curved in a bow shape and heated under pressure until the moisture content of the material decreases to a predetermined value (not more than 5.9 mass% for example) less
10 than the original moisture content of the material.

First, from bread on the market (bread with a moisture content of about 35 mass% for example), the whole brown-baked crust is removed with a slicer. By cutting the bread with the slicer, a white (crustless) slice is obtained in a size of 50mm
15 × 30mm × 10mm (thickness), for example.

Next, as shown in Fig. 7A, this bread 1 is heated under pressure in the press device 2. In this press device 2, bow-shaped concave surfaces 21b are formed at predetermined intervals on the upper surface of a lower part 21 of steel, and
20 convex surfaces 22b, which correspond to the concave surfaces 21b, are formed on the lower surface of an upper part 22 of steel. A concave surface 21b and a convex surface 22b compose a pair of pressurizing surfaces curved in a bow shape. The bread 1 is placed on the concave surface 21b of the lower part 21 of

the press device 2.

Under this condition, as shown in Fig. 7B, the upper part 22 is lowered until the distance between the pair of the concave surface 21b and the convex surface 22b reaches the predetermined gap t to press the bread 1. This gap t is to be set suitably at one's discretion according to the thickness of the bread 1 as material and the thickness of a processed product to produce. Under this condition, the material is heated and pressurized simultaneously by holding it at a predetermined temperature and a predetermined pressure for a predetermined time until the moisture content decreases to about 5 mass%, for example.

After the elapse of a predetermined time, as shown in Fig. 7C, the upper part 2 is raised and the pressurization is stopped. Under this condition, the bread 1 is in a bow-shaped plate that has a concave surface 11, which correspond to the concave surface 21b as one pressurizing surface and a convex surface 12, which corresponds to the convex surface 22b as the other pressurizing surface. As a result, as shown in Fig. 8, for example, a processed product in a shape which the short-sides of a rectangular are curved in a circular-arc can be obtained. By applying seasoning or the like to this processed product, a snack is completed.

Meanwhile, a processed product shown in Fig. 8 was obtained as follows. From bread ("Honjikomi" (Brand name) by Fujipan

Co., Japan) with a moisture content of 36.3 mass% and an oil content of 2.5 mass%, the whole crust was removed and a slice was cut out of the bread with a slicer in a size of 50mm × 30mm × 10mm (thickness), and the slice was used as material. And
5 the above-mentioned gap t was set at 2mm, and conditions of heating under pressure were 130°C temperature, 4.9×10^{-1} MPa pressure and 120sec holding time.

The moisture content of the processed product was 4.5 mass% and the thickness was 1.0mm. The texture of the processed
10 product was similar to potato chips.

Processed products such as shown in Fig. 8 has an advantage that because they can be piled one on top of another in a container, they can be densely stacked in a container and are easy to pick up when eating.

15 (Fifth Embodiment)

A method for producing a snack according to a fifth embodiment of the present invention will be described with reference to Figs. 1A to 1E and 9. In this method, heating, wherein a slice with a thickness of not less than 1mm cut out
20 of bread with brown-baked crust is used as material and placed between a pair of flat pressurizing surfaces, and heated while pressure is applied until the moisture content of the material decreases to a predetermined value less than the original moisture content of the material (a value not less than 6.0 mass%

and below the original moisture content of the material, for example), and after the heating, the material is dried without applying pressure (by additionally performing the above-mentioned drying process, a processed product with the
5 curled outer edges is obtained).

First, by cutting French bread available on the market (bread with a moisture content of about 26 mass%, for example) with a slicer, a crusted slice of bread substantially elliptic in cross section with a 80mm major axis and a 40mm minor axis
10 in a thickness of about 7mm is obtained.

Then, as shown in Fig. 1A, the bread 1 is heated under pressure in the press device 2. In this press 2, a pair of flat pressurizing surfaces is composed by the upper surface 21a of a steel-made lower part 21 and the lower surface 22a of a
15 steel-made upper part 22. The bread 1 is placed on the upper surface 21a of the lower part 21 of the press device 2.

Under this condition, as shown in Fig. 1B, the upper part 22 is lowered until the distance between the pair of pressurizing surfaces 21a and 22a comes to a predetermined gap
20 t to press the bread 1. This gap t is to be set suitably at one's discretion according to the thickness of the bread 1 as material and the thickness of a processed product to produce. Under this condition, the bread is heated and pressurized simultaneously by holding it at a predetermined temperature and

a predetermined pressure for a predetermined time until the moisture content becomes about 25 mass%, for example.

After the elapse of a predetermined time, as shown in Fig. 1C, the upper part 22 is raised and the pressurization is stopped.

5 Under this condition, the bread 1 has been pressed and is in a flat plate shape, but because the bread 1 still has a high moisture content, as time passes, the bread will change from a flat shape to a shape that has a slightly curved portion as shown in Fig. 1D.

10 Next, as shown in Fig. 1E, the bread 1 is taken out and placed in a hot air dryer 3 and held at a predetermined temperature for a predetermined time so as to be dried by hot air until the moisture content of the bread 1 decreases to 5.9 mass% or lower, for example. By this process, a processed
15 product is obtained which is curved along the major axis of the elliptic shape with the outer edges curled as shown in Fig. 9, for example. Further, by applying seasoning or the like to the processed product, a snack is completed.

Incidentally, the processed product shown in Fig. 9 was
20 obtained as follows. From French bread ("Parisian" (Brand name) by Yamazaki Baking Co., Japan) with a crust-portion moisture content of 21.0 mass%, a crustless-portion moisture content of 26.0 mass% and an oil content of 0.9 mass%, a slice was cut out with a slicer in a thickness of 7mm. And the slice

was used as material, and the above-mentioned gap t was set at 2mm, and conditions of heating under pressure were 60 °C temperature, 4.9×10^{-1} MPa pressure and 40sec holding time, and a drying condition was 90°C for 30min.

5 The moisture content of the bread just after the heating was 25.1 mass%, the thickness of the bread just after the heating was 1.6mm, the moisture content of the bread (processed product) after the drying was 1.7 mass%, and the thickness of the bread (processed product) after the drying was 1.6mm. The texture
10 of the processed product was similar to that of potato chips.

Because crusted bread was used as material to obtain the processed product by the above method, this processed product is more savory than those produced from crustless bread. Another advantage of this processed product is that because
15 there is the crust along the outer edges of this processed product, the quantity of the processed product breaking during production of the processed product and during transportation of the merchandise is reduced.

(Sixth Embodiment)

20 A method for producing a snack according to a sixth embodiment of the present invention will be described with reference to Figs. 3A to 3C and 10. In this method, a slice with a thickness of not less than 1mm cut out of bread with brown-baked crust is used as material, and placed between a pair

of flat pressurizing surfaces, and heated while pressure is applied until the moisture content of the material decreases to a predetermined value (not more than 5.9 mass%, for example) less than the original moisture content of the material.

5 By cutting French bread available on the market (bread with a moisture content of 26 mass%, for example) with a slicer, a crusted bread is obtained with a thickness of about 7mm in a substantially elliptic cross section with a 80mm major axis and a 40mm minor axis.

10 Then, as shown in Fig. 3A, the bread 1 is heated under pressure in the press device 2. In the press device 2, a pair of flat pressurizing surfaces is composed by the upper surface 21a of the steel-made lower part 21 and the lower surface 22a of the steel-made upper part 22. The bread 1 is placed on the
15 upper surface 21a of the lower part 21 of the press device 2.

Under this condition, as shown in Fig. 3B, the upper part 22 is lowered until the distance between the pair of pressurizing surfaces 21a and 22a reaches a predetermined gap t to press the bread 1. This gap t is to be set suitably at
20 one's discretion according to the thickness of bread 1 as material and the thickness of a processed product to produce. Under this condition, the bread is heated and pressurized simultaneously by holding it at a predetermined temperature and a predetermined pressure for a predetermined time until the

moisture content decreases to about 5 mass%, for example.

After the elapse of a predetermined time, as shown in Fig. 3C, the upper part 22 is raised and the pressurization is stopped. Under this condition, the bread 1 is pressed out into a flat plate shape. Therefore, a processed product in a substantially flat shape is obtained as shown in Fig. 10, for example. By applying seasoning or the like to this processed product, a snack is completed.

Incidentally, the processed product shown in Fig. 10 was obtained as follows. From French bread ("Parisian" (Brand name) by Yamazaki Baking Co., Japan) with a crust-portion moisture content of 21.0 mass%, a crustless-portion moisture content of 26.0 mass% and an oil content of 0.9 mass%, a slice was cut out with a slicer in a thickness of 7mm and used as material. And the above-mentioned gap t was set at 2mm and conditions of heating under pressure were 140°C temperature, 4.9×10^{-1} MPa pressure and 120 sec holding time.

The moisture content of the processed product was 1.7 mass%, and the thickness was 1.3mm. The texture of the processed product was similar to that of potato chips.

Because crusted bread was used as material to obtain the processed product by the above method, this processed product is more savory than those produced from crustless bread. Another advantage of this processed product is that because this

processed product has the crusty outer edges, the quantity of the processed product breaking during production of the processed product and during transportation of the merchandise is reduced.

5 (Seventh Embodiment)

A method for producing a snack according to a seventh embodiment of the present invention will be described with reference to Figs. 5A to 5D and 11. In this method, a slice with a thickness of not less than 1mm cut out of bread with
10 brown-baked crust is used as material and placed between a pair of pressurizing surfaces curved in a bow shape, and heated while pressure is applied until the moisture content of the material decreases to a predetermined value less than the original moisture content of the material (a value not less than 6.0 mass%
15 and below the original moisture content of the material), and after the heating, the material is dried without applying pressure (by additionally performing the above-mentioned drying process, a processed product with the curled outer edges is obtained.)

20 First, by cutting French bread available on the market (bread with a moisture content of 26 mass%, for example) with a slicer, crusted bread is obtained with a thickness of about 7mm and in a substantially elliptic section with a 80mm major axis and a 40mm minor axis, for example.

Then, as shown in Fig. 5A, the bread 1 is heated under pressure in the press device 2. In this press device 2, bow-shaped concave surfaces 21b are formed at predetermined intervals on the upper surface of a lower part 21 made of steel, and convex surfaces 22b, which correspond to the concave surfaces 21b, are formed on the lower surface of an upper part 22 made of steel. A concave surface 21b and a convex surface 22b compose a pair of curved pressurizing surfaces. The bread 1 is placed on the concave surface 21b of the lower part 21 of the press device 2.

Under this condition, as shown in Fig. 5B, the upper part 22 is lowered until the distance between the pair of the concave surface 21b and the convex surface 22b reaches a predetermined gap t to press the bread 1. This gap t is to be set suitably at one's discretion according to the thickness of the bread 1 as material and the thickness of a processed product to produce. Under this condition, the material is heated and pressurized simultaneously by holding it at a predetermined temperature and a predetermined pressure for a predetermined time until the moisture content decreases to about 25 mass%, for example.

After the elapse of a predetermined time, as shown in Fig. 5C, the upper part 22 is raised and the pressurization is stopped. Under this condition, the bread 1 is in a bow-shaped plate having a concave surface 11, which corresponds to the concave surface

21b as one pressurizing surface and a convex surface 12, which corresponds to the convex surface 22b as the other pressurizing surface. Having a still high moisture content, this bread 1 is in such a shape that the concave surface 12 and the convex surface 11 partially deviate from the circular-arc of the bow shape.

Then, as shown in Fig. 5D, the bread 1 is taken out and put in a hot air dryer 3, and held at a predetermined temperature for a predetermined time to be dried by hot air such that the moisture content of the bread 1 decreases to not higher than 5.9 mass%, for example. As a result, a processed product is obtained in a shape curled such that open-end portions of the circular-arc of the bow shape came close together. In some case where the curling occurs to an excessive degree, a processed product as shown in Fig. 11 may be obtained. By applying seasoning or the like to the processed product, a snack can be completed.

Incidentally, the processed product shown in Fig. 11 was obtained as follows. From French bread ("Parisian" (Brand name) by Yamazaki Baking Co., Japan) with a crust-portion moisture content of 21.0 mass%, a crustless-portion moisture content of 26.0 mass% and an oil content of 0.9 mass%, a slice was cut out with a slicer in a thickness of 7mm. And the slice was used as material, and the above-mentioned gap t was set at

2mm, and conditions of heating under pressure were 60 °C temperature, 4.9×10^{-1} MPa pressure and 90sec holding time, and a drying condition was 90°C for 30min.

The moisture content of the bread just after the pressurized heating was 24.8 mass%, the thickness of the bread just after the heating was 1.6mm, the moisture content of the bread (processed product) after the drying was 1.7 mass%, and the thickness of the bread (processed product) after the drying was 1.6mm. The texture of the processed product was similar to that of potato chips.

Because crusted bread was used as material to obtain the processed product by the above method, this processed product is more savory than those produced from crustless bread. Another advantage of this processed product is that because this processed product has the crusty outer edges, the quantity of the processed product breaking during production of the processed product and during transportation of the merchandise is reduced.

(Eighth Embodiment)

A method for producing a snack according to an eighth embodiment of the present invention will be described with reference to Figs. 7A to 7C and 12. In this method, a slice with a thickness of not less than 1mm cut out of bread with brown-baked crust is used as material and placed between a pair

of pressurizing surfaces curved in a bow shape, and heated while pressure is applied until the moisture content of the material decreases to a predetermined value (not more than 5.9 mass%, for example) less than the original moisture content of the material.

First, by cutting French bread on the market (bread with a moisture content of 26 mass%, for example) by a slicer, a crusted slice is obtained with a thickness of about 7mm in a substantially elliptic shape with a 80mm major axis and a 40mm minor axis, for example.

Next, as shown in Fig. 7A, the bread 1 is heated under pressure in the press device 2. In this press device 2, bow-shaped concave surfaces 21b are formed at predetermined intervals on the upper surface of a lower part 21 of steel, and convex surfaces 22b, which correspond to the concave surfaces 21b, are formed on the lower surface of an upper part 22 of steel. A concave surface 21b and a convex surface 22b compose a pair of curved pressurizing surfaces. The bread 1 is placed on the concave surface 21b of the lower part 21 of the press device 2.

Under this condition, as shown in Fig. 7B, the upper part 22 is lowered until the distance between the pair of pressurizing surfaces 21b and 22b reaches a predetermined gap t to thereby flatten the bread 1. This gap t is to be set

suitably at one's discretion according to the thickness of bread 1 as material and the thickness of a processed product to produce. Under this condition, the material is heated and pressurized simultaneously by holding it at a predetermined temperature and
5 a predetermined pressure for a predetermined time until the moisture content decreases to about 5 mass%, for example.

After the elapse of a predetermined time, as shown in Fig. 7C, the upper part 22 is raised and the pressurization is stopped. Under this condition, the bread 1 is a bow-shaped plate having
10 a concave surface 11, which corresponds to the concave surface 21b as one pressurizing surface, and a convex surface 12, which corresponds to the convex surface 22b as the other pressurizing surface. Thus, a processed product is obtained with the minor-axis portion curved in a circular arc as shown in Fig.
15 12, for example. By applying seasoning or the like to this processed product, a snack is completed.

Incidentally, the processed product shown in Fig. 12 was obtained as follows. From French bread ("Parisian" (Brand name) by Yamazaki Baking Co., Japan) with a crust-portion
20 moisture content of 21.0 mass%, a crustless-portion moisture content of 26.0 mass% and an oil content of 0.9 mass%, a slice was cut out with a slicer in a thickness of 7mm. And the slice was used as material, and a processed product was obtained by drying the material with the above-mentioned gap t was set at

2mm, and conditions of heating under pressure were 130°C temperature, 4.9×10^{-1} MPa pressure and 120sec holding time.

The moisture content of the processed product heating was 1.7 mass%, and the thickness was 1.8mm. The texture of the
5 processed product was similar to that of potato chips.

Because crusted bread is used as material to obtain processed product by the above method, this processed product is more savory than those produced from crustless bread. Another advantage of this processed product is that because this
10 processed product has the crusty outer edges, the quantity of the processed product breaking during production of the processed product and during transportation of the merchandise is reduced.

Processed products such as shown in Fig. 12 have an
15 advantage that because they can be piled one on top of another in a container, they can be packed densely in a container and are easy to pick up when eating.

(Ninth Embodiment)

A method for producing a snack according to a ninth
20 embodiment of the present invention will be described with reference to Figs. 13A to 13E and 14. In this method, crumbs made by crushing the brown-baked crust of bread are used as material, and the material is placed between a pair of flat pressurizing surfaces and heated while pressure is applied

until the moisture content decreases to a predetermined value less than the original moisture content of the material (a value not less than 6.0 mass% and below the original moisture content of the material, for example), and after the heating, the material is dried without applying pressure (by additionally performing the drying process, a processed product with the curled outer edges is obtained.)

First, by crushing the crust of bread, which is available on the market, with a grinding mill to a particle diameter of about 2 to 5 mm for example, a large number of granules are obtained. If the moisture content of the granules is below 10 mass%, the granules are added with water to adjust the moisture content so as to be 10 mass% or higher, and then the granules are used as material. If the moisture content of the granules is 10 mass% or higher, the granules in this condition are used as material.

Then, as shown in Fig. 13A, a material 10 composed of granules as mentioned above is heated under pressure by the press device 2. In the press device 2, a pair of flat pressurizing surfaces is composed by the upper surface 21a of the steel-made lower part 21 and the lower surface 22a of the steel-made upper part 22. A predetermined amount of material 10 composed of granules mentioned above is placed on the upper surface 21a of the lower part 21 of the press device 2.

Under this condition, as shown in Fig. 13B, the upper part 22 is lowered until the distance between the pair of pressurizing surfaces 21a and 22a reaches a predetermined gap t to press the material 10 composed of granules. This gap t is to be set suitably at one's discretion according to the particle size and the quantity of granules and the thickness of a processed product to produce. Under this condition, the material is heated and pressurized simultaneously by holding it at a predetermined temperature and a predetermined pressure for a predetermined time until the moisture content of the material 10 decreases to an appropriate value (not less than 6 mass%, for example).

After the elapse of a predetermined time, as shown in Fig. 13C, the upper part 22 is raised and the pressurization is stopped. Under this condition, the material is a substantially elliptic plate object 10A, which is a joined body of a large number of granules and in a flat plate shape. However, still having a high moisture content, as time passes, the plate 10A changes from a flat plate shape to a shape that has a slightly curved portion as shown in Fig. 13D.

Next, as shown in 13(e), the plate object 10A is extracted and placed in a hot air dryer 3, and heated by hot air by holding it at a predetermined temperature for a predetermined time until the moisture content of the plate object 10A decreases to not

more than 5.9 mass%, for example. As a result, a processed product is obtained in an elliptic plate shape that the outer edges are curled as shown in Fig. 14, for example. By applying seasoning or the like to the processed product, a snack is
5 completed.

Meanwhile, a processed product shown in Fig. 14 was obtained as follows. From bread ("Honjikomi" (Brand name) by Fujipan Co., Japan) with a crust-portion moisture content of 29.1 mass% and an oil content of 2.5 mass%, the crust was crushed to a
10 particle diameter of 2~5mm and used in this condition as material, and the above-mentioned gap t was set at 2mm, and conditions of heating under pressure were 60°C temperature, 4.9×10^{-1} MPa pressure and 90sec holding time, and a drying condition was 90°C temperature for 30min.

15 The moisture content of the plate object just after the heating was 26.8 mass% and the thickness of the plate object just after the heating was 1.8mm, and the moisture content of plate object (processed product) after the drying was 4.7 mass% and the thickness of the plate object (processed product) after
20 the drying was 1.7mm. The texture of the processed product was similar to potato chips.

The processed product obtained by this method has an advantage that because the crushed crust is used as material, the crust, which is thrown away in most cases, can be used

effectively.

(Tenth Embodiment)

A method for producing a snack according to a tenth embodiment of the present invention will be described with reference to Figs. 15A to 15C and 16. In this method, crumbs made by crushing the brown-baked crust of bread is used as material, and placed between a pair of fine pressurizing surfaces and heated while pressure is applied until the moisture content decreases to a predetermined value (not more than 5.9 mass%, for example).

First, by crushing the crust of bread, which is available on the market, with a grinding mill to a particle diameter of about 2 to 5 mm, a large number of granules are obtained. If the moisture content of the granules is below 10 mass%, the granules are added with water to adjust the moisture content so as to be 10 mass% or higher, and then the granules are used as material. If the moisture content is 10 mass% or higher, the granules in this condition are used as material.

Then, as shown in Fig. 15A, a material 10 composed of granules as mentioned above is heated under pressure in the press device 2. In the press device 2, a pair of flat pressurizing surfaces is composed by the upper surface 21a of the steel-made lower part 21 and the lower surface 22a of the steel-made upper part 22. A predetermined amount of material

10 composed of granules mentioned above is placed on the upper surface 21a of the lower part 21 of the press device 2.

Under this condition, as shown in Fig. 15B, the upper part 22 is lowered until the distance between the pair of pressurizing surfaces 21a and 22a reaches a predetermined gap t to press the material 10 composed of granules. This gap t is to be set suitably at one's discretion according to the particle size and the quantity of granules and the thickness of a processed product to produce. Under this condition, the material is heated and pressurized simultaneously by holding it at a predetermined temperature and a predetermined pressure for a predetermined time until the moisture content of the material 10 decreases to an appropriate value (not less than 6 mass%, for example).

After the elapse of a predetermined time, as shown in Fig. 15C, the upper part 22 is raised and the pressurization is stopped. Under this condition, the material is a joined body of a large number of granules and is in the form of a substantially elliptic plate object 10A. As a result, a processed product in a substantially elliptic and flat plate shape can be obtained as shown in Fig. 16, for example. By applying seasoning or the like to the processed object, a snack is completed.

Meanwhile, a processed product shown in Fig. 16 was obtained

as follows. From bread ("Honjikomi" (Brand name) by Fujipan Co., Japan) with a crust-portion moisture content of 29.1 mass% and an oil content of 2.5 mass%, the crust was crushed to a particle diameter of 2~5mm. And the particles were used in this condition as material, and the above-mentioned gap t was set at 2mm, and conditions of heating under pressure were 140°C temperature, 4.9×10^{-1} MPa pressure and 120sec holding time.

The moisture content of the processed product was 5.5 mass% and the thickness was 1.3mm. The texture of the processed product was similar to potato chips.

The processed product obtained by this method has an advantage that because the crushed crust is used as material, the crust which is thrown away in most cases, can be used effectively.

15 (Eleventh Embodiment)

A method for producing a snack according to an eleventh embodiment of the present invention will be described with reference to Figs. 17A to 17D and 18. In this method, crumbs made by crushing the brown-baked crust of bread are used as material, and the material is placed between a pair of pressurizing surfaces curved in a bow shape and heated while pressure is applied until the moisture content decreases to a predetermined value less than the original moisture content of the material (a value not less than 6.0 mass% and below the

original moisture content of the material, for example), and after the heating, the material is dried without applying pressure (by additionally performing the above-mentioned drying process, a processed product with the curled outer edges
5 is obtained.)

First, by crushing the crust of bread, which is available on the market, with a grinding mill to a particle diameter of about 2 to 5 mm for example, a large number of granules are obtained. If the moisture content of the granules is below 10
10 mass%, the granules are added with water to adjust the moisture content so as to be 10 mass% or higher, and then the granules are used as material. If the moisture content of the granules is 10 mass% or higher, the granules in this condition are used as material.

15 Then, as shown in Fig. 17A, the material 10 composed of the above-mentioned granules is heated under pressure in the press device 2. In this press device 2, bow-shaped concave surfaces 21b are formed at predetermined intervals on the upper surface of a lower part 21 made of steel, and convex surfaces
20 22b, which correspond to the concave surfaces 21b, are formed on the lower surface of an upper part 22 made of steel. A concave surface 21b and a convex surface 22b compose a pair of pressurizing surfaces curved in a bow shape. A predetermined amount of material 10 composed of the above-mentioned granules

is placed on the concave surface 21b of the lower part 21 of the press device 2.

Under this condition, as shown in Fig. 17B, the upper part 22 is lowered until the distance between the pair of pressurizing surfaces 21b and 22b reaches a predetermined gap t to press the material 10 composed of granules. This gap t is to be set suitably at one's discretion according to the particle size and the quantity of granules and the thickness of a processed product to produce. Under this condition, the material is heated and pressurized simultaneously by holding it at a predetermined temperature and a predetermined pressure for a predetermined time until the moisture content of the material 10 decreases to an appropriate value (not less than 6 mass%, for example).

After the elapse of a predetermined time, as shown in Fig. 17C, the upper part 22 is raised and the pressurization is stopped. Under this condition, the material is a joined body of a large number of granules and is in a bow-shaped plate object 10A having a concave surface 11, which corresponds to the concave surface 21b as one pressurizing surface, and a convex surface 12, which corresponds to the convex surface 22b as the other pressurizing surface. Having a still high moisture content, this plate object 10A is in such a shape that the concave surface 12 and the convex surface 11 partially deviate from the

circular-arc of a bow shape.

Next, as shown in Fig. 17D, this plate object 10A is extracted and placed in a hot air dryer 3, and dried by hot air by holding it at a predetermined temperature for a predetermined
5 time until the moisture content of the plate object 10A decreases to 5.9 mass% or lower, for example. As a result, a processed product is obtained in a shape curled such that open-end portions of circular-arc of the bow shape came close together as shown in Fig. 18. By applying seasoning or the like
10 to the processed product, a snack is completed.

Meanwhile, a processed product shown in Fig. 18 was obtained as follows. From bread ("Honjikomi" (Brand name) by Fujipan Co., Japan) with a crust-portion moisture content of 29.1 mass% and an oil content of 2.5 mass%, the crust was crushed to a
15 particle diameter of 2~5mm. And the particles were used in this condition as material, and the above-mentioned gap t was set at 2mm, and conditions of heating under pressure were 60°C temperature, 4.9×10^{-1} MPa pressure and 90sec holding time, and a drying condition was 90°C for 30min.

20 The moisture content of the plate object just after pressurized heating was 27.1 mass% and the thickness of the plate object just after pressurized heating was 2.1mm, and the moisture content of plate object (processed product) after drying was 4.7 mass% and the thickness of the plate object

(processed product) after drying was 2.0mm. The texture of the processed product was similar to potato chips.

The processed product obtained by this method has an advantage that because the crushed crust is used as material, the crust, which is thrown away in most cases, can be used effectively.

(Twelfth Embodiment)

A method for producing a snack according to a twelfth embodiment of the present invention will be described with reference to Figs. 19A to 19C and 20. In this method, crumbs made by crushing the brown-baked crust of bread are used as material, and the material is placed between a pair of pressurizing surfaces curved in a bow shape and heated while pressure is applied until the moisture content of the material decreases to a predetermined value (not more than 5.9 mass%, for example) less than the original moisture content of the material.

First, by crushing the crust of bread, which is available on the market, with a grinding mill to a particle diameter of about 2 to 5 mm for example, a large number of granules are obtained. If the moisture content of the granules is below 10 mass%, the granules are added with water to adjust the moisture content so as to be 10 mass% or higher, and then the granules are used as material. If the moisture content of the granules

is 10 mass% or higher, the granules in this condition are used as material.

Then, as shown in Fig. 19A, the material 10 composed of the above-mentioned granules is heated under pressure in the press device 2. In this press device 2, bow-shaped concave surfaces 21b are formed at predetermined intervals on the upper surface of a lower part 21 made of steel, and convex surfaces 22b, which correspond to the concave surfaces 21b, are formed on the lower surface of an upper part 22 made of steel. A concave surface 21b and a convex surface 22b compose a pair of curved pressurizing surfaces. A predetermined amount of material 10 composed of the above-mentioned granules is placed on the concave surface 21b of the lower part 21 of the press device 2.

Under this condition, as shown in Fig. 19B, the upper part 22 is lowered until the distance between the pair of pressurizing surfaces 21b and 22b reaches a predetermined gap t to press the material 10 composed of granules. This gap t is to be set suitably at one's discretion according to the particle size and the quantity of granules and the thickness of a processed product to produce. Under this condition, the material 10 is heated and pressurized simultaneously by holding it at a predetermined temperature and a predetermined pressure for a predetermined time until the moisture content of the

material 10 decreases to not less than 5 mass%, for example.

After the elapse of a predetermined time, as shown in Fig. 19C, the upper part 22 is raised and the pressurization is stopped. Under this condition, the material is a joined body
5 of a large number of granules and is in a bow-shaped plate object 10A having a concave surface 11, which corresponds to the convex surface 21b as one pressurizing surface, and a convex surface 12, which corresponds to the convex surface 22b as the other pressurizing surface. As a result, a processed product is
10 obtained with the minor axis curved in a circular-arc as shown in Fig. 20, for example. By applying seasoning or the like to this processed product, a snack is completed.

Incidentally, the processed product shown in Fig. 20 was obtained as follows. From bread ("Honjikomi" (Brand name) by
15 Fujipan Co., Japan) with a crust-portion moisture content of 29.1 mass% and an oil content of 2.5 mass%, the crust was crushed to a particle diameter of 2~5mm. And the particles were used in this condition as material, and the above-mentioned gap t was set at 2mm, and conditions of heating under pressure were
20 130°C temperature, 4.9×10^{-1} MPa pressure and 120sec holding time.

The moisture content of this processed product was 4.7 mass% and the thickness was 1.9mm, and the texture was similar to potato chips.

The processed product obtained by this method has an advantage that because the crushed crust is used as material, the crust, which is thrown away in most cases, can be used effectively.

5 Processed products such as shown in Fig. 20 have an advantage that because they can be piled one on top of another in a container, they can be packed densely in a container and are easy to pick up when eating.

(Thirteenth Embodiment)

10 A method for producing a snack according to a thirteen embodiment of the present invention will be described with reference to Figs. 21A, 21B and 22. This method comprises rolling out a brown-baked crusted slice with a thickness of not less than 5mm cut out of bread is used as material (with a roller
15 gap of not more than 2mm, for example) and heating the rolled-out slice until the moisture content decreases to a predetermined value (not more than 5.9 mass%, for example) less than the original moisture content of the material.

By cutting bread available on the market (bread with a
20 moisture content of about 35 mass%, for example) with a slicer, a crusted slice with a 50mm X 30mm rectangular cross section and a thickness of 5mm, 10mm or 20mm is obtained.

Then, as shown in Fig. 21A, the slice 1 is rolled out by a dough sheet former used to produce noodle (a device to roll

a lump of dough into a dough sheet).

This dough sheet former comprises a pair of rollers 4a, 4b, a tilted plate to guide an object to roll between the rollers, and a receiver block 6 arranged below the rollers 4a, 4b. The
5 two rollers 4a, 4b are arranged in a horizontal direction with a predetermined gap t (not more than 2mm) spaced between them. The tilted plate 5 is arranged so that an object to be rolled is guided from a direction lateral to the roller 4a to the top of the roller 4a. The receiver block 6 receives a rolled object
10 that drops from between the rollers.

As shown in Fig. 21B, the bread 1 rolled by the dough sheet former is put into a hot air dryer 3, and by holding it at a predetermined temperature for a predetermined time, the bread 1 is dried (heated) by hot air until the moisture content of
15 the bread 1 decreases to not more than 5.9 mass%, for example. As a result, a processed product is obtained in such a shape that the outer edges are curled as shown in Fig. 22, for example. By adding seasoning or the like to the processed product, a snack is completed.

20 The processed product shown in Fig. 22 was obtained by using a 5mm-thick slice of bread ("Honjikomi" (Brand name) by Fujipan Co., Japan) with a moisture content of 36.3 mass% and an oil content of 2.5 mass% cut out by a slicer, and by rolling and heating under conditions as follows. The rolling conditions

were: roller diameter: 110 mm, roller peripheral velocity: 324m/hour, and roller gap t: 1mm, and the heating condition was 90°C temperature for 40min.

The thickness of the bread just after rolling was 1.4mm,
5 the moisture content of the processed product (bread dried by heating) was 4.5 mass%, and the thickness of the processed product was 2.6mm. The texture of this processed product was similar to potato chips.

In addition, by using a slice of the same bread as mentioned
10 above cut out in a thickness of 10mm with a slicer and by rolling and heating it under the same conditions as mentioned above, a processed product was obtained in such a shape that the outer edges are curled. In this case, the thickness of the bread just after rolling was 1.6mm, the moisture content of the processed
15 product as 4.5 mass% and the thickness of the processed product was 1.9mm. The texture of this processed product resembled potato chips.

Moreover, by using as material a slice of the same bread as mentioned above in a thickness of 20mm cut out with a slicer
20 and by rolling and heating it under the same conditions as mentioned above, a processed product was obtained in such a shape that the outer edges are curled. In this case, the thickness of the bread just after rolling was 1.7mm, and the moisture content of the processed product was 4.7 mass%, and

the thickness of the processed product was 2.0mm. The texture of the processed product was similar to potato chips.

In addition, by using slices of the same bread as above cut out in a thickness of 5mm, 10mm and 20mm as material, and
5 by rolling them with the roller gap t set at different values of 8mm, 5mm, 3mm or 2mm with the other conditions unchanged, the materials of a thickness of 5mm and 10mm did not take such a shape that the outer edges were curled after the rolling when the above-mentioned roller gap was at any of the above-mentioned
10 values.

In the case of a material with a thickness of 20mm, after it was rolled, the material did not assume a shape that the outer edges were curled at the roller gap of 8mm, 5mm and 3mm. When the roller gap was 2mm, however, the thickness of the bread just
15 after it was rolled was 3.4mm, and the processed product obtained by heating under the same conditions mentioned as above had a moisture content of 4.7 mass%, and the thickness of the processed product was 3.7mm. The texture of this processed product resembled potato chips.

20 (Fourteenth Embodiment)

Description will be made of a method for producing a snack according to a fourteenth embodiment of the present invention. This method comprises rolling out a brown-baked sliced bread with a thickness of not less than 5mm is used as material (with

a roller gap of not more than 2mm, for example) and heating the rolled-out slice until the moisture content decreases to a predetermined value (not more than 5.9 mass%) less than the original moisture content of the material.

5 First, by cutting a roll bread (one with a moisture content of about 30 mass%, for example) with a slicer, a crusted slice is obtained in a substantially elliptic cross section with a 55mm major axis and a 40mm minor axis, for example, in a thickness of 5mm, 10mm or 20mm.

10 Then, just as in the thirteenth embodiment, by rolling out the bread slice by a dough sheet former used to manufacture noodle (a device for transforming a lump of dough into a dough sheet), then placing a rolled-out slice in a hot air dryer, and holding it at a predetermined temperature for a predetermined
15 time, the slice is dried by hot air (heated) until the moisture content decreases to not more than 5.9 mass%, for example. Consequently, a processed product is obtained which is curled along the major axis of its elliptic shape as shown in Fig. 23, for example. By adding seasoning or the like to the processed
20 product, a snack is completed.

The processed product shown in Fig. 23 is obtained by using a butter roll bread ("Chojiku Roll"(Brand name) by Shikishima Baking Co.) with a moisture content of 27.3 mass% and an oil content of 8.5 mass% as material, and cutting a 5-mm-thick slice

out of the roll bread with a slicer, and by rolling and heating the bread slice under conditions as follows. The rolling conditions were; roller diameter: 110mm, roller peripheral velocity: 324m/hour and roller gap t: 1mm, and the heating
5 condition was 90°C temperature for 40min.

The thickness of the bread slice just after it was rolled was 2.9mm, the moisture content of the processed product (the bread after drying by heating) was 4.4mass%, and the thickness of the processed product was 5.0mm. The texture of the
10 processed products resembled potato chips.

Meanwhile, by using a 10-mm-thick slice cut out of the same roll bread as mentioned above as material and by rolling and heating it under the same condition as mentioned above, a processed product was obtained in such a shape that the outer
15 edges were curled. In this case, the thickness of the bread just after it was rolled was 1.4mm, the moisture content of the processed product was 4.4 mass%, and the thickness of the processed products was 3.4mm. The texture of the processed product was similar to potato chips.

20 Moreover, by using a 20-mm-thick slice cut out of the same roll bread as mentioned above with a slicer as material and by rolling and heating the bread slice under the same conditions as mentioned above, a processed product was obtained in such a shape that the outer edges were curled. In this case, the

thickness of the bread just after it was rolled was 1.4mm, the moisture content of the processed product as 4.4 mass%, and the thickness of the processed product 2.0mm. The texture of this processed product was similar to potato chips.

5 Furthermore, by using slices cut out of the same roll bread as mentioned above in a thickness of 5mm, 10mm, and 20mm as material, and by rolling out the slice with the roller gap t changed to 3mm or 2mm with the other conditions unchanged, the materials of a thickness of 5mm and 10mm did not take a shape
10 that the outer edges were curled after the rolling, in either case of the roller gaps.

 In the case of material with a thickness of 20mm, after it is rolled, the material did not assume a shape that the outer edges were curled at the roller gaps of 3mm. When the roller
15 gap was 2mm, the thickness of the bread just after rolling was 2.4mm, and the moisture content of a processed product obtained by heating under the same conditions as mentioned above was 4.5 mass%, and the thickness of the processed product was 3.8mm. The texture of this processed product was similar to potato
20 chips.

(Result of Questionnaire)

 People participated in an evaluation test were asked to eat snacks (trial products) finished by adding seasoning to processed products produced by the methods of the respective

embodiments of the present invention and also eat rusks available on the market to compare the texture and so on, and fill out a questionnaire, the results of which are as follows.

Question: Which do you like better, the texture of trial products or that of rusks on the market? Answers: 0 person for
5 rusks; 16 persons for the trial products

Question: Which product do you want to buy? Answers: 5 persons for rusks; 11 persons for the trial products

Question: Which do you like to eat more? Answers: 3 persons
10 for rusks; 13 persons for the trial products

Question: Which do you think worthy of the name of snack?
Answers: 0 person for rusks; 16 persons for the trial product

From the above results, it has become clear that the trial products received a higher evaluation than rusks and that the
15 trial products were accepted as snacks worthy of the name.

INDUSTRIAL APPLICABILITY

As has been described, according to the methods of the present invention, it is possible to obtain foods for teatime
20 other than rusks or applied products of rusks as cakes made from bread. Furthermore, by using material other than potato (bread, for example), snacks can be obtained which have the texture close to potato chips.

What is claimed is:

1. A method of producing a snack, comprising a step of heating under pressure, which includes placing a material comprising bread between a pair of pressurizing surfaces, and heating said material under pressure,

wherein after said step of heating under pressure, which is performed by pressurizing said material until the moisture content of said material decreases to a value which is not less than 6.0 mass % and below the moisture content of said material, the method further comprises the step of drying the material without applying pressure.

2. The method according to Claim 1, wherein after said pressurising surfaces are flat.

3. The method according to Claim 1, wherein after said pressurising surfaces are curved.

4. The method according to Claim 1, wherein said material is bread without a brown-baked crust.

5. The method according to Claim 1, wherein said material is bread with a brown-baked crust.

25

6. The method according to Claim 1, wherein said material is a slice with a thickness of not less than 1mm without a brown-baked crust cut out of the bread.

5 7. The method according to Claim 1, wherein said material is a slice with a thickness of not less than 1mm cut out of bread and with a brown-baked crust remaining along outer edges of the bread.

10 8. The method according to Claim 1, wherein said material is crumbs made by crushing a brown-baked crust.

9. A snack produced by the method according to one of Claims 1 to 8.

15

10. Food like a snack produced by the method according to one of Claims 1 to 8.