

Description

This invention relates generally to phosphorus containing compounds useful as additives in lubricants and more specifically to reaction products of inorganic phosphorus containing acids or anhydrides, including partial and total sulfur analogs thereof, a boron compound and ashless dispersants. The products are oil-soluble and impart antiwear and extreme pressure (EP) properties and antioxidant to lubricating oils including functional fluids.

Nitrogen and phosphorus containing succinic acid derivatives are disclosed in U.S. Patent 3,502,677 for use in lubricants, fuels and power transmitting fluids to provide antiwear properties in addition to dispersancy. We have now prepared antiwear compositions of inorganic phosphorus containing acids and ashless dispersants in oil-soluble form which provide improved oxidation performance as well as protection for rubber seals.

In accordance with this invention, there is provided an oil-soluble reaction product of an inorganic phosphorus acid or anhydride, including partial and total sulfur analogs thereof, a boron compound and an ashless dispersant which contains basic nitrogen and/or a free hydroxyl group. The ashless dispersants can be selected from hydrocarbyl succinimides, hydrocarbyl succinamides, mixed ester/amides of hydrocarbyl-substituted succinic acid, hydroxyesters of hydrocarbyl-substituted succinic acid, and Mannich condensation products of hydrocarbyl-substituted phenols, formaldehyde and polyamines. Mixtures of such dispersants can also be used.

Examples of inorganic phosphorus acids and anhydrides which are useful in forming the products of the invention include phosphorous acid, phosphoric acid, hypo phosphoric acid, phosphorous trioxide (P_2O_3), phosphorous tetraoxide (P_2O_4), and phosphoric anhydride (P_2O_5). Partial or total sulfur analogs such as phosphorotetra thioic acid (H_3PS_4), phosphoromonothioic acid (H_3PO_3S), phosphorodithioic acid ($H_3PO_2S_2$) and phosphorotrithioic acid (H_3POS_3), and P_2S_5 can also be used. Preferred is phosphorous acid (H_3PO_3).

The inorganic, oil-insoluble phosphorus containing acids are reacted with a boron compound and an ashless dispersant which contains basic nitrogen or one or more free hydroxyl groups. The resulting product is oil-soluble. The ashless dispersants are well known lubricating oil additives. They include the hydrocarbyl-substituted succinamides and succinimides of polyethylene polyamines such as tetraethylene-pentamine which are more fully described, for example, in U.S. Patent Nos. 3,172,892; 3,219,666 and 3,361,673. Other examples of suitable ashless dispersants include (i) mixed ester/amides of hydrocarbyl-substituted succinic acid made using alkanols, amines, and/or aminoalkanols, (ii) hydrocarbyl-substituted succinic acid hydroxyesters containing at least one free hydroxyl group made using polyhydroxy alcohols such as are disclosed in U.S. 3,381,022 and (iii) the Mannich dispersants which are condensation products of hydrocarbyl-substituted phenols, formaldehyde and polyethylene polyamines such as are described, for example, in U.S. Patent Nos. 3,368,972; 3,413,374; 3,539,633; 3,649,279; 3,798,247 and 3,803,039. The hydrocarbyl substituent is usually a polyolefin and preferably a polyisobutylene group having a number average molecular weight of from 800 to 5,000. The ashless dispersant is preferably an alkenyl succinimide such as is commercially available from Ethyl Corporation under the trademark HITEC® 644.

Suitable compounds of boron include, for example, boron acids such as boric acid, boronic acid, tetraboric acid, metaboric acid, esters of such acids, such as mono-, di- and tri-organic esters with alcohols having 1 to 20 carbon atoms, e.g., methanol, ethanol, isopropanols, butanols, pentanols, hexanols, ethylene glycol, propylene glycol and the like, and boron oxides such as boron oxide and boron oxide hydrate.

Optionally, additional sources of basic nitrogen can be included in the phosphorus acid-ashless dispersant-boron mixture so as to provide a molar amount (atomic proportion) of basic nitrogen up to that equal to the molar amount of basic nitrogen contributed by the ashless dispersant. Preferred auxiliary nitrogen compounds are long chain primary, secondary and tertiary alkyl amines containing from 12 to 24 carbon atoms, including their hydroxyalkyl and aminoalkyl derivatives. The long chain alkyl group may optionally contain one or more ether groups. Examples of suitable compounds are oleyl amine, N-oleyltrimethylene diamine, N-tallow diethanolamine, N,N-dimethyl oleylamine and myristyloxapropyl amine.

Other materials normally used in lubricant additives which do not interfere with the reaction may also be added, for example, a benzotriazole, including lower (C_1 - C_4) alkyl-substituted benzotriazoles, which function to protect copper surfaces.

The reaction can be carried out in the absence of solvent by mixing and heating the reactants at temperatures of 40-150°C (preferred about 100°C) for 1 to 3 hours with agitation until a clear, oil-soluble solution is obtained. Preferably, water is added to facilitate the initial dissolution of the boron compound. Water formed in the reaction and any added water is then removed by vacuum distillation at temperatures of from 100-140°C. Preferably, the reaction is carried out in a diluent oil or a solvent such as a mixture of aromatic hydrocarbons.

The amount of phosphorus compound employed ranges from 0.001 mole to 0.999 mole per mole of basic nitrogen and free hydroxyl in the reaction mixture up to one half of which may be contributed by an auxiliary nitrogen compound. The amount of boron compound employed ranges from 0.001 mole to 1 mole per mole of

basic nitrogen and/or hydroxyl in the mixture which is in excess of the molar amount of inorganic phosphorus compound.

The amount of added water is not particularly critical as it is removed by distillation at the end of the reaction. Amounts up to about one percent by weight of the mixture are preferred. When used, the amount of diluent generally ranges from 10 to 50 percent by weight of the mixture. When added, the amount of copper protectant generally ranges from 0.5 to 5 percent by weight of the mixture.

Generally, the following amounts of ingredients in relative proportions by weight are used in the reaction:

Dispersant	0.2 to 10 parts
Phosphorus Acid	0.01 to 2 parts
H ₂ O	0 to 2 parts
Diluent Oil or Solvent	0 to 10 parts
Boric Acid	0.01 to 2 parts
Auxiliary Nitrogen Compound	0 to 5.0 parts

Preferred amounts are:

Dispersant	1 to 5 parts
Phosphorus Acid	0.01 to 0.5 part
Water	0.01 to 1 part
Diluent	0.5 to 3 parts
Boric Acid	0.01 to 0.5 part
Auxiliary Nitrogen Compound	0.001 to 2.0 parts

The clear product solution can be blended with other ingredients as is known in the art to form either a lubricant additive concentrate or a complete lubricant. Such ingredients include, for example, (1) additional copper corrosion protectants such as thiadiazole derivatives (2) friction modifiers such as sulfurized fatty esters, long chain amides, long chain amines, organic phosphonates, phosphates and phosphites (3) antioxidants such as dialkyl diphenylamines, hindered phenols, such as bis-o-t-butyl phenols and sulfur bridged phenolic derivatives (4) seal swelling agents such as aromatic hydrocarbons and aromatic sulfones (5) defoamants such as polydimethyl silicones and/or polyethyl-octyl acrylates (6) viscosity index improvers such as polymethacrylate, and (7) diluent oils.

The ashless dispersant usually comprises up to about 98% by weight and preferably 80 to 96% by weight of the active ingredients, excluding the diluent oil, in the additive composition. As known in the art additive concentrates contain a major portion of additive and a minor amount of oil and lubricants contain a major portion of an oil of lubricating viscosity and a minor, effective antiwear and rubber seal protecting amount of additive composition.

The invention is further illustrated by, but is not intended to be limited to, the following examples in which parts are parts by weight unless otherwise indicated.

Example 1A

A preblend is made using a commercial succinimide ashless dispersant (HITEC® 644 dispersant), 260 parts, an alkylnaphthalene aromatic oil diluent, 100 parts, phosphorous acid, 8 parts, toluotriazole, 3.5 parts, boric acid, 8 parts and water, 3.0 parts. The materials are mixed and heated at 100°C for 2 hours until all of the solid materials are dissolved. A vacuum of 40 mm is gradually drawn on the product to remove the water formed while the temperature is slowly raised to 110°C. A clear solution is obtained which is soluble in oil.

Example 1B

A partial concentrate is prepared from sulfurized fat, 30 parts, styrene-maleic anhydride copolymer pour point depressant, 15 parts, phenolic antioxidant (Ethyl® 728), 20 parts, hydroxyethylated long chain amine, 10 parts, 4% Dow-Corning/antifoam fluid, 6 parts, polymethylmethacrylate viscosity index improver, 340 parts and red dye, 2 parts. The materials are stirred and mixed for 45 minutes at 60-70°C.

Example 1C

A mixture of 378 parts of the preblend of Example 1A is mixed with 447 parts of the partial concentrate of Example 1B together with 9175 parts of Exxon 1365 base oil to prepare a complete blended lubricant.

Comparison 1

A preblend was made using a commercial succinimide ashless dispersant (HITEC® 644 dispersant), 260 parts, an alkylnaphthalene aromatic oil diluent, 100 parts, boric acid, 8 parts and toluotriazole, 3.5 parts. The materials were mixed and heated at 100 degrees C for 2 hours until all of the solid materials had dissolved. A vacuum of 40 mm was gradually drawn on the product to remove the water formed while the temperature was slowly raised to 110°C. A mixture of 370 parts of the preblend was mixed with 447 parts of the partial concentrate of Example 1B, and 46 parts of zinc bis-(2-ethylhexyl) phosphorodithioate together with 9137 parts of Exxon 1365 base oil to prepare a complete blended lubricant.

Comparison 2

A mixture of 370 parts of the preblend of Comparison 1 was mixed with 447 parts of the partial concentrate of Example 1B and 37 parts of tricresyl phosphate together with 9146 parts of Exxon 1365 base oil to prepare a complete blended lubricant.

Friction Test

Using the LVFA (low velocity friction apparatus) the coefficient of friction was measured at sliding speeds of 10 and 40 feet (3 to 12 m) per minute using a friction pad of SD1777 material. The same measurement was also made on oil which had been subjected to a HOOT (hot oil oxidation test) test for 16 hours with no catalyst added.

<u>COEF. OF FRICTION (X 1000)</u>			
<u>Lubricant</u>	<u>(A) 10 FT/ MIN</u>	<u>(B) 40 FT/ MIN</u>	<u>Delta (A-B)</u>
Comparison 1			
(Fresh)	132	132	0
(Hooted)	164	150	14
Comparison 2			
(Fresh)	140	132	8
(Hooted)	162	150	12
Example 1C			
(Fresh)	130	130	0
(Hooted)	160	153	7

These results show that the frictional properties of blends using phosphorous acid are just as good as those of the other phosphorus sources and superior in retaining those properties after oxidation.

Hoot Test

The lubricants prepared in Example 1C, the two comparisons, and a control with no phosphorus were subjected to 64 hour HOOT tests. In this procedure, 30 ml. of oil is placed in a 1 x 6 in. (25.4 x 152.4 mm) test tube containing a 7 mm. OD. tube 8 inches (203 mm) in length. As a catalyst, 1.0 ml of a 3.3% solution of ferric acetylacetonate is added along with a small drop of Dow-Corning antifoam solution. After 64 hours in a bath at 161°C with an airflow of 10 L/h. passing through the oil, the absorbance of the oil at a peak in the 1720 reciprocal centimeter region of the infra-red spectrum is measured. The difference from that of the fresh oil is taken as a measure of the susceptibility to oxidation.

OXIDATION THERMAL STABILITY64 HOUR HOOT

5

10

15

20

<u>Lubricant</u>	<u>Phosphorus Source</u>	<u>% By Wt.</u>	<u>Blotter Spot</u>	<u>IR</u>
Comparison 1	Zinc dialkyl-dithiophosphate	0.46	Black Tar	>1.0
Comparison 2	Tricresyl-phosphate	0.37	Black Tar	>1.0
Example 1C	Phosphorous acid	0.08	Light Brown	0.2, 0.13
Control	None	—	Black Tar	>1.0

25

The results show that the phosphorous acid based additive is much superior in oxidation resistance to additives containing the other two phosphorus sources.

4-Ball Test

30

The lubricants prepared in Example 1C, the two comparison compositions and a control with containing no phosphorous additive were tested in the 4-Ball Wear Test. In this procedure, 10 ml. of oil is placed on the 4 steel balls arranged in a pyramidal configuration in a steel cup with the 3 lower balls held fast and the top one rotating against them. The test was run for two hours under a 40 Kg. load at 1200 Rpm and at 150°F (65°C). At the end of the test the average wear scar diameter on the three lower balls was measured.

35

FOUR BALL WEAR TEST EVALUATION

40

45

50

55

<u>Lubricant</u>	<u>Phosphorus Source</u>	<u>% By Wt.</u>	<u>P %</u>	<u>Scar Diameter, MM</u>
Comparison 1	Zinc dialkyl-dithiophosphate	0.46	0.03	0.400
Comparison 2	Tricresyl-phosphate	0.37	0.03	0.475
Example 1C	Phosphorous acid	0.08	0.03	0.400
Control	None	—	—	0.525

The results show that the phosphorous acid product is superior in wear resistance to the additive containing

tricresyl phosphate and equal to that of the additive containing zinc dithiophosphate.

Copper Corrosion Test

The lubricants were tested in the D-130 test at 150°C for three hours. This test indicates the resistance of the lubricant to corrosion of copper. A freshly refined copper strip is placed in a 1 x 6 in. (25.4 x 152.4 mm.) test tube with 30 ml. of the oil being tested. The tube is placed in a heated bath for the proper period of time. After removal from the bath the condition of the strip is compared with a set of standard strips and given a rating according to the standard strip most closely matched. The ratings ranged from 1 to 4 with letters A to D for intermediate ranges.

<u>Lubricant</u>	<u>D-130 Rating</u>
Comparison 1	IB-2C
Comparison 2	IB
Example 1C	IB

The results show that the phosphorous acid blend provided excellent control of copper corrosion. A power steering pump wear evaluation was conducted with lubricants containing zinc dialkyl dithiophosphate, tricresylphosphate and a control in comparison to the lubricant of Example 1C with the following results.

POWER STEERING PUMP WEAR EVALUATION OF AUTOMATIC TRANSMISSION FLUIDS

<u>Lubricant</u>	<u>Phosphorus Source</u>	<u>% By Wt.</u>	<u>P %</u>	<u>Rating</u>
Comparison 1	Zinc dialkyldithio- phosphate	0.46	0.03	2.5 (Fair to Good)
Comparison 2	Tricresylphosphate	0.37	0.03	3.8 (Borderline)
Example 1C	Phosphorous acid	0.08	0.03	1.0 (Excellent)
Control	No phosphorus	0	0	5.0 (Bad Failure)

Comparison 3

Example 1 was repeated except that no boric acid was added to the mixture in Example 1A and 9183 parts of oil were used in Example 1C.

Mercon® ATRR 300 Silicone Elastomer Test

Two strips of red silicon rubber cut per ASTM D471 are immersed in a tube containing the test oil. The tube is placed in an oven at 163°C for 240 hours (10 days). The silicone rubber should show no reversion (as determined by the smear test). The smear test consists of sliding the aged reference sample across a section of white cardboard under approximately 1.8 Kg thumb force. The color smear can be no greater than that produced by sliding an unaged coupon across an identical piece of white cardboard under the same 1.8 Kg thumb

force.

SILICON SEAL EVALUATION (MERCON®)

<u>Lubricant</u>	<u>Boron Weight</u>	<u>Phosphorus Source</u>	<u>Weight %</u>	<u>Phosphorus %</u>	<u>Rubber Smear</u>
Example 1	0.014	Phosphorous Acid	0.08	0.03	None (Pass)
Comparison 3	None	Phosphorous Acid	0.08	0.03	Medium (Fail)

The lubricant additive of the invention thus provides protection against attack of silicon rubber seals compared to an additive prepared without the boron compound.

Example 2

A preblend was made using an ashless dispersant made from 2,100 molecular weight polybutene, 260 parts, an aromatic oil diluent, 100 parts, phosphorous acid, 8 parts, boric acid, 8 parts, tolyltriazole 3.5 parts and water, 3 parts. The materials were mixed and heated at 100°C for 2 hours until all solids were dissolved. A vacuum of 40 mm was drawn on the product to remove the water formed while the temperature was slowly raised to 110°C. A clear solution was obtained which was soluble in oil.

Example 3

A preblend was made using a commercial ashless dispersant of the Mannich reaction product type, (Amoco® 9250 dispersant), 260 parts, an aromatic oil diluent, 100 parts, phosphorous acid, 8 parts, boric acid, 8 parts, tolyltriazole, 3.5 parts and water, 3 parts. The materials were mixed and heated at 100°C for 2 hours until all solids were dissolved. A vacuum of 40 mm was drawn on the product to remove the water formed while the temperature was slowly raised to 110°C. A clear solution was obtained which was soluble in oil.

Example 4

A preblend was made using a commercial ashless dispersant of the pentaerythritol ester type (Lubrizol®-936 dispersant), 260 parts, an aromatic oil diluent, 100 parts, phosphorous acid, 8 parts, boric acid, 8 parts, tolyltriazole, 3.5 parts and water, 3 parts. The materials were mixed and heated at 100°C for 2 hours until all solids were dissolved. A vacuum of 40 mm was drawn on the product to remove the water formed while the temperature was slowly raised to 110°C. A clear solution was obtained which was soluble in oil.

Example 5

The process of Example 1 was repeated except that 11 parts of P_2S_5 were used in place of the phosphorous acid, the P_2S_5 was added to the preblend after water distillation and the mixture was then heated for an additional hour at 100°C to provide a clear, oil-soluble solution. The blended lubricant contained 9172 parts of 100 neutral base oil. The lubricant contained 0.11 percent by weight P_2S_5 and 0.03 percent by weight phosphorous. The lubricant gave a 4-Ball scar diameter of 0.450 and a black tar blotter spot with an IR value of 0.8 in the 65 hour HOOT thermal stability test.

Example 6

The process of Example 5 was repeated except that the P_2S_5 was replaced by 7 parts of P_2O_5 . A clear oil-soluble product was produced and the complete blended lubricant contained 9176 of neutral base oil, 0.07 percent by weight P_2O_5 and 0.03 percent by weight phosphorus. The lubricant gave a 4-Ball scar diameter of 0.450, a black oil blotter spot with an IR value of 0.5 in the 65 hour HOOT Thermal stability test, and a 2.0 (good)

power steering pump wear test rating. The lubricant passed the silicon seal test (no smear).

FZG LOAD (EP) TEST

	Phosphorus Source	Wt. %	P %	Pass, Stages
Control	None	--	--	8
Comparison 2	Tricresyl phosphate	0.37	0.03	8
Comparison 1	Zinc dialkyldithio- phosphate	0.46	0.03	10
Example 1C	Phosphorous acid	0.08	0.03	10

FZG WEAR TEST - LOW SPEED (10 stages, 100 RPM, 20 hours)

	Phosphorus Source	Wt. %	P %	WEAR. MG
Comparison 1	Zinc dialkyldithio- phosphate	0.46	0.03	26
Comparison 2	Tricresyl phosphate	0.37	0.03	41
Example 1C	Phosphorous acid	0.08	0.03	21

FZG test apparatus and procedure is fully described in the DIN 51354 (Germany) IP 334 (U.K.) and CEC L-07-A-75 (common market) official standards. The lubricant of Example 1C gave improved FZG wear test results compared to those containing zinc dialkyldithiophosphate (ZDDP) and tricresyl phosphate. The lubricant was equal to ZDDP and better than tricresyl phosphate in the FZG load test.

As illustrated by the foregoing comparative test data, the oil-soluble additives of the invention, which are formed using inorganic phosphorus acids and anhydrides, provide lubricants with improved anti-wear and rubber seal protective properties. A further commercial advantage is provided because the inorganic phosphorus acids and anhydrides are less expensive than the organic phosphates and phosphites.

Claims

1. An oil-soluble lubricant additive composition comprising the reaction product of an inorganic phosphorus acid or anhydride, including partial and total sulfur analogs thereof, a boron compound, and an ashless dispersant which contains basic nitrogen and/or hydroxyl group.

2. A composition according to claim 1 wherein the ashless dispersant is a hydrocarbyl succinimide, hydrocarbyl succinamide, mixed ester/amide of a hydrocarbyl-substituted succinic acid, hydroxyester of a hyd-



power steering pump wear test rating. The lubricant passed the silicon seal test (no smear).

FZG LOAD (EP) TEST

	Phosphorus Source	Wt. %	P %	Pass, Stages
Control	None	--	--	8
Comparison 2	Tricresyl phosphate	0.37	0.03	8
Comparison 1	Zinc dialkyldithio- phosphate	0.46	0.03	10
Example 1C	Phosphorous acid	0.08	0.03	10

FZG WEAR TEST - LOW SPEED (10 stages, 100 RPM, 20 hours)

	Phosphorus Source	Wt. %	P %	WEAR. MG
Comparison 1	Zinc dialkyldithio- phosphate	0.46	0.03	26
Comparison 2	Tricresyl phosphate	0.37	0.03	41
Example 1C	Phosphorous acid	0.08	0.03	21

FZG test apparatus and procedure is fully described in the DIN 51354 (Germany) IP 334 (U.K.) and CEC L-07-A-75 (common market) official standards. The lubricant of Example 1C gave improved FZG wear test results compared to those containing zinc dialkyldithiophosphate (ZDDP) and tricresyl phosphate. The lubricant was equal to ZDDP and better than tricresyl phosphate in the FZG load test.

As illustrated by the foregoing comparative test data, the oil-soluble additives of the invention, which are formed using inorganic phosphorus acids and anhydrides, provide lubricants with improved anti-wear and rubber seal protective properties. A further commercial advantage is provided because the inorganic phosphorus acids and anhydrides are less expensive than the organic phosphates and phosphites.

Claims

1. An oil-soluble lubricant additive composition comprising the reaction product of an inorganic phosphorus acid or anhydride, including partial and total sulfur analogs thereof, a boron compound, and an ashless dispersant which contains basic nitrogen and/or hydroxyl group.

2. A composition according to claim 1 wherein the ashless dispersant is a hydrocarbyl succinimide, hydrocarbyl succinamide, mixed ester/amide of a hydrocarbyl-substituted succinic acid, hydroxyester of a hydro-



rocarbyl-substituted succinic acid, Mannich condensation product of a hydrocarbyl-substituted phenol, formaldehyde and a polyamine, or a mixture thereof.

3. A composition according to claim 2 wherein the ashless dispersant is a polyisobutenyl succinimide in which the polyisobutenyl group has a number average molecular weight of from 800 to 5,000, the acid is phosphorous acid, and the boron compound is boric acid.

4. A composition according to any one of the preceding claims wherein the amount of phosphorus acid or anhydride is from 0.001 mole to 0.999 mole per mole of basic nitrogen and hydroxyl in the composition and the amount of boron compound is from 0.001 mole to 1 mole per mole of basic nitrogen and hydroxyl in the mixture which is in excess of the molar amount of phosphorous acid.

5. A process for preparing an oil-soluble lubricant additive composition according to any one of the preceding claims which comprises heating a mixture of the inorganic phosphorus acid or anhydride, including partial and total sulfur analogs thereof, with the boron compound and the ashless dispersant which contains basic nitrogen and/or a hydroxyl group until a clear, oil-soluble solution is obtained.

6. Process according to Claim 5 wherein the mixture is heated at a temperature of from 40-150°C for 1 to 3 hours.

7. Process according to Claim 5 or 6 wherein the ashless dispersant is a polyisobutenyl succinimide in which the polyisobutenyl group has a number average molecular weight of from 800 to 5,000, the acid is phosphorous acid, the boron compound is boric acid and water is added to the mixture.

8. Process according to Claim 5, 6 or 7 which is carried out in the presence of a benzotriazole.

9. An oil-soluble lubricant additive composition according to any one of claims 1 to 4 in the form of a concentrate comprising a major portion of the said reaction product and a minor portion of a diluent oil.

10. A lubricating oil composition comprising a major portion of an oil of lubricating viscosity and a minor portion of an oil-soluble lubricant additive composition according to any one of claims 1 to 4.

Patentansprüche

1. Öllösliche Schmiermitteladditiv-Zubereitung, welche das Reaktionsprodukt einer anorganischen Phosphor-Säure oder eines Anhydrids davon, einschließlich partieller und vollständiger Schwefelanaloga davon, eine Borverbindung und eine aschefreies Dispergiermittel umfaßt, welches basischen Stickstoff und/oder eine Hydroxylgruppe enthält.

2. Zubereitung nach Anspruch 1, worin das aschefreie Dispergiermittel ein Hydrocarbilsuccinimid, ein Hydrocarbilsuccinamid, ein gemischter Ester/Amid einer Hydrocarbyl-substituierten Bernsteinsäure, ein Hydroxyester einer Hydrocarbyl-substituierten Bernsteinsäure, ein Mannich-Kondensationsprodukt von einem Hydrocarbyl-substituierten Phenol, von Formaldehyd und von einem Polyamid, oder einer Mischung daraus ist.

3. Zubereitung nach Anspruch 2, worin das aschefreie Dispergiermittel ein Polyisobutenylsuccinimid ist, worin die Polyisobutenylgruppe ein Zahlenmittel des Molekulargewichts von 800 bis 5.000 aufweist, die Säure phosphorige Säure ist und die Borverbindung Borsäure ist.

4. Zubereitung nach irgendeinem der vorangehenden Ansprüche, worin die Menge and phosphoriger Säure oder deren Anhydrid 0,001 Mol bis 0,999 Mol pro Mol an basischem Stickstoff und Hydroxyl in der Zubereitung beträgt und die Menge an Borverbindung 0,001 Mol bis 1 Mol pro Mol an basischem Stickstoff und Hydroxyl in der Mischung beträgt, welcher im Überschuß über die molare Menge an phosphoriger Säure vorliegt.

5. Verfahren zur Herstellung einer öllöslichen Schmiermitteladditiv-Zubereitung gemäß irgendeinem der vorangehenden Ansprüche, welches das Aufheizen einer Mischung der anorganischen Phosphor-Säure oder von deren Anhydrid, einschließlich partieller und vollständiger Schwefelanaloga davon, mit der Borverbindung und dem aschefreien Dispergiermittel umfaßt, welches basischen Stickstoff und/oder eine Hydroxylgruppe enthält, bis eine klare, öllösliche Lösung erhalten wird.

6. Verfahren nach Anspruch 5, worin die Mischung auf eine Temperatur von 40 bis 150 °C 1 bis 3 Stunden lang erhitzt wird.

7. Verfahren nach Anspruch 5 oder Anspruch 6, worin das aschefreie Dispergiermittel ein Polyisobutenylsuccinimid ist, in dem die Polyisobutenylgruppe ein Zahlenmittel des Molekulargewichts von 800 bis 5.000 aufweist, die Säure phosphorige Säure ist, die Borverbindung Borsäure ist und Wasser der Mischung zugesetzt wird.

8. Verfahren nach Anspruch 5, 6 oder 7, welches in Gegenwart von Benzotriazol durchgeführt wird.

9. Öllösliche Schmiermitteladditiv-Zubereitung nach irgendeinem der Ansprüche 1 bis 4 in Form eines Konzentrats, welches einen größeren Teil des Reaktionsprodukts und einem kleineren Teil eines Öl als Verdünnungs-



mittel umfaßt.

10. Schmiermittelöl-Zubereitung, welche einen größeren Anteil eines Öls von für die Schmiereung geeigneter Viskosität und einen kleineren Anteil einer öllöslichen Schmiermitteladditiv-Zubereitung gemäß irgendeinem der Ansprüche 1 bis 4 umfaßt.

Revendications

1. Composition d'additif pour lubrifiant oléosoluble, comprenant le produit de réaction d'un acide ou anhydride d'acide phosphoré inorganique, y compris ses analogues sulfurés partiels et totaux, un composé de bore et un dispersant sans cendres qui contient de l'azote basique et/ou un groupe hydroxyle.

2. Composition suivant la revendication 1, dans laquelle le dispersant sans cendres est un hydrocarbyle-succinimide, un hydrocarbylesuccinamide, un ester/amide mixte d'un acide succinique à substituant hydrocarbyle, un hydroxyester d'un acide succinique à substituant hydrocarbyle, un produit de condensation de Mannich d'un phénol à substituant hydrocarbyle, de formaldéhyde et d'une polyamine, ou un mélange de ces dispersants.

3. Composition suivant la revendication 2, dans laquelle le dispersant sans cendres est un polyisobuténylsuccinimide dont le groupe polyisobutényle a une moyenne numérique du poids moléculaire de 800 à 5000, l'acide est l'acide phosphoreux et le composé de bore est l'acide borique.

4. Composition suivant l'une quelconque des revendications précédentes, dans laquelle la quantité d'acide ou d'anhydride phosphoré est de 0,001 à 0,999 mole par mole d'azote basique et de groupe hydroxyle dans la composition et la quantité de composé de bore va de 0,001 à 1 mole par mole d'azote basique et de groupe hydroxyle dans le mélange qui est en excès de la quantité molaire d'acide phosphoré.

5. Procédé de préparation d'une composition d'additif oléosoluble pour lubrifiant suivant l'une quelconque des revendications précédentes, qui consiste à chauffer un mélange de l'acide ou de l'anhydride phosphoré inorganique, y compris ses analogues sulfurés partiels et totaux, avec le composé de bore et le dispersant sans cendres qui contient de l'azote basique et/ou un groupe hydroxyle jusqu'à l'obtention d'une solution claire oléosoluble.

6. Procédé suivant la revendication 5, dans lequel le mélange est chauffé à une température de 40 à 150°C pendant 1 à 3 heures.

7. Procédé suivant la revendication 5 ou 6, dans lequel le dispersant sans cendres est un polyisobuténylsuccinimide dans lequel le groupe polyisobutényle a une moyenne numérique du poids moléculaire de 800 à 5000, l'acide est l'acide phosphoreux, le composé de bore est l'acide borique et de l'eau est ajoutée au mélange.

8. Procédé suivant la revendication 5, 6 ou 7, qui est mis en oeuvre en présence de benzotriazole.

9. Composition d'additif oléosoluble pour lubrifiant suivant l'une quelconque des revendications 1 à 4, sous la forme d'un concentré comprenant une portion dominante dudit produit réactionnel et une portion secondaire d'une huile de dilution.

10. Composition d'huile lubrifiante, comprenant une portion dominante d'une huile de viscosité propre à la lubrification et une portion secondaire d'une composition d'additif oléosoluble pour lubrifiant suivant l'une quelconque des revendications 1 à 4.