WHAT IS CLAIMED IS:

1. A random access method, performed by a user equipment (UE), comprising:

receiving resource configuration information sent by a base station;

determining slice information of a target network slice that triggers a random access;

determining a first random access resource according to at least one of the resource configuration information and the slice information; and

initiating the random access based on the first random access resource;

wherein the resource configuration information is used to configure at least one of: a common random access resource; a specified random access resource corresponding to at least one network slice; a two-step random access resource; a four-step random access resource; a two-step common random access resource; a four-step common random access resource; a two-step specified random access resource; or a four-step specified random access resource,

wherein determining the first random access resource according to at least one of the resource configuration information and the slice information comprises:

determining that the base station has configured the two-step random access resource and the four-step random access resource, according to the resource configuration information and the slice information;

in response to determining that a signal quality is greater than a second threshold, determining the two-step random access resource as a candidate resource;

in response to determining that the signal quality is less than or equal to the second threshold, determining the four-step random access resource as the candidate resource; and

determining the first random access resource based on the candidate resource.

2. The method according to claim 1, wherein determining the first random access resource according to at least one of the resource configuration information and the slice information comprises:

determining that the base station has configured at least a specified random access resource corresponding to the target network slice, according to the resource configuration information and the slice information;

determining the specified random access resource corresponding to the target network slice as a candidate resource; and

determining the first random access resource based on the candidate resource.

3. The method according to claim 1, wherein determining the first random access resource according to at least one of the resource configuration information and the slice information comprises:

determining that the base station has not configured a specified random access resource corresponding to the target network slice, but has configured the common random access resource, according to the resource configuration information and the slice information;

determining the common random access resource as a candidate resource; and

determining the first random access resource based on the candidate resource.

4. The method according to claim 1, wherein determining the first random access resource according to at least one of the resource configuration information and the slice information comprises:

determining that the base station has configured at least a specified random access resource corresponding to the target network slice and the common random access resource, according to the resource configuration information and the slice information;

in response to determining that a signal quality is greater than a first threshold, determining the specified random access resource corresponding to the target network slice as a candidate resource;

in response to determining that the signal quality is less than or equal to the first threshold, determining the common random access resource as the candidate resource; and

determining the first random access resource based on the candidate resource.

5. The method according to claim 1, wherein determining the first random access resource according to at least one of the resource configuration information and the slice information comprises:

determining that the base station has configured the two-step random access resource or the four-step random access resource, according to the resource configuration information;

determining the two-step random access resource or the four-step random access resource as a candidate resource; and

determining the first random access resource based on the candidate resource.

6. The method according to any one of claims 2-5, wherein determining the first random access resource based on the candidate resource comprises any one of:

in a case where the candidate resource comprises any one of the common random access resource, the specified random access resource corresponding to the target network slice, the two-step random access resource or the four-step random access resource, determining the candidate resource as the first random access resource;

in a case where the candidate resource comprises the common random access resource, determining the two-step common random access resource or the four-step common random access resource as the first random access resource;

in a case where the candidate resource comprises the specified random access resource

corresponding to the target network slice, determining the two-step specified random access resource or the four-step specified random access resource as the first random access resource;

in a case where the candidate resource comprises the two-step random access resource, determining the two-step common random access resource or the two-step specified random access resource as the first random access resource; or

in a case where the candidate resource comprises the four-step random access resource, determining the four-step common random access resource or the four-step specified random access resource as the first random access resource.

7. The method according to claim 6, wherein in the case where the candidate resource comprises the specified random access resource corresponding to the target network slice, determining the two-step specified random access resource or the four-step specified random access resource as the first random access resource comprises:

in the case where the candidate resource comprises the specified random access resource corresponding to the target network slice, determining that the base station has configured at least the two-step specified random access resource and the four-step specified random access resource according the resource configuration information;

in response to determining that a signal quality is greater than a second threshold, determining the two-step specified random access resource as the first random access resource; or

in response to determining that a signal quality is less than or equal to a second threshold, determining the four-step specified random access resource as the first random access resource.

8. The method according to claim 7, wherein in the case where the candidate resource comprises the two-step random access resource, determining the two-step common random access resource or the two-step specified random access resource as the first random access resource comprises:

in the case where the candidate resource comprises the two-step random access resource, determining that the base station has configured the two-step common random access resource and the two-step specified random access resource according to the resource configuration information;

determine the two-step specified random access resource as the first random access resource; or

in response to determining that a signal quality is greater than a second threshold, determining the two-step specified random access resource as the first random access resource; or

in response to determining that a signal quality is less than or equal to a second threshold,

determining the two-step common random access resource as the first random access resource.

9. The method according to claim 7, wherein in the case where the candidate resource comprises the four-step random access resource, determining the four-step common random access resource or the four-step specified random access resource as the first random access resource according to the resource configuration information comprises:

in the case where the candidate resource comprises the four-step random access resource, determining that the base station has configured the four-step common random access resource and the four-step specified random access resource according to the resource configuration information;

determining the four-step specified random access resource as the first random access resource; or

in response to determining that a signal quality is greater than a first threshold, determining the four-step specified random access resource as the first random access resource; or

in response to determining that a signal quality is less than or equal to a first threshold, determining the four-step common random access resource as the first random access resource.

10. The method according to any one of claims 1-9, further comprising:

in response to meeting a preset fallback condition, not performing a resource fallback;

or

in response to meeting the preset fallback condition, determining a second random access resource to be fallen back to; and reinitiating the random access based on the second random access resource,

wherein the preset fallback condition comprises any one of:

a number of failures of the random access initiated based on the first random access resource reaching a first fallback threshold;

a first fallback timer expiring; or

receiving a random access resource fallback indication message corresponding to the target network slice.

11. The method according to claim 10, wherein in response to meeting the preset fallback condition, not performing the resource fallback comprises any one of:

in response to meeting the preset fallback condition when the random access is initiated by using a specified random access resource corresponding to the target network slice as the first random access resource, not performing the resource fallback; or

in response to meeting the preset fallback condition when the random access is initiated by using the common random access resource as the first random access resource, not performing the resource fallback.

12. The method according to claim 10, wherein the first random access resource is the two-step specified random access resource,

wherein determining the second random access resource to be fallen back to comprises any one of:

determining that the base station has configured the four-step specified random access resource according to the resource configuration information and the slice information; and determining the four-step specified random access resource as the second random access resource,

or

determining that the base station has configured the common random access resource according to the resource configuration information and the slice information; and determining the second random access resource from the common random access resource according to the resource configuration information and a signal quality,

or

determining that the base station has configured the common random access resource according to the resource configuration information and the slice information; determining to be capable of falling back to the common random access resource to reinitiate the random access, according to first indication information sent by the base station; and determining the second random access resource from the common random access resource according to the resource configuration information and a signal quality.

13. The method according to claim 12, wherein determining the second random access resource from the common random access resource according to the resource configuration information and the signal quality comprises:

determining that the base station has configured the two-step common random access resource according to the resource configuration information;

determining that the signal quality is greater than a third threshold; and

determining the two-step common random access resource as the second random access resource.

14. The method according to claim 10, wherein the first random access resource belongs to the common random access resource,

wherein determining the second random access resource to be fallen back to comprises any one of:

determining that the base station has configured the four-step common random access resource according to the resource configuration information and the slice information; determining the four-step common random access resource as the second random access

resource,

or

determining that the base station has configured a specified random access resource corresponding to the target network slice according to the resource configuration information and the slice information; and determining the second random access resource from the specified random access resource corresponding to the target network slice according to the resource configuration information and a signal quality,

or

determining that the base station has configured a specified random access resource corresponding to the target network slice according to the resource configuration information and the slice information; determining to be capable of falling back to the specified random access resource corresponding to the target network slice to reinitiate the random access, according to second indication information sent by the base station; and determining the second random access resource from the specified random access resource corresponding to the target network slice according to the resource configuration information and a signal quality.

15. The method according to claim 14, wherein determining the second random access resource from the specified random access resource corresponding to the target network slice according to the resource configuration information and the signal quality comprises:

determining that the base station has configured the four-step specified random access resource according to the resource configuration information; and determining the four-step specified random access resource as the second random access resource,

or

determining that the base station has configured the four-step specified random access resource according to the resource configuration information; determining that the signal quality is greater than a fourth threshold; and determining the four-step specified random access resource as the second random access resource.

16. A random access method, performed by a base station, comprising:

sending resource configuration information to a user equipment (UE);

wherein the resource configuration information is used to configure at least one of: a common random access resource; a specified random access resource corresponding to at least one network slice; a two-step random access resource; a four-step random access resource; a two-step common random access resource; a four-step common random access resource; a two-step specified random access resource; or a four-step specified random access resource;

wherein the method further comprises any one of:

broadcasting a second system message, wherein the second system message is used to

configure a second threshold corresponding to at least one network slice; or

sending a second RRC message to the UE, wherein the second RRC message is used to configure a second threshold corresponding to at least one network slice,

wherein the second threshold is configured for the terminal, when determining that the base station has configured the two-step random access resource and the four-step random access resource according to the resource configuration information and slice information, to determine the two-step random access resource as a candidate resource in response to determining that a signal quality is greater than a second threshold, or determine the four-step random access resource as the candidate resource in response to determining that the signal quality is less than or equal to the second threshold.

17. A random access device, applicable to a user equipment (UE), comprising:

a receiving module configured to receive resource configuration information sent by a base station;

a first determining module configured to determine slice information of a target network slice that triggers a random access;

a second determining module configured to determine a first random access resource according to at least one of the resource configuration information and the slice information; and

a random access module configured to initiate the random access based on the first random access resource;

wherein the resource configuration information is used to configure at least one of: a common random access resource; a specified random access resource corresponding to at least one network slice; a two-step random access resource; a four-step random access resource; a two-step common random access resource; a four-step common random access resource; a two-step specified random access resource; or a four-step specified random access resource,

wherein the second determining module is further configured to:

determine that the base station has configured the two-step random access resource and the four-step random access resource, according to the resource configuration information and the slice information;

in response to determining that a signal quality is greater than a second threshold, determine the two-step random access resource as a candidate resource;

in response to determining that the signal quality is less than or equal to the second threshold, determine the four-step random access resource as the candidate resource; and

determine the first random access resource based on the candidate resource.

18. A computer-readable storage medium having stored therein a computer program for executing the random access method according to any one of claims 1-16.

19. A random access device, comprising:

a processor; and

a memory for storing an instruction executable by the processor;

wherein the processor is configured to execute the random access method according to any one of claims 1-16.