



159159

SPECIFICATION



G00002

APPARATUS AND METHOD OF COMBUSTION DIAGNOSIS/CONTROL IN INTERNAL COMBUSTION ENGINE

Technical field

The present invention relates to an apparatus and method for diagnosing and controlling combustion in an internal combustion engine including a gas engine which is constituted so that fuel gas is mixed with air and burned in the combustion chamber thereof.

Background art

It is demanded in an internal combustion engine, particularly in an gas engine which uses clean gas such as town gas as main fuel, to sense with reliability the occurrence of knock due to misfire, flame quenching or uneven mixture in the combustion chamber and to take a measure to deal with the phenomenon without delay. Further, it is required in said gas engine, petrol engine, and diesel engine, etc. to detect positively the excessive increase of the maximum combustion pressure in the combustion chamber, i.e. the maximum cylinder pressure or the reduction of compression pressure in addition to said misfire, flame quenching, or knock for maintaining the durability, stability of performance of the engine.

It is inevitable in said gas engine, petrol engine, and diesel engine, etc. that the condition of combustion in the combustion chamber is detected, diagnosed, and the ignition timing of the fuel and the fuel injection quantity are properly

controlled according to the result of the diagnosis. Further, it is required that, even when something wrong occurs with the maximum cylinder pressure detector which is the detector of the condition of combustion, speedy recovery from the abnormal condition and resumption of normal diagnosis and control of combustion.

Combustion diagnosis systems for detecting and diagnosing the condition of combustion in the combustion chamber of internal combustion engines are disclosed in Japanese Patent Application Publication No.2000-110652, No.11-183330, and Japanese Patent No.2712332, etc.

According to Japanese Patent Application Publication No.2000-110652, frequency band is determined according to the now-operating parameter of the internal combustion engine, the signal component of frequencies belonging to said extraction frequency band is extracted from said detected signal of cylinder pressure by means of a filter, and knock is judged to be occurring when the extracted component exceeds a threshold value.

In Japanese Patent Application Publication No.11-183330, misfire is judged to be present when the crank angle when the value of the pressure in the detected signal from the cylinder pressure detector is maximum, i.e. the crank angle at the maximum cylinder pressure is in the range of predetermined crank angle and at the same time the mean effective pressure calculated from the detected cylinder pressure signal is below the predetermined value.

According to Japanese Patent No.2712332, engine rotation speed is detected to monitor the change thereof, and misfire is judged to be present when engine rotation speed has gone below the predetermined value.

However, in the invention of Japanese Patent Application Publication No.2000-110652, the signal component of frequencies belonging to the extraction frequency band is extracted by a filter means, so complicated computation processing such as changing of pass band accompanying the treatment by the filter means is necessary. Therefore, the judgement of the occurrence of knock and control thereof are complicated. Further, as the absolute value of the cylinder pressure is necessary, the accuracy of the detected cylinder pressure decreases and correct diagnosis of combustion is impossible when the output level of the cylinder pressure sensor reduces totally due to the deterioration, temperature drift, failed calibration, etc. of the cylinder pressure sensor.

Also in the invention of Japanese Patent Application Publication No.11-183330, the absolute value of the cylinder pressure is necessary for the judgement of misfire, so, in an analogous fashion as mentioned above, the accuracy of the detected cylinder pressure decreases and correct diagnosis of combustion is impossible when the output level of the cylinder pressure sensor reduces totally due to the deterioration, temperature drift, failed calibration, etc. of the cylinder pressure sensor.

In the invention of Japanese Patent No.2712332, the condition of combustion in the combustion chamber is detected and diagnosed by the indirect means of monitoring the change of rotation speed of the engine, so the accuracy of combustion diagnosis is low.

Further, in any of the prior inventions, an apparatus carries out combustion diagnosis only on one item, that is knock or misfire, therefore the cost of apparatuses becomes expensive to provide for a plurality of diagnosis functions.

In an multi-cylinder gas engine provided with an ignition device among those internal combustion engines, combustion efficiency increases and engine performance improves by advancing the fuel ignition timing, however, knock becomes easy to occur due to the earlier spontaneous ignition of unburned fuel. Therefore, it is required to operate with the fuel ignition timing with which knock is evaded and the maximum engine performance is maintained.

It is required, in a multiple-cylinder gas engine like this, to carry out the combustion diagnosis and combustion control so that, through the detection of the occurrence of misfire or flame quenching with good accuracy without delay from the detected data of the cylinder pressure, the fuel ignition timing and fuel injection quantity for the cylinder in which said misfire or flame quenching is occurring are adjusted to deal with said misfire or flame quenching so as to make the smooth operation of the other cylinders possible without affected by the cylinders in which the misfire or flame quenching is occurring.

Further, in the multi-cylinder gas engine, it is required that, when abnormality occurs to any of the cylinder pressure detecting means for detecting the combustion condition in combustion chamber due to any failure of the detecting means, the recovery of the function of the cylinder pressure detecting means is carried out while adjusting the fuel ignition timing and fuel injection quantity of the cylinder in which said abnormality in the pressure detecting means has occurred to conditions safe against abnormal combustion, and after the recovery of the function of the pressure detecting means the normal combustion control is recovered automatically, thus the occurrence of abnormality in any of the cylinder pressure detecting means can be dealt with without stopping the operation of the engine.

Further, in the multi-cylinder gas engine, it is required that the standard values (thresholds) of diagnosis items such as maximum cylinder pressure, maximum limit pressure of knock, permissible pressure concerning occurrence of flame quenching are adjustable to match the operation condition of the engine and the high accuracy of diagnosis of the condition of combustion is maintained.

Further, in the multi-cylinder gas engine, it is required that the occurrence of abnormality in any of the cylinder pressure detecting means can be detected at an early stage and automatically, swift recovery of the function of the cylinder pressure detecting means from the abnormal state is possible, and the combustion diagnosis is carried out

smoothly.

However, none of prior arts including said prior invention provides a combustion diagnosis and combustion control means which can suffice the requirements mentioned above.

Particularly, when the information of combustion diagnosis such as misfire, flame quenching is sent to a combustion control device, the method of sending the information of a plurality of cylinders digitally through a serial wire is not desirable, for the influence of a break in the wire and noise affects the control of all of the cylinders.

For this reason, with a method of parallel transmittal of each individual combustion diagnosis information between the combustion diagnosis apparatus and combustion control apparatus as shown in FIG.32 according to the thought of fail-safe, several kinds of category's information (2^n kinds) for each of m cylinders are necessary for sending digital signals, so $2^n \times m$ or more wires are required, which demands much expense in time and effort.

Further, in none of conventional combustion diagnosis systems of multi-cylinder engine has been used a display which can display always changing combustion conditions of all of the cylinders in a manner easily understandable to the worker. Because of the necessity of observing the waveform of cylinder pressure for investigating the details of abnormality of combustion, an oscilloscope must be provided for each cylinder, which not only results in a complicated display but also the

connection of the combustion apparatus to each oscilloscope is difficult.

Further, the historical changes of combustion conditions of the engine can be understood by observing the result of each category of diagnosis, but as the result of diagnosis changes rapidly, it is not possible to observe the output result in time sequence.

Disclosure of the Invention

The present invention was made in light of the problems of prior art mentioned above. An object of the invention is to provide a combustion diagnosis system of an internal combustion engine, with which combustion diagnosis such as knock, misfire, flame quenching, and excessively high cylinder pressure is possible by single apparatus; computation processing is simple; and highly accurate result of diagnosis is obtainable without influenced by the changes in performance of the cylinder pressure detecting means due to the deterioration of cylinder pressure sensor, temperature drift, calibration deficiency, etc.

Another object of the invention is to provide a method and apparatus for diagnosing and controlling the combustion in an internal combustion engine, with which the accuracy of diagnosis using detected cylinder pressure is improved; stable operation of the engine is possible with the fuel ignition timing with which the occurrence of knock is evaded and maximum engine performance can be maintained; smooth operation of the engine is possible without exposed to the

influence by the combustion in the cylinder in which misfire or flame quenching is occurring by adjusting the combustion condition in the concerned cylinder to eliminate such abnormality; and further the occurrence of abnormality in any of the cylinder pressure detecting means is detected without delay and adjustment of combustion condition in the cylinder of which the cylinder pressure detecting means has become abnormal is made so that the function of the cylinder pressure detecting means can be recovered without stopping the engine.

A further object of the invention is to provide a combustion diagnosis system, with which the control of all cylinders can be performed smoothly without influenced by data transmitting wire break, noise, etc., when the diagnosis information such as misfire, flame quenching is sent from the combustion diagnosis apparatus to the combustion control apparatus and display.

A further object of the invention is to provide a combustion diagnosis system with which the number of wires corresponding to the number of cylinders suffices for the transmission of several kinds of information of combustion diagnosis of each of a plurality of cylinders between the combustion diagnosis apparatus and combustion control apparatus and the expense in time and effort for the connection of wires is largely saved.

A still further object of the invention is to provide a combustion diagnosis system for a multi-cylinder engine, with which always changing combustion conditions of all of the cylinders can be displayed in a manner easily understandable

to an operator.

A yet further object of the invention is to provide a combustion diagnosis system for a multi-cylinder engine, with which the waveform of cylinder pressure of each cylinder for the detailed investigation of abnormality in combustion in each cylinder can be effectively displayed without using oscilloscopes for all of the cylinders.

A further object of the invention is to provide a combustion diagnosis system, with which the result of each category of diagnosis can be displayed in a manner easily understandable to the operator even when the result of diagnosis judged by a combustion diagnosis apparatus for a multi-cylinder engine is changing rapidly.

To achieve these objectives, an apparatus for diagnosing and controlling combustion of an internal combustion engine according to the present invention comprises; a cylinder pressure detector for detecting the pressure in said combustion chamber; a means(step) for calculating the ratio of the maximum cylinder pressure P_p to the compression pressure or pressures P_0 at one or a plurality of predetermined crank angles in the compression stroke (P_p/P_0) which is the maximum pressure ratio, the pressures being determined based on the pressures detected by said cylinder pressure detector; a means(step) for comparing the maximum pressure ratio (P_p/P_0) with the pressure ratios predetermined stepwise for each category of diagnosis (hereafter referred to as threshold pressure ratio); and a means(step) for diagnosing the

condition of combustion such as the cylinder pressure condition in said combustion chamber by judging from the result of said comparison; and each of said threshold pressure ratios are changed as a function of the engine operating conditions including engine load, engine rotation speed, and inlet air temperature as necessary.

By the way, said means is suitable to be constructed in hardware or in software. A term "step" is added in parenthesis, for said means is constructed in soft ware in the embodiment described later.

To be more specific, the apparatus comprises following means(steps) :

a means(step) for calculating the ratio of the maximum cylinder pressure P_p to the compression pressure P_0 , P_s (hereafter represented by P_0) at one or a plurality of predetermined crank angles in the compression stroke (P_p/P_0), the pressures being determined based on the pressures detected by said cylinder pressure detector, and a means(step) which judges that the combustion is abnormal when said maximum pressure ratio (P_p/P_0) is equal to or exceeds the predetermined maximum permissible pressure ratio P_{p0} or when the number of operation cycles N_h when said maximum pressure ratio (P_p/P_0) is equal to or exceeds the predetermined pressure ratio P_{h1} (i.e., when $P_p/P_0 \geq P_{h1}$) is equal to or exceeds the permissible number N_{h0} (i.e., when $N_h \geq N_{h0}$);

a means (step) which judges that knock has occurred in the combustion chamber when the number of cycles S_n in which said maximum pressure ratio (P_p/P_0) is equal to or exceeds the

predetermined permissible pressure ratio of knock P_{h2} (i.e., when $P_p/P_0 \geq P_{h2}$) in a plurality of cycles in the past is equal to or exceeds the permissible number S_{n0} (i.e., when $S_n \geq S_{n0}$);

a means(step) which judges that misfire has occurred when said maximum pressure ratio P_p/P_0 is equal to or smaller than the predetermined minimum permissible pressure ratio P_n (i.e., when $P_p/P_0 \leq P_n$) and at the same time said combustion pressure ratio (P_1/P_0) is equal to or smaller than the predetermined permissible pressure ratio P_m of misfire (i.e., when $P_1/P_0 \leq P_m$);

a means(step) for calculating the ratio of the lower side pressure P_2 in the combustion stroke lower than said pressure P_1 at a predetermined crank angle in the combustion stroke to said pressure P_0 at a predetermined crank angle in the compression stroke P_2/P_0 ; and

a means(step) which judges that flame quenching has occurred when said maximum pressure ratio is equal to or smaller than the predetermined minimum permissible pressure ratio P_n (i.e., when $P_p/P_0 \leq P_n$), at the same time said combustion pressure ratio P_1/P_0 is equal to or smaller than the predetermined minimum permissible pressure ratio P_m (i.e., when $P_p/P_0 \leq P_m$) and the combustion pressure ratio P_2/P_0 is equal to or larger than the permissible pressure ratio P_{m1} (i.e., when $P_2/P_0 \geq P_{m1}$).

In the configuration described above, it is preferable that a means (step) is provided which judges the compression pressure P_0 is abnormal when said compression pressure P_0 at a predetermined crank angle in the compression stroke is equal to or lower than the predetermined permissible compression

pressure P_{c0} , (i.e., when $P_0 \leq P_{c0}$).

According to the invention, combustion diagnosis of detecting the occurrences of knock, misfire, excessively high maximum cylinder pressure, or flame quenching is performed by single combustion diagnosis apparatus 100 by carrying out diagnosis using pressure ratios based on the compression pressure at a predetermined crank angle in the compression stroke, so all of necessary combustion diagnoses can be performed with an apparatus of simple construction and low-cost.

As the combustion diagnosis is done using pressure ratios based on a compression pressure as described above, absolute values of cylinder pressures is unnecessary and normal diagnosis is maintained without reduction in accuracy even when the output level from the cylinder pressure detector totally decreases due to the deterioration, temperature drift, failed calibration, etc. of the cylinder pressure detector. Accordingly, the operation life of combustion diagnosis apparatus can be extended.

Further, combustion diagnosis with high accuracy is possible by using for combustion diagnosis the cylinder pressure signals of which filtration of only noise is done through a simple low-pass filter by removing triggers. Therefore, complicated processing such as the change of pass-band of the filter is unnecessary as has been with one of said prior arts, and the efficiency of operation of combustion diagnosis is enhanced.

Further, combustion diagnosis with high accuracy is possible by simple means (steps), as the combustion diagnosis is carried out directly by using only cylinder pressures detected.

Therefore, according to the embodiment, all of necessary combustion diagnoses such as knock, misfire, excessively high maximum cylinder pressure, and flame quenching are possible with simple equipment and simple manner, and the decrease in combustion performance of engine can be detected with high accuracy and without delay.

The present invention is characterized in that the pressure in the combustion chamber is detected, the pressure difference ΔP between the detected pressure P and reference pressure P_b which is the pressure at or before the beginning of compression including inlet air pressure ($\Delta P = P - P_b$) is calculated for every crank angle, and standardized pressure ratio which is the ratio of said pressure difference ΔP to the pressure difference ΔP_0 , i.e. $\Delta P / \Delta P_0$, ΔP_0 being the pressure difference between the pressure P_0 at one or a plurality of predetermined crank angle in the compression stroke and said reference pressure P_b ($\Delta P_0 = P - P_b$), is used for the diagnosis of the combustion conditions such as the condition of cylinder pressure in the combustion chamber.

As an apparatus suited for effecting said method of diagnosing and controlling combustion is proposed an apparatus for diagnosing and controlling combustion of an

internal combustion engine which is constituted such that fuel gas is mixed with air and burned in the combustion chamber, wherein are provided; a cylinder pressure detector for detecting the pressure in said combustion chamber, a crank angle detector for detecting crank rotation angles of the engine, a means(step) for calculating the pressure difference ΔP between detected cylinder pressure P and the reference pressure P_b at or before the beginning of compression including inlet pressure ($\Delta P = P - P_b$) from the cylinder pressure detected by said cylinder pressure detector for every crank angle, a means(step) for calculating standardized pressure ratio which is the ratio of said pressure difference ΔP to the pressure difference ΔP_0 , i.e. $\Delta P / \Delta P_0$, ΔP_0 being the pressure difference between the pressure P_0 at one or a plurality of predetermined crank angles in the compression stroke and said reference pressure P_b ($\Delta P_0 = P - P_b$), a means(step) for diagnosing the condition of combustion such as the cylinder pressure condition in said combustion chamber using said standardized pressure ratio $\Delta P / \Delta P_0$, and a combustion control apparatus for controlling the combustion condition of the engine on the basis of the result of the combustion condition diagnosis outputted from the combustion condition diagnosis means (step).

According to the invention, absolute cylinder pressure is not required for the diagnosis because standardized pressure ratio $\Delta P / \Delta P_0$ based on the pressure difference ΔP_0 between pressure P and the pressure P_b ($\Delta P_0 = P - P_b$), P_b being the pressure at or before the beginning of compression including inlet air pressure of which the fluctuation due to outside

conditions such as atmospheric condition is small during the operation of the engine, and normal diagnosis can be carried out maintaining the specified accuracy of diagnosis without reducing the accuracy even when the output level of the cylinder pressure detector is totally reduced or increased due to the deterioration thereof, temperature drift, calibration deficiency, etc.

The present invention is characterized in that the engine is stopped when said standardized cylinder pressure ratio $\Delta P / \Delta P_0$ at the maximum cylinder pressure P_p , that is the standardized maximum pressure ratio $\Delta P_p / \Delta P_0$, is equal to or exceeds the predetermined maximum permissible pressure ratio P_{p0} (i.e., when $\Delta P_p / \Delta P_0 \geq P_{p0}$), and for example, it is suitable to stop the engine when the pressure difference ΔP_0 at one or a plurality of predetermined crank angle is equal to or lower than a predetermined permissible compression pressure difference P_{c0} (i.e., when $\Delta P_0 \leq P_{c0}$).

It is also suitable that fuel (including the pilot fuel injected into the sub-chamber of a gas engine) ignition timing is retarded by a certain crank angle when said standardized maximum cylinder pressure ratio $\Delta P_p / \Delta P_0$ is equal to or exceeds the predetermined maximum reference pressure ratio P_{sh} (i.e., when $\Delta P_p / \Delta P_0 \geq P_{sh}$), and fuel ignition timing is advanced by a certain crank angle when said standardized maximum cylinder pressure ratio $\Delta P_p / \Delta P_0$ is equal to or below the predetermined minimum reference pressure ratio P_{s1} (i.e., when $\Delta P_p / \Delta P_0 \leq P_{s1}$).

In this case, as an apparatus suited for effecting said method of diagnosing and controlling combustion, said combustion diagnosis apparatus is provided with a means (step) for comparing the standardized maximum cylinder pressure ratio $\Delta P_p / \Delta P_0$ with predetermined maximum permissible pressure ratio P_{p0} , and said combustion control apparatus is provided with a stopping means (step) for activate an engine stopper to halt the operation of the engine when the result of comparison in the combustion diagnosis apparatus is $\Delta P_p / \Delta P_0 \geq P_{p0}$.

It is preferable in the invention that said combustion diagnosis apparatus is provided with a means (step) for comparing said standardized maximum pressure ratio $\Delta P_p / \Delta P_0$ with the maximum value P_{sh} of maximum reference pressure ratio and with the minimum value P_{s1} of maximum reference pressure ratio, and

said combustion control apparatus is provided with a means (step) for retarding the fuel ignition timing by a certain crank angle when the result of said comparison is $\Delta P_p / \Delta P_0 > P_{sh}$ and for advancing the ignition timing by a certain crank angle when the result of said comparison is $\Delta P_p / \Delta P_0 \leq P_{s1}$.

According to the invention, by stopping the engine by allowing the combustion control apparatus to activate the engine operation stopper when a diagnosis result has been outputted from the combustion diagnosis apparatus that the standardized maximum pressure ratio $\Delta P_p / \Delta P_0$ is equal to or exceeds the predetermined permissible maximum pressure ratio

P_{p0} , the detection of the excessive high maximum cylinder pressure and the action to deal with that can be taken exactly without delay. Therefore, engine breakage or reduction of engine durability due to the excessive high cylinder pressure can be prevented with reliability.

Further, when the standardized maximum pressure ratio $\Delta P_p / \Delta P_0$ is judged to be equal to or exceeds the maximum reference pressure ratio P_{sh} , the fuel ignition timing by a certain crank angle by the combustion control apparatus and when the standardized maximum pressure ratio $\Delta P_p / \Delta P_0$ is judged to be smaller than the maximum reference pressure ratio P_{sh} , the fuel ignition timing is advanced by a certain crank angle by the combustion control apparatus. Therefore, the cylinder pressure is maintained below the maximum reference pressure and the expected engine performance is maintained resulting in suppression of increased generation of NOx due to excessively high combustion temperature.

The method of diagnosing and controlling combustion according to the present invention is characterized in that the fuel ignition timing is retarded by a certain crank angle when said standardized maximum pressure ratio $\Delta P_p / \Delta P_0$ is equal to or exceeds the predetermined permissible pressure ratio P_{h2} of knock (i.e., when $\Delta P_p / \Delta P_0 \geq P_{h2}$).

For effecting said method of diagnosing and controlling combustion, the apparatus is composed such that said combustion diagnosis apparatus is provided with a means (step) for comparing said standardized maximum pressure ratio $\Delta P_p /$

ΔP_0 with the predetermined permissible pressure ratio P_{h2} of knock and judging that knock has occurred when said standardized maximum pressure ratio $\Delta P_p / \Delta P_0$ is equal to or exceeds said permissible pressure ratio P_{h2} of knock, and said combustion control apparatus is provided with a means (step) for retarding the fuel ignition timing by a certain crank angle upon receipt of judgement signal of the occurrence of knock.

According to the invention, if the result of diagnosis by the combustion diagnosis that the standardized maximum pressure ratio $\Delta P_p / \Delta P_0$ reaches the predetermined permissible value for knock, i.e. the maximum limit of maximum cylinder pressure ratio at which the engine performance is maintained at maximum while evading the occurrence of knock, the fuel ignition timing is retarded through the combustion control apparatus. As a result, the engine performance is controlled optimally to operate with high performance in the condition just before the occurrence of knock.

According to the method of diagnosing and controlling combustion of the invention, misfire is judged to have occurred in the combustion chamber and the fuel injection for the cylinder in which misfire is judged to have occurred is shut off when said standardized maximum pressure ratio $\Delta P_p / \Delta P_0$ is equal to or below the predetermined minimum permissible pressure ratio P_n of misfire (i.e., when $\Delta P_p / \Delta P_0 \leq P_n$).

As an apparatus for effecting the method of the invention, said combustion diagnosis apparatus is provided with a means (step) for comparing said standardized maximum pressure

ratio $\Delta P_p / \Delta P_0$ with the predetermined permissible pressure ratio of misfire and judging that misfire has occurred in the combustion chamber when said standardized maximum pressure ratio $\Delta P_p / \Delta P_0$ is equal to or smaller than the minimum permissible pressure ratio P_n of misfire, and said combustion control apparatus is provided with a means (step) for cutting off the fuel injection to the cylinder in which misfire has occurred upon receipt of judgement signal of the occurrence of misfire.

According to the invention, when a diagnosis result has been outputted from the combustion diagnosis apparatus that the number of continual cycles in which the standardized maximum pressure ratio $\Delta P_p / \Delta P_0$ reaches the predetermined permissible pressure ratio of misfire reaches the predetermined permissible number of continual cycles, the fuel injection to the concerned cylinder in which misfire has occurred is cut off.

Therefore, the occurrence of misfire is detected with reliability without delay and measures can be taken to deal with the situation, that is, to stop the fuel injection to the concerned cylinder, through which the operation of the other cylinders can be continued without influenced by the concerned cylinder.

The method of diagnosing and controlling combustion according to the present invention is characterized in that flame quenching is judged to have occurred and the fuel injection quantity for the cylinder in which flame quenching

is judged to have occurred is increased when said standardized maximum pressure ratio $\Delta P_p / \Delta P_0$ and a standardized combustion pressure ratio $\Delta P_1 / \Delta P_0$ in the combustion stroke are equal to or smaller than the minimum permissible pressure ratio P_n and permissible pressure ratio P_m of misfire respectively (i.e., when $\Delta P_p / \Delta P_0 \leq P_n$ and $\Delta P_p / \Delta P_0 \leq P_m$) and a combustion pressure ratio $\Delta P_2 / \Delta P_0$ is larger than permissible pressure ratio P_{m1} .

As the apparatus for effectuating the method of the present invention, the apparatus is composed such that said combustion diagnosis apparatus is provided with a means (step) for outputting a judgement signal of the occurrence of flame quenching in the combustion chamber when said standardized maximum pressure ratio $\Delta P_p / \Delta P_0$ and a standardized combustion pressure ratio $\Delta P_1 / \Delta P_0$ in the combustion stroke are smaller than the permissible minimum pressure ratio P_n and permissible pressure ratio P_m of flame quenching and at the same time combustion pressure ratio $\Delta P_2 / \Delta P_0$ is equal to or exceeds the permissible pressure ratio P_{m1} , and said combustion control apparatus is provided with a means (step) for increasing the fuel quantity injected to the cylinder in which flame quenching has occurred upon receipt of the occurrence of flame quenching.

According to the invention, when a diagnosis result has been outputted from the combustion diagnosis apparatus that said standardized maximum pressure ratio $\Delta P_p / \Delta P_0$ and combustion pressure ratio $\Delta P_1 / \Delta P_0$ are equal to or smaller than permissible minimum pressure ratio P_n and permissible pressure ratio of misfire P_m respectively, and that said

standardized combustion pressure ratio $\Delta P_2/\Delta P_0$ is equal to or larger than permissible pressure ratio of flame quenching P_{m1} , the fuel injection quantity to the concerned cylinder in which flame quenching has occurred or, for example, pilot fuel injection quantity in the case of a gas engine having sub-combustion chamber to be injected with pilot fuel, is increased. Thus, the occurrence of flame quenching is detected with reliability without delay and measures can be taken to deal with the situation, that is, to increase the quantity of fuel injection to the concerned cylinder, through which the continuation of misfire can be prevented and the operation of the other cylinders can be continued without influenced by the concerned cylinder.

In the method of the invention, by determining threshold values for diagnosing combustion as a function of engine operating conditions, threshold pressure ratios for diagnosis categories such as permissible maximum cylinder pressure ratio, permissible compression pressure ratio, permissible pressure ratio of knock, misfire, flame quenching can be changed according to detected engine load, engine rotation speed, inlet air temperature, etc.

Accordingly, the threshold values can be adjusted to match the engine operating conditions, and accurate combustion diagnosis can be effectuated.

It is preferable in the method of diagnosing and controlling combustion according to the present invention that when abnormality is detected concerning a cylinder pressure

detector which detects the pressure in combustion chamber and inputs it to the combustion diagnosis apparatus, the fuel ignition timing of the concerned cylinder of which the cylinder pressure detector is abnormal is retarded by a certain crank angle to a safety position for combustion through a combustion control apparatus which performs combustion control including the controlling of ignition timing and fuel injection quantity, and after said pressure detector is recovered by replacement or repair thereof, said combustion control apparatus is allowed to return to normal operation to restore the fuel ignition timing of the concerned cylinder to normal timing.

By the invention, when a diagnosis result has been outputted from the combustion diagnosis apparatus that the cylinder pressure detector is abnormal, the fuel injection timing of the concerned cylinder of which the pressure detector is abnormal is retarded by a certain crank angle to a safety range for combustion while leaving the abnormal state of the pressure detector as it is. After the pressure detector is recovered, the combustion diagnosis apparatus recovers automatically normal operation and allows the combustion control apparatus to operate normally to restore the normal injection timing of the concerned cylinder.

Therefore, when abnormality occurs in a cylinder pressure detector, the pressure detector is repaired or recovered while the injection timing of the concerned cylinder is adjusted to a safe timing for combustion, and after the recovery of the pressure detector, the normal combustion control is

recovered, so the abnormal pressure detector can be dealt with without halting the operation of the engine.

The method of diagnosing and controlling combustion of the present invention is characterized in that a plurality of kinds of abnormality are judged in a predetermined crank angle range in suction ~ combustion stroke, and when the condition not sufficing any one of the kinds of abnormality continues for a predetermined plurality of number of cycles i , the concerned cylinder pressure detector is judged to be abnormal.

Concretely, said steps comprises;

- (a) a step for judging whether the detected pressure by the cylinder pressure detector 1 is within the range $PTa \sim PTb$ or not during the whole crank angle of one cycle, (b) a step for judging whether the detected pressure is within the range PSb (permissible maximum inlet pressure) $\sim Psa$ (permissible minimum inlet pressure) or not in the suction stroke, (c) a step for judging whether crank angle $Ppang$ at the maximum pressure P_p is within the crank angle range corresponding to combustion range $Aa \sim Ab$ or not, and (d) a step for judging whether the standard deviation $Pb\sigma$ of P_b 's of past n cycles, pb being reference pressure at or before the beginning of compression including inlet air pressure, is smaller than predetermined value ϵ or not.

(b)

According to the invention, by judging in step (a) whether the detected pressure is within the range $PTa \sim PTb$ or not

during the whole crank angle of one cycle, the presence or absence of fundamental abnormality in the pressure detector can be judged. In step (b) is judged whether the cylinder pressure in the suction stroke is between the maximum permissible value PS_b and minimum permissible value PS_a , so the occurrence of drift due to the change-over-time of the detector can be detected in the condition of nearly constant suction pressure. Further, in step (c), as whether the crank angle $Ppang$ at the maximum cylinder pressure is within the crank angle range $Aa \sim Ab$ corresponding to the combustion range or not is judged, it can be ascertained if the cylinder pressure is detected without deviation in relation to crank angle or not. Further, in step (d), since whether the standard deviation of reference pressure at or before the beginning of compression for a plurality of cycles, the reference pressure being by its nature substantially constant, is within permissible value ϵ or not, misdiagnosis due to stationary noise can be evaded.

Furthermore, since the pressure detector is judged to be abnormal only after the state which do not suffice any one of the conditions (a) ~ (d) described above continues to occur for a plurality of times, the influence of instantaneous trigger noise can be neglected.

Therefore, according to the invention, abnormality in the pressure detector is judged through a plurality of detecting methods from various facets and moreover the detector is determined to be abnormal only after dubious phenomenon is detected for a plurality of times, so the abnormality can

be judged with high accuracy without misjudging owing to trigger pulse, etc. irrelevant to the abnormality of the pressure detector, resulting in smooth combustion diagnosis by the elimination of misjudgment.

The present invention is characterized in that there are provided a means(step) for calculating the pressure difference ΔP between detected cylinder pressure P detected for every crank angle in said combustion crank angle range and the reference pressure P_b at or before the beginning of compression including inlet pressure ($\Delta P = P - P_b$), a means(step) for calculating standardized cylinder pressure ratio which is the ratio of said pressure difference ΔP to the pressure difference ΔP_0 , i.e. $\Delta P / \Delta P_0$, ΔP_0 being the pressure difference between the pressure P_0 at one or a plurality of predetermined crank angle in the compression stroke and said reference pressure P_b ($\Delta P_0 = (P_0 - P_b)$), a combustion diagnosis apparatus provided with a pressure/analog voltage converting means(step) for outputting at least a part of the result of diagnosis as analog information when diagnosing the condition of combustion such as cylinder pressure condition in said combustion chamber using said standardized cylinder pressure ratio $\Delta P / \Delta P_0$, and a combustion control apparatus for controlling the combustion condition of the engine by reconvertng the analog information outputted from said combustion diagnosis apparatus to pressure information; and engine stopping or fuel ignition timing or the injection quantity of the pilot fuel and gas fuel is controlled based on the diagnosis result of the pressure information reconverted from said analog information.

It is suitable that the combustion is diagnosed on the basis of each threshold value determined for each diagnosis category information using said cylinder pressure ratio $\Delta P / \Delta P_0$ in said predetermined combustion crank angle range. To be more specific, it is suitable that said threshold values determined for every diagnosis category information are determined so that the level of each threshold decreases stepwise, and information of different diagnosis category can be judged in different threshold level, for example, that a pressure detection range is determined near the crank angle of maximum combustion pressure, the threshold for each diagnosis category information is P_{p0} and P_{h1} for abnormal P_{max} , P_{h2} for knock, P_n for misfire and flame quenching, and the level of each threshold value being decreased in orderly sequence of $P_n \leq P_{s1} \leq P_{sh} \leq P_{h2} \leq P_{h1} \leq P_{p0}$.

Signals of the result of diagnosis transmitted from the combustion diagnosis apparatus to the combustion control apparatus are composed of analog levels, and each analog level for each diagnosis category is determined to decrease stepwise so that the information of different category is able to be discriminated by the analog level on the combustion control apparatus side. Said analog levels for each of the diagnosis categories are determined so that the level for transmitting the information of diagnosis category of normal combustion state is positioned in the middle of the levels, the levels for transmitting the information of abnormal maximum cylinder pressure or compression pressure, etc., which are generally related to engine conditions as a whole,

are set to values in higher level range, and the levels for transmitting the information of misfire, flame quenching, abnormal sensor, a break in wire and so on, which are generally experienced in an individual cylinder, are set to values in lower level range. By determining each level like this, simple and reliable transmission of information is effectuated, and even if an analog level at the transition instant of analog level or erroneous information is read, critical malfunction of the control apparatus is evaded.

To be more specific, it is suitable that each of said analog levels, that is, Cp: the analog level for transmitting abnormal Pmax judgement, Ce: analog level for compression pressure judgement, Ck: analog level for knock judgement, Cq: analog level for flame judgement quenching, Cm: analog level for misfire judgement, Cx; analog level for abnormal sensor judgement, is determined to decrease stepwise in the orderly sequence of $Cp > Ce > Ck > Cq > Cm > Cx$.

It is suitable that, when the range of normal combustion pressure or pressure ratio of each cylinder, the pressure or pressure ratio being between the threshold for knock and that for flame quenching, is transmitted to the combustion control apparatus side in analog level, the pressure (pressure ratio) is converted in stepless analog level signal corresponding with the pressure (pressure ratio) and the steplessly controlled analog signal is transmitted to the combustion control apparatus side.

It is also suitable, when applying to a multi-cylinder engine, that a number of analog signal transmission wires

corresponding to the number of cylinders are connected between the combustion diagnosis apparatus and combustion control apparatus, the diagnosis result of each category are transmitted in serial order on each analog level determined to decrease in stepwise, and diagnosis category is judged or the combustion pressure or pressure ratio is judged based on the corresponding analog level on the combustion control apparatus side.

A knocking state which has been difficult to detect hitherto can be grasped indirectly by the ratio of pressure differences as a measure, and engine operation near knock limit is always possible, resulting in increased engine efficiency. The combustion diagnosis is not influenced by the change in temperature of the pressure sensor and abnormal combustion and abnormal pressure sensor such as a broken sensor or a break in wire can be detected without influenced by the drift due to the change over time of the pressure sensor.

The number of signal transmission wires between the combustion diagnosis apparatus and combustion control apparatus is reduced compared with the conventional method of connection, and if a break in wire occurs, the influence thereof is limited only to the concerned cylinder; besides, the broken wire is able to be identified, which has been impossible with conventional digital signal transmission wires, because the analog value on the wire becomes zero level which belongs to no category of diagnosis.

By adopting stepless control to effect feedback of the

deviation in pressure from the target value of cylinder pressure, and more carefully thought out control is possible, resulting in further increased engine efficiency.

For example, a stepless analog level is determined for normal combustion range in FIG.23(A) and FIG.23(B). The data of the result of diagnosis $\{P_{h2} \sim P_n\}$ is converted to analog information $\{Ck \sim Cq\}$ to be transmitted as a substitute for the diagnosis result, and it is reconverted to $\{P_{h2} \sim P_n\}$. By determining necessary increment or decrement ΔT of the injection timing for keeping the cylinder pressure ratio in the normal range, the injection timing of each cylinder is properly changed for each cycle.

The present invention is characterized in having a displaying apparatus for representing detected cylinder pressure-crank angle curve inputted to the combustion diagnosis apparatus, the displaying apparatus comprising

- a first ring memory provided on the diagnosis apparatus side for memorizing the cam top crank angle of a reference cam and the cylinder pressure-crank angle curve, and

- a second ring memory provided on the displaying apparatus side for memorizing the cylinder pressure-crank angle curve in a certain crank angle range of each cylinder and a display; and

- the first ring memory on the diagnosis side has a means(step) to start the program by an interrupt of the signal from the crank angle detector after the detection of the cam top crank angle of the reference cam and write in the cylinder pressure wave form, which indicates combustion condition, at

a certain interval of crank angle to the ring memory in the determined area corresponding to each cylinder, and

the pressure-crank angle curves of all cylinder are read out from the determined area of the second ring memory and these pressure curves are displayed on the display with the pressure curves shifted so that each curve does not overlaps.

It is suitable that the cylinder pressure-crank angle curves of all cylinders are written into the first ring memory on the diagnosis apparatus side in synchronization with the crank angle at the moment-to-moment detection of the pressure with the cylinder pressure detector(sensor), on the other hand, said cylinder pressure-crank angle curves of all cylinders are written in the second ring memory after the cam top crank angle of the next cycle after the previous cycle(720°) is completed, is detected, and the memorized pressure curves are represented on the display.

According to the invention, visualization of combustion condition changing moment-to-moment is possible on an oscilloscope (display), and the cylinder pressure-crank angle data overlapped with regard to time is easily recognizable. It becomes possible to observe pressure curves of a plurality of cylinders by transmitting the data to the displaying apparatus in serial order while diagnosing combustion.

Brief Description of the Drawings

FIG.1 is a diagrammatic representation showing the total

configuration of the combustion diagnosis system of a gas engine of an embodiment according to the present invention.

FIG.2 is a first example of control flowchart of the combustion diagnosis apparatus.

FIG.3 is a second example of control flowchart of the combustion diagnosis apparatus.

FIG.4 is a diagram showing the relation of cylinder pressure to crank angle of said gas engine.

FIG.5 is a diagrammatic representation showing the total configuration of the combustion diagnosis system of a gas engine of another embodiment according to the present invention.

FIG.6 is the control block diagram(1) of said embodiment.

FIG.7 is the control block diagram(2) of said embodiment.

FIG.8(A) is a diagram showing cylinder pressure in said embodiment, and FIG.8(B) is a diagram showing cylinder pressure in prior art.

FIG.9 is the flowchart (1) of said embodiment.

FIG.10(A) ~ FIG.10(F) each is the control-chart(1) for every item of the combustion diagnosis/control in said embodiment.

FIG.11(A) ~ FIG.11(G) each is the control-chart(2); charts of column (a) show fuel ignition timing and those of column (b) show fuel injection quantity.

FIG.12 is the flowchart (2) of said embodiment.

FIG.13 is the flowchart (3) of said embodiment.

FIG.14(A) ~ FIG.14(D) are diagrams showing fuel ignition timing and fuel injection quantity in said embodiment.

FIG.15 is an illustration explaining the working of the combustion diagnosis apparatus, combustion control apparatus, and gas engine.

FIG.16(A) is a diagram showing cylinder pressure curves of said gas engine(curves for explanation).

FIG.16(B) is a diagram explaining combustion diagnosis items and permissible value(threshold value) on cylinder pressure curves.

FIG.17(A) and FIG.17(B) are a flowchart when threshold value is varied and the curve(1) of variation of the threshold value respectively in said embodiment.

FIG.18(A) and FIG.18(B) are a flowchart when threshold value is varied and the curve(2) of variation of the threshold value respectively in said embodiment.

FIG.19 a flowchart in prior arts.

FIG.20 is a total block diagram of the combustion diagnosis system of gas engine of the embodiment according to the present invention in the case stepless control is done only in normal range and corresponds to FIG.7.

FIG.21 is a total control flowchart of the combustion diagnosis system of gas engine of the embodiment according to the present invention and corresponds to FIG.9 except that stepless control is done only in normal range.

FIG.22 is an illustration explaining the method of transmission of combustion diagnosis signals in analog form applied to the invention of FIG.20 and FIG.21.

FIG.23(A) is a graph showing totally the change of the value of analog-form signal for each of the categories of the result of combustion diagnosis, and FIG.23(B) is a graph partially enlarged.

FIG.24 is a cylinder pressure curve for explaining the detection of abnormality in the cylinder pressure detector.

FIG.25 is a representation showing the display of the results of the combustion diagnosis sent from the combustion diagnosis apparatus, in which the results are given for each cylinder number and each item of abnormality.

FIG.26 is a diagram showing the process of transmittal of cylinder pressures wave form from the combustion diagnosis apparatus side to the display side, in which an example in the case of a 4-cylinder engine is shown.

FIG.27 is a representation showing the configuration of data in the combustion diagnosis apparatus side and display side.

FIG.28 is the wave form recording flowchart (1) of said data configuration, which is the interrupt processing flowchart of crank angle of the combustion diagnosis apparatus side (data sending-out side).

FIG.29 is the wave form recording flowchart (2) of said data configuration, which is the main processing flowchart of the combustion diagnosis apparatus side (data sending-out side).

FIG.30 is the wave form recording flowchart (3) of said data configuration, which is the interrupt processing flowchart of data receiving of the display side (data receiving side).

FIG.31 is the wave form recording flowchart (3) of said data configuration, which is the main processing flowchart of the display side (data receiving side).

FIG.32 an illustration explaining the method of transmission of combustion diagnosis signals in digital form.

FIG.33(A) is a diagram showing cylinder pressure wave form

without noise superimposed thereon.

FIG.34(B) is a diagram showing cylinder pressure wave form with stationary noise superimposed thereon.

FIG.34 is the flowchart of detecting abnormality in cylinder pressure.

Best mode for embodiment of the Invention

Preferred embodiments of the present invention will now be detailed with reference to the accompanying drawings. It is intended, however, that unless particularly specified, dimensions, materials, relative positions and so forth of the constituent parts in the embodiments shall be interpreted as illustrative only not as limitative of the scope of the present invention.

In FIG.1 showing an embodiment, reference number 20 is the main body of a gas engine, 45 is a piston, 46 is a crankshaft, 44 is a combustion chamber, 41 is an inlet valve, 42 is an exhaust valve, and 43 is an exhaust pipe.

A gas injection device 10 is provided midway along an inlet pipe 9 for injecting fuel gas into the inlet air flowing in the inlet pipe 9 to be charged into the cylinder through said inlet valve 41.

Reference number 8 is a gas supply pipe for connecting a fuel gas tank (not shown) accommodating fuel gas and said gas

injection device 10. Reference number 7 is a gas supply electromagnetic valve provided at the entrance of said gas into said gas injection device 10. The opening of said valve is controlled under the control signal from an electromagnetic valve control device not shown in the drawing to adjust the flow of the gas fuel. The valve is also controlled under the control signal from a combustion control apparatus 200 mentioned later to be shut-off or adjusted of the opening.

Reference number 11 is an ignition device for torch-igniting the pilot fuel injected into a sub-chamber not shown in the drawing from a pilot fuel injection valve 0011 to promote the combustion of lean fuel gas/air mixture in the main combustion chamber.

The gas pressure in the combustion chamber, i.e. cylinder pressure is detected with a cylinder pressure detector 1, and crank angle is detected with a crank angle detector 2.

Reference number 100 is a combustion diagnosis apparatus composed of a noise filter 3, an amplifier 4 for amplifying the cylinder pressure signal passed through the noise filter, and a combustion diagnosis section 5.

Said noise filter is composed of a low-pass filter for filtering out the noise on the signal inputted from said cylinder pressure detector.

Said combustion diagnosis section 5 diagnoses the combustion condition in said combustion chamber 44 on the

basis of the cylinder pressure signal amplified by said amplifier 4 with the assistance of the crank angle signal from said crank angle detector.

Reference number 200 is a combustion control apparatus to which is inputted the signal of the result of diagnosis at said combustion diagnosis section 5, and which shuts off or controls the opening of said gas supply electromagnetic valve 7 and also controls the action of said ignition device 11.

The result of diagnosis by the combustion diagnosis section 5 is displayed on a displaying apparatus 6. It is suitable that an alarm which generates an alarm based on the result of diagnosis is connected to the combustion diagnosis apparatus 100.

On the operation of the gas engine of this configuration, torch-ignition is done in said ignition device 11, a gas valve(not shown) is unclosed and the fuel in a fuel gas tank(not shown) is supplied to said gas injection device 10, the fuel being adjusted in pressure by a gas pressure adjusting device(not shown). By the opening of said gas supply valve 7, the fuel is injected into the air flowing through the gas injection device 10 provided midway along said inlet pipe 9 to be mixed with the flowing air. The mixture is introduced into the combustion chamber 44 through the inlet valve 41 and ignited by the flame spouting from said ignition device 11 to be burned in the combustion chamber 44.

The working of the combustion diagnosis apparatus will be

explained below.

The gas pressure in the combustion chamber 44 detected by said cylinder pressure detector 1 is inputted to the noise filter 3 composed of a super low-pass filter in the combustion diagnosis apparatus 100, high frequency noises are filtered at the noise filter 3, and the cylinder pressure signal smoothed through the filtration is amplified by the amplifier 4 to be inputted to said combustion diagnosis section 5.

To the combustion diagnosis section 5 is also inputted the crank angle signal from said crank angle detector 2.

Next, a first example of combustion diagnosis operation by the combustion diagnosis apparatus 100 will be explained with reference to the first example of combustion control flowchart shown in FIG.2 and cylinder pressure curve shown in FIG.4.

The cylinder pressure-crank angle curve as shown in FIG.4 is obtained in the combustion diagnosis section 5 from the cylinder pressure inputted from the cylinder pressure detector 1 and the crank angle inputted from the crank angle detector 2.

Curve A in FIG.4 is a cylinder pressure curve when the combustion is normal.

First the compression pressure P_0 at a predetermined crank angle in the compression stroke shown in FIG.4 is compared

in a compression pressure judging means(step) with the predetermined permissible compression pressure P_{c0} which is the minimum permissible pressure in the compression stroke, and it is judged that the compression pressure P_0 is abnormally low compared to the normal value due to troubles such as gas leakage or mechanical troubles when the pressure P_0 is equal to or lower than the permissible compression pressure P_{c0} , i.e. when $P_0 \leq P_{c0}$ (E1). Curve E in FIG.4 is a cylinder pressure curve when the compression pressure is abnormally low.

Next the ratio of the maximum cylinder pressure P_p to said compression pressure P_0 at a predetermined crank angle in the compression stroke P_p/P_0 is calculated and the calculated maximum pressure ratio P_p/P_0 is compared in a maximum cylinder pressure judging means(step) with the predetermined permissible maximum pressure ratio P_{p0} which is the maximum permissible maximum pressure ratio, and it is judged that the maximum cylinder pressure is abnormally high compared to the design value(normal value) when said calculated maximum pressure ratio P_p/P_0 is equal to or exceeds said permissible maximum pressure ratio P_{p0} , i.e. when $P_p/P_0 \geq P_{p0}$ (E2) or when the number of operation cycles N_h in which said maximum pressure ratio P_p/P_0 is equal to or exceeds the predetermined pressure ratio P_{h1} , i.e. when $P_p/P_0 \geq P_{h1}$ (E3) is equal to or exceeds the permissible number N_{h0} , i.e. when $N_h \geq N_{h0}$ (E4).

Then it is judged by a knock judging means(step) that knock is occurring in the combustion chamber 44 when the number of cycles S_n in which said maximum pressure ratio P_p/P_0 is equal to or exceeds the predetermined permissible pressure ratio

of knock P_{h2} , i.e. when $P_p/P_0 \geq P_{h2}$ (E5) in a plurality of past cycles before the time point of judgement is equal to or exceeds the permissible number S_{n0} , i.e. when $S_n \geq S_{n0}$ (E6). Curve B in FIG.4 is a cylinder pressure curve when knock has occurred.

Then, in the misfire judging means (step), when said maximum pressure ratio P_p/P_0 is equal to or smaller than the predetermined minimum permissible pressure ratio P_n , i.e. when $P_p/P_0 \leq P_n$ (E7), the combustion pressure ratio P_1/P_0 , which is the ratio of the pressure P_1 at a predetermined crank angle in the combustion stroke to the pressure P_0 at a predetermined crank angle in the compression stroke shown in FIG.4, is calculated, and when the pressure ratio P_1/P_0 is equal to or smaller than the predetermined permissible pressure ratio P_m of misfire, i.e. when $P_1/P_0 \leq P_m$ (E8), misfire is judged to be occurring.

In this case, a predetermined crank angle θ_1 at which pressure P_1 is detected is determined at the position of crank angle symmetrical with regard to the top dead center to the position of a predetermined crank angle θ_0 at which pressure P_0 is detected, as shown in FIG.4. Curve C in FIG.4 is a cylinder pressure curve when misfire has occurred.

Next, a second example of combustion diagnosis by the combustion diagnosis section 5 will be explained with reference to the second example of combustion control flowchart shown in FIG.3 and cylinder pressure curve shown in FIG.4.

The second example of combustion diagnosis is the one added to the first example shown in FIG.2 with a process of judging the occurrence of flame quenching.

In the flame quenching judging means(step) of the second example, when the maximum cylinder pressure ratio P_p/P_0 is equal to or smaller than the minimum permissible pressure ratio P_n , i.e. when $P_p/P_0 \leq P_n$ (F7) and at the same time the combustion pressure ratio P_1/P_0 is equal to or smaller than the predetermined permissible pressure ratio P_m of misfire, i.e. when $P_1/P_0 \leq P_m$ (F8), lower pressure side combustion pressure ratio P_2/P_0 , which is the ratio of the lower side pressure P_2 lower than said pressure P_1 at a predetermined crank angle in the combustion stroke to the pressure P_0 at a predetermined crank angle in the compression stroke, is calculated, and when the lower pressure side combustion pressure ratio P_2/P_0 is equal to or larger than the permissible pressure ratio P_{m1} of flame quenching, i.e. when $P_2/P_0 \geq P_{m1}$ (F9), flame quenching is judged to be occurring. Curve D in FIG.4 is a cylinder pressure curve when flame quenching has occurred.

When the lower pressure side pressure ratio P_2/P_0 is smaller than the permissible pressure ratio P_{m1} of flame quenching, it is judged that the combustion chamber 44 is in the state misfire has occurred.

Thus, misfire can be discriminated from flame quenching by calculating combustion pressure ratios P_1/P_0 and P_2/P_0 using

higher pressure side pressure P_1 and lower pressure side pressure P_2 at two crank angles respectively, and comparing each combustion pressure with the permissible pressure ratio P_m of misfire and permissible pressure ratio P_{m1} of flame quenching respectively.

When knock, misfire, excessively high maximum cylinder pressure, or flame quenching is judged to be occurring by the diagnosis at the combustion diagnosis section 5, the signal of the result of diagnosis is sent to the combustion control apparatus 200. The control apparatus 200 shuts off or controls the opening of the gas supply electromagnetic valve 7 and controls the ignition device 11. The contents of the result of diagnosis are displayed on the displaying apparatus 6.

According to the embodiment, combustion diagnosis of detecting the occurrences of knock, misfire, excessively high maximum cylinder pressure, or flame quenching is performed by a single combustion diagnosis apparatus 100 by carrying out diagnosis using pressure ratios based on the compression pressure at a predetermined crank angle in the compression stroke, so all of necessary combustion diagnoses can be performed with an apparatus of simple construction and low-cost.

As the combustion diagnosis is done using pressure ratios based on a compression pressure as described above, absolute values of cylinder pressures is unnecessary and normal diagnosis is maintained without reduction in accuracy even when the output level from the cylinder pressure detector 1

totally decreases due to the deterioration, temperature drift, failed calibration, etc. of the cylinder pressure detector 1. Accordingly, the operation life of combustion diagnosis apparatus can be extended.

Further, combustion diagnosis with high accuracy is possible by using for combustion diagnosis cylinder pressure signals of which only the filtration of noise is done through a simple low-pass filter. Therefore, complicated processing such as the change of pass-band of the filter is unnecessary as has been with one of the prior arts, and the efficiency of operation of combustion diagnosis is enhanced.

Further, combustion diagnosis with high accuracy is possible by simple means(steps), as the combustion diagnosis is carried out directly by using only cylinder pressures detected.

Therefore, according to the embodiment, all of necessary combustion diagnoses such as knock, misfire, excessively high maximum cylinder pressure, and flame quenching are possible with simple equipment and simple manner, and the decrease in combustion performance of engine can be detected with high accuracy and without delay.

In FIG.5 showing another embodiment of the present invention, reference number 20 is the main body of a gas engine, 45 is a piston, 46 is a crankshaft, 44 is a combustion chamber, 41 is an inlet valve, 42 is an exhaust valve, and 43 is an exhaust pipe.

A gas injection device 10 is provided midway along an inlet pipe 9 for injecting fuel gas into the inlet air flowing in the inlet pipe 9 to be charged into the cylinder through said inlet valve 41. Reference number 8 is a gas supply pipe for connecting a fuel gas tank (not shown) accommodating fuel gas and said gas injection device 10. Reference number 7 is a gas supply electromagnetic valve provided at the entrance of said gas into said gas injection device 10. The opening of said valve is controlled under the control signal from an electromagnetic valve control device not shown in the drawing to adjust the flow of the gas fuel. The valve is also controlled under the control signal from a combustion control apparatus 200 mentioned later to be shut-off or adjusted of the opening.

Reference number 11 is an ignition device for torch-igniting the pilot fuel injected into a sub-chamber not shown in the drawing from a pilot fuel injection valve 0011 to promote the combustion of lean fuel gas/air mixture in the main combustion chamber.

The construction of the engine proper described above is the same as that of the first embodiment.

The gas pressure in the combustion chamber, i.e. cylinder pressure is detected with a cylinder pressure detector 1, and crank angle is detected with a crank angle detector 2.

Reference number 100 is a combustion diagnosis apparatus.

The signal of cylinder pressure detected by the cylinder pressure detector 1 and the signal of crank angle detected by the crank angle detector are inputted to the combustion diagnosis apparatus 100, which carries out the diagnosis of the combustion condition in the combustion chamber 44 on the basis of the cylinder pressure signal with the assistance of the crank angle signal.

Reference number 30 is a generator driven by the gas engine 20, 36 is a load detector for detecting the load of the gas engine 20 (load of the generator 30), 32 is a cam top detector for detecting the crank angle at which the cam is at top position for a selected cylinder of the gas engine 20 (the cam may be inlet or exhaust cam). The signal of the load of the gas engine from the load detector 32 and the signal of the cam top crank angle from the cam top detector are inputted to the combustion diagnosis apparatus 100.

Reference number 200 is a combustion control apparatus which controls the fuel injection quantity to be injected from the gas injection device 10 by shutting off or adjusting the openings of the gas supply electromagnetic valve 7 according to a signal 34 of diagnosis result and at the same time controls the injection timing and quantity of the pilot fuel injected from the pilot fuel injection valve 0011 into the ignition device 11 according to a control signal 33, and thus the fuel injection timing and quantity (the fuel injected from the gas injection device and that injected from the pilot fuel

injection valve are together referred to as fuel hereafter). The result of diagnosis by the combustion diagnosis apparatus 100 is displayed on a displaying apparatus 6. It is suitable that an alarm which generates an alarm based on the result of diagnosis is connected to the combustion diagnosis apparatus 100.

The working of the combustion diagnosis apparatus 100 and combustion control apparatus 200 will be explained below.

The gas pressure in the combustion chamber 44, i.e. the pressure signal is inputted to the combustion diagnosis apparatus 100 and the high frequency component is removed by the noise removing filter (not shown in the drawing) to be reduced to an averaged pressure signal without fluctuation in voltage. On the other hand, to the combustion diagnosis apparatus 100 has been inputted the engine crank angle signal from the crank angle detector 2, the engine load signal from the load detector 36, and cam top signal from the cam top detector 32. In FIG.6 and FIG.7, the cylinder pressure signals of a plurality of cylinders, crank angle signal, cam top crank angle signal, and load signal are inputted continuously to the combustion diagnosis apparatus 100, the combustion is diagnosed in the apparatus 100 based on the input signals, and the result of the diagnosis is inputted moment-to-moment to the combustion control device 200.

The combustion control device 200 outputs the fuel ignition time control signal to the engine 20 as shown in FIG.6 or the fuel ignition time control signal and fuel injection

quantity control signal to the engine 20 as shown FIG.7 so as the engine to be controlled to be operated in the combustion condition judged to be changed to according to the result of the result of the diagnosis or to be halted as necessary.

In FIG.6 and FIG.7, the combustion diagnosis apparatus 100 comprises a single CPU and the combustion control apparatus 200 comprises a double CPU so that, even when the combustion diagnosis apparatus 100 does not work due to run away or so, the control of ignition timing and fuel injection quantity of each cylinder is performed by independent operation of the CPU in the combustion control apparatus 200, while ceasing the function of the combustion diagnosis apparatus 100.

The detected data of the pressure in the cylinder sent from the cylinder pressure detector 1 is processed in the combustion diagnosis apparatus 100 as follows.

The pressure signal shown in FIG.8(A) and FIG.8(B) by line Z is evaluated on the basis of the reference pressure P_b which is the cylinder pressure at or before the beginning of compression, the pressure being about the same as the inlet pressure when the inlet valve 41 and exhaust valve 42 are open, and a difference ΔP between the detected pressure P and said reference pressure P_b ($\Delta P = P - P_b$) is calculated for every crank angle inputted from the crank angle detector.

A standardized cylinder pressure ratio $\Delta P / \Delta P_0$, where ΔP_0 is the difference of the cylinder pressure at a predetermined crank angle in the compression stroke and said

reference pressure P_b , is calculated, and combustion diagnosis is done using said standardized pressure ratio $\Delta P / \Delta P_0$.

The cylinder pressure signal shown in FIG.8(A) and (B) may be drifted upward or down ward as shown by line Z_1 or Z_2 in the drawings due to the difference in thermal expansion of the component of the pressure detector 1 by the change in the ambient temperature, deterioration with time of the detector 1, etc.

However, in the past, the absolute value of the pressure signal P_0 and P_p was adopted as cylinder pressure data as shown in FIG.8(B), so errorneous combustion diagnosis was resulted when the output level of the pressure detector 1 totally decreased or increased.

On the contrary, according to the embodiment of the present invention shown in FIG.8(A), the difference ΔP between the concerned cylinder pressure P and the reference pressure P_b ($\Delta P = P - P_b$), P_b being the cylinder pressure at or before the beginning of compression including the inlet pressure which is small in fluctuation due to the outside condition such as the atmospheric condition during engine operation, and combustion diagnosis is done on the basis of the standardized cylinder pressure ratio $\Delta P / \Delta P_0$, so the absolute values of the cylinder pressure are not required.

The combustion diagnosis using said standardized cylinder pressure ratio makes it possible to diagnose maintaining

desired accuracy without decreasing the accuracy even when the output level of the cylinder pressure detector decreases totally due to the deterioration of the pressure detector, temperature drift, calibration failure, and so on, or the level increases totally due to other reasons.

Next, the working of the combustion diagnosis apparatus 100 will be explained with reference to the control flowchart shown in FIG.9 and cylinder pressure-crank angle diagram shown in FIG.16(A).

The data of cylinder pressure-crank angle diagram as shown in FIG.16(A) is inputted in the combustion diagnosis apparatus 100 from the cylinder pressure detector 1 and crank angle detector 2. Curve A in FIG.16(A) is a cylinder pressure curve when the combustion in the cylinder is normal.

Referring to FIG.9, whether the sensor is abnormal or not (S01) is determined according to the flowchart of FIG.34 in which whether the sensor is normal or abnormal is judged. If the sensor is abnormal, an action of changing the detector or other appropriate action must be taken. If the sensor is normal, the flow proceeds to cylinder pressure diagnosis steps.

The pressure difference $\Delta P (=P - P_b)$, which is the difference of detected cylinder pressure P and the reference pressure P_b as cited above is calculated for each crank angle inputted from the crank angle detector 2, and a standardized pressure ration $\Delta P / \Delta P_0$ which is the ratio of the pressure difference

ΔP to the pressure difference ΔP_0 which is the difference of the cylinder pressure P_0 at a predetermined crank angle and the reference pressure P_b mentioned before, ($\Delta P_0 = P_0 - P_b$).

Then, the pressure difference ΔP_0 is compared with the minimum permissible value P_{c0} for ΔP_0 , and when $\Delta P_0 \leq P_{c0}$, the compression pressure P_0 is judged to be abnormally low (S1). Curve E in FIG.16(A) is a cylinder pressure diagram when compression pressure P_0 is abnormally low.

Then, standardized maximum pressure ratio $\Delta P_p / \Delta P_0$ is compared with the maximum permissible pressure ratio P_{p0} , and when $\Delta P_p / \Delta P_0 \geq P_{p0}$ (S2), or when the number N_h of cycles operated under the condition of $\Delta P_p / \Delta P_0 \geq P_{h1}$, where P_{h1} is a predetermined pressure ratio lower than a predetermined pressure ratio P_{p0} , is equal to or exceeds the permissible number N_0 , that is, when $N_h \geq N_0$ (S4), the maximum pressure is judged to be abnormally high.

Then, in the knock judging means(step), it is judged that knock is occurring in the combustion chamber 44 when the number of cycles S_n in which said standardized maximum pressure ratio $\Delta P_p / \Delta P_0$ is equal to or exceeds the predetermined permissible pressure ratio of knock P_{h2} , i.e. when $\Delta P_p / \Delta P_0 \geq P_{h2}$ (S5) in a plurality of past cycles before the time point of judgement is equal to or exceeds the permissible number S_{n0} , i.e. when $S_n \geq S_{n0}$ (S6). Curve B in FIG.16(A) is a cylinder pressure curve when knock has occurred.

Then, in the misfire judging means(step), when said

standardized maximum pressure ratio $\Delta P_p / \Delta P_0$ is equal to or smaller than the predetermined minimum permissible pressure ratio P_n , i.e. when $\Delta P_p / \Delta P_0 \leq P_n$ (S7), a standardized combustion pressure ratio $\Delta P_1 / \Delta P_0$, which is the ratio of the pressure difference ΔP_1 at a predetermined crank angle in the combustion stroke to the pressure difference ΔP_0 at a predetermined crank angle in the compression stroke shown in FIG.16(A), is calculated, and when the pressure ratio $\Delta P_1 / \Delta P_0$ is equal to or smaller than permissible pressure ratio P_m of misfire, i.e. when $\Delta P_1 / \Delta P_0 \leq P_m$ and, as mentioned later, a standardized pressure ratio $\Delta P_2 / \Delta P_0$ concerning pressure difference ΔP_2 in the lower pressure side lower than ΔP_1 is equal to or smaller than permissible pressure ratio P_{m1} , i.e. when $\Delta P_2 / \Delta P_0 \leq P_{m1}$ (S9), misfire is judged to be occurring in the combustion chamber 44.

In this case, the predetermined crank angle θ_1 at which pressure P_1 is detected is determined at the position of crank angle symmetrical with regard to the top dead center to the position of the predetermined crank angle θ_0 at which pressure P_0 is detected, as shown in FIG.16(A). The predetermined crank angle θ_2 at which pressure P_2 is detected is determined at the position of crank angle symmetrical with regard to the top dead center to the position of the predetermined crank angle θ_b at which reference pressure P_b is detected, as shown in FIG.16(A). Curve C in FIG.16(A) is a cylinder pressure curve when misfire has occurred.

Then, in the flame quenching judging means(step), when the standardized maximum pressure ratio $\Delta P_p / \Delta P_0$ is equal to or

smaller than the minimum permissible pressure ratio P_n , i.e. when $P_p/P_0 \leq P_n$ (S7) and at the same time the standardized combustion pressure ratio $\Delta P_1/\Delta P_0$ is equal to or smaller than the predetermined permissible pressure ratio P_m of misfire, i.e. when $\Delta P_1/\Delta P_0 \leq P_m$ (S8) and further the lower pressure side standardized combustion pressure ratio $\Delta P_2/\Delta P_0$ is equal to or larger than the permissible pressure ratio P_{m1} of flame quenching, i.e. when $\Delta P_2/\Delta P_0 \geq P_{m1}$ (S9), flame quenching is judged to be occurring. Curve D in FIG.16(A) is a cylinder pressure curve when flame quenching has occurred.

When said lower pressure side standardized pressure ratio $\Delta P_2/\Delta P_0$ is smaller than the permissible pressure ratio P_{m1} (S9), misfire is judged to be occurring in the combustion chamber 44, as mentioned before.

Therefore, misfire can be discriminated from flame quenching by calculating standardized combustion pressure ratios $\Delta P_1/\Delta P_0$ and $\Delta P_2/\Delta P_0$ using higher pressure side pressure P_1 and lower pressure side pressure P_2 at two crank angles respectively, and comparing each combustion pressure with the permissible pressure ratio P_m of misfire and permissible pressure ratio P_{m1} of flame quenching respectively.

When the combustion is normal, i.e. when $\Delta P_p/\Delta P_0 > P_n$ and the standardized maximum pressure ratio $\Delta P_p/\Delta P_0$ is equal to or exceeds the predetermined maximum reference pressure ratio P_{sh} , i.e. when $\Delta P_p/\Delta P_0 \geq P_{sh}$ (S10), the maximum cylinder pressure is judged to be higher than reference value (permissible maximum pressure).

When the standardized maximum pressure ratio $\Delta P_p / \Delta P_0$ is equal to or smaller than the predetermined minimum value of maximum pressure ratio P_{s1} , i.e. when $\Delta P_p / \Delta P_0 \leq P_{sh}$ (S11), the maximum cylinder pressure is judged to be lower than reference value.

Fig.16(B) shows schematically, by scaling as $\Delta P_0 = 1$, the maximum pressure difference ΔP_p and permissible values P_{p0} , P_{h1} , P_{h2} , P_n , P_m , P_{m1} , P_{sh} , P_{s1} .

As can be recognized in Fig.16(B), the threshold value P_{p0} , P_{h1} for the maximum pressure, threshold value P_{h2} for knock, threshold value P_n for misfire and flame quenching are such that $P_n \leq P_{s1} \leq P_{sh} \leq P_{h2} \leq P_{h1} < P_{p0}$. Each of these threshold values may be changed as a function of engine load or engine rotation speed or engine operating conditions including inlet air temperature.

Next, the result of combustion diagnosis by the combustion diagnosis apparatus 100 and the work of the combustion control apparatus 200 based on the result of the diagnosis will be explained with reference to FIG.10(A) ~ FIG.10(F), FIG.11(A) ~ FIG.11(G), FIG.12, and FIG.13.

First, when it is diagnosed by the combustion diagnosis apparatus 100 that the maximum cylinder pressure P_p is abnormally high with the result of $\Delta P_p / \Delta P_0 \geq P_{p0}$ or that the compression pressure P_c is abnormally low with the result of $\Delta P_0 \leq P_{c0}$, the combustion control apparatus 200 causes the

activation of the engine stopper to shut down the engine 20 (FIG.10(A), FIG.11(A), step D1 and D2 of FIG.12 ~ FIG.13).

Therefore, the proper step to deal with the result can be taken accurately without delay, and engine breakage or the reduction of engine durability due to excessively high maximum cylinder pressure P_p is prevented with certainty and continuation of failed combustion due to abnormally reduced compression pressure P_c is prevented.

Then, when it is diagnosed by the combustion diagnosis apparatus 100 that knock has occurred with the result of $\Delta P_p / \Delta P_0 \geq P_{h2}$, the combustion control apparatus 200 allows the fuel injection timing to be retarded by a certain crank angle α (FIG.10(B), FIG.11(B), step D5 and D11 of FIG.12 ~ 13).

Accordingly, the occurrence or continuation of knock can be prevented positively without delay and fluctuations in combustion condition is suppressed. As a result, the engine can be controlled to operate in the high performance range just before knock occurs.

Then, when it is diagnosed by the combustion diagnosis apparatus 100 that the cylinder pressure detector 1 does not work properly, the combustion control apparatus 200 allows the fuel supply to the concerned cylinder to be shut off or retard the ignition timing to be retarded to that with which the engine can be operated safely (FIG.10(F), FIG.11(G), step D4 and D10 of FIG.12 ~ FIG.13).

Then, when it is diagnosed by the combustion diagnosis apparatus 100 that the maximum cylinder pressure is too high, the combustion control apparatus 200 allows the fuel ignition timing to be retarded with a rate of a certain crank angle (ΔT_h) per unit time (FIG.10(C), FIG.11(C), step D6 and D12 of FIG.12 ~ FIG.13).

When the standardized maximum pressure ratio becomes lower than the reference maximum pressure ratio, the combustion control apparatus allows the fuel injection timing to be advanced with a rate of a certain crank angle (ΔT_l) per unit time (FIG.10(E), FIG.11(E), step D7 and D13 of FIG.12 ~ FIG.13).

As a result, the maximum pressure is always maintained in the range of the reference maximum pressure, the engine performance is maintained at desired one, and at the same time the increase of generation of NOx due to excess elevation of combustion temperature is suppressed.

Then, when it is diagnosed by the combustion diagnosis apparatus 100 that misfire is occurring, the combustion control apparatus 200 allows to shut off the fuel injection of the concerned cylinder in which misfiring is occurring (FIG.10(F), FIG.11(G), step D3 and D10 of FIG.12 ~ FIG.13).

As a result of shutoff of the fuel injection of the cylinder in which misfire has occurred, the smooth operation of other cylinders can be continued without influenced by the misfire in the concerned cylinder.

Then, when it is diagnosed by the combustion diagnosis apparatus 100 that flame quenching is occurring, the combustion control apparatus 200 allows the fuel injection to the concerned cylinder in which flame quenching has occurred to be increased (FIG.11(F), step D04 and D011 of FIG.13).

As a result of increasing the fuel injection to the cylinder in which flame quenching has occurred, the continuation of the flame quenching is prevented and other cylinders can be operated smoothly without otherwise continued flame quenching of the concerned cylinder.

As has been described in the foregoing, according to the embodiment, combustion diagnosis by the combustion diagnosis apparatus 100 and control of combustion by the combustion control apparatus 200 in response to the result of the diagnosis can always be done during the operation of the engine. In FIG.14A) ~ FIG.14(D) are shown the changes of the fuel injection timing and fuel injection quantity with time when the combustion is controlled by the combustion control apparatus 200 on the basis of the result of the diagnosis by the combustion diagnosis apparatus 100.

Next, FIG.15 shows the working state of the combustion diagnosis apparatus 100, combustion control apparatus 200 and gas engine 20. When a diagnosis result is outputted from the combustion diagnosis apparatus 100 showing abnormality of a cylinder pressure sensor 1, this sensor is stopped to

diagnose the combustion by the combustion control apparatus 200, and the apparatus 200 allows the ignition timing to be retarded by a certain crank angle to bring it to a safety range while leaving the abnormal state of the cylinder pressure sensor as it is.

After the failed cylinder pressure sensor 1 is recovered, the combustion diagnosis apparatus 100 and combustion control apparatus 200 restore normal operation and the ignition timing of the concerned cylinder is recovered to the normal timing.

Therefore, when abnormality occurs in a cylinder pressure sensor 1, the sensor is recovered while adjusting the fuel ignition timing and fuel injection quantity to deal with the abnormality, and after the recovery of the failed sensor, the normal control of the combustion of the concerned cylinder is effected. Thus, the occurrence of abnormality in the cylinder pressure sensor 1 can be coped with without halting the operation of the engine.

Next, changing operation of threshold value for combustion diagnosis in the combustion diagnosis apparatus 100 will be explained with reference to FIG.17(A), FIG.17(B), FIG.18(A), and FIG.18(B).

Permissible maximum pressure ratio P_{p0} (threshold value) of the maximum cylinder pressure is determined in the combustion diagnosis apparatus 100 as a function of engine load W ($P_{p0} = f(W)$ as shown in FIG.17(A)), a relation between them being shown in FIG.17(B) for example.

In FIG.17(A), when the engine load detected by the load detector 36 is inputted, the standardized maximum pressure ratio $\Delta P_p / \Delta P_0$ is compared with the permissible maximum pressure ratio P_{p0} (threshold value) determined in accordance with engine load W , and it is judged that, if $\Delta P_p / \Delta P_0 \geq P_{p0}$ the combustion is abnormal, if $\Delta P_p / \Delta P_0 < P_{p0}$ the combustion is normal.

Permissible maximum pressure ratio P_{p0} (threshold value) of the maximum cylinder pressure is determined in the combustion diagnosis apparatus 100 as a function of engine rotation speed N ($P_{p0} = f(N)$ as shown in FIG.18(A)), a relation between them being shown in FIG.17(B) for example.

In FIG.18(A), when the engine rotation speed N detected through the crank angle detector 2 is inputted, the standardized maximum pressure ratio $\Delta P_p / \Delta P_0$ is compared with the permissible maximum pressure ratio P_{p0} (threshold value) determined in accordance with engine rotation speed N , and it is judged that, if $\Delta P_p / \Delta P_0 \geq P_{p0}$ the combustion is abnormal, if $\Delta P_p / \Delta P_0 < P_{p0}$ the combustion is normal.

Permissible maximum pressure ratios P_{p0} (threshold values) are determined as a function of engine operating conditions including inlet air temperature, and the combustion is judged similarly as mentioned above.

Other than said permissible maximum pressure ratio P_{p0} (threshold value), the maximum value P_{sh} and minimum value

P_{s1} for reference maximum pressure ratio, permissible compression pressure difference P_{c0} , permissible pressure ratio for knock P_{h2} , permissible minimum pressure ratio for misfire P_n , permissible pressure ratio for misfire P_m , and permissible pressure ratio for flame quenching P_{m1} , etc. may be determined as a function of engine load W , engine rotation speed N , and engine operating conditions including inlet air temperature respectively.

According to the embodiment, threshold values such as permissible maximum pressure ratios P_{p0} (threshold values), the maximum value P_{sh} and minimum value P_{s1} for reference maximum pressure ratio, permissible compression pressure difference P_{c0} , permissible pressure ratio for knock P_{h2} , permissible minimum pressure ratio for misfire P_n , permissible pressure ratio for misfire P_m , and permissible pressure ratio for flame quenching P_{m1} are not constant in diagnosing the combustion but they are changed according to changes in engine operating conditions and the combustion is controlled per cylinder.

The reference values (threshold values) can be adjusted to the values appropriate to the engine operating condition and the combustion is controlled for each cylinder, so that the combustion diagnosis can be effected always with high accuracy. In FIG.6, FIG.7, and FIG.20 about that is explained later, reference numeral 100a is an ON-OFF switch for allowing-or-not the actuation of the combustion diagnosis apparatus.

Next, the judging of abnormality of cylinder pressure sensor 1 will be explained with reference to FIG.24, FIG.33(A),

FIG.33(B), and FIG.34.

In FIG.24 showing a cylinder pressure diagram, P_0 is the reference pressure at or before the beginning of compression, P_3 is the pressure at a crank angle advanced by a certain crank angle from that of P_0 (i.e. P_3 is measured earlier in time than P_0), P_1 is the pressure at a crank angle in retard of a certain crank angle from that of P_0 (i.e. P_1 is measured later in time than P_0), P_2 is the pressure at a crank angle in retard of a certain crank angle from that of P_1 . The crank angle range between RWA and RWB is the abnormality judging range, the cylinder pressure range between PTb and PTa is the pressure detecting range including the high pressure for detecting knock, PSb is the maximum permissible inlet air pressure, and Psa is the minimum permissible inlet air pressure. The range between Aa and Ab is the range of combustion in which the maximum cylinder pressure P_p occurs.

In FIG.24 and FIG.34, when judging the abnormality of cylinder pressure detector 1, cylinder No.k is set to 1 (E0) at first in pressure sensor abnormality judging routine of FIG.34, then cylinder pressure of the No.1 cylinder is sampled at equal crank angle intervals (E01) to determine the cylinder pressure P_k ($k=1$) of cylinder number k ($k=1$) and inputted to the combustion diagnosis apparatus 100 (E1).

Whether the sensor is normal or abnormal is judged as follows:

(a) if the pressure detected by the sensor 1 is within the range of PTa ~ PTb or not all over the crank angle is judged

(E2),

(b) then, if the pressure is within the range of $PSb \sim Psa$ or not in the suction range is judged (E3),

(c) further, if the crank angle $Ppang$ of the maximum pressure P_p is within the crank angle range of $Aa \sim Ab$ or not is judged (E4), and

(d) if the sensor is normal or abnormal is judged in step E7 or E8 by proceeding as follows;

When the sensor is normal, usually the detected cylinder pressure includes almost no noise as shown in FIG.33(A). If the detected pressure includes noise as shown in FIG.33(B), the presence or absence of abnormality of the sensor is judged by calculating the standard deviation of Pb as shown in FIG.34.

If the standard deviation σPb of $\{Pb_{j-n+1}, Pb_{j-n+2}, Pb_{j-n+3}, \dots, pb_j\}$ is smaller than the permissible standard deviation ϵ , the sensor is judged to be normal. If the standard deviation is not smaller than the permissible standard deviation ϵ , the pressure detector(sensor) 1 is judged to be abnormal (E8) when the states which do not suffice any one of the conditions (a) ~ (d) described above continues to occur for predetermined i times (E6), since the case may occur in which the pressure exceeds instantaneously said range of $PTa \sim PTb$ owing to trigger pulses due to noise.

Then, the cylinder number k is changed to $k=k+1$ (E10) to diagnose all cylinders. When all cylinders are diagnosed, k is set to 1 and again the diagnosis of all cylinders is performed.

According to the embodiment, as the sensor 1 is judged to be abnormal by step (a) when there occurs a plurality of the cases in which the detected pressure signal exceed the pressure range of $P_{Tb} \sim P_{Ta}$, the occurrence of spark noise, a break in wire, poor electric contact, etc. can be detected with high accuracy even when there occurs instantaneous overshoot in pressure beyond said pressure range due to trigger pulses, etc. The occurrence of drift due to the change with time is detected by step (b). Further, whether the pressure is detected or not with correct relation between the pressure and crank angle is confirmed by step (c).

Therefore, abnormalities in the cylinder pressure detector 1 and crank angle detection are detected from many faces automatically, runaway of diagnosis can be prevented without fail when the cylinder pressure detector 1 is abnormal. When abnormality occurs in a pressure detector 1, the engine can be operated by controlling only by the combustion control apparatus 200 with diagnosing suspended or the engine can be halted to repair the detector 1 as shown in FIG.6, 7, 20.

To be more specific, the combustion controller actuates to retard the ignition timing to a safety range to preserve the abnormality thereof as it is. The combustion diagnosis apparatus diagnoses normally after the sensor is replaced, but in this state the apparatus judges misfire.

If the ignition in the concerned cylinder is effected in this state, the combustion in the cylinder begins with the

ignition timing set to a value in the safety range. Combustion control of the cylinder is restarted by manually resetting the sensor of the concerned cylinder, and the combustion recovers to a normal state from a state of rather weak combustion.

FIG.20 is a total block diagram of the combustion diagnosis system of gas engine of the embodiment according to the present invention in the case stepless control is done only in normal range and corresponds to FIG.7.

FIG.21 is a total control flowchart of the combustion diagnosis system of gas engine of the embodiment according to the present invention and corresponds to FIG.9 except that stepless control is done only in normal range.

FIG.22 is an illustration explaining the method of transmission of combustion diagnosis signals in analog form applied to the invention of FIG.20 and FIG.21.

FIG.23(A) is a graph showing totally the change of the value of analog-form signal for each of the categories of the result of combustion diagnosis, and FIG.23(B) is a graph a part of FIG.23(a) partially enlarged.

FIG.24 is a pressure curve for explaining the detection of cylinder pressure for combustion diagnosis.

In this embodiment, differing from the cases of previous embodiments, threshold values are provided for detected

pressure in the combustion range of crank angle of the range $Aa \sim Ab$ shown in FIG.24 so that stepwise representation of analogue value is possible in a serial data transmission wire.

Each level of threshold values P_{p0} and P_{h1} for detecting the abnormal P_{max} , P_{h2} for detecting knock, P_n for detecting misfire and flame quenching, etc. are determined to be $P_{p0} \geq P_{h1} \geq P_{h2} \geq P_{sh} \geq P_{s1} \geq P_n$, the level decreasing stepwise.

Returning to FIG.21, if the sensor is judged to be normal in step S'01, then compression pressure difference ΔP_0 is abnormally low or not is judged(S'1).

Said reference pressure difference ΔP_0 detected in the compression stroke range is compared with the permissible pressure difference P_{c0} (threshold value) for ΔP_0 , and when $\Delta P_0 \leq P_{c0}$, the compression pressure P_c is judged to be abnormally low due to mechanical trouble such as gas leakage(S'1).

When the condition of step S'2 holds or the number N_h of operated cycles in S'3 is equal to or exceeds the permissible number N_{h0} (S'4), the maximum cylinder pressure P_p is judged to be abnormally elevated over the design value(normal value).

Knock judging step S'5 ~ S'6, and misfire and flame quenching judging step S'7 ~ S'9 are the same as FIG.9.

Thus, in the embodiment, combustion diagnosis is performed by comparing standardized cylinder pressure ratio $\Delta P / \Delta P_0$ in said combustion range with threshold values determined for

every diagnosis category information, each level of said threshold values being decreased stepwise so that the information of different category can be judged based on the corresponding level of threshold value, detection range being set to be in the crank angle near the maximum pressure, said threshold values being P_{p0} and P_{h1} for detecting abnormal P_{max} , P_{h2} for detecting knock, P_n for detecting misfire and flame quenching, etc., the level of each threshold value being decreased in orderly sequence of $P_{p0} \geq P_{h1} \geq P_{h2} \geq P_{sh} \geq P_{s1} \geq P_n$.

Accordingly, as the standardized maximum pressure ratio $\Delta P_p / \Delta P_0$ in normal combustion is below the threshold value for knock, i.e. $\Delta P_p / \Delta P_0 < P_{h2}$, values of $P_{h2} \sim P_n$ are converted by the following equation to values in the range of $C_k \sim C_q$ to be transmitted to the combustion diagnosis apparatus as analogue information in step 20 in FIG.21.

$$C = \{ (C_q - C_k) / (P_n - P_{h2}) \} \times \{ (\Delta P_p / \Delta P_0) - P_{h2} \} + C_k$$

FIG.20 is a block diagram showing total configuration of the embodiment of a gas engine combustion diagnosis system, in which diagnosis is done by determining threshold values shown in FIG.23(A) and FIG.23(B) for the maximum pressure P_p detected in the range of crank angle $Aa \sim Ab$ corresponding to combustion range.

In the drawing, reference numeral 20 is the multi-cylinder engine, 100 is the combustion diagnosis apparatus which diagnoses the combustion by detected cam top crank angle and

cylinder pressure-crank angle data through following the flow shown in FIG.21.

The result of the diagnosis is transmitted on analog levels shown in FIG.23(A) and FIG.23(B), i.e. Cp: the analog level for transmitting abnormal Pmax judgement, Ce: analog level for compression pressure judgement, Ck: analog level for knock judgement, Cq: analog level for flame judgement quenching, Cm: analog level for misfire judgement, Cx; analog level for abnormal sensor judgement, each analog level being determined to decrease stepwise in the orderly sequence of $Cp > Ce > Ck > Cq > Cm > Cx$.

The signal of the result of diagnosis transmitted from the combustion diagnosis apparatus 100 to the combustion control apparatus 200 is composed of analog levels, each analog level being determined for each diagnosis category. Therefore, the combustion control apparatus 200 is able to judge each information of different category in each pertinent analog level. The analog level for transmitting the information of diagnosis category of normal combustion state is positioned in the center part of the levels, the level for transmitting the information of abnormal maximum cylinder pressure or compression pressure which generally related to engine conditions as a whole is set to a value in higher level range, and the levels for transmitting the information of misfire, flame quenching, abnormal sensor, and break in wire, that are generally experienced in an individual cylinder are set to a value in lower level range. When the range of normal combustion pressure or pressure ratio of each cylinder, the

pressure or pressure ratio being between the threshold for knock and that for flame quenching, is transmitted to the combustion control apparatus by way of signal transmitting wire 101 (see FIG.22) in analog level, the pressure or pressure ratio converted in stepless analog level signal corresponding with the pressure or pressure ratio can be transmitted to the combustion control apparatus 200. Accordingly, with the combustion diagnosis/control apparatus of an internal combustion engine, the number of analog signal transmission wire corresponding with the number of cylinders is connected between the combustion diagnosis apparatus 100 and combustion control apparatus 200, and the diagnosed result of each diagnosis category is transmitted in serial order on each of analog signals which are set in stepwise decreasing sequence. The combustion control apparatus judges the diagnosis category or can determine the combustion pressure or pressure ratio corresponding with the analog signal.

Therefore, as shown in FIG.22, by sending each information in an analog signal of pertinent level in serial order, the analog information of K category of diagnosis result can be transmitted on one analog signal transmission wire 101 per cylinder, which means that m wires suffice for m cylinders.

As one of signal transmission wires 101 corresponds to the information of one of cylinders, only the combustion in the cylinder of which the wire is broken becomes uncontrollable and the combustion in other cylinders are not influenced. Furthermore, as the information is of analog, malfunctions do not occur due to noises in the signals.

Concerning the normal pressure range, P is calculated by $P = \Delta P_p / \Delta P_0$, and analog information thereof is calculated by the following equation;

$$C = (C_q - C_k) \times (P - P_{h2}) / (P_n - P_{h2}) + C_k.$$

Thus, by the conversion of $\{P_{h2} \sim P_n\} \rightarrow \{C_k \sim C_q\}$, the combustion control apparatus 200 receives stepless pressure level information in the normal combustion range.

The received analog information $\{C_k \sim C_q\}$ are again converted to pressure information $\{P_{h2} \sim P_n\}$ in the control apparatus 200, as shown in FIG.20, by the following equation;

$$P = \{(P_n - P_{h2}) / (C_k - C_q)\} \times (C - C_k) + P_{h2}.$$

Then, the ignition timing is changed from T to $T + \Delta T$, where $\Delta T = F \times (P - P_{sm})$, F is a feedback gain constant, and P_{sm} is a target figure of cylinder pressure ratio in a normal combustion state.

Thus, by retarding or advancing the ignition timing by a certain crank angle ΔT in the normal pressure range $\{P_{h2} \sim P_n\}$, the engine can be effectively maintained to operate with desired performance. The combustion control apparatus 200 always controls the combustion condition according to the result of moment-to-moment diagnosis obtained by the combustion diagnosis apparatus through changing the fuel ignition timing of pilot fuel or gas fuel, or fuel injection

quantity.

Next, the construction of the displaying apparatus 6 shown in FIG.1 and FIG.6 will be explained with reference to FIG.25 = FIG.31.

The display connected to the combustion diagnosis apparatus of the present invention can display two kinds of data, combustion diagnosis data and pressure waves.

FIG.25 shows an example of displayed combustion diagnosis result. In the drawing, cylinder numbers #1 ~ # 18 are arranged in columns, diagnosis categories are arranged in rows, and the result of each diagnosis category for each cylinder transmitted from the combustion diagnosis apparatus is displayed by pertinent mark such as abnormal sensor(X), abnormal maximum pressure $P_p(E)$, knock(K), high maximum pressure $P_p(H)$, adequate maximum pressure $P_p(N)$, low maximum pressure $P_p(L)$, flame quenching(Q), misfire(M), and reduced compression pressure(C). These results are renewed per cycle according to the diagnosis result.

Each mark of the diagnosis category is shown in blank letter in a black rectangle so as to be easily recognized, as the number of cylinders is large in this case.

FIG.26 shows the representation of the cylinder pressure waves of each cylinder of a 4-cylinder engine in the display and the process of transmitting the pressure waves from the combustion diagnosis apparatus to the display, as an example

of a multi-cylinder engine.

The pressure wave-forms in the top to 4th stage in the drawing are the detected cylinder pressure wave-forms of the four cylinders in which the pressure waves are shown for every cycle, the crank angle of cam top (of the inlet cam) being indicated as 0° , the pressures being measured at equal interval of crank angle.

The pressure waves of four cylinders are shown in the display 124 as shown in the last but one stage. The data is transmitted from the combustion diagnosis apparatus 100 to the displaying apparatus 6 in serial order, as there is no relation between displaying and controlling of combustion.

Only the thick line part which is necessary for combustion diagnosis in the pressure wave detected after the detection of cam top crank angle is represented on the display 124.

The thick line part of each pressure-crank angle curve of four cylinders is written to the first ring memory of the combustion diagnosis side every time the pressure is detected by the cylinder pressure detector(sensor). These pressure-crank angle curves are transmitted on the signal transmission wire 101 to the displaying apparatus 6 in such a way that the pressure of each cylinder is retarded in phase from that of the cylinder of next cylinder number by crank angle {a1}, {a2}, {a3}, {a4} respectively. They are transmitted in serial order in the crank angle range of 720° of one cycle, thus the small number of transmission wire 101

is effectively utilized. If the transmission range is set to $60 \sim 80^\circ$ crank angle for example, the pressure waves are possible to be sent on the signal transmission wire 101 in serial order within 720° of one cycle.

The representation in the last stage in the drawing shows the cylinder pressure curves displayed on the oscillograph 124 of the displaying apparatus 6. As shown in the representation, each of the curves is shown on the oscillograph 124 of the displaying apparatus 6 at a spacing of pressure value β for easy recognition of all of the pressure curves, as the cylinder pressure curves are very similar to each other.

For realizing this, the curves sent from the combustion diagnosis side by retarding in phase by crank angles of $\{a1\}$, $\{a2\}$, $\{a3\}$, $\{a4\}$ respectively are advanced by the same crank angles respectively and displayed with reference to the cam top crank angle of reference cam (for example, the inlet cam of #1 cylinder) with a spacing of pressure value β .

FIG.27 shows an example of data configuration on the combustion diagnosis apparatus side and displaying apparatus side to perform said displaying.

First, constituent elements for data processing on the combustion diagnosis apparatus side will be explained.

A ring buffer memory 110 (rbuf1) of the combustion diagnosis apparatus side has a memory part for memorizing the cam top

crank angle of the reference cam and ring memory parts for memorizing the pressure curves of #1 ~ #4 cylinders during at least 720° of one cycle or above, concretely, during several cycles.

A write-in pointer 113 determines the position for writing the detected data from the cylinder pressure detector 1 and crank angle detector 2.

Reference numeral 112 is a memory for memorizing the relative angle information that are crank angles {a1 ~ a4} from the cam top crank angle of the reference cam to the start crank angle of each pressure curve. Reference numeral 111 is a readout pointer for reading from the ring memory parts each pressure curve with the timing determined based on said memorized angle information of {a1 ~ a4} in order to read out the data with crank angle phase retarded by angle {a1}, {a2}, {a3}, {a4} respectively.

Next, constituent elements for data processing on the displaying apparatus side will be explained.

A ring buffer memory 120 (rbuf2) of the displaying apparatus side has four ring memory parts for memorizing pressure curves, in which the pressure data of #1 ~ #4 cylinders sent from the combustion diagnosis 100 side with crank angle phase retarded by angle {a1}, {a2}, {a3}, {a4} respectively are memorized in a certain area (wlen) in sequence with crank angle phase advanced this time by angle {a1}, {a2}, {a3}, {a4} respectively.

Reference numeral 121 is a write-in pointer for determining write-in timing to write in the pressure data transmitted on the serial signal transmission wire 101 with crank angle phase advanced by angle {a1}, {a2}, {a3}, {a4} respectively to the ring memory parts corresponding to #1 ~ #4 cylinders.

Reference numeral 122 is a readout pointer for determining the timing to read out the data from the ring memory parts corresponding to #1 ~ #4 cylinders, giving pressure spacing value β between each pressure data.

FIG.28 ~ FIG.31 are flowcharts for processing the pressure data for displaying. FIG. 28 is a crank angle interrupt handling flowchart on the combustion diagnosis apparatus side(data sending-out side), FIG.29 is a main processing flowchart on the combustion diagnosis side(data sending-out side), FIG.30 is a data reception interrupt handling flowchart on the displaying apparatus side(data receiving side), and FIG.31 is a crank angle interrupt handling flowchart on the displaying apparatus side(data receiving side).

In FIG.28, the program is started with interrupt timing of the signal from the crank angle detector (S20), the write-in pointer 113 is set to k(0 ~ 4) (S21), the detected cam top crank angle of the reference cam is written to the memory part of the ring buffer memory rbuf1 for memorizing the cam top crank (0°) of the reference cam when k = 0. Then the pressure data of #1 ~ #4 cylinders are written to the corresponding ring memory part in succession (S22).

Similar operation is effected in the succeeding cycles until the write-in pointer runs over the size of the ring buffer memory rbuf1. When the write-in pointer 113 overrun the size of the ring buffer memory rbuf1 (S23), the write-in pointer is initialized to 0 (S24) to overwrite from the initial part of the ring memory.

FIG.29 is a main processing flowchart of the combustion diagnosis apparatus side (data sending-out side).

The write-in pointer and readout pointer is set to 0 (S30), after the cam top crank angle of the reference cam is detected (S32), if memory area for more than 1 cycle of crank angle (720°) is remaining in the write-in memory area of the ring buffer rbuf1 (33), k is set to 1 for #1 cylinder (34), crank angle a1 is read out from the timing memory, and the pressure data of #1 cylinder in the crank angle range corresponding to the diagnosis range is transmitted on the signal transmission wire 101 to the displaying apparatus 6.

Then, k is increased (S37), and when k does not exceeds the number of cylinders, crank angle a2, a3, a4, ... is read out every time k is increased by 1 to transmit successively the pressure data of each cylinder to the displaying apparatus with the crank angle phase thereof retarded by the value of said corresponding crank angle (S36).

When k is equal to or succeeds the number of cylinders (S38), next write-in area iptr is set to iptr++ (S39), if the write-in

area is equal to or larger than $rdptr + wlen$ (area corresponding to the diagnosis range) (S40), similar operation is repeated to write the data successively into the still-unwritten area in the ring buffer $rbuf1$. When write-in area $itpr$ is smaller than $rdptr + wlen$ (area corresponding to the diagnosis range), $iptr$ is set to $rdptr++$ to proceed to overwriting to the ring buffer $rbuf1$ (S41).

Thus, the pressure-crank angle data of each cylinder and cam top crank angle of the reference cam detected by the cylinder pressure detector 1 and crank angle detector 2 are memorized to the ring buffer $rbuf1$ in the combustion diagnosis apparatus 100.

Next, displaying apparatus side (data receiving side) will be explained.

Referring to FIG.30, data interrupt is started every time data is received from the signal transmission wire 101 (S50A), write-in pointer is set to $iptr$ (S50) to write each data of #1 ~ #4 cylinders to the corresponding ring memory part of the ring buffer $rbuf2$ (S50).

After said data of #1 ~ #4 cylinder are written in $iptr$ area of the ring buffer $rbuf2$, write-in area is advanced to $iptr++$ (S52), and similar operation is effected until all data of one cycle are written in (S53).

When all the data are written in, the write-in pointer 122 is again set to $iptr$ to effect the writing-in of the next

cycle(S54).

Next, the main processing flow on the display side(data receiving side) will be explained with reference to FIG.31.

First, whether the position of the write-in pointer coincides or not with that of the readout pointer is judged(S60), when coinciding, the position is advanced by wlen and wait until full data of one cycle after detecting cam top crank angle of the reference cam is received(S66).

When difference between the memory capacity of the ring buffer rbufmax and difference {the position of write-in pointer WTPTR - the position of the readout pointer RDPTR}, i.e. remaining area of the ring buffer memory is equal to or larger than wlen(S61), the readout pointer is matched with the cam top crank angle(S62), and the data of #1 ~ #4 cylinders are read out from the corresponding ring memory part in the ring buffer rbuf2(S63).

When all the data(pressure curves in the diagnosis range), each data being the pressure-crank angle curve in a certain crank angle range wlen from the pressure wave data beginning point which is at a crank angle of relative crank angle information a1, a2, ... respectively from the cam top crank angle of the reference cam, are received, for example when the cam top crank angle for the next cycle is detected, the pressure curves are displayed on the oscilloscope 124 of the displaying apparatus with the pressure curve of each cylinder spaced by a pressure value β .

After all the data of #1 ~ #4 cylinders are read out from iptr area of the ring buffer rbuf2, readout area is advanced to iptr++(S65), and similar operation is effected until all the data during one cycle are written in the crank angle range wlen.

Then, whether the position of the readout pointer coincides or not, if coinciding, the readout pointer is advanced by wlen to be returned to S61 to readout the data of the next cycle.

Industrial applicability

As described in the foregoing, according to the present invention, the combustion diagnosis can be done which detects the occurrence of knock, misfire, excessive elevation of the maximum cylinder pressure, and flame quenching, with a combustion diagnosis system by diagnosing combustion using the pressure ratio based on the detected cylinder pressure. Therefore, all categories necessary for combustion diagnosis of an internal combustion engine can be performed by an apparatus of simple constitution and low cost.

As the combustion diagnosis is effected by using the pressure ratio based on the cylinder pressure as mentioned above, the absolute value of the cylinder pressure is not required. So, even when the output level from the cylinder pressure detector totally decreases, normal combustion diagnosing function can be maintained without reduction in accuracy. Accordingly, life expectancy of usage of the combustion diagnosis system can be extended.

Further, highly accurate combustion diagnosis can be possible by using the detected cylinder pressure signal with only noise eliminated and complicated computation is not required, so the efficiency of operation of combustion diagnosis is increased.

Yet further, the combustion diagnosis can be performed directly by using only the detected cylinder pressure, so highly accurate combustion diagnosis is possible with simple means(step).

Therefore, according to the present invention, all the necessary combustion diagnosis such as the occurrence of knock, misfire, excessively high maximum cylinder pressure, and flame quenching can be performed, and reduction in engine performance can be detected without delay and with high accuracy.

Still further, according to the present invention, since the combustion diagnosis is effected by using the standardized cylinder pressure ratio $\Delta P / \Delta P_0$ based on the pressure difference between the concerned pressure P and a reference pressure P_0 at or before the beginning of compression including inlet air pressure with small fluctuation in pressure, i.e. $\Delta P = P - P_0$, so the absolute cylinder pressure is not required. Therefore, even when the output level from the cylinder pressure detectors totally decrease or increase, normal diagnosis can be performed, maintaining expected accuracy without reduction in accuracy thereof.

Further, according to the present invention, by stopping the engine by allowing the combustion control apparatus to activate the engine operation stopper when a diagnosis result has been outputted from the combustion diagnosis apparatus that the standardized maximum pressure ratio $\Delta P_p / \Delta P_0$ is equal to or exceeds the predetermined permissible maximum pressure ratio P_{p0} , the detection of excessively high maximum cylinder pressure and the action to deal with that can be taken exactly without delay. Therefore, engine breakage or reduction of engine durability due to the excessive high cylinder pressure can be prevented with reliability.

Further, when the standardized maximum pressure ratio $\Delta P_p / \Delta P_0$ is judged to be equal to or exceeds the maximum reference pressure ratio P_{sh} , the fuel ignition timing is retarded by a certain crank angle by the combustion control apparatus. When the standardized maximum pressure ratio $\Delta P_p / \Delta P_0$ is judged to be smaller than the maximum reference pressure ratio P_{sh} , the fuel ignition timing is advanced by a certain crank angle by the combustion control apparatus. Therefore, the cylinder pressure is maintained below the maximum reference pressure and the expected engine performance is maintained resulting in suppression of increased generation of NOx due to excessively high combustion temperature.

Further, according to the present invention, when a diagnosis result has been outputted from the combustion diagnosis apparatus that knock has occurred by comparing the standardized maximum pressure ratio $\Delta P_p / \Delta P_0$ with knock

threshold, the knock is prevented without delay and with reliability by retarding the fuel ignition timing by a certain crank angle through the combustion control apparatus, and the engine can always be operated in the high performance range just before knock occurs.

Further, according to the present invention, when a diagnosis result has been outputted from the combustion diagnosis apparatus that the number of continual cycles in which the standardized maximum pressure ratio $\Delta P_p / \Delta P_0$ reaches the predetermined permissible pressure ratio of misfire reaches the predetermined permissible number of continual cycles, the fuel injection to the concerned cylinder in which misfire has occurred is cut off. Thus, the occurrence of misfire is detected with reliability without delay and measures can be taken to deal with the situation, that is, to stop the fuel injection to the concerned cylinder, through which the operation of the other cylinders can be continued without influenced by the concerned cylinder.

Further, according to the present invention, when a diagnosis result has been outputted from the combustion diagnosis apparatus that the standardized maximum pressure ratio $\Delta P_p / \Delta P_0$ and combustion pressure ratio $\Delta P_1 / \Delta P_0$ is equal to or smaller than permissible minimum pressure ratio P_n and permissible pressure ratio of misfire P_m respectively, and that combustion pressure ratio $\Delta P_2 / \Delta P_0$ is equal to or larger than permissible pressure ratio of flame quenching P_{m1} , the fuel injection to the concerned cylinder in which flame quenching has occurred is increased. Thus, the occurrence

of flame quenching is detected with reliability without delay and measures can be taken to deal with the situation, that is, to increase the quantity of fuel injection to the concerned cylinder, through which the continuation of misfire is prevented and the operation of the other cylinders can be continued without influenced by the concerned cylinder.

Further, according to the present invention, each of threshold values for combustion diagnosis such as permissible maximum cylinder pressure, permissible minimum compression pressure, permissible pressure of knock, misfire, flame quenching can be determined as a function of engine operating conditions such as engine load, engine rotation speed, inlet air temperature. Therefore, the threshold values can be adjusted according to engine operating conditions so that the engine is operated always near knocking limit, resulting in highly accurate combustion diagnosis.

Further, according to the present invention, when a diagnosis result has been outputted from the combustion diagnosis apparatus that a cylinder pressure detector is abnormal, the fuel injection timing of the concerned cylinder of which the pressure detector is abnormal is retarded by a certain crank angle to a safety range. After the pressure detector is recovered, the combustion diagnosis apparatus recovers automatically normal operation and allows the combustion control apparatus to operate normally to recover the normal injection timing of the concerned cylinder.

Therefore, when abnormality occurs in any of the cylinder

pressure detectors, the pressure detector of the concerned cylinder is repaired or recovered while the injection timing of the concerned cylinder is adjusted to a safe timing for combustion, and after the recovery of the pressure detector, the normal combustion control is recovered, so the abnormal pressure detector can be dealt with without halting the operation of the engine.

Further, according to the present invention, the occurrence of spark noise, a break in wire, poor electric contact, etc. can be detected by detecting the pressure signal overshooting or undershooting the ordinary maximum or minimum value of cylinder pressure, the occurrence of drift due to the change over time of the pressure detector can be detected, and whether the pressure is detected without deviation in relation to crank angle or not can be confirmed.

Therefore, the abnormality of cylinder pressure detector can be detected automatically from various facets, and fast recovery of the pressure detector from abnormal state is possible resulting in smooth combustion diagnosis.

Further, according to the present invention, the drift due to the change in the temperature of the pressure sensor and change over time of the pressure sensor does not influence the result of diagnosis, and abnormalities such as abnormal combustion, failure in the cylinder pressure sensor, and a break in wire can be detected.

Further, according to the present invention, the detection

of knocking state which has been difficult can be grasped indirectly by the ratio of pressure differences as a measure, and engine operation near knock limit is always possible, resulting in increased engine efficiency.

Further, according to the present invention, even when the combustion diagnosis apparatus stops the operation due to failure, etc., the apparatus can be recovered without stopping the engine, since in such a case the fuel ignition timing is retarded to a position safe for combustion through the combustion control apparatus.

Further, according to the present invention, the number of signal transmission wires between the combustion diagnosis apparatus and combustion control apparatus is reduced compared with the conventional method of connection, and if a break in wire occurs, the influence thereof is limited only to the concerned cylinder; besides, the broken wire is able to be identified because the analog value on the wire becomes zero level which belongs to no category of diagnosis. On the contrary, with conventional digital signal transmission wires, the identification of broken wire is impossible.

Further, according to the present invention, when any of the cylinder pressure sensors fails during engine operation, the failed sensor can be replaced without stopping the engine operation.

Further, according to the present invention, visualization of combustion condition changing moment-to-moment is

possible. Particularly, it is possible to observe pressure curves of a plurality of cylinders while diagnosing combustion by temporarily memorizing the cylinder pressure data measured overlapped with regard to time in the combustion diagnosis apparatus and then sending to the displaying apparatus in serial transmission.

Further, by adopting stepless control to effect feedback of the deviation in pressure from the target value of cylinder pressure, and more carefully thought out control is possible, resulting in further increased engine efficiency.

The present invention is applicable not only to the gas engine ignited by torch ignition of pilot fuel explained in the embodiments but also to all types of reciprocating internal combustion engine such as other type of gas engines and diesel engines.

CLAIMS

1. An apparatus for diagnosing and controlling combustion of an internal combustion engine including a gas engine which is constituted so that fuel gas is mixed with air and burned in the combustion chamber there, wherein are provided;

a cylinder pressure detector for detecting the pressure in said combustion chamber,

a means(step) for calculating the ratio of the maximum cylinder pressure P_p to the compression pressure or pressures P_0 at one or a plurality of predetermined crank angle in the compression stroke (P_p/P_0) which is the maximum pressure ratio from cylinder pressure detected by said cylinder pressure detector,

a means(step) for comparing the maximum pressure ratio (P_p/P_0) with the pressure ratios predetermined stepwise for each category of diagnosis (hereafter referred to as threshold pressure ratio), and

a means(step) for diagnosing the condition of combustion such as the cylinder pressure condition in said combustion chamber by judging from the result of said comparison.

2. An apparatus for diagnosing and controlling combustion of an internal combustion engine as in claim 1, wherein said threshold pressure ratio is changed as a function of engine operating conditions including engine load, engine rotation speed, and inlet air temperature.

3. An apparatus for diagnosing and controlling combustion of an internal combustion engine as in claim 1, wherein a

means(step) is provided which judges that the combustion is abnormal when said maximum pressure ratio (P_p/P_0) is equal to or exceeds a predetermined maximum permissible pressure ratio P_{p0} or when the number of operation cycles N_h when said maximum pressure ratio (P_p/P_0) is equal to or exceeds the predetermined pressure ratio P_{h1} (i.e., when $P_p/P_0 \geq P_{h1}$) is equal to or exceeds the permissible number N_{h0} (i.e., when $N_h \geq N_{h0}$).

4. An apparatus for diagnosing and controlling combustion of an internal combustion engine as in claim 1, wherein a means (step) is provided which judges the compression pressure P_0 is abnormal when said compression pressure P_0 at a predetermined crank angle in the compression stroke is equal to or lower than the predetermined permissible compression pressure P_{c0} , (i.e., when $P_0 \leq P_{c0}$).

5. An apparatus for diagnosing and controlling combustion of an internal combustion engine as in claim 1, wherein a means (step) is provided which judges that knock has occurred in the combustion chamber when the number of cycles S_n in which said maximum pressure ratio (P_p/P_0) is equal to or exceeds the predetermined permissible pressure ratio of knock P_{h2} (i.e., when $P_p/P_0 \geq P_{h2}$) in a plurality of cycles in the past is equal to or exceeds the permissible number S_{n0} (i.e., when $S_n \geq S_{n0}$).

6. An apparatus for diagnosing and controlling combustion of an internal combustion engine as in claim 1, wherein are provided;

a means(step) for calculating the ratio of the maximum cylinder pressure P_p to the compression pressure or pressures

P_0 at a predetermined crank angle in the compression stroke (P_p/P_0), the pressures being determined based on the pressures detected by said cylinder pressure detector,

a means(step) for calculating the ratio of the pressure P_1 at a predetermined crank angle in the combustion stroke to said pressure P_0 at a predetermined crank angle in the compression stroke (P_1/P_0) which is the combustion pressure ratio, and

a means(step) which judges that misfire has occurred when said maximum pressure ratio P_p/P_0 is equal to or smaller than the predetermined minimum permissible pressure ratio P_n (i.e., when $P_p/P_0 \leq P_n$) and at the same time said combustion pressure ratio (P_1/P_0) is equal to or smaller than the predetermined permissible pressure ratio P_m of misfire (i.e., when $P_1/P_0 \leq P_m$).

7. An apparatus for diagnosing and controlling combustion of an internal combustion engine as in claim 1, wherein are provided;

a means(step) for calculating the ratio of the lower side pressure P_2 in the combustion stroke lower than said pressure P_1 at a predetermined crank angle in the combustion stroke to said pressure P_0 at a predetermined crank angle in the compression stroke P_2/P_0 , and

a means(step) which judges that flame quenching has occurred in the combustion chamber when said maximum pressure ratio is equal to or smaller than the predetermined minimum permissible pressure ratio P_n (i.e., when $P_p/P_0 \leq P_n$), said combustion pressure ratio P_1/P_0 is equal to or smaller than the predetermined minimum permissible pressure ratio P_m of

misfire (i.e., when $P_p/P_0 \leq P_m$), and the combustion pressure ratio P_2/P_0 is equal to or larger than the permissible pressure ratio P_{m1} of flame quenching (i.e., when $P_2/P_0 \geq P_{m1}$).

8. A method of diagnosing and controlling combustion of an internal combustion engine including a gas engine which is constituted so that fuel gas is mixed with air and burned in the combustion chamber there, wherein the diagnosis of the condition of combustion in the combustion chamber such as cylinder pressure condition is performed in such a manner in which

the pressure in the combustion chamber is detected,

the pressure difference ΔP between the detected pressure P and reference pressure P_b which is the pressure at or before the beginning of compression including inlet air pressure ($\Delta P = P - P_b$) is calculated for every crank angle, and

standardized pressure ratio which is the ratio of said pressure difference ΔP to the pressure difference ΔP_0 , i.e. $\Delta P / \Delta P_0$, ΔP_0 being the pressure difference between the pressure P_0 at one or a plurality of predetermined crank angle in the compression stroke and said reference pressure P_b ($\Delta P_0 = P - P_b$), is used for the diagnosis of the combustion conditions such as the condition of cylinder pressure in the combustion chamber.

9. A method of diagnosing and controlling combustion of an internal combustion engine as in claim 8, wherein said standardized pressure ratio $\Delta P / \Delta P_0$ in the cylinder is compared with the pressure ratio predetermined stepwise for each category of diagnosis (hereafter referred to as threshold

pressure ratio), and the result of said comparison is evaluated for every one or a plurality of cycles to diagnose the condition of combustion in the combustion chamber such as cylinder pressure condition.

10. A method of diagnosing and controlling combustion of an internal combustion engine as in claim 9, wherein the engine is stopped when said standardized pressure ratio $\Delta P / \Delta P_0$ at the maximum cylinder pressure P_p , that is the standardized maximum pressure ratio $\Delta P_p / \Delta P_0$, is equal to or exceeds the predetermined permissible maximum pressure ratio P_{p0} (i.e., when $\Delta P_p / \Delta P_0 \geq P_{p0}$).

11. A method of diagnosing and controlling combustion of an internal combustion engine as in claim 9, wherein fuel ignition timing is retarded by a certain crank angle when said standardized maximum pressure ratio $\Delta P_p / \Delta P_0$ is equal to or exceeds the predetermined maximum reference pressure ratio P_{sh} (i.e., when $\Delta P_p / \Delta P_0 \geq P_{sh}$), and fuel ignition timing is advanced by a certain crank angle when said standardized maximum pressure ratio $\Delta P_p / \Delta P_0$ is equal to or below the predetermined minimum reference pressure ratio P_{s1} (i.e., when $\Delta P_p / \Delta P_0 \leq P_{s1}$).

12. A method of diagnosing and controlling combustion of an internal combustion engine as in claim 9, wherein the engine is stopped when said pressure difference ΔP_0 at the predetermined crank angle in the compression stroke is equal to or smaller than the predetermined permissible compression pressure difference P_{c0} (i.e., when $\Delta P_0 \leq P_{c0}$).

13. A method of diagnosing and controlling combustion of an internal combustion engine as in claim 9, wherein the fuel ignition timing is retarded by a certain crank angle when said standardized maximum pressure ratio $\Delta P_p / \Delta P_0$ is equal to or exceeds the predetermined permissible pressure ratio P_{h2} of knock (i.e., when $\Delta P_p / \Delta P_0 \geq P_{h2}$).

14. A method of diagnosing and controlling combustion of an internal combustion engine as in claim 9, wherein misfire is judged to have occurred in the combustion chamber and the fuel injection for the cylinder in which misfire is judged to have occurred is shut off when said standardized maximum pressure ratio $\Delta P_p / \Delta P_0$ is equal to or below the predetermined minimum permissible pressure ratio P_n of misfire (i.e., when $\Delta P_p / \Delta P_0 \leq P_n$).

15. A method of diagnosing and controlling combustion of an internal combustion engine as in claim 9, wherein flame quenching is judged to have occurred and the fuel injection quantity for the cylinder in which flame quenching is judged to have occurred is increased when said standardized maximum pressure ratio $\Delta P_p / \Delta P_0$ and a standardized combustion pressure ratio $\Delta P_1 / \Delta P_0$ in the combustion stroke are equal to or smaller than the minimum permissible pressure ratio P_n and permissible pressure ratio P_m of misfire respectively (i.e., when $\Delta P_p / \Delta P_0 \leq P_n$ and $\Delta P_1 / \Delta P_0 \leq P_m$) and a standardized combustion pressure ratio $\Delta P_2 / \Delta P_0$ is larger than permissible pressure ratio P_{m1} of flame quenching.

16. A method of diagnosing and controlling combustion of an internal combustion engine as in claim 9, wherein the standardized threshold pressure ratio cited in claim 9 is any one of said permissible maximum pressure ratio P_{p0} , maximum value P_{sh} of maximum reference pressure ratio, permissible pressure ratio of knock P_{h2} , minimum pressure ratio of misfire P_n , permissible pressure ratio of misfire P_m , and permissible pressure ratio of flame quenching P_{m1} , and these threshold pressure ratios and the compression pressure difference P_{c0} cited in claim 12 are variable as function of engine load or engine rotation speed or engine operating conditions including inlet air temperature.

17. A method of diagnosing and controlling combustion of an internal combustion engine including a gas engine which is constituted so that fuel gas is mixed with air and burned in the combustion chamber there, wherein, when abnormality is detected concerning a cylinder pressure detector which detects the pressure in a combustion chamber and inputs it to the combustion diagnosis apparatus, the fuel ignition timing of the concerned cylinder of which the cylinder pressure detector is abnormal is retarded by a certain crank angle to a safety position for combustion through a combustion control apparatus which performs combustion control including the controlling of ignition timing of engine fuel and fuel injection quantity (including pilot fuel), and after said pressure detector is recovered by replacement or repair thereof, said combustion control apparatus is allowed to return to normal operation to restore the fuel ignition timing of the concerned cylinder to normal timing.

18. A method of diagnosing and controlling combustion of an internal combustion engine including a gas engine which is constituted so that fuel gas is mixed with air and burned in the combustion chamber there, wherein a plurality of kinds of abnormality are judged in a predetermined crank angle range in suction ~ combustion stroke, and when the condition not sufficing any one of the kinds of abnormality continues for a predetermined plurality of number of cycles i , the cylinder pressure detector is judged to be abnormal.

19. A method of diagnosing and controlling combustion of an internal combustion engine as in claim 18, wherein said plurality of steps for judging abnormality comprises;

(a) a step for judging whether the detected pressure by the cylinder pressure detector 1 is within the pressure range $PTa \sim PTb$ or not during whole crank angle of one cycle,

(b) a step for judging whether the detected pressure is within the pressure range PSb (permissible maximum inlet pressure) $\sim$ Psa (permissible minimum inlet pressure) or not in the suction stroke,

(c) a step for judging whether crank angle $Ppang$ at the maximum pressure P_p is within the crank angle range corresponding to combustion range $Aa \sim Ab$ or not, and

(d) a step for judging whether the standard deviation of P_b 's of past n cycles, i.e. $\{P_{b_{j-n+1}}, P_{b_{j-n+2}}, P_{b_{j-n+3}}, \dots, P_{b_j}\}$, p_b being reference pressure at or before the beginning of compression including inlet air pressure, is smaller than predetermined value ϵ or not.

20. An apparatus for diagnosing and controlling combustion of an internal combustion engine including a gas engine which is constituted such that fuel gas is mixed with air and burned in the combustion chamber, wherein are provided;

a cylinder pressure detector for detecting the pressure in said combustion chamber,

a crank angle detector for detecting crank rotation angles of the engine,

a means(step) for calculating the pressure difference ΔP between detected cylinder pressure P and the reference pressure P_0 at or before the beginning of compression including inlet pressure ($\Delta P = P - P_0$) from the cylinder pressure detected by said cylinder pressure detector for every crank angle,

a means(step) for calculating standardized pressure ratio which is the ratio of said pressure difference ΔP to the pressure difference ΔP_0 , i.e. $\Delta P / \Delta P_0$, ΔP_0 being the pressure difference between the pressure P_0 at one or a plurality of predetermined crank angles in the compression stroke and said reference pressure P_0 ($\Delta P_0 = P - P_0$),

a means(step) for diagnosing the condition of combustion such as the cylinder pressure condition in said combustion chamber using said standardized pressure ratio $\Delta P / \Delta P_0$, and

a combustion control apparatus for controlling the combustion condition of the engine on the basis of the result of the combustion condition diagnosis outputted from the combustion condition diagnosis means (step).

21. An apparatus for diagnosing and controlling combustion of an internal combustion engine as in claim 20, wherein

said combustion diagnosis apparatus is provided with a

means(step) for comparing said standardized maximum pressure ratio $\Delta P_p / \Delta P_0$ with the predetermined maximum permissible pressure ratio P_{p0} and outputting the result of the comparison, and

said combustion control apparatus is provided with a means(step) for actuating the engine stopper to stop the engine when said result of comparison outputted from the combustion diagnosis apparatus is $\Delta P_p / \Delta P_0 \geq P_{p0}$.

22. An apparatus for diagnosing and controlling combustion of an internal combustion engine as in claim 20, wherein

said combustion diagnosis apparatus is provided with a means(step) for comparing said standardized maximum pressure ratio $\Delta P_p / \Delta P_0$ with the maximum value P_{sh} of maximum reference pressure ratio and with the minimum value P_{s1} of maximum reference pressure ratio and outputting the result of the comparison, and

said combustion control apparatus is provided with a means(step) for retarding the ignition timing of fuel including pilot fuel by a certain crank angle when the result of said comparison is $\Delta P_p / \Delta P_0 > P_{sh}$ and for advancing the ignition timing by a certain crank angle when the result of said comparison is $\Delta P_p / \Delta P_0 \leq P_{s1}$.

23. An apparatus for diagnosing and controlling combustion of an internal combustion engine as in claim 20, wherein

said combustion diagnosis apparatus is provided with a means(step) for comparing said standardized maximum pressure ratio $\Delta P_p / \Delta P_0$ with the predetermined permissible pressure ratio P_{h2} of knock and judging that knock has occurred when

said standardized maximum pressure ratio $\Delta P_p / \Delta P_0$ is equal to or exceeds said permissible pressure ratio P_{h2} of knock, and

said combustion control apparatus is provided with a means(step) for retarding the fuel ignition timing by a certain crank angle upon receipt of judgement signal of the occurrence of knock from said combustion diagnosis apparatus.

24. An apparatus for diagnosing and controlling combustion of an internal combustion engine as in claim 20, wherein

said combustion diagnosis apparatus is provided with a means(step) for comparing said standardized maximum pressure ratio $\Delta P_p / \Delta P_0$ with the predetermined permissible pressure ratio of misfire and judging that misfire has occurred in the combustion chamber when said standardized maximum pressure ratio $\Delta P_p / \Delta P_0$ is equal to or smaller than the minimum permissible pressure ratio P_n of misfire, and

said combustion control apparatus is provided with a means(step) for cutting off the fuel injection to the cylinder in which misfire has occurred upon receipt of judgement signal of the occurrence of misfire.

25. An apparatus for diagnosing and controlling combustion of an internal combustion engine as in claim 22, wherein

said combustion diagnosis apparatus is provided with a means(step) for outputting a judgement signal of the occurrence of flame quenching in the combustion chamber when said standardized maximum pressure ratio $\Delta P_p / \Delta P_0$ and a standardized combustion pressure ratio $\Delta P_1 / \Delta P_0$ in the combustion stroke are smaller than the permissible minimum pressure ratio P_n and permissible pressure ratio P_m of flame

quenching respectively and at the same time a standardized combustion pressure ratio $\Delta P_2/\Delta P_0$ is equal to or exceeds the permissible pressure ratio P_{m1} , and

said combustion control apparatus is provided with a means(step) for increasing the quantity of fuel(including pilot fuel to be injected to the sub-combustion chamber) injected to the cylinder in which flame quenching has occurred upon receipt of the occurrence of flame quenching.

26. An apparatus for diagnosing and controlling combustion of an internal combustion engine including a gas engine which is constituted so that fuel gas is mixed with air and burned in the combustion chamber, wherein are provided;

a cylinder pressure detector for detecting the pressure in said combustion chamber,

a crank angle detector for detecting crank rotation angle of the engine,

a means(step) for calculating the pressure difference ΔP between detected cylinder pressure P and the reference pressure P_b at or before the beginning of compression including inlet pressure($\Delta P=P-P_b$) from cylinder pressure detected by said cylinder pressure detector for every crank angle in said combustion crank angle range,

a means(step) for calculating standardized pressure ratio which is the ratio of said pressure difference ΔP to the pressure difference ΔP_0 , i.e. $\Delta P/\Delta P_0$, ΔP_0 being the pressure difference between the pressure P_0 at one or a plurality of predetermined crank angles in the compression stroke and said reference pressure P_b ($\Delta P_0=P-P_b$),

a combustion diagnosis apparatus provided with a

pressure/analog voltage converting means(step) for outputting at least a part of the result of diagnosis as analog information when diagnosing the condition of combustion such as cylinder pressure condition in said combustion chamber using said standardized cylinder pressure ratio $\Delta P/\Delta P_0$, and a combustion control apparatus for controlling the combustion condition of the engine by reconverting the analog information outputted from said combustion diagnosis apparatus to pressure information.

27. An apparatus for diagnosing and controlling combustion of an internal combustion engine as in claim 26, wherein the ignition timing of fuel including pilot fuel or quantity of fuel injection is controlled based on the diagnosis result of the pressure information reconverted from said analog information.

28. An apparatus for diagnosing and controlling combustion of an internal combustion engine as in claim 26, wherein the combustion is diagnosed on the basis of each threshold value determined for each diagnosis category information using said standardized pressure ratio $\Delta P/\Delta P_0$ in said predetermined crank angle range of combustion.

29. An apparatus for diagnosing and controlling combustion of an internal combustion engine as in claim 26, wherein said threshold values determined for every diagnosis category information are determined so that the level of each threshold decreases stepwise, and information of different diagnosis category can be judged in different threshold level.

30. An apparatus for diagnosing and controlling combustion of an internal combustion engine as in claim 26, wherein a pressure detection range is determined near the crank angle of maximum combustion pressure, the threshold for each diagnosis category information is P_{p0} and P_{h1} for abnormal P_{max} , P_{h2} for knock, P_n for misfire and flame quenching, and the level of each threshold value being decreased in orderly sequence of $P_n \leq P_{s1} \leq P_{sh} \leq P_{h2} \leq P_{h1} \leq P_{p0}$.

31. An apparatus for diagnosing and controlling combustion of an internal combustion engine as in claim 26, wherein signals of the result of diagnosis transmitted from the combustion diagnosis apparatus to the combustion control apparatus are composed of analog levels, and each analog level for each diagnosis category is determined to decrease stepwise so that the information of different category is able to be discriminated by the analog level on the combustion control apparatus side.

32. An apparatus for diagnosing and controlling combustion of an internal combustion engine as in claim 31, wherein said analog levels for each of diagnosis categories are determined so that the level for transmitting the information of diagnosis category of normal combustion state is positioned in the middle of the levels, the levels for transmitting the information of abnormal maximum cylinder pressure or compression pressure, etc., which are generally related to engine conditions as a whole, are set to values in higher level range, and the levels for transmitting the information of a

misfire, flame quenching, abnormal sensor, a break in wire, and so on, that are generally experienced in an individual cylinder, are set to values in lower level range.

33. An apparatus for diagnosing and controlling combustion of an internal combustion engine as in claim 26, wherein, when the range of normal combustion pressure or pressure ratio of each cylinder, the pressure or pressure ratio being between the threshold for knock and that for flame quenching, is transmitted to the combustion control apparatus side in analog level, the pressure (pressure ratio) is converted in stepless analog level signal corresponding with the pressure (pressure ratio) and the steplessly controlled analog signal is transmitted to the combustion control apparatus side.

34. An apparatus for diagnosing and controlling combustion of an internal combustion engine as in claim 26, wherein a number of analog signal transmission wires corresponding to the number of cylinders are connected between the combustion diagnosis apparatus and combustion control apparatus, the diagnosis result is transmitted in serial order in the form of analog levels each determined to decrease in stepwise for each diagnosis category, and diagnosis category is judged or the combustion pressures or pressure ratios corresponding to analog levels is judged based on the corresponding analog level on the combustion control apparatus side.

35. An apparatus for diagnosing and controlling combustion of an internal combustion engine including a gas engine which is composed so that fuel gas is mixed with air to be burned

in its combustion chamber, provided with a cylinder pressure detector to detect the pressure in the combustion chamber, a crank angle detector to detect the crank rotation angle of the engine, and a displaying apparatus to display the cylinder pressure curve, wherein

a first ring memory for memorizing the cam top crank angle of a reference cam and the cylinder pressure-crank angle curve is provided on the diagnosis apparatus side,

a second ring memory for memorizing the cylinder pressure-crank angle curve in a certain crank angle range of each cylinder and a single displaying part are provided on the displaying apparatus side,

the first ring memory on the diagnosis side has a means (step) to start the program by the interrupt of the signal from the crank angle detector after the detection of the cam top crank angle of the reference cam and write in the cylinder pressure wave form, which indicates combustion condition, at a certain interval of crank angle to the ring memory in the determined area corresponding to each cylinder, and

the pressure-crank angle curves of all cylinder are read out from the determined area of the second ring memory and these pressure curves are displayed on said single displaying part with the pressure curves shifted so that each curve does not overlaps.

36. An apparatus for diagnosing and controlling combustion of an internal combustion engine as in claim 33, wherein the cylinder pressure-crank angle curves of all cylinders are written into the first ring memory on the diagnosis apparatus side in synchronization with the crank angle at the

moment-to-moment detection of the pressure with the cylinder pressure detector(sensor), on the other hand, said cylinder pressure-crank angle curves of all cylinder are written in the second ring memory after the cam top crank angle of the next cycle after the previous cycle (720°) is completed, is detected, and the memorized pressure curves are represented on a single displaying part.