

(13)

- 1 -

DEVICE FOR HOLDING A SLIDER
FOR A SLIDE FASTENER

The present invention relates to the production of slide fasteners, and more particularly to a device for holding a slider in position for threading or mounting onto a slide fastener chain.

5 In the manufacture of a slide fastener, a slider is held in position by a device while a pair of fastener stringers, each stringer having a row of coupling elements mounted on a stringer tape, is threaded through a Y-shape channel in the slider; the coupling elements on one tape
10 is interengaged with the coupling elements on the other tape as they pass through the slider.

A known slider holding device, as disclosed in U. S. Patent 3,685,814 issued August 22, 1972, includes a housing having a support surface for supporting thereon
15 a slider body upside down, a slit receptive of a pull tab hanging from the slider body, and a lever pivotally mounted in the housing and having an upper and a lower projection. The lever is pivotable between a slider-holding position in which the upper projection projects

into the slit for engagement with an opening in the pull
tab, and a slider-release position in which the upper
projection is retracted out of the slit for releasing
the pull tab and for allowing the pull tab to be inserted
5 into the slit. The lever is urged to either the slider-
holding position or the slider-release position in a
known manner. The lower projection extends across the
slit for being pressed downwardly by the free end of the
pull tab when the latter is inserted into the slit. This
10 downward pressing causes the lever to be pivotally moved
to the slider-holding position. The prior art device
requires a plurality of levers of different length one
for each holding of the pull tab. Thus a suitable one
of the levers must be chosen depending on the length of
15 the pull tab, which is laborious and time-consuming.
Otherwise the prior device cannot be used for various
kinds of sliders having pull tabs of different length.

According to the invention, there is provided
a device for holding a slider in position for threading
20 onto a slide fastener chain, the slider including a slider
body, a yoke mounted on the slider body, and a pull tab
pivotally connected to the yoke and having an opening,
said device comprising: a housing having a horizontal
support surface for supporting thereon the slider body
25 upside down, and a vertical slit opening into said
support surface for receiving the pull tab hanging from
the slider body supported on said support surface; a
lever pivotally mounted in said housing and having a pair

15 of juxtaposed arms disposed one on each side of said slit, one of said arms having a locking projection extending toward and terminating short of the other arm, said lever being pivotable between a slider-holding position in which said locking projection projects into said slit for engagement with the opening of the pull tab, and a slider-release position in which said locking projection is retracted out of said slit for releasing the pull tab; and means urging said lever to either said slider-holding position or said slider-release position; CHARACTERIZED in that said other arm extends beyond said one arm to such an extent that as the slider is placed on said support surface, said other arm is pressed downwardly by the yoke of the slider to cause said lever to be pivotally moved from said slider-release position to said slider-holding position.

The present invention seeks to provide a slider holder suitable to be used for various kinds of sliders having pull tabs of different length.

20 The invention further seeks to provide a slider holder with which a slider is held in position without being removed during the threading of a slide fastener through the slider.

Many other advantages, features and additional objects of the present invention will become manifest to those versed in the art upon making reference to the detailed description and the accompanying drawings in which a preferred embodiment incorporating the principles

(18)

of the present invention is shown by way of illustrative example.

Figure 1 is a perspective view of a slider holder according to the present invention, and a slider to be placed on the slider holder;

Figure 2 is an exploded perspective view of the slider holder of Figure 1;

Figure 3 is an enlarged side elevational view, partly in cross section, of the slide holder, illustrating the manner in which the slider is held in position by the slider holder;

Figure 4 is an enlarged cross-sectional view taken along line IV - IV of FIG. 3;

Figure 5 is a view similar to Figure 3, but showing the slider holder in a slider-holding position;

Figure 6 is an enlarged cross-sectional view taken along line VI - VI of Figure 5; and

Figure 7 is a view similar to Figure 5, but illustrating the manner in which the slider is prevented from being removed from the slider holder while the slider is threaded onto a slide fastener chain.

Figures 1 and 2 show a slider holder 10 for holding or retaining a slider 11 in position for threading or mounting onto a slide fastener chain 12 (Figure 7). The slider 11 includes a slider body 13, a yoke or cover 14 mounted on the slider body 13, and a pull tab 15 pivotally connected to the yoke 14 and having an opening 16 adjacent to the yoke 14.

17

The slider holder 10 includes a combined housing composed of a pair of first and second housing parts 17A,17B complementary in shape with one another and having a combined slider rest 18A,18B on which the slider 11 is to be placed upside down. The first and second housing parts 17A,17B are connected together by means of a pair of screws 20,20 extending through a pair of holes 21,21, respectively, in the second housing part 17B into a pair of threaded holes 22,22, respectively, in the first housing part 17A. The slider rest 18A,18B has a combined horizontal support surface 19A,19B for supporting thereon the slider body 13.

The housing 17A,17B also has a vertical slit 23 opening into the support surface 19A,19B for loosely receiving the pull tab 15 hanging from the slider body 13 supported on the support surface 19A,19B, and the housing still also has a combined cavity 24A,24B communicating with the slit 23 and opening into the support surface 19A,19B. The slit 23 includes a groove formed in the second housing part 17B. Alternatively, the groove may be formed in the first housing part 17A or may be composed of a pair of vertical groove halves formed one in each of the first and second housing parts 17A,17B.

A lever 25 is pivotally mounted in the housing 17A,17B by means of a pin 25a extending through a hole 27 in the second housing part 17B and also through a hole 28 in the lever 25. The lever 25 is generally U-shaped and hence has a pair of juxtaposed first and second arms 29,30



disposed one on each side of the slit 23, there being a cutout 31 between the first and second arms 29,30. The first arm 29 has an inwardly directed locking projection 32 on its upper end 29a, the locking projection 32 thus extending toward and terminating short of the second arm 30. The lever 25 is pivotable between a slider-holding position (Figure 5) in which the locking projection 32 projects into the slit 23 for engagement with the opening 16 of the slider pull tab 15, and a slider-release position (not shown, but the solid line position in Figure 3 is virtually the same as this position) in which the locking projection 32 is retracted out of the slit 23 for releasing the pull tab 15.

The second arm 30 of the lever 25 extends beyond the first arm 29 to such an extent that as the slider 11 is placed on the support surface 19A,19B, the second arm 30 is pressed downwardly by the yoke 14 of the slider 11 to cause the lever to be pivotally moved from the slider-release position to the slider-holding position, as described below. The second arm 30 has an outwardly inclined contact surface 33 which is engageable with the yoke 14 when the second arm 30 is pressed by the yoke 14. The contact surface 33 serves to prevent the lever 25 from being pivotally moved to the slider-release position even when a pulling force is exerted on the slider 11 during the threading of a slide fastener chain 12 through the slider 11, as shown in Figure 7.

The locking projection 32 has an inclined contact surface 32a extending along a lower side edge thereof for engagement with an opening-defining edge 16a (Figures 3, 5 and 7) of the pull tab 15 when the lever 25 is in the slider-holding position and also when the pull tab 15 is pulled upwardly in the slit 23. With the contact surface 32a, when the slider 11 is removed from the slider holder 10, the pull tab 15 is pulled upwardly to push the locking projection 32 out of the slit 23 as the lever 25 is pivotally moved to the slider-release position. At that time, the slider 11 is pulled upwardly with the slider body 13 tilted so as to be kept off the contact surface 33 of the second arm 30, thus allowing the lever 25 to be pivotally moved to the slider-release position.

The lever 25 is urged to either the slider-holding position or the slider-release position in the following manner. The second arm 30 has at midportion two pairs of recesses 34,35 and 34,35 disposed one pair on each side. The recesses 34,35 of each pair are disposed close to one another; the small recess 34 has a frustoconical surface, and the large recess 35 has a half-frustoconical surface. Thus the second arm 30 has a neck portion 36 of generally rhombic cross section (Figures 4 and 6) having a pair of ridges 37,37 (Figures 4 and 5) on opposite sides. A pair of balls 38,38 preferably made of steel is received in a pair of holes 39,39, respectively, in the first housing part 17A and is urged against the



ridges 37,37, respectively, of the rhombic neck portion 36 by a pair of leaf springs 40,40. Each leaf spring 40 is secured to the second housing part 29 by a screw 41 extending through a washer 42 and an opening 43 of the

5 leaf spring 40 into a threaded hole 44 in the second housing part 29, as shown in Figures 1 and 2. Thus, each ball 38 is, in response to the pivotal movement of the lever 25, shiftable between the large and small recesses 35,34, at which time the ball 38 rides over the ridge 37.

10 In order to make the slider holder 10 suitable to be used for a variety of sliders 11 (only one illustrated) having pull tabs 15 of different length, the slit 23 has a length longer than that of the longest one of the different pull tabs, the cutout 31 of the lever 17

15 extending downwardly beyond the slit 23.

In operation, the slider 11 is placed upside down on the slider rest 18A,18B with the pull tab 15 is inserted into the slit 23. At that time, the second arm 30 of the lever 25, which is in the slider-release

20 position, is pressed on the contact surface 33 by the yoke 14 of the slider 11 as shown in Figure 3. In the slider-release position, the locking projection 32 on the first arm 29 is retracted out of the slit 23, the second arm 30 projects beyond the support surface 19A,19B,

25 and each ball 38 is disposed in the small recess 34. The second arm 30 is thereby pushed downwardly to cause the lever 25 to be pivotally moved clockwise in Figure 3 until each ball 38 rides over the ridge 37 into the

large recess 35. As a result, the lever 25 has come to the slider-holding position (Figure 5) in which the locking projection 32 projects into the slit 23 to engage in the opening 16 of the pull tab 15.

5 With the slider 11 thus held on the slider rest 18A, 18A, a slide fastener chain 12 (phantom lines in Figure 7) is threaded through the slider body 13. At that time, a pair of disengaged fastener stringers 12a, 12a of the fastener chain 12 is threaded through the
10 slider body 13 from its flared or front end 13a (Figures 3, 5 and 7). As the fastener chain 12 is moved rightwardly in Figure 5, the pair of disengaged fastener stringers 12a, 12a is progressively interengaged. When misinterengagement of the fastener stringers has occurred,
15 the fastener chain 12 is pulled back leftwardly for reinterengagement as shown in Figure 7, at which time a pull is necessarily exerted on the slider body 13 as indicated by an arrow 45. The pull tab 15 is thus pulled upwardly to cause the lever 15 to be pivotally
20 moved counterclockwise. The contact surface 33 of the second arm 30 is brought into contact with the slider body 13 on its rear end 13b, and further pivotal movement of the lever 15 in the counterclockwise direction is thereby prevented.

25 For removal from the slider holder 10, the slider 11 is pulled upwardly with the slider body 13 tilted leftwardly so as to be kept off the contact surface 33 of the second arm 30, thus allowing the lever 25 to be

pivotally moved to the slider-release position as the locking projection 32 is pushed by the pull tab 15 out of the slit 23 to release the pull tab 15.

5 Since the pivotal movement of the lever 15 from the slider-release position to the slider-holding position is caused by the slider body 13 rather than the pull tab 15, the slider holder 10 is suitable to be used for various kinds sliders having pull tabs of different length. Further, with this arrangement, it is possible
10 to hold or retain a slider in a position reliably in a single simple snap action.

In the illustrated embodiment, the second arm 30 of the lever 25 projects beyond the support surface 19A, 19B as the lever 25 is in the slider-release position.
15 However, if a slider (not shown) in which a yoke co-extends with slider body is to be held by the slider holder 10, the top of the second arm 30 may be disposed below or in the same plane as the support surface 19A, 19B, when the lever 25 is in the slider-release position.



CLAIMS:

1. A device (10) for holding a slider (11) in position for threading onto a slide fastener chain (12), the slider (11) including a slider body (13), a yoke (14) mounted on the slider body (13), and a pull tab (15) pivotally connected to the yoke (14) and having an opening (16), said device comprising: a housing (17A,17B) having a horizontal support surface (19A,19B) for supporting thereon the slider body (13) upside down, and a vertical slit (23) opening into said support surface (19A,19B) for receiving the pull tab (15) hanging from the slider body (13) supported on said support surface (19A,19B); a lever (25) pivotally mounted in said housing (17A,17B) and having a pair of juxtaposed arms (29,30) disposed one on each side of said slit (23), one of said arms (29) having a locking projection (32) extending toward and terminating short of the other arm (30), said lever (25) being pivotable between a slider-holding position in which said locking projection projects into said slit (23) for engagement with the opening (16) of the pull tab (15), and a slider-release position in which said locking projection (32) is retracted out of said slit (23) for releasing the pull tab (15); and means (34,35,38,40) urging said lever (25) to either said slider-holding position or said slider-release position; CHARACTERIZED in that said other arm (30) extends beyond said one arm (29) to such an extent that as the slider (11) is placed on said support surface (19A,19B), said other arm (30)



- 12 -

is pressed downwardly by the yoke (14) of the slider (11) to cause said lever (25) to be pivotally moved from said slider-release position to said slider-holding position.

2. A device (10) according to claim 1, said other arm (30), as said lever (25) is in said slider-release position, projecting beyond said support surface (19A,19B).

3. A device (10) according to claim 1, said other arm (30) having an outwardly inclined surface (33) engageable with the yoke (14) of the slider (11) when the latter is placed on said support surface (19A,19B).
