

CLAIMS

1. A patient interface for delivering a supply of gases to a patient, comprising:
a gas supply manifold for receiving and directing to an outlet or outlets to a
5 patient a gas supply, and
a pair of elongate side arms extending from opposite sides of the manifold
to contact a user's face in use to aid in stabilising the interface on the user's face,
each of said side arms comprising a part twisted portion, such that a cross-
section shape orthogonally through the side arm is part twisted anti-clockwise or
10 clockwise at a part of the side arm closer to an outer end relative to a part of the
side arm closer to the manifold, the twist being when considered from a top or
bottom view of the interface and said respective side arm(s).
2. The patient interface of claim 1, wherein each of said side arms comprise a
curve or bend upwardly along their length.
- 15 3. The patient interface of claim 2, wherein each side arm has an inner first
portion and an outer second portion which extends at an angle upwardly relative to
the inner first portion.
4. The patient interface of claim 3, wherein the inner first portion and outer
second portion are joined by an intermediate curved portion.
- 20 5. The patient interface of claims 3 or 4, wherein at least a part of the outer
second portion extends at an angle of between 20 and 70 degrees to the inner first
portion.
6. The patient interface of any one of claims 2 to 5, wherein the side arms are
shaped to engage the wearer's face below the cheek bones.
- 25 7. The patient interface of claim 1 or 2, wherein each of said side arms having
an inner first portion extending laterally and rearwardly from the manifold at a first
angle to the manifold and an outer second portion extending from the first portion
and rearwardly at a relatively shallower angle to the manifold or a relatively deeper
angle relative to the manifold.

8. The patient interface of any preceding claim, wherein the cross-section shape orthogonally through the side arm is part twisted anti-clockwise or clockwise up to about 45 degrees, or between about 2 and about 20 degrees.
9. The patient interface of claim 8, wherein a major part or all of the part twisted shape is in said second outer portion of each side arm.
10. The patient interface of any preceding claim, wherein a cross-section area of each side arm reduces along the length of the side arm.
11. The patient interface of any preceding claim, wherein a distal end of each side arm comprises a formation configured to releasably couple with a complementary connector of a headgear.
12. The patient interface of any preceding claim, wherein the interface outlet or outlets comprise a nasal cannula including a face mount part comprising at least one nasal prong integrally moulded with or removably attached to said face mount part.
13. The patient interface of claim 12, wherein the at least one nasal prong is configured not to seal about the patient's nares in use.
14. The patient interface of claim 12 or claim 13, wherein a gases flow manifold part is insertable into a body of the face mount part from either one of two opposing horizontal directions.
15. The patient interface of claim 14, wherein a position or location of the gases flow manifold part is reversible with respect to the body of the face mount part.
16. The patient interface of claim 14 or claim 15, wherein the gases flow manifold part is receivable by a gases chamber of the patient interface via a push-fit type configuration.
17. The patient interface of any one of claims 14 to 16, wherein the gases flow manifold part is receivable by a gases chamber of the patient interface from either, or both, of a left-side or a right-side of said patient interface, and/or wherein the gases flow manifold part is connectable with a gases chamber of the patient interface so as to orient a gas supply conduit to a left-side or a right-side of a user of said patient interface.

18. The patient interface of any preceding claim, comprising a clip for retention of a breathing tube to the patient interface.

19. The patient interface of claim 18, wherein the clip is configured to engage a mounting portion of the patient interface, the mounting portion positioned on a side arm of the pair of elongate side arms of the patient interface, and/or

the patient interface comprising mounting portions positioned on each side arm, the mounting portions positioned at the same location on each side arm such that the clip is connectable to a side arm to retain the tube in the same location on each respective side arm.

20. The patient interface of any one of claims 12 to 19, wherein the face mount part is shaped to generally follow the contours of a patient's face around the upper lip area.

21. The patient interface of any one of claims 12 to 20, wherein the face mount part is moulded or pre-formed to be able to conform to and/or is pliable to adapt, accommodate and/or correspond with the contours of the patient's face, in the region of the face where the cannula is to be located.

22. The patient interface of any one of claims 12 to 21, wherein the side arms extend laterally from opposite sides of the face mount part.

23. The patient interface of any preceding claim, wherein the cross-section shape of the side arms changes orientation through a longitudinal path of travel being positioned upon and extending along a rear surface of the patient interface, the longitudinal path of travel being located substantially as a mid-point of the height of the rear surface that contacts the user's face in use.