What is claimed is:

1. A method of arranging a transport service, the method being performed by a computing device and comprising:

causing a map interface to be displayed to the user, the map interface enabling the user to make a request, and to select, with the request, a location in a given region to receive the transport service, the selected location being represented by a first graphic indicator on the map interface;

obtaining a user input indicating at least the selected location;

determining a calculated location from the plurality of locations, based at least in part on information associated with the selected location; and

providing a second graphic indicator to be dynamically displayed on the map interface, the second graphic indicator representing the calculated location and providing to the user a visual feedback that the calculated location is different from the selected location.

2. The method of claim 1, wherein calculating the plurality of locations by accessing a mapping table stored in one or more memory resources of the computing system, the mapping table including one or more entries that individually associate a specified region with at least one corresponding predetermined location data point of the set.

3. The method of claim 1 or 2, wherein determining the calculated location includes determining that the calculated location is within a predefined distance of the user device at a time the request for the transport service is made.

4. A non-transitory computer-readable medium storing instructions that, when executed by a processor of a computing system, causes the computing system to:

cause a map interface to be displayed to the user, the map interface enabling the user to make a request, and to select, with the request, a location in a given region to receive the transport service, the selected location being represented by a first graphic indicator on the map interface;

obtain a user input indicating at least selected location;

determine a plurality of locations of completed transport services of other users in the given region, based on the given region of the selected location;

determine a calculated location from the plurality of locations, based at least in part on information associated with the selected location; and

provide a second graphic indicator to be dynamically displayed on the map interface, the second graphic indicator representing the calculated location and providing to the user a visual feedback that the calculated location is different from the selected location.

5. The non-transitory computer-readable medium of claim 4, wherein the instructions cause the computing system to calculate the plurality of locations by:

accessing a mapping table stored in one or more memory resources of the computing system, the mapping table including one or more location entries that individually associate a specified region with at least one corresponding predetermined location data point of the set.

6. The non-transitory computer-readable medium of claim 4, wherein the instructions that cause the computing system to determine the calculated location includes:

determining that the calculated location data is within a predefined distance of the user device at a time the request for the transport service is made.

7. A computing system comprising:

a set of memory resources that store a set of instructions, and a set of on-demand entries, each on-demand entry of the set of on-demand entries including a location of a completed transport request of other users in a given region;

one or more processors, the one or more processors utilizing the set of instructions to:

cause a map interface to be displayed to the user, the map interface enabling the user to make a request, and to select, with the request, a location in a given region to receive the transport service, the selected location being represented by a first graphic indicator on the map interface;

obtain a user input indicating at least the selected location;

determine a calculated location from the plurality of locations, based, at least in part, on information associated with the selected location; and

provide a second graphic indicator to be dynamically displayed on the map interface, the second graphic indicator representing the calculated location and providing to the user a visual feedback that the calculated location is different from the selected location.

8. The method of any one of claims 1 to 3, further comprising: selecting a driver to provide the transport service for the user based on the selected location of the request.

9. The method of claim 8, further comprising: transmitting, to a driver device of the driver, the calculated location.

10. The method of any one of claims 1, 2, 3, 8, and 9, wherein providing the second graphic indicator to be dynamically displayed includes communicating, by the computer system, with a service application operating on a mobile computing device of the user.

11. The method of claim 10, further comprising: determining the user is moving the first graphic indicator to the second graphic indicator, based on the user input.

12. The method of claim 11, further comprising: dynamically changing the size of the second graphic indicator based on the distance between the first graphic indicator and the second graphic indicator.

13. The method of claim 12, wherein the second graphic indicator of the calculated location is expanded in size in response to the first graphic indicator towards the second graphic indicator.

14. The method of claim 13, further comprising:

determining the first graphic indicator is on the expanded second graphic indicator; and

snapping the first graphic indicator to a center of the second graphic indicator.

15. The method of any one of claims 1, 2, 3, 8-14, further comprising determining the selected location as being a current location of the user.

16. The method of claim 15, further comprising causing a service application to approximate the current location of the user using a geo-aware resource of a mobile computing device on which the service application is operated.

17. The non-transitory computer-readable medium of any one of claims 4 to 6, wherein the instructions further cause the computing device to: select a driver to provide the transport service for the user based on the selected location of the request.

18. The non-transitory computer-readable medium of claim 17, wherein the instructions further cause the computing device to: transmit, to a driver device of the driver, the calculated location.

19. The non-transitory computer-readable medium of any one of claims 4, 5, 6, 17 and 18, wherein the instructions for causing the graphic indicator to be dynamically displayed includes instructions that cause the computing system to: communicate with a service application operating on a mobile computing device of the user.