

PRINthead MAINTENANCE STATION

Field of the Invention

- 5 This invention relates to a maintenance station for an inkjet printhead. It has been developed primarily for facilitating maintenance operations, such as sealing, cleaning or unblocking nozzles in an inkjet printhead.

Cross References to Related Applications

- 10 Various methods, systems and apparatus relating to the present invention are disclosed in the following US Patents/ Patent Applications filed by the applicant or assignee of the present invention:

09/517539	6566858	09/112762	6331946	6246970	6442525	09/517384
09/505951	6374354	09/517608	09/505147	10/203564	6757832	6334190
6745331	09/517541	10/203559	10/203560	10/636263	10/636283	10/866608
10/902889	10/902833	10/940653	10/942858	10/727181	10/727162	10/727163
10/727245	10/727204	10/727233	10/727280	10/727157	10/727178	10/727210
10/727257	10/727238	10/727251	10/727159	10/727180	10/727179	10/727192
10/727274	10/727164	10/727161	10/727198	10/727158	10/754536	10/754938
10/727227	10/727160	10/934720	11/212,702	10/296522	6795215	10/296535
09/575109	10/296525	09/575110	09/607985	6398332	6394573	6622923
6747760	10/189459	10/884881	10/943941	10/949294	11/039866	11/123011
11/123010	11/144769	11/148237	10/922846	10/922845	10/854521	10/854522
10/854488	10/854487	10/854503	10/854504	10/854509	10/854510	10/854496
10/854497	10/854495	10/854498	10/854511	10/854512	10/854525	10/854526
10/854516	10/854508	10/854507	10/854515	10/854506	10/854505	10/854493
10/854494	10/854489	10/854490	10/854492	10/854491	10/854528	10/854523
10/854527	10/854524	10/854520	10/854514	10/854519	10/854513	10/854499
10/854501	10/854500	10/854502	10/854518	10/854517	10/934628	PLT046US
10/728804	10/728952	10/728806	10/728834	10/729790	10/728884	10/728970
10/728784	10/728783	10/728925	10/728842	10/728803	10/728780	10/728779
10/773189	10/773204	10/773198	10/773199	10/773190	10/773201	10/773191
10/773183	10/773195	10/773196	10/773186	10/773200	10/773185	10/773192
10/773197	10/773203	10/773187	10/773202	10/773188	10/773194	10/773193

10/773184	11/008118	11/060751	11/060805	11/188017	6623101	6406129
6505916	6457809	6550895	6457812	10/296434	6428133	6746105
10/407212	10/407207	10/683064	10/683041	6750901	6476863	6788336
11/097308	11/097309	11/097335	11/097299	11/097310	11/097213	11/210687
11/097212	11/212637	10/760272	10/760273	10/760187	10/760182	10/760188
10/760218	10/760217	10/760216	10/760233	10/760246	10/760212	10/760243
10/760201	10/760185	10/760253	10/760255	10/760209	10/760208	10/760194
10/760238	10/760234	10/760235	10/760183	10/760189	10/760262	10/760232
10/760231	10/760200	10/760190	10/760191	10/760227	10/760207	10/760181
10/815625	10/815624	10/815628	10/913375	10/913373	10/913374	10/913372
10/913377	10/913378	10/913380	10/913379	10/913376	10/913381	10/986402
11/172816	11/172815	11/172814	11/003786	11/003354	11/003616	11/003418
11/003334	11/003600	11/003404	11/003419	11/003700	11/003601	11/003618
11/003615	11/003337	11/003698	11/003420	11/003682	11/003699	11/071473
11/003463	11/003701	11/003683	11/003614	11/003702	11/003684	11/003619
11/003617	10/760254	10/760210	10/760202	10/760197	10/760198	10/760249
10/760263	10/760196	10/760247	10/760223	10/760264	10/760244	10/760245
10/760222	10/760248	10/760236	10/760192	10/760203	10/760204	10/760205
10/760206	10/760267	10/760270	10/760259	10/760271	10/760275	10/760274
10/760268	10/760184	10/760195	10/760186	10/760261	10/760258	11/014764
11/014763	11/014748	11/014747	11/014761	11/014760	11/014757	11/014714
11/014713	11/014762	11/014724	11/014723	11/014756	11/014736	11/014759
11/014758	11/014725	11/014739	11/014738	11/014737	11/014726	11/014745
11/014712	11/014715	11/014751	11/014735	11/014734	11/014719	11/014750
11/014749	11/014746	11/014769	11/014729	11/014743	11/014733	11/014754
11/014755	11/014765	11/014766	11/014740	11/014720	11/014753	11/014752
11/014744	11/014741	11/014768	11/014767	11/014718	11/014717	11/014716
11/014732	11/014742	11/097268	11/097185	11/097184	09/575197	09/575195
09/575159	09/575132	09/575123	09/575148	09/575130	09/575165	09/575153
09/575118	09/575131	09/575116	09/575144	09/575139	09/575186	6681045
6728000	09/575145	09/575192	09/575181	09/575193	09/575156	09/575183
6789194	09/575150	6789191	6644642	6502614	6622999	6669385
6549935	09/575187	6727996	6591884	6439706	6760119	09/575198
6290349	6428155	6785016	09/575174	09/575163	6737591	09/575154

09/575129 09/575124 09/575188 09/575189 09/575162 09/575172 09/575170
09/575171 09/575161

The disclosures of these applications and patents are incorporated herein by reference.

Background of the Invention

Inkjet printers are commonplace in homes and offices. More recently, inkjet printers
5 have been proposed for use in portable devices, such as digital cameras, mobile phones *etc.*
Furthermore, with the advent of MEMS technology, whereby inexpensive photolithographic
techniques from the semiconductor industry are used to manufacture microelectromechanical
systems, the possibility of disposable inkjet printers is becoming a commercial reality. The
present Applicant has developed many different types of MEMS inkjet printheads, some of
10 which are described in the patents and patent applications listed in the above cross reference
list.

The contents of these patents and patent applications are incorporated herein by
cross-reference in their entirety.

15 Although the cost and power requirements of inkjet printheads is being reduced
through the use of MEMS technology and improved inkjet nozzle designs, it is also
necessary to reduce the cost and power requirements of other printer components, in order
to incorporate inkjet printers into portable devices or to provide disposable inkjet printers.

A crucial aspect of inkjet printing is maintaining the printhead in an operational
20 printing condition throughout its lifetime. A number of factors may cause an inkjet
printhead to become non-operational and it is important for any inkjet printer to include a
strategy for preventing printhead failure and/or restoring the printhead to an operational
printing condition in the event of failure. Printhead failure may be caused by, for example,
printhead face flooding, dried-up nozzles (due to evaporation of water from the nozzles – a
25 phenomenon known in the art as decap), or particulates fouling nozzles.

In some cases, printhead failure may be remedied by simply firing nozzles
periodically using a 'keep wet cycle'. This strategy does not require any external mechanical
maintenance of the printhead and may be appropriate when a nozzle has not been fired for a
relatively short period of time (*e.g.* less than 60 seconds). A 'keep wet cycle' can be used to
30 address decap, and the consequent formation of viscous plugs in nozzles, during active
printing.

However, a 'keep wet cycle' cannot be used when the printer is left idle over long
periods of time, for example, when it is in between print jobs, switched off or in transit.

Furthermore, a 'keep wet cycle' is not appropriate for clearing severely blocked nozzles and does not address the problem of printhead face flooding. Accordingly, inkjet printers typically include a printhead maintenance station, which is designed to prevent printhead failure and/or remediate printheads to an operational condition.

- 5 One measure that has been used for preventing printhead failure is sealing the printhead, thereby preventing evaporation of water and the drying up of nozzles. Commercial inkjet printers are typically supplied with a sealing tape across the printhead, which the user removes when the printer is installed for use. The sealing tape protects the primed printhead from particulates and prevents the nozzles from drying up during transit.
- 10 Sealing tape also controls flooding of ink over the printhead face.

- Aside from one-time use sealing tape on new printers, sealing has also been used as a strategy for maintaining printheads in an operational condition during printing. In some commercial printers, a gasket-type sealing ring and cap engages around a perimeter of the printhead when the printer is idle. With the printhead capped in this way, evaporation of
- 15 water from the nozzles is minimized, and a relatively humid atmosphere can be maintained above the nozzles, thereby minimizing the extent to which nozzles dry up.

- Furthermore, gasket-type sealing rings have been combined with suction cleaning in prior art maintenance stations. A vacuum may be connected to the sealing cap and used to suck ink from the nozzles. The sealing cap minimizes nozzle drying and entrance of
- 20 particulates from the atmosphere, while the suction ensures any blocked nozzles are cleared prior to printing. Hence, this type of maintenance station employs both preventative and remedial measures.

- Another remedial strategy used in prior art printhead maintenance stations is a rubber squeegee. The squeegee does not act as seal; rather, it is wiped across the printhead
- 25 and removes any flooded ink. Squeegee cleaning may be used immediately prior to printing, after the vacuum flush described above.

- The printhead maintenance strategies described above have several shortcomings, especially in the present age of inkjet printing. Modern inkjet printers are required to have smaller drop volumes, and hence smaller nozzle openings, for high resolution photographic
- 30 printing. It is also desirable to use stationary pagewidth printheads for high-speed printing, as opposed to scanning printheads. It is also desirable to reduce the overall cost of inkjet printers and incorporate them into low-powered portable devices, such as digital cameras and mobile phones.

Current printhead maintenance strategies are unable to provide inkjet printers, which meet these demands. With smaller nozzle openings (of the order of 5-20 microns), nozzle blocking due to decap becomes a serious problem. At present, the only reliable way of dealing with blocked nozzles is to use a suction pad. However, suction devices are bulky, expensive and consume large amounts of power, making them unsuitable for many inkjet applications. Furthermore, suction pads are wasteful of ink and can consume up to 0.25 ml of ink with each remediation.

Additionally, none of the prior art maintenance stations are able to provide a printhead ready for printing after a single maintenance operation. Typically, it is necessary to employ separate preventative (*e.g.* sealing) and remedial (*e.g.* suction and squeegee-cleaning) measures in order to provide a fully operational printhead. However, operations such as squeegee-cleaning are not suitable for all types of printhead, because it exerts shear stress across the printhead and can damage sensitive nozzle structures.

Therefore, it would be desirable to provide an inkjet printhead maintenance station, which combines both preventative and remedial measures. It would further be desirable to provide an inkjet printhead maintenance station, which can be fabricated at low cost and is therefore suitable for fabrication of a disposable printer. It would be further desirable to provide an inkjet printhead maintenance station, which does not significantly impact on the overall size of the printer and is therefore suitable for incorporation into handheld electronic devices. It would be further desirable to provide an inkjet printhead maintenance station, which does not impact on the overall power consumption of the printer and is therefore suitable for incorporation into battery-powered electronic devices. It would be further desirable to provide an inkjet printhead maintenance station, which does not waste large quantities of ink with each remedial operation. It would further be desirable to provide an inkjet printhead maintenance station, which cleans ink from a flooded printhead without exerting high shear stresses across the printhead.

Summary of the Invention

In a first aspect, there is provided a printhead maintenance station for maintaining a stationary pagewidth inkjet printhead in an operable condition, said maintenance station comprising:

an elastically deformable pad having a contact surface for sealing engagement with nozzles in an ink ejection face of said printhead, said contact surface being sloped with respect to said ink ejection face; and

an engagement mechanism for moving said pad substantially perpendicularly with respect to said ink ejection face between a first position in which said contact surface is sealingly engaged with said face, and a second position in which said contact surface is disengaged from said face,

5 wherein said sloped contact surface is progressively contacted with said face during said sealing engagement such that a first part of said surface is contacted with said face prior to a second part of said surface, and wherein said contact surface is peeled away from said face during said disengagement.

10 For the avoidance of doubt, the term “progressively contacted” is used to mean a type of engagement, which is opposite to “peeling away”. In other words, different portions of the contact surface progressively come into contact with the ink ejection face at different times during engagement. Likewise, different portions of the contact surface are progressively peeled away from the ink ejection face at different times during disengagement. The specification and drawings below describe in detail this type of
15 engagement and disengagement, and various ways of achieving such engagement and disengagement.

The printhead maintenance station advantageously combines both preventative and remedial measures for maintaining an inkjet printhead in an operable condition. In terms of preventative measures, the contact surface seals the ink ejection face, thereby minimizing
20 evaporation of water from the nozzles and minimizing the effects of ink drying up inside the nozzles. Sealing engagement of the contact surface with the ink ejection face also protects the printhead from particulates in the atmosphere, which can damage or block nozzles. Typically, the pad is held in its first position when the printhead is left idle over relatively long periods. However, the pad may be moved into sealing engagement at any time when
25 the printhead is not printing.

In terms of remedial measures, the contact surface cleans ink from the ink ejection face due to the unique interaction between the contact surface and the printhead. From a detailed analysis of advancing and receding contact angles, the present inventors have found that peeling disengagement of the contact surface from the ink ejection face has the effect of
30 moving ink along the contact surface (or the ink ejection face) towards an edge portion. Once deposited at an edge portion, the ink may be readily removed. A detailed explanation of the principle of advancing and receding contact angles, and how these relate to the present invention is given below.

In addition to cleaning flooded ink from the ink ejection face, the peeling disengagement action of the contact surface from the printhead also has the effect of unblocking nozzles. Peeling disengagement generates a negative pressure above nozzles in the printhead and, hence, draws out viscous ink material or particulate contaminants blocking the nozzles. Accordingly, the peeling disengagement has the combined effects of clearing blocked nozzles and removing ink to an edge portion of the contact surface or printhead.

A further advantage of the printhead maintenance station is that it has a simple design, which is compact, can be manufactured at low cost and consumes very little power. The suction devices of the prior art require external pumps, which add significantly to the cost and power consumption of prior art printers. Moreover, the requirement of an external vacuum pump adds significantly to the bulk of prior art printers. By obviating the need for a vacuum pump to effectively unblock printhead nozzles, the present invention allows inkjet printers to be installed into a wider range of devices and also opens up the potential for a commercially-viable disposable inkjet printer.

A further advantage of the printhead maintenance station is that nozzles can be unblocked without wasting large quantities of ink. Whereas prior art suction devices are wasteful of ink, adding to the overall cost of printer operation, the present invention withdraws only a minimum quantity of ink from nozzles during remediation. Moreover, by depositing the ink onto an edge portion of the pad (and/or the printhead), the means for removing this ink is greatly simplified.

A further advantage of the printhead maintenance station is that the cleaning action exerts minimal shear stress across the ink ejection face. Accordingly, sensitive nozzle structures are less likely to be damaged during maintenance when compared to, for example, wiping or squeegee cleaning of printheads.

Optionally, the pad is substantially coextensive with the printhead. A pad configured in this way ensures maintenance of the entire printhead, whilst simplifying the design of the maintenance station as far as possible. As described below a portion of the pad may extend beyond one end of the printhead, although this type of arrangement is still understood to be within the definition of the term 'substantially coextensive'.

Optionally, the contact surface is substantially uniform, so that ink can flow freely across its surface. Optionally, the contact surface should have a minimal number of pits or indentations, to avoid trapping ink in micro-pockets and consequently reducing the efficacy of the cleaning action.

The pad is elastically deformable and, preferably, has minimal or no creep. Elastic deformability provides sealing engagement of the pad with the printhead. Moreover, it ensures the pad can be used repeatedly without loss of either sealing or cleaning performance. Suitable materials for forming the pad include thermosetting or thermoplastic elastomers. For example, the pad may be comprised of silicone or polyurethane. Optionally, the pad is comprised of a silicone rubber.

Optionally a peel zone between the contact surface and the ink ejection face advances and retreats transversely across the ink ejection face during engagement and disengagement. In this embodiment, ink retreats with the peel zone in a longitudinal line towards a longitudinal edge portion of the contact surface or printhead as the pad is peeled away. This has the advantage that the ink travels a minimum distance across the ink ejection face and maximizes the cleaning efficiency of the maintenance station.

The engagement mechanism moves the pad substantially perpendicularly with respect to the ink ejection face. This arrangement has the advantage of simplifying the motion of the pad and, moreover, the means for achieving this. For example, a simple solenoid or motor/cam arrangement, consuming very little power, may be used to provide reciprocal linear movement of the pad.

Optionally, the pad is received in a housing with the pad being slidably movable relative to the housing. Typically, the pad extends through a slit in the housing in the first position and the pad is retracted into the housing in the second position. Optionally, the pad is mounted on a support arm, the arm having lugs at each end for engagement with the engagement mechanism. The lugs extend through complementary slots in side walls of the housing, thereby allowing sliding movement of the support arm and the pad.

With the pad being moved perpendicularly with respect to the ink ejection face, the unique engagement action of the contact surface is usually determined by the profile of the contact surface itself. Optionally, the pad is configured so that the contact surface is sloped with respect to the ink ejection face. Accordingly, during perpendicular engagement of the pad with the ink ejection face, a first end of the contact surface is contacted before a second end of the contact surface. Sloping of the contact surface may be in the form of a linear gradient (*i.e.* the contact surface is flat). For example, the contact surface may be angled at 5-30°, 8-20° or 10-15° with respect to the ink ejection face. Alternatively, sloping of the contact surface may be in the form of a curved or rounded gradient. In either case, progressive contact of the surface with the ink ejection face is ensured during engagement. Likewise, a peeling motion is ensured during disengagement.

Optionally, the pad is wedge-shaped with an angled surface of the wedge being the contact surface presented to the ink ejection face. A wedge-shaped pad is advantageous, since its manufacture is relatively facile using conventional molding, machining or laser-cutting techniques.

5 Optionally, a peel zone between the contact surface and the ink ejection face advances and retreats longitudinally along the printhead during engagement and disengagement. In this embodiment, ink retreats with the peel zone in a transverse line towards a transverse edge portion of the contact surface or ink ejection face as the pad is peeled away. An advantage of this arrangement is that excess ink is concentrated into a
10 smaller area by the cleaning action, making its removal more facile.

The maintenance station is typically configured so that peeling disengagement of the contact surface from the ink ejection face draws ink from the printhead towards an edge portion of the contact surface, the ink ejection face, or both. This cleaning action may be used to clear blocked nozzles and remove ink flooded on the surface of the ink ejection face.

15 The speed of engagement and disengagement, together with the contact time, may be varied in order to optimize the cleaning action. Optimal cleaning will also depend on other factors, such as the size of printhead, the elasticity of the pad, the shape of the pad, the motion of the engagement mechanism *etc.* The skilled person will readily be able to optimize cleaning of the printhead for any given system by varying one or more of these
20 parameters.

The pad may be moved according to a predetermined algorithm, depending on the expected severity of nozzle blockage. For example, different maintenance actions may be suitable for different printer conditions (*e.g.* first use, paper jam, recovery, user intervention *etc.*). Some situations may require five reciprocal movements of the pad, whereas other
25 situations may require only one engage/disengage sequence. Suitable algorithms may be programmed into a control system controlling operation of the printhead maintenance station.

Optionally, the maintenance station further comprises an ink removal system for removing ink deposited on an edge portion of the contact surface or ink ejection face. The
30 ink removal system advantageously avoids build up of ink on the pad or on the printhead, and channels any surplus ink away from the printhead.

The ink removal system may comprise any substrate or mechanism that can effectively remove ink from the edge portion(s). For example, the pad may be moved and contacted with an absorbent material after it has disengaged from the printhead.

Optionally, the ink removal system comprises a wicking element positioned adjacent an edge of the printhead. Ink which has been deposited towards the edge of the printhead and the pad is absorbed into the wicking element, which may simply be an absorbent material, and removed by wicking through the material. This arrangement has the advantage of simplicity and obviates the need for additional moving parts or a vacuum system in the maintenance station.

Optionally, the wicking element is positioned away from wirebonds on the printhead. The wirebonds are usually positioned along one longitudinal edge portion of the printhead, and the wicking element is optionally positioned adjacent an opposite longitudinal edge portion. Optionally, the wicking element extends into a cavity defined by a print media guide and a support to which the guide is mounted. This advantageously avoids ink from flooding and becoming trapped inside this cavity.

Optionally, the ink removal system further comprises an ink collector for receiving ink, which has wicked through the wicking element. By channeling surplus ink into a dedicated collector, the ink may be continuously taken away from the printhead region and cannot re-contaminate the printhead.

Optionally, the ink removal system comprises a film attached to the printhead support, wherein the film defines a wicking channel. The film is positioned such that the channel receives ink from an edge portion of the face and/or an edge portion of the pad being disengaged from the face. Optionally, the wicking channel is tapered to provide a capillary action. Optionally, a channel inlet is positioned adjacent proximal to the printhead and a channel outlet is positioned distal from the printhead, the channel being tapered towards the channel outlet. The channel inlet is typically defined by a proximal edge portion of the film, while the channel outlet is defined by a distal edge portion of the film.

Optionally, the film is anchored to the support along its distal edge portion via a plurality of anchor points. Typically, the anchor points are spaced apart to allow ink to exit the channel outlet. Alternatively, the distal edge portion of the film is attached to the print media guide and the distal edge portion be sandwiched between the print media guide and the support. Such an arrangement has manufacturing advantages in an automated assembly process when compared to bonding the film directly to the support.

Optionally, the film is substantially coextensive with the printhead and positioned adjacent a longitudinal edge thereof. Optionally, a plurality of vents are defined in the film. The vents are positioned for receiving ink from an outer surface of the film. Typically, the

vents are positioned towards the channel inlet. The vents may take the form of elongate slots extending parallel with a longitudinal edge of the film.

Typically, the film is resiliently displaceable and is usually comprised of a polymer. Examples of suitable polymer films include polyester, polyethylene, polypropylene, polyacrylate films *etc.*

Optionally, an edge portion of the pad extends beyond an edge of the printhead, such that at least part of the pad abuts the film when the pad is engaged with the face. Accordingly, the channel may be resiliently defined as the pad disengages from the face.

As an alternative, or in addition to the wicking element or wicking channel adjacent the printhead, the pad is optionally moveable to a third position in which it is engaged with a pad cleaner. Typically, the pad is rotated into engagement with the pad cleaner after disengagement from the ink ejection face of the printhead. The pad cleaner may be, for example, a rubber squeegee or an absorbent pad and typically forms part of the printhead maintenance station.

The invention has been developed primarily for use with a pagewidth inkjet printhead. Optionally, the printhead comprises a plurality of nozzles, with each nozzle having a diameter of less than 20 microns or less than 15 microns.

However, the invention is equally applicable to any type of printhead where sealing and/or remedial measures are required to maintain the printhead in an operable condition.

For example, the invention may be used in connection with standard scanning inkjet printheads in order to simplify conventional maintenance stations.

Brief Description of the Drawings

Specific forms of the present invention will now be described in detail, with reference to the following drawings, in which:-

Figure 1 shows an equilibrium contact angle for a wetting droplet of liquid on a surface;

Figure 2 shows an equilibrium contact angle for a non-wetting droplet of liquid on a surface;

Figure 3 shows advancing and receding contact angles for a droplet of liquid moving along a surface;

Figure 4A is a side view of a contact surface before engagement with an ink ejection face of a printhead;

Figure 4B is a side view of a contact surface partially engaged with the ink ejection face during engagement;

Figure 4C shows in detail a peel zone between the contact surface and a printhead nozzle during engagement;

5 Figure 4D shows in detail the peel zone in Figure 4C after it has advanced past the nozzle;

Figure 5A is a side view of the contact surface sealingly engaged with the ink ejection face;

10 Figure 5B is a side view of a contact surface partially engaged with the ink ejection face during disengagement;

Figure 5C shows in detail a peel zone between the contact surface and a printhead nozzle during disengagement;

Figure 5D shows in detail the peel zone in Figure 4C as it retreats from the nozzle;

15 Figure 5E shows in detail the peel zone in Figure 4D after it has retreated from the nozzle;

Figure 6 is a side view of the contact surface immediately after it has disengaged from the ink ejection face;

Figure 7 is a longitudinal side section view through a printhead maintenance station according to the invention;

20 Figure 8 is a side view of the printhead maintenance station shown in Figure 7;

Figure 9 is a transverse side section view of the printhead maintenance station shown in Figure 7;

Figure 10 is an end view of the printhead maintenance station shown in Figure 7;

25 Figure 11 is an exploded perspective view of the printhead maintenance station shown in Figure 7;

Figure 12 is a perspective view of a pad moving perpendicularly with respect to an ink ejection face of a printhead;

Figure 13 is a perspective view of a pad;

Figure 14 is a perspective view of a pad;

30 Figure 15A-C are schematic side views of a cylindrical pad at various stages of engagement with an ink ejection face of a printhead;

Figure 16A-C are schematic side views of a contact surface being brought into engagement with an ink ejection face of a printhead by rotational movement;

Figure 17 is a schematic side view of a roller being rolled across an ink ejection face of a printhead;

Figure 18 is a schematic side view of a printhead assembly comprising a wicking element;

5 Figure 19 is a schematic side view of a printhead assembly comprising a wicking channel;

Figure 20 is a plan view of the printhead and film shown in Figure 19;

Figure 21 is a schematic side view of the printhead assembly shown in Figure 19 with the pad fully engaged;

10 Figure 22 is a schematic side view of the printhead assembly shown in Figure 21 at the point of disengagement; and

Figures 23A-D are transverse side section views of a printhead maintenance station, having a rotating pad cleaning action, in various stages of a printhead maintenance cycle.

15 Detailed Description of Specific Embodiments

Contact Angle Hysteresis

In general terms, and as mentioned above, the present invention relies on an understanding of contact angles – specifically, a hysteresis between advancing and receding
20 contact angles.

The shape of a droplet of liquid on a solid surface is determined by its contact angle(s). Depending on factors such as the surface tension in the liquid and the interactive forces between the solid and the liquid, the shape of the droplet will change. Figure 1 shows a droplet of liquid 1 having a contact angle of 20° on a solid surface 2. With acute contact
25 angles, the liquid is said to be “mostly wetting” the surface 2. Figure 2 shows a droplet of another liquid 3 having a contact angle of 110° on the solid surface 2. With obtuse contact angles, the liquid is said to be “mostly non-wetting”.

The contact angles shown in Figures 1 and 2 are static or equilibrium contact angles. Since the droplet is symmetrical, the contact angle measured on either side of the
30 droplet would be the same. However, the situation changes if the droplet of liquid is moving. Figure 3 shows a droplet of liquid 4 moving down the surface 2, which is now sloped. As shown in Figure 3, the shape of the droplet changes when it is moving. The result is that the contact angle on its leading (advancing) edge is greater than the contact on its tailing (receding) edge. In other words, the droplet is more wetting when receding and less

wetting when advancing. The contact angle designated as θ_A in Figure 3 is called the Advancing Contact Angle, and the contact angle designated as θ_R in Figure 3 is called the Receding Contact Angle.

For a typical droplet of ink moving across a silicone surface, the advancing contact angle is about 90° , whereas the receding contact angle is about 15° . Without wishing to be bound by theory, it is understood by the present inventors that this contact angle hysteresis is responsible for the cleaning action provided by the present invention.

In Figures 4A and 4B, a flexible pad 6 having a contact surface 7 is progressively brought into contact with a printhead 5 having an ink ejection face 8. Figure 4C shows an exploded view of a peel zone 9 in Figure 4B, when the contact surface 7 is partially in contact with the ink ejection face 8. Figure 4C shows in detail the behaviour of ink 11 as the surface 7 is contacted with a nozzle opening 10 on the printhead. Ink 11 in the nozzle opening 10 makes contact with the contact surface 7 as it advances across the printhead 5. However, since the advancing contact angle θ_A of the ink 11 on the contact surface 7 is relatively non-wetting (about 90°), the ink has little or no tendency to wet onto the contact surface 7. Hence, as shown in Figure 4D, the ink 11 remains on the ink ejection face 8 or in the nozzle 10, and the peel zone 9 advancing across the ink ejection face is relatively dry.

In Figures 5A and 5B, the reverse process is shown as the flexible pad 6 is peeled away from the ink ejection face 8. Initially, as shown in Figure 5A, the contact surface 7 is sealingly engaged with the ink ejection face 8. In Figure 5B, the contact surface 7 is peeled away from the ink ejection face 8, and the peel zone 9 retreats across the face. Figure 5C shows a magnified view of the peel zone 9 as the contact surface 7 is peeled away from the nozzle opening 10 on the printhead 5. Ink 11 in the nozzle opening 10 makes contact with the contact surface 7 as it recedes across the ink ejection face 8. However, since the receding contact angle θ_R of the ink 11 on the surface 7 is relatively wetting (about 15°), the ink in the nozzle opening 10 now tends to wet onto the contact surface 7. Hence, as shown in Figures 5D and 5E, the peel zone 9 retreating across the ink ejection face 8 is wet, carrying with it a droplet of ink 12 drawn from the nozzle opening 10 or from the ink ejection face 8. This has the effect of clearing blocked nozzles in the printhead 5 and cleaning ink flooded on the ink ejection face 8.

Figure 6 shows the flexible pad 6 as the last part of the contact surface 7 is peeled away from the ink ejection face 8. The contact surface 7 has collected a bead of ink 12 at the final point of contact with the printhead 5.

As will be readily appreciated from the foregoing discussion, the present invention may be implemented in many different forms, provided that the contact surface 7 is contacted with the ink ejection face 8 so as to produce a contact angle hysteresis. Various forms of the invention are described in detail below.

5

Printhead Maintenance Station Having Linear Pad Movement

Referring to Figures 7 to 11, a printhead maintenance station 20 comprises an elastically deformable pad 6 having a contact surface 7. The pad 6 is mounted on a support 23, having a recess 24 for receiving the pad. The support 23 is mounted on a support arm 25 having lugs 26 protruding from each end. The pad 21, support 23 and support arm 25 are bonded together to form a pad sub-assembly.

A housing 30 comprises a body 31 and a cap 32, which is snap-fitted to the body with a plurality of snap-locks 33. The two-part construction of the housing 30 enables it to be assembled by receiving the pad sub-assembly in the body 31 and then snap-fitting the cap 32 onto the body. The lugs 26 protruding from each end of the support arm 25 are received in complementary slots 34 in the housing 30. Accordingly, the support arm 25 is slidably movable within the slots 34, allowing the pad 6 to move slidably relative to the housing 30.

The extent of movement of the pad 6 is defined by the slots 34. In a first position shown in Figure 7, the lugs 26 abut an upper end 37 of each slot 34 and the pad 6 protrudes, at least partially, from the housing 30. In a second position (not shown), the lugs 26 abut a lower end 38 of each slot 34, defined by the cap 32, and the pad 6 is withdrawn inside the housing 30.

As shown in Figure 11, a pair of springs 35 are fixed to the cap 32 and urge against a lower surface 36 of the support arm 25. The springs 35 bias the pad 6 towards the first position shown in Figure 7.

The pad 6 is movable between the first and second positions by means of an engagement mechanism 40, which is shown in Figure 7. The engagement mechanism 40 comprises a motor 41, which rotates a pair of cams 42, engaged with respective lugs 26 at each end of the support arm 25. Rotation of the motor 41 and the cam 42 causes linear sliding movement of the support arm 25 and, hence, the pad 6. Accordingly, the pad 6 may be moved reciprocally between the first and second positions upon actuation of the motor 41.

In the first position, the contact surface 7 is sealingly engaged with the ink ejection face 8, as shown in detail in Figure 5A. In the second position, the contact surface 7, is

disengaged from the ink ejection 8, as shown in Figure 4A. In between these two positions, the contact surface 7 may be either progressively contacting or peeling away from the ink ejection face 8.

Figure 12 shows the perpendicular movement of the pad 6 with respect to the ink ejection face 8. As discussed above, this movement together with the profile of the contact surface 7 allows the printhead 5 to be maintained in an operable condition by sealing, cleaning and/or nozzle-clearing actions.

Alternative Pad Configurations

In the embodiment shown in Figures 4-12, the pad 6 is moved linearly and substantially perpendicularly with respect to the ink ejection face 8. The pad 6 is shown in Figures 4A and 12 having a sloped contact surface 7 in the form of a straight-line gradient. This sloped contact surface 7 allows it to be progressively contacted with and peeled away from the ink ejection face 8 during engagement and disengagement respectively.

However, the contact surface may adopt other profiles and still achieve a similar effect when moved perpendicularly with respect to the ink ejection face 8. Figures 13 and 14 show two alternative configurations for the pad 6 in which the contact surface 7 has a curved profile in cross-section.

As shown in Figures 15A-C, the pad may alternatively be in the form of a cylinder 50, extending along the length of the printhead 5. The cylinder may be moved perpendicularly with respect to the ink ejection face 8 so that it is in either an engaged or a disengaged position. Figures 15A-C show progressive contacting of a curved contact surface 51 of the cylinder 50 so that it is brought into sealing engagement with the ink ejection face 8. The reverse process of peeling the contact surface 51 away from the ink ejection face 8 cleans the face or clears blocked nozzles on the printhead 5, as described above. The cylinder 50 is offset from the printhead 5 so that any ink drawn from the printhead moves towards an edge portion of the printhead during disengagement, and not towards the centre.

Any of these alternative pads may readily be incorporated into the printhead maintenance station 20 described above by simple replacement of the pad 6 in Figure 11.

Printhead Maintenance Station Having Rotational Pad Movement

In all the embodiments described thus far, the contact surface 7 has been sloped. With a sloped contact surface 7, linear motion of the pad 6 produces the peeling action required by the invention. However, as an alternative, the pad 6 may be moved rotationally

in order to achieve the progressive engagement and peeling disengagement from the ink ejection face 8.

In Figures 16A-C, there is shown a pad 60 mounted on an arm 61, which is attached to a pivot 62 at one end. The arm 61 is rotated by means of a motor 63 connected to the pivot 62. The pad 60 has a flat contact surface 64, which is progressively contacted with the ink ejection face 8 by virtue of the rotational movement of the arm 61. In the reverse process (not shown), the pad 60 is peeled away from the ink ejection face 8 also by virtue of the rotational movement of the arm 61. The pad 60 may be cuboid-shaped in this embodiment, since the requisite engagement and disengagement action is generated by the rotational movement of the pad.

As shown in Figures 16A-C, the pad is progressively contacted (and, by the reverse process, peeled away) along the longitudinal direction of the printhead 5. The printhead 5 has longitudinal rows of nozzles (not shown), with each row ejecting the same colored ink. By engaging/disengaging the pad 60 along the longitudinal direction of the printhead 5, color mixing between adjacent rows of nozzles is minimized as ink is drawn longitudinally along the ink ejection face 8 towards a transverse edge portion of the face and the pad 60.

Printhead Maintenance Station Having Rolling Pad Movement

As shown in Figure 17, the pad may alternatively be in the form a roller 70, which extends along the length of the printhead 5. In this embodiment, the roller 70 is rolled transversely across the ink ejection face 8 so that a leading peel zone 71 between the roller and the face is dry, and a tailing peel zone 72 between the roller and the face is wet. As explained above, this difference is due to an advancing contact angle at the leading peel zone 71 being greater than a receding contact angle at the tailing peel zone 72. Accordingly, the rolling action has the effect of cleaning the ink ejection face 8 due to this contact angle hysteresis. Unlike the embodiments described above, in this embodiment, advancing and receding contact angles are experienced simultaneously by different surfaces of the roller 70.

The roller 70 is rolled across the ink ejection face using a rolling mechanism 73. The rolling mechanism 73 comprises a pivot arm 74 to which the roller 70 is rotatably mounted at one end. The pivot arm 74 is pivoted about a pivot 75, and an opposite end of the arm is moved by means of a solenoid 76. Actuation of the solenoid 76 causes the pivot arm 74 to pivot and the roller 70 is consequently rolled transversely across the ink ejection face 8.

Absorbent Wicking Element Adjacent Printhead For Removing Ink

In all the embodiments described above, the cleaning action of the pad 6 generally deposits ink towards a predetermined region of the contact surface 7, which is typically an edge portion. Some ink may also be deposited on an edge portion of the ink ejection face 8 – either a transverse edge portion or a longitudinal edge portion depending on the configuration or movement of the pad 6.

Figure 18 shows an embodiment where deposited ink 81 is removed by means of a wicking element 80 positioned adjacent a longitudinal edge 83 of the printhead 5. The wicking element 80 wicks ink away from a longitudinal edge portion 82 of the contact surface 7 and/or the ink ejection face 8. From Figure 18, it can be seen that the edge portion 82 of the contact surface 7 extends past an edge of the printhead 5, allowing the edge portion 82 to contact with the wicking element 80 adjacent the printhead. Hence, ink deposited at the edge portion 82, as the contact surface 7 peels away from the ink ejection face 8, is transferred onto the wicking element 80. The edge portion 82 is the final point of contact between the contact surface 7 and the ink ejection face 8 during disengagement.

The pad 6 and wicking element 80 are configured to move ink away from an opposite longitudinal edge portion 84 of the printhead 5, which comprises wirebond encapsulant 85. The encapsulant 85 protects wirebonds (not shown) connecting the printhead 5 to other printer components (not shown).

The crowded environment around the printhead 5 means that the wirebonded edge portion 84 is relatively inaccessible. It is an advantage of the present invention that the pad 6 can access and move ink away from this severely crowded edge portion 84.

The wicking element 80 is formed from an absorbent material, such as paper or foam, and is positioned in a cavity defined between a print media guide 86 and a support 87 on which the printhead 5 and print media guide are mounted. The print media guide 86 has a guide surface 88 for guiding print media past the printhead 5 when the pad 6 is fully disengaged from the ink ejection face 8.

An ink collector 89 receives ink that has wicked through the wicking element 80, ensuring that ink is always removed away from the printhead 5.

Wicking Channel Adjacent Printhead For Removing Ink

With repeated maintenance operations, the wicking element 80 may become damaged after repeated engagement of the pad 6. In particular, if the wicking element 80 is

comprised of paper and saturated with absorbed ink, it may disintegrate when contacted with the contact surface 7. Whilst more robust wicking materials may be used, a problem remains in that wicking rates through the material are relatively slow.

In an alternative embodiment, and referring to Figures 19 and 20, a film 120 is positioned adjacent the longitudinal edge 83 of the printhead 5. The film 120 has a proximal longitudinal edge 121 and a distal longitudinal edge 122 relative to the printhead 5. The film 120 cooperates with the support 87 to define a wicking channel 124. The distal longitudinal edge 122 may be attached to the support 87 via a plurality of anchor points 123. The anchor points 123 may be, for example, spots of adhesive spaced apart along the distal edge 122.

Alternatively, the distal edge 122 of the film 120 may be fixed to the paper guide 86, and the film held in position by being sandwiched between the support 87 and the paper guide.

The film 120 is typically a biaxially oriented polyester film (*e.g.* Mylar[®] film). Due to the stiffness and resilience of the film 120, attachment to the support 87 along the distal longitudinal edge 122 provides a tapered wicking channel 124. A channel inlet 125 is provided adjacent the longitudinal edge 83 of the printhead 5, while a channel outlet 126 is provided distal from the printhead 5.

Due to the tapering of the wicking channel 124, ink received in the channel inlet 125 wicks rapidly along the channel towards the channel outlet 126 by capillary action, thereby removing ink away from the printhead 5. Furthermore, since the anchor points 123 are spaced apart along the distal longitudinal edge 122 of the film 120, ink can flow in between the anchor points and exit the channel outlet 126.

A secondary wicking element 127 is positioned between the media guide 86 and the support 87 at the channel outlet 126. The secondary wicking element 87 is positioned to receive ink from the channel outlet 126 and wicks ink into the ink collector 89. The secondary wicking element 127 is comprised of an absorbent material, such as paper or foam. Since the secondary wicking element 127 is not physically contacted by the pad 6 during printhead maintenance operations, it has a comparatively long lifetime compared to the wicking element 80 described above.

Referring to Figure 20, a plurality of vents in the form of slots 128 are defined in the film 120 towards its proximal longitudinal edge 121. The slots 128 are positioned for receiving any ink, which does not enter the channel inlet 125. For example, any ink deposited on the outer surface of the film 120 (*i.e.* the upper surface of the film 120 as shown in Figure 19) during printhead maintenance, is wicked into the channel 124 via the slots 128. The elongate slots 128, extending longitudinally along the film 120, have been

shown to be particularly effective in wicking ink into the channel 124. However, any shape of vent may equally be used for the same purpose.

Referring to Figures 21 and 22, there is shown a printhead maintenance operation including cooperation of the contact surface 7 and the film 120. In Figure 21, the pad 6 is fully engaged with the printhead 5. The edge portion 82 of the contact surface 7 abuts against the film 120, urging the film against the support 87. The edge portion 82 contacts the film 120 so that the vents 128 are sealed by the contact surface 7. In this way, any ink on the edge portion 82 of the contact surface 7 is squeezed into the vents 128 and into the channel 124, during engagement of the pad 6.

In Figure 22, the contact surface 7 has peeled away from the ink ejection face 8 so that ink 81 has moved towards the edge portions 82 and 83. Due to the resilience of the film 120 (and due, in part, to stiction forces between the film 120 and the contact surface 7), the tapered channel 124 is defined as the pad 6 is disengaged from the printhead 5. Accordingly, as shown in Figure 22, the ink 81 removed from the ink ejection face 8 is positioned in the channel inlet 125 at the point of disengagement.

Once the ink 81 has entered the channel inlet 125, it is rapidly wicked towards the channel outlet 126 due to the tapering of the channel 124 and the capillary action provided thereby. The ink 81 is subsequently received by the secondary wicking element 127 and deposited into the ink collector 89. Hence, efficient and rapid removal of ink 81 away from the contact surface 7 and/or printhead 5 is achieved.

Engagement Mechanism with Rotating Pad-Cleaning Action

As described above, a wicking element 80 or film 120 may be positioned adjacent an edge portion 83 of the printhead 5, so that ink 81 is removed from the contact surface 7, ready for the next cleaning sequence.

In an alternative embodiment, the maintenance station may be configured so that ink is removed from contact surface 7 after the pad 6 is disengaged from the printhead face 8. In this embodiment, the engagement mechanism is configured to move the contact surface 7 into engagement with a remote cleaning means after it has disengaged from the printhead face 8. For example, rotation of the pad 6 after disengagement may be used to bring the contact surface 7 into cleaning engagement with a squeegee or blotter. Rotation may, for example, rock the pad through an arc and past a squeegee. Alternatively, rotation may be fully through 180° using a similar mechanism to those used in rotating 'self-inking' stamps. Self-inking stamps have been known for decades in the stamping art (see, for

example, US Patent Nos. 239,779; 405,704; 669,137; 827,347; 1,121,940; 2,079,080; 2,312,727; 2,919,645; 3,364,856; 3,402,663; 3,631,799; 3,952,653; 3,988,987; 4,432,281 and 4,852,489, the contents of which are incorporated herein by cross-reference), and the skilled person will readily appreciate how such stamping mechanisms may be used to rotate the pad 6 through 180° onto a blotter after it has disengaged from the printhead face 8.

Figures 23A-D show a cleaning sequence for a printhead assembly 90, in which the pad 6 is cleaned after disengagement from the printhead face 8 by rocking past a rubber squeegee.

Referring to Figure 23A, there is shown in cross-section a printhead cartridge 91 comprising the printhead 5 mounted on support 92. Encapsulated wirebonds 85 extend from one longitudinal edge of the printhead 5, while the paper guide 88 is fixed to the support 87 on an opposite side of the printhead. Still referring to Figure 23A, there is also shown a printhead maintenance station 100 comprising the pad 6 having the contact surface 7 for engagement with the ink ejection face 8 of the printhead 5. The pad is mounted on a cradle 101, which can be moved vertically towards the printhead 5 and which can also be rotated or rocked towards a rubber squeegee 102 fixed to a wall 103 of the maintenance station 100.

Referring now to Figure 23B, the sloped contact surface 7 is brought into sealing engagement with the printhead face 8 by moving the pad 6 vertically upwards using an engagement mechanism (not shown) similar to that shown in Figures 7-11.

In Figure 23C, the printhead face 8 is cleaned by moving the pad 6 vertically downwards, thereby peeling the contact surface 7 away from the printhead face. A droplet of ink 104 is deposited along an edge portion of the contact surface 7 after it has disengaged from the printhead.

In Figure 23D, the engagement mechanism (not shown) moves the cradle 101 further downwards so that its bottom surface 105 abuts with a cam surface 106 on the maintenance station. Abutment of the cradle 101 with the cam surface 106 causes the cradle to rock towards the rubber squeegee 102. The squeegee 102 removes the ink droplet 104 from the contact surface 7 as it rocks past the squeegee. This cleans the pad ready for re-use in the next maintenance cycle. Any suitable cleaning means, such as a foam pad, may of course be used to clean the pad 6 instead of the rubber squeegee 102 shown in Figures 19A-D.

Finally, the cradle 101 is moved back into the position shown in Figure 23A, which completes the maintenance cycle. A biasing mechanism (not shown) rocks the cradle 101

back into its vertical position shown in Figure 23A as the cradle is moved upwards and away from the cam surface 106.

It will, of course, be appreciated that the present invention has been described purely by way of example and that modifications of detail may be made within the scope of
5 the invention, which is defined by the accompanying claims.

CLAIMS

1. A printhead maintenance station for maintaining a stationary pagewidth inkjet printhead in an operable condition, said maintenance station comprising:

an elastically deformable pad having a contact surface for sealing engagement with nozzles in an ink ejection face of said printhead, said contact surface being sloped with respect to said ink ejection face; and

an engagement mechanism for moving said pad substantially perpendicularly with respect to said ink ejection face between a first position in which said contact surface is sealingly engaged with said face, and a second position in which said contact surface is disengaged from said face,

wherein said sloped contact surface is progressively contacted with said face during said sealing engagement such that a first part of said surface is contacted with said face prior to a second part of said surface, and wherein said contact surface is peeled away from said face during said disengagement.

2. The maintenance station of claim 1, wherein said pad is substantially coextensive with said printhead.

3. The maintenance station of claim 1, wherein said contact surface is substantially uniform.

4. The maintenance station of claim 1, wherein said pad is comprised of silicone or polyurethane.

5. The maintenance station of claim 1, wherein a peel zone between said contact surface and said ink ejection face advances and retreats transversely across said face during engagement and disengagement.

6. The maintenance station of claim 1, wherein said pad is wedge-shaped.

7. The maintenance station of claim 1, wherein a peel zone between said contact surface and said ink ejection face advances and retreats longitudinally along said face during engagement and disengagement.
8. The maintenance station of claim 1, wherein said pad is biased towards said first position.
9. The maintenance station of claim 1, wherein a peeling disengagement draws ink from said printhead towards an edge portion of said contact surface and/or said face.
10. The maintenance station of claim 1, further comprising an ink removal system for removing ink from an edge portion of said contact surface and/or said face.
11. The maintenance station of claim 10, wherein said ink removal system comprises a wicking element or wicking channel positioned adjacent an edge of said printhead.
12. The maintenance station of claim 11, wherein said wicking element or wicking channel is positioned to receive ink from said edge portion of said contact surface when said contact surface is being disengaged from said face.
13. The maintenance station of claim 11, wherein said ink removal system further comprises an ink collector for receiving ink wicked through said wicking element or wicking channel.